



ANDROID STATIC ANALYSIS REPORT




 TikTok (45.2.3)

File Name:	TikTok_-_Videos_Shop_LIVE_45.2.3_apkcombo.com.apk
Package Name:	com.zhiliaoapp.musically
Scan Date:	May 27, 2026, 11:25 a.m.

App Security Score:

45/100 (MEDIUM RISK)

Grade:



Trackers Detection:

7/432

 FINDINGS SEVERITY

 HIGH	 MEDIUM	 INFO	 SECURE	 HOTSPOT
8	72	1	1	10

 FILE INFORMATION

File Name: TikTok_-_Videos_Shop_LIVE_45.2.3_apkcombo.com.apk

Size: 529.97MB
MD5: 669f7a60b777f04d7719949da140df72
SHA1: ea96ebda1230953505fe594387b2a7f1a659626d
SHA256: a09c2cd121b781a46c4e55a75f098e320bec674f1efcc075e49e1cb258b7586a

i APP INFORMATION

App Name: TikTok
Package Name: com.zhiliiaoapp.musically
Main Activity:
Target SDK: 35
Min SDK: 23
Max SDK:
Android Version Name: 45.2.3
Android Version Code: 2024502030

APP COMPONENTS

Activities: 482
Services: 88
Receivers: 43
Providers: 16
Exported Activities: 32
Exported Services: 12
Exported Receivers: 10
Exported Providers: 6

CERTIFICATE INFORMATION

Binary is signed
v1 signature: True
v2 signature: True
v3 signature: True
v4 signature: False
X.509 Subject: C=86, ST=Shanghai, L=Shanghai, O=musical.ly Inc., OU=android, CN=musical.ly
Signature Algorithm: rsassa_pkcs1v15
Valid From: 2015-04-28 04:27:17+00:00
Valid To: 2040-04-21 04:27:17+00:00
Issuer: C=86, ST=Shanghai, L=Shanghai, O=musical.ly Inc., OU=android, CN=musical.ly
Serial Number: 0x32c7a2f7
Hash Algorithm: sha256
md5: 194326e82c84a639a52e5c023116f12a
sha1: d79f7cb8509a5e7e71c4f2afcfb75ea8c87177ca
sha256: 9041803e91bcb814b4b4399fb5c85a91640b755e5e8ba76813814bf4cf2ab5ba
sha512: e3bb2a1f5a84ca3ac0723d8541450f17ad578004e4c8008edac9e44c3cfb459dd31c62a5459e8befc2eed365608ba37837e35b0b6198acc58bc654cd11ed2f01
PublicKey Algorithm: rsa
Bit Size: 2048
Fingerprint: 2e585cb61d063b14873ff4b952388052d6c8209901ec7e7bf4ee38a2fa81288e
Found 1 unique certificates

≡ APPLICATION PERMISSIONS

PERMISSION	STATUS	INFO	DESCRIPTION
android.permission.ACCESS_COARSE_LOCATION	dangerous	coarse (network-based) location	Access coarse location sources, such as the mobile network database, to determine an approximate phone location, where available. Malicious applications can use this to determine approximately where you are.
android.permission.ACCESS_FINE_LOCATION	dangerous	fine (GPS) location	Access fine location sources, such as the Global Positioning System on the phone, where available. Malicious applications can use this to determine where you are and may consume additional battery power.
android.permission.CHANGE_WIFI_STATE	normal	change Wi-Fi status	Allows an application to connect to and disconnect from Wi-Fi access points and to make changes to configured Wi-Fi networks.
com.google.android.gms.permission.AD_ID	normal	application shows advertisements	This app uses a Google advertising ID and can possibly serve advertisements.
android.permission.FOREGROUND_SERVICE_MICROPHONE	normal	permits foreground services with microphone use.	Allows a regular application to use Service.startForeground with the type "microphone".
com.oplus.ocs.permission.third	unknown	Unknown permission	Unknown permission from android reference
android.permission.SYSTEM_ALERT_WINDOW	dangerous	display system-level alerts	Allows an application to show system-alert windows. Malicious applications can take over the entire screen of the phone.
android.permission.DETECT_SCREEN_CAPTURE	normal	notifies when a screen capture of the app's windows is attempted.	Allows an application to get notified when a screen capture of its windows is attempted.
android.permission.WRITE_EXTERNAL_STORAGE	dangerous	read/modify/delete external storage contents	Allows an application to write to external storage.
android.permission.READ_EXTERNAL_STORAGE	dangerous	read external storage contents	Allows an application to read from external storage.
android.permission.REORDER_TASKS	normal	reorder applications running	Allows an application to move tasks to the foreground and background. Malicious applications can force themselves to the front without your control.
android.permission.INTERNET	normal	full Internet access	Allows an application to create network sockets.

PERMISSION	STATUS	INFO	DESCRIPTION
android.permission.READ_MEDIA_VISUAL_USER_SELECTED	dangerous	allows reading user-selected image or video files from external storage.	Allows an application to read image or video files from external storage that a user has selected via the permission prompt photo picker. Apps can check this permission to verify that a user has decided to use the photo picker, instead of granting access to READ_MEDIA_IMAGES or READ_MEDIA_VIDEO . It does not prevent apps from accessing the standard photo picker manually. This permission should be requested alongside READ_MEDIA_IMAGES and/or READ_MEDIA_VIDEO , depending on which type of media is desired.
android.permission.ACCESS_NETWORK_STATE	normal	view network status	Allows an application to view the status of all networks.
android.permission.ACCESS_WIFI_STATE	normal	view Wi-Fi status	Allows an application to view the information about the status of Wi-Fi.
android.permission.CAMERA	dangerous	take pictures and videos	Allows application to take pictures and videos with the camera. This allows the application to collect images that the camera is seeing at any time.
android.permission.RECORD_AUDIO	dangerous	record audio	Allows application to access the audio record path.
android.permission.WAKE_LOCK	normal	prevent phone from sleeping	Allows an application to prevent the phone from going to sleep.
android.permission.READ_CONTACTS	dangerous	read contact data	Allows an application to read all of the contact (address) data stored on your phone. Malicious applications can use this to send your data to other people.
android.permission.VIBRATE	normal	control vibrator	Allows the application to control the vibrator.
android.permission.BLUETOOTH	normal	create Bluetooth connections	Allows applications to connect to paired bluetooth devices.
com.android.launcher.permission.READ_SETTINGS	unknown	Unknown permission	Unknown permission from android reference
android.permission.FOREGROUND_SERVICE	normal	enables regular apps to use Service.startForeground.	Allows a regular application to use Service.startForeground.
android.permission.FOREGROUND_SERVICE_MEDIA_PROJECTION	normal	allows foreground services for media projection.	Allows a regular application to use Service.startForeground with the type "mediaProjection".
com.sec.android.provider.badge.permission.READ	normal	show notification count on app	Show notification count or badge on application launch icon for samsung phones.
com.sec.android.provider.badge.permission.WRITE	normal	show notification count on app	Show notification count or badge on application launch icon for samsung phones.
android.permission.POST_NOTIFICATIONS	dangerous	allows an app to post notifications.	Allows an app to post notifications

PERMISSION	STATUS	INFO	DESCRIPTION
com.orange.update.permission.READ_ATTRIBUTION	unknown	Unknown permission	Unknown permission from android reference
com.samsung.android.mapsagent.permission.READ_APP_INFO	unknown	Unknown permission	Unknown permission from android reference
com.tiktok.preload.permission.IDENTIFY	unknown	Unknown permission	Unknown permission from android reference
com.tiktok.manager.SYS_START_PERMISSION	unknown	Unknown permission	Unknown permission from android reference
android.permission.READ_MEDIA_IMAGES	dangerous	allows reading image files from external storage.	Allows an application to read image files from external storage.
android.permission.READ_MEDIA_VIDEO	dangerous	allows reading video files from external storage.	Allows an application to read video files from external storage.
android.permission.BLUETOOTH_SCAN	dangerous	required for discovering and pairing Bluetooth devices.	Required to be able to discover and pair nearby Bluetooth devices.
android.permission.BLUETOOTH_ADVERTISE	dangerous	required to advertise to nearby Bluetooth devices.	Required to be able to advertise to nearby Bluetooth devices.
android.permission.BLUETOOTH_CONNECT	dangerous	necessary for connecting to paired Bluetooth devices.	Required to be able to connect to paired Bluetooth devices.
android.permission.FOREGROUND_SERVICE_MEDIA_PLAYBACK	normal	enables foreground services for media playback.	Allows a regular application to use Service.startForeground with the type "mediaPlayback".
android.permission.FOREGROUND_SERVICE_DATA_SYNC	normal	permits foreground services for data synchronization.	Allows a regular application to use Service.startForeground with the type "dataSync".
android.permission.ACCESS_MEDIA_LOCATION	dangerous	access any geographic locations	Allows an application to access any geographic locations persisted in the user's shared collection.
android.permission.READ_MEDIA_AUDIO	dangerous	allows reading audio files from external storage.	Allows an application to read audio files from external storage.
android.permission.CHANGE_NETWORK_STATE	normal	change network connectivity	Allows applications to change network connectivity state.

PERMISSION	STATUS	INFO	DESCRIPTION
android.permission.FOREGROUND_SERVICE_CAMERA	normal	allows foreground services with camera use.	Allows a regular application to use Service.startForeground with the type "camera".
android.permission.MODIFY_AUDIO_SETTINGS	normal	change your audio settings	Allows application to modify global audio settings, such as volume and routing.
android.permission.NFC	normal	control Near-Field Communication	Allows an application to communicate with Near-Field Communication (NFC) tags, cards and readers.
com.zhiliao.musically.livewallpaper.permission.wallpaperplugin	unknown	Unknown permission	Unknown permission from android reference
android.permission.USE_BIOMETRIC	normal	allows use of device-supported biometric modalities.	Allows an app to use device supported biometric modalities.
android.permission.USE_FINGERPRINT	normal	allow use of fingerprint	This constant was deprecated in API level 28. Applications should request USE_BIOMETRIC instead.
com.google.android.c2dm.permission.RECEIVE	normal	recieve push notifications	Allows an application to receive push notifications from cloud.
com.android.vending.BILLING	normal	application has in-app purchases	Allows an application to make in-app purchases from Google Play.
android.permission.ACCESS_AD_SERVICES_ATTRIBUTION	normal	allow applications to access advertising service attribution	This enables the app to retrieve information related to advertising attribution, which can be used for targeted advertising purposes. App can gather data about how users interact with ads, such as clicks or impressions, to measure the effectiveness of advertising campaigns.
android.permission.ACCESS_AD_SERVICES_AD_ID	normal	allow app to access the device's advertising ID.	This ID is a unique, user-resettable identifier provided by Google's advertising services, allowing apps to track user behavior for advertising purposes while maintaining user privacy.
com.google.android.finsky.permission.BIND_GET_INSTALL_REFERRER_SERVICE	normal	permission defined by google	A custom permission defined by Google.
com.zhiliaoapp.musically.DYNAMIC_RECEIVER_NOT_EXPORTED_PERMISSION	unknown	Unknown permission	Unknown permission from android reference
com.huawei.appmarket.service.commondata.permission.GET_COMMON_DATA	unknown	Unknown permission	Unknown permission from android reference
com.zhiliaoapp.musically.permission.RECEIVE_ADM_MESSAGE	unknown	Unknown permission	Unknown permission from android reference
com.amazon.device.messaging.permission.RECEIVE	unknown	Unknown permission	Unknown permission from android reference
android.permission.SET_WALLPAPER	normal	set wallpaper	Allows the application to set the system wallpaper.
com.google.android.apps.aicore.service.BIND_SERVICE	unknown	Unknown permission	Unknown permission from android reference

FILE	DETAILS	
classes.dex	FINDINGS	DETAILS
	Compiler	dexlib 2.x
classes10.dex	FINDINGS	DETAILS
	Anti-VM Code	Build.MANUFACTURER check possible Build.SERIAL check
	Compiler	dexlib 2.x
classes11.dex	FINDINGS	DETAILS
	Anti-VM Code	Build.FINGERPRINT check Build.MODEL check Build.MANUFACTURER check Build.PRODUCT check Build.BOARD check possible Build.SERIAL check Build.TAGS check ro.kernel.qemu check
	Anti Debug Code	Debug.isDebuggerConnected() check
	Compiler	dexlib 2.x
classes12.dex	FINDINGS	DETAILS
	Compiler	dexlib 2.x

FILE	DETAILS	
classes13.dex	FINDINGS	DETAILS
	Anti-VM Code	Build.MANUFACTURER check possible Build.SERIAL check
	Compiler	dexlib 2.x
classes14.dex	FINDINGS	DETAILS
	Anti-VM Code	Build.BOARD check
	Compiler	dexlib 2.x
classes15.dex	FINDINGS	DETAILS
	Compiler	dexlib 2.x
classes16.dex	FINDINGS	DETAILS
	Anti-VM Code	Build.MANUFACTURER check possible Build.SERIAL check
	Compiler	dexlib 2.x
classes17.dex	FINDINGS	DETAILS
	Compiler	dexlib 2.x
classes18.dex	FINDINGS	DETAILS
	Compiler	dexlib 2.x

FILE	DETAILS	
classes19.dex	FINDINGS	DETAILS
	Anti-VM Code	Build.MODEL check Build.MANUFACTURER check Build.HARDWARE check Build.BOARD check possible Build.SERIAL check
	Compiler	dexlib 2.x
classes2.dex	FINDINGS	DETAILS
	Compiler	dexlib 2.x
classes20.dex	FINDINGS	DETAILS
	Compiler	dexlib 2.x
classes21.dex	FINDINGS	DETAILS
	Compiler	dexlib 2.x
classes22.dex	FINDINGS	DETAILS
	Anti-VM Code	Build.FINGERPRINT check Build.MANUFACTURER check Build.BOARD check
	Compiler	dexlib 2.x
classes23.dex	FINDINGS	DETAILS
	Anti-VM Code	Build.MODEL check possible Build.SERIAL check
	Compiler	dexlib 2.x

FILE	DETAILS	
classes24.dex	FINDINGS	DETAILS
	Anti-VM Code	Build.MANUFACTURER check
	Compiler	dexlib 2.x
classes25.dex	FINDINGS	DETAILS
	Anti-VM Code	Build.MANUFACTURER check possible Build.SERIAL check
	Compiler	dexlib 2.x
classes26.dex	FINDINGS	DETAILS
	Anti-VM Code	Build.MODEL check Build.MANUFACTURER check Build.BOARD check possible Build.SERIAL check SIM operator check network operator name check
	Compiler	dexlib 2.x
classes27.dex	FINDINGS	DETAILS
	Anti-VM Code	possible Build.SERIAL check
	Compiler	dexlib 2.x

FILE	DETAILS	
classes28.dex	FINDINGS	DETAILS
	Anti-VM Code	Build.MANUFACTURER check Build.BOARD check
	Compiler	dexlib 2.x
classes29.dex	FINDINGS	DETAILS
	Anti-VM Code	Build.FINGERPRINT check Build.MODEL check Build.MANUFACTURER check Build.PRODUCT check Build.BOARD check
	Compiler	dexlib 2.x
classes3.dex	FINDINGS	DETAILS
	Compiler	dexlib 2.x
classes30.dex	FINDINGS	DETAILS
	Anti-VM Code	Build.MODEL check Build.MANUFACTURER check possible Build.SERIAL check
	Compiler	dexlib 2.x
classes31.dex	FINDINGS	DETAILS
	Anti-VM Code	Build.BOARD check possible Build.SERIAL check
	Compiler	dexlib 2.x

FILE	DETAILS	
classes32.dex	FINDINGS	DETAILS
	Anti-VM Code	Build.MANUFACTURER check Build.BOARD check possible Build.SERIAL check
	Compiler	dexlib 2.x
classes33.dex	FINDINGS	DETAILS
	Anti-VM Code	Build.FINGERPRINT check Build.MODEL check Build.MANUFACTURER check Build.PRODUCT check SIM operator check network operator name check
	Anti Debug Code	Debug.isDebuggerConnected() check
classes34.dex	FINDINGS	DETAILS
	Anti-VM Code	Build.MODEL check Build.MANUFACTURER check Build.PRODUCT check Build.BOARD check
	Compiler	dexlib 2.x
classes35.dex	FINDINGS	DETAILS
	Anti-VM Code	Build.MODEL check Build.MANUFACTURER check
	Compiler	dexlib 2.x

FILE	DETAILS	
classes36.dex	FINDINGS	DETAILS
	Anti-VM Code	Build.FINGERPRINT check Build.MANUFACTURER check ro.kernel.qemu check
	Compiler	dexlib 2.x
classes37.dex	FINDINGS	DETAILS
	Compiler	dexlib 2.x
classes38.dex	FINDINGS	DETAILS
	Compiler	dexlib 2.x
classes39.dex	FINDINGS	DETAILS
	Compiler	dexlib 2.x
classes4.dex	FINDINGS	DETAILS
	Compiler	dexlib 2.x
classes40.dex	FINDINGS	DETAILS
	Compiler	dexlib 1.x

FILE	DETAILS	
classes41.dex	FINDINGS	DETAILS
	Compiler	unknown (please file detection issue!)
classes42.dex	FINDINGS	DETAILS
	Compiler	dexlib 2.x
classes43.dex	FINDINGS	DETAILS
	Compiler	dexlib 2.x
classes44.dex	FINDINGS	DETAILS
	Compiler	unknown (please file detection issue!)
classes45.dex	FINDINGS	DETAILS
	Compiler	dexlib 2.x
classes46.dex	FINDINGS	DETAILS
	Compiler	dexlib 2.x
classes47.dex	FINDINGS	DETAILS
	Compiler	unknown (please file detection issue!)
classes48.dex	FINDINGS	DETAILS
	Compiler	dexlib 2.x

FILE	DETAILS	
classes49.dex	FINDINGS	DETAILS
	Compiler	dexlib 2.x
classes5.dex	FINDINGS	DETAILS
	Anti-VM Code	Build.FINGERPRINT check Build.MANUFACTURER check possible Build.SERIAL check
	Compiler	dexlib 2.x
classes50.dex	FINDINGS	DETAILS
	Compiler	dexlib 2.x
classes51.dex	FINDINGS	DETAILS
	Compiler	unknown (please file detection issue!)
classes52.dex	FINDINGS	DETAILS
	Compiler	dexlib 1.x
classes6.dex	FINDINGS	DETAILS
	Compiler	dexlib 2.x
classes7.dex	FINDINGS	DETAILS
	Compiler	dexlib 2.x

FILE	DETAILS	
classes8.dex	FINDINGS	DETAILS
	Compiler	dexlib 2.x
classes9.dex	FINDINGS	DETAILS
	Anti-VM Code	Build.MODEL check
	Compiler	dexlib 2.x
lib/arm64-v8a/libAndroidPitayaCore.so	FINDINGS	DETAILS
	anti_hook	syscalls
lib/arm64-v8a/libAwebviewbytedance.so	FINDINGS	DETAILS
	anti_hook	syscalls
lib/arm64-v8a/libartshadowhook.so	FINDINGS	DETAILS
	anti_hook	syscalls
lib/arm64-v8a/libbytehook.so	FINDINGS	DETAILS
	anti_hook	syscalls

FILE	DETAILS	
lib/arm64-v8a/libdex_df_ccdc_impl_ocr.so!classes.dex	FINDINGS	DETAILS
	Anti-VM Code	Build.MANUFACTURER check
	Compiler	dexlib 2.x
lib/arm64-v8a/libdex_df_live_cast.so!classes.dex	FINDINGS	DETAILS
	Anti-VM Code	Build.FINGERPRINT check Build.MANUFACTURER check
	Compiler	dexlib 2.x
lib/arm64-v8a/libdex_df_music_dsp.so!classes.dex	FINDINGS	DETAILS
	Anti-VM Code	Build.MANUFACTURER check
	Compiler	dexlib 2.x
lib/arm64-v8a/libdex_df_pipo_bnpl.so!classes.dex	FINDINGS	DETAILS
	Compiler	dexlib 2.x
lib/arm64-v8a/libdex_df_pipo_external_payments.so!classes.dex	FINDINGS	DETAILS
	Anti-VM Code	Build.FINGERPRINT check Build.MODEL check Build.MANUFACTURER check Build.PRODUCT check Build.HARDWARE check Build.BOARD check Build.TAGS check emulator file check
	Compiler	dexlib 2.x

FILE	DETAILS	
lib/arm64-v8a/libdex_df_pitaya.so!classes.dex	FINDINGS	DETAILS
	Compiler	dexlib 2.x
lib/arm64-v8a/libdex_df_ship.so!classes2.dex	FINDINGS	DETAILS
	Compiler	dexlib 2.x
lib/arm64-v8a/libdex_df_ship.so!classes.dex	FINDINGS	DETAILS
	Anti-VM Code	Build.BOARD check possible Build.SERIAL check
	Compiler	dexlib 2.x
lib/arm64-v8a/libdex_df_ttwebview.so!classes.dex	FINDINGS	DETAILS
	Anti-VM Code	Build.FINGERPRINT check Build.MODEL check Build.MANUFACTURER check Build.BOARD check
	Compiler	dexlib 2.x
lib/arm64-v8a/libmetasec_ov.so	FINDINGS	DETAILS
	anti_hook	syscalls

FILE	DETAILS	
lib/arm64-v8a/libnpth.so	FINDINGS	DETAILS
	anti_hook	syscalls
lib/arm64-v8a/libnpth_dumper.so	FINDINGS	DETAILS
	anti_hook	syscalls
lib/arm64-v8a/libnpth_unwind.so	FINDINGS	DETAILS
	anti_hook	syscalls
lib/arm64-v8a/liboecsec_ov.so	FINDINGS	DETAILS
	anti_hook	syscalls
lib/arm64-v8a/libshadowhook.so	FINDINGS	DETAILS
	anti_hook	syscalls
lib/armeabi-v7a/libdex_df_ccdc_impl_ocr.so!classes.dex	FINDINGS	DETAILS
	Anti-VM Code	Build.MANUFACTURER check
	Compiler	dexlib 2.x
lib/armeabi-v7a/libdex_df_live_cast.so!classes.dex	FINDINGS	DETAILS
	Anti-VM Code	Build.FINGERPRINT check Build.MANUFACTURER check
	Compiler	dexlib 2.x

FILE	DETAILS	
lib/armeabi-v7a/libdex_df_music_dsp.so!classes.dex	FINDINGS	DETAILS
	Anti-VM Code	Build.MANUFACTURER check
	Compiler	dexlib 2.x
lib/armeabi-v7a/libdex_df_pipo_bnpl.so!classes.dex	FINDINGS	DETAILS
	Compiler	dexlib 2.x
lib/armeabi-v7a/libdex_df_pipo_external_payments.so!classes.dex	FINDINGS	DETAILS
	Anti-VM Code	Build.FINGERPRINT check Build.MODEL check Build.MANUFACTURER check Build.PRODUCT check Build.HARDWARE check Build.BOARD check Build.TAGS check emulator file check
	Compiler	dexlib 2.x
lib/armeabi-v7a/libdex_df_pitaya.so!classes.dex	FINDINGS	DETAILS
	Compiler	dexlib 2.x
lib/armeabi-v7a/libdex_df_ship.so!classes2.dex	FINDINGS	DETAILS
	Compiler	dexlib 2.x

FILE	DETAILS	
lib/armeabi-v7a/libdex_df_ship.solclasses.dex	FINDINGS	DETAILS
	Anti-VM Code	Build.BOARD check possible Build.SERIAL check
	Compiler	dexlib 2.x
lib/armeabi-v7a/libdex_df_ttwebview.solclasses.dex	FINDINGS	DETAILS
	Anti-VM Code	Build.FINGERPRINT check Build.MODEL check Build.MANUFACTURER check Build.BOARD check
	Compiler	dexlib 2.x

BROWSABLE ACTIVITIES

ACTIVITY	INTENT
net.openid.appauth.RedirectUriReceiverActivity	Schemes: com.googleusercontent.apps.616463764658-p01hhcj82u4mqjnp1oca04i3o67fjsm1://,
com.ss.android.ugc.aweme.music.addtodsp.auth.RedirectUriReceiverActivity	Schemes: com.googleusercontent.apps.417228529645-jdo9meeg0hj7ouonvqnd27euu73dekom://, com.googleusercontent.apps.417228529645-qrk0ggdk3g2ns00ibp2qet3jvqdinr9k://,
com.ss.android.ugc.aweme.splash.ApplinkHookActivity	Schemes: https://, Hosts: app-va.tiktokv.com, www.tiktokv.com, m.tiktok.com, t.tiktok.com, www.tiktok.com, us.tiktok.com, vm.tiktok.com, vt.tiktok.com, www.tt.site, www.tt.inc, www.tt.fun, vt.tokopedia.com, link.e.tiktok.com, oec-api.tiktokv.com, shop.tiktok.com, tiktok.me, Paths: /shop, /us, /sg, /my, /jp, /vn, /th, /ph, /mx, /sa, /br, /gb, /ie, /es, /de, /it, /fr, Path Prefixes: /redirect, /m_otl_redirect, /m_m2_redirect, /m_only_redirect, /m_litem2_redirect, /i18n/share/music/, /i18n/share/video/, /i18n/share/challenge/, /i18n/share/user/, /share/stickers/detail/, /share/live/, /live/monetization/square/, /share/game/, /chatting/message, /bulletin_board, /v/, /V/, /live/, /h5/share/usr/, /h5/share/tag/, /h5/share/music/, /H5/share/, /playlist-music/, /ucenter_web/deepink/, /tag/, /music/, /sticker/, /share/tag/, /share/music/, /share/sticker/, /share/video/, /share/user/, /share/challenge/, /messages/, /t/, /search/campaign/, /question/, /discover/, /find/, /channel/, /revenue/subscription/invitation, /ug/ads/landing/, /now, /place/, /v2/h5/auth/authorize, /third-party-oauth-redirect/, /ucenter_web/passkey_wizard, /minis/, /d/1/, /d/7/, /d/8/, /uni/, Path Patterns: /, /@.*, /share/@.*, /view/product/.*, /.*trending/.*, /shop/pdp/.*, /product/.*, /shop/product/.*, /shop/c/.*, /shop/k/.*, /shop/blog/.*, /shop/store/.*, /shop/open_homepage.*, /shop/ug/ads.*, /.*, /us/.*, /sg/.*, /my/.*, /jp/.*, /vn/.*, /th/.*, /ph/.*, /mx/.*, /sa/.*, /br/.*, /gb/.*, /ie/.*, /es/.*, /de/.*, /it/.*, /fr/.*,
com.kakao.sdk.auth.AuthCodeHandlerActivity	Schemes: kakao61f447fe9723aa9c0b67a52eeb998e77://, Hosts: oauth,

ACTIVITY	INTENT
com.ss.android.sdk.activity.BootstrapActivity	Schemes: snssdk0://,
com.ss.android.ugc.aweme.deeplink.DeepLinkActivityV2	Schemes: snssdk1180://, musically://, snssdk1233://, tiktok://, snssdkonly1233://, snssdkotl1233://, snssdkm21233://, snssdkitem21233://,
com.ss.android.ugc.aweme.deeplink.AppLinkHandlerV2	Schemes: https://, Hosts: app-v.a.tiktokv.com, www.tiktokv.com, m.tiktok.com, t.tiktok.com, www.tiktok.com, us.tiktok.com, vm.tiktok.com, vt.tiktok.com, www.tt.site, www.tt.inc, www.tt.fun, vt.tokopedia.com, link.e.tiktok.com, oec-api.tiktokv.com, shop.tiktok.com, tiktok.me, Paths: /shop, /us, /sg, /my, /jp, /vn, /th, /ph, /mx, /sa, /br, /gb, /ie, /es, /de, /it, /fr, Path Prefixes: /redirect, /m_otl_redirect, /m_m2_redirect, /m_only_redirect, /m_litem2_redirect, /i18n/share/music/, /i18n/share/video/, /i18n/share/challenge/, /i18n/share/user/, /share/stickers/detail/, /share/live/, /live/monetization/square/, /share/game/, /chatting/message, /bulletin_board, /v/, /V/, /live/, /h5/share/usr/, /h5/share/tag/, /h5/share/music/, /H5/share/, /playlist-music/, /ucenter_web/deeplink, /tag/, /music/, /sticker/, /share/tag/, /share/music/, /share/sticker/, /share/video/, /share/user/, /share/challenge/, /messages/, /t/, /search/campaign/, /question/, /discover/, /find/, /channel/, /revenue/subscription/invitation, /ug/ads/landing/, /now, /place/, /v2/h5/auth/authorize, /third-party-oauth-redirect/, /ucenter_web/passkey_wizard, /minis/, /d/1/, /d/7/, /d/8/, /uni/, Path Patterns: /, /@.*, /share/@.*, /view/product/.*, /.*trending/.*, /shop/pdp/.*, /product/.*, /shop/product/.*, /shop/c/.*, /shop/k/.*, /shop/blog/.*, /shop/store/.*, /shop/open_homepage.*, /shop/ug/ads.*, /.*, /us/.*, /sg/.*, /my/.*, /jp/.*, /vn/.*, /th/.*, /ph/.*, /mx/.*, /sa/.*, /br/.*, /gb/.*, /ie/.*, /es/.*, /de/.*, /it/.*, /fr/.*,
com.facebook.CustomTabActivity	Schemes: fbconnect://, Hosts: cct.com.zhiliaoapp.musically,
com.ss.android.ugc.aweme.pipo.payments.braintree.PayPalTransitionActivity	Schemes: com.zhiliaoapp.musically.braintree://,
com.braintreepayments.api.BraintreeDeepLinkActivity	Schemes: com.zhiliaoapp.musically.braintree.deeplinkhandler://,
com.apple.android.sdk.authentication.SDKUriHandlerActivity	Schemes: musicsdk://, Hosts: com.zhiliaoapp.musically, Path Patterns: /authenticateresult.*,
com.bytedance.pipo.checkout.sdk.internal.CheckoutActivity	Schemes: snssdk1180://, Hosts: pipopay, Paths: /payin_checkout, /payin_checkout_bind,
com.bytedance.pipo.checkout.sdk.internal.PiManagementActivity	Schemes: snssdk1180://, Hosts: pipopay, Paths: /payin_pi_management,

NETWORK SECURITY

HIGH: 3 | WARNING: 1 | INFO: 0 | SECURE: 1

NO	SCOPE	SEVERITY	DESCRIPTION
1	*	high	Base config is insecurely configured to permit clear text traffic to all domains.

NO	SCOPE	SEVERITY	DESCRIPTION
2	*	warning	Base config is configured to trust system certificates.
3	*	high	Base config is configured to bypass certificate pinning.
4	zero-rating.tiktok.com	high	Domain config is insecurely configured to permit clear text traffic to these domains in scope.

NO	SCOPE	SEVERITY	DESCRIPTION
5	tiktokcdn.com tiktokv.com tiktokcdn-us.com isnssdk.com ibyteimg.com bytegecko-i18n.com goofy-cdn.com pitaya-clientai.com ibytedtos.com ttlstatic.com byteoversea.com bytedapm.com ttwstatic.com byteeffecttos-g.com tiktok.com ttapis.com capcutvod.com capcut.com byteicdn.com ifdmstatic.com oecstatic.com bytedgame.com fdmstatic.com sgsnssdk.com ttlimgs.com byteingress.com g-p-static.com byteintl.com muscdn.com byteoversea.net tiktokglobalshopv.com xcs3zlph.com g-t-static.com fdmimgs.com musical.ly tiktokstaticb.com goofy.app byteintl.net bitssec.com resso.me byteintlapi.com ifdmimgs.com yhgfb-static.com resso.app byteintlstatic.com zhiliaoapp.com tiktokmusic.me tiktokglobalshop.com topbuzzcdn.com rtcplus.com tiktokv-us.com oneunita.com	secure	Domain config is securely configured to disallow clear text traffic to these domains in scope.

CERTIFICATE ANALYSIS

HIGH: 0 | WARNING: 1 | INFO: 1

TITLE	SEVERITY	DESCRIPTION
Signed Application	info	Application is signed with a code signing certificate
Application vulnerable to Janus Vulnerability	warning	Application is signed with v1 signature scheme, making it vulnerable to Janus vulnerability on Android 5.0-8.0, if signed only with v1 signature scheme. Applications running on Android 5.0-7.0 signed with v1, and v2/v3 scheme is also vulnerable.

MANIFEST ANALYSIS

HIGH: 2 | WARNING: 63 | INFO: 0 | SUPPRESSED: 0

NO	ISSUE	SEVERITY	DESCRIPTION
1	App can be installed on a vulnerable unpatched Android version 6.0-6.0.1, [minSdk=23]	high	This application can be installed on an older version of android that has multiple unfixed vulnerabilities. These devices won't receive reasonable security updates from Google. Support an Android version => 10, API 29 to receive reasonable security updates.
2	Clear text traffic is Enabled For App[android:usesCleartextTraffic=true]	high	The app intends to use cleartext network traffic, such as cleartext HTTP, FTP stacks, DownloadManager, and MediaPlayer. The default value for apps that target API level 27 or lower is "true". Apps that target API level 28 or higher default to "false". The key reason for avoiding cleartext traffic is the lack of confidentiality, authenticity, and protections against tampering; a network attacker can eavesdrop on transmitted data and also modify it without being detected.
3	App has a Network Security Configuration[android:networkSecurityConfig=@xml/u]	info	The Network Security Configuration feature lets apps customize their network security settings in a safe, declarative configuration file without modifying app code. These settings can be configured for specific domains and for a specific app.
4	Application Data can be Backed up [android:allowBackup=true]	warning	This flag allows anyone to backup your application data via adb. It allows users who have enabled USB debugging to copy application data off of the device.
5	Activity (net.openid.appauth.RedirectUriReceiverActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
6	Activity (com.ss.android.ugc.aweme.music.addtodsp.auth.RedirectUriReceiverActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
7	Content Provider (com.ss.android.ugc.aweme.tools.draft.DraftFileProvider) is not Protected. [android:exported=true]	warning	A Content Provider is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
8	Activity (com.ss.android.ugc.aweme.main.MainActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.

NO	ISSUE	SEVERITY	DESCRIPTION
9	Activity-Alias (com.ss.android.ugc.aweme.splash.ApplinkHookActivity) is not Protected. [android:exported=true]	warning	An Activity-Alias is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
10	Activity-Alias (com.ss.android.ugc.aweme.splash.SplashActivity) is not Protected. [android:exported=true]	warning	An Activity-Alias is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
11	Activity (com.kakao.sdk.auth.AuthCodeHandlerActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
12	Broadcast Receiver (com.ss.android.ugc.aweme.common.net.NetworkReceiver) is not Protected. [android:exported=true]	warning	A Broadcast Receiver is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
13	Content Provider (com.ss.android.ugc.aweme.livewallpaper.WallPaperDataProvider) is Protected by a permission.Permission: com.zhiliaoapp.musically.permission.wallpaper</br>protectionLevel: signature [android:exported=true]	info	A Content Provider is found to be exported, but is protected by permission.
14	Content Provider (com.ss.android.ugc.aweme.account.provider.OneTapLoginTokenProvider) is not Protected. [android:exported=true]	warning	A Content Provider is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
15	Content Provider (com.ss.android.ugc.aweme.account.provider.AccountInfoProvider) is not Protected. [android:exported=true]	warning	A Content Provider is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
16	Content Provider (com.ss.android.ugc.aweme.lemon.TTReferrerForLemon8Provider) is not Protected. [android:exported=true]	warning	A Content Provider is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
17	Service (com.ss.android.ugc.trill.account.TiktokAuthService) is not Protected. [android:exported=true]	warning	A Service is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
18	Broadcast Receiver (com.appsflyer.MultipleInstallBroadcastReceiver) is not Protected. [android:exported=true]	warning	A Broadcast Receiver is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
19	Broadcast Receiver (com.appsflyer.SingleInstallBroadcastReceiver) is not Protected. [android:exported=true]	warning	A Broadcast Receiver is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
20	Broadcast Receiver (com.ss.android.ugc.trill.abtest.impl.NotificationBroadcastReceiver) is not Protected. [android:exported=true]	warning	A Broadcast Receiver is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
21	Broadcast Receiver (com.ss.android.ugc.aweme.common.net.NetWorkStateReceiver) is not Protected. [android:exported=true]	warning	A Broadcast Receiver is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
22	Service (com.ss.android.ugc.aweme.tile.PublishTileService) is Protected by a permission, but the protection level of the permission should be checked. Permission: android.permission.BIND_QUICK_SETTINGS_TILE [android:exported=true]	warning	A Service is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.

NO	ISSUE	SEVERITY	DESCRIPTION
23	Service (com.ss.android.ugc.aweme.tile.HotVideoTileService) is Protected by a permission, but the protection level of the permission should be checked. Permission: android.permission.BIND_QUICK_SETTINGS_TILE [android:exported=true]	warning	A Service is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.
24	Activity (com.ss.android.sdk.activity.BootstrapActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
25	Service (com.ss.android.message.NotifyService) is not Protected. [android:exported=true]	warning	A Service is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
26	Activity (com.ss.android.ugc.aweme.share.SystemShareActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
27	Activity (com.ss.android.ugc.aweme.share.linkshare.OpenLinkShareActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
28	Activity (com.ss.android.ugc.aweme.share.linkshare.OpenLinkShareMainActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
29	Service (com.ss.android.ugc.aweme.tools.policysecurity.OriginalSoundUploadService) is Protected by a permission, but the protection level of the permission should be checked. Permission: android.permission.BIND_JOB_SERVICE [android:exported=true]	warning	A Service is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.
30	Service (com.ss.android.ugc.aweme.tools.extract.video.VideoFramesUploadService) is Protected by a permission, but the protection level of the permission should be checked. Permission: android.permission.BIND_JOB_SERVICE [android:exported=true]	warning	A Service is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.
31	Activity (com.ss.android.ugc.aweme.shortvideo.ui.VideoRecordPermissionActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
32	Activity (com.ss.android.ugc.gamora.recorder.sticker.aigc.AIGCGenerationDraftCompatActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
33	Broadcast Receiver (com.ss.android.ugc.aweme.cubes.engage.EngageBroadcastReceiver) is not Protected. [android:exported=true]	warning	A Broadcast Receiver is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
34	Service (com.ss.android.ugc.tiktok.samsungfinder.SamsungSearchTikTokBrowserService) is not Protected. [android:exported=true]	warning	A Service is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.

NO	ISSUE	SEVERITY	DESCRIPTION
35	Activity (com.bytedance.android.livesdk.game.broadcast.mirror.activity.UsbSourceProxyActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
36	Activity (com.byted.cast.usbsource.usbdisplaysource.UsbSourceActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
37	Activity (com.ss.android.ugc.tiktok.pns.privacy.setting.paprompt.ui.PaPromptContainerActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
38	TaskAffinity is set for activity (com.zhiliaapp.musically.openauthorize.AwemeAuthorizedActivity)	warning	If taskAffinity is set, then other application could read the Intents sent to Activities belonging to another task. Always use the default setting keeping the affinity as the package name in order to prevent sensitive information inside sent or received Intents from being read by another application.
39	Activity (com.zhiliaapp.musically.openauthorize.AwemeAuthorizedActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
40	TaskAffinity is set for activity (com.aweme.account.login.OTLIntentHandlerActivity)	warning	If taskAffinity is set, then other application could read the Intents sent to Activities belonging to another task. Always use the default setting keeping the affinity as the package name in order to prevent sensitive information inside sent or received Intents from being read by another application.
41	Activity (com.aweme.account.login.OTLIntentHandlerActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
42	Content Provider (com.facebook.FacebookContentProvider) is not Protected. [android:exported=true]	warning	A Content Provider is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
43	Activity (com.ss.android.ugc.aweme.deeplink.DeepLinkActivityV2) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
44	Activity (com.ss.android.ugc.aweme.deeplink.AppLinkHandlerV2) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
45	Activity (com.ss.n_project.opensdk_tt.ui.Lemon8AuthActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
46	Activity (com.ss.n_project.opensdk_tt.ui.WebAuthActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
47	Activity (com.tokopedia.loginkit.view.LoginLauncherActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.

NO	ISSUE	SEVERITY	DESCRIPTION
48	Content Provider (com.bytedance.preinstall.attribution.provider.PreinstallAttributionProvider) is Protected by a permission.Permission: com.zhiliaapp.musically.permission.ATTRIBUTION_INFO</br>protectionLevel: signature [android:exported=true]	info	A Content Provider is found to be exported, but is protected by permission.
49	Activity (com.facebook.CustomTabActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
50	Activity (com.bytedance.globalpayment.googlepayapi.PIOPayActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
51	Broadcast Receiver (com.ss.android.push.window.oppo.ScreenReceiver) is not Protected. [android:exported=true]	warning	A Broadcast Receiver is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
52	Broadcast Receiver (com.google.firebase.iid.FirebaseInstanceIdReceiver) is Protected by a permission, but the protection level of the permission should be checked. Permission: com.google.android.c2dm.permission.SEND [android:exported=true]	warning	A Broadcast Receiver is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.
53	Service (com.google.android.gms.auth.api.signin.RevocationBoundService) is Protected by a permission, but the protection level of the permission should be checked. Permission: com.google.android.gms.auth.api.signin.permission.REVOCATION_NOTIFICATION [android:exported=true]	warning	A Service is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.
54	Service (androidx.work.impl.background.systemjob.SystemJobService) is Protected by a permission, but the protection level of the permission should be checked. Permission: android.permission.BIND_JOB_SERVICE [android:exported=true]	warning	A Service is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.
55	Broadcast Receiver (androidx.work.impl.diagnostics.DiagnosticsReceiver) is Protected by a permission, but the protection level of the permission should be checked. Permission: android.permission.DUMP [android:exported=true]	warning	A Broadcast Receiver is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.
56	Service (com.heyta.msp.push.service.DataMessageCallbackService) is Protected by a permission, but the protection level of the permission should be checked. Permission: com.heyta.mcs.permission.SEND_PUSH_MESSAGE [android:exported=true]	warning	A Service is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.

NO	ISSUE	SEVERITY	DESCRIPTION
57	Service (com.heyta.msp.push.service.CompatibleDataMessageCallbackService) is Protected by a permission, but the protection level of the permission should be checked. Permission: com.coloros.mcs.permission.SEND_MCS_MESSAGE [android:exported=true]	warning	A Service is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.
58	Activity (com.ss.android.account.share.data.write.activity.ShareDataActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
59	Content Provider (com.ss.android.account.share.data.write.provider.SecShareDataProvider) is not Protected. [android:exported=true]	warning	A Content Provider is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
60	Broadcast Receiver (com.adm.push.ADMMessageHandler\$Receiver) is Protected by a permission, but the protection level of the permission should be checked. Permission: com.amazon.device.messaging.permission.SEND [android:exported=true]	warning	A Broadcast Receiver is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.
61	Activity (com.ss.android.ugc.aweme.pipo.payments.braintree.PayPalTransitionActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
62	Activity (com.ss.android.ugc.aweme.pipo.payments.braintree.VenmoTransitionActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
63	Activity (com.braintreepayments.api.BraintreeDeepLinkActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
64	Service (com.ss.android.ugc.aweme.livewallpaper.AmeLiveWallpaper) is Protected by a permission, but the protection level of the permission should be checked. Permission: android.permission.BIND_WALLPAPER [android:exported=true]	warning	A Service is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.
65	Activity (com.bytedance.effectcreatormobile.creatortiktok.preview.CKNewEffectEditorActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
66	Activity (com.bytedance.effectcreatormobile.effectimgcreator.EffectImgCreatorActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
67	Activity (com.bytedance.pipo.checkout.sdk.internal.CheckoutActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
68	Activity (com.bytedance.pipo.checkout.sdk.internal.PIManagementActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.

</> CODE ANALYSIS

HIGH: 2 | WARNING: 6 | INFO: 1 | SECURE: 0 | SUPPRESSED: 0

NO	ISSUE	SEVERITY	STANDARDS	FILES
1	Files may contain hardcoded sensitive information like usernames, passwords, keys etc.	warning	CWE: CWE-312: Cleartext Storage of Sensitive Information OWASP Top 10: M9: Reverse Engineering OWASP MASVS: MSTG-STORAGE-14	X/C20074813gp.java com/ss/android/ugc/aweme/playereventreporter/Videol nfo.java
2	The App logs information. Sensitive information should never be logged.	info	CWE: CWE-532: Insertion of Sensitive Information into Log File OWASP MASVS: MSTG-STORAGE-3	X/C1036660d5N.java X/C1897770zUG.java com/bytedance/frameworks/core/artsym/StubClass.java
3	MD5 is a weak hash known to have hash collisions.	warning	CWE: CWE-327: Use of a Broken or Risky Cryptographic Algorithm OWASP Top 10: M5: Insufficient Cryptography OWASP MASVS: MSTG-CRYPTO-4	X/C00A8.java X/C00A9.java X/C00AB.java X/C00Y8.java X/C1544980qjF.java X/C530280Kr5.java X/C531910kti.java X/C605790Npa.java X/C605800Npb.java X/C607610NsW.java X/C607620NsX.java com/bytedance/retrofit2/mime/DigestUtil.java
4	App uses SQLite Database and execute raw SQL query. Untrusted user input in raw SQL queries can cause SQL Injection. Also sensitive information should be encrypted and written to the database.	warning	CWE: CWE-89: Improper Neutralization of Special Elements used in an SQL Command ('SQL Injection') OWASP Top 10: M7: Client Code Quality	X/C1288540jdd.java
5	The App uses an insecure Random Number Generator.	warning	CWE: CWE-330: Use of Insufficiently Random Values OWASP Top 10: M5: Insufficient Cryptography OWASP MASVS: MSTG-CRYPTO-6	X/C1087140eOn.java
6	SHA-1 is a weak hash known to have hash collisions.	warning	CWE: CWE-327: Use of a Broken or Risky Cryptographic Algorithm OWASP Top 10: M5: Insufficient Cryptography OWASP MASVS: MSTG-CRYPTO-4	X/C630710Oog.java
7	The App uses ECB mode in Cryptographic encryption algorithm. ECB mode is known to be weak as it results in the same ciphertext for identical blocks of plaintext.	high	CWE: CWE-327: Use of a Broken or Risky Cryptographic Algorithm OWASP Top 10: M5: Insufficient Cryptography OWASP MASVS: MSTG-CRYPTO-2	X/C1531540pxZ.java
8	IP Address disclosure	warning	CWE: CWE-200: Information Exposure OWASP MASVS: MSTG-CODE-2	X/C1518220pc5.java com/ss/android/ugc/network/observer/bean/DetectorPa ram.java

NO	ISSUE	SEVERITY	STANDARDS	FILES
9	Weak Encryption algorithm used	high	CWE: CWE-327: Use of a Broken or Risky Cryptographic Algorithm OWASP Top 10: M5: Insufficient Cryptography OWASP MASVS: MSTG-CRYPTO-4	com/heytap/mcssdk/utlis/c.java

SHARED LIBRARY BINARY ANALYSIS

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
1	arm64-v8a/libbyteVC2dec.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk', '__memcpy_chk', '__strchr_chk', '__strcat_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
2	arm64-v8a/libreschecker.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['_strchr_chk', '_strrchr_chk', '__memset_chk', '__memmove_chk', '__memcpy_chk', '__vsnprintf_chk', '__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
3	arm64-v8a/libtt_ugen_layout.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
4	arm64-v8a/liborbuculumadapter.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strcpy_chk', '__vsprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
5	arm64-v8a/liblens.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk', '__vsprintf_chk', '__memset_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
6	arm64-v8a/libavocadoguard.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memmove_chk', '__memset_chk', '__memcpy_chk', '__vsprintf_chk', '__vsnprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
7	arm64-v8a/libbase_live.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strchr_chk', ['__strlen_chk', ['__vsprintf_chk', ['__strcat_chk', ['__read_chk', ['__memcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
8	arm64-v8a/libbdhm_native.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	\$ORIGIN/../../../../usr/local/rustup/toolchains/1.70.0-x86_64-unknown-linux-gnu/lib/rustlib/aarch64-linux-android/lib high The binary has RUNPATH set. In certain cases, an attacker can abuse this feature and or modify environment variables to run arbitrary libraries for code execution and privilege escalation. The only time a library should set RUNPATH is when it is linked to private libraries in the same package. Remove the compiler option --enable-new-dtags,-rpath to remove RUNPATH.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
9	arm64-v8a/libcverify.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
10	arm64-v8a/libpumbaa-network.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
11	arm64-v8a/libstarship_sdk.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memmove_chk', '__strrchr_chk', '__memset_chk', '__memcpy_chk', '__strlen_chk', '__vsnprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
12	arm64-v8a/libv8_libfull.cr.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk', '__strchr_chk', '__memcpy_chk', '__vsprintf_chk', '__memmove_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
13	arm64-v8a/libttmverify.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
14	arm64-v8a/libvcn.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position Independent Code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memmove_chk', '__strchr_chk', '__memset_chk', '__read_chk', '__strchr_chk', '__memcpy_chk', '__strcpy_chk', '__vsnprintf_chk', '__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
15	arm64-v8a/libfly-main-color-lib.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__read_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
16	arm64-v8a/libshadowhook_nothing.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
17	arm64-v8a/libarc4_sdk_c.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
18	arm64-v8a/libByteAINN.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memmove_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
19	arm64-v8a/libbytebench.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memmove_chk', '__vsprintf_chk', '__read_chk', '__strlen_chk', '__vsprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
20	arm64-v8a/libCepProxy.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
21	arm64-v8a/libconfigcenter.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
22	arm64-v8a/libartshadowhook.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strchr_chk', '__memcpy_chk', '__memset_chk', '__strncpy_chk', '__strlen_chk', '__read_chk', '__strchr_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
23	arm64-v8a/libjazz.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memmove_chk', '__memcpy_chk', '__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
24	arm64-v8a/libnpth_tls_monitor.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
25	arm64-v8a/libonetex.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memmove_chk', '__strlen_chk', '__vsprintf_chk', '__read_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
26	arm64-v8a/libtt_c2pa_sdk_d.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	\$ORIGIN/../../../../usr/local/rustup/toolchains/1.77.1-x86_64-unknown-linux-gnu/lib/rustlib/aarch64-linux-android/lib high The binary has RUNPATH set. In certain cases, an attacker can abuse this feature and or modify environment variables to run arbitrary libraries for code execution and privilege escalation. The only time a library should set RUNPATH is when it is linked to private libraries in the same package. Remove the compiler option --enable-new-dtags,-rpath to remove RUNPATH.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
27	arm64-v8a/libEffectCreatorjni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strncpy_chk', ['__memmove_chk', ['__memcpy_chk', ['__memset_chk', ['__strlen_chk', ['__vsprintf_chk', ['__strchr_chk', ['__vsnprintf_chk']]	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
28	arm64-v8a/libvideodec.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk', '__memcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
29	arm64-v8a/libnpth_dumper.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Position Independent Executable (PIE) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__read_chk', '__vsprintf_chk', '__memset_chk', '__memcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
30	arm64-v8a/liblynxstarlight.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
31	arm64-v8a/libmotion.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memset_chk', '__memcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
32	arm64-v8a/libpy-cv-numpycv.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strchr_chk', '__memset_chk', '__strlen_chk', '__vsprintf_chk', '__vsnprintf_chk', '__strcat_chk', '__memcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
33	arm64-v8a/libtbboringssl.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
34	arm64-v8a/libnetecho.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
35	arm64-v8a/libjazz_plugin.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memmove_chk', '__memcpy_chk', '__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
36	arm64-v8a/libsimba.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
37	arm64-v8a/libArchive.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', '__strlen_chk', '__memmove_chk', '__read_chk', '__strcat_chk', '__umask_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
38	arm64-v8a/libres_memory.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
39	arm64-v8a/libaudioeffect.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk', '__memmove_chk', '__memset_chk', '__strchr_chk', '__strlen_chk', '__vsprintf_chk', '__vsnprintf_chk', '__vsnprintf_chk', '__vsnprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
40	arm64-v8a/libsscronet.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__read_chk', '__memcpy_chk', '__FD_ISSET_chk', '__FD_SET_chk', '__FD_CLR_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
41	arm64-v8a/libstatic-webp.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', ['__memcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
42	arm64-v8a/libttr.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk', '__strlen_chk', '__memmove_chk', '__vsnprintf_chk', '__strchr_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
43	arm64-v8a/libspeechsdk.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memmove_chk', '__memset_chk', '__memcpy_chk', '__vsnprintf_chk', '__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
44	arm64-v8a/liblynxsecurity.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
45	arm64-v8a/liblynx_krypton.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
46	arm64-v8a/libshadowhook.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__read_chk', '__strchr_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
47	arm64-v8a/libtexturerender_native.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strchr_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
48	arm64-v8a/libtt_c2pa_sdk.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
49	arm64-v8a/libILAMaterialSDK.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk', '__vsnprintf_chk', '__memcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
50	arm64-v8a/libworker.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
51	arm64-v8a/libnxreword.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__read_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
52	arm64-v8a/libbytenn.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,nov to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', '__memmove_chk', '__memcpy_chk', '__vsnprintf_chk', '__strcat_chk', '__read_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
53	arm64-v8a/liblink_mic_sdk.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	\$ORIGIN/../../../../usr/local/rustup/toolchains/1.70.0-x86_64-unknown-linux-gnu/lib/rustlib/aarch64-linux-android/lib high The binary has RUNPATH set. In certain cases, an attacker can abuse this feature and or modify environment variables to run arbitrary libraries for code execution and privilege escalation. The only time a library should set RUNPATH is when it is linked to private libraries in the same package. Remove the compiler option --enable-new-dtags,-rpath to remove RUNPATH.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
54	arm64-v8a/libstarship_wrapper.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
55	arm64-v8a/libvolcenginertc.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk', '__strlen_chk', '__memset_chk', '__vsprintf_chk', '__vsnprintf_chk', '__memmove_chk', '__FD_SET_chk', '__strcpy_chk', '__strchr_chk', '__strcat_chk', '__read_chk', '__FD_CLR_chk', '__FD_ISSET_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
56	arm64-v8a/libByteAIDT.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
57	arm64-v8a/libjato.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', '__read_chk', '__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
58	arm64-v8a/libbytevc1enc.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strcpy_chk', '__strchr_chk', '__vsnprintf_chk', '__strlen_chk', '__memcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
59	arm64-v8a/libbytennllm-jni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk', '__vsprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
60	arm64-v8a/libmonitorcollector-lib.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memmove_chk', '__strncpy_chk', '__memset_chk', '__memcpy_chk', '__read_chk', '__vsprintf_chk', '__strcpy_chk', '__vsnprintf_chk', '__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
61	arm64-v8a/lib_jhmp.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
62	arm64-v8a/libkryptonaudio.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
63	arm64-v8a/libgeckox_bspatch.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', '__strlen_chk', '__read_chk', '__strcat_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
64	arm64-v8a/liborbuculum.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', '__strncat_chk', '__vsnprintf_chk', '__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
65	arm64-v8a/libyoga.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', '__strlen_chk', '__memmove_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
66	arm64-v8a/libnpth_unw.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
67	arm64-v8a/libNLEEditorjni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,nov to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', '__strlen_chk', '__strncpy_chk', '__memcpy_chk', '__memmove_chk', '__memset_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
68	arm64-v8a/libttvesdk_plugin.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: <pre>['__memcpy_chk', '__memset_chk', '__vsnprintf_chk', '__strlen_chk', '__memmove_chk', '__strchr_chk', '__strchr_chk', '__read_chk', '__vsprintf_chk', '__strcpy_chk', '__strncpy_chk']</pre>	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
69	arm64-v8a/libfile_lock.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
70	arm64-v8a/libgodzilla-memspunge.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
71	arm64-v8a/libfdk-aac.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
72	arm64-v8a/libjarvis-trace.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['_vsprintf_chk', '_strchr_chk', '_strrchr_chk', '_memcpy_chk', '_vsnprintf_chk', '_read_chk', '_strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
73	arm64-v8a/lib_jbmf.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
74	arm64-v8a/libanimax_bytevc1.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
75	arm64-v8a/libminizip.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memmove_chk', '__vsprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
76	arm64-v8a/libCutSamejni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memmove_chk', '__strlen_chk', '__memset_chk', '__strcpy_chk', '__vsnprintf_chk', '__memcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
77	arm64-v8a/libEncryptor.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
78	arm64-v8a/libwatson.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
79	arm64-v8a/libotis_attrib.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk', '__strcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
80	arm64-v8a/liblynxbase.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', '__memcpy_chk', '__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
81	arm64-v8a/libwcd.db.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,nov to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memmove_chk', '__strncpy_chk', '__memset_chk', '__memcpy_chk', '__vsnprintf_chk', '__strncpy_chk', '__read_chk', '__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
82	arm64-v8a/libttdemux.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
83	arm64-v8a/libNLETemplateModelJni_plugin.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk', '__strncpy_chk', '__memcpy_chk', '__memmove_chk', '__memset_chk', '__vsnprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
84	arm64-v8a/libpipo-security-sdk.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
85	arm64-v8a/libCepFast.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
86	arm64-v8a/libanrrelief.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', '__strlen_chk', '__memmove_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
87	arm64-v8a/libDavinciResourceJni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memmove_chk', '__strncpy_chk', '__memset_chk', '__strlen_chk', '__strcpy_chk', '__memcpy_chk', '__vsnprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
88	arm64-v8a/libfileprotect.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
89	arm64-v8a/libnpth_repair.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
90	arm64-v8a/libkrypton_sar.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strcat_chk', '__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
91	arm64-v8a/libbmf_hydra_lite.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
92	arm64-v8a/libquick.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', '__strlen_chk', '__vsnprintf_chk', '__strchr_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
93	arm64-v8a/libfastcv.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['_vsnprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
94	arm64-v8a/libBlinkCard.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
95	arm64-v8a/libbdzstd.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
96	arm64-v8a/libbytelink.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['_vsnprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
97	arm64-v8a/libforestx_native_buffer.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__read_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
98	arm64-v8a/libttmverifylite.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
99	arm64-v8a/libbmf_mods.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
100	arm64-v8a/libresource_monitor.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['_vsprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
101	arm64-v8a/libkryptoneffect.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
102	arm64-v8a/libptyjemalloc.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
103	arm64-v8a/libtffmjpeg.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
104	arm64-v8a/libanimax_textra.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
105	arm64-v8a/liblynxtrace.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
106	arm64-v8a/libpythonA.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', '__memmove_chk', '__memcpy_chk', '__strcpy_chk', '__read_chk', '__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
107	arm64-v8a/libgifimage.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
108	arm64-v8a/libsysoptimizer.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memmove_chk', '__strrchr_chk', '__memset_chk', '__memcpy_chk', '__vsprintf_chk', '__strchr_chk', '__strcpy_chk', '__vsnprintf_chk', '__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
109	arm64-v8a/libtailor.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memmove_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
110	arm64-v8a/libkryptonaurum.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
111	arm64-v8a/libbdmpg123.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__read_chk', '__strncpy_chk', '__FD_SET_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
112	arm64-v8a/libbd-install.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memmove_chk', '__memset_chk', '__memcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
113	arm64-v8a/libNLEMediaJni_plugin.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk', '__memmove_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
114	arm64-v8a/libiesapplogger.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
115	arm64-v8a/libpsp_engine.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
116	arm64-v8a/libdelta.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
117	arm64-v8a/libNLEditorJni_plugin.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', '__strlen_chk', '__strncpy_chk', '__memcpy_chk', '__memmove_chk', '__memset_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
118	arm64-v8a/libclient_ai_impl_jni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
119	arm64-v8a/libnpth_fp_unw.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
120	arm64-v8a/libkeva.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
121	arm64-v8a/libflipped.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
122	arm64-v8a/libbat.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', '__vsnprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
123	arm64-v8a/libAwplatsupport.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
124	arm64-v8a/libttmplayer.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strncpy_chk', '__strchr_chk', '__strlen_chk', '__strcpy_chk', '__vsprintf_chk', '__vsnprintf_chk', '__strncpy_chk', '__memcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
125	arm64-v8a/libBDPythonVM.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
126	arm64-v8a/libgaia_lib.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memmove_chk', '__read_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
127	arm64-v8a/libsliver.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memmove_chk', '__memset_chk', '__memcpy_chk', '__strcpy_chk', '__vsprintf_chk', '__strchr_chk', '__strncpy_chk', '__read_chk', '__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
128	arm64-v8a/libTTMStrategyCenter.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
129	arm64-v8a/libbytennllm.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk', '__vsprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
130	arm64-v8a/liblynx_v8_bridge.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
131	arm64-v8a/libnativeaudio.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', '__read_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
132	arm64-v8a/libskity.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
133	arm64-v8a/libropaencrypt.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
134	arm64-v8a/libstorage-hook.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
135	arm64-v8a/libjson_opt.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
136	arm64-v8a/libavmdlp2pv2.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strchr_chk', ['__strlen_chk', ['__vsprintf_chk', ['__vsnprintf_chk', ['__read_chk', ['__memcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
137	arm64-v8a/libskbase.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', '__strncpy_chk', '__memcpy_chk', '__strcpy_chk', '__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
138	arm64-v8a/libbdsword.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
139	arm64-v8a/libttpreload.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk', '__vsprintf_chk', '__vsnprintf_chk', '__strncpy_chk', '__read_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
140	arm64-v8a/libarc4_sdk_jni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
141	arm64-v8a/libttheif_dec.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
142	arm64-v8a/libfast_engine_api_loader.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
143	arm64-v8a/libalog.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,nov to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memset_chk', '__strncpy_chk', '__strcpy_chk', '__vsprintf_chk', '__strlen_chk', '__memcpy_chk', '__read_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
144	arm64-v8a/libavmdlbase.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk', '__read_chk', '__vsprintf_chk', '__memcpy_chk', '__vsnprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
145	arm64-v8a/libEffectEditorJni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memmove_chk', '__strncpy_chk', '__memset_chk', '__memcpy_chk', '__strlen_chk', '__vsprintf_chk', '__strchr_chk', '__vsnprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
146	arm64-v8a/libhelios_bm.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
147	arm64-v8a/libnpth_bt.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
148	arm64-v8a/libttext_lite.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk', '__memcpy_chk', '__vsnprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
149	arm64-v8a/libqmiVsyncHook.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
150	arm64-v8a/libttmcmf.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
151	arm64-v8a/libNLEResourcesDAVJni_plugin.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk', ['__strncpy_chk', ['__memcpy_chk', ['__memmove_chk', ['__memset_chk', ['__vsnprintf_chk']]	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
152	arm64-v8a/libAGFX.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memmove_chk', '__memset_chk', '__strcpy_chk', '__vsprintf_chk', '__strchr_chk', '__memcpy_chk', '__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
153	arm64-v8a/libnpath_unwind.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
154	arm64-v8a/libandroidx.graphics.path.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
155	arm64-v8a/liblynx_service_api.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
156	arm64-v8a/libbytehook.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__read_chk', '__vsprintf_chk', '__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
157	arm64-v8a/libbmf_module_sdk.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', '__vsnprintf_chk', '__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
158	arm64- v8a/libpns_ttmachine_adapter.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memmove_chk', '__memset_chk', '__memcpy_chk', '__strcpy_chk', '__strlen_chk', '__vsprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
159	arm64-v8a/libtisopt.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
160	arm64-v8a/libpunch.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
161	arm64-v8a/libvegasdk.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memmove_chk', '__memset_chk', '__memcpy_chk', '__vsnprintf_chk', '__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
162	arm64-v8a/libbmf_hydra.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memmove_chk', '__memcpy_chk', '__strcpy_chk', '__vsprintf_chk', '__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
163	arm64-v8a/liblynx.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk', '__strlen_chk', '__vsnprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
164	arm64-v8a/libanimax.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk', '__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
165	arm64-v8a/libpreload.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
166	arm64-v8a/libimagepipeline.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['_vsprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
167	arm64-v8a/libPitayaBdComponent.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', '__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
168	arm64-v8a/librex.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
169	arm64-v8a/libAndroidPitayaCore.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memmove_chk', '__memset_chk', '__strlen_chk', '__strcpy_chk', '__read_chk', '__memcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
170	arm64-v8a/libbdheif.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
171	arm64-v8a/libbytevc1enc10b.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memmove_chk', '__strchr_chk', '__memcpy_chk', '__strcpy_chk', '__vsnprintf_chk', '__read_chk', '__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
172	arm64-v8a/liblynx_text_service.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
173	arm64-v8a/libSmartMovieJni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memmove_chk', '__strncpy_chk', '__strlen_chk', '__strcpy_chk', '__memset_chk', '__vsprintf_chk', '__vsnprintf_chk', '__memcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
174	arm64-v8a/libNLEMediaRemoteJni_plugin.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memset_chk', '__memcpy_chk', '__strlen_chk', '__strncpy_chk', '__memmove_chk', '__vsnprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
175	arm64-v8a/libnpath_logcat.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Position Independent Executable (PIE) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strncpy_chk', '__strlen_chk', '__strchr_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
176	arm64-v8a/libnpth_xasan.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strchr_chk', '__vsprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
177	arm64-v8a/libc++_shared.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', '__strlen_chk', '__memmove_chk', '__read_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
178	arm64-v8a/libzoin.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__read_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
179	arm64-v8a/libalignpage.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk', '__strcpy_chk', '__vsnprintf_chk', '__strlen_chk', '__vsprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
180	arm64-v8a/libh3-java.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['_vsprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
181	arm64-v8a/libnapi.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
182	arm64-v8a/libkrypton.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk', '__memset_chk', '__vsprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
183	arm64-v8a/libnpth_ref_monitor.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', ['__memcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
184	arm64-v8a/libByteVC1_dec.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
185	arm64-v8a/libbytevc1enc8bwrapper.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', ['__memcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
186	arm64-v8a/libCepAuth.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
187	arm64-v8a/libvctfo.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
188	arm64-v8a/libcybertron_base.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
189	arm64-v8a/libp2plivevdp.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
190	arm64-v8a/libffmpeg_dashdec.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strchr_chk', '__vsprintf_chk', '__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
191	arm64-v8a/libwasm.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', '__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
192	arm64-v8a/libbyteMonitor.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memmove_chk', '__memset_chk', '__memcpy_chk', '__strcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
193	arm64-v8a/libserval_svg.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strchr_chk', '__memcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
194	arm64-v8a/libartlog_monitor.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
195	arm64-v8a/libvolcenginertc_plugin.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk', '__strlen_chk', '__memset_chk', '__vsprintf_chk', '__vsnprintf_chk', '__memmove_chk', '__FD_SET_chk', '__strcpy_chk', '__strchr_chk', '__strcat_chk', '__read_chk', '__FD_CLR_chk', '__FD_ISSET_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
196	arm64-v8a/libCepEngine.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
197	arm64-v8a/libttminisnative.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk', '__memmove_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
198	arm64-v8a/libttquic.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk', '__read_chk', '__vsprintf_chk', '__memcpy_chk', '__vsnprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
199	arm64-v8a/libspeechspg.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memmove_chk', '__strlen_chk', '__vsprintf_chk', '__memcpy_chk', '__memset_chk', '__vsnprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
200	arm64-v8a/libnpath_dl.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__read_chk', '__vsprintf_chk', '__strchr_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
201	arm64-v8a/libbytedt.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
202	arm64-v8a/libfast_engine.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strchr_chk', '__memcpy_chk', '__vsprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
203	arm64-v8a/libbytevc1enc10bwrapper.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', ['__memcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
204	arm64-v8a/libbytevc0.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['_strchr_chk', ['_memset_chk', ['_memcpy_chk', ['_strcpy_chk', ['_vsnprintf_chk', ['_strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
205	arm64-v8a/libhmp.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
206	arm64-v8a/libpns_crypto.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
207	arm64-v8a/libPitayaTTPolicy.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
208	arm64-v8a/libopus.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
209	arm64-v8a/libTTMachineCore.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', '__strcpy_chk', '__vsnprintf_chk', '__strcat_chk', '__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
210	arm64-v8a/libNLEMediaRemoteJni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memset_chk', ['__memcpy_chk', ['__strlen_chk', ['__strncpy_chk', ['__memmove_chk', ['__vsnprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
211	arm64-v8a/libvcbasekit.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk', '__vsnprintf_chk', '__strcat_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
212	arm64-v8a/libug_share_sort.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', '__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
213	arm64-v8a/libBDMicroPythonVM.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
214	arm64-v8a/liblivestrategy.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', '__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
215	arm64-v8a/libspeechpeg.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
216	arm64-v8a/libbdvideouploader.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strchr_chk', ['__memmove_chk', ['__memset_chk', ['__strrchr_chk', ['__strlen_chk', ['__strcpy_chk', ['__vprintf_chk', ['__vsnprintf_chk', ['__strncat_chk', ['__strcat_chk', ['__read_chk', ['__memcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
217	arm64-v8a/librtmglobal.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memset_chk', '__memcpy_chk', '__memmove_chk', '__strlen_chk', '__vsnprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
218	arm64-v8a/libbuffer.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__read_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
219	arm64-v8a/libfast_engine_api.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
220	arm64-v8a/libworkerv8.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
221	arm64-v8a/libeffect_plugin.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: <pre>['__memmove_chk', '__memcpy_chk', '__strlen_chk', '__strcpy_chk', '__memset_chk', '__vsnprintf_chk', '__strncpy_chk', '__strcat_chk', '__strchr_chk', '__vsprintf_chk', '__read_chk']</pre>	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
222	arm64-v8a/libbytennwrapper.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
223	arm64-v8a/libicu.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
224	arm64-v8a/libnative-filters.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
225	arm64-v8a/libpsiencript.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk', '__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
226	arm64-v8a/liblynx_markdown.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk', '__strlen_chk', '__strchr_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
227	arm64-v8a/libjnidispatch.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
228	arm64-v8a/libtccrypto.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memset_chk', '__memcpy_chk', '__read_chk', '__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
229	arm64-v8a/libspeechengine.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
230	arm64-v8a/libxtrace.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
231	arm64-v8a/libpy-numpy.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memmove_chk', '__memset_chk', '__memcpy_chk', '__vsnprintf_chk', '__read_chk', '__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
232	arm64-v8a/liboecsec_ov.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strncpy_chk', ['__strchr_chk', ['__strrchr_chk', ['__read_chk', ['__memset_chk', ['__vsprintf_chk', ['__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
233	arm64-v8a/libvoip.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', '__memset_chk', '__memcpy_chk', '__vsnprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
234	arm64-v8a/liburiparser.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
235	arm64-v8a/libmemrelief.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk', '__memset_chk', '__vsnprintf_chk', '__strlen_chk', '__memmove_chk', '__vsprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
236	arm64-v8a/libCepAST.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
237	arm64-v8a/libEffectEditorABTestjni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memmove_chk', '__strncpy_chk', '__memset_chk', '__memcpy_chk', '__strlen_chk', '__vsprintf_chk', '__strchr_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
238	arm64-v8a/libNLEResourcesDAVjni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk', '__strncpy_chk', '__memcpy_chk', '__memmove_chk', '__memset_chk', '__vsnprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
239	arm64-v8a/libNLEMediaPublicjni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk', '__strncpy_chk', '__memmove_chk', '__memcpy_chk', '__memset_chk', '__vsnprintf_chk', '__strchr_chk', '__read_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
240	arm64-v8a/libbtch_collection.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memmove_chk', '__memset_chk', '__strlen_chk', '__memcpy_chk', '__strcpy_chk', '__vsnprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
241	arm64-v8a/libaudio_fingerprint_sdk.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
242	arm64-v8a/libart_sym.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
243	arm64-v8a/libnpth_fd_tracker.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', '__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
244	arm64-v8a/libkomprese-decompressor.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
245	arm64-v8a/libmmt.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memset_chk', '__memcpy_chk', '__vsprintf_chk', '__strchr_chk', '__strncpy_chk', '__read_chk', '__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
246	arm64-v8a/libapplog_rust.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
247	arm64-v8a/libwhisper.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
248	arm64-v8a/libnpth.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strcat_chk', '__vsprintf_chk', '__strncpy_chk', '__strlen_chk', '__strcpy_chk', '__read_chk', '__strchr_chk', '__strrchr_chk', '__vsprintf_chk', '__memmove_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
249	arm64-v8a/libprofiler.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
250	arm64-v8a/libanimax_napi.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
251	arm64-v8a/libyuv.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
252	arm64-v8a/libbach-sdk-jni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
253	arm64-v8a/libmetasec_ov.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', '__vsnprintf_chk', '__read_chk', '__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
254	arm64-v8a/libanrthanos.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strchr_chk', '__strncpy_chk', '__memcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
255	arm64-v8a/libAwebviewbytedance.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk', '__memset_chk', '__strlen_chk', '__read_chk', '__write_chk', '__strchr_chk', '__vsprintf_chk', '__memchr_chk', '__fwrite_chk', '__pread64_chk', '__pread_chk', '__pwrite64_chk', '__strncat_chk', '__sendto_chk', '__readlink_chk', '__FD_SET_chk', '__FD_ISSET_chk', '__FD_CLR_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
256	arm64-v8a/libnewep.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
257	arm64-v8a/libNLETemplateModelJni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk', '__strncpy_chk', '__memcpy_chk', '__memmove_chk', '__memset_chk', '__vsnprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
258	arm64-v8a/libNLEMediaPublicjni_plugin.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk', '__strncpy_chk', '__memmove_chk', '__memcpy_chk', '__memset_chk', '__strchr_chk', '__vsprintf_chk', '__read_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
259	arm64-v8a/libvcnverifylite.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strchr_chk', '__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
260	arm64-v8a/libNLEMediajni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk', '__memmove_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
261	arm64-v8a/libflock-lib.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
262	arm64-v8a/libnapi_v8.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
263	arm64-v8a/libbvcparser.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
264	arm64-v8a/libjarvis-metrics.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
265	arm64-v8a/libcrashpad_handler_trampoline.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Position Independent Executable (PIE) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
266	arm64-v8a/libkryptonremote.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
267	arm64-v8a/libgodzilla-sysopt.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
268	arm64-v8a/libTTNativeML.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
269	armeabi-v7a/libbyteVC2dec.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
270	armeabi-v7a/libreschecker.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', '__strchr_chk', '__strlen_chk', '__memcpy_chk', '__memmove_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
271	armeabi-v7a/libtt_ugen_layout.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
272	armeabi-v7a/liborbuculumadapter.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strcpy_chk', '__vsprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
273	armeabi-v7a/liblens.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk', '__vsprintf_chk', '__memmove_chk', '__memset_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
274	armeabi-v7a/libavocadoguard.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', '__vsnprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
275	armeabi-v7a/libbase_live.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strchr_chk', '__vsprintf_chk', '__strlen_chk', '__read_chk', '__memcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
276	armeabi-v7a/libbdhm_native.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	\$ORIGIN/../../../../usr/local/rustup/toolchains/1.70.0-x86_64-unknown-linux-gnu/lib/rustlib/armv7-linux-androideabi/lib high The binary has RUNPATH set. In certain cases, an attacker can abuse this feature and or modify environment variables to run arbitrary libraries for code execution and privilege escalation. The only time a library should set RUNPATH is when it is linked to private libraries in the same package. Remove the compiler option --enable-new-dtags,-rpath to remove RUNPATH.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
277	armeabi-v7a/libcverify.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
278	armeabi-v7a/libpumbaa-network.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
279	armeabi-v7a/libstarship_sdk.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', '__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
280	armeabi-v7a/libv8_libfull.cr.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', '__strlen_chk', '__strchr_chk', '__memcpy_chk', '__memmove_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
281	armeabi-v7a/libttmverify.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
282	armeabi-v7a/libvcn.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
283	armeabi-v7a/libfly-main-color-lib.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
284	armeabi-v7a/libshadowhook_nothing.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
285	armeabi-v7a/libarcore_sdk_c.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
286	armeabi-v7a/libByteAINN.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memmove_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
287	armeabi-v7a/libbytebench.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', '__read_chk', '__vsprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
288	armeabi-v7a/libCepProxy.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
289	armeabi-v7a/libconfigcenter.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
290	armeabi-v7a/libartshadowhook.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
291	armeabi-v7a/libjazz.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
292	armeabi-v7a/libnpth_tls_monitor.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
293	armeabi-v7a/libonetex.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
294	armeabi-v7a/libtt_c2pa_sdk_d.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	\$ORIGIN/../../../../usr/local/rustup/toolchains/1.77.1-x86_64-unknown-linux-gnu/lib/rustlib/armv7-linux-androideabi/lib high The binary has RUNPATH set. In certain cases, an attacker can abuse this feature and or modify environment variables to run arbitrary libraries for code execution and privilege escalation. The only time a library should set RUNPATH is when it is linked to private libraries in the same package. Remove the compiler option --enable-new-dtags,-rpath to remove RUNPATH.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
295	armeabi-v7a/libEffectCreatorJni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk', '__memmove_chk', '__memset_chk', '__vsnprintf_chk', '__strlen_chk', '__strchr_chk', '__strncpy_chk', '__vsprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
296	armeabi-v7a/libvideodec.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
297	armeabi-v7a/libnpth_dumper.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Position Independent Executable (PIE) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__read_chk', '__vsprintf_chk', '__memset_chk', '__memcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
298	armeabi-v7a/liblynxstarlight.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
299	armeabi-v7a/libmotion.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
300	armeabi-v7a/libpy-cv-numpycv.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
301	armeabi-v7a/libtbboringssl.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
302	armeabi-v7a/libnetecho.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
303	armeabi-v7a/libjazz_plugin.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
304	armeabi-v7a/libsimba.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
305	armeabi-v7a/libArchive.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__read_chk', '__strlen_chk', '__umask_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
306	armeabi-v7a/libres_memory.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
307	armeabi-v7a/libaudioeffect.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk', ['__memmove_chk', ['__strchr_chk', ['__strlen_chk', ['__vsnprintf_chk', ['__vsprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
308	armeabi-v7a/libsscronet.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', '__read_chk', '__memcpy_chk', '__FD_ISSET_chk', '__FD_SET_chk', '__FD_CLR_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
309	armeabi-v7a/libstatic-webp.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
310	armeabi-v7a/libttr.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk', '__vsnprintf_chk', '__strchr_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
311	armeabi-v7a/libspeechsdk.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memmove_chk', '__memcpy_chk', '__vsnprintf_chk', '__memset_chk', '__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
312	armeabi-v7a/liblynxsecurity.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
313	armeabi-v7a/liblynx_krypton.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
314	armeabi-v7a/libshadowhook.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
315	armeabi-v7a/libtexturerender_native.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
316	armeabi-v7a/libtt_c2pa_sdk.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
317	armeabi-v7a/libILAMaterialSDK.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk', '__vsprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
318	armeabi-v7a/libworker.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
319	armeabi-v7a/libxreword.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__read_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
320	armeabi-v7a/libbytenn.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
321	armeabi-v7a/liblink_mic_sdk.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	\$ORIGIN/../../../../usr/local/rustup/toolchains/1.70.0-x86_64-unknown-linux-gnu/lib/rustlib/armv7-linux-androideabi/lib high The binary has RUNPATH set. In certain cases, an attacker can abuse this feature and or modify environment variables to run arbitrary libraries for code execution and privilege escalation. The only time a library should set RUNPATH is when it is linked to private libraries in the same package. Remove the compiler option --enable-new-dtags,-rpath to remove RUNPATH.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
322	armeabi-v7a/libstarship_wrapper.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
323	armeabi-v7a/libvolcenginertc.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk', '__strlen_chk', '__memset_chk', '__vsprintf_chk', '__vsnprintf_chk', '__memmove_chk', '__strcpy_chk', '__strchr_chk', '__strcat_chk', '__fgets_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
324	armeabi-v7a/libByteAIDT.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
325	armeabi-v7a/libjato.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk', '__read_chk', '__vsprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
326	armeabi-v7a/libbytevc1enc.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strcpy_chk', '__strchr_chk', '__vsnprintf_chk', '__strlen_chk', '__memcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
327	armeabi-v7a/libbytennllm-jni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk', '__vsnprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
328	armeabi-v7a/libmonitorcollector-lib.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
329	armeabi-v7a/lib_jhmp.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
330	armeabi-v7a/libkryptonaudio.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
331	armeabi-v7a/libgeckox_bspatch.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strcat_chk', '__strlen_chk', '__read_chk', '__vsprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
332	armeabi-v7a/liborbuculum.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strncat_chk', '__strlen_chk', '__vsprintf_chk', '__vsnprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
333	armeabi-v7a/libyoga.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
334	armeabi-v7a/libnpth_unw.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
335	armeabi-v7a/libNLEditorJni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', '__strlen_chk', '__memcpy_chk', '__memmove_chk', '__memset_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
336	armeabi-v7a/libttvesdk_plugin.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk', '__memset_chk', '__vsnprintf_chk', '__strlen_chk', '__memmove_chk', '__strchr_chk', '__strchr_chk', '__vsprintf_chk', '__strcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
337	armeabi-v7a/libfile_lock.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
338	armeabi-v7a/libgodzilla-mem sponge.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
339	armeabi-v7a/libfdk-aac.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
340	armeabi-v7a/lib_jbmf.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
341	armeabi-v7a/libanimax_bytevc1.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
342	armeabi-v7a/libminizip.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', '__memmove_chk', '__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
343	armeabi-v7a/libCutSamejni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
344	armeabi-v7a/libEncryptor.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
345	armeabi-v7a/libwatson.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
346	armeabi-v7a/libotis_attrib.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk', '__strcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
347	armeabi-v7a/liblynxbase.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', '__memcpy_chk', '__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
348	armeabi-v7a/libwcd.db.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
349	armeabi-v7a/libttdemux.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
350	armeabi-v7a/libNLETemplateModelJni_plugin.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk', '__memcpy_chk', '__memmove_chk', '__memset_chk', '__vsnprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
351	armeabi-v7a/libpipo-security-sdk.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
352	armeabi-v7a/libCepFast.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
353	armeabi-v7a/libanrrelief.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
354	armeabi-v7a/libDavinciResourceJni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
355	armeabi-v7a/libfileprotect.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
356	armeabi-v7a/libnpth_repair.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
357	armeabi-v7a/libkrypton_sar.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strcat_chk', '__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
358	armeabi-v7a/libbmf_hydra_lite.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['_vsnprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
359	armeabi-v7a/libquick.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
360	armeabi-v7a/libfastcv.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', '__vsnprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
361	armeabi-v7a/libBlinkCard.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
362	armeabi-v7a/libbdzstd.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
363	armeabi-v7a/libbytelink.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
364	armeabi-v7a/libforestx_native_buffer.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__read_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
365	armeabi-v7a/libttmverifylite.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
366	armeabi-v7a/libbmf_mods.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
367	armeabi-v7a/libresource_monitor.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['_vsprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
368	armeabi-v7a/libkryptoneffect.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
369	armeabi-v7a/libptyjemalloc.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
370	armeabi-v7a/libtftfmpeg.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
371	armeabi-v7a/libanimax_textra.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
372	armeabi-v7a/liblynxtrace.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
373	armeabi-v7a/libpythonA.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
374	armeabi-v7a/libgifimage.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
375	armeabi-v7a/libsysoptimizer.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk', '__strcpy_chk', '__vsprintf_chk', '__strchr_chk', '__vsnprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
376	armeabi-v7a/libtailor.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
377	armeabi-v7a/libkryptonaurem.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
378	armeabi-v7a/libbdmpg123.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
379	armeabi-v7a/libbd-install.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
380	armeabi-v7a/libNLEMediaJni_plugin.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
381	armeabi-v7a/libiesapplogger.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
382	armeabi-v7a/libpsp_engine.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
383	armeabi-v7a/libdelta.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
384	armeabi-v7a/libNLEditorJni_plugin.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', '__strlen_chk', '__memcpy_chk', '__memmove_chk', '__memset_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
385	armeabi-v7a/libclient_ai_impl_jni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
386	armeabi-v7a/libkeva.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
387	armeabi-v7a/libflipped.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
388	armeabi-v7a/libbat.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
389	armeabi-v7a/libAwplatsupport.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
390	armeabi-v7a/libttmpplayer.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk', '__vsprintf_chk', '__memcpy_chk', '__strchr_chk', '__strcpy_chk', '__vsprintf_chk', '__strcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
391	armeabi-v7a/libBDPythonVM.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
392	armeabi-v7a/libgaia_lib.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
393	armeabi-v7a/libsliver.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
394	armeabi-v7a/libTTMStrategyCenter.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
395	armeabi-v7a/libbytennllm.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
396	armeabi-v7a/liblynx_v8_bridge.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
397	armeabi-v7a/libnativeaudio.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__read_chk', '__vsprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
398	armeabi-v7a/libskity.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
399	armeabi-v7a/libropaencrypt.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
400	armeabi-v7a/libstorage-hook.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
401	armeabi-v7a/libjson_opt.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
402	armeabi-v7a/libavmdlp2pv2.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
403	armeabi-v7a/libskbase.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', '__strlen_chk', '__memcpy_chk', '__strcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
404	armeabi-v7a/libbdsword.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
405	armeabi-v7a/libtppreload.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__read_chk', '__vsprintf_chk', '__vsprintf_chk', '__strlen_chk', '__strcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
406	armeabi-v7a/libarc4core_sdk_jni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
407	armeabi-v7a/libttheif_dec.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
408	armeabi-v7a/libfast_engine_api_loader.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
409	armeabi-v7a/libalog.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
410	armeabi-v7a/libavmdlbase.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk', '__read_chk', '__vsprintf_chk', '__memcpy_chk', '__vsnprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
411	armeabi-v7a/libEffectEditorJni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strchr_chk', '__vsprintf_chk', '__strlen_chk', '__strncpy_chk', '__memcpy_chk', '__memmove_chk', '__memset_chk', '__vsnprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
412	armeabi-v7a/libhelios_bm.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
413	armeabi-v7a/libnpth_bt.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
414	armeabi-v7a/libttext_lite.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
415	armeabi-v7a/libqmiVsyncHook.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
416	armeabi-v7a/libttmcmaf.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
417	armeabi-v7a/libNLEResourcesDAVJni_plugin.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk', '__memcpy_chk', '__memmove_chk', '__memset_chk', '__vsnprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
418	armeabi-v7a/libAGFX.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
419	armeabi-v7a/libnpth_unwind.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
420	armeabi-v7a/libandroidx.graphics.path.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
421	armeabi-v7a/liblynx_service_api.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
422	armeabi-v7a/libbytehook.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
423	armeabi-v7a/libbmf_module_sdk.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
424	armeabi-v7a/libpns_ttmachine_adapter.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk', '__strcpy_chk', '__vsprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
425	armeabi-v7a/libotisoapt.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
426	armeabi-v7a/libpunch.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
427	armeabi-v7a/libvegasdk.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk', '__vsprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
428	armeabi-v7a/libbmf_hydra.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strcpy_chk', '__vsprintf_chk', '__memcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
429	armeabi-v7a/liblynx.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk', '__strlen_chk', '__vsprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
430	armeabi-v7a/libanimax.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk', '__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
431	armeabi-v7a/libpreload.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
432	armeabi-v7a/libimagepipeline.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
433	armeabi-v7a/libPitayaBdComponent.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', '__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
434	armeabi-v7a/librex.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
435	armeabi-v7a/libAndroidPitayaCore.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk', '__read_chk', '__memset_chk', '__memmove_chk', '__memcpy_chk', '__strcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
436	armeabi-v7a/libbdheif.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
437	armeabi-v7a/libbytevc1enc10b.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
438	armeabi-v7a/liblynx_text_service.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
439	armeabi-v7a/libSmartMovieJni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['_vsprintf_chk', '__strlen_chk', '__strcpy_chk', '__memcpy_chk', '__memmove_chk', '__memset_chk', '__vsnprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
440	armeabi-v7a/libNLEMediaRemoteJni_plugin.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memset_chk', '__memcpy_chk', '__strlen_chk', '__memmove_chk', '__vsnprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
441	armeabi-v7a/libnpth_logcat.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Position Independent Executable (PIE) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strncpy_chk', '__strlen_chk', '__strchr_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
442	armeabi-v7a/libnpth_xasan.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
443	armeabi-v7a/libc++_shared.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
444	armeabi-v7a/libzoin.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
445	armeabi-v7a/libalignpage.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk', '__vsprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
446	armeabi-v7a/libh3-java.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['_vsprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
447	armeabi-v7a/libnapi.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
448	armeabi-v7a/libkrypton.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk', '__memset_chk', '__vsprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
449	armeabi-v7a/libnpth_ref_monitor.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', '__memcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
450	armeabi-v7a/libByteVC1_dec.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
451	armeabi-v7a/libvebytevc1enc8bwrapper.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', ['__memcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
452	armeabi-v7a/libCepAuth.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
453	armeabi-v7a/libvctfo.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
454	armeabi-v7a/libcybertron_base.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
455	armeabi-v7a/libp2plivevdp.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
456	armeabi-v7a/libffmpeg_dashdec.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
457	armeabi-v7a/libwasm.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
458	armeabi-v7a/libbytemonitor.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
459	armeabi-v7a/libserval_svg.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk', '__strchr_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
460	armeabi-v7a/libartlog_monitor.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
461	armeabi-v7a/libvolcenginertc_plugin.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk', '__strlen_chk', '__memset_chk', '__vsprintf_chk', '__vsnprintf_chk', '__memmove_chk', '__strcpy_chk', '__strchr_chk', '__strcat_chk', '__fgets_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
462	armeabi-v7a/libCepEngine.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
463	armeabi-v7a/libttminisnative.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
464	armeabi-v7a/libttquic.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__read_chk', '__vsprintf_chk', '__memcpy_chk', '__vsnprintf_chk', '__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
465	armeabi-v7a/libspeechspg.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memmove_chk', '__memcpy_chk', '__vsnprintf_chk', '__memset_chk', '__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
466	armeabi-v7a/libnpth_dl.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: <pre>['__read_chk', '__vsprintf_chk', '__strchr_chk']</pre>	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
467	armeabi-v7a/libbytedt.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', '__vsnprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
468	armeabi-v7a/libfast_engine.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
469	armeabi-v7a/libvebytevc1enc10bwrapper.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk', '__vsprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
470	armeabi-v7a/libbytevc0.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
471	armeabi-v7a/libhmp.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
472	armeabi-v7a/libpns_crypto.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
473	armeabi-v7a/libPitayaTTPPolicy.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
474	armeabi-v7a/libopus.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
475	armeabi-v7a/libTMachineCore.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk', '__vsprintf_chk', '__strcpy_chk', '__strcat_chk', '__vsnprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
476	armeabi-v7a/libNLEMediaRemoteJni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memset_chk', '__memcpy_chk', '__strlen_chk', '__memmove_chk', '__vsnprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
477	armeabi-v7a/libvcbasekit.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
478	armeabi-v7a/libug_share_sort.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
479	armeabi-v7a/libBDMicroPythonVM.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
480	armeabi-v7a/liblivestrategy.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['_vsnprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
481	armeabi-v7a/libspeechpeg.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
482	armeabi-v7a/libbdvideouploader.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strchr_chk', ['__strlen_chk', ['__memcpy_chk', ['__strncat_chk', ['__strcpy_chk', ['__vsnprintf_chk', ['__strcat_chk', ['__read_chk', ['__vsprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
483	armeabi-v7a/librtmglobal.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memset_chk', '__memcpy_chk', '__strlen_chk', '__vsprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
484	armeabi-v7a/libbuffer.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__read_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
485	armeabi-v7a/libfast_engine_api.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
486	armeabi-v7a/libworkerv8.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
487	armeabi-v7a/libeffect_plugin.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: <pre>['__memmove_chk', '__memcpy_chk', '__strlen_chk', '__strcpy_chk', '__memset_chk', '__vsnprintf_chk', '__vsprintf_chk', '__strncpy_chk', '__read_chk']</pre>	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
488	armeabi-v7a/libbytennwrapper.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
489	armeabi-v7a/libicu.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
490	armeabi-v7a/libnative-filters.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
491	armeabi-v7a/libpsiencript.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
492	armeabi-v7a/liblynx_markdown.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk', '__strlen_chk', '__strchr_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
493	armeabi-v7a/libjnidispatch.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
494	armeabi-v7a/libttcrypto.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
495	armeabi-v7a/libspeechengine.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
496	armeabi-v7a/libxtrace.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
497	armeabi-v7a/libpy-numpy.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
498	armeabi-v7a/liboecsec_ov.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strchr_chk', '__strrchr_chk', '__memset_chk', '__vsprintf_chk', '__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
499	armeabi-v7a/libvoip.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
500	armeabi-v7a/liburiparser.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
501	armeabi-v7a/libmemrelief.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['_vsprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
502	armeabi-v7a/libCepAST.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
503	armeabi-v7a/libEffectEditorABTestJni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strchr_chk', '__vsprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
504	armeabi-v7a/libNLEResourcesDAVJni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk', '__memcpy_chk', '__memmove_chk', '__memset_chk', '__vsprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
505	armeabi-v7a/libNLEMediaPublicjni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk', '__memmove_chk', '__memcpy_chk', '__memset_chk', '__vsnprintf_chk', '__strchr_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
506	armeabi-v7a/libbtch_collection.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', ['__memcpy_chk', ['__strcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
507	armeabi-v7a/libaudio_fingerprint_sdk.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
508	armeabi-v7a/libart_sym.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
509	armeabi-v7a/libnpth_fd_tracker.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', '__strlen_chk', '__read_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
510	armeabi-v7a/libkomprese-decompressor.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
511	armeabi-v7a/libmmt.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk', '__strchr_chk', '__strncpy_chk', '__vsprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
512	armeabi-v7a/libapplog_rust.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
513	armeabi-v7a/libwhisper.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
514	armeabi-v7a/libnpth.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: <pre>['__strcat_chk', '__vsprintf_chk', '__memcpy_chk', '__strncpy_chk', '__strlen_chk', '__strcpy_chk', '__read_chk', '__strchr_chk', '__strrchr_chk', '__vsprintf_chk', '__memmove_chk']</pre>	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
515	armeabi-v7a/libprofiler.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['_vsnprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
516	armeabi-v7a/libanimax_napi.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
517	armeabi-v7a/libyuv.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
518	armeabi-v7a/libbach-sdk-jni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
519	armeabi-v7a/libmetasec_ov.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
520	armeabi-v7a/libanrthanos.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
521	armeabi-v7a/libAwebviewbytedance.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: <pre>['__memcpy_chk', '__memset_chk', '__strlen_chk', '__read_chk', '__write_chk', '__strchr_chk', '__vsprintf_chk', '__memchr_chk', '__fwrite_chk', '__pread64_chk', '__pread_chk', '__pwrite64_chk', '__strncat_chk', '__sendto_chk', '__readlink_chk', '__FD_SET_chk', '__FD_ISSET_chk', '__FD_CLR_chk']</pre>	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
522	armeabi-v7a/libnewep.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
523	armeabi-v7a/libNLETemplateModelJni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk', '__memcpy_chk', '__memmove_chk', '__memset_chk', '__vsnprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
524	armeabi- v7a/libNLEMediaPublicjni_plugin.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk', '__memmove_chk', '__memcpy_chk', '__memset_chk', '__vsnprintf_chk', '__strchr_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
525	armeabi-v7a/libcverifylite.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
526	armeabi-v7a/libNLEMediaJni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
527	armeabi-v7a/libflock-lib.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
528	armeabi-v7a/libnapi_v8.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
529	armeabi-v7a/libbvcparser.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
530	armeabi-v7a/libjarvis-metrics.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
531	armeabi-v7a/libcrashpad_handler_trampoline.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Position Independent Executable (PIE) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
532	armeabi-v7a/libkryptonremote.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
533	armeabi-v7a/libgodzilla-sysopt.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
534	armeabi-v7a/libTTNativeML.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
535	arm64-v8a/libbyteVC2dec.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk', ['__memcpy_chk', ['__strchr_chk', ['__strcat_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
536	arm64-v8a/libreschecker.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['_strchr_chk', ['_strrchr_chk', ['_memset_chk', ['_memmove_chk', ['_memcpy_chk', ['_vsnprintf_chk', ['_strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
537	arm64-v8a/libtt_ugen_layout.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
538	arm64-v8a/liborbuculumadapter.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strcpy_chk', '__vsprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
539	arm64-v8a/liblens.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk', '__vsprintf_chk', '__memset_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
540	arm64-v8a/libavocadoguard.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memmove_chk', '__memset_chk', '__memcpy_chk', '__vsprintf_chk', '__vsnprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
541	arm64-v8a/libbase_live.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strchr_chk', ['__strlen_chk', ['__vsprintf_chk', ['__strcat_chk', ['__read_chk', ['__memcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
542	arm64-v8a/libbdhm_native.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	\$ORIGIN/../../../../usr/local/rustup/toolchains/1.70.0-x86_64-unknown-linux-gnu/lib/rustlib/aarch64-linux-android/lib high The binary has RUNPATH set. In certain cases, an attacker can abuse this feature and or modify environment variables to run arbitrary libraries for code execution and privilege escalation. The only time a library should set RUNPATH is when it is linked to private libraries in the same package. Remove the compiler option --enable-new-dtags,-rpath to remove RUNPATH.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
543	arm64-v8a/libcverify.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
544	arm64-v8a/libpumbaa-network.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
545	arm64-v8a/libstarship_sdk.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memmove_chk', '__strrchr_chk', '__memset_chk', '__memcpy_chk', '__strlen_chk', '__vsnprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
546	arm64-v8a/libv8_libfull.cr.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk', '__strchr_chk', '__memcpy_chk', '__vsprintf_chk', '__memmove_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
547	arm64-v8a/libttmverify.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
548	arm64-v8a/libvcn.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memmove_chk', '__strrchr_chk', '__memset_chk', '__read_chk', '__strchr_chk', '__memcpy_chk', '__strcpy_chk', '__vsnprintf_chk', '__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
549	arm64-v8a/libfly-main-color-lib.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__read_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
550	arm64-v8a/libshadowhook_nothing.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
551	arm64-v8a/libarc4_sdk_c.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
552	arm64-v8a/libByteAINN.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memmove_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
553	arm64-v8a/libbytebench.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memmove_chk', '__vsprintf_chk', '__read_chk', '__strlen_chk', '__vsprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
554	arm64-v8a/libCepProxy.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
555	arm64-v8a/libconfigcenter.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
556	arm64-v8a/libartshadowhook.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strchr_chk', '__memcpy_chk', '__memset_chk', '__strncpy_chk', '__strlen_chk', '__read_chk', '__strchr_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
557	arm64-v8a/libjazz.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memmove_chk', '__memcpy_chk', '__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
558	arm64-v8a/libnpth_tls_monitor.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
559	arm64-v8a/libonetex.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memmove_chk', '__strlen_chk', '__vsnprintf_chk', '__read_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
560	arm64-v8a/libtt_c2pa_sdk_d.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	\$ORIGIN/../../../../usr/local/rustup/toolchains/1.77.1-x86_64-unknown-linux-gnu/lib/rustlib/aarch64-linux-android/lib high The binary has RUNPATH set. In certain cases, an attacker can abuse this feature and or modify environment variables to run arbitrary libraries for code execution and privilege escalation. The only time a library should set RUNPATH is when it is linked to private libraries in the same package. Remove the compiler option --enable-new-dtags,-rpath to remove RUNPATH.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
561	arm64-v8a/libEffectCreatorjni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strncpy_chk', '__memmove_chk', '__memcpy_chk', '__memset_chk', '__strlen_chk', '__vsprintf_chk', '__strchr_chk', '__vsnprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
562	arm64-v8a/libvideodec.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk', '__memcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
563	arm64-v8a/libnpth_dumper.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Position Independent Executable (PIE) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__read_chk', '__vsprintf_chk', '__memset_chk', '__memcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
564	arm64-v8a/liblynxstarlight.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
565	arm64-v8a/libmotion.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memset_chk', '__memcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
566	arm64-v8a/libpy-cv-numpycv.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strchr_chk', '__memset_chk', '__strlen_chk', '__vsprintf_chk', '__vsnprintf_chk', '__strcat_chk', '__memcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
567	arm64-v8a/libtbboringssl.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
568	arm64-v8a/libnetecho.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
569	arm64-v8a/libjazz_plugin.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memmove_chk', '__memcpy_chk', '__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
570	arm64-v8a/libsimba.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
571	arm64-v8a/libArchive.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', '__strlen_chk', '__memmove_chk', '__read_chk', '__strcat_chk', '__umask_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
572	arm64-v8a/libres_memory.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
573	arm64-v8a/libaudioeffect.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk', '__memmove_chk', '__memset_chk', '__strchr_chk', '__strlen_chk', '__vsnprintf_chk', '__vsprintf_chk', '__strchr_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
574	arm64-v8a/libsscronet.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__read_chk', '__memcpy_chk', '__FD_ISSET_chk', '__FD_SET_chk', '__FD_CLR_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
575	arm64-v8a/libstatic-webp.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', '__memcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
576	arm64-v8a/libttr.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,nov to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk', '__strlen_chk', '__memmove_chk', '__vsnprintf_chk', '__strchr_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
577	arm64-v8a/libspeechsdk.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memmove_chk', '__memset_chk', '__memcpy_chk', '__vsnprintf_chk', '__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
578	arm64-v8a/liblynxsecurity.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
579	arm64-v8a/liblynx_krypton.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
580	arm64-v8a/libshadowhook.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__read_chk', '__strchr_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
581	arm64-v8a/libtexturerender_native.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strchr_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
582	arm64-v8a/libtt_c2pa_sdk.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
583	arm64-v8a/libILAMaterialSDK.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk', '__vsnprintf_chk', '__memcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
584	arm64-v8a/libworker.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
585	arm64-v8a/libnxreword.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__read_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
586	arm64-v8a/libbytenn.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['_vsprintf_chk', '__memmove_chk', '__memcpy_chk', '__vsnprintf_chk', '__strcat_chk', '__read_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
587	arm64-v8a/liblink_mic_sdk.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	\$ORIGIN/../../../../usr/local/rustup/toolchains/1.70.0-x86_64-unknown-linux-gnu/lib/rustlib/aarch64-linux-android/lib high The binary has RUNPATH set. In certain cases, an attacker can abuse this feature and or modify environment variables to run arbitrary libraries for code execution and privilege escalation. The only time a library should set RUNPATH is when it is linked to private libraries in the same package. Remove the compiler option --enable-new-dtags,-rpath to remove RUNPATH.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
588	arm64-v8a/libstarship_wrapper.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
589	arm64-v8a/libvolcenginertc.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk', '__strlen_chk', '__memset_chk', '__vsprintf_chk', '__vsnprintf_chk', '__memmove_chk', '__FD_SET_chk', '__strcpy_chk', '__strchr_chk', '__strcat_chk', '__read_chk', '__FD_CLR_chk', '__FD_ISSET_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
590	arm64-v8a/libByteAIDT.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
591	arm64-v8a/libjato.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', '__read_chk', '__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
592	arm64-v8a/libbytevc1enc.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strcpy_chk', '__strchr_chk', '__vsnprintf_chk', '__strlen_chk', '__memcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
593	arm64-v8a/libbytennllm-jni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk', '__vsprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
594	arm64-v8a/libmonitorcollector-lib.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memmove_chk', '__strncpy_chk', '__memset_chk', '__memcpy_chk', '__read_chk', '__vsprintf_chk', '__strcpy_chk', '__vsnprintf_chk', '__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
595	arm64-v8a/lib_jhmp.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
596	arm64-v8a/libkryptonaudio.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
597	arm64-v8a/libgeckox_bspatch.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', '__strlen_chk', '__read_chk', '__strcat_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
598	arm64-v8a/liborbuculum.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', '__strncat_chk', '__vsnprintf_chk', '__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
599	arm64-v8a/libyoga.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', '__strlen_chk', '__memmove_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
600	arm64-v8a/libnpth_unw.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
601	arm64-v8a/libNLEEditorjni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', '__strlen_chk', '__strncpy_chk', '__memcpy_chk', '__memmove_chk', '__memset_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
602	arm64-v8a/libttvesdk_plugin.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk', '__memset_chk', '__vsnprintf_chk', '__strlen_chk', '__memmove_chk', '__strchr_chk', '__strchr_chk', '__read_chk', '__vsprintf_chk', '__strcpy_chk', '__strncpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
603	arm64-v8a/libfile_lock.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
604	arm64-v8a/libgodzilla-mem sponge.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
605	arm64-v8a/libfdk-aac.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
606	arm64-v8a/libjarvis-trace.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['_vsprintf_chk', '_strchr_chk', '_strrchr_chk', '_memcpy_chk', '_vsnprintf_chk', '_read_chk', '_strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
607	arm64-v8a/lib_jbmf.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
608	arm64-v8a/libanimax_bytevc1.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
609	arm64-v8a/libminizip.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memmove_chk', '__vsprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
610	arm64-v8a/libCutSamejni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memmove_chk', '__strlen_chk', '__memset_chk', '__strcpy_chk', '__vsnprintf_chk', '__memcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
611	arm64-v8a/libEncryptor.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
612	arm64-v8a/libwatson.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
613	arm64-v8a/libotis_attrib.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk', '__strcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
614	arm64-v8a/liblynxbase.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', '__memcpy_chk', '__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
615	arm64-v8a/libwcd.db.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memmove_chk', '__strncpy_chk', '__memset_chk', '__memcpy_chk', '__vsnprintf_chk', '__strncpy_chk', '__read_chk', '__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
616	arm64-v8a/libttdemux.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
617	arm64-v8a/libNLETemplateModelJni_plugin.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk', '__strncpy_chk', '__memcpy_chk', '__memmove_chk', '__memset_chk', '__vsnprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
618	arm64-v8a/libpipo-security-sdk.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
619	arm64-v8a/libCepFast.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
620	arm64-v8a/libanrrelief.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', '__strlen_chk', '__memmove_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
621	arm64-v8a/libDavinciResourceJni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memmove_chk', '__strncpy_chk', '__memset_chk', '__strlen_chk', '__strcpy_chk', '__memcpy_chk', '__vsprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
622	arm64-v8a/libfileprotect.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
623	arm64-v8a/libnpth_repair.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
624	arm64-v8a/libkrypton_sar.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strcat_chk', '__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
625	arm64-v8a/libbmf_hydra_lite.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
626	arm64-v8a/libquick.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', '__strlen_chk', '__vsnprintf_chk', '__strchr_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
627	arm64-v8a/libfastcv.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['_vsnprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
628	arm64-v8a/libBlinkCard.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
629	arm64-v8a/libbdzstd.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
630	arm64-v8a/libbytelink.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['_vsnprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
631	arm64-v8a/libforestm_native_buffer.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__read_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
632	arm64-v8a/libttmverifylite.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
633	arm64-v8a/libbmf_mods.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
634	arm64-v8a/libresource_monitor.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['_vsprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
635	arm64-v8a/libkryptoneffect.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
636	arm64-v8a/libptyjemalloc.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
637	arm64-v8a/libtffmjpeg.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
638	arm64-v8a/libanimax_textra.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
639	arm64-v8a/liblynxtrace.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
640	arm64-v8a/libpythonA.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', '__memmove_chk', '__memcpy_chk', '__strcpy_chk', '__read_chk', '__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
641	arm64-v8a/libgifimage.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
642	arm64-v8a/libsysoptimizer.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memmove_chk', '__strrchr_chk', '__memset_chk', '__memcpy_chk', '__vsprintf_chk', '__strchr_chk', '__strcpy_chk', '__vsnprintf_chk', '__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
643	arm64-v8a/libtailor.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memmove_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
644	arm64-v8a/libkryptonaurum.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
645	arm64-v8a/libbdmpg123.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__read_chk', '__strncpy_chk', '__FD_SET_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
646	arm64-v8a/libbd-install.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memmove_chk', '__memset_chk', '__memcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
647	arm64-v8a/libNLEMediaJni_plugin.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk', '__memmove_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
648	arm64-v8a/libiesapplogger.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
649	arm64-v8a/libpsp_engine.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
650	arm64-v8a/libdelta.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
651	arm64-v8a/libNLEditorJni_plugin.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', '__strlen_chk', '__strncpy_chk', '__memcpy_chk', '__memmove_chk', '__memset_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
652	arm64-v8a/libclient_ai_impl_jni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
653	arm64-v8a/libnpth_fp_unw.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
654	arm64-v8a/libkeva.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
655	arm64-v8a/libflipped.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
656	arm64-v8a/libbat.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', '__vsnprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
657	arm64-v8a/libAwplatsupport.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
658	arm64-v8a/libttmplayer.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strcpy_chk', '__strchr_chk', '__strlen_chk', '__strcpy_chk', '__vsprintf_chk', '__vsnprintf_chk', '__strncpy_chk', '__memcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
659	arm64-v8a/libBDPythonVM.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
660	arm64-v8a/libgaia_lib.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memmove_chk', '__read_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
661	arm64-v8a/libsliver.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memmove_chk', '__memset_chk', '__memcpy_chk', '__strcpy_chk', '__vsprintf_chk', '__strchr_chk', '__strncpy_chk', '__read_chk', '__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
662	arm64-v8a/libTTMStrategyCenter.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
663	arm64-v8a/libbytennllm.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk', '__vsprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
664	arm64-v8a/liblynx_v8_bridge.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
665	arm64-v8a/libnativeaudio.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', '__read_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
666	arm64-v8a/libskity.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
667	arm64-v8a/libropaencrypt.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
668	arm64-v8a/libstorage-hook.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
669	arm64-v8a/libjson_opt.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
670	arm64-v8a/libavmdlp2pv2.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strchr_chk', ['__strlen_chk', ['__vsprintf_chk', ['__vsnprintf_chk', ['__read_chk', ['__memcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
671	arm64-v8a/libskbase.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', '__strncpy_chk', '__memcpy_chk', '__strcpy_chk', '__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
672	arm64-v8a/libbdsword.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
673	arm64-v8a/libttpreload.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk', '__vsprintf_chk', '__vsnprintf_chk', '__strncpy_chk', '__read_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
674	arm64-v8a/libarc4_sdk_jni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
675	arm64-v8a/libttheif_dec.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
676	arm64-v8a/libfast_engine_api_loader.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
677	arm64-v8a/libalog.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,nov to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memset_chk', '__strncpy_chk', '__strcpy_chk', '__vsprintf_chk', '__strlen_chk', '__memcpy_chk', '__read_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
678	arm64-v8a/libavmdlbase.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk', '__read_chk', '__vsprintf_chk', '__memcpy_chk', '__vsnprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
679	arm64-v8a/libEffectEditorJni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memmove_chk', '__strncpy_chk', '__memset_chk', '__memcpy_chk', '__strlen_chk', '__vsprintf_chk', '__strchr_chk', '__vsnprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
680	arm64-v8a/libhelios_bm.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
681	arm64-v8a/libnpth_bt.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
682	arm64-v8a/libttext_lite.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk', '__memcpy_chk', '__vsprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
683	arm64-v8a/libqmiVsyncHook.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
684	arm64-v8a/libttmcmf.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
685	arm64-v8a/libNLEResourcesDAVJni_plugin.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk', '__strncpy_chk', '__memcpy_chk', '__memmove_chk', '__memset_chk', '__vsnprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
686	arm64-v8a/libAGFX.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memmove_chk', '__memset_chk', '__strcpy_chk', '__vsprintf_chk', '__strchr_chk', '__memcpy_chk', '__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
687	arm64-v8a/libnpth_unwind.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
688	arm64-v8a/libandroidx.graphics.path.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
689	arm64-v8a/liblynx_service_api.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
690	arm64-v8a/libbytehook.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__read_chk', '__vsprintf_chk', '__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
691	arm64-v8a/libbmf_module_sdk.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', '__vsnprintf_chk', '__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
692	arm64- v8a/libpns_ttmachine_adapter.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memmove_chk', '__memset_chk', '__memcpy_chk', '__strcpy_chk', '__strlen_chk', '__vsprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
693	arm64-v8a/libtisopt.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
694	arm64-v8a/libpunch.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
695	arm64-v8a/libvegasdk.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memmove_chk', '__memset_chk', '__memcpy_chk', '__vsnprintf_chk', '__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
696	arm64-v8a/libbmf_hydra.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memmove_chk', '__memcpy_chk', '__strcpy_chk', '__vsprintf_chk', '__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
697	arm64-v8a/liblynx.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk', '__strlen_chk', '__vsnprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
698	arm64-v8a/libanimax.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk', '__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
699	arm64-v8a/libpreload.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
700	arm64-v8a/libimagepipeline.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
701	arm64-v8a/libPitayaBdComponent.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', '__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
702	arm64-v8a/librex.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
703	arm64-v8a/libAndroidPitayaCore.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memmove_chk', '__memset_chk', '__strlen_chk', '__strcpy_chk', '__read_chk', '__memcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
704	arm64-v8a/libbdheif.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
705	arm64-v8a/libbytevc1enc10b.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memmove_chk', '__strchr_chk', '__memcpy_chk', '__strcpy_chk', '__vsnprintf_chk', '__read_chk', '__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
706	arm64-v8a/liblynx_text_service.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
707	arm64-v8a/libSmartMoviejni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memmove_chk', '__strncpy_chk', '__strlen_chk', '__strcpy_chk', '__memset_chk', '__vsprintf_chk', '__vsnprintf_chk', '__memcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
708	arm64-v8a/libNLEMediaRemoteJni_plugin.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memset_chk', '__memcpy_chk', '__strlen_chk', '__strncpy_chk', '__memmove_chk', '__vsnprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
709	arm64-v8a/libnpth_logcat.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Position Independent Executable (PIE) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strncpy_chk', '__strlen_chk', '__strchr_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
710	arm64-v8a/libnpth_xasan.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strchr_chk', '__vsprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
711	arm64-v8a/libc++_shared.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', '__strlen_chk', '__memmove_chk', '__read_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
712	arm64-v8a/libzoin.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__read_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
713	arm64-v8a/libalignpage.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk', '__strcpy_chk', '__vsnprintf_chk', '__strlen_chk', '__vsprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
714	arm64-v8a/libh3-java.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
715	arm64-v8a/libnapi.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
716	arm64-v8a/libkrypton.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk', '__memset_chk', '__vsprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
717	arm64-v8a/libnpth_ref_monitor.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', ['__memcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
718	arm64-v8a/libByteVC1_dec.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
719	arm64-v8a/libbytevc1enc8bwrapper.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['_vsnprintf_chk', '_memcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
720	arm64-v8a/libCepAuth.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
721	arm64-v8a/libvctfo.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
722	arm64-v8a/libcybertron_base.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
723	arm64-v8a/libp2plivevdp.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
724	arm64-v8a/libffmpeg_dashdec.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strchr_chk', '__vsprintf_chk', '__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
725	arm64-v8a/libwasm.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', '__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
726	arm64-v8a/libbyteMonitor.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memmove_chk', '__memset_chk', '__memcpy_chk', '__strcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
727	arm64-v8a/libserval_svg.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strchr_chk', '__memcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
728	arm64-v8a/libartlog_monitor.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
729	arm64-v8a/libvolcenginertc_plugin.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk', '__strlen_chk', '__memset_chk', '__vsprintf_chk', '__vsnprintf_chk', '__memmove_chk', '__FD_SET_chk', '__strcpy_chk', '__strchr_chk', '__strcat_chk', '__read_chk', '__FD_CLR_chk', '__FD_ISSET_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
730	arm64-v8a/libCepEngine.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
731	arm64-v8a/libttminisnative.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk', '__memmove_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
732	arm64-v8a/libttquic.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk', '__read_chk', '__vsprintf_chk', '__memcpy_chk', '__vsnprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
733	arm64-v8a/libspeechspg.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memmove_chk', '__strlen_chk', '__vsprintf_chk', '__memcpy_chk', '__memset_chk', '__vsnprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
734	arm64-v8a/libnpth_dl.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__read_chk', '__vsprintf_chk', '__strchr_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
735	arm64-v8a/libbytedt.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
736	arm64-v8a/libfast_engine.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strchr_chk', '__memcpy_chk', '__vsprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
737	arm64- v8a/libvebytevc1enc10bwrapper.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', '__memcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
738	arm64-v8a/libbytevc0.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['_strchr_chk', ['_memset_chk', ['_memcpy_chk', ['_strcpy_chk', ['_vsnprintf_chk', ['_strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
739	arm64-v8a/libhmp.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
740	arm64-v8a/libpns_crypto.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
741	arm64-v8a/libPitayaTTPPolicy.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
742	arm64-v8a/libopus.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
743	arm64-v8a/libTTMachineCore.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', '__strcpy_chk', '__vsnprintf_chk', '__strcat_chk', '__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
744	arm64-v8a/libNLEMediaRemoteJni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memset_chk', ['__memcpy_chk', ['__strlen_chk', ['__strncpy_chk', ['__memmove_chk', ['__vsnprintf_chk']]	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
745	arm64-v8a/libvcbasekit.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk', '__vsprintf_chk', '__strcat_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
746	arm64-v8a/libug_share_sort.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', '__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
747	arm64-v8a/libBDMicroPythonVM.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
748	arm64-v8a/liblivestrategy.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', '__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
749	arm64-v8a/libspeechepeg.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
750	arm64-v8a/libbdvideouploader.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,nov to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strchr_chk', '__memmove_chk', '__memset_chk', '__strrchr_chk', '__strlen_chk', '__strcpy_chk', '__vsprintf_chk', '__vsnprintf_chk', '__strncat_chk', '__strcat_chk', '__read_chk', '__memcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
751	arm64-v8a/librtmglobal.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memset_chk', '__memcpy_chk', '__memmove_chk', '__strlen_chk', '__vsprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
752	arm64-v8a/libbuffer.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__read_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
753	arm64-v8a/libfast_engine_api.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
754	arm64-v8a/libworkerv8.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
755	arm64-v8a/libeffect_plugin.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memmove_chk', '__memcpy_chk', '__strlen_chk', '__strcpy_chk', '__memset_chk', '__vsnprintf_chk', '__strncpy_chk', '__strcat_chk', '__strchr_chk', '__vsprintf_chk', '__read_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
756	arm64-v8a/libbytennwrapper.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
757	arm64-v8a/libicu.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
758	arm64-v8a/libnative-filters.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
759	arm64-v8a/libpsiencript.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk', '__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
760	arm64-v8a/liblynx_markdown.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk', '__strlen_chk', '__strchr_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
761	arm64-v8a/libjnidispatch.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
762	arm64-v8a/libtccrypto.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memset_chk', '__memcpy_chk', '__read_chk', '__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
763	arm64-v8a/libspeechengine.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
764	arm64-v8a/libxtrace.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
765	arm64-v8a/libpy-numpy.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memmove_chk', '__memset_chk', '__memcpy_chk', '__vsnprintf_chk', '__read_chk', '__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
766	arm64-v8a/liboecsec_ov.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strncpy_chk', ['__strchr_chk', ['__strrchr_chk', ['__read_chk', ['__memset_chk', ['__vsprintf_chk', ['__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
767	arm64-v8a/libvoip.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', '__memset_chk', '__memcpy_chk', '__vsnprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
768	arm64-v8a/liburiparser.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
769	arm64-v8a/libmemrelief.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk', '__memset_chk', '__vsnprintf_chk', '__strlen_chk', '__memmove_chk', '__vsprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
770	arm64-v8a/libCepAST.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
771	arm64-v8a/libEffectEditorABTestjni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memmove_chk', '__strncpy_chk', '__memset_chk', '__memcpy_chk', '__strlen_chk', '__vsprintf_chk', '__strchr_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
772	arm64-v8a/libNLEResourcesDAVjni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk', '__strncpy_chk', '__memcpy_chk', '__memmove_chk', '__memset_chk', '__vsnprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
773	arm64-v8a/libNLEMediaPublicjni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk', ['__strncpy_chk', ['__memmove_chk', ['__memcpy_chk', ['__memset_chk', ['__vsnprintf_chk', ['__strrchr_chk', ['__read_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
774	arm64-v8a/libbtch_collection.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memmove_chk', '__memset_chk', '__strlen_chk', '__memcpy_chk', '__strcpy_chk', '__vsprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
775	arm64-v8a/libaudio_fingerprint_sdk.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
776	arm64-v8a/libart_sym.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
777	arm64-v8a/libnpth_fd_tracker.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', '__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
778	arm64-v8a/libkomprese-decompressor.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
779	arm64-v8a/libmmt.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memset_chk', '__memcpy_chk', '__vsprintf_chk', '__strchr_chk', '__strncpy_chk', '__read_chk', '__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
780	arm64-v8a/libapplog_rust.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
781	arm64-v8a/libwhisper.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
782	arm64-v8a/libnpth.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strcat_chk', '__vsprintf_chk', '__strncpy_chk', '__strlen_chk', '__strcpy_chk', '__read_chk', '__strchr_chk', '__strrchr_chk', '__vsprintf_chk', '__memmove_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
783	arm64-v8a/libprofiler.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
784	arm64-v8a/libanimax_napi.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
785	arm64-v8a/libyuv.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
786	arm64-v8a/libbach-sdk-jni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
787	arm64-v8a/libmetasec_ov.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', '__vsnprintf_chk', '__read_chk', '__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
788	arm64-v8a/libanrthanos.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strchr_chk', '__strncpy_chk', '__memcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
789	arm64-v8a/libAwebviewbytedance.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: <pre>['__memcpy_chk', '__memset_chk', '__strlen_chk', '__read_chk', '__write_chk', '__strchr_chk', '__vsprintf_chk', '__memchr_chk', '__fwrite_chk', '__pread64_chk', '__pread_chk', '__pwrite64_chk', '__strncat_chk', '__sendto_chk', '__readlink_chk', '__FD_SET_chk', '__FD_ISSET_chk', '__FD_CLR_chk']</pre>	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
790	arm64-v8a/libnewep.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
791	arm64-v8a/libNLETemplateModelJni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk', '__strncpy_chk', '__memcpy_chk', '__memmove_chk', '__memset_chk', '__vsnprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
792	arm64-v8a/libNLEMediaPublicjni_plugin.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk', '__strncpy_chk', '__memmove_chk', '__memcpy_chk', '__memset_chk', '__strchr_chk', '__vsprintf_chk', '__read_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
793	arm64-v8a/libvcnverifylite.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strchr_chk', '__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
794	arm64-v8a/libNLEMediajni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk', '__memmove_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
795	arm64-v8a/libflock-lib.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
796	arm64-v8a/libnapi_v8.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
797	arm64-v8a/libbvcparser.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
798	arm64-v8a/libjarvis-metrics.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
799	arm64-v8a/libcrashpad_handler_trampoline.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Position Independent Executable (PIE) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
800	arm64-v8a/libkryptonremote.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
801	arm64-v8a/libgodzilla-sysopt.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
802	arm64-v8a/libTTNativeML.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
803	armeabi-v7a/libbyteVC2dec.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
804	armeabi-v7a/libreschecker.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', '__strchr_chk', '__strlen_chk', '__memcpy_chk', '__memmove_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
805	armeabi-v7a/libtt_ugen_layout.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['_vsnprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
806	armeabi-v7a/liborbuculumadapter.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strcpy_chk', '__vsprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
807	armeabi-v7a/liblens.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk', '__vsprintf_chk', '__memmove_chk', '__memset_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
808	armeabi-v7a/libavocadoguard.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', '__vsnprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
809	armeabi-v7a/libbase_live.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strchr_chk', '__vsprintf_chk', '__strlen_chk', '__read_chk', '__memcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
810	armeabi-v7a/libbdhm_native.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	\$ORIGIN/../../../../usr/local/rustup/toolchains/1.70.0-x86_64-unknown-linux-gnu/lib/rustlib/armv7-linux-androideabi/lib high The binary has RUNPATH set. In certain cases, an attacker can abuse this feature and or modify environment variables to run arbitrary libraries for code execution and privilege escalation. The only time a library should set RUNPATH is when it is linked to private libraries in the same package. Remove the compiler option --enable-new-dtags,-rpath to remove RUNPATH.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
811	armeabi-v7a/libcverify.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
812	armeabi-v7a/libpumbaa-network.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
813	armeabi-v7a/libstarship_sdk.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', '__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
814	armeabi-v7a/libv8_libfull.cr.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', '__strlen_chk', '__strchr_chk', '__memcpy_chk', '__memmove_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
815	armeabi-v7a/libttmverify.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
816	armeabi-v7a/libvcn.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
817	armeabi-v7a/libfly-main-color-lib.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
818	armeabi-v7a/libshadowhook_nothing.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
819	armeabi-v7a/libarccore_sdk_c.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
820	armeabi-v7a/libByteAINN.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memmove_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
821	armeabi-v7a/libbytebench.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', '__read_chk', '__vsprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
822	armeabi-v7a/libCepProxy.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
823	armeabi-v7a/libconfigcenter.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
824	armeabi-v7a/libartshadowhook.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
825	armeabi-v7a/libjazz.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
826	armeabi-v7a/libnpth_tls_monitor.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
827	armeabi-v7a/libonetex.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
828	armeabi-v7a/libtt_c2pa_sdk_d.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	\$ORIGIN/../../../../usr/local/rustup/toolchains/1.77.1-x86_64-unknown-linux-gnu/lib/rustlib/armv7-linux-androideabi/lib high The binary has RUNPATH set. In certain cases, an attacker can abuse this feature and or modify environment variables to run arbitrary libraries for code execution and privilege escalation. The only time a library should set RUNPATH is when it is linked to private libraries in the same package. Remove the compiler option --enable-new-dtags,-rpath to remove RUNPATH.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
829	armeabi-v7a/libEffectCreatorJni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: <pre>['__memcpy_chk', '__memmove_chk', '__memset_chk', '__vsnprintf_chk', '__strlen_chk', '__strchr_chk', '__strncpy_chk', '__vsprintf_chk']</pre>	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
830	armeabi-v7a/libvideodec.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
831	armeabi-v7a/libnpth_dumper.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Position Independent Executable (PIE) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__read_chk', '__vsprintf_chk', '__memset_chk', '__memcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
832	armeabi-v7a/liblynxstarlight.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
833	armeabi-v7a/libmotion.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
834	armeabi-v7a/libpy-cv-numpycv.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
835	armeabi-v7a/libtbboringssl.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
836	armeabi-v7a/libnetecho.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
837	armeabi-v7a/libjazz_plugin.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
838	armeabi-v7a/libsimba.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
839	armeabi-v7a/libArchive.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__read_chk', '__strlen_chk', '__umask_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
840	armeabi-v7a/libres_memory.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
841	armeabi-v7a/libaudioeffect.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk', '__memmove_chk', '__strchr_chk', '__strlen_chk', '__vsnprintf_chk', '__vsprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
842	armeabi-v7a/libsscronet.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', '__read_chk', '__memcpy_chk', '__FD_ISSET_chk', '__FD_SET_chk', '__FD_CLR_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
843	armeabi-v7a/libstatic-webp.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
844	armeabi-v7a/libttr.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk', '__vsprintf_chk', '__strchr_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
845	armeabi-v7a/libspeechsdk.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memmove_chk', '__memcpy_chk', '__vsnprintf_chk', '__memset_chk', '__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
846	armeabi-v7a/liblynxsecurity.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
847	armeabi-v7a/liblynx_krypton.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
848	armeabi-v7a/libshadowhook.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
849	armeabi-v7a/libtexturerender_native.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
850	armeabi-v7a/libtt_c2pa_sdk.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
851	armeabi-v7a/libILAMaterialSDK.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk', '__vsprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
852	armeabi-v7a/libworker.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
853	armeabi-v7a/libxreword.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__read_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
854	armeabi-v7a/libbytenn.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
855	armeabi-v7a/liblink_mic_sdk.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	\$ORIGIN/../../../../usr/local/rustup/toolchains/1.70.0-x86_64-unknown-linux-gnu/lib/rustlib/armv7-linux-androideabi/lib high The binary has RUNPATH set. In certain cases, an attacker can abuse this feature and or modify environment variables to run arbitrary libraries for code execution and privilege escalation. The only time a library should set RUNPATH is when it is linked to private libraries in the same package. Remove the compiler option --enable-new-dtags,-rpath to remove RUNPATH.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
856	armeabi-v7a/libstarship_wrapper.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
857	armeabi-v7a/libvolcenginertc.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk', '__strlen_chk', '__memset_chk', '__vsprintf_chk', '__vsnprintf_chk', '__memmove_chk', '__strcpy_chk', '__strchr_chk', '__strcat_chk', '__fgets_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
858	armeabi-v7a/libByteAIDT.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
859	armeabi-v7a/libjato.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk', '__read_chk', '__vsprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
860	armeabi-v7a/libbytevc1enc.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strcpy_chk', '__strchr_chk', '__vsnprintf_chk', '__strlen_chk', '__memcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
861	armeabi-v7a/libbytennllm-jni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk', '__vsprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
862	armeabi-v7a/libmonitorcollector-lib.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
863	armeabi-v7a/lib_jhmp.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
864	armeabi-v7a/libkryptonaudio.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
865	armeabi-v7a/libgeckox_bspatch.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strcat_chk', '__strlen_chk', '__read_chk', '__vsprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
866	armeabi-v7a/liborbuculum.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strncat_chk', '__strlen_chk', '__vsprintf_chk', '__vsnprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
867	armeabi-v7a/libyoga.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
868	armeabi-v7a/libnpth_unw.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
869	armeabi-v7a/libNLEditorJni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', '__strlen_chk', '__memcpy_chk', '__memmove_chk', '__memset_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
870	armeabi-v7a/libttvesdk_plugin.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: <pre>['__memcpy_chk', '__memset_chk', '__vsnprintf_chk', '__strlen_chk', '__memmove_chk', '__strchr_chk', '__strchr_chk', '__vsprintf_chk', '__strcpy_chk']</pre>	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
871	armeabi-v7a/libfile_lock.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
872	armeabi-v7a/libgodzilla-mem sponge.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
873	armeabi-v7a/libfdk-aac.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
874	armeabi-v7a/lib_jbmf.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
875	armeabi-v7a/libanimax_bytevc1.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
876	armeabi-v7a/libminizip.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', '__memmove_chk', '__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
877	armeabi-v7a/libCutSamejni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
878	armeabi-v7a/libEncryptor.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
879	armeabi-v7a/libwatson.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
880	armeabi-v7a/libotis_attrib.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk', '__strcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
881	armeabi-v7a/liblynxbase.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', '__memcpy_chk', '__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
882	armeabi-v7a/libwcd.db.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
883	armeabi-v7a/libttdemux.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
884	armeabi-v7a/libNLETemplateModelJni_plugin.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk', '__memcpy_chk', '__memmove_chk', '__memset_chk', '__vsprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
885	armeabi-v7a/libpipo-security-sdk.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
886	armeabi-v7a/libCepFast.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
887	armeabi-v7a/libanrrelief.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
888	armeabi-v7a/libDavinciResourceJni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
889	armeabi-v7a/libfileprotect.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
890	armeabi-v7a/libnpth_repair.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
891	armeabi-v7a/libkrypton_sar.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strcat_chk', '__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
892	armeabi-v7a/libbmf_hydra_lite.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
893	armeabi-v7a/libquick.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
894	armeabi-v7a/libfastcv.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', '__vsnprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
895	armeabi-v7a/libBlinkCard.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
896	armeabi-v7a/libbdzstd.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
897	armeabi-v7a/libbytelink.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
898	armeabi- v7a/libforestx_native_buffer.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__read_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
899	armeabi-v7a/libttmverifylite.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
900	armeabi-v7a/libbmf_mods.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
901	armeabi-v7a/libresource_monitor.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['_vsprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
902	armeabi-v7a/libkryptoneffect.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
903	armeabi-v7a/libptyjemalloc.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
904	armeabi-v7a/libtftfmpeg.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
905	armeabi-v7a/libanimax_textra.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
906	armeabi-v7a/liblynxtrace.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
907	armeabi-v7a/libpythonA.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
908	armeabi-v7a/libgifimage.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
909	armeabi-v7a/libsysoptimizer.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk', '__strcpy_chk', '__vsprintf_chk', '__strchr_chk', '__vsnprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
910	armeabi-v7a/libtailor.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
911	armeabi-v7a/libkryptonaurem.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
912	armeabi-v7a/libbdmpg123.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
913	armeabi-v7a/libbd-install.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
914	armeabi-v7a/libNLEMediaJni_plugin.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
915	armeabi-v7a/libiesapplogger.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
916	armeabi-v7a/libpsp_engine.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
917	armeabi-v7a/libdelta.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
918	armeabi-v7a/libNLEditorJni_plugin.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', '__strlen_chk', '__memcpy_chk', '__memmove_chk', '__memset_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
919	armeabi-v7a/libclient_ai_impl_jni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
920	armeabi-v7a/libkeva.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
921	armeabi-v7a/libflipped.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
922	armeabi-v7a/libbat.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
923	armeabi-v7a/libAwplatsupport.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
924	armeabi-v7a/libttmplayer.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk', '__vsprintf_chk', '__memcpy_chk', '__strchr_chk', '__strcpy_chk', '__vsprintf_chk', '__strcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
925	armeabi-v7a/libBDPythonVM.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
926	armeabi-v7a/libgaia_lib.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
927	armeabi-v7a/libsliver.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
928	armeabi-v7a/libTTMStrategyCenter.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
929	armeabi-v7a/libbytennllm.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
930	armeabi-v7a/liblynx_v8_bridge.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
931	armeabi-v7a/libnativeaudio.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__read_chk', '__vsprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
932	armeabi-v7a/libskity.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
933	armeabi-v7a/libropaencrypt.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
934	armeabi-v7a/libstorage-hook.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
935	armeabi-v7a/libjson_opt.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
936	armeabi-v7a/libavmdlp2pv2.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
937	armeabi-v7a/libskbase.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', '__strlen_chk', '__memcpy_chk', '__strcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
938	armeabi-v7a/libbdsword.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
939	armeabi-v7a/libtppreload.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__read_chk', '__vsprintf_chk', '__vsprintf_chk', '__strlen_chk', '__strcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
940	armeabi-v7a/libarc4core_sdk_jni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
941	armeabi-v7a/libttheif_dec.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
942	armeabi-v7a/libfast_engine_api_loader.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
943	armeabi-v7a/libalog.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
944	armeabi-v7a/libavmdlbase.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk', '__read_chk', '__vsprintf_chk', '__memcpy_chk', '__vsnprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
945	armeabi-v7a/libEffectEditorJni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strchr_chk', '__vsprintf_chk', '__strlen_chk', '__strncpy_chk', '__memcpy_chk', '__memmove_chk', '__memset_chk', '__vsnprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
946	armeabi-v7a/libhelios_bm.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
947	armeabi-v7a/libnpth_bt.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
948	armeabi-v7a/libttext_lite.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
949	armeabi-v7a/libqmiVsyncHook.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
950	armeabi-v7a/libttmcmaf.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
951	armeabi-v7a/libNLEResourcesDAVJni_plugin.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk', '__memcpy_chk', '__memmove_chk', '__memset_chk', '__vsnprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
952	armeabi-v7a/libAGFX.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
953	armeabi-v7a/libnpth_unwind.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
954	armeabi-v7a/libandroidx.graphics.path.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
955	armeabi-v7a/liblynx_service_api.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
956	armeabi-v7a/libbytehook.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
957	armeabi-v7a/libbmf_module_sdk.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
958	armeabi-v7a/libpns_ttmachine_adapter.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk', '__strcpy_chk', '__vsprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
959	armeabi-v7a/libotisoapt.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
960	armeabi-v7a/libpunch.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
961	armeabi-v7a/libvegasdk.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk', '__vsprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
962	armeabi-v7a/libbmf_hydra.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strcpy_chk', '__vsprintf_chk', '__memcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
963	armeabi-v7a/liblynx.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk', '__strlen_chk', '__vsprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
964	armeabi-v7a/libanimax.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk', '__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
965	armeabi-v7a/libpreload.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
966	armeabi-v7a/libimagepipeline.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
967	armeabi-v7a/libPitayaBdComponent.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', '__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
968	armeabi-v7a/librex.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
969	armeabi-v7a/libAndroidPitayaCore.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk', '__read_chk', '__memset_chk', '__memmove_chk', '__memcpy_chk', '__strcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
970	armeabi-v7a/libbdheif.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
971	armeabi-v7a/libbytevc1enc10b.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
972	armeabi-v7a/liblynx_text_service.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
973	armeabi-v7a/libSmartMovieJni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['_vsprintf_chk', '__strlen_chk', '__strcpy_chk', '__memcpy_chk', '__memmove_chk', '__memset_chk', '__vsnprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
974	armeabi-v7a/libNLEMediaRemoteJni_plugin.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memset_chk', '__memcpy_chk', '__strlen_chk', '__memmove_chk', '__vsnprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
975	armeabi-v7a/libnpth_logcat.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Position Independent Executable (PIE) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strncpy_chk', '__strlen_chk', '__strchr_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
976	armeabi-v7a/libnpth_xasan.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
977	armeabi-v7a/libc++_shared.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
978	armeabi-v7a/libzoin.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
979	armeabi-v7a/libalignpage.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk', '__vsprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
980	armeabi-v7a/libh3-java.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['_vsprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
981	armeabi-v7a/libnapi.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
982	armeabi-v7a/libkrypton.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk', '__memset_chk', '__vsnprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
983	armeabi-v7a/libnpth_ref_monitor.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', ['__memcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
984	armeabi-v7a/libByteVC1_dec.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
985	armeabi-v7a/libvebytevc1enc8bwrapper.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', ['__memcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
986	armeabi-v7a/libCepAuth.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
987	armeabi-v7a/libvctfo.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
988	armeabi-v7a/libcybertron_base.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
989	armeabi-v7a/libp2plivevdp.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
990	armeabi-v7a/libffmpeg_dashdec.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
991	armeabi-v7a/libwasm.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
992	armeabi-v7a/libbytemonitor.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
993	armeabi-v7a/libserval_svg.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk', '__strchr_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
994	armeabi-v7a/libartlog_monitor.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
995	armeabi-v7a/libvolcenginertc_plugin.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk', '__strlen_chk', '__memset_chk', '__vsprintf_chk', '__vsnprintf_chk', '__memmove_chk', '__strcpy_chk', '__strchr_chk', '__strcat_chk', '__fgets_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
996	armeabi-v7a/libCepEngine.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
997	armeabi-v7a/libttminisnative.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
998	armeabi-v7a/libttquic.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__read_chk', '__vsprintf_chk', '__memcpy_chk', '__vsnprintf_chk', '__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
999	armeabi-v7a/libspeechspg.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memmove_chk', '__memcpy_chk', '__vsnprintf_chk', '__memset_chk', '__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
1000	armeabi-v7a/libnpth_dl.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__read_chk', '__vsprintf_chk', '__strchr_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
1001	armeabi-v7a/libbytedt.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', '__vsnprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
1002	armeabi-v7a/libfast_engine.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
1003	armeabi-v7a/libvebytevc1enc10bwrapper.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk', '__vsprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
1004	armeabi-v7a/libbytevc0.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
1005	armeabi-v7a/libhmp.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
1006	armeabi-v7a/libpns_crypto.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
1007	armeabi-v7a/libPitayaTTPPolicy.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
1008	armeabi-v7a/libopus.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
1009	armeabi-v7a/libTTMachineCore.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk', '__vsprintf_chk', '__strcpy_chk', '__strcat_chk', '__vsnprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
1010	armeabi-v7a/libNLEMediaRemoteJni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memset_chk', '__memcpy_chk', '__strlen_chk', '__memmove_chk', '__vsnprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
1011	armeabi-v7a/libvcbasekit.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
1012	armeabi-v7a/libug_share_sort.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['_vsnprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
1013	armeabi-v7a/libBDMicroPythonVM.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
1014	armeabi-v7a/liblivestrategy.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['_vsnprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
1015	armeabi-v7a/libspeechpeg.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
1016	armeabi-v7a/libbdvideouploader.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strchr_chk', '__strlen_chk', '__memcpy_chk', '__strncat_chk', '__strcpy_chk', '__vsnprintf_chk', '__strcat_chk', '__read_chk', '__vsprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
1017	armeabi-v7a/librtmglobal.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memset_chk', '__memcpy_chk', '__strlen_chk', '__vsprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
1018	armeabi-v7a/libbuffer.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__read_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
1019	armeabi-v7a/libfast_engine_api.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
1020	armeabi-v7a/libworkerv8.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
1021	armeabi-v7a/libeffect_plugin.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memmove_chk', '__memcpy_chk', '__strlen_chk', '__strcpy_chk', '__memset_chk', '__vsnprintf_chk', '__vsprintf_chk', '__strncpy_chk', '__read_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
1022	armeabi-v7a/libbytennwrapper.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
1023	armeabi-v7a/libicu.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
1024	armeabi-v7a/libnative-filters.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
1025	armeabi-v7a/libpsiencript.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
1026	armeabi-v7a/liblynx_markdown.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk', '__strlen_chk', '__strchr_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
1027	armeabi-v7a/libjnidispatch.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
1028	armeabi-v7a/libttcrypto.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
1029	armeabi-v7a/libspeechengine.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
1030	armeabi-v7a/libxtrace.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
1031	armeabi-v7a/libpy-numpy.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
1032	armeabi-v7a/liboecsec_ov.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strchr_chk', '__strrchr_chk', '__memset_chk', '__vsprintf_chk', '__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
1033	armeabi-v7a/libvoip.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
1034	armeabi-v7a/liburiparser.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
1035	armeabi-v7a/libmemrelief.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['_vsprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
1036	armeabi-v7a/libCepAST.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
1037	armeabi-v7a/libEffectEditorABTestJni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strchr_chk', '__vsprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
1038	armeabi-v7a/libNLEResourcesDAVJni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk', '__memcpy_chk', '__memmove_chk', '__memset_chk', '__vsnprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
1039	armeabi-v7a/libNLEMediaPublicjni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk', '__memmove_chk', '__memcpy_chk', '__memset_chk', '__vsnprintf_chk', '__strchr_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
1040	armeabi-v7a/libbtch_collection.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', '__memcpy_chk', '__strcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
1041	armeabi-v7a/libaudio_fingerprint_sdk.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
1042	armeabi-v7a/libart_sym.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
1043	armeabi-v7a/libnpth_fd_tracker.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', '__strlen_chk', '__read_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
1044	armeabi-v7a/libkomprese-decompressor.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
1045	armeabi-v7a/libmmt.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk', '__strchr_chk', '__strncpy_chk', '__vsprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
1046	armeabi-v7a/libapplog_rust.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
1047	armeabi-v7a/libwhisper.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
1048	armeabi-v7a/libnpth.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strcat_chk', '__vsprintf_chk', '__memcpy_chk', '__strncpy_chk', '__strlen_chk', '__strcpy_chk', '__read_chk', '__strchr_chk', '__strrchr_chk', '__vsprintf_chk', '__memmove_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
1049	armeabi-v7a/libprofiler.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
1050	armeabi-v7a/libanimax_napi.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
1051	armeabi-v7a/libyuv.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
1052	armeabi-v7a/libbach-sdk-jni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
1053	armeabi-v7a/libmetasec_ov.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
1054	armeabi-v7a/libanrthanos.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
1055	armeabi-v7a/libAwebviewbytedance.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk', '__memset_chk', '__strlen_chk', '__read_chk', '__write_chk', '__strchr_chk', '__vsprintf_chk', '__memchr_chk', '__fwrite_chk', '__pread64_chk', '__pread_chk', '__pwrite64_chk', '__strncat_chk', '__sendto_chk', '__readlink_chk', '__FD_SET_chk', '__FD_ISSET_chk', '__FD_CLR_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
1056	armeabi-v7a/libnewep.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
1057	armeabi-v7a/libNLETemplateModeljni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk', '__memcpy_chk', '__memmove_chk', '__memset_chk', '__vsnprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
1058	armeabi-v7a/libNLEMediaPublicjni_plugin.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk', '__memmove_chk', '__memcpy_chk', '__memset_chk', '__vsnprintf_chk', '__strchr_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
1059	armeabi-v7a/libcverifylite.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
1060	armeabi-v7a/libNLEMediaJni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
1061	armeabi-v7a/libflock-lib.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
1062	armeabi-v7a/libnapi_v8.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
1063	armeabi-v7a/libbvcparser.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
1064	armeabi-v7a/libjarvis-metrics.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
1065	armeabi-v7a/libcrashpad_handler_trampoline.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Position Independent Executable (PIE) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
1066	armeabi-v7a/libkryptonremote.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
1067	armeabi-v7a/libgodzilla-sysopt.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
1068	armeabi-v7a/libTTNativeML.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NIAP ANALYSIS v1.3

NO	IDENTIFIER	REQUIREMENT	FEATURE	DESCRIPTION
----	------------	-------------	---------	-------------

BEHAVIOUR ANALYSIS

RULE ID	BEHAVIOUR	LABEL	FILES
00013	Read file and put it into a stream	file	X/C150L.java X/C20271614Tz.java
00022	Open a file from given absolute path of the file	file	X/C20810516cC.java
00005	Get absolute path of file and put it to JSON object	file	X/C20810516cC.java

RULE ID	BEHAVIOUR	LABEL	FILES
00001	Initialize bitmap object and compress data (e.g. JPEG) into bitmap object	camera	com/bef/effectsdk/ImgporcUtils.java

🚫: ABUSED PERMISSIONS

TYPE	MATCHES	PERMISSIONS
Malware Permissions	14/25	android.permission.ACCESS_COARSE_LOCATION, android.permission.ACCESS_FINE_LOCATION, android.permission.SYSTEM_ALERT_WINDOW, android.permission.WRITE_EXTERNAL_STORAGE, android.permission.READ_EXTERNAL_STORAGE, android.permission.INTERNET, android.permission.ACCESS_NETWORK_STATE, android.permission.ACCESS_WIFI_STATE, android.permission.CAMERA, android.permission.RECORD_AUDIO, android.permission.WAKE_LOCK, android.permission.READ_CONTACTS, android.permission.VIBRATE, android.permission.SET_WALLPAPER
Other Common Permissions	8/44	android.permission.CHANGE_WIFI_STATE, com.google.android.gms.permission.AD_ID, android.permission.BLUETOOTH, android.permission.FOREGROUND_SERVICE, android.permission.CHANGE_NETWORK_STATE, android.permission.MODIFY_AUDIO_SETTINGS, com.google.android.c2dm.permission.RECEIVE, com.google.android.finsky.permission.BIND_GET_INSTALL_REFERRER_SERVICE

Malware Permissions:

Top permissions that are widely abused by known malware.

Other Common Permissions:

Permissions that are commonly abused by known malware.

! OFAC SANCTIONED COUNTRIES

This app may communicate with the following OFAC sanctioned list of countries.

DOMAIN	COUNTRY/REGION
www.slpost.gov.lk	IP: 124.43.176.51 Country: Sri Lanka Region: Western Province City: Colombo
m.sogou.com	IP: 43.153.236.147 Country: China Region: Beijing City: Beijing
cpdc.chinapost.com.cn	IP: 211.156.206.242 Country: China Region: Beijing City: Beijing

DOMAIN	COUNTRY/REGION
www.sogou.com	IP: 43.153.236.147 Country: China Region: Beijing City: Beijing
ex.belpost.by	IP: 212.98.168.66 Country: Belarus Region: Minskaya voblasts' City: Minsk
suggestion.baidu.com	IP: 39.156.68.207 Country: China Region: Beijing City: Beijing
sug.so.360.cn	IP: 36.99.172.202 Country: China Region: Zhejiang City: Hangzhou
www.baidu.com	IP: 103.235.46.115 Country: Hong Kong Region: Hong Kong City: Hong Kong

 DOMAIN MALWARE CHECK

DOMAIN	STATUS	GEOLOCATION
es.search.yahoo.com	ok	IP: 212.82.100.137 Country: Ireland Region: Dublin City: Dublin Latitude: 53.343990 Longitude: -6.267190 View: Google Map
tw.search.yahoo.com	ok	IP: 212.82.100.137 Country: Ireland Region: Dublin City: Dublin Latitude: 53.343990 Longitude: -6.267190 View: Google Map

DOMAIN	STATUS	GEOLOCATION
www.tensorflow.org	ok	IP: 216.58.198.206 Country: United States of America Region: California City: Mountain View Latitude: 37.405991 Longitude: -122.078514 View: Google Map
ns.apple.com	ok	No Geolocation information available.
www.slpost.gov.lk	ok	IP: 124.43.176.51 Country: Sri Lanka Region: Western Province City: Colombo Latitude: 6.931940 Longitude: 79.847778 View: Google Map
m.sogou.com	ok	IP: 43.153.236.147 Country: China Region: Beijing City: Beijing Latitude: 39.907501 Longitude: 116.397232 View: Google Map
www.ctt.pt	ok	IP: 104.18.11.173 Country: United States of America Region: California City: San Francisco Latitude: 37.775700 Longitude: -122.395203 View: Google Map
psc.posta.sk	ok	IP: 62.152.231.250 Country: Slovakia Region: Trnavsky kraj City: Trnava Latitude: 48.377399 Longitude: 17.587231 View: Google Map

DOMAIN	STATUS	GEOLOCATION
hackmd.io	ok	IP: 99.83.179.177 Country: United States of America Region: Washington City: Seattle Latitude: 47.606209 Longitude: -122.332069 View: Google Map
www.evrotrust.com	ok	IP: 35.214.237.62 Country: Netherlands Region: Groningen City: Groningen Latitude: 53.219170 Longitude: 6.566670 View: Google Map
api.music.apple.com	ok	IP: 104.103.64.25 Country: Finland Region: Uusimaa City: Helsinki Latitude: 60.169521 Longitude: 24.935450 View: Google Map
c.docs.google.com	ok	No Geolocation information available.
www.years	ok	No Geolocation information available.
openmp.lvm.org	ok	IP: 54.67.122.174 Country: United States of America Region: California City: San Francisco Latitude: 37.774929 Longitude: -122.419418 View: Google Map
nz.search.yahoo.com	ok	IP: 212.82.100.137 Country: Ireland Region: Dublin City: Dublin Latitude: 53.343990 Longitude: -6.267190 View: Google Map

DOMAIN	STATUS	GEOLOCATION
suggest.search.daum.net	ok	IP: 211.183.211.7 Country: Korea (Republic of) Region: Seoul-teukbyeolsi City: Seoul Latitude: 37.568260 Longitude: 126.977829 View: Google Map
go.imgsmail.ru	ok	IP: 89.221.236.13 Country: Russian Federation Region: Stavropol'skiy kray City: Stavropol' Latitude: 45.042801 Longitude: 41.973400 View: Google Map
m.so.com	ok	IP: 104.192.110.225 Country: United States of America Region: California City: Los Angeles Latitude: 34.052986 Longitude: -118.263687 View: Google Map
i.isnssdk.com	ok	IP: 71.18.222.1 Country: United States of America Region: Massachusetts City: Burlington Latitude: 42.508480 Longitude: -71.201134 View: Google Map
www.color.org	ok	IP: 8.47.69.0 Country: United States of America Region: California City: San Francisco Latitude: 37.775700 Longitude: -122.395203 View: Google Map
www.nigeriapostcodes.com	ok	IP: 172.67.148.202 Country: United States of America Region: California City: San Francisco Latitude: 37.775700 Longitude: -122.395203 View: Google Map

DOMAIN	STATUS	GEOLOCATION
www.posta-romana.ro	ok	IP: 5.254.103.154 Country: Spain Region: Madrid, Comunidad de City: Madrid Latitude: 40.416500 Longitude: -3.702560 View: Google Map
search.lilo.org	ok	IP: 141.95.150.143 Country: Germany Region: Hessen City: Frankfurt am Main Latitude: 50.115520 Longitude: 8.684170 View: Google Map
baltazar.microblink.com	ok	IP: 8.6.112.0 Country: United States of America Region: Texas City: Dallas Latitude: 32.783058 Longitude: -96.806671 View: Google Map
www.manifestations	ok	No Geolocation information available.
www.iec.ch	ok	IP: 3.174.113.89 Country: United States of America Region: Washington City: Seattle Latitude: 47.627499 Longitude: -122.346199 View: Google Map
youtrack.jetbrains.com	ok	IP: 63.33.88.220 Country: Ireland Region: Dublin City: Dublin Latitude: 53.343990 Longitude: -6.267190 View: Google Map

DOMAIN	STATUS	GEOLOCATION
id.search.yahoo.com	ok	IP: 212.82.100.137 Country: Ireland Region: Dublin City: Dublin Latitude: 53.343990 Longitude: -6.267190 View: Google Map
yandex.com	ok	IP: 5.255.255.77 Country: Russian Federation Region: Moskva City: Moscow Latitude: 55.752220 Longitude: 37.615559 View: Google Map
www.israelpost.co.il	ok	IP: 66.22.35.41 Country: United States of America Region: New Jersey City: Mahwah Latitude: 41.075279 Longitude: -74.157295 View: Google Map
support.google.com	ok	IP: 173.194.221.138 Country: United States of America Region: California City: Mountain View Latitude: 37.405991 Longitude: -122.078514 View: Google Map
clients2.google.com	ok	IP: 64.233.161.100 Country: United States of America Region: California City: Mountain View Latitude: 37.405991 Longitude: -122.078514 View: Google Map
rtcp-access-sg.tiktokv.com	ok	IP: 71.18.253.156 Country: United States of America Region: Massachusetts City: Burlington Latitude: 42.508480 Longitude: -71.201134 View: Google Map

DOMAIN	STATUS	GEOLOCATION
search.tiktokv.com	ok	IP: 95.101.133.57 Country: Sweden Region: Stockholms lan City: Stockholm Latitude: 59.332581 Longitude: 18.064899 View: Google Map
postcode.vnpost.vn	ok	IP: 10.1.45.14 Country: - Region: - City: - Latitude: 0.000000 Longitude: 0.000000 View: Google Map
update.googleapis.com	ok	IP: 74.125.205.138 Country: United States of America Region: California City: Mountain View Latitude: 37.405991 Longitude: -122.078514 View: Google Map
search.yahoo.com	ok	IP: 212.82.100.137 Country: Ireland Region: Dublin City: Dublin Latitude: 53.343990 Longitude: -6.267190 View: Google Map
it.search.yahoo.com	ok	IP: 212.82.100.137 Country: Ireland Region: Dublin City: Dublin Latitude: 53.343990 Longitude: -6.267190 View: Google Map
www.hortcut	ok	No Geolocation information available.

DOMAIN	STATUS	GEOLOCATION
github.com	ok	IP: 140.82.121.3 Country: United States of America Region: California City: San Francisco Latitude: 37.775700 Longitude: -122.395203 View: Google Map
doh.quickline.ch	ok	IP: 212.60.61.246 Country: Switzerland Region: Bern City: Biel Latitude: 47.132401 Longitude: 7.244110 View: Google Map
dns.quad9.net	ok	IP: 149.112.112.112 Country: United States of America Region: California City: San Francisco Latitude: 37.796986 Longitude: -122.462738 View: Google Map
www.ecosia.org	ok	IP: 104.18.37.185 Country: United States of America Region: Texas City: Dallas Latitude: 32.783058 Longitude: -96.806671 View: Google Map
cpdc.chinapost.com.cn	ok	IP: 211.156.206.242 Country: China Region: Beijing City: Beijing Latitude: 39.907501 Longitude: 116.397232 View: Google Map
www.post.lu	ok	IP: 78.141.185.153 Country: Luxembourg Region: Luxembourg City: Luxembourg Latitude: 49.611671 Longitude: 6.130000 View: Google Map

DOMAIN	STATUS	GEOLOCATION
tosv-va.tiktok-row.org	ok	IP: 10.105.215.225 Country: - Region: - City: - Latitude: 0.000000 Longitude: 0.000000 View: Google Map
doh.opendns.com	ok	IP: 146.112.41.2 Country: United Kingdom of Great Britain and Northern Ireland Region: England City: London Latitude: 51.508530 Longitude: -0.125740 View: Google Map
oauth.anghami.com	ok	IP: 104.18.12.158 Country: United States of America Region: California City: San Francisco Latitude: 37.775700 Longitude: -122.395203 View: Google Map
schemas.android.com	ok	No Geolocation information available.
suggest.yandex.kz	ok	IP: 213.180.204.63 Country: Russian Federation Region: Moskva City: Moscow Latitude: 55.752220 Longitude: 37.615559 View: Google Map
www.post.lt	ok	IP: 194.33.96.11 Country: Lithuania Region: Vilniaus apskritis City: Vilnius Latitude: 54.689159 Longitude: 25.279800 View: Google Map

DOMAIN	STATUS	GEOLOCATION
tasks.googleapis.com	ok	IP: 173.194.73.95 Country: United States of America Region: California City: Mountain View Latitude: 37.405991 Longitude: -122.078514 View: Google Map
transparencyreport.google.com	ok	IP: 216.58.198.206 Country: United States of America Region: California City: Mountain View Latitude: 37.405991 Longitude: -122.078514 View: Google Map
th.search.yahoo.com	ok	IP: 212.82.100.137 Country: Ireland Region: Dublin City: Dublin Latitude: 53.343990 Longitude: -6.267190 View: Google Map
clientservices.googleapis.com	ok	IP: 142.251.38.78 Country: United States of America Region: California City: Mountain View Latitude: 37.405991 Longitude: -122.078514 View: Google Map
api.you.com	ok	IP: 8.6.112.0 Country: United States of America Region: Texas City: Dallas Latitude: 32.783058 Longitude: -96.806671 View: Google Map
postalcodes.elta.gr	ok	IP: 194.30.229.125 Country: Greece Region: Attiki City: Athens Latitude: 37.979450 Longitude: 23.716221 View: Google Map

DOMAIN	STATUS	GEOLOCATION
www.correosdemexico.gob.mx	ok	No Geolocation information available.
kagi.com	ok	IP: 34.111.242.115 Country: United States of America Region: California City: Mountain View Latitude: 37.405991 Longitude: -122.078514 View: Google Map
www.ietf.org	ok	IP: 104.16.45.99 Country: United States of America Region: Texas City: Dallas Latitude: 32.783058 Longitude: -96.806671 View: Google Map
cleanbrowsing.org	ok	IP: 95.179.200.247 Country: United Kingdom of Great Britain and Northern Ireland Region: England City: Blackwall Latitude: 51.509708 Longitude: -0.001600 View: Google Map
api.karmasearch.org	ok	IP: 8.6.112.0 Country: United States of America Region: Texas City: Dallas Latitude: 32.783058 Longitude: -96.806671 View: Google Map
www.post.japanpost.jp	ok	IP: 43.253.212.25 Country: Japan Region: Tokyo City: Tokyo Latitude: 35.689507 Longitude: 139.691696 View: Google Map

DOMAIN	STATUS	GEOLOCATION
api.qwant.com	ok	IP: 141.94.211.182 Country: Germany Region: Hessen City: Frankfurt am Main Latitude: 50.115520 Longitude: 8.684170 View: Google Map
beacons3.gvt2.com	ok	IP: 108.177.14.94 Country: United States of America Region: California City: Mountain View Latitude: 37.405991 Longitude: -122.078514 View: Google Map
correos.go.cr	ok	IP: 181.193.34.242 Country: Costa Rica Region: San Jose City: San Jose Latitude: 9.933330 Longitude: -84.083328 View: Google Map
you.com	ok	IP: 8.47.69.0 Country: United States of America Region: California City: San Francisco Latitude: 37.775700 Longitude: -122.395203 View: Google Map
posturinn.is	ok	IP: 13.33.235.36 Country: Spain Region: Madrid, Comunidad de City: Madrid Latitude: 40.416500 Longitude: -3.702560 View: Google Map
www.correos.es	ok	IP: 3.164.206.34 Country: United States of America Region: Washington City: Seattle Latitude: 47.627499 Longitude: -122.346199 View: Google Map

DOMAIN	STATUS	GEOLOCATION
www.resso.com	ok	IP: 104.109.128.185 Country: Russian Federation Region: Moskva City: Moscow Latitude: 55.752220 Longitude: 37.615559 View: Google Map
adressesok.posten.no	ok	IP: 51.107.209.39 Country: Norway Region: Oslo City: Oslo Latitude: 59.912731 Longitude: 10.746090 View: Google Map
suggest.yandex.com.tr	ok	IP: 213.180.204.63 Country: Russian Federation Region: Moskva City: Moscow Latitude: 55.752220 Longitude: 37.615559 View: Google Map
www.codigopostal.gov.co	ok	IP: 190.144.185.2 Country: Colombia Region: Distrito Capital de Bogota City: Bogota Latitude: 4.609710 Longitude: -74.081749 View: Google Map
s.yimg.jp	ok	IP: 183.79.219.124 Country: Japan Region: Tokyo City: Tokyo Latitude: 35.689507 Longitude: 139.691696 View: Google Map
www.tt.site	ok	IP: 212.188.39.34 Country: Russian Federation Region: Moskva City: Moscow Latitude: 55.752220 Longitude: 37.615559 View: Google Map

DOMAIN	STATUS	GEOLOCATION
uz.post	ok	IP: 84.54.74.198 Country: Uzbekistan Region: Toshkent City: Tashkent Latitude: 41.264648 Longitude: 69.216270 View: Google Map
android.com	ok	IP: 142.251.38.68 Country: United States of America Region: California City: Mountain View Latitude: 37.405991 Longitude: -122.078514 View: Google Map
www.so.com	ok	IP: 104.192.110.226 Country: United States of America Region: California City: Los Angeles Latitude: 34.052986 Longitude: -118.263687 View: Google Map
location.tiktokw.us	ok	IP: 23.211.241.75 Country: Japan Region: Tokyo City: Tokyo Latitude: 35.689507 Longitude: 139.691696 View: Google Map
suggest.seznam.cz	ok	IP: 77.75.77.63 Country: Czechia Region: Praha, Hlavní mesto City: Prague Latitude: 50.088039 Longitude: 14.420760 View: Google Map
beacons.gvt2.com	ok	IP: 64.233.162.94 Country: Brazil Region: Sao Paulo City: Sao Paulo Latitude: -23.547501 Longitude: -46.636108 View: Google Map

DOMAIN	STATUS	GEOLOCATION
www.sec.co.kr	ok	IP: 112.106.187.200 Country: Korea (Republic of) Region: Seoul-teukbyeolsi City: Seoul Latitude: 37.568260 Longitude: 126.977829 View: Google Map
api.tiktokv.com	ok	IP: 95.101.133.26 Country: Sweden Region: Stockholms lan City: Stockholm Latitude: 59.332581 Longitude: 18.064899 View: Google Map
docs.google.com	ok	IP: 172.253.130.194 Country: United States of America Region: California City: Mountain View Latitude: 37.405991 Longitude: -122.078514 View: Google Map
www.correoargentino.com.ar	ok	IP: 45.60.71.195 Country: United Kingdom of Great Britain and Northern Ireland Region: England City: London Latitude: 51.508530 Longitude: -0.125740 View: Google Map
aomediadecodec.github.io	ok	IP: 185.199.108.153 Country: United States of America Region: Pennsylvania City: California Latitude: 40.065632 Longitude: -79.891708 View: Google Map
c.play.google.com	ok	No Geolocation information available.

DOMAIN	STATUS	GEOLOCATION
www.post.ch	ok	IP: 194.41.184.148 Country: Switzerland Region: Bern City: Zollikofen Latitude: 46.999050 Longitude: 7.458090 View: Google Map
www.amazon.com	ok	IP: 3.164.64.231 Country: United States of America Region: Washington City: Seattle Latitude: 47.627499 Longitude: -122.346199 View: Google Map
classroom.googleapis.com	ok	IP: 142.251.38.74 Country: United States of America Region: California City: Mountain View Latitude: 37.405991 Longitude: -122.078514 View: Google Map
f-p.sgsnssdk.com	ok	IP: 212.188.39.24 Country: Russian Federation Region: Moskva City: Moscow Latitude: 55.752220 Longitude: 37.615559 View: Google Map
www.webrtc.org	ok	IP: 216.58.198.206 Country: United States of America Region: California City: Mountain View Latitude: 37.405991 Longitude: -122.078514 View: Google Map
www.gpo.gov.np	ok	IP: 103.69.124.8 Country: Nepal Region: Bagmati City: Kathmandu Latitude: 27.701691 Longitude: 85.320602 View: Google Map

DOMAIN	STATUS	GEOLOCATION
xmlsoft.org	ok	IP: 149.202.84.84 Country: France Region: Hauts-de-France City: Roubaix Latitude: 50.694210 Longitude: 3.174560 View: Google Map
www.yandex.by	ok	IP: 77.88.44.55 Country: Russian Federation Region: Moskva City: Moscow Latitude: 55.752220 Longitude: 37.615559 View: Google Map
safesearch.googleapis.com	ok	IP: 216.239.38.223 Country: United States of America Region: California City: Mountain View Latitude: 37.405991 Longitude: -122.078514 View: Google Map
starling-vb.byteoversea.com	ok	IP: 212.188.39.48 Country: Russian Federation Region: Moskva City: Moscow Latitude: 55.752220 Longitude: 37.615559 View: Google Map
www.laposte.fr	ok	IP: 95.101.133.56 Country: Sweden Region: Stockholms län City: Stockholm Latitude: 59.332581 Longitude: 18.064899 View: Google Map
c.android.clients.google.com	ok	No Geolocation information available.
c.pack.google.com	ok	No Geolocation information available.

DOMAIN	STATUS	GEOLOCATION
dns11.quad9.net	ok	IP: 9.9.9.11 Country: United States of America Region: California City: Berkeley Latitude: 37.879318 Longitude: -122.265205 View: Google Map
inposdom.gob.do	ok	IP: 75.102.22.85 Country: United States of America Region: Illinois City: Chicago Latitude: 41.878201 Longitude: -87.625397 View: Google Map
co.search.yahoo.com	ok	IP: 212.82.100.137 Country: Ireland Region: Dublin City: Dublin Latitude: 53.343990 Longitude: -6.267190 View: Google Map
developers.cloudflare.com	ok	IP: 104.16.2.189 Country: United States of America Region: California City: San Francisco Latitude: 37.775700 Longitude: -122.395203 View: Google Map
api.amazon.com	ok	IP: 98.82.142.181 Country: United States of America Region: Washington City: Seattle Latitude: 47.606209 Longitude: -122.332069 View: Google Map
publickeyservice.gcp.privacysandboxservices.com	ok	No Geolocation information available.
gvt2.com	ok	No Geolocation information available.

DOMAIN	STATUS	GEOLOCATION
ssl.gstatic.com	ok	IP: 64.233.163.94 Country: United States of America Region: California City: Mountain View Latitude: 37.405991 Longitude: -122.078514 View: Google Map
www.poste.it	ok	IP: 13.107.213.43 Country: United States of America Region: Washington City: Redmond Latitude: 47.682899 Longitude: -122.120903 View: Google Map
storage.ape.yandex.net	ok	IP: 87.250.251.66 Country: Russian Federation Region: Moskva City: Moscow Latitude: 55.752220 Longitude: 37.615559 View: Google Map
html.spec.whatwg.org	ok	IP: 165.227.248.76 Country: United States of America Region: New Jersey City: Clifton Latitude: 40.858429 Longitude: -74.163757 View: Google Map
rtc-logger-va.tiktokv.com	ok	IP: 95.101.133.26 Country: Sweden Region: Stockholms lan City: Stockholm Latitude: 59.332581 Longitude: 18.064899 View: Google Map
hk.search.yahoo.com	ok	IP: 212.82.100.137 Country: Ireland Region: Dublin City: Dublin Latitude: 53.343990 Longitude: -6.267190 View: Google Map

DOMAIN	STATUS	GEOLOCATION
safebrowsing.googleapis.com	ok	IP: 64.233.162.95 Country: Brazil Region: Sao Paulo City: Sao Paulo Latitude: -23.547501 Longitude: -46.636108 View: Google Map
jmt17.google.com	ok	IP: 216.58.198.206 Country: United States of America Region: California City: Mountain View Latitude: 37.405991 Longitude: -122.078514 View: Google Map
cdn.yep.com	ok	IP: 8.6.112.0 Country: United States of America Region: Texas City: Dallas Latitude: 32.783058 Longitude: -96.806671 View: Google Map
ac.ecosia.org	ok	IP: 104.18.37.185 Country: United States of America Region: Texas City: Dallas Latitude: 32.783058 Longitude: -96.806671 View: Google Map
www.gmail.com	ok	IP: 142.251.38.69 Country: United States of America Region: California City: Mountain View Latitude: 37.405991 Longitude: -122.078514 View: Google Map
ss.s	ok	No Geolocation information available.

DOMAIN	STATUS	GEOLOCATION
www.philpost.gov.ph	ok	IP: 192.185.39.242 Country: United States of America Region: Utah City: Provo Latitude: 40.233841 Longitude: -111.658531 View: Google Map
.jpg	ok	No Geolocation information available.
quendu.com	ok	IP: 63.177.54.21 Country: United States of America Region: Virginia City: Reston Latitude: 38.925961 Longitude: -77.397331 View: Google Map
www.yandex.kz	ok	IP: 45.138.0.2 Country: Netherlands Region: Flevoland City: Dronten Latitude: 52.525002 Longitude: 5.718060 View: Google Map
www.maltapost.com	ok	IP: 217.168.161.7 Country: Malta Region: Valletta City: Valletta Latitude: 35.899719 Longitude: 14.514720 View: Google Map
purl.org	ok	IP: 207.241.225.157 Country: United States of America Region: California City: San Francisco Latitude: 37.781734 Longitude: -122.459435 View: Google Map

DOMAIN	STATUS	GEOLOCATION
malaysia.search.yahoo.com	ok	IP: 212.82.100.137 Country: Ireland Region: Dublin City: Dublin Latitude: 53.343990 Longitude: -6.267190 View: Google Map
duckduckgo.com	ok	IP: 20.204.244.192 Country: United States of America Region: Washington City: Redmond Latitude: 47.682899 Longitude: -122.120903 View: Google Map
dns.google	ok	IP: 8.8.8.8 Country: United States of America Region: California City: Mountain View Latitude: 37.405991 Longitude: -122.078514 View: Google Map
bytecast.tiktokv.com	ok	IP: 95.101.133.26 Country: Sweden Region: Stockholms lan City: Stockholm Latitude: 59.332581 Longitude: 18.064899 View: Google Map
www.tiktok.in	ok	IP: 95.101.133.51 Country: Sweden Region: Stockholms lan City: Stockholm Latitude: 59.332581 Longitude: 18.064899 View: Google Map
coccoc.com	ok	IP: 123.30.175.29 Country: Viet Nam Region: Thanh Hoa City: Thanh Hoa Latitude: 19.799999 Longitude: 105.766670 View: Google Map

DOMAIN	STATUS	GEOLOCATION
uploadffmpeg.org	ok	IP: 213.36.253.119 Country: France Region: Ile-de-France City: Paris Latitude: 48.853409 Longitude: 2.348800 View: Google Map
oauth.deezer.com	ok	IP: 95.101.133.17 Country: Sweden Region: Stockholms lan City: Stockholm Latitude: 59.332581 Longitude: 18.064899 View: Google Map
au.search.yahoo.com	ok	IP: 212.82.100.137 Country: Ireland Region: Dublin City: Dublin Latitude: 53.343990 Longitude: -6.267190 View: Google Map
play.google.com	ok	IP: 142.250.150.139 Country: United States of America Region: California City: Mountain View Latitude: 37.405991 Longitude: -122.078514 View: Google Map
c2pa.org	ok	IP: 23.185.0.4 Country: United States of America Region: California City: San Francisco Latitude: 37.792030 Longitude: -122.406853 View: Google Map
goo.gl	ok	IP: 74.125.131.100 Country: United States of America Region: California City: Mountain View Latitude: 37.405991 Longitude: -122.078514 View: Google Map

DOMAIN	STATUS	GEOLOCATION
b.stats.paypal.com	ok	IP: 34.147.177.40 Country: United States of America Region: Texas City: Houston Latitude: 29.941401 Longitude: -95.344498 View: Google Map
www.lilo.org	ok	IP: 141.94.211.182 Country: Germany Region: Hessen City: Frankfurt am Main Latitude: 50.115520 Longitude: 8.684170 View: Google Map
google-analytics.com	ok	IP: 173.194.220.147 Country: United States of America Region: California City: Mountain View Latitude: 37.405991 Longitude: -122.078514 View: Google Map
www.indiapost.gov.in	ok	IP: 45.127.75.247 Country: India Region: Tamil Nadu City: Madurantakam Latitude: 12.516670 Longitude: 79.900002 View: Google Map
sugg.sogou.com	ok	No Geolocation information available.
www.mojeeek.com	ok	IP: 5.102.173.68 Country: United Kingdom of Great Britain and Northern Ireland Region: England City: Kent Latitude: 51.250000 Longitude: 0.750000 View: Google Map

DOMAIN	STATUS	GEOLOCATION
api.sandbox.braintreegateway.com	ok	IP: 159.242.242.129 Country: United States of America Region: Illinois City: Chicago Latitude: 41.888401 Longitude: -87.635101 View: Google Map
www.bgpost.bg	ok	IP: 172.67.187.143 Country: United States of America Region: California City: San Francisco Latitude: 37.775700 Longitude: -122.395203 View: Google Map
gvt6.com	ok	No Geolocation information available.
xhr.spec.whatwg.org	ok	IP: 165.227.248.76 Country: United States of America Region: New Jersey City: Clifton Latitude: 40.858429 Longitude: -74.163757 View: Google Map
api.oceanhero.today	ok	IP: 104.18.22.99 Country: United States of America Region: California City: San Francisco Latitude: 37.775700 Longitude: -122.395203 View: Google Map
fi.search.yahoo.com	ok	IP: 212.82.100.137 Country: Ireland Region: Dublin City: Dublin Latitude: 53.343990 Longitude: -6.267190 View: Google Map

DOMAIN	STATUS	GEOLOCATION
www.tt.inc	ok	IP: 212.188.39.16 Country: Russian Federation Region: Moskva City: Moscow Latitude: 55.752220 Longitude: 37.615559 View: Google Map
www.postnl.nl	ok	IP: 95.101.133.58 Country: Sweden Region: Stockholms lan City: Stockholm Latitude: 59.332581 Longitude: 18.064899 View: Google Map
developers.google.com	ok	IP: 142.251.1.102 Country: United States of America Region: California City: Mountain View Latitude: 37.405991 Longitude: -122.078514 View: Google Map
www.googleorganizationautocomplete requirementsconservative	ok	No Geolocation information available.
www.icon	ok	No Geolocation information available.
www.royalmail.com	ok	IP: 212.188.39.19 Country: Russian Federation Region: Moskva City: Moscow Latitude: 55.752220 Longitude: 37.615559 View: Google Map
public.dns.ijj.jp	ok	IP: 103.2.57.5 Country: Japan Region: Tokyo City: Tokyo Latitude: 35.689507 Longitude: 139.691696 View: Google Map

DOMAIN	STATUS	GEOLOCATION
karmasearch.org	ok	IP: 8.6.112.0 Country: United States of America Region: Texas City: Dallas Latitude: 32.783058 Longitude: -96.806671 View: Google Map
ping.microblink.com	ok	IP: 8.47.69.0 Country: United States of America Region: California City: San Francisco Latitude: 37.775700 Longitude: -122.395203 View: Google Map
www.unicode.org	ok	IP: 8.47.69.0 Country: United States of America Region: California City: San Francisco Latitude: 37.775700 Longitude: -122.395203 View: Google Map
google.com	ok	IP: 216.58.201.14 Country: United States of America Region: California City: Mountain View Latitude: 37.405991 Longitude: -122.078514 View: Google Map
at.search.yahoo.com	ok	IP: 212.82.100.137 Country: Ireland Region: Dublin City: Dublin Latitude: 53.343990 Longitude: -6.267190 View: Google Map
pay.google.com	ok	IP: 173.194.221.92 Country: United States of America Region: California City: Mountain View Latitude: 37.405991 Longitude: -122.078514 View: Google Map

DOMAIN	STATUS	GEOLOCATION
cl.search.yahoo.com	ok	IP: 212.82.100.137 Country: Ireland Region: Dublin City: Dublin Latitude: 53.343990 Longitude: -6.267190 View: Google Map
www.yandex.ru	ok	IP: 5.255.255.77 Country: Russian Federation Region: Moskva City: Moscow Latitude: 55.752220 Longitude: 37.615559 View: Google Map
api-m.paypal.com	ok	IP: 151.101.7.1 Country: United States of America Region: California City: San Francisco Latitude: 37.775700 Longitude: -122.395203 View: Google Map
oauthaccountmanager.googleapis.com	ok	IP: 216.239.38.223 Country: United States of America Region: California City: Mountain View Latitude: 37.405991 Longitude: -122.078514 View: Google Map
nl.search.yahoo.com	ok	IP: 212.82.100.137 Country: Ireland Region: Dublin City: Dublin Latitude: 53.343990 Longitude: -6.267190 View: Google Map
www.postdirekt.de	ok	IP: 46.231.177.227 Country: Germany Region: Berlin City: Berlin Latitude: 52.524368 Longitude: 13.410530 View: Google Map

DOMAIN	STATUS	GEOLOCATION
www.bing.com	ok	IP: 62.115.252.43 Country: Finland Region: - City: - Latitude: 60.169521 Longitude: 24.935450 View: Google Map
yastatic.net	ok	IP: 37.9.64.225 Country: Russian Federation Region: Moskva City: Moscow Latitude: 55.752220 Longitude: 37.615559 View: Google Map
go.mail.ru	ok	IP: 95.163.61.107 Country: Russian Federation Region: Moskva City: Moscow Latitude: 55.752220 Longitude: 37.615559 View: Google Map
www.risktabsprev10pxrise25pxblueding300ballfordearnwildbox.fairlackverspairjunetechifpickevil	ok	No Geolocation information available.
.css	ok	No Geolocation information available.
www.guernseypost.com	ok	IP: 8.47.69.0 Country: United States of America Region: California City: San Francisco Latitude: 37.775700 Longitude: -122.395203 View: Google Map
w3c.github.io	ok	IP: 185.199.109.153 Country: United States of America Region: Pennsylvania City: California Latitude: 40.065632 Longitude: -79.891708 View: Google Map

DOMAIN	STATUS	GEOLOCATION
anglebug.com	ok	IP: 216.239.32.29 Country: United States of America Region: California City: Mountain View Latitude: 37.405991 Longitude: -122.078514 View: Google Map
venmo.com	ok	IP: 52.84.150.58 Country: Germany Region: Rheinland-Pfalz City: Isenburg Latitude: 50.483330 Longitude: 7.600000 View: Google Map
www.posta.hr	ok	IP: 172.66.153.201 Country: United States of America Region: California City: San Francisco Latitude: 37.775700 Longitude: -122.395203 View: Google Map
www1.web-platform.test127.0.0.1example.testwww.google.com	ok	No Geolocation information available.
doh.cleanbrowsing.org	ok	IP: 185.228.168.168 Country: United States of America Region: California City: Temecula Latitude: 33.530987 Longitude: -117.103394 View: Google Map
www.poste.tn	ok	IP: 193.95.101.227 Country: Tunisia Region: Tunis City: Tunis Latitude: 36.818970 Longitude: 10.165790 View: Google Map

DOMAIN	STATUS	GEOLOCATION
blog.chromium.org	ok	IP: 216.239.32.27 Country: United States of America Region: California City: Mountain View Latitude: 37.405991 Longitude: -122.078514 View: Google Map
www.georgianpost.ge	ok	IP: 91.239.206.36 Country: Georgia Region: Tbilisi City: Tbilisi Latitude: 41.694111 Longitude: 44.833679 View: Google Map
www.tiktok.com2ffalcon2ftiktok	ok	No Geolocation information available.
www.chromestatus.com	ok	IP: 64.233.161.121 Country: United States of America Region: California City: Mountain View Latitude: 37.405991 Longitude: -122.078514 View: Google Map
www.google.com	ok	IP: 142.251.155.119 Country: United States of America Region: California City: Mountain View Latitude: 37.405991 Longitude: -122.078514 View: Google Map
www.landvaluation.bm	ok	IP: 142.176.55.72 Country: Canada Region: Nova Scotia City: Sydney Latitude: 46.135101 Longitude: -60.183102 View: Google Map

DOMAIN	STATUS	GEOLOCATION
google-ohhttp-relay-safebrowsing.fastly-edge.com	ok	IP: 199.232.173.91 Country: United States of America Region: California City: San Francisco Latitude: 37.775700 Longitude: -122.395203 View: Google Map
www.postnord.se	ok	IP: 172.64.154.47 Country: United States of America Region: Texas City: Dallas Latitude: 32.783058 Longitude: -96.806671 View: Google Map
invalid.url	ok	No Geolocation information available.
tools.usps.com	ok	IP: 23.32.25.126 Country: Sweden Region: Stockholms lan City: Stockholm Latitude: 59.332581 Longitude: 18.064899 View: Google Map
www.pakpost.gov.pk	ok	IP: 203.101.184.81 Country: Pakistan Region: Sindh City: Karachi Latitude: 24.905600 Longitude: 67.082199 View: Google Map
www.ibm.com	ok	IP: 23.43.27.57 Country: United Kingdom of Great Britain and Northern Ireland Region: England City: London Latitude: 51.508530 Longitude: -0.125740 View: Google Map
c.bigcache.googleapis.com	ok	No Geolocation information available.
lepus.js	ok	No Geolocation information available.

DOMAIN	STATUS	GEOLOCATION
bit.ly	ok	IP: 67.199.248.10 Country: United States of America Region: New York City: New York City Latitude: 40.739288 Longitude: -73.984955 View: Google Map
www.sogou.com	ok	IP: 43.153.236.147 Country: China Region: Beijing City: Beijing Latitude: 39.907501 Longitude: 116.397232 View: Google Map
search.seznam.cz	ok	IP: 77.75.76.39 Country: Czechia Region: Praha, Hlavní mesto City: Prague Latitude: 50.088039 Longitude: 14.420760 View: Google Map
www.tt.fun	ok	IP: 212.188.39.51 Country: Russian Federation Region: Moskva City: Moscow Latitude: 55.752220 Longitude: 37.615559 View: Google Map
starling.tiktokv.us	ok	IP: 23.58.85.112 Country: Canada Region: British Columbia City: Vancouver Latitude: 49.249660 Longitude: -123.119339 View: Google Map
webRTC.googleSource.com	ok	IP: 108.177.14.82 Country: United States of America Region: California City: Mountain View Latitude: 37.405991 Longitude: -122.078514 View: Google Map

DOMAIN	STATUS	GEOLOCATION
www.codigopostal.gob.ec	ok	IP: 190.152.52.204 Country: Ecuador Region: Pichincha City: Quito Latitude: -0.229850 Longitude: -78.524948 View: Google Map
zip4.usps.com	ok	IP: 23.32.25.126 Country: Sweden Region: Stockholms lan City: Stockholm Latitude: 59.332581 Longitude: 18.064899 View: Google Map
pitaya.tiktokv.com	ok	IP: 71.18.222.1 Country: United States of America Region: Massachusetts City: Burlington Latitude: 42.508480 Longitude: -71.201134 View: Google Map
gpuweb.github.io	ok	IP: 185.199.108.153 Country: United States of America Region: Pennsylvania City: California Latitude: 40.065632 Longitude: -79.891708 View: Google Map
www.a	ok	No Geolocation information available.
127.0.0.1	ok	IP: 127.0.0.1 Country: - Region: - City: - Latitude: 0.000000 Longitude: 0.000000 View: Google Map

DOMAIN	STATUS	GEOLOCATION
exslt.org	ok	IP: 172.67.204.219 Country: United States of America Region: California City: San Francisco Latitude: 37.775700 Longitude: -122.395203 View: Google Map
mon.byteoversea.com	ok	IP: 71.18.222.1 Country: United States of America Region: Massachusetts City: Burlington Latitude: 42.508480 Longitude: -71.201134 View: Google Map
www.chromium.org	ok	IP: 199.36.158.100 Country: United States of America Region: California City: Mountain View Latitude: 37.405991 Longitude: -122.078514 View: Google Map
chromium.googlesource.com	ok	IP: 74.125.131.82 Country: United States of America Region: California City: Mountain View Latitude: 37.405991 Longitude: -122.078514 View: Google Map
suggest.yandex.ru	ok	IP: 213.180.204.63 Country: Russian Federation Region: Moskva City: Moscow Latitude: 55.752220 Longitude: 37.615559 View: Google Map
android.googlesource.com	ok	IP: 64.233.162.82 Country: Brazil Region: Sao Paulo City: Sao Paulo Latitude: -23.547501 Longitude: -46.636108 View: Google Map

DOMAIN	STATUS	GEOLOCATION
pe.search.yahoo.com	ok	IP: 212.82.100.137 Country: Ireland Region: Dublin City: Dublin Latitude: 53.343990 Longitude: -6.267190 View: Google Map
www.w3.org	ok	IP: 8.6.112.0 Country: United States of America Region: Texas City: Dallas Latitude: 32.783058 Longitude: -96.806671 View: Google Map
googlevideo.com	ok	IP: 173.194.221.106 Country: United States of America Region: California City: Mountain View Latitude: 37.405991 Longitude: -122.078514 View: Google Map
chrome.cloudflare-dns.com	ok	IP: 162.159.61.3 Country: United States of America Region: California City: San Francisco Latitude: 37.775700 Longitude: -122.395203 View: Google Map
beacons5.gvt3.com	ok	IP: 64.233.162.94 Country: Brazil Region: Sao Paulo City: Sao Paulo Latitude: -23.547501 Longitude: -46.636108 View: Google Map
www.bpost.be	ok	IP: 193.191.180.79 Country: Belgium Region: Brussels Hoofdstedelijk Gewest City: Brussels Latitude: 50.850449 Longitude: 4.348780 View: Google Map

DOMAIN	STATUS	GEOLOCATION
dns64.dns.google	ok	No Geolocation information available.
doh-02.spectrum.com	ok	IP: 24.240.146.8 Country: United States of America Region: Louisiana City: Monroe Latitude: 32.509312 Longitude: -92.119301 View: Google Map
postakodu.ptt.gov.tr	ok	IP: 185.220.152.65 Country: Turkey Region: Ankara City: Ankara Latitude: 39.919868 Longitude: 32.854271 View: Google Map
www.srgb.com	ok	IP: 172.104.149.86 Country: Germany Region: Hessen City: Frankfurt am Main Latitude: 50.115520 Longitude: 8.684170 View: Google Map
www.posta.rs	ok	IP: 212.62.32.46 Country: Serbia Region: Beograd City: Belgrade Latitude: 44.804008 Longitude: 20.465130 View: Google Map
mon.tiktokv.com	ok	IP: 212.188.39.17 Country: Russian Federation Region: Moskva City: Moscow Latitude: 55.752220 Longitude: 37.615559 View: Google Map

DOMAIN	STATUS	GEOLOCATION
freespoke.com	ok	IP: 8.6.112.0 Country: United States of America Region: Texas City: Dallas Latitude: 32.783058 Longitude: -96.806671 View: Google Map
beacons2.gvt2.com	ok	IP: 142.250.206.3 Country: United States of America Region: California City: Mountain View Latitude: 37.405991 Longitude: -122.078514 View: Google Map
www.cisco.com	ok	IP: 23.32.26.4 Country: Sweden Region: Stockholms lan City: Stockholm Latitude: 59.332581 Longitude: 18.064899 View: Google Map
nextdns.io	ok	IP: 8.6.112.0 Country: United States of America Region: Texas City: Dallas Latitude: 32.783058 Longitude: -96.806671 View: Google Map
api-lb.freespoke.com	ok	IP: 8.6.112.0 Country: United States of America Region: Texas City: Dallas Latitude: 32.783058 Longitude: -96.806671 View: Google Map
starling-oversea.byteoversea.com	ok	IP: 80.239.254.2 Country: Sweden Region: Stockholms lan City: Stockholm Latitude: 59.332581 Longitude: 18.064899 View: Google Map

DOMAIN	STATUS	GEOLOCATION
ar.search.yahoo.com	ok	IP: 212.82.100.137 Country: Ireland Region: Dublin City: Dublin Latitude: 53.343990 Longitude: -6.267190 View: Google Map
br.search.yahoo.com	ok	IP: 212.82.100.137 Country: Ireland Region: Dublin City: Dublin Latitude: 53.343990 Longitude: -6.267190 View: Google Map
www.nzpost.co.nz	ok	IP: 35.71.155.231 Country: United States of America Region: Washington City: Seattle Latitude: 47.627499 Longitude: -122.346199 View: Google Map
www.maldivespost.com	ok	IP: 172.67.170.99 Country: United States of America Region: California City: San Francisco Latitude: 37.775700 Longitude: -122.395203 View: Google Map
wicg.github.io	ok	IP: 185.199.110.153 Country: United States of America Region: Pennsylvania City: California Latitude: 40.065632 Longitude: -79.891708 View: Google Map
www.caymanpost.gov.ky	ok	IP: 80.239.137.145 Country: Netherlands Region: Noord-Holland City: Amsterdam Latitude: 52.374031 Longitude: 4.889690 View: Google Map

DOMAIN	STATUS	GEOLOCATION
www.text-decoration	ok	No Geolocation information available.
www.post.at	ok	IP: 20.101.14.176 Country: United States of America Region: Washington City: Redmond Latitude: 47.682899 Longitude: -122.120903 View: Google Map
pitaya-task.tiktokv.com	ok	IP: 130.44.212.78 Country: United States of America Region: California City: Palo Alto Latitude: 37.416859 Longitude: -122.129219 View: Google Map
www.iompost.com	ok	IP: 46.31.200.44 Country: Isle of Man Region: Isle of Man City: Douglas Latitude: 54.150002 Longitude: -4.483330 View: Google Map
fr.search.yahoo.com	ok	IP: 212.82.100.137 Country: Ireland Region: Dublin City: Dublin Latitude: 53.343990 Longitude: -6.267190 View: Google Map
developer.chrome.com	ok	IP: 216.58.201.14 Country: United States of America Region: California City: Mountain View Latitude: 37.405991 Longitude: -122.078514 View: Google Map
webapps.mtic.gov.bn	ok	No Geolocation information available.

DOMAIN	STATUS	GEOLOCATION
panda-search.org	ok	IP: 85.13.151.2 Country: Germany Region: Thuringen City: Friedersdorf Latitude: 50.604919 Longitude: 11.035770 View: Google Map
www.style	ok	IP: 75.2.38.108 Country: United States of America Region: Washington City: Seattle Latitude: 47.606209 Longitude: -122.332069 View: Google Map
uk.search.yahoo.com	ok	IP: 212.82.100.137 Country: Ireland Region: Dublin City: Dublin Latitude: 53.343990 Longitude: -6.267190 View: Google Map
www.language	ok	No Geolocation information available.
search.brave.com	ok	IP: 13.33.235.41 Country: Spain Region: Madrid, Comunidad de City: Madrid Latitude: 40.416500 Longitude: -3.702560 View: Google Map
uri.etsi.org	ok	IP: 8.47.69.0 Country: United States of America Region: California City: San Francisco Latitude: 37.775700 Longitude: -122.395203 View: Google Map
c.drive.google.com	ok	No Geolocation information available.
www.aa.comhttps	ok	No Geolocation information available.

DOMAIN	STATUS	GEOLOCATION
dnsnl.alekberg.net	ok	IP: 133.167.212.25 Country: Japan Region: Tokyo City: Tokyo Latitude: 35.689507 Longitude: 139.691696 View: Google Map
emea.search.yahoo.com	ok	IP: 212.82.100.137 Country: Ireland Region: Dublin City: Dublin Latitude: 53.343990 Longitude: -6.267190 View: Google Map
search.daum.net	ok	IP: 211.183.208.36 Country: Korea (Republic of) Region: Seoul-teukbyeolsi City: Seoul Latitude: 37.568260 Longitude: 126.977829 View: Google Map
www.pochta.ru	ok	IP: 212.164.140.129 Country: Russian Federation Region: Novosibirskaya oblast' City: Novosibirsk Latitude: 55.041500 Longitude: 82.934601 View: Google Map
ex.belpost.by	ok	IP: 212.98.168.66 Country: Belarus Region: Minskaya voblasts' City: Minsk Latitude: 53.900002 Longitude: 27.566669 View: Google Map
dk.search.yahoo.com	ok	IP: 212.82.100.137 Country: Ireland Region: Dublin City: Dublin Latitude: 53.343990 Longitude: -6.267190 View: Google Map

DOMAIN	STATUS	GEOLOCATION
epab.posten.no	ok	IP: 51.107.209.39 Country: Norway Region: Oslo City: Oslo Latitude: 59.912731 Longitude: 10.746090 View: Google Map
search.yahoo.co.jp	ok	IP: 183.79.219.124 Country: Japan Region: Tokyo City: Tokyo Latitude: 35.689507 Longitude: 139.691696 View: Google Map
schemas.xmlsoap.org	ok	IP: 150.171.109.100 Country: United States of America Region: Washington City: Redmond Latitude: 47.682899 Longitude: -122.120903 View: Google Map
example.org	ok	IP: 8.6.112.0 Country: United States of America Region: Texas City: Dallas Latitude: 32.783058 Longitude: -96.806671 View: Google Map
cola.melon.com	ok	IP: 211.249.216.12 Country: Korea (Republic of) Region: Seoul-teukbyeolsi City: Seoul Latitude: 37.568260 Longitude: 126.977829 View: Google Map
publickeyservice.pa.aws.privacysandboxservices.com	ok	IP: 108.156.22.30 Country: United States of America Region: Washington City: Redmond Latitude: 47.682899 Longitude: -122.120903 View: Google Map

DOMAIN	STATUS	GEOLOCATION
tools.ietf.org	ok	IP: 104.16.44.99 Country: United States of America Region: Texas City: Dallas Latitude: 32.783058 Longitude: -96.806671 View: Google Map
c.paypal.com	ok	IP: 199.232.173.21 Country: United States of America Region: California City: San Francisco Latitude: 37.775700 Longitude: -122.395203 View: Google Map
f-p-va.isnssdk.com	ok	IP: 95.101.133.18 Country: Sweden Region: Stockholms lan City: Stockholm Latitude: 59.332581 Longitude: 18.064899 View: Google Map
crashpad.chromium.org	ok	IP: 64.233.161.121 Country: United States of America Region: California City: Mountain View Latitude: 37.405991 Longitude: -122.078514 View: Google Map
www.world	ok	IP: 99.83.155.228 Country: United States of America Region: Washington City: Seattle Latitude: 47.606209 Longitude: -122.332069 View: Google Map
c.googlesyndication.com	ok	No Geolocation information available.

DOMAIN	STATUS	GEOLOCATION
screen-share.github.io	ok	IP: 185.199.108.153 Country: United States of America Region: Pennsylvania City: California Latitude: 40.065632 Longitude: -79.891708 View: Google Map
people.googleapis.com	ok	IP: 74.125.205.95 Country: United States of America Region: California City: Mountain View Latitude: 37.405991 Longitude: -122.078514 View: Google Map
www.pos.com.my	ok	IP: 95.101.133.49 Country: Sweden Region: Stockholms lan City: Stockholm Latitude: 59.332581 Longitude: 18.064899 View: Google Map
h.online-metrix.net	ok	IP: 91.235.132.130 Country: Netherlands Region: Noord-Holland City: Amsterdam Latitude: 52.374031 Longitude: 4.889690 View: Google Map
api.braintreegateway.com	ok	IP: 159.242.242.193 Country: United States of America Region: Illinois City: Chicago Latitude: 41.888401 Longitude: -87.635101 View: Google Map
tiktok.com	ok	IP: 95.101.133.25 Country: Sweden Region: Stockholms lan City: Stockholm Latitude: 59.332581 Longitude: 18.064899 View: Google Map

DOMAIN	STATUS	GEOLOCATION
www.eswatinipost.co.sz	ok	No Geolocation information available.
doh.familyshield.opendns.com	ok	IP: 146.112.41.3 Country: United Kingdom of Great Britain and Northern Ireland Region: England City: London Latitude: 51.508530 Longitude: -0.125740 View: Google Map
cdn.sapphire.microsoftapp.net	ok	IP: 150.171.109.101 Country: United States of America Region: Washington City: Redmond Latitude: 47.682899 Longitude: -122.120903 View: Google Map
www.postdanmark.dk	ok	IP: 13.33.235.83 Country: Spain Region: Madrid, Comunidad de City: Madrid Latitude: 40.416500 Longitude: -3.702560 View: Google Map
monitoring.url.loader.factory.invalid	ok	No Geolocation information available.
www.youtube.com	ok	IP: 64.233.164.198 Country: United States of America Region: California City: Mountain View Latitude: 37.405991 Longitude: -122.078514 View: Google Map
c.doc-0-0-sj.sj.googleusercontent.com	ok	No Geolocation information available.
www.postoffice.co.za	ok	IP: 165.8.13.24 Country: South Africa Region: Gauteng City: Pretoria Latitude: -25.744860 Longitude: 28.187830 View: Google Map

DOMAIN	STATUS	GEOLOCATION
www.qwant.com	ok	IP: 141.94.211.182 Country: Germany Region: Hessen City: Frankfurt am Main Latitude: 50.115520 Longitude: 8.684170 View: Google Map
scc.tiktokv.com	ok	IP: 95.101.133.50 Country: Sweden Region: Stockholms lan City: Stockholm Latitude: 59.332581 Longitude: 18.064899 View: Google Map
cdn.ecosia.org	ok	IP: 172.64.150.71 Country: United States of America Region: Texas City: Dallas Latitude: 32.783058 Longitude: -96.806671 View: Google Map
www.jclark.com	ok	IP: 119.81.18.13 Country: Singapore Region: Singapore City: Singapore Latitude: 1.289670 Longitude: 103.850067 View: Google Map
www.quad9.net	ok	IP: 195.176.255.138 Country: Switzerland Region: Zurich City: Zuerich (Kreis 1) / Rathaus Latitude: 47.371609 Longitude: 8.545010 View: Google Map
suggest.yandex.com	ok	IP: 213.180.204.63 Country: Russian Federation Region: Moskva City: Moscow Latitude: 55.752220 Longitude: 37.615559 View: Google Map

DOMAIN	STATUS	GEOLOCATION
developer.paypal.com	ok	IP: 199.232.173.21 Country: United States of America Region: California City: San Francisco Latitude: 37.775700 Longitude: -122.395203 View: Google Map
accountcapabilities-pa.googleapis.com	ok	IP: 142.251.38.74 Country: United States of America Region: California City: Mountain View Latitude: 37.405991 Longitude: -122.078514 View: Google Map
gcp.gvt2.com	ok	No Geolocation information available.
www.singpost.com	ok	IP: 45.60.53.165 Country: United Kingdom of Great Britain and Northern Ireland Region: England City: London Latitude: 51.508530 Longitude: -0.125740 View: Google Map
yandex.by	ok	IP: 77.88.44.55 Country: Russian Federation Region: Moskva City: Moscow Latitude: 55.752220 Longitude: 37.615559 View: Google Map
psc.ceskaposta.cz	ok	IP: 193.150.24.114 Country: Czechia Region: Praha, Hlavní město City: Prague Latitude: 50.088039 Longitude: 14.420760 View: Google Map

DOMAIN	STATUS	GEOLOCATION
bdpost.portal.gov.bd	ok	IP: 131.186.50.33 Country: United States of America Region: Washington City: Seattle Latitude: 47.611679 Longitude: -122.333260 View: Google Map
safebrowsing.google.com	ok	IP: 108.177.14.190 Country: United States of America Region: California City: Mountain View Latitude: 37.405991 Longitude: -122.078514 View: Google Map
beacons5.gvt2.com	ok	IP: 216.239.32.116 Country: United States of America Region: California City: Mountain View Latitude: 37.405991 Longitude: -122.078514 View: Google Map
i.sgsnssdk.com	ok	IP: 103.136.220.198 Country: Singapore Region: Singapore City: Singapore Latitude: 1.289670 Longitude: 103.850067 View: Google Map
in.search.yahoo.com	ok	IP: 212.82.100.137 Country: Ireland Region: Dublin City: Dublin Latitude: 53.343990 Longitude: -6.267190 View: Google Map
dns.google.com	ok	IP: 8.8.8.8 Country: United States of America Region: California City: Mountain View Latitude: 37.405991 Longitude: -122.078514 View: Google Map

DOMAIN	STATUS	GEOLOCATION
beacons4.gvt2.com	ok	IP: 216.239.32.116 Country: United States of America Region: California City: Mountain View Latitude: 37.405991 Longitude: -122.078514 View: Google Map
sf16-sg.tiktokcdn.com	ok	IP: 104.109.128.208 Country: Russian Federation Region: Moskva City: Moscow Latitude: 55.752220 Longitude: 37.615559 View: Google Map
doh-01.spectrum.com	ok	IP: 24.240.146.7 Country: United States of America Region: Louisiana City: Monroe Latitude: 32.509312 Longitude: -92.119301 View: Google Map
www.googleapis.com	ok	IP: 142.251.38.74 Country: United States of America Region: California City: Mountain View Latitude: 37.405991 Longitude: -122.078514 View: Google Map
mx.search.yahoo.com	ok	IP: 212.82.100.137 Country: Ireland Region: Dublin City: Dublin Latitude: 53.343990 Longitude: -6.267190 View: Google Map
finder.eircode.ie	ok	IP: 18.165.122.68 Country: United States of America Region: Washington City: Seattle Latitude: 47.627499 Longitude: -122.346199 View: Google Map

DOMAIN	STATUS	GEOLOCATION
www.quendu.com	ok	IP: 63.177.54.21 Country: United States of America Region: Virginia City: Reston Latitude: 38.925961 Longitude: -77.397331 View: Google Map
ns.adobe.com	ok	No Geolocation information available.
odvr.nic.cz	ok	IP: 185.43.135.1 Country: Czechia Region: Praha, Hlavní mesto City: Prague Latitude: 50.088039 Longitude: 14.420760 View: Google Map
unisolated.invalid	ok	No Geolocation information available.
domain.com	ok	IP: 8.6.112.0 Country: United States of America Region: Texas City: Dallas Latitude: 32.783058 Longitude: -96.806671 View: Google Map
www1.auspost.com.au	ok	IP: 155.144.114.143 Country: Australia Region: New South Wales City: Sydney Latitude: -33.867851 Longitude: 151.207321 View: Google Map
www.posta.fo	ok	IP: 212.55.56.83 Country: Faroe Islands Region: Streymoy City: Torshavn Latitude: 62.009731 Longitude: -6.771640 View: Google Map

DOMAIN	STATUS	GEOLOCATION
suggestion.baidu.com	ok	IP: 39.156.68.207 Country: China Region: Beijing City: Beijing Latitude: 39.907501 Longitude: 116.397232 View: Google Map
location-v4.byteintl.com	ok	IP: 95.101.133.16 Country: Sweden Region: Stockholms lan City: Stockholm Latitude: 59.332581 Longitude: 18.064899 View: Google Map
se.search.yahoo.com	ok	IP: 212.82.100.137 Country: Ireland Region: Dublin City: Dublin Latitude: 53.343990 Longitude: -6.267190 View: Google Map
www.startpage.com	ok	IP: 67.63.60.233 Country: United States of America Region: California City: Venice Latitude: 33.994320 Longitude: -118.461960 View: Google Map
sg.search.yahoo.com	ok	IP: 212.82.100.137 Country: Ireland Region: Dublin City: Dublin Latitude: 53.343990 Longitude: -6.267190 View: Google Map
search.yahooapis.jp	ok	IP: 183.79.219.124 Country: Japan Region: Tokyo City: Tokyo Latitude: 35.689507 Longitude: 139.691696 View: Google Map

DOMAIN	STATUS	GEOLOCATION
www.zipcode.mn	ok	IP: 203.26.189.57 Country: Mongolia Region: Ulaanbaatar City: Ulaanbaatar Latitude: 47.907711 Longitude: 106.883240 View: Google Map
www.correos.gob.ni	ok	IP: 8.47.69.0 Country: United States of America Region: California City: San Francisco Latitude: 37.775700 Longitude: -122.395203 View: Google Map
www.nic.cz	ok	IP: 217.31.205.50 Country: Czechia Region: Praha, Hlavní mesto City: Prague Latitude: 50.088039 Longitude: 14.420760 View: Google Map
ca.search.yahoo.com	ok	IP: 212.82.100.137 Country: Ireland Region: Dublin City: Dublin Latitude: 53.343990 Longitude: -6.267190 View: Google Map
ph.search.yahoo.com	ok	IP: 212.82.100.137 Country: Ireland Region: Dublin City: Dublin Latitude: 53.343990 Longitude: -6.267190 View: Google Map
alekberg.net	ok	IP: 133.167.212.25 Country: Japan Region: Tokyo City: Tokyo Latitude: 35.689507 Longitude: 139.691696 View: Google Map

DOMAIN	STATUS	GEOLOCATION
www.info.com	ok	IP: 8.47.69.0 Country: United States of America Region: California City: San Francisco Latitude: 37.775700 Longitude: -122.395203 View: Google Map
fp.us.tiktokv.com	ok	IP: 23.58.85.109 Country: Canada Region: British Columbia City: Vancouver Latitude: 49.249660 Longitude: -123.119339 View: Google Map
starling-sg.byteoversea.com	ok	IP: 212.188.39.57 Country: Russian Federation Region: Moskva City: Moscow Latitude: 55.752220 Longitude: 37.615559 View: Google Map
relaxng.org	ok	IP: 185.199.108.153 Country: United States of America Region: Pennsylvania City: California Latitude: 40.065632 Longitude: -79.891708 View: Google Map
dns.levonet.sk	ok	IP: 109.236.120.2 Country: Slovakia Region: Presovský kraj City: Levoca Latitude: 49.021729 Longitude: 20.592119 View: Google Map
content-autofill.googleapis.com	ok	IP: 216.239.34.223 Country: United States of America Region: California City: Mountain View Latitude: 37.405991 Longitude: -122.078514 View: Google Map

DOMAIN	STATUS	GEOLOCATION
kody.poczta-polska.pl	ok	IP: 45.60.74.15 Country: United States of America Region: California City: Redwood City Latitude: 37.532440 Longitude: -122.248833 View: Google Map
ssl.pstatic.net	ok	IP: 2.20.254.120 Country: Russian Federation Region: Moskva City: Moscow Latitude: 55.752220 Longitude: 37.615559 View: Google Map
posta.hu	ok	IP: 194.88.45.136 Country: Hungary Region: Csongrad City: Csongrad Latitude: 46.713322 Longitude: 20.142420 View: Google Map
dummy.invalid	ok	No Geolocation information available.
rtc-access-sg.tiktokv.com	ok	IP: 95.101.133.50 Country: Sweden Region: Stockholms lan City: Stockholm Latitude: 59.332581 Longitude: 18.064899 View: Google Map
www.privacywall.org	ok	IP: 150.171.109.101 Country: United States of America Region: Washington City: Redmond Latitude: 47.682899 Longitude: -122.120903 View: Google Map

DOMAIN	STATUS	GEOLOCATION
www.tiktok.com	ok	IP: 212.188.39.25 Country: Russian Federation Region: Moskva City: Moscow Latitude: 55.752220 Longitude: 37.615559 View: Google Map
www.oasis-open.org	ok	IP: 104.21.49.97 Country: United States of America Region: California City: San Francisco Latitude: 37.775700 Longitude: -122.395203 View: Google Map
dawn.googlesource.com	ok	IP: 74.125.131.82 Country: United States of America Region: California City: Mountain View Latitude: 37.405991 Longitude: -122.078514 View: Google Map
publickeyservice.msmt.aws.privacysandboxservices.com	ok	IP: 34.98.114.124 Country: United States of America Region: Missouri City: Kansas City Latitude: 39.099731 Longitude: -94.578568 View: Google Map
go.onelink.me	ok	IP: 108.156.22.64 Country: United States of America Region: Washington City: Redmond Latitude: 47.682899 Longitude: -122.120903 View: Google Map
www.opt.nc	ok	IP: 202.87.129.166 Country: New Caledonia Region: Province Sud City: Noumea Latitude: -22.276310 Longitude: 166.457199 View: Google Map

DOMAIN	STATUS	GEOLOCATION
suggests.go.mail.ru	ok	IP: 95.163.58.189 Country: Russian Federation Region: Moskva City: Moscow Latitude: 55.752220 Longitude: 37.615559 View: Google Map
www.yandex.com.tr	ok	IP: 45.148.65.5 Country: Estonia Region: Harjumaa City: Tallinn Latitude: 59.436958 Longitude: 24.753531 View: Google Map
location-sg.byteintl.com	ok	IP: 95.101.133.16 Country: Sweden Region: Stockholms lan City: Stockholm Latitude: 59.332581 Longitude: 18.064899 View: Google Map
ep2.adtrafficquality.google	ok	IP: 142.251.38.65 Country: United States of America Region: California City: Mountain View Latitude: 37.405991 Longitude: -122.078514 View: Google Map
publickeyservice.pa.gcp.privacysandboxservices.com	ok	IP: 34.54.30.30 Country: United States of America Region: Texas City: Houston Latitude: 29.941401 Longitude: -95.344498 View: Google Map
icl.com	ok	No Geolocation information available.
www.in	ok	No Geolocation information available.

DOMAIN	STATUS	GEOLOCATION
chrome-devtools-frontend.appspot.com	ok	IP: 142.251.38.84 Country: United States of America Region: California City: Mountain View Latitude: 37.405991 Longitude: -122.078514 View: Google Map
rtc-sg.tiktokv.com	ok	IP: 95.101.133.50 Country: Sweden Region: Stockholms lan City: Stockholm Latitude: 59.332581 Longitude: 18.064899 View: Google Map
gvt1.com	ok	No Geolocation information available.
chromium.dns.nextdns.io	ok	IP: 45.142.246.128 Country: Russian Federation Region: Sankt-Peterburg City: Saint Petersburg Latitude: 59.894440 Longitude: 30.264170 View: Google Map
perpetto.dev	ok	IP: 216.239.38.21 Country: United States of America Region: California City: Mountain View Latitude: 37.405991 Longitude: -122.078514 View: Google Map
www.jerseypost.com	ok	IP: 209.251.252.9 Country: Jersey Region: Jersey City: Saint Helier Latitude: 49.183331 Longitude: -2.100000 View: Google Map

DOMAIN	STATUS	GEOLOCATION
dns.sb	ok	IP: 45.11.45.11 Country: Germany Region: Hessen City: Frankfurt am Main Latitude: 50.115520 Longitude: 8.684170 View: Google Map
doh.xfinity.com	ok	IP: 96.106.7.234 Country: United States of America Region: Illinois City: Naperville Latitude: 41.785858 Longitude: -88.147293 View: Google Map
doh.cox.net	ok	IP: 68.105.28.12 Country: United States of America Region: Florida City: Pensacola Latitude: 30.421310 Longitude: -87.216911 View: Google Map
issues.chromium.org	ok	IP: 173.194.221.138 Country: United States of America Region: California City: Mountain View Latitude: 37.405991 Longitude: -122.078514 View: Google Map
www.omniva.ee	ok	IP: 141.101.90.16 Country: France Region: Ile-de-France City: Paris Latitude: 48.853409 Longitude: 2.348800 View: Google Map
publickeyservice.msmt.gcp.privacysandboxservices.com	ok	IP: 34.49.23.1 Country: United States of America Region: Texas City: Houston Latitude: 29.941401 Longitude: -95.344498 View: Google Map

DOMAIN	STATUS	GEOLOCATION
api-va.tiktokv.com	ok	IP: 95.101.133.50 Country: Sweden Region: Stockholms lan City: Stockholm Latitude: 59.332581 Longitude: 18.064899 View: Google Map
my-pac-script.invalid	ok	No Geolocation information available.
javax.xml.xmlconstants	ok	No Geolocation information available.
oceanhero.today	ok	IP: 216.150.16.129 Country: Canada Region: Ontario City: Etobicoke Latitude: 43.623768 Longitude: -79.559723 View: Google Map
bugs.chromium.org	ok	IP: 64.233.161.121 Country: United States of America Region: California City: Mountain View Latitude: 37.405991 Longitude: -122.078514 View: Google Map
www.interpretation	ok	No Geolocation information available.
c.youtube.com	ok	No Geolocation information available.
braintreepayments.com	ok	IP: 151.101.67.1 Country: United States of America Region: California City: San Francisco Latitude: 37.775700 Longitude: -122.395203 View: Google Map
model.txt	ok	No Geolocation information available.

DOMAIN	STATUS	GEOLOCATION
secure.soundcloud.com	ok	IP: 13.33.235.59 Country: Spain Region: Madrid, Comunidad de City: Madrid Latitude: 40.416500 Longitude: -3.702560 View: Google Map
gcp.gvt6.com	ok	No Geolocation information available.
www.cambodiapost.post	ok	IP: 103.16.62.46 Country: Cambodia Region: Phnom Penh City: Phnom Penh Latitude: 11.562450 Longitude: 104.916008 View: Google Map
www.epost.go.kr	ok	IP: 211.250.131.141 Country: Korea (Republic of) Region: Seoul-teukbyeolsi City: Seoul Latitude: 37.568260 Longitude: 126.977829 View: Google Map
bhutanpost.bt	ok	IP: 202.144.128.131 Country: Bhutan Region: Thimphu City: Thimphu Latitude: 27.466089 Longitude: 89.641907 View: Google Map
www.gstatic.com	ok	IP: 142.251.38.67 Country: United States of America Region: California City: Mountain View Latitude: 37.405991 Longitude: -122.078514 View: Google Map

DOMAIN	STATUS	GEOLOCATION
ac.search.naver.com	ok	IP: 223.130.192.99 Country: Korea (Republic of) Region: Gyeonggi-do City: Seongnam Latitude: 37.438610 Longitude: 127.137779 View: Google Map
www.buscacep.correios.com.br	ok	IP: 201.48.198.42 Country: Brazil Region: Distrito Federal City: Brasilia Latitude: -15.779720 Longitude: -47.929722 View: Google Map
de.search.yahoo.com	ok	IP: 212.82.100.137 Country: Ireland Region: Dublin City: Dublin Latitude: 53.343990 Longitude: -6.267190 View: Google Map
suggest.yandex.by	ok	IP: 213.180.204.63 Country: Russian Federation Region: Moskva City: Moscow Latitude: 55.752220 Longitude: 37.615559 View: Google Map
www.paypalobjects.com	ok	IP: 151.101.7.1 Country: United States of America Region: California City: San Francisco Latitude: 37.775700 Longitude: -122.395203 View: Google Map
pasts.lv	ok	IP: 8.47.69.0 Country: United States of America Region: California City: San Francisco Latitude: 37.775700 Longitude: -122.395203 View: Google Map

DOMAIN	STATUS	GEOLOCATION
www.rfc-editor.org	ok	IP: 8.47.69.0 Country: United States of America Region: California City: San Francisco Latitude: 37.775700 Longitude: -122.395203 View: Google Map
api.yep.com	ok	IP: 8.6.112.0 Country: United States of America Region: Texas City: Dallas Latitude: 32.783058 Longitude: -96.806671 View: Google Map
policy.public.dns.ijj.jp	ok	IP: 160.13.190.102 Country: Japan Region: Tokyo City: Tokyo Latitude: 35.689507 Longitude: 139.691696 View: Google Map
c.sandbox.paypal.com	ok	IP: 199.232.175.1 Country: United States of America Region: California City: San Francisco Latitude: 37.775700 Longitude: -122.395203 View: Google Map
bugs.lvm.org	ok	IP: 54.67.122.174 Country: United States of America Region: California City: San Francisco Latitude: 37.774929 Longitude: -122.419418 View: Google Map
ch.search.yahoo.com	ok	IP: 212.82.100.137 Country: Ireland Region: Dublin City: Dublin Latitude: 53.343990 Longitude: -6.267190 View: Google Map

DOMAIN	STATUS	GEOLOCATION
webaddress.elided	ok	No Geolocation information available.
tr.search.yahoo.com	ok	IP: 212.82.100.137 Country: Ireland Region: Dublin City: Dublin Latitude: 53.343990 Longitude: -6.267190 View: Google Map
www.post.gov.tw	ok	IP: 175.98.173.167 Country: Taiwan (Province of China) Region: Taipei City: Taipei Latitude: 25.047760 Longitude: 121.531853 View: Google Map
ns.google.com	ok	IP: 216.239.32.10 Country: United States of America Region: California City: Mountain View Latitude: 37.405991 Longitude: -122.078514 View: Google Map
beacons.gcp.gvt2.com	ok	IP: 64.233.163.94 Country: United States of America Region: California City: Mountain View Latitude: 37.405991 Longitude: -122.078514 View: Google Map
search.privacywall.org	ok	IP: 150.171.109.100 Country: United States of America Region: Washington City: Redmond Latitude: 47.682899 Longitude: -122.120903 View: Google Map

DOMAIN	STATUS	GEOLOCATION
docs.rs	ok	IP: 151.101.129.91 Country: United States of America Region: California City: San Francisco Latitude: 37.775700 Longitude: -122.395203 View: Google Map
search.naver.com	ok	IP: 110.93.154.71 Country: Korea (Republic of) Region: Gyeonggi-do City: Seongnam Latitude: 37.438610 Longitude: 127.137779 View: Google Map
lf19-effect.tiktokcdn-us.com	ok	IP: 146.75.34.73 Country: Sweden Region: Vstra Gotalands lan City: Goeteborg Latitude: 57.707161 Longitude: 11.966790 View: Google Map
sug.so.360.cn	ok	IP: 36.99.172.202 Country: China Region: Zhejiang City: Hangzhou Latitude: 30.293650 Longitude: 120.161423 View: Google Map
services.ukrposhta.com	ok	No Geolocation information available.
kagisuggest.com	ok	IP: 34.36.67.198 Country: United States of America Region: Texas City: Houston Latitude: 29.941401 Longitude: -95.344498 View: Google Map

DOMAIN	STATUS	GEOLOCATION
support.posti.fi	ok	IP: 13.33.235.32 Country: Spain Region: Madrid, Comunidad de City: Madrid Latitude: 40.416500 Longitude: -3.702560 View: Google Map
www.alandpost.ax	ok	IP: 76.76.21.61 Country: United States of America Region: California City: Walnut Latitude: 34.015400 Longitude: -117.858223 View: Google Map
www.wencodeuricomponent	ok	No Geolocation information available.
10.0.2.2	ok	IP: 10.0.2.2 Country: - Region: - City: - Latitude: 0.000000 Longitude: 0.000000 View: Google Map
oauth2.googleapis.com	ok	IP: 142.251.1.95 Country: United States of America Region: California City: Mountain View Latitude: 37.405991 Longitude: -122.078514 View: Google Map
www.baidu.com	ok	IP: 103.235.46.115 Country: Hong Kong Region: Hong Kong City: Hong Kong Latitude: 22.285521 Longitude: 114.157692 View: Google Map

DOMAIN	STATUS	GEOLOCATION
www.nona.de	ok	IP: 116.203.55.73 Country: Germany Region: Bayern City: Gunzenhausen Latitude: 48.323330 Longitude: 11.601220 View: Google Map
oneunita.com	ok	IP: 184.86.103.95 Country: Germany Region: Hessen City: Frankfurt am Main Latitude: 50.115520 Longitude: 8.684170 View: Google Map
www.css	ok	No Geolocation information available.
doh.dns.sb	ok	IP: 78.142.193.53 Country: Netherlands Region: Noord-Holland City: Duivendrecht Latitude: 52.329411 Longitude: 4.939640 View: Google Map
ml.byteintl.net	ok	IP: 10.8.112.201 Country: - Region: - City: - Latitude: 0.000000 Longitude: 0.000000 View: Google Map
www.svgpost.gov.vc	ok	IP: 23.170.80.10 Country: - Region: - City: - Latitude: 0.000000 Longitude: 0.000000 View: Google Map

DOMAIN	STATUS	GEOLOCATION
yandex.com.tr	ok	IP: 45.148.65.5 Country: Estonia Region: Harjumaa City: Tallinn Latitude: 59.436958 Longitude: 24.753531 View: Google Map
dns10.quad9.net	ok	IP: 9.9.9.10 Country: United States of America Region: California City: Berkeley Latitude: 37.879318 Longitude: -122.265205 View: Google Map
yep.com	ok	IP: 8.47.69.0 Country: United States of America Region: California City: San Francisco Latitude: 37.775700 Longitude: -122.395203 View: Google Map
cdn.search.brave.com	ok	IP: 3.164.206.28 Country: United States of America Region: Washington City: Seattle Latitude: 47.627499 Longitude: -122.346199 View: Google Map
mon.isnssdk.com	ok	IP: 71.18.222.1 Country: United States of America Region: Massachusetts City: Burlington Latitude: 42.508480 Longitude: -71.201134 View: Google Map
crbug.com	ok	IP: 216.239.32.29 Country: United States of America Region: California City: Mountain View Latitude: 37.405991 Longitude: -122.078514 View: Google Map

DOMAIN	STATUS	GEOLOCATION
model.bin	ok	No Geolocation information available.
accounts.google.com	ok	IP: 173.194.222.84 Country: United States of America Region: California City: Mountain View Latitude: 37.405991 Longitude: -122.078514 View: Google Map
sapp.s	ok	No Geolocation information available.
www.bluetooth.com	ok	IP: 35.184.1.175 Country: United States of America Region: Iowa City: Council Bluffs Latitude: 41.261940 Longitude: -95.860832 View: Google Map
www.codigopostal.gob.pe	ok	IP: 200.62.243.18 Country: Peru Region: Lima City: Lima Latitude: -12.043333 Longitude: -77.028336 View: Google Map
www.recent	ok	No Geolocation information available.
www.correo.com.uy	ok	IP: 179.27.60.69 Country: Uruguay Region: Montevideo City: Montevideo Latitude: -34.833462 Longitude: -56.167351 View: Google Map
yandex.kz	ok	IP: 45.138.0.2 Country: Netherlands Region: Flevoland City: Dronten Latitude: 52.525002 Longitude: 5.718060 View: Google Map

DOMAIN	STATUS	GEOLOCATION
open-ap-singapore-1.bytevcloudapi.com	ok	IP: 80.239.254.32 Country: Sweden Region: Stockholms lan City: Stockholm Latitude: 59.332581 Longitude: 18.064899 View: Google Map
www.canadapost.ca	ok	IP: 13.33.235.126 Country: Spain Region: Madrid, Comunidad de City: Madrid Latitude: 40.416500 Longitude: -3.702560 View: Google Map
www.c	ok	No Geolocation information available.
staticcdn.duckduckgo.com	ok	IP: 40.114.178.124 Country: Netherlands Region: Noord-Holland City: Amsterdam Latitude: 52.374031 Longitude: 4.889690 View: Google Map
yandex.ru	ok	IP: 77.88.44.55 Country: Russian Federation Region: Moskva City: Moscow Latitude: 55.752220 Longitude: 37.615559 View: Google Map
mon-va.tiktokv.com	ok	IP: 71.18.222.1 Country: United States of America Region: Massachusetts City: Burlington Latitude: 42.508480 Longitude: -71.201134 View: Google Map

DOMAIN	STATUS	GEOLOCATION
dev.chromium.org	ok	IP: 199.36.158.100 Country: United States of America Region: California City: Mountain View Latitude: 37.405991 Longitude: -122.078514 View: Google Map
suggest.panda-search.org	ok	IP: 35.201.116.236 Country: United States of America Region: Missouri City: Kansas City Latitude: 39.099731 Longitude: -94.578568 View: Google Map

EMAILS

EMAIL	FILE
safeloggingrunnable@c83c.run	X/C19XE.java
aredpreferencesqueue@d01a.syncstatea	X/C1297940jsn.java
fixexecutorwrapper@c421.runtask	X/ExecutorServiceC1547030qMY.java
reporterrunnable@2e79.run	X/C286890BMq.java
default@email.com	X/C215500sU.java
livecoreimpl@e164.pushrtcsei	X/C1036660d5N.java
asselfiescanfragment@f36d.onmanualca checkoutprocess@fad.presentpim checkouthomekt@de1b.checkoutho 4camerapreview@5543.initcamera 0detailviewmodel@e36a.onclickpre ailablemethodspagekt@df6.availablen billhomeviewmodel@7c13.load paymentconfig@4a3b.initstarli reetfillercontroller@1e6f.onvaluecha veritasidvcameraview@3351.downgradem baseviewmodel@a8bd.loadcashie addressviewmodel@1396.synchroniz mentprepareviewmodel@97b5.getrepayme	

pimanagementkt@49.handlenavi EMAILreviewmodel@7c13.loadcustom asselfiescanfragment@f36d.showcamera	FILE
baseviewmodel@a8bd.initnoncet payment@a405.presentpim echeckoutviewmodel@de26.startpolli icontextcard@cb18.onbindview tainerassemviewmodel@65ad.createsubc piviewmodel@e244.deletestor piviewmodel@e244.storepayme puxtoastkt@4a5b.puxtoast andingcontainerassem@e692.presentbut asselfiescanfragment@f36d.oncapturer ritasidvscanfragment@17f6.onviewcrea ritasidvscanfragment@17f6.doupdate dcamerapreview@5543.createcame payresultpagekt@ebf8.payresultp ogressassemviewmodel@10f5.getinstitu +repaymentviewmodel@2076.presentche reementsignviewmodel@4cbe.signagreem animationcontroller@2ab.dismiss 0landingassemvm@e5ad.createcred +baseviewmodel@a8bd.showgenera cardnumbercontroller@eba5.debounce checkoutviewmodel@de26.closecheck 2repaymentviewmodel@daf6.onpreparer asselfiescanfragment@f36d.doliveness example@email.com tainerassemviewmodel@65ad.signagreem detailviewmodel@e36a.onloadmore kycnfcscanningassem@2bbe.showreadyt itasselfiecameraview@347f.downgradem ritasidvscanfragment@17f6.onresume rationdatecontroller@a578.validatewi puxdialogkt@8092.dialogcont piviewmodel@e244.checkbinds tainerassemviewmodel@65ad.requestreg checkoutbarkt@7ee0.checkoutba noncecontainer@4140.getnonce 9checkoutprocess@fad.presentpim pimanagementkt@49.pimanageme andingcontainerassem@e692.initcontai addressviewmodel@1396.preparedat baseviewmodel@a8bd.isnetworka formskt@ec82.forms +checkoutcontainerkt@7c59.handlenavi piviewmodel@e244.getpibasic ritasidvscanfragment@17f6.downgrader +checkoutactivity@41a1.showcompos stagreementviewmodel@417d.getagreeme tainerassemviewmodel@65ad.recordcl ritasidvwelcomeassem@6b26.sessiontim bnplcommonpopup@7d4b.sendreques postartnfcscanmethod@d0e8.handle nfcscanningviewmodel@a548.startnfcsc repaymentviewmodel@2076.getnonce ritasidvscanfragment@17f6.onmanualca	

checkoutviewmodel@de26.pay EMAIL numberkt@d397.oncountryc ndwallerlandingassem@7d5c.handleclie	FILE
ycnfcscanningassemv2@7418.showreadyt 2bindcontainerkt@813f.showbindpa piviewmodel@e244.saveasprim 4detailviewmodel@e36a.onclickpre -checkoutactivity@41a1.showcompos asselfiescanfragment@f36d.sessiontim cscanningviewmodelv2@eb11.handlescan checkouthomekt@de1b.imespaceho -camerapreview@5543.initcamera piviewmodel@e244.redirectha ndpaymentmethodnavkt@cf39.navigation tainerassemviewmodel@65ad.createcred ogressassemviewmodel@10f5.getroutein .bnplentryviewmodel@c16.getstepcod apiservice@bd9b.getstarlin tuxdialogkt@608c.tuxdialogc reetfillercontroller@1e6f.debounce ogressassemviewmodel@10f5.createsubc addressviewmodel@1396.ondone reetfillercontroller@1e6f.onfocuscha 3clientaicameraview@ec4c.processfra buttoncard@7e9c.handledata -checkoutviewmodel@de26.storepayme creaselimitviewmodel@9cba.submit bottomsheetkt@3e26.bottomshee ignagreementfragment@3451.onviewcrea animationcontroller@2ab.show selectpikt@1283.selectpi ritasidvsanfragment@17f6.sessiontim +checkoutviewmodel@de26.storepayme selectassemblepikt@73eb.selectasse repaymentviewmodel@daf6.loopforres asselfiescanfragment@f36d.doimageupl bizdataholder@86cc.getconfigu repaymentviewmodel@daf6.load repaymentviewmodel@2076.initpaymen ritasidvsanfragment@17f6.showcamera 1addressviewmodel@1396.synchroniz checkoutprocess@fad.getnonce fcscanningfragmentv2@4475.onviewcrea 4checkoutviewmodel@de26.startpolli checkoutviewmodel@de26.initmethod nfcscanningviewmodel@a548.handlescan baseviewmodel@a8bd.requeststa checkoutviewmodel@de26.getpayment piviewmodel@e244.launchbind ogressassemviewmodel@10f5.createmain pimanagementkt@49.cardlist cscanningviewmodelv2@eb11.startnfcsc piviewmodel@e244.getpimanag retrykt@6b9c.retry landingassemvm@e5ad.signagreem asselfiescanfragment@f36d.downgrader piviewmodel@e244.havestored	apktool_out/lib/arm64-v8a/libdex_df_pipo_bnpl.so

checkoutviewmodel@de26.storepayme EMAIL kt@ec82.forms postalcodecontroller@cdhb.synchroniz	FILE
ritasidvscanfragment@17f6.oncapturer cnfscanningactivity@ca29.setupbotto configuration@2711.getidempot .camerapreview@5543.initcamera -checkoutcontainerkt@7c59.handlenavi ycnfscanningassemv2@7418.onviewcrea outbackinterceptortkt@9a2b.showclosed 1billhomeviewmodel@7c13.onpreparer ogressassemviewmodel@10f5.decideuser reetfillercontroller@1e6f.onclick payment@a405.presentche -addressviewmodel@1396.initdatafo statementsviewmodel@5867.onrefresh phonenumbertkt@d397.oncountryc ndpaymentmethodnavkt@cf39.bindpaymen .bindcontainerkt@813f.showbottom .repaymentviewmodel@daf6.onpreparer animationcontroller@2ab.startanima fieldcontroller@7de7.validatewi 1clientaicameraview@ec4c.handlecapt cardnumbercontroller@eba5.onvaluecha pipoclientaimanager@79c1.prefetch addressviewmodel@1396.fetchdata repaymentviewmodel@2076.presentche clientaicameraview@ec4c.handlecapt fcscanningfragmentv2@4475.onnewisode livenesscheckhelper@23d.livenessch fcscanningfragmentv2@4475.oncreatevi ritasidvscanfragment@17f6.doimageupl repaymentassem@956f.scrolltobo tuxtoastkt@aeed.tuxtoast -billhomeviewmodel@7c13.onpreparer asselfiescanfragment@f36d.doupdate addressviewmodel@1396.datainitia asselfiescanfragment@f36d.permission asselfiescanfragment@f36d.releaseres creaselimitviewmodel@9cba.presubmit piviewmodel@e244.closebinds ritasidvscanfragment@17f6.releaseres asselfiescanfragment@f36d.onviewcrea bnplentryviewmodel@c16.getstepcod landingassemvm@e5ad.requestreg rogressanimationview@4d84.initstepvi piviewmodel@e244.dealbindre ritasidvscanfragment@17f6.permission baseviewmodel@a8bd.getnoncewi tainerassemviewmodel@65ad.decideuser +baseviewmodel@a8bd.shownetwor piviewmodel@e244.cancelaspr piviewmodel@e244.initmethod cardnumbertkt@6a2f.cardnumber bnplcommonpopup@7d4b.onapierror ogressassemviewmodel@10f5.signagreem clientaicameraview@ec4c.ongetnewim	

EMAIL	FILE
nmolifecycleobserver@fb35.onstatecha paypalsdkprocess@6938.clear +httpclient@bac3.notifysucc pallifecycleobserver@fa45.onstatecha httpclient@bac3.notifyerro httpclient@bac3.schedule	apktool_out/lib/arm64-v8a/libdex_df_pipo_external_payments.so
appro@openssl.org	apktool_out/lib/arm64-v8a/libtt_c2pa_sdk_d.so
appro@openssl.org	apktool_out/lib/arm64-v8a/libtt_c2pa_sdk.so
ffmpeg-devel@ffmpeg.org	apktool_out/lib/arm64-v8a/libttvesdk_plugin.so
.ilililili@7cb8.onsurfacet iiililili@5021.run ilililili@e761.run linkccdcocrviewmodel@5bad.restarttim lilililil@7742.run ardoverlaycontroller@1499.liililili innerreticleview@c576.ilililili ilililil@2f90.liililil llililili@f61d.run ilililil@c351.run tooltipmanager@42cd.showtoolti lilililil@9dcb.run ardoverlaycontroller@1499.ilililili llililil@3a5c.ilililil liililil@c4a4.run liililili@aef1.run llililil@3a5c.liililil innerreticleview@c576.ilililil llililili@66.liililil liililili@66.ilililil iiililil@41e6.liililil llililil@3b67.run ilililili@ad44.run ilililil@2f90.liililil blinkccdcocractivity@a0d7.initview .ilililil@2341.onsurfacet progressview@d1bc.ilililil llililil@3a5c.ilililil llililil@3a5c.ilililil llililil@8193.onshakings ilililili@abc1.run llililil@54ad.run ilililili@7cb8.onsurfacet linkccdcocrviewmodel@5bad.frontsides llililil@3a5c.liililili llililil@38b7.run llililil@3a5c.dispose snackbarmanager@7b73.liililil iiililili@48d.run	apktool_out/lib/arm64-v8a/libdex_df_ccdc_impl_ocr.so

EMAIL	FILE
nliliilil@7584.com_microb snackbarmanager@42cd.hidetoolti ilililil@419e.ilililil rdreticleoverlayview@d3ea.createlayo ilililil@5a54.onpicturet ilililil@96bf.run nlilililil@396d.com_microb ililililil@a68a.surfacecha ililililil@c56c.run snackbarmanager@7b73.ilililili ilililil@a728.onimageava ilililil@3a5c.ililililil rdreticleoverlayview@d3ea.changestat ilililil@6eaf.run 3@1fe5.run ililililil@2f90.ilililili ardoverlaycontroller@1499.ilililil Odebugviewhandler@3d30.initialize ilililil@7584.run ililililil@904d.run rdreticleoverlayview@d3ea.ilililil ililililil@caaf.run ililililil@9cd3.run ililililil@d9d.run ililililil@4550.run progressview@d1bc.ilililili 3@a98.run ililililil@4526.run ililililil@2341.onsurfacet ililililil@189d.run ililililil@396d.run ililililil@396d.ilililili ililililil@cc66.run ililililil@2f90.dispose ililililil@9821.run	
styleselectcomponent@eeed.getselects ttliquefyviewmodelv2@3195.applyclear secondobjectfragment@25bf.initdata hsladjustfragment@cc19.cancelvalu opickpanelguidescene@80d3.initviews viourpreviewfragment@b187.initaction sthitsviewController@3138.bindobserv allfragmentviewmodel@c61.downloadpi bverticalmusicview@a7b8.buildcolle jarvis@b146.init seteditpagecomponent@a788.oncreate keffecteditorcontext@5cb5.ttdoaftere ostdeleteserviceimpl@ec46.delete enscreenfuncprovider@4094.switchreal ganviewmodel@586e.removeface bbottombarcontroller@48f3.setupleftb ntiputilskt@10d0.dowhenloca Oeventtrackingextkt@d694.sendeventt tiktokgifrepository@f767.trendgifs facestretchfragment@cdc6.initview	

eprogresscoordinator@b04d.syncrelas EMAIL layerfragment@d93c.calculatea ttpromotionviewmodel@b3db.selectprom	FILE
0prefabeditviewmodel@58ec.compresssh .amestickertab@f726.preloadmat cefusionfuncprovider@d4bb.addfusion +nowlikeviewmodel@da60.handlenowp 6filteredassetpool@8672.getassetsw seteditpagecomponent@a788.launchscen creendataresprovider@2dc8.preloadgre archloadingcomponent@a395.observewor amecorepresenterimpl@6f97.launchawai amedbinitwavetask@901c.run ffectimgcropfragment@6e89.startloadi 0ameautocutoutrepo@8606.chaincallb faceinsetresflowimpl@5b2e.obtainaddf makeupviewmodel@3113.initfeatur amakeuppagefragment@9516.observedat makeupviewmodel@3113.updateload eampipelineexecution@1e2.processnod mstickerpagefragment@e4f5.initobserv canvasactionlistener@ff32.ondoublecl elactionreportheper@7a1f.onoperatio atorofficialrepoimpl@eb36.reqofficia ckcliprailpanelscene@f69d.loadingrot ecutoutpanelfragment@2aad.gotosticke acestretchrepository@575f.apply styleselectcomponent@eeed.downloadst sealbumpickermirror@9b40.changeload alicondirlistadapter@f848.onbindview ecutoutpanelfragment@2aad.gotomediad canvasactionlistener@ff32.singletap modelselectcomponent@ef2b.downloadmo eaimattingresfetcher@5768.loadmattin enstyleresultmanager@35df.showloadin aimetabviewmodel@6323.loginload inpreviewtitlewidget@434a.updaterend fbaseiconlistadapter@8bdc.onbindview iganpanelfragment@9fd9.bindseekba stickerguidefragment@1ac2.onlytipsca localconfigsfragment@720d.submitlist al@737.run imestylepreviewscene@1044.handlesucc editpreviewviewmodel@f9a1.fetchuserp dganpanelfragment@9fd9.initview stickerresflowimpl@8b68.preloadadd amemusictab@d8c.showmusicn tgreenscreenhelperv1@b92c.gengreensc 3ganviewmodel@586e.onfacefusi cutoutcanvasfragment@a1bc.initobserv creendataresprovider@2dc8.downloadgr ti2iloadcomponent@5889.msgcenterl customizeviewmodelv2@83ed.performgen carouselplayerview@e8e0.applycente prefabviewmodel@5840.fetchlokup taskrepositoryimpl@c0e3.getaigtas ckerguideserviceimpl@2357.startstick	

gifsfragment@3c5.addgifstic EMAILguidefragment@b009.preloadalp eampipelineexecution@1e2.emit	FILE
drafthandler@f1f0.showsavadr inpreviewmusicwidget@e63e.onconfigur seteditpagecomponent@a788.prehandlel ganpanelfragment@9fd9.initdata epreupgradedrafttask@a3b4.preupgrade -amecutouttab@330b.gotomediac -amenewflowtexttab@32b6.handleedit ltiponboardingv3node@2b24.launchpane slistpanelcontroller@51da.handleitem texteditpagescreenkt@f833.textinputi prefabviewmodel@5840.preloadow gifsviewmodel@472a.loadmoregi aiselfcarouselkt@ac9a.autoscroll verseclusterstrategy@91c8.dogenerate perfintervalmonitor@6311.run wcaptioneditfragment@3c1b.initeditvi 0facefusionrepo@41cc.loadfacefu amecovereditfragment@1c20.initview cutoutbottomfragment@2b85.observevie ttlquefyviewmodelv2@3195.initfollow objectcontainer@a25.build hprefabeditfragment@56ec.observecan componentviewmodelv2@695f.performsuc bytebenchv2@5dc8.reportresu stprefabpagefragment@a912.getlayerdi drafthandler@f1f0.handleconf 2aimetrystylemanager@6ec4.shouldshow itionstatustextassem@b2f.startdotup 1ganviewmodel@586e.onmediasel edgeflowmanager@9681.initialize aimetabviewmodel@6323.loadmore tickersearchfragment@bb76.addorrepla ewpager2heighthelper@f55d.pagechange tiktogifrepository@f767.searchgifs ltiponboardingv3node@2b24.registerpa imagecutoutviewmodel@497d.clearstep ameupgradedrafttask@e63f.run gtoolseditcontroller@c679.compressbi eatorstickerfragment@a9ce.observesea faceinsetresflowimpl@5b2e.obtainface imagecutoutviewmodel@497d.intercepts assetreverseproducer@54de.getcluster dataeventreceiverpro@8b02.ondataeven +ganviewmodel@586e.flushfacef otionrouterprocessor@713a.process scenemonitor@e338.stopintern ffectentranceservice@55a.isaifeatur facefusionrepo@41cc.changefusi creatorlayerfragment@d676.initlisten ttlquifyfragmentv2@52bb.onattach packagefetchwavetask@bf55.run ramepreviewcomponent@482.startgener ganviewmodel@586e.createfeat 6makeupviewmodel@3113.selectfirs	

acefusionresprovider@cfcf.preload EMAIL fragment@9411.initaction perintervalmonitor@6311.flush	FILE
effectdraftcomponent@138b.savei2vdra editpreviewviewmodel@f9a1.updateaise autopicksession@14df.awaitnexts 6prefabpagefragment@feb3.observadat inpreviewtitlewidget@434a.setviewloc feaimenetworkapiimpl@b2d9.getaimerec 5autopicksession@14df.launchstra enscreenfuncprovider@4094.updategree ltiponboardingv3node@2b24.registerro ganviewmodel@586e.changefusi canvasactionlistener@ff32.onscale zemonitorserviceimpl@c952.fetcheffec ttliquefyviewmodelv2@3195.initautoch gslispanelviewmodel@c975.changeport aimeservicesimpl@2ffe.fetchaisel eatorstickerfragment@a9ce.initview bytebenchv2@5dc8.stop phasestackview@ebdd.animatepha eselectpagecomponent@f889.sceneactio qlambda@f73a.run aimetabviewmodel@6323.loadinitia drafthandler@f1f0.getdraftsi orstickerpageadapter@f578.bindfuncit faceinsetresflowimpl@5b2e.applyfacei verecordhelper@7eb6.effecthand musictrimviewmodel@3254.getmusicwa imakeuppanelfragment@e4b6.initdata animationviewmodel@e3f4.initfeatur amecovereditfragment@1c20.initchoose languageodeltask@fc90.downloadre editloadingcomponent@f330.oncreate iquefyv2pagefragment@4341.initshowde iprailpanelcomponent@65e4.checktaskr aimeservicesimpl@2ffe.createaime .makeupviewmodel@3113.shownotcon ti2iloadcomponent@5889.starti2ilo orstickerpageadapter@f578.onbindview ualframepreviewscene@5c67.changefram ewpager2heighthelper@f55d.requesthei templateapplyoldflow@8f3d.upgradedra modelpreloadwavetask@8ac2.run ionlatesthitsadapter@788a.onbindview tretchpersistentimpl@595d.deletefile gifsfragment@3c5.observadat nowpostvideoassem@41aa.onhostdest emegenerationservice@ce2d.generateth aistylesfetcher@6d7b.fetchstyle atorstickerviewmodel@4254.requestrec rtoofficialrepository@5713.request 3prefabviewmodel@5840.loadeffect prefabpanelfragment@ff3c.initview facestretchviewmodel@bd65.setisfaces aimeservicesimpl@2ffe.hasaiself makeupviewmodel@3113.emitsucces	

+makeupresfetcher@9b27.fetchmakeu EMAIL: rouselkt@ac9a.carousel nowbaselistassem@a120.setlistpad	FILE
officialiconutilskt@8545.loadoffici ourcedownloadnewimpl@4e8a.startcoldb mecovereditviewmodel@c5c4.init facestretchviewmodel@bd65.applyeffec dotmatrixviewkt@eccf.dotmatrixv ameimagecutouteditor@22c0.changeprev faceinsetresflowimpl@5b2e.changetrac imgautogeniconhelper@4893.genbmpbyof canvasactionlistener@ff32.ontoucheve makeupviewmodel@3113.generateai iprefabpanelfragment@ff3c.initview imenewcustomizescene@55e6.successgen objecteffecthandler@657f.inneraddst sictrimpanelfragment@bc06.initobserv deouploaduicomponent@4d62.oncreate nativescenemonitor@1ad6.stopintern 1ganviewmodel@586e.clearselec atorstickereditpanel@52bb.handlereed facestretchviewmodel@bd65.changeface omptenhancecomponent@5992.translatep iprailpanelcomponent@65e4.onaiautocu feaimenetworkapiimpl@b2d9.getaigcquo componentviewmodelv2@695f.handlecl aimelistrepo@d69d.getaimelis kprefabpagefragment@feb3.observedat ctcreatepipelineimpl@e2ca.onexportwh reupdateeventapiimpl@a3d.onfireeven 9aistyleresfetcher@6d7b.getstylera customdownloader@85b1.download +verticalmusicview@a7b8.getrecentm ttnewcreatorfragment@9077.delayloadi timewindowfilter@11c7.filter kloadingcontentscene@f88d.updateprog fectfeaturecomponent@168f.downloadre 6verticalmusicview@a7b8.getsearchm ortitlebarcontroller@3a4.registerli filteredassetpool@8672.getassets nowlikeviewmodel@da60.onclicklik ttnewcreatorfragment@9077.handleinfo eaimetabfragment@e8f3.checklogin videouploadcomponent@95e9.startuploa 8textstickerresflow@3f39.preloaddef ameimagecutouteditor@22c0.addaimatti archloadingcomponent@a395.showresult istadapterviewholder@1d11.bind viourcontentfragment@6376.compatoncl videouploadcomponent@95e9.pickvideo eocutoutplayfragment@c596.initview bytebenchv2@5dc8.loadtaskto ctcreatepipelineimpl@e2ca.logsavedra uefyprefabrepository@5cd4.getorcreat ctimgcreatorfragment@fc30.initlisten imestylepreviewscene@1044.checklogin .aimetabfragment@e8f3.setviewmod	

owdownloadbottomview@abfa.handler EMAIL barqueetextview@dc03.applymarqu editloadingcomponent@f330.regenerate	FILE
otoseditpagefragment@8917.restorese -aimetabfragment@e8f3.scrolltoto ttlquefyviewmodelv2@3195.startfaces 2collectmusicmanager@f40.loadcollec atorofficialrepoimpl@eb36.preloadran feaimenetworkapiimpl@b2d9.postaistyl makeupviewmodel@3113.launchaigc dialogcontentbuilder@336e.createdial lbumpickeralgoloader@82cb.getdetectm pickloadingcomponent@6ba2.submitnewt istadapterviewholder@50d.bind themeclusterproducer@ba79.producecan bannerviewcontroller@20d0.initobserv 1animationviewmodel@e3f4.onbehaviou cutoutcanvasfragment@a1bc.showtipifn longloadingpredictor@973f.predict runtimeevent@d9a0.record autopicksession@14df.start previewpagecomponent@e7db.onconfirmc aimetabviewmodel@6323.aihubclick facestretchviewmodel@bd65.setupforex companion@98eb.mergemodel nowlikeviewmodel@da60.handlenowp ganviewmodel@586e.onmediasel selector@9dcc.select bytebenchv2@5dc8.checktestr reparestagecomponent@58.repreparep objectpreparewavetask@36f5.run slistpanelcontroller@51da.back chestrationcomponent@b9ce.repick fyoriginalrepository@defb.followface .dynamichookhelper@e04c.switchtoma rcollectionlistassem@fdbd.onbind slistpanelcontroller@51da.oninit prefabviewmodel@5840.emiteditpr phaseitemholder@dd98.crossfadet amelaunchtask@d1f1.runasync jankframecollector@560d.stop tnewcreatorfragment@9077.onviewcrea imagecutoutviewmodel@497d.triggeraut eupexchangeviewmodel@7f33.updatemake customdownloader@5e04.download topickpanelcomponent@d649.savedrafta eaimattingresfetcher@5768.preloadmat ttiponboardingv3node@13d5.tryshowani iprailpanelcomponent@65e4.sam makeupviewmodel@3113.clearcateg ttlquefyviewmodelv2@3195.selectloca inspectoretutils@602c.reportgree ttlquefyviewmodelv2@3195.cancel otiontemplateadapter@7abb.onbindview 9amedebugfragment@39de.doinit languageodeltask@fc90.forward -prefabeditviewmodel@58ec.saveselect	

picklottedownloader@294b.downloadto EMAIL pagefragment@8917.updatealbu fectfeaturecomponent@168f.preloadloa	FILE
facestretchviewmodel@bd65.refreshkey componentviewmodelv2@695f.handlegene ctcreatepipelineimpl@e2ca.resolvecro baseclusterstrategy@860d.cvscan editpreviewviewmodel@f9a1.observerre prefabviewmodel@5840.clearselec gifsviemodel@472a.downloadgi fectfeaturecomponent@168f.applyprefa enscreenfuncprovider@4094.changetrac bfourpicturefragment@febe.mobdeletep stickerguidefragment@1ac2.registerob stickerselecthandler@50af.autochange lbummultiselectlogic@8114.bindholder +prefabviewmodel@5840.loadeffect rtofficialrepository@5713.createoffi imgautogeniconhelper@4893.applyeffec usionganpagefragment@5dee.initview .alphavideoscene@9f94.animlisten photostorehelper@25da.getphotodi +autopickpanelscene@9db7.adjustcove eratorstickerfragment@a9ce.parseselec amemodelpreloadtask@f983.modelprelo ckerfacefusionloader@46fb.load ltiponboardingv3node@2b24.tryshowani voicesearchviewmodel@8ed6.startdotup tylepreviewviewmodel@9526.getpagesta qpreviewmodeladapter@a893.onbindview textinittaskwavetask@c15a.run 0ganviewmodel@586e.applyfacef enstyleresultmanager@35df.openresult thememarqueetextview@dc03.ontextchan inpreviewtitlewidget@434a.onconfigur screenthumbgenerator@4b96.tryshotscr atorstickereditpanel@52bb.playmusicw romotionbottomdrawer@6faa.initview ecutoutpanelfragment@2aad.onactivity ttpreviewmodehandler@bae4.initprevie rsecondobjectadapter@a42d.onbindview normalhandlerimpl@927f.update fectpreviewviewmodel@ace0.regenerate 0ttlquifyfragmentv2@52bb.mobcategor stickerselecthandler@50af.selectobje ormigrateserviceimpl@95ca.awaitchang selectpanelcomponent@4222.fetchmodel 7nowsharebottomassem@8f07.sharebutto elfawemecachemanager@5c53.deletecach bprefabpanelfragment@ff3c.bindseekba ramepreviewcomponent@482.oncreate hsladjustfragment@cc19.initview localconfigsfragment@720d.observedat uefyprefabrepository@5cd4.eecreatefe ickeroperatefragment@36ad.initobserv autopickpanelscene@9db7.scheduleco fyoriginalrepository@defb.load	

EMAIL	FILE
imationpanelfragment@9f44.initview ameralaunchcomponent@a0cb.awaitpages viewlazyinittask@9248.run 1baseclusterstrategy@860d.dogenerate gridadapter@5c48.onbindview 4consumercoordinator@9d43.consumeava ickerrouterprocessor@1f13.process xtstickerinputlayout@542c.showinputl kttliquifyfragmentv2@52bb.initobserv amecorepresenterimpl@6f97.runvelaunc gpicturecropfragment@16c2.getstyleta ganpanelfragment@9fd9.initview cialiconlistfragment@1f25.startobser mainpackagefetchtask@1fcd.run picklotteddownloader@294b.downloadlo eeklyclusterstrategy@9057.dogenerate archloadingcomponent@a395.submitaigc ourcedownloadnewimpl@4e8a.startdownl ickrootslotcomponent@4cb3.showautopi stprefabpagefragment@a912.applyadju modelmanager@75cd.downloadmo ameprojectcreatetask@5356.run customizeviewmodel@8957.performapp tv2vreeditgroupscene@ac19.initobserv canvasactionlistener@ff32.oncornerdr onboardingv2cardview@b442.initpopove 2customizeviewmodel@8957.reportcl chestrationcomponent@b9ce.startautop meonboardingwavetask@78c8.run ganviewmodel@586e.fetchganli amevesdkinittask@222.run .draftupgradehelper@28d6.updatedraf mainpackagefetchtask@1fcd.needforceu normalhandlerimpl@927f.onscale editpreviewviewmodel@f9a1.discardcur nowcachedelegate@6dbd.ondeleteno ompatibilitytuxsheet@8c3.tasksimage 1facestretchfragment@cdc6.onconfigur lbumpickeruidelegate@b7b1.init ailfragmentviewmodel@c61.oncustomiz gcreatorcamerahelper@1908.opencamera componentpreparatask@b449.run facestretchfragment@cdc6.initobserv +makeupviewmodel@3113.loadeffect 2stickerresflowimpl@8b68.obtainaddf mfacestretchfragment@cdc6.initobserv ontouchdraghandler@960f.ontouch 5prefabeditviewmodel@58ec.notifycont slistpanelcontroller@51da.handlechan omptenhancecomponent@5992.innerreque meprojectpreparatask@6513.processdra ttpromotionfragment@f369.initview animationviewmodel@e3f4.loadeffect calendarmonthview@efb3.enableagai	

agifsfragment@3c5.initview EMAIL panelscene@9db7.tryexitloa odelpictureviewmodel@fa9c.loadmodell	FILE
ttnewcreatorfragment@9077.mpreviewti tictsearchfragment@bb76.replaceip makeupviewmodel@3113.selectedai fyoriginalrepository@defb.waiteffect tuspublishedrepoimpl@cbec.save2disk lbottombarcontroller@1f1b.setupright voicesearchhelper@9a5c.performvoi 0draftupdater@ff1a.updatedraf ultnavigationhandler@e1fd.navigateto ttnewcreatorfragment@9077.onconfigur onboardingv2fragment@d2c5.setdata -animationviewmodel@e3f4.clearselec imenewcustomizescene@55e6.associated ttlquefyviewmodelv2@3195.selectpref facestretchviewmodel@bd65.changeprev amestickertab@f726.handlelic bfourpicturefragment@febe.gosinglevi videocutoutviewmodel@ffde.removeback videocutoutviewmodel@ffde.updateprog autopickpanelscene@9db7.onshow previewpagecomponent@e7db.savedraft enscreenfuncprovider@4094.portraitcu +objecteffecthandler@657f.scopedadds econfigpagecomponent@842b.fetchstyle camebasetooltab@fb4c.attachcont qprefabeditfragment@56ec.observecon bytebenchv2@5dc8.start metricschecker@577.run aichoosemusicmanager@da6d.downloadmu ti2ilodingcomponent@5889.commitgree ffectaudioscrollview@d2a5.startscrol editpreviewviewmodel@f9a1.loadmodelp aycomponentviewmodel@715b.performpol ttnewcreatorfragment@9077.observedou bgifsfragment@3c5.observedat inpreviewtitlewidget@434a.calculatea fectdownloaderhelper@3320.localdownl 9collectmusicmanager@f40.loadmoreco ganviewmodel@586e.oncommitup 2aistyleresfetcher@6d7b.getstylera eatoralbumfragmentv2@90fe.initlisten refabsublistloadtask@dbe7.run .ganviewmodel@586e.createganv amecorerepresenter@ee9a.prepareeres bfourpicturefragment@febe.onviewcrea isdayclusterstrategy@81e2.scanyearcl imakeuppagefragment@9516.observedat secondobjnormalrepo@d5b7.fetchpanel amevideocutoutplayer@403b.setmatting -widgetlocationimpl@5c3c.recordpane statistichelper@8108.onevent nowmediacachemanager@3ec6.deletetecach 1nowareamonitorassem@4391.sam gpicturecropfragment@16c2.initcropvi	

6baseclusterstrategy@860d.loadfilter EMAILdhelper@7eb6.initvereco texteditactivity@468a.update	FILE
.ganviewmodel@586e.loadfacefu rtoofficialrepository@5713.onofficial ttlquefyviewmodelv2@3195.done drafhandler@f1f0.openpublis ffectimgcropfragment@6e89.initlisten lreeditpaneladapter@da98.bindselect otiondataresprovider@6cc3.fetchbanne gcreatorcamerahelper@1908.init languagemodeltask@fc90.preloadint uctcomponentwavetask@509e.run aimakeuprepo@5ae4.loadaimake pickloadingcomponent@6ba2.observechi asrstreamtask@8422.createinit facestretchviewmodel@bd65.changemirr ameupgradedrafttask@e63f.upgrade aganpanelfragment@9fd9.bindseekba omotionbanneradapter@6b1c.onbindview kganviewmodel@586e.onfacefusi delivery@5dd5.deliverloc drafhandler@f1f0.downloadic seteditpagecomponent@a788.downloadai -makeupviewmodel@3113.cancelgene reparestagecomponent@58.ensurestyl mganpanelfragment@9fd9.initphotop amecanvasadjustlogic@563a.adjustamec 7normalhandlerimpl@927f.updatecall secondobjectfetcher@49c2.fetchnorma recapclusterstrategy@674c.generateye uefyprefabrepository@5cd4.doneifiswo hganpanelfragment@9fd9.initobserv seteditpagecomponent@a788.waitmodeli amestickertab@f726.preloadsti gttpromotionfragment@f369.initview effectdraftcomponent@138b.openpublis topickserviceapiimpl@43d4.checkaiaut picklotteddownloader@294b.ensurelott editpreviewviewmodel@f9a1.tryagain ganpanelfragment@9fd9.onactivity stprefabpagefragment@a912.updateenab picklotteddownloader@294b.ensureedit oderationhandlerimpl@1de9.handle makeuppresfetcher@9b27.getaimakeu archloadingcomponent@a395.starti2ilo amecorerepresenterimpl@6f97.awaitretry recapclusterstrategy@674c.dogenerate localconfigsfragment@720d.handlerecl gpicturecropfragment@16c2.stoploadin gpicturecropfragment@16c2.doonfinish baseclusterstrategy@860d.runpipelin feaimenetworkapiimpl@b2d9.postaimecr 5makeuppanelfragment@e4b6.calculatea videouploadcomponent@95e9.fetchststo fectmodelselectscene@98b.initdata odelpicturereviewmodel@fa9c.select	

gifsviewmodel@472a.searchgifs EMAIL repositoryimpl@c0e3.fetchaigct stprefabpagefragment@a912.initdata	FILE
tservicelisterimpl@d51a.trytrigger idetaskdialogmanager@215d.showcompat kganpanelfragment@9fd9.initphotop aimetrystylemanager@6ec4.performapp selector@9dcc.ondownload cmakeuppagefragment@9516.observedat makeupviewmodel@3113.selectcolo tpreviewmodehandler@bae4.swaptomode draftupgradehelper@28d6.upgradedra hubmainviewmodel@a63a.getstylede itionstatustextassem@b2f.starttimer aimakeupprepo@5ae4.storetofil assetreverseproducer@54de.producecan sttpanelhomefragment@8f3f.observecor imgautogeniconhelper@4893.genicon canvasactionlistener@ff32.onlongpres enscreenfuncprovider@4094.changeplac tretchpersistentimpl@595d.deleteleloca ganviewmodel@586e.fetchpanel ideopreviewcomponent@f19c.getlastfra ctsettingspanelscene@878.initview aycomponentviewmodel@715b.loadprevie 7alphavideoscene@9f94.maybestart verticalmusicview@a7b8.buildcolle selectpanelcomponent@2b29.fetchmodel eautocutoutcomponent@4327.autocutout 3aimecreationmanager@e605.aimecreati deletemanager@c8e8.deleteaist 6gifsfragment@3c5.initview atorstickereditpanel@52bb.checkshowg customizeviewmodelv2@83ed.handlefree topickserviceapiimpl@43d4.getautopic 2filteredassetpool@8672.getassetsw imgautogeniconhelper@4893.prepareame draftupgradehelper@28d6.downloadef tnewcreatorfragment@9077.onsaveinst seteditpagecomponent@a788.gotoprevie userexpmapmanager@4632.onappexit seteditpagecomponent@a788.startprevi stickerfragmenttextkt@8f12.initbottom drafhandler@f1f0.savedraft +amecutouttab@330b.gotocutout prefabeditfragment@56ec.onclose rcollectionlistassem@fdbd.onviewcrea attpanelhomefragment@8f3f.openpanelo 3autopicksession@14df.awaitnexts am@736.run 1autopicksession@14df.awaitnexts inpreviewtitlewidget@434a.pagestateo makeuppanelfragment@e4b6.initdata collectmusicmanager@f40.collectmus ieffectlokicomponent@e537.fetchaigcp archloadingcomponent@a395.getresulti userexpmapmanager@4632.onappenter	

imagecutoutviewmodel@497d.preview EMAIL pagecomponent@a788.preloaddat atordraftserviceimpl@96ac.getdraftin	FILE
.customizeviewmodel@8957.reportpage 3ganviewmodel@586e.oncommitup editpreviewviewmodel@f9a1.updateaime facestretchfragment@cdc6.exit imagecutoutviewmodel@497d.changebrus feaimenetworkapiimpl@b2d9.postaigcdi absonboardingv3node@83df.destroy ganviewmodel@586e.setseekbar oderationhandlerimpl@1de9.keepprafto bcarouselplayerview@e8e0.makevideos ttpromotionviewmodel@b3db.checkrespa acstretchrepository@39dc.apply topickpanelcomponent@d649.checktaskr slistpanelcontroller@51da.setupbydef imestylepreviewscene@1044.handleload pickloadingcomponent@6ba2.onrunindra autopickpanelscene@9db7.initview ganviewmodel@586e.clearselec ttnewcreatorfragment@9077.initconge ormigrateserviceimpl@95ca.packdrafti prefabeditviewmodel@58ec.done reparestagecomponent@58.preparepro cananalysiscomponent@8894.scanassets +globaleventhelper@930c.emitonboar atorstickereditpanel@52bb.handleswit pickloadingcomponent@6ba2.setupprogr acstretchrepository@39dc.handleaddn estretchresviewmodel@7ac.downloadfa ocaliconlistfragment@8061.initdirlis facestretchfragment@cdc6.onsaveclic makeupviewmodel@3113.updatecate nscreenpromotionimpl@aca7.needshowwe makeupviewmodel@3113.changeacti emanagerinitwavetask@d87b.run imestylepreviewscene@1044.navigateed tickerfeaturehandler@84e5.onsendadds 0aimeimagerepo@b921.downloadim gtoolseditcontroller@c679.saveimg -lamecorepresenter@89d0.runasyncun aycomponentviewmodel@715b.fetchtasks enscreenfuncprovider@4094.applygreen ameimagecutouteditor@22c0.export fyoriginalrepository@defb.apply atorstickereditpanel@52bb.opencutout qlambda@f73a.accept imagecutoutviewmodel@497d.export 8aimecreationmanager@e605.gotoeditpa +makeupviewmodel@3113.saveaimake 6ganviewmodel@586e.toggleface amevelaunhtask@f810.dooncreate 5snowsharebottomassem@8f07.sharebutto ffectimgcropfragment@6e89.initcropvi pickloadingcomponent@6ba2.reportsave kmakeuppagefragment@9516.observedat	

sprefabeditfragment@56ec.observecon EMAILlocutoutnode@483c.process feaimenetworkapiimpl@b2d9.getaimedis	FILE
1facefusionrepo@41cc.changeitem normalhandlerimpl@927f.onrotate 0consumercoordinator@9d43.hasavailab prefabviewmodel@5840.loadeffect perfintervalmonitor@6311.flushpart facestretchfragment@cdc6.onbackclit verseclusterstrategy@818a.processnex templateapplynewflow@e669.applytempl bfourpicturefragment@febe.quotacheck uefyprefabrepository@5cd4.apply albmpickerrepo@7798.fetchalbum hubmainfragment@b23d.initdata prefabpanelfragment@ff3c.initdata 2draftupdater@ff1a.updatedraf delivery@5dd5.deliverbin reparestagecomponent@58.waitstylem nowglobalstateutilkt@c142.subscribe umakeuppagefragment@9516.launcheffe transcodenode@bb9a.onprocess voicerearchfragment@47ab.ondisplayw ttnewcreatorfragment@9077.playmusico delivery@5dd5.delivereve iontplviewcontroller@1a31.bindobserv reparestagecomponent@58.setdatatof aimetabviewmodel@6323.updateaime faceinsetresflowimpl@5b2e.waitframeu 1prefabviewmodel@5840.loadeffect htnesschangeobserver@7ddd.onbrightne 7musictrimviewmodel@3254.getmusicwa effectaudiowaveview@f30c.setaudiowa +draftupgradehelper@28d6.prepareupg tpreviewmodehandler@bae4.getorfetch atorofficialrepoimpl@eb36.handlerreqs modelselectimpl@5ce2.fetchfacem pickloadingcomponent@6ba2.ondiscard fyoriginalrepository@defb.createnewf p@w.a5 autopicksession@14df.awaitnext 9makeuppagefragment@9516.observedat fusionofficialloader@efe7.onofficial ganviewmodel@586e.onfacefusi meprojectpreparerequest@6513.getdraftin lmodepicturefragment@490e.initbottom gpicturecropfragment@16c2.downloadta meprojectpreparerequest@6513.run 3aistylerefetcher@6d7b.getmodelef +amenewflowtexttab@32b6.handleedit ackingpanelviewmodel@98d3.downloadan erdonemodeuidelegate@cc84.oninit edithitpanelfragment@5674.onfinishfr ramepreviewcomponent@6cce.oncreate sealbmpickermonitor@9b40.loadfinish ttnewcreatorfragment@9077.observefor 2bytebenchv2@5dc8.initcollec	

imagecutoutviewmodel@497d.downloadre EMAIL imagecutoutviewmodel@497d.undo draftimpl@6e0f.cleancache	FILE
pickloadingcomponent@6ba2.getorcreat pickloadingcomponent@6ba2.findprevio stickerframeimpl@91f8.hideallsho ewpager2heighthelper@f55d.updateheig ttlquifyfragmentv2@52bb.initview ffectimgcropfragment@6e89.doonfinish tuspublishedrepoimpl@cbec.doload acefusionresprovider@cfcf.getresfrom gpicturecropfragment@16c2.startloadi projectmanager@dca6.createfeat ewpager2heighthelper@f55d.attach acefusionresprovider@cfcf.getfacefus recapclusterstrategy@674c.generatemo ittlquifyfragmentv2@52bb.observewhe makeupviewmodel@3113.removeaima 3ganviewmodel@586e.savelocalf hubmainfragment@b23d.getmoredat cutoutnode@f12.onprocess ttnewcreatorfragment@9077.savedraft iprefabpagefragment@feb3.observedat 6ganviewmodel@586e.fetchpanel perfintervalmonitor@6311.markend stickerselecthandler@50af.replacesti amecutouttab@330b.onactivity amecanvasadjustlogic@563a.updateonbo aimakeuprepo@5ae4.checkandlo musicpanelcomponent@b870.showmusicp picklotteddownloader@294b.awaitdefer 3ganpagefragment@ccac.observedat makeupviewmodel@3113.cancelcate odelresourceprovider@c3f1.getfacemod creenrecordingfilter@43d1.filter seteditpagecomponent@a788.observecam drafthandler@f1f0.onmaineven ganviewmodel@586e.applyprefa eratorstickerfragment@a9ce.initdata reatorcamerafragment@db9c.initview .collectmusicmanager@f40.initcollec visionvisibility@2ff1.record templateapplynewflow@e669.updandsele iktokaigcserviceimpl@ca7b.submitwork reatoralbumtophintvm@c751.onclosecli gcreatorcamerahelper@1908.injectcomp customizeviewmodelv2@83ed.bubblechan mgcreatorv2viewmodel@7599.applyeffec ailfragmentviewmodel@c61.delstyle aimetabviewmodel@6323.getaimemod previewpagecomponent@e7db.onCreate prefabeditviewmodel@58ec.validatest seteditpagecomponent@a788.oncancelbt ckeroperateviewmodel@8eb0.selectfeat terpipelinecomponent@7672.applyl1fil plusbuttoncontroller@4766.waitfacest amenewflowtexttab@32b6.addsticker	apktool_out/lib/arm64-v8a/libdex_df_ship.so

ti2iloadcomponent@5889.onCreate EMAILfigsfragment@720d.initview nlistlocalrepository@143f.request	FILE
outbottomtabfragment@feef.downloadre -filteredassetpool@8672.getassets p@s.a5 7baseclusterstrategy@860d.runpipelin editpreviewviewmodel@f9a1.fetchaimem amebaseloadingtab@e052.injectretr ttlquifyfragmentv2@52bb.onviewcrea ailfragmentviewmodel@c61.onprofileb imgautogeniconhelper@4893.preparerem ittlquifyfragmentv2@52bb.initview asetemplateapplyflow@6e5e.fetchmodel ttlquefyviewmodelv2@3195.followface fectfeaturecomponent@168f.createfeat uploadstatuswavetask@8dac.run tnewcreatorfragment@9077.observepag eatorstickerfragment@eb94.handlesele aimelauncherfragment@9de9.normalpage perfevent@a4de.record caliconlistviewmodel@4695.createrequ eatoralbumfragmentv2@90fe.setupicont cameraassetfilter@f334.filter tretchpersistentimpl@595d.updateloca stprefabpagefragment@a912.done makeupviewmodel@3113.selectasse componentviewmodelv2@695f.observewor pickloadingcomponent@6ba2.handletask pickloadingcomponent@6ba2.querydraft 0aimeservicesimpl@2ffe.getcurrent gtoolseditcontroller@c679.saveiminn aprefabpagefragment@feb3.observdat templateapplynewflow@e669.upgrade stickerguidefragment@1ac2.lottiecanc localconfigsfragment@720d.applyeffec atortexthomefragment@5114.addsticker eatorstickerfragment@eb94.addsticker 2hubmainfragment@b23d.itemclick ttlquefyviewmodelv2@3195.doapplycle amecorepresenterimpl@6f97.onactivity themeclusterproducer@30fc.producecan imenewcustomizescene@55e6.effecttemp ailfragmentviewmodel@c61.mobdeletep eampipelineexecution@1e2.initialize tnewcreatorfragment@9077.initlayerl mgcreatorv2viewmodel@7599.commitgree aimakeuprepo@5ae4.remove statebundle@c896.emit makeupviewmodel@3113.checkfiles isdayclusterstrategy@81e2.dogenerate dprefabpanelfragment@ff3c.bindseekba seteditpagecomponent@a788.observevid facefusionrepo@41cc.getfusionm baseclusterstrategy@860d.requestthe componentviewmodelv2@695f.reportstar slistpanelcontroller@51da.changeauto	

+stickerframeimpl@91f8.changecorn EMAIL handlerimpl@927f.onmove lbottombarcontroller@1f1b.setuprente	FILE
kageandscriptfetcher@cb75.fetchmainp faceinsetresflowimpl@5b2e.preloadfac atordraftserviceimpl@96ac.packagedra producercoordinator@371.ensureprog aimecreationmanager@e605.aimecreati tservicelistenerimpl@d51a.triggernet eaimattingresfetcher@5768.downloadai aimetabviewmodel@6323.unloginloa liquefyimpl@9f1.refreshmai facestretchviewmodel@bd65.requestdat rchcontainerfragment@c389.onviewcrea feaimenetworkapiimpl@b2d9.postaigcge icelistenerproxyimpl@3459.addlistene aimeinterview@b693.setbuttons amecorepresenterimpl@6f97.updateproj videocutoutviewmodel@ffde.showcompil 5autopicksession@14df.awaitnexts pickloadingcomponent@6ba2.submitorre 6reeditutils@c260.preloadgre makeupviewmodel@3113.executeame .hubmainfragment@b23d.itemclick bumsingleselectlogic@1ca8.bindholder asrstreamtask@8422.ensuremode ctcreatepipelineimpl@e2ca.writelabel prefabviewmodel@5840.initfeatur meprojectpreparatask@6513.preparev2 lttliquifyfragmentv2@52bb.initseekba aimemodelreporter@b81d.reportstar baseclusterstrategy@860d.timed baseclusterstrategy@860d.consumeacan creatorstylerepoimpl@eb15.clear ibilitydialoghandler@2de2.showcompat kttpromotionfragment@f369.initobserv archloadingcomponent@a395.commitgree 6consumercoordinator@9d43.triggernon bytebenchconnection@a5b1.onservicec reparestagecomponent@58.waitmodeli lprefabeditfragment@56ec.observeval ffectimgcropfragment@6e89.onapplyeff dgifsfragment@3c5.observedat .amerouter@3af6.handlerrou ttnewcreatorfragment@9077.createsubm imagecutoutviewmodel@497d.init alalbumpickermmonitor@fa41.loadercall omptenhancecomponent@5992.enhancepro reparestagecomponent@58.preparefea 4tttoolbarwidget@a9e.addtoolbar nowpostbasecellassem@351e.assembleui companion@98eb.checkandme delivery@5dd5.delivermem inpreviewmusicwidget@e63e.getdraftin ffectimgcropfragment@6e89.geticonbit atorstickereditpanel@52bb.featureupd jganpanelfragment@9fd9.initobserv	

customizeviewmodelv2@83ed.bubblelic EMAIL@5dd5.delivermes tiktokgifrepository@f767.downloadgi	FILE
7prefabviewmodel@5840.loadeffect triggerviewmodel@22d9.load eampipelineexecution@1e2.processsyn amecorepresenter@ee9a.bindsurf defaultfetcherimpl@a191.load creatorstylerepoimpl@eb15.createands creendataresprovider@2dc8.preloadpre ttpromotionviewmodel@b3db.fetchdata ti2iloadcomponent@5889.shotscreen imationpanelfragment@9f44.initobserv cefusionfuncprovider@d4bb.changetrac thememarqueetextview@dc03.onvisibili jankframecollector@560d.onframeend 0verticalmusicview@a7b8.buildrecom ckcliprailpanelscene@f69d.runshowsl redraftmodelwavetask@3d29.run templateapplyoldflow@8f3d.refresheff lbottombarcontroller@1f1b.setupleftb reparestagecomponent@58.oncreate aimakeuprepo@5ae4.removeaima atorofficialrepoimpl@eb36.getrandomo pickloadingcomponent@6ba2.handlenonm tcreatorlayeradapter@bc73.seticon templateapplyoldflow@8f3d.onupgraded recoveryimpl@2170.onrestore filteredassetpool@8672.loadslice prefabitemadapter@7279.performuse kfacestretchfragment@cdc6.initobserv 9baseassethandler@7ec4.newupdatec amebasetooltab@fb4c.movetoscre opickpanelguidescene@80d3.updatescro eautocutoutcomponent@4327.calculateu pickloadingcomponent@6ba2.observevas cefusionfuncprovider@d4bb.changefusi fectpromptinputscene@9194.updateacti af@73d.run 0baseclusterstrategy@860d.checkandtr pickloadingcomponent@6ba2.handleretr owmutualrelationview@6b4b.bindavatar tchcanvasadjustlogic@bb02.adjustcanv tnewcreatorfragment@9077.startstick promptinputcomponent@dac6.onprompten makeupresfetcher@9b27.getmakeupp terpipelinecomponent@7672.applyl2sec aa@742.run seteditpagecomponent@a788.showsavedr enscreenfuncprovider@4094.checkgreen cbottomtabadapter@976c.onbindview warchivecalendarcell@2337.onbinditem feaimenetworkapiimpl@b2d9.postaimeap prefabviewmodel@5840.createfeat keffecteditorcontext@5cb5.initialize seteditpagecomponent@a788.fetchprese l@7c13.run	

cutoutcanvasfragment@a1bc.processaut EMAILviewmodel@3113.createaima nnprefabeditfragment@56ec.observeval	FILE
delivery@5dd5.dumpmemory kageandscriptfetcher@cb75.fetchmainr ameimagecutouteditor@22c0.copyimage amevesdkinitwavetask@2eac.run enstyleresultmanager@35df.removeload ailfragmentviewmodel@c61.getstylede perfevent@a4de.onframedro econfigpagecomponent@842b.fetchprese -alphavideoscene@9f94.onseg0star angmodeldownloadtask@7c68.startorres makeupresfetcher@9b27.fetchmakeu atorstylefactoryimpl@3118.createstyl gpicturecropfragment@16c2.onapplyeff reparestagecomponent@58.translatep 7collectmusicmanager@f40.initunlimi efabcategoryloadtask@8de0.run gslistpanelviewmodel@c975.changeauto asrstreamtask@8422.preloadint ormigrateserviceimpl@95ca.migratedra ttnewcreatorfragment@9077.initaimake styleselectcomponent@eeed.recorddata longloadingpredictor@973f.countasset hsladjustfragment@cc19.recoverlas ectmediadetectorutil@1704.detectorim effectmediadetector@cd93.detectface facestretchviewmodel@bd65.setupforcr 9messagecarouselview@c57a.schedulero -amecutouttab@330b.gotocutout imakeuppanelfragment@e4b6.initview animationviewmodel@e3f4.done amecutouttab@330b.getsticker .collectmusicmanager@f40.loadmoreco archloadingcomponent@a395.onsavedraf tgreenscreenhelperv1@b92c.genveframe 0hubmainfragment@b23d.itemclick ceinsetpanelfragment@3e93.initdata aimelauncherfragment@9de9.navigateto canvasactionlistener@ff32.onpointdra enstyleresultmanager@35df.postnaviga autopicksession@14df.repick +stickerframeimpl@91f8.showfacefo idereditpagefragment@c761.onviewcrea oubleclicklikelayout@fa95.doafterani econdobjectviewmodel@9b86.fetchpanel eatorlayerviewholder@b52a.onstatecha fganpagefragment@ccac.observedat picklotteddownloader@294b.ensurelong adjustpanelutiltextkt@cd4.createadju stickerpanelimpl@54a9.showsticke dailyclusterstrategy@ea07.dogenerate stylerepository@15e0.getstyle gprefabpanelfragment@ff3c.initdata opickpanelguidescene@80d3.changestat localconfigsfragment@720d.refreshdat	

+baseassethandler@7ec4.schedulefr EMAILcropfragment@6e89.getstyleta perintervalmonitor@6311.markbegin	FILE
mttliquifyfragmentv2@52bb.initobserv 6ganpagefragment@ccac.observdat ailfragmentviewmodel@c61.quotacheck ganviewmodel@586e.initfeatur makeupviewmodel@3113.emitparams tickersearchfragment@bb76.addgiphyst amegreenscreentab@f75.applygreen amegreenscreentab@f75.handletabc ctcreatepipelineimpl@e2ca.ondraftore amelaunchtask@d1f1.await .verticalmusicview@a7b8.showfavori opickpanelguidescene@80d3.preloadalp facestretchviewmodel@bd65.recoverfac feaimenetworkkapiimpl@b2d9.postaimede enscreenfuncprovider@4094.autoalignc eautocutoutcomponent@4327.oncutoutsu routerfragment@7afa.initobserv eprogresscoordinator@b04d.ensurephas inpreviewtitlewidget@434a.draftupdat amerouter@3af6.handlerrou keffecteditorcontext@5cb5.callnative taskexecutor@f5da.completeim adapter@4278.onbindview ocutagenttaskservice@c073.fetchtask archloadingcomponent@a395.ontexturev enscreenfuncprovider@4094.getportrai tiktokdialogimpl@519f.show 1cliprailcardview@7e75.scrollrail stprefabpagefragment@a912.featureupd amevelaunchtask@f810.run creendataresprovider@2dc8.loadgreens producercoordinator@371.awaitchang feaimenetworkkapiimpl@b2d9.getaimeass elactionreportheper@7a1f.reportobje stickerselecthandler@50af.addsticker consumercoordinator@9d43.awaitnorma topickpanelcomponent@d649.sam -musicpanelcomponent@b870.updatemusi imgautogeniconhelper@4893.exporteffe pickloadingcomponent@6ba2.initialize istadapterviewholder@56e2.bind progresssmoother@1224.catchupto rackingpanelfragment@a05c.exit amakeuppanelfragment@e4b6.initdata nowpostbasecellassem@351e.selectsubs ectpreseteditorscene@8d4e.initview dialogcontentbuilder@336e.buildactio tpreviewmodehandler@bae4.selectedon cganviewmodel@586e.fetchpanel customizeviewmodel@8957.getfreecre ltiputilskt@10d0.dowhenloca imgautogeniconhelper@4893.autogenico customizeviewmodelv2@83ed.fetchrecom templateapplyoldflow@8f3d.applytempl	

ensuredraftmodeltask@d10a.run EMAILrepresenterimpl@6f97.runeffecte adjustpanelutiltextkt@cd4.updateadju	FILE
makeupviewmodel@3113.loadeffect amejumpmodulelogic@e6ce.jump aycomponentviewmodel@715b.fetchaimem screenshotfilter@a7eb.filter ameapplyeffecttask@d64d.run actionviewmodel@3d37.load iprefabpanelfragment@ff3c.initdata baseclusterstrategy@860d.processscvb themeclusterproducer@30fc.getcluster 3consumercoordinator@9d43.awaitnorma ttlquefyviewmodelv2@3195.gethandled volumechangeobserver@10a.onvolumech yfastclusterstrategy@ab24.dogenerate effecteditoractivity@a2af.oncreate ffectimgcropfragment@6e89.stoploadin ideopreviewcomponent@f19c.oncreate lbumpickeralgoloader@82cb.load express4runner@e270.getparsefu imationpanelfragment@9f44.initdata prefabeditviewmodel@58ec.validateph onboardingv3fragment@a2a8.registerob jttlquifyfragmentv2@52bb.initseekba enstyleresultmanager@35df.generateon eeklyclusterstrategy@9057.processnex makeupviewmodel@3113.downloadre eprogresscoordinator@b04d.runrelease keffecteditorcontext@5cb5.ttdoafterr animationviewmodel@e3f4.onpagefixe eautocutoutcomponent@4327.registerob ameautocutoutrepo@8606.chaincallb 1makeupviewmodel@3113.loadeffect secondobjectfetcher@49c2.fetchpanel atorstickerviewmodel@4254.updatelast ourcedownloadnewimpl@4e8a.updatereso nowsharebottomassem@8f07.onhostpaus gtoolseditcontroller@c679.saveoffici aimakeuptophintvm@5ac4.onclosecli ganpanelfragment@9fd9.bindseekba 3phasestackview@ebdd.animatepha ckpanelguidefragment@b009.changestat -customizeviewmodel@8957.getfreecre lectionlistviewmodel@a262.onloadbefo stprefabpagefragment@a912.resetall hsladjustfragment@cc19.resetvalue 2textstickerresflow@3f39.obtainaddf jankframecollector@560d.start nimationpagefragment@b779.observadat amecorerepresenterimpl@6f97.awaitproje progresssmoother@1224.startfilli bfourpicturefragment@febe.delstyle hsladjustfragment@cc19.applyadjus 0amecutouttab@330b.preloadfac categoryitemview@b2ec.updatedata ganviewmodel@586e.eecreatefe	

singledetailfragment@8081.showsaveto EMAIL videoscene@9f94.performsub gmakeuppanelfragment@e4b6.initdata	FILE
behaviourimpl@96c1.showprevie enstyleresultmanager@35df.styledetai gmakeupviewmodel@3113.loadeffect imgautogeniconhelper@4893.loadrandom +filteredassetpool@8672.getassetsw faceinsetresflowimpl@5b2e.changeface ckedraftextraimpl@fabf.savefile tuspublishedrepoimpl@cbec.fetchusers bbottombarcontroller@48f3.setupright customizeviewmodelv2@83ed.newcustomi faceinsetresflowimpl@5b2e.getlayerdi 4nowsharebottomassem@8f07.clearconta 8officialiconutilskt@8545.loadoffici creatorbaseviewmodel@6ca3.emitevent defaultfetcherimpl@a191.doload mestickercutoutfuckt@8cf2.addorrepla fganpanelfragment@9fd9.initview consumercoordinator@9d43.hasonlypre iprailpanelcomponent@65e4.savedrafta inglepicturefragment@9.onviewcrea gonboardingv3tipview@64f2.initview ifacestretchfragment@cdc6.initview 9prefabpagefragment@feb3.observemat 2ganviewmodel@586e.loadfacefu topickserviceapiimpl@43d4.trackuploa cprefabeditfragment@56ec.onviewcrea ttnewcreatorfragment@9077.startameco noweventregistry@2a90.fire acstretchrepository@39dc.applyeffec delivery@5dd5.deliversam ecutoutpanelfragment@2aad.getsticker fectfeaturecomponent@168f.replaceand stylerepository@15e0.usecache loadinggate@35b9.tryfire ntalviewshowctrlimpl@4f40.triggersho inpreviewtitlewidget@434a.reqandupda aimeintroview@b693.setupscrol makeuppanelfragment@e4b6.initview feaimenetworkapiimpl@b2d9.getstylede stprefabpagefragment@a912.resetallva atorstickereditpanel@52bb.reportinsp selectpanelcomponent@4222.sceneactio delivery@5dd5.delivercpu componentviewmodelv2@695f.openstyler amedbinittask@1716.run delivery@5dd5.dumpcpu 3ganviewmodel@586e.setfacefus +editormodelimpl@5d2e.selectandc prefabviewmodel@5840.eecreatefe stickerframeimpl@91f8.alwayshide wabsonboardingv3node@83df.downhenloca reeditpaneladapter@da98.bindselect mestickercutoutfuckt@8cf2.handlesele hubmainfragment@b23d.delaimemod	

ckcliprailpanelscene@f69d.onshow EMAILmodeuidelegate@240a.oninit eampipelineexecution@1e2.processasy taskexecutor@f5da.call imagecutoutviewmodel@497d.reverse2db makeupviewmodel@3113.selectpref ickrootslotcomponent@4cb3.warmupalph ameimagecutouteditor@22c0.initmattin amevideocutoutplayer@403b.prepareasn ramepreviewcomponent@482.launchuplo ttpanelhomefragment@8f3f.openpanelo texteditpagefragment@ce45.onviewcrea duplicateinterceptor@cafa.intercept hsladjustfragment@cc19.getadjustf amecorerepresenterimpl@6f97.prepareres onboardingv2fragment@d2c5.updatecard gcreateeffecthelper@7d21.loadrafte amecorerepresenter@ee9a.updateproj kstickerpagefragment@e4f5.initobserv 2nowsharebottomassem@8f07.startshare hsubverecorderhelper@2fed.initsubver uabsonboardingv3node@83df.dowhenloca ttliquefyviewmodelv2@3195.mirror zemonitorserviceimpl@c952.calculatef verseclusterstrategy@818a.dogenerate ameimagecutouteditor@22c0.init acestretchrepository@39dc.handlerrepl gganpanelfragment@9fd9.bindseekba effecthintviewmodel@ee0c.load otoseditpagefragment@8917.onviewcrea jarvisuploader@bb4f.reportanr 0draftupgradehelper@28d6.getupdated seteditpagecomponent@a788.setdatatof cutoutbottomfragment@2b85.initprevie themeclusterproducer@ba79.getcluster atortexthomefragment@5114.ontextedit canvasactionlistener@ff32.onmove gaimetabfragment@e8f3.checklogin eimagecutoutactivity@e7b9.initobserv angmodeldownloadtask@7c68.downloadli canvasactionlistener@ff32.onrotation verticalmusicview@a7b8.loadingvie uttpanelhomefragment@8f3f.observecor fyoriginalrepository@defb.doneifiswo ttfeatureoperator@9edd.copy anelcomponentmanager@d39d.initcompon creendataresprovider@2dc8.getgreensc feaimenetworkapiimpl@b2d9.postaimest tservicelisterimpl@d51a.onafterdel ieffectlokicomponent@e537.fetchstyle ttliquefyviewmodelv2@3195.stateselec aimeservicesimpl@2ffe.trycustomi ttnewcreatorfragment@9077.selectobse sictrimpanelfragment@bc06.initview eampipelineexecution@1e2.complete editpreviewviewmodel@f9a1.observerst creendataresprovider@2dc8.preparegre	FILE
---	------

<pre> inpreviewmusicwidget@e63e.checkshowm EMAILsterstrategy@ea07.processnex aimetabfragment@e8f3.setviewmod </pre>	FILE
<pre> facefusionrepo@41cc.addfacefus imagecutoutviewmodel@497d.redo ceinsetpanelfragment@3e93.updateface secondobjcombinerepo@822a.fetchpanel companion@98eb.warmloadmo archloadingcomponent@a395.onCreate nscreenpromotionimpl@aca7.showwebshe ailfragmentviewmodel@c61.downloadac screenthumbgenerator@4b96.initrecord cefusionfuncprovider@d4bb.handlechan -draftupgradehelper@28d6.updatedraf ttcreatorlayerimpl@3b51.updatelaye freeditpaneladapter@da98.bindstater mttpromotionfragment@f369.initobserv draftupgradehelper@28d6.fetcheffec fprefabeditfragment@56ec.observecan ntalviewshowctrlimpl@4f40.init -makeupviewmodel@3113.loadaimake icelistenerproxyimpl@3459.onevent 2alphavideoscene@9f94.runsubtitl facefusionrepo@41cc.removeface nowpostbasecellassem@351e.dispatchot eatorstickerfragment@eb94.calculatea templateapplynewflow@e669.handleappl ganviewmodel@586e.emiteditpr ctcreatepipelineimpl@e2ca.cropandsav imgautogeniconhelper@4893.preparecus -stickerresflowimpl@8b68.obtainstic greeditpaneladapter@da98.bindnormal stprefabpagefragment@a912.getadjustf eeffectenvlaunchtask@8b0e.run ngslistpanelfragment@20bf.initview gpicturecropfragment@16c2.initview recapclusterstrategy@674c.generateca customizeviewmodelv2@83ed.fetchaimes canvasactionlistener@ff32.ondown creendataresprovider@2dc8.getprefabb aimemoduleimpl@3a8c.createorfe ti2illoadingcomponent@5889.onrecordfi eatorstickerfragment@a9ce.handleitem baseclusterstrategy@860d.initialize draftupdater@ff1a.updatedraf creatorviewmodel@f9f8.triggerlay amecorerepresenterimpl@6f97.needrunfet dithitpanelviewmodel@a5bb.commitgree +aimetabviewmodel@6323.checkcusto ctonboardingfragment@7b49.initview topickpanelcomponent@d649.onaiautocu aimelauncherfragment@9de9.redirectst amecorerepresenterimpl@6f97.upgradedra gcreatorcamerahelper@1908.takephoto seteditpagecomponent@a788.preloadi2i ourcedownloadnewimpl@4e8a.blockrules -behaviourimpl@96c1.notifycomm </pre>	

npostgestur listener@e05f.checkandha EMAILentviewmodelv2@695f.handle succ kamelaunchpanellogic@a41c.initseqlau	FILE
aichoosemusicmanager@da6d.getaipanel attingresfetcherimpl@8fc8.preloadmat ideopreviewcomponent@f19c.choosemode imgautogeniconhelper@4893.prepareran ctcreatepipelineimpl@e2ca.cropiconan ganviewmodel@586e.applyfacef hganpagefragment@ccac.observedat ackingpanelviewmodel@98d3.changetrac 7messagecarouselview@c57a.clearstabl atorstickerviewmodel@4254.requeststi ttnewcreatorfragment@9077.observedra verseclusterstrategy@91c8.scanwindow tttingspanelcomponent@2acc.showsettin slistpanelcontroller@51da.changeport 6officialiconutilskt@8545.loadoffici mestickercutoutfuckt@8cf2.addsticker wverticalmusicview@a7b8.initsearch languageodeltask@fc90.forwardsin fectfeaturecomponent@168f.exporteffe tttoolbarwidget@a9e.onconfigur 1drafthandler@f1f0.handleconf feaimenetworkapiimpl@b2d9.getaimelis prefabviewmodel@5840.cancelpref messagecarouselview@c57a.clearswitc ttttoolbarwidget@a9e.rendertool cefusionfuncprovider@d4bb.changetofu ttlquefyviewmodelv2@3195.loadfacest ameimagecutouteditor@22c0.onactionup pickerviewcontroller@a872.initobserv utopicklogfilewriter@b890.onlog ttdataeventreceiver@e70e.ondataeven chestrationcomponent@b9ce.executefix mecovereditviewmodel@c5c4.detectface prefabviewmodel@5840.applyprefa fectpreviewviewmodel@ace0.sendprevie editpreviewviewmodel@f9a1.buildstyle 0secondobjectfetcher@49c2.fetchcombi ttlquefyviewmodelv2@3195.togglepage tylepreviewviewmodel@9526.generatest goalbumpickermirror@2ce0.loadercall ectimgcreatorveutils@fa0a.renderimag 6filteredassetpool@8672.getorloads ti2iloadcomponent@5889.getresulti 0collectmusicmanager@f40.updatecoll ganpagefragment@ccac.observedat elangdeviceexecution@ad3f.preloadres verticalmusicview@a7b8.showaidata nowpostutilskt@9e4e.roundandad -draftupgradehelper@28d6.refresheff aistyleresfetcher@6d7b.getmodelef makeupresfetcher@9b27.getmakeupf ackingpanelviewmodel@98d3.exit ilamaterialsdkiimpl@a5d8.downloadmo gslistpanelviewmodel@c975.fetchlist	

atorstickereditpanel@52bb.showgreens EMAILutocutoutrepo@8606.chaincallb edgeflowmanager@9681.sendtoutp	FILE
filterchain@7194.filter promptinputcomponent@dac6.onreferenc tservicelistenerimpl@d51a.savedeploy ailfragmentviewmodel@c61.onpostbutt mgiconeditcontroller@c62e.fetcheffec amakeuppagefragment@9516.showaimake prefabeditviewmodel@58ec.updatesubm retryimagelayout@8d71.enableagai modelfetcher@5c4a.fetchmodel tretchpersistentimpl@595d.getlocalfa reparestagecomponent@58.expotteffe amecorepresenterimpl@6f97.runupgrade asrstreamtask@8422.process inglepicturefragment@9.downloadpi eautocutoutcomponent@4327.loading asrstreamtask@8422.initchanne 7makeupviewmodel@3113.loadeffect kttlquifyfragmentv2@52bb.observewhe -amegreenscreentab@f75.preparegre amecorepresenter@ee9a.onactivity vadaptershowctrlimpl@8d09.bind amecorepresenterimpl@6f97.runapplyef modelselectcomponent@ef2b.notifysele makeupviewmodel@3113.selectcate bytebenchv2@5dc8.loadbytebe aimetabfragment@e8f3.onviewcrea carouselplayerview@e8e0.scheduletr fectcomponentmanager@3783.checkandad imagecutoutresloader@6fb5.init ommoncustomizeviewkt@aa97.customizee gcreatorcamerahelper@1908.onCreate atordraftserviceimpl@96ac.getproject tservicelistenerimpl@d51a.fetchdeplo iquefyv2pagefragment@4341.initobserv prefabpagefragment@feb3.observadat 0collectmusicmanager@f40.initcollec mecovereditviewmodel@c5c4.generateco retchdragchildlayout@bf04.setoverlap ffectentranceservice@55a.chechaifea tpreviewmodehandler@bae4.onmodechan aprefabpanelfragment@ff3c.initdata selector@9dcc.notifysele attingresfetcherimpl@8fc8.loadmattin mgcreatorcameratools@c0f6.registerli aimelauncherfragment@9de9.redirectmo creatorviewmodel@f9f8.resetstatu tretchpersistentimpl@595d.addlocalfa selectpanelcomponent@2b29.sceneactio atapvidercomponent@ba4b.loadassets +amecutouttab@330b.gotomediad atapvidercomponent@ba4b.loadaluma eshapepanelviewmodel@fe83.changeshap prefabeditviewmodel@58ec.initdata cprefabpagefragment@feb3.observadat	

edithitpanelfragment@5674.replaymusi EMAIL bretutils@602c.getplaceho	FILE
iquefyw2pagefragment@4341.onautojump defaultadapter@8c6.timer pitayahostdefault@b731.hostsetup ptysettingsutil@2f5f.updatesett clientaihttpclient@89c8.postinwork -npthstackreporter@c9f.reportalln defaulthttpclient@6245.post +coredefaultimpl@d2fa.releasenat 4coredefaultimpl@d2fa.removeappl tionlifecyclewatcher@4905.registerap 1@6830.call ttnehttpclientimpl@7567.get coredefaultimpl@d2fa.removemess defaultadapter@8c6.timer .coredefaultimpl@d2fa.registerme ttnehttpclientimpl@7567.post -pitayahostdefault@b731.oncustomap 6pitayapluginimpl@80c8.registerpi tionlifecyclewatcher@4905.onappstatu coredefaultimpl@d2fa.runtask	apktool_out/lib/arm64-v8a/libdex_df_pitaya.so
g@9277.run d0@43b9.call gluetosdkincookie@1cce.setsyscook l0@3ee1.run p@9280.run o@929f.run j@929a.run u@9285.run k@927b.run b0@43f7.run owserpreinitexecutor@4d02.handlemess r@92a2.run j0@42ff.run y@92a9.call c0@3ff8.call m@929d.call n0@3ea3.call v0@418b.run q0@4226.call v@9286.run w0@416c.call m0@3ec2.call x0@414d.call g0@435c.run s@9283.run w@9287.call t0@3de9.run	

webviewchromium@d8d6.onmeasure EMAIL	FILE
h0@4017.run t1@3de8.handlemess e1@4399.call k0@42e0.run h0@3f5d.run a@9271.call q@92a1.run p0@3e65.run i0@431e.call y0@3d4e.run b@9292.allow k0@3f00.run s0@41e8.call m0@42a2.run f1@437a.run i0@3f3e.run g1@3f7b.run i@9299.getusagefo t@92a4.run b@9292.clear o@927f.call g1@435b.run g0@3f7c.run d@9274.call n@927e.call e0@3fba.run w0@3d8c.run f0@437b.call n0@4283.call l@929c.call z@928a.run z0@3d2f.run c1@3ff7.run h1@433c.call i@9279.run x@9288.run h0@433d.run f0@3f9b.run z0@410f.call z@92aa.run a1@4035.call k@929b.run i@9299.deletealld e@9275.run m@927d.call c@9273.call u0@41aa.run android-webview-dev@chromium.org j@927a.call v@92a6.run u0@3dca.call q@9281.call d1@3fd8.run o0@4264.call q0@3e46.run	apktool_out/lib/arm64-v8a/libdex_df_ttwebview.so

n@929e.run EMAIL h@9272.run h@9272.run	FILE
y@9289.run i1@3f3d.run t0@41c9.run p0@4245.call x@92a8.run b@9292.getallowed u@92a5.run s@92a3.run t@9284.run b1@4016.call e0@439a.call o0@3e84.call j0@3f1f.run b@9292.getorigins r0@3e27.call p@92a0.run a0@4036.run r0@4207.call l0@42c1.run s0@3e08.call l@927c.run w@92a7.call e1@3fb9.call v0@3dab.run a0@4416.run miumfactoryprovider@38d1.initialize ebviewruntimeservice@6831.registerda b@9292.clearall x0@3d6d.call y0@412e.call h@9278.call d0@3fd9.run	
zhangke.finn@bytedance.com	apktool_out/lib/arm64-v8a/libfast_engine.so
6bddlnasourcewrapper@10b1.setplayerl rtceventnotifier@2c05.onfirstvid zzc@c2ed.call dlnasourceimpl@1a94.resume chromecastsourceimpl@71b3.play 8bddlnasourcewrapper@10b1.setplayerl bytemediarecorder@e39e.init chromecastsourceimpl@71b3.add dramali nsdhelper@cdf3.startdisco stopbrowserrunnable@80f7.run rvicediskcachehelper@769c.checkservi zzbr@17e6.run castingmanager@f46d.startbrows castingplayerimpl@f321.addseeklis chromecastsourceimpl@71b3.updatedisc nsdhelper@cdf3.stopdiscov retryexecutor@3f26.onfail readerthread@d197.run	

castingplaymanager@89e6.ondramaid EMAIL panelcomponent@c8ae.onchange castingmanager@f46d.emit	FILE
rtceventnotifier@2c05.onvideoenc videorecordermanager@acb0.preparevid dlnasourceimpl@1a94.pause nsdclient@70a1.handlereso nsdserver@c708.stopserver rtceventnotifier@2c05.onintofore rtceventnotifier@2c05.onconnect bytecastsourcimpl@9ea6.getsinkdev dlnasourceimpl@1a94.addvolume omecastsourcwrapper@3a80.setplayerl dlnasourceimpl@1a94.play smhandler@e866.handlemess .mirroringmanager@9956.delayendmi chromecastsourcimpl@71b3.playnextdr chromecastsourcimpl@71b3.resume castingmanager@f46d.initsdk zzbe@2161.run dlnasourceimpl@1a94.changereso astingpanelcomponent@c8ae.onparentvi startbrowserrunnable@cc6.run 3bytecastsourcimpl@9ea6.authbylice chromecastsourcimpl@71b3.addvolume tvcasting@552b.initialize dlnasourceimpl@1a94.setvolume chromecastsourcimpl@71b3.swapdevice e@84c7.oncast zzq@bce7.run nsdserver@c708.startserve chromecastsourcimpl@71b3.destroy nsdhelper@cdf3.handlefoun getvolumerunnable@90a7.run dlnasourceimpl@1a94.getdevicei servicelistpanelkt@6531.servicelis dlnasourceimpl@1a94.getmediain -castingmanager@f46d.initsdk chromecastsourcimpl@71b3.playpredra pauserunnable@b7d1.run chromecastsourcimpl@71b3.disconnect decodethread@c0e7.run rtceventnotifier@2c05.onpaused castingmanager@f46d.runonuthr chromecastsourcimpl@71b3.refreshrou zzba@2165.run audiopassiveplayer@bdac.callbackau ssdpsearchsocket@1033.run zzc@8fc7.call nsdhelper@cdf3.onnsdresol 9mirroringmonitor@94c.displaylis mirrorcontroller@933f.startmirro controlpoint@eae5.checkandad castadvertiser@44ac.run zzbp@17e4.run chromecastsourcimpl@71b3.connect videorecordermanager@acb0.restart	

playlistsenderforall@e6a8.playdramai EMAILnabile@d87.run dlnasourceimpl@1a94.changedanm	FILE
zzbq@17e5.run castcontrolpoint@2577.search stingplugininstaller@8e02.trypluginw rtceventnotifier@2c05.onstucksta bytecastsourceimpl@9ea6.deinit zzax@216d.run eractinfotvcastassem@7913.onbind rtceventnotifier@2c05.oncancelre dlink servicedetector@2147.detectserv e@84c7.onerror astingplaylistsender@5860.onfail voipvideorender@6561.notifyvide displaysourceservice@89e3.handlesink b@afad.onbrowse nsdhelper@cdf3.registerse connecttask@dbef.run mirroringmonitor@94c.displaylis disposer@b3a7.run rtceventnotifier@2c05.onconnects rtceventnotifier@2c05.oncancelsu rtceventnotifier@2c05.onsinklate nsdhandler@5fbf.handlemess dlnasourceimpl@1a94.disconnect einfo listenerwrapper@18c9.onsuccess e@84c7.onstop timeouttask@d703.run zza@c2eb.call zzbc@2163.run e@84c7.ondisconne rtceventnotifier@2c05.onresumed bytecastsource@596e.stopbrowse bddlnasourcewrapper@10b1.setbrowser zzk@75d8.run rtceventnotifier@2c05.onvideosiz jbddlnasourcewrapper@10b1.setbrowser nsdclient@70a1.onnetworka dlnasourceimpl@1a94.startdlnas zze@c2ef.call rtceventnotifier@2c05.oncastcont audiothread@e4af.run zzb@c2ec.call searchresponsesocket@b893.run 2dlnasourceimpl@1a94.checkandcr bddlnasourcewrapper@10b1.setplayerl cbddlnasourcewrapper@10b1.setplayerl rtceventnotifier@2c05.onstopped dlnasourceimpl@1a94.seekto dlnasourceimpl@1a94.startbrows nsdhelper@cdf3.unregister laybackcontrol layout@5e8c.maybeshowi eractinfotvcastassem@7913.initialize nsdclient@70a1.handnsdser chromecastsourceimpl@71b3.stop rtceventnotifier@2c05.onrecvmeta	apktool_out/lib/arm64-v8a/libdex_df_live_cast.so

chromecastsourceimpl@71b3.subvolume EMAIL gmonitor@94c.init eractinfotvcstassem@7913.onviewwrea	FILE
castssdpsearchsocket@ef9.run chromecastsourceimpl@71b3.setupnewap renderthread@49f0.run playercontroller@ab13.play writethread@1526.run astingservicemanager@3eb0.startbrows zzbq@45db.run advertiser@631e.run -bddlnasourcewrapper@10b1.getvolume chromecastsourceimpl@71b3.playdramai zzs@bce9.run renewssubscriber@a501.run chromecastsourceimpl@71b3.updatemedi bytecastsource@596e.init zzr@8534.run zzs@8535.run controlpoint@eae5.search chromecastsourceimpl@71b3.setvolume bddlnasourcewrapper@10b1.send 5bddlnasourcewrapper@10b1.setplayerl zzg@bcdd.run dlnasourceimpl@1a94.send chromecastsourceimpl@71b3.seekto castssdpnotifysocket@ebb6.run astingpanelcomponent@c8ae.startplaya rtceventnotifier@2c05.onsinkstuc zzas@2172.run rtceventnotifier@2c05.onmonitore -networkutil@dfe1.checkandcr zzbo@17e3.run zzbn@17e2.run rvisediskcachehelper@769c.writecache dlnasourceimpl@1a94.getstatusi rtcengineimpl@2d44.playvideo setvolumerunnable@c0a9.run -voipvideorender@6561.notifyvide httpsocketrunnable@df35.run nsdclient@70a1.notifybrow zzbm@17e1.run zzt@8536.run castingutils@42a6.getawemeli laybackcontrollayout@5e8c.maybeshown videorecordermanager@acb0.pause 1bytecastsourceimpl@9ea6.initperfor searchresponsesocket@7471.run zzah@17bd.run videorecordermanager@acb0.stop httpserver@dd9f.run videorecordermanager@acb0.start zzu@8537.run rtceventnotifier@2c05.onstat rtceventnotifier@2c05.onintoback eoflistenerwrapper@18c9.delaysched chromecastsourceimpl@71b3.init	

rtceventnotifier@2c05.onlogmonit EMAIL urceimpl@1a94.subvolume stringplugininstaller@8e02.oninstallp	FILE
-rtceventnotifier@2c05.onconnects -bytecastsourcimpl@9ea6.connect networkmanager@4f82.start zzbl@17e0.run zzd@c2ee.call transporthandler@d93c.handlemess zzav@1fbc.run concurrentsubject@e489.notifyobse threadcore@9e70.run devicemanager@ae59.clearbrows astingpanelcomponent@c8ae.onconnect rtceventnotifier@2c05.oncastsucc zzl@8d1b.run mainhandler@148c.handlemess devicemanager@ae59.deviceadde rtceventnotifier@2c05.onaudioset stoprunnable@46ac.run astingpanelcomponent@c8ae.startmirro rtceventnotifier@2c05.onkilled dlnasourceimpl@1a94.stop dlnasourceimpl@1a94.connect e@84c7.onstart videorecordermanager@acb0.resume seekdelayrunnable@9f68.run ssdpnotifysocket@f51d.run zzar@2173.run omecastsourcewriter@3a80.setbrowser 9bddlnasourcewriter@10b1.setmessage bytecastsourc@596e.startbrows rtceventnotifier@2c05.ondisconne zzq@75d2.run chromecastsourcimpl@71b3.pause controlpoint@eae5.handledevi concurrentsubject@e489.notifyexce dlnasourceimpl@1a94.changespee .bytecastsourcimpl@9ea6.setauthbyl dlnasourceimpl@1a94.checkandcr e@84c7.onrecvmeta playdramaidlistener@ec4c.onfail +dlnasourceimpl@1a94.getstatusa chromecastsourcimpl@71b3.setrepeatm f@84c8.setvolume e@84c7.onconnect einfoListenerWrapper@18c9.onerror playrunnable@6bf9.run bytecastsourc@596e.deinit +bddlnasourcewriter@10b1.send rtceventnotifier@2c05.onerror chromecastsourcimpl@71b3.cleardrama chromecastsourcimpl@71b3.playdramal 0bddlnasourcewriter@10b1.getvolume	
devicemanager@ae59.devicereemo ecardlinkbuttonassem@9885.onviewcrea ttdsptablayout@2a64.addtabview	

baseplayerfragment@28f8.setupviewp EMAIL stviewmodel@1cef.loaddata edsongslstviewmodel@7b6e.loaddata	FILE
6dspauthtokenfetcher@f3a9.requestdsp n@t.jt ryoriginsourceloader@22de.load n@t.j2 tabpageassem@e8f7.subscribev aunchstrategymanager@e163.requestlin mainpagedatamutation@42dd.operate baselyricsview@d7c.reset2star edspplaylistmutation@12cc.operate -addtomymusicmanager@f107.addsongtom addedsongslistassem@a434.onwindowfo azonmusicauthhandler@45cb.refreshama cacesstokenmutation@c4ec.operate tagpanelviewmodel@f282.gettagpane dspfpsreporthelper@a7a.dspsubplay rddetaildatamutation@8893.operate nginelisteneradapter@cbe8.ontimeupda librarylistviewmodel@7bbd.loadsongs tdspplaylistmutation@d215.operate mediaplayer@e4b0.onattach ngtomusicappmutation@1f63.operate tificationcontroller@925b.mhandler dspauthtokenfetcher@f3a9.refreshacc ongcardlistviewmodel@3014.onprepared fanspotlightassem@70ab.initbottom -mdverticalviewpager@8f2e.mendscroll cacesstokenmutation@b5ae.operate ddtomusicdspauthutil@c894.selectdsp 6dspauthtokenfetcher@f3a9.requestref ddtomusicdspauthutil@c894.updatedsp ouoriginsourceloader@bec7.load sicspqueueelistassem@3dab.onviewcrea -mymusicongassem@bd6a.bindexposu +multisongcardassem@64e2.onviewcrea adspfpsreporthelper@a7a.forcedspu queueloadplugin@b85e.loadmore tyoauthmusicreceiver@1868.oncreate baseplayerviewmodel@37a1.loadmore otlightdetailsharevm@1691.onrefresh tailhitlistviewmodel@a699.onrefresh sprackexpiredplugin@2375.showsubscr ddtomusicdspauthutil@c894.addsongtom ixoriginsourceloader@232e.load icdspplayerviewmodel@83f0.checkswipe journeysourceloader@5df4.load journeysourceloader@5df4.loadmore addtodspviewmodel@9231.reportadds dspitemreusedassem@b7ba.onviewcrea lightsharedviewmodel@fb69.saveselect getdspplaylistsquery@f8ff.operate cdetailistviewmodel@ea91.loaddata librarylistviewmodel@7bbd.loaddata platformssettingpage@9a54.loaddsppla mysongssourceloader@3da7.loadmore	

piredplayablemanager@9b00.resetactio EMAIL strip@aa32.attach ddtomusicdspauthutil@c894.getusersel	FILE
edsongslstviewmodel@7b6e.clicklinkb .campaigncardassem@ea73.bindexposu librarylstviewmodel@7bbd.loadmoreso tabpageassem@e8f7.onwindowfo nginelisteneradapter@cbe8.togglelime absplayablequeue@1604.load ddtomusicdspauthutil@c894.getinstall -dspauthtokenfetcher@f3a9.refreshacc pplemusicauthhandler@f019.refreshapp haccesstokenmutation@4fee.operate teoriginsourceloader@f51e.load 0dspauthtokenfetcher@f3a9.requestdsp mysongssourceloader@3da7.load 8dspfpsreportherper@a7a.forcedspla +baselyricsviewmodel@c093.getirclyri sicdpspsheetviewmodel@3e3c.loadplatfo latformlistmethodidl@d11f.handle guidehelper@f22a.checkswipe ouoriginsourceloader@bec7.loadmore musicplayviewmodel@970a.playmusic reportactionmutation@6d59.operate edsongslstviewmodel@7b6e.reportshow oidsessioncontroller@2942.maudiooutp eekbarchangelistener@11c0.onstoptrac mymusicactivity@4fe3.oncreate +addtomymusicmanager@f107.addsongtom odspnetworkmonitorkt@e6a0.addsongmus imilarsongsviewmodel@5e01.getsimilar haccesstokenmutation@68bf.operate edspauthtokenfetcher@f3a9.requestref musicdsplikeassem@dd13.onlikecllc mediaplayer@e4b0.play 1addtomymusicmanager@f107.addsongtom ryoriginsourceloader@22de.loadmore zespecificdsphandler@b324.handle ongscheckfordspquery@6a28.operate queueloadplugin@b85e.load getsimilarsongsquery@d509.operate 2dspauthtokenfetcher@f3a9.requestdsp 3dspfpsreportherper@a7a.dsplaunchd threadutil@fcce.sam lottieguide@f3e7.dismiss librarylstviewmodel@7bbd.refreshjou musicsettingpage@e355.initdata dspplatformlistquery@5a00.operate lechangereportplugin@9eed.onplayable teoriginsourceloader@f51e.loadmore reportmanager@d9ac.reportacti +dailypickcardassem@5864.onviewcrea addtopresaveauthutil@7d3.addpresave lechangereportplugin@9eed.doaddrepor similarmusicfragment@feee.oncreatevi cacesstokenmutation@f6d2.operate ixoriginsourceloader@232e.loadmore	apktool_out/lib/arm64-v8a/libdex_df_music_dsp.so

ddtomusicdspauthutil@c894.getdspplat EMAIL musicdspauthutil@c894.songcheckf 2lyricinfoanalyzer@3645.getlyricin	FILE
addedsongslistassem@a434.subscribev azonmusicauthhandler@45cb.getamazonm otlightdetailsharevm@1691.onloadmore sprackexpiredplugin@2375.onplayback umtomusicappmutation@f5d8.operate cdspjourneyviewmodel@e737.fetchsongs musicdsptabfragment@f159.oncreatevi songcheckfordspquery@d39e.operate ddtomusicdspauthutil@c894.createdsp lottieguide@f3e7.show preloadplugin@b661.preload sicsdpaudiocardassem@3fa1.onviewcrea sicsdpsheetviewmodel@3e3c.requestpla cketplatformsyncpage@3038.initdata dspaudioseekbarassem@9696.seekbarsho absplayablequeue@1604.loadmore piredplayablemanager@d256.resetactio usicsdplikeviewmodel@8702.savesongto baselyricsview@d7c.mhandler installdetectmanager@c140.getdspinst moveanimator@6935.run ddtomusicdspauthutil@c894.getdspplay edspplatformmutation@394.operate sicmainpageviewmodel@271e.loaddata lightbottomcomponent@75a.createbott gstomusicappmutation@76c2.operate justtagscachemanager@77d9.writelocal	
appro@openssl.org	apktool_out/lib/arm64-v8a/libtccrypto.so
appro@openssl.org	apktool_out/lib/arm64-v8a/libAwebviewbytedance.so
asselfiescanfragment@f36d.onmanualca checkoutprocess@fad.presentpim checkouthomekt@de1b.checkoutho 4camerapreview@5543.initcamera 0detailviewmodel@e36a.onclickpre ailablemethodspagekt@df6.ailablem billhomeviewmodel@7c13.load paymentconfig@4a3b.initstarli reetfillercontroller@1e6f.onvaluecha veritasidvcameraview@3351.downgradem baseviewmodel@a8bd.loadcashie addressviewmodel@1396.synchroniz mentprepareviewmodel@97b5.getrepayme pimanagementkt@49.handlenavi billhomeviewmodel@7c13.loadcustom asselfiescanfragment@f36d.showcamera baseviewmodel@a8bd.initnoncet payment@a405.presentpim echeckoutviewmodel@de26.startpolli icontextcard@cb18.onbindview tainerassemviewmodel@65ad.createsubc	

piviewmodel@e244.deletestor EMAIL piviewmodel@e244.storepayme puxtoastkt@4a5b.puxtoast	FILE
andingcontainerassem@e692.presentbut asselfiescanfragment@f36d.oncapturer ritasidvscanfragment@17f6.onviewcrea ritasidvscanfragment@17f6.doupdate dcamerapreview@5543.createcame payresultpagekt@ebf8.payresultp ogressassemviewmodel@10f5.getinstitu +repaymentviewmodel@2076.presentche reementsignviewmodel@4cbe.signagreem animationcontroller@2ab.dismiss 0landingassemvm@e5ad.createcred +baseviewmodel@a8bd.showgenera cardnumbercontroller@eba5.debounce checkoutviewmodel@de26.closecheck 2repaymentviewmodel@daf6.onpreparer asselfiescanfragment@f36d.doliveness example@email.com tainerassemviewmodel@65ad.signagreem detailviewmodel@e36a.onloadmore kycnfcscanningassem@2bbe.showreadyt itasselfiecameraview@347f.downgradem ritasidvscanfragment@17f6.onresume rationdatecontroller@a578.validatewi puxdialogkt@8092.dialogcont piviewmodel@e244.checkbinds tainerassemviewmodel@65ad.requestreg checkoutbarkt@7ee0.checkoutba noncecontainer@4140.getnonce 9checkoutprocess@fad.presentpim pimanagementkt@49.pimanageme andingcontainerassem@e692.initcontai addressviewmodel@1396.preparedat baseviewmodel@a8bd.isnetworka formskt@ec82.forms +checkoutcontainerkt@7c59.handlenavi piviewmodel@e244.getpibasic ritasidvscanfragment@17f6.downgrader +checkoutactivity@41a1.showcompos stagreementviewmodel@417d.getagreeme tainerassemviewmodel@65ad.recordclic ritasidvwelcomeassem@6b26.sessiontim bnplcommonpopup@7d4b.sendreques postartnfcscanmethod@d0e8.handle nfcscanningviewmodel@a548.startnfcsc repaymentviewmodel@2076.getnonce ritasidvscanfragment@17f6.onmanualca checkoutviewmodel@de26.pay -phonenumbertkt@d397.oncountryc ndwalletlandingassem@7d5c.handleclic ycnfcscanningassemv2@7418.showreadyt 2bindcontainerkt@813f.showbindpa piviewmodel@e244.saveasprim 4detailviewmodel@e36a.onclickpre -checkoutactivity@41a1.showcompos	

asselfiescanfragment@f36d.sessiontim EMAIL ingviewmodelv2@eb11.handlescan checkouthomekt@de1b.imesparehn	FILE
-camerapreview@5543.initcamera piviewmodel@e244.redirectha ndpaymentmethodnavkt@cf39.navigation tainerassemviewmodel@65ad.createcred ogressassemviewmodel@10f5.getroutein .bnplentryviewmodel@c16.getstepcod apiservice@bd9b.getstarlin tuxdialogkt@608c.tuxdialogc reetfillercontroller@1e6f.debounce ogressassemviewmodel@10f5.createsubc addressviewmodel@1396.ondone reetfillercontroller@1e6f.onfocuscha 3clentaicameraview@ec4c.processfra buttoncard@7e9c.handledata -checkoutviewmodel@de26.storepayme creaselimitviewmodel@9cba.submit bottomsheetkt@3e26.bottomshee ignagreementfragment@3451.onviewcrea animationcontroller@2ab.show selectpikt@1283.selectpi ritasidvscanfragment@17f6.sessiontim +checkoutviewmodel@de26.storepayme selectassembledpikt@73eb.selectasse repaymentviewmodel@daf6.loopforres asselfiescanfragment@f36d.doimageupl bizdataholder@86cc.getconfigu repaymentviewmodel@daf6.load repaymentviewmodel@2076.initpaymen ritasidvscanfragment@17f6.showcamera 1addressviewmodel@1396.synchroniz checkoutprocess@fad.getnonce fcscanningfragmentv2@4475.onviewcrea 4checkoutviewmodel@de26.startpolli checkoutviewmodel@de26.initmethod nfcscanningviewmodel@a548.handlescan baseviewmodel@a8bd.requeststa checkoutviewmodel@de26.getpayment piviewmodel@e244.launchbind ogressassemviewmodel@10f5.createmain pimanagementkt@49.cardlist cscanningviewmodelv2@eb11.startnfcsc piviewmodel@e244.getpimanag retrykt@6b9c.retry landingassemvm@e5ad.signagreem asselfiescanfragment@f36d.downgrader piviewmodel@e244.havestored checkoutviewmodel@de26.storepayme +formskt@ec82.forms postalcodecontroller@cddb.synchroniz ritasidvscanfragment@17f6.oncapturer cnfcscanningactivity@ca29.setupbotto configuration@2711.getidempot .camerapreview@5543.initcamera -checkoutcontainerkt@7c59.handlenavi	apktool_out/lib/armeabi-v7a/libdex_df_pipo_bnpl.so

ycnfscanningassemv2@7418.onviewcrea EMAIL interceptortk@9a2b.showclosed billhomeviewmodel@7c13.onpreparer	FILE
ogressassemviewmodel@10f5.decideuser reetfillercontroller@1e6f.onclick payment@a405.presentche -addressviewmodel@1396.initdatafo statementsviewmodel@5867.onrefresh phonenumberkt@d397.oncountryc ndpaymentmethodnavkt@cf39.bindpaymen .bindcontainerkt@813f.showbottom .repaymentviewmodel@daf6.onpreparer animationcontroller@2ab.startanima fieldcontroller@7de7.validatewi 1clintaicameraview@ec4c.handlecapt cardnumbercontroller@eba5.onvaluecha pipoclientaimanager@79c1.prefetch addressviewmodel@1396.fetchdata repaymentviewmodel@2076.presentche clintaicameraview@ec4c.handlecapt fcscanningfragmentv2@4475.onnewisode livenesscheckhelper@23d.livenessch fcscanningfragmentv2@4475.onCreateevi ritasidvscanfragment@17f6.doimageupl repaymentassem@956f.scrolltobo tuxtoastkt@aeed.tuxtoast -billhomeviewmodel@7c13.onpreparer asselfiescanfragment@f36d.doupdatese addressviewmodel@1396.datainitia asselfiescanfragment@f36d.permission asselfiescanfragment@f36d.releaseres creaselimitviewmodel@9cba.presubmit piviewmodel@e244.closebinds ritasidvscanfragment@17f6.releaseres asselfiescanfragment@f36d.onviewcrea bnplentryviewmodel@c16.getstepcod landingassemvm@e5ad.requestreg rogressanimationview@4d84.initstepvi piviewmodel@e244.dealbindre ritasidvscanfragment@17f6.permission baseviewmodel@a8bd.getnoncewi tainerassemviewmodel@65ad.decideuser +baseviewmodel@a8bd.shownetwor piviewmodel@e244.cancelaspr piviewmodel@e244.initmethod cardnumberkt@6a2f.cardnumber bnplcommonpopup@7d4b.onapierror ogressassemviewmodel@10f5.signagreem clintaicameraview@ec4c.ongetnewim	
nmolifecycleobserver@fb35.onstatecha paypalSdkprocess@6938.clear +httpClient@bac3.notifysucc pallifecycleobserver@fa45.onstatecha httpClient@bac3.notifyerro httpClient@bac3.schedulere	apktool_out/lib/armeabi-v7a/libdex_df_pipo_external_payments.so

EMAIL	FILE
ffmpeg-devel@ffmpeg.org	apktool_out/lib/armeabi-v7a/libttvesdk_plugin.so
.ilililili@7cb8.onsurfacet iiiiilili@5021.run ilililili@e761.run linkccdcocrviewmodel@5bad.restarttim liliilil@7742.run ardoverlaycontroller@1499.iiiiiilili innerreticleview@c576.ilililili ilililil@2f90.iiiiiilil liliilili@f61d.run ilililil@c351.run tooltipmanager@42cd.showtoolti liliilil@9dcb.run ardoverlaycontroller@1499.ilililili liliilil@3a5c.ilililil liliilil@c4a4.run liliilili@aef1.run liliilil@3a5c.ilililil innerreticleview@c576.ilililil liliilili@66.lilililil liliilili@66.ilililil iiiiilil@41e6.lilililil liliilil@3b67.run ilililili@ad44.run ilililil@2f90.lilililil blinkccdcocractivity@a0d7.initview .ilililil@2341.onsurfacet progressview@d1bc.ilililil liliilil@3a5c.ilililil liliilil@3a5c.ilililil liliilil@8193.onshakings ilililili@abc1.run liliilil@54ad.run ilililili@7cb8.onsurfacet linkccdcocrviewmodel@5bad.frontsides liliilil@3a5c.lilililili liliilil@38b7.run liliilil@3a5c.dispose snackbarmanager@7b73.lilililil iiiiilili@48d.run nllililil@7584.com_microb tooltipmanager@42cd.hidetoolti ilililili@419e.ilililil rdreticleoverlayview@d3ea.createlayo liliilil@5a54.onpicturet liliilil@96bf.run nllililil@396d.com_microb ilililil@a68a.surfacecha iiiiilili@c56c.run snackbarmanager@7b73.ilililili ilililil@a728.onimageava liliilil@3a5c.lilililil	apktool_out/lib/armeabi-v7a/libdex_df_ccdc_impl_ocr.so

rdreticleoverlayview@d3ea.changestat EMAIL:caaf.run 3@1fe5.run	FILE
ilililil@2f90.lliilili ardoverlaycontroller@1499.lliililil Odebugviewhandler@3d30.initialize lliililil@7584.run lliililil@904d.run rdreticleoverlayview@d3ea.lliililil lliililil@caaf.run lliililil@9cd3.run iilililil@d9d.run iilililil@4550.run progressview@d1bc.lliililili 3@a98.run iilililil@4526.run iilililil@2341.onsurfacet iilililil@189d.run lliililil@396d.run lliililil@396d.lliililili lliililil@cc66.run iilililil@2f90.dispose lliililil@9821.run	
styleselectcomponent@eed.getselects ttliquefyviewmodelv2@3195.applyclear secondobjectfragment@25bf.initdata hsladjustfragment@cc19.cancelvalu opickpanelguidescene@80d3.initviews viourpreviewfragment@b187.initaction sthitsviewcontroller@3138.bindobserv ailfragmentviewmodel@c61.downloadpi bverticalmusicview@a7b8.buildcolle jarvis@b146.init seteditpagecomponent@a788.oncreate keffecteditorcontext@5cb5.ttdoaftere ostdeleteserviceimpl@ec46.delete enscreenfuncprovider@4094.switchreal ganviewmodel@586e.removeface bbottombarcontroller@48f3.setupleftb ntiputilskt@10d0.dowhenloca 0eventtrackingextkt@d694.sendeventt tiktokgifrepository@f767.trendgifs facestretchfragment@cdc6.initview eprogresscoordinator@b04d.syncreleas creatorlayerfragment@d93c.calculatea ttpromotionviewmodel@b3db.selectprom 0prefabeditviewmodel@58ec.compresssh .amestickertab@f726.preloadmat cefusionfuncprovider@d4bb.addfusion +nowlikeviewmodel@da60.handlenowp 6filteredassetpool@8672.getassetsw seteditpagecomponent@a788.launchscen creendataresprovider@2dc8.preloadgre archloadingcomponent@a395.observewor amecorepresenterimpl@6f97.launchawai amedbinitwavetask@901c.run	

ffectimgcropfragment@6e89.startloadi EMAIL utocutoutrepo@8606.chaincallb faceinsetresflowimpl@5b2e.obtainaddf	FILE
makeupviewmodel@3113.initfeatur amakeuppagefragment@9516.observdat makeupviewmodel@3113.updateload eampipelineexecution@1e2.processnod mstickerpagefragment@e4f5.initobserv canvasactionlistener@ff32.ondoublecl elactionreportheper@7a1f.onoperatio atorofficialrepoimpl@eb36.reqofficia ckcliprailpanelscene@f69d.loadingrot ecutoutpanelfragment@2aad.gotosticke acestretchrepository@575f.apply styleselectcomponent@eeed.downloadst sealbumpickmonitor@9b40.changeload alicondirlistadapter@f848.onbindview ecutoutpanelfragment@2aad.gotomedi canvasactionlistener@ff32.singletap modelselectcomponent@ef2b.downloadmo eaimattingresfetcher@5768.loadmattin enstyleresultmanager@35df.showloadin aimetabviewmodel@6323.loginload inpreviewtitlewidget@434a.updaterend fbaseconlistadapter@8bdc.onbindview iganpanelfragment@9fd9.bindseekba stickerguidefragment@1ac2.onlytipsca localconfigsfragment@720d.submitlist al@737.run imestylepreviewscene@1044.handlesucc editpreviewviewmodel@f9a1.fetchuserp dganpanelfragment@9fd9.initview stickerresflowimpl@8b68.preloadadd amemusictab@d8c.showmusicn tgreenscreenhelperv1@b92c.gengreensc 3ganviewmodel@586e.onfacefusi cutoutcanvasfragment@a1bc.initobserv creendataresprovider@2dc8.downloadgr ti2iloadcomponent@5889.msgcenterl customizeviewmodelv2@83ed.performgen carouselplayerview@e8e0.applycente prefabviewmodel@5840.fetchlokip taskrepositoryimpl@c0e3.getaigtas ckerguideserviceimpl@2357.startstick gifsfragment@3c5.addgifstic ckpanelguidefragment@b009.preloadalp eampipelineexecution@1e2.emit drafthandler@f1f0.showsavadr inpreviewmusicwidget@e63e.onconfigur seteditpagecomponent@a788.prehandlel ganpanelfragment@9fd9.initdata epreupgradedrafttask@a3b4.preupgrade -amecutouttab@330b.gotomedi -amenewflowtexttab@32b6.handleedit ltiponboardingv3node@2b24.launchpane slistpanelcontroller@51da.handleitem texteditpagescreenkt@f833.textinputi	

prefabviewmodel@5840.preloadaddow EMAIL model@472a.loadmoregi aiselfcarouselkt@ac9a.autoscroll	FILE
verseclusterstrategy@91c8.dogenerate perfintervalmonitor@6311.run wcaptioneditfragment@3c1b.initeditvi 0facefusionrepo@41cc.loadfacefu amecovereditfragment@1c20.initview cutoutbottomfragment@2b85.observevie ttlquefyviewmodelv2@3195.initfollow objectcontainer@a25.build hprefabeditfragment@56ec.observecan componentviewmodelv2@695f.performsuc bytebenchv2@5dc8.reportresu stprefabpagefragment@a912.getlayerdi drafhandler@f1f0.handleconf 2aimetrystylemanager@6ec4.shouldshow itionstatustextassem@b2f.startdotup 1ganviewmodel@586e.onmediasel edgeflowmanager@9681.initialize aimetabviewmodel@6323.loadmore tickersearchfragment@bb76.addorrepla ewpager2heighthelper@f55d.pagechange tiktokgifrepository@f767.searchgifs ltiponboardingv3node@2b24.registerpa imagecutoutviewmodel@497d.clearstep ameupgradedrafttask@e63f.run gtoolseditcontroller@c679.compressbi eratorstickerfragment@a9ce.observesea faceinsetresflowimpl@5b2e.obtainface imagecutoutviewmodel@497d.intercepts assetreverseproducer@54de.getcluster dataeventreceiverpro@8b02.ondataeven +ganviewmodel@586e.flushfacef otionrouterprocessor@713a.process scenemonitor@e338.stopintern ffectentranceservice@55a.isaifeatur facefusionrepo@41cc.changeefusi creatorlayerfragment@d676.initlisten ttlquifyfragmentv2@52bb.onattach packagefetchwavetask@bf55.run ramepreviewcomponent@482.startgener ganviewmodel@586e.createfeat 6makeupviewmodel@3113.selectfirs acefusionresprovider@cfcf.preload gfeaturefragment@9411.initaction perfintervalmonitor@6311.flush effectdraftcomponent@138b.savei2vdra editpreviewviewmodel@f9a1.updateaise autopicksession@14df.awaitnexts 6prefabpagefragment@feb3.observedat inpreviewtitlewidget@434a.setviewloc feaimenetworkapiimpl@b2d9.getaimerec 5autopicksession@14df.launchstra enscreenfuncprovider@4094.updategree ltiponboardingv3node@2b24.registerro ganviewmodel@586e.changeefusi	

EMAIL	FILE
canvasactionlistener@ff32.onscale gslstpanelviewmodel@c975.changeport aimeservicesimpl@2ffe.fetchaisel eatorstickerfragment@a9ce.initview bytebenchv2@5dc8.stop phasestackview@ebdd.animatepha eselectpagecomponent@f889.sceneactio qlambda@f73a.run aimetabviewmodel@6323.loadinitia drafthandler@f1f0.getdraftsi orstickerpageadapter@f578.bindfuncit faceinsetresflowimpl@5b2e.applyfacei verecordhelper@7eb6.effecthand musictrimviewmodel@3254.getmusicwa imakeuppanelfragment@e4b6.initdata animationviewmodel@e3f4.initfeatur amecovereditfragment@1c20.initchoose languageodeltask@fc90.downloadre editloadingcomponent@f330.oncreate iquefyv2pagefragment@4341.initshowde iprailpanelcomponent@65e4.checktaskr aimeservicesimpl@2ffe.createaime .makeupviewmodel@3113.shownotcon ti2iloadcomponent@5889.starti2ilo orstickerpageadapter@f578.onbindview ualframepreviewscene@5c67.changefram ewpager2heighthelper@f55d.requesthei templateapplyoldflow@8f3d.upgradedra modelpreloadwavetask@8ac2.run ionlatesthitsadapter@788a.onbindview tretchpersistentimpl@595d.deletefile gifsfragment@3c5.observedat nowpostvideoassem@41aa.onhostdest emegenerationsservice@ce2d.generateth aistyleresfetcher@6d7b.fetchstyle atorstickerviewmodel@4254.requestrec rtofficialrepository@5713.request 3prefabviewmodel@5840.loadeffect prefabpanelfragment@ff3c.initview facestretchviewmodel@bd65.setisfaces aimeservicesimpl@2ffe.hasaiself makeupviewmodel@3113.emitssucces +makeupresfetcher@9b27.fetchmakeu aiselfcarouselkt@ac9a.carousel nowbaselistassem@e120.setlistpad officialiconutilskt@8545.loadoffici ourcedownloadnewimpl@4e8a.startcoldb mecovereditviewmodel@c5c4.init facestretchviewmodel@bd65.applyeffec dotmatrixviewkt@eccf.dotmatrixv ameimagecutouteditor@22c0.changeprev faceinsetresflowimpl@5b2e.changetrac imgautogeniconhelper@4893.genbmpbyof canvasactionlistener@ff32.ontoucheve makeupviewmodel@3113.generateai	

iprefabpanelfragment@ff3c.initview EMAIL customizescene@55e6.successgen objecteffecthandler@657f.inneraddst	FILE
sictrimpanelfragment@bc06.initobserv deuploaduicomponent@4d62.oncreate nativescenemonitor@1ad6.stopintern 1ganviewmodel@586e.clearselec atorstickereditpanel@52bb.handlerreed facestretchviewmodel@bd65.changeface omptenhancecomponent@5992.translatep iprailpanelcomponent@65e4.onaiautocu feaimenetworkapiimpl@b2d9.getaigcquo componentviewmodelv2@695f.handlecllic aimelistrepo@d69d.getaimelis kprefabpagefragment@feb3.observedat ctcreatepipelineimpl@e2ca.onexportwh reupdateeventapiimpl@a3d.onfireeven 9aistyleresfetcher@6d7b.getstylera customdownloader@85b1.download +verticalmusicview@a7b8.getrecentm ttnewcreatorfragment@9077.delayloadi timewindowfilter@11c7.filter kloadingcontentscene@f88d.updateprog fectfeaturecomponent@168f.downloadre 6verticalmusicview@a7b8.getsearchm ortitlebarcontroller@3a4.registerli filteredassetpool@8672.getassets nowlikeviewmodel@da60.onclicklik ttnewcreatorfragment@9077.handleinfo eaimetabfragment@e8f3.checklogin videouploadcomponent@95e9.startuploa 8textstickerresflow@3f39.preloaddef ameimagecutouteditor@22c0.addaimatti archloadingcomponent@a395.showresult istadapterviewholder@1d11.bind viourcontentfragment@6376.compatoncl videouploadcomponent@95e9.pickvideo eocutoutplayfragment@c596.initview bytebenchv2@5dc8.loadtaskto ctcreatepipelineimpl@e2ca.logsavedra uefyprefabrepository@5cd4.getorcreat ctimgcreatorfragment@fc30.initlisten imestylepreviewscene@1044.checklogin .aimetabfragment@e8f3.setviewmod owdownloadbottomview@abfa.handler thememarqueeetextview@dc03.applymarqu editloadingcomponent@f330.regenerate otoseditpagefragment@8917.restoresel -aimetabfragment@e8f3.scrolltoto ttliqueryviewmodelv2@3195.startfaces 2collectmusicmanager@f40.loadcollec atorofficialrepoimpl@eb36.preloadran feaimenetworkapiimpl@b2d9.postaistyl makeupviewmodel@3113.launhaigc dialogcontentbuilder@336e.createdial lbumpickeralgolader@82cb.getdetectm pickloadingcomponent@6ba2.submitnewt	

istadapterviewerholder@50d.bind EMAILclusterproducer@ba79.producecan hannerviewcontroller@20d0.initobserv	FILE
1animationviewmodel@e3f4.onbehaviou cutoutcanvasfragment@a1bc.showtipifn longloadingpredictor@973f.predict runtimeevent@d9a0.record autopicksession@14df.start previewpagecomponent@e7db.onconfirmc aimetabviewmodel@6323.aihubclick facestretchviewmodel@bd65.setupforex companion@98eb.mergemodel nowlikeviewmodel@da60.handlenowp ganviewmodel@586e.onmediasel selector@9dcc.select bytebenchv2@5dc8.checktestr reparestagecomponent@58.repreparep objectpreparewavetask@36f5.run slistpanelcontroller@51da.back chestrationcomponent@b9ce.repick fyoriginalrepository@defb.followface .dynamichookhelper@e04c.switchtoma rcollectionlistassem@fdbd.onbind slistpanelcontroller@51da.oninit prefabviewmodel@5840.emiteditpr phaseitemholder@dd98.crossfadet amelaunchtask@d1f1.runasync jankframecollector@560d.stop ttnewcreatorfragment@9077.onviewcrea imagecutoutviewmodel@497d.triggeraut eupexchangeviewmodel@7f33.updatemake customdownloader@5e04.download topickpanelcomponent@d649.savedrafta eaimattingresfetcher@5768.preloadmat ttiponboardingv3node@13d5.tryshowani iprailpanelcomponent@65e4.sam makeupviewmodel@3113.clearcateg ttlquefyviewmodelv2@3195.selectloca inspectoretutils@602c.reportgree ttlquefyviewmodelv2@3195.cancel otiontemplateadapter@7abb.onbindview 9amedebbugfragment@39de.doinit languageodeltask@fc90.forward -prefabeditviewmodel@58ec.saveselect picklotteddownloader@294b.downloadto otoseditpagefragment@8917.updatealbu fectfeaturecomponent@168f.preloadloa facestretchviewmodel@bd65.refreshkey componentviewmodelv2@695f.handlegene ctcreatepipelineimpl@e2ca.resolvecro baseclusterstrategy@860d.cvscan editpreviewviewmodel@f9a1.observerre prefabviewmodel@5840.clearselec gifsviweviewmodel@472a.downloadgi fectfeaturecomponent@168f.applyprefa enscreenfuncprovider@4094.changetrac bfourpicturefragment@febe.mobdeletp	

stickerguidefragment@1ac2.registerob EMAIL Electhandler@50af.autochange lbummultiselectlogir@8114.bindholder	FILE
+prefabviewmodel@5840.loadeffect rtoofficialrepository@5713.createoffi imgautogeniconhelper@4893.applyeffec usiongangepagefragment@5dee.initview .alphavideoscene@9f94.animlisten photostorehelper@25da.getphotodi +autopickpanelscene@9db7.adjustcove eatorstickerfragment@a9ce.parseselec amemodelpreloadtask@f983.modelprelo ckerfacefusionloader@46fb.load ltiponboardingv3node@2b24.tryshowani voicerearchviewmodel@8ed6.startdotup tlepreviewviewmodel@9526.getpagesta qpreviewmodeladapter@a893.onbindview textinittaskwavetask@c15a.run 0ganviewmodel@586e.applyfacef enstyleresultmanager@35df.openresult thememarqueetextview@dc03.ontextchan inpreviewtitlewidget@434a.onconfigur screenthumbgenerator@4b96.tryshotscr atorstickereditpanel@52bb.playmusicw romotionbottomdrawer@6faa.initview ecutoutpanelfragment@2aad.onactivity ttpreviewmodehandler@bae4.initprevie rsecondobjectadapter@a42d.onbindview normalhandlerimpl@927f.update fectpreviewviewmodel@ace0.regenerate Ottlquifyfragmentv2@52bb.mobcategor stickerselecthandler@50af.selectobje ormigrateserviceimpl@95ca.awaitchang selectpanelcomponent@4222.fetchmodel 7nowsharebottomassem@8f07.sharebutto elfawemecachemanager@5c53.deletecach bprefabpanelfragment@ff3c.bindseekba ramepreviewcomponent@482.oncreate hsladjustfragment@cc19.initview localconfigsfragment@720d.observemat uefyprefabrepository@5cd4.eecreatefe ickeroperatefragment@36ad.initobserv autopickpanelscene@9db7.scheduleco fyoriginalrepository@defb.load imationpanelfragment@9f44.initview amevelaunchtask@f810.oncreate ckpanelguidefragment@b009.updatescro actionviewmodel@3d37.filternots ameralaunchcomponent@a0cb.awaitpages viewlazyinittask@9248.run 1baseclusterstrategy@860d.dogenerate gridadapter@5c48.onbindview 4consumercoordinator@9d43.consumeava ickerrouterprocessor@1f13.process xtstickerinputlayout@542c.showinputl kttlquifyfragmentv2@52bb.initobserv amecorepresenterimpl@6f97.runvelaunc	

gpicturecropfragment@16c2.getstyleta EMAIL Helpfragment@9fd9.initview cialiconlistfragment@1f25.startobser	FILE
mainpackagefetchtask@1fcd.run picklotteddownloader@294b.downloadlo eeklyclusterstrategy@9057.dogenerate archloadingcomponent@a395.submitaigc ourcedownloadnewimpl@4e8a.startdownl ickrootslotcomponent@4cb3.showautopi stprefabpagefragment@a912.applyadjus modelmanager@75cd.downloadmo ameprojectcreatetask@5356.run customizeviewmodel@8957.performapp tv2vreeditgroupscene@ac19.initobserv canvasactionlistener@ff32.oncornerdr onboardingv2cardview@b442.initpopove 2customizeviewmodel@8957.reportcl chestrationscomponent@b9ce.startautop meonboardingwavetask@78c8.run ganviewmodel@586e.fetchganli amevesdkinittask@222.run .draftupgradehelper@28d6.updatedraf mainpackagefetchtask@1fcd.needforceu normalhandlerimpl@927f.onscale editpreviewviewmodel@f9a1.discardcur nowcachedelegate@6dbd.ondeleteno ompatibilitytuxsheet@8c3.tasksimge 1facestretchfragment@cdc6.onconfigur lbumpickeruidelegate@b7b1.init ailfragmentviewmodel@c61.oncustomiz gcreatorcamerahelper@1908.opencamera componentpreparer@b449.run facestretchfragment@cdc6.initobserv +makeupviewmodel@3113.loadeffect 2stickerresflowimpl@8b68.obtainaddf mfacestretchfragment@cdc6.initobserv ontouchdraghandler@960f.ontouch 5prefabeditviewmodel@58ec.notifycont slistpanelcontroller@51da.handlechan omptenhancecomponent@5992.innerreque meprojectpreparer@6513.processdra ttpromotionfragment@f369.initview animationviewmodel@e3f4.loadeffect calendarmonthview@efb3.enableagai agifsfragment@3c5.initview autopickpanelscene@9db7.tryexitloa odelpictureviewmodel@fa9c.loadmodell ttnewcreatorfragment@9077.mpreviewti ticersearchfragment@bb76.replacegip makeupviewmodel@3113.selectedai fyoriginalrepository@defb.waiteffect tuspublishedrepoimpl@cbec.save2disk lbottombarcontroller@1f1b.setupright voicerearchhelper@9a5c.performvoi 0draftupdater@ff1a.updatedraf ultnavigationhandler@e1fd.navigateto ttnewcreatorfragment@9077.onconfigur	

onboardingv2fragment@d2c5.setdata EMAILlionviewmodel@e3f4.clearselec imenewcustomizescene@55e6.associated	FILE
ttliuefyviewmodelv2@3195.selectpref facestretchviewmodel@bd65.changeprev amestickertab@f726.handlelic bfourpicturefragment@febe.gosinglevi videocutoutviewmodel@ffde.removeback videocutoutviewmodel@ffde.updateprog autopickpanelscene@9db7.onshow previewpagecomponent@e7db.savedraft enscreenfuncprovider@4094.portraitcu +objecteffecthandler@657f.scopedadds econfigpagecomponent@842b.fetchstyle camebasetooltab@fb4c.attachcont qprefabeditfragment@56ec.observecon bytebenchv2@5dc8.start metricschecker@577.run aichoosemusicmanager@da6d.downloadmu ti2iloadcomponent@5889.commitgree ffectaudioscrollview@d2a5.startscrol editpreviewviewmodel@f9a1.loadmodelp aycomponentviewmodel@715b.performpol ttnewcreatorfragment@9077.observedou bgifsfragment@3c5.observedat inpreviewtitlewidget@434a.calculatea fectdownloaderhelper@3320.localdownl 9collectmusicmanager@f40.loadmoreco ganviewmodel@586e.oncommitup 2aistyleresfetcher@6d7b.getstylera eatoralbumfragmentv2@90fe.initlisten refabsublistloadtask@dbe7.run .ganviewmodel@586e.createganv amecorepresenter@ee9a.preparereres bfourpicturefragment@febe.onviewcrea isdayclusterstrategy@81e2.scanyearcl imakeuppagefragment@9516.observedat secondobjnormalrepo@d5b7.fetchpanel amevideocutoutplayer@403b.setmatting -widgetlocationimpl@5c3c.recordpane statistichelper@8108.onevent nowmediacachemanager@3ec6.deletecach 1nowareamonitorassem@4391.sam gpicturecropfragment@16c2.initcropvi 6baseclusterstrategy@860d.loadfilter verecordhelper@7eb6.initvereco texteditactivity@468a.update .ganviewmodel@586e.loadfacefu rtofficialrepository@5713.onofficial ttliuefyviewmodelv2@3195.done drafhandler@f1f0.openpublis ffectimgcropfragment@6e89.initlisten lreeditpaneladapter@da98.bindselect otiondataresprovider@6cc3.fetchbanne gcreatorcamerahelper@1908.init languagemodeltask@fc90.preloadint uctcomponentwavetask@509e.run	

aimakeuprepo@5ae4.loadaimake EMAIL ingcomponent@6ba2.observechi asrstreamtask@8422.createinit	FILE
facestretchviewmodel@bd65.changemirr ameupgradedrafttask@e63f.upgrade aganpanelfragment@9fd9.bindseekba omotionbanneradapter@6b1c.onbindview kganviewmodel@586e.onfacefusi delivery@5dd5.deliverloc drafthandler@f1f0.downloadic seteditpagecomponent@a788.downloadai -makeupviewmodel@3113.cancelgene reparestagecomponent@58.ensurestyl mganpanelfragment@9fd9.initphotop amecanvasadjustlogic@563a.adjustamec 7normalhandlerimpl@927f.updatecall secondobjectfetcher@49c2.fetchnorma recapclusterstrategy@674c.generateye uefyprefabrepository@5cd4.doneifiswo hganpanelfragment@9fd9.initobserv seteditpagecomponent@a788.waitmodeli amestickertab@f726.preloadsti gttpromotionfragment@f369.initview effectdraftcomponent@138b.openpublis topickserviceapiimpl@43d4.checkaiaut picklotteddownloader@294b.ensurelott editpreviewviewmodel@f9a1.tryagain ganpanelfragment@9fd9.onactivity stprefabpagefragment@a912.updateenab picklotteddownloader@294b.ensureedit oderationhandlerimpl@1de9.handle makeuppresfetcher@9b27.getaimakeu archloadingcomponent@a395.starti2ilo amecorepresenterimpl@6f97.awaitretry recapclusterstrategy@674c.dogenerate localconfigsfragment@720d.handlerrecl gpicturecropfragment@16c2.stoploadin gpicturecropfragment@16c2.doonfinish baseclusterstrategy@860d.runpipelin feaimenetworkapiimpl@b2d9.postaimecr 5makeuppanelfragment@e4b6.calculatea videouploadcomponent@95e9.fetchststo fectmodelsselectscene@98b.initdata odelpicturereviewmodel@fa9c.select gifsviemodel@472a.searchgifs +taskrepositoryimpl@c0e3.fetchaigct stprefabpagefragment@a912.initdata tservicelistenerimpl@d51a.trytrigger idetaskdialogmanager@215d.showcompat kganpanelfragment@9fd9.initphotop aimetrstylemanager@6ec4.performapp selector@9dcc.ondownload cmakeuppagefragment@9516.observedat makeupviewmodel@3113.selectcolo ttpreviewmodehandler@bae4.swaptomode draftupgradehelper@28d6.upgradedra hubmainviewmodel@a63a.getstylede	

itionstatustextassem@b2f.starttimer EMAILuprepo@5ae4.storetofil assetreverseproducer@54de.produceran	FILE
sttpanelhomefragment@8f3f.observecor imgautogeniconhelper@4893.genicon canvasactionlistener@ff32.onlongpres enscreenfuncprovider@4094.changeplac tretchpersistentimpl@595d.deleteloca ganviewmodel@586e.fetchpanel ideopreviewcomponent@f19c.getlastfra ctsettingspanelscene@878.initview aycomponentviewmodel@715b.loadprevie 7alphavideoscene@9f94.maybestart verticalmusicview@a7b8.buildcolle selectpanelcomponent@2b29.fetchmodel eautocutoutcomponent@4327.autocutout 3aimecreationmanager@e605.aimecreati deletemanager@c8e8.deleteaist 6gifsfragment@3c5.initview atorstickereditpanel@52bb.checkshowg customizeviewmodelv2@83ed.handlefree topickserviceapiimpl@43d4.getautopic 2filteredassetpool@8672.getassetsw imgautogeniconhelper@4893.prepareame draftupgradehelper@28d6.downloaddef ttnewcreatorfragment@9077.onsaveinst seteditpagecomponent@a788.gotoprevie userexpmapmanager@4632.onappexit seteditpagecomponent@a788.startprevi stickerfragmentextkt@8f12.initbottom drafhandler@f1f0.savedraft +amecutouttab@330b.gotocutout prefabeditfragment@56ec.onclose rcollectionlistassem@fdbd.onviewcrea attpanelhomefragment@8f3f.openpanelo 3autopicksession@14df.awaitnexts am@736.run 1autopicksession@14df.awaitnexts inpreviewtitlewidget@434a.pagestateo makeuppanelfragment@e4b6.initdata collectmusicmanager@f40.collectmus ieffectlokicomponent@e537.fetchaigcp archloadingcomponent@a395.getresulti userexpmapmanager@4632.onappenter imagecutoutviewmodel@497d.preview seteditpagecomponent@a788.preloadat atordraftserviceimpl@96ac.getdraftin .customizeviewmodel@8957.reportpage 3ganviewmodel@586e.oncommitup editpreviewviewmodel@f9a1.updateaime facestretchfragment@cdc6.exit imagecutoutviewmodel@497d.changebrus feaimenetworkapiimpl@b2d9.postaigcdi absonboardingv3node@83df.destroy ganviewmodel@586e.setseekbar oderationhandlerimpl@1de9.keepprafto bcarouselplayerview@e8e0.makevideos	

ttpromotionviewmodel@b3db.checkrespa MAHchrepository@39dc.apply topickpanelcomponent@d649.checktaskr	FILE
slistpanelcontroller@51da.setupbydef imestylepreviewscene@1044.handleload pickloadingcomponent@6ba2.onrunindra autopickpanelscene@9db7.initview ganviewmodel@586e.clearselec ttnewcreatorfragment@9077.initconge ormigrateserviceimpl@95ca.packdrafti prefabeditviewmodel@58ec.done reparestagecomponent@58.preparepro canalysiscomponent@8894.scanassets +globaleventhelper@930c.emitonboar atorstickereditpanel@52bb.handleswit pickloadingcomponent@6ba2.setupprogr acestretchrepository@39dc.handleaddn estretchresviewmodel@7ac.downloadfa ocaliconlistfragment@8061.initdirlis facestretchfragment@cdc6.onsaveclic makeupviewmodel@3113.updatecate nscreenpromotionimpl@aca7.needshowwe makeupviewmodel@3113.changeacti emanagerinitwavetask@d87b.run imestylepreviewscene@1044.navigateed tickerfeaturehandler@84e5.onsendadds 0aimeimagerepo@b921.downloadim gtoolseditcontroller@c679.saveimg -iamecorepresenter@89d0.runasyncun aycomponentviewmodel@715b.fetchtasks enscreenfuncprovider@4094.applygreen ameimagecutouteditor@22c0.export fyoriginalrepository@defb.apply atorstickereditpanel@52bb.opencutout qlambda@f73a.accept imagecutoutviewmodel@497d.export 8aimecreationmanager@e605.gotoeditpa +makeupviewmodel@3113.saveaimake 6ganviewmodel@586e.toggleface amevelaunttask@f810.dooncreate 5snowsharebottomassem@8f07.sharebutto ffectimgcropfragment@6e89.initcropvi pickloadingcomponent@6ba2.reportsave kmakeuppagefragment@9516.observecon sprefabeditfragment@56ec.observecon baseautocutoutnode@483c.process feaimenetworkapiimpl@b2d9.getaimedis 1facefusionrepo@41cc.changeitem normalhandlerimpl@927f.onrotate 0consumercoordinator@9d43.hasavailab prefabviewmodel@5840.loadeffect perintervalmonitor@6311.flushpart facestretchfragment@cdc6.onbackclic verseclusterstrategy@818a.processnex templateapplynewflow@e669.applytempl bfourpicturefragment@febe.quotacheck uefyprefabrepository@5cd4.apply	

alumpickerrepo@7798.fetchalbum EMAIL fragment@b23d.initdata prefabpanelfragment@ff3c.initdata 2draftupdater@ff1a.updatedraf delivery@5dd5.deliverbin reparestagecomponent@58.waitstylem nowglobalstateutilkt@c142.subscribe umakeuppagefragment@9516.launcheffe transcodenode@bb9a.onprocess voicesearchfragment@47ab.ondisplayw ttnewcreatorfragment@9077.playmusico delivery@5dd5.delivereve iontplviewController@1a31.bindobserv reparestagecomponent@58.setdatatof aimetabviewmodel@6323.updateaime faceinsetresflowimpl@5b2e.waitframeu 1prefabviewmodel@5840.loadeffect htnesschangeobserver@7ddd.onbrightne 7musictrimviewmodel@3254.getmusicwa effectaudiowaveview@f30c.setaudiowa +draftupgradehelper@28d6.prepareupg ttpreviewmodehandler@bae4.getorfetch atorofficialrepoimpl@eb36.handlerreqs modelselectimpl@5ce2.fetchfacem pickloadingcomponent@6ba2.ondiscard fyoriginalrepository@defb.createnewf p@w.a5 autopicksession@14df.awaitnextr 9makeuppagefragment@9516.observedat fusionofficialloader@efe7.onofficial ganviewmodel@586e.onfacefusi meprojectpreparetask@6513.getdraftin lmodepicturefragment@490e.initbottom gpicturecropfragment@16c2.downloadta meprojectpreparetask@6513.run 3aistyleresfetcher@6d7b.getmodelef +amenewflowtexttab@32b6.handleedit ackingpanelviewmodel@98d3.downloadan erdonemodeuidelegate@cc84.oninit edithitpanelfragment@5674.onfinishfr ramepreviewcomponent@6cce.oncreate sealumpickermonitor@9b40.loadfinish ttnewcreatorfragment@9077.observefor 2bytebenchv2@5dc8.initcollec imagecutoutviewmodel@497d.downloadre imagecutoutviewmodel@497d.undo draftimpl@6e0f.cleancache pickloadingcomponent@6ba2.getorcreat pickloadingcomponent@6ba2.findprevio stickerframeimpl@91f8.hideallsho ewpager2heighthelper@f55d.updateheig ttliquifyfragmentv2@52bb.initview ffectingcropfragment@6e89.doonfinish tuspublishedrepoimpl@cbec.doload acefusionresprovider@cfcf.getresfrom gpicturecropfragment@16c2.startloadi projectmanager@dca6.createfeat	FILE
--	------

ewpager2heighthelper@f55d.attach Email b:inresprovider@cfcf.getfacefus recapclusterstrategy@674c.generatemo	FILE
ittliquifyfragmentv2@52bb.observewhe makeupviewmodel@3113.removeaima 3ganviewmodel@586e.savelocalf hubmainfragment@b23d.getmoredat cutoutnode@f12.onprocess ttnewcreatorfragment@9077.savedraft iprefabpagefragment@feb3.observedat 6ganviewmodel@586e.fetchpanel perfintervalmonitor@6311.markend stickerselecthandler@50af.replacesti amecutouttab@330b.onactivity amecanvasadjustlogic@563a.updateonbo aimakeuprepo@5ae4.checkandlo musicpanelcomponent@b870.showmusicp picklotteddownloader@294b.awaitdefer 3ganpagefragment@ccac.observedat makeupviewmodel@3113.cancelcate odelresourceprovider@c3f1.getfacemod creenrecordingfilter@43d1.filter seteditpagecomponent@a788.observecam drafhandler@f1f0.onmaineven ganviewmodel@586e.applyprefa eratorstickerfragment@a9ce.initdata reatorcamerafragment@db9c.initview .collectmusicmanager@f40.initcollec visionvisibility@2ff1.record templateapplynewflow@e669.updandsele iktokaigcserviceimpl@ca7b.submitwork reatoralbumtophintvm@c751.onclosecli gcreatorcamerahelper@1908.injectcomp customizeviewmodelv2@83ed.bubblechan mgcreatorv2viewmodel@7599.applyeffec ailfragmentviewmodel@c61.delstyle aimetabviewmodel@6323.getaimemod previewpagecomponent@e7db.onCreate prefabeditviewmodel@58ec.validatest seteditpagecomponent@a788.oncancelbt ckeroperateviewmodel@8eb0.selectfeat terpipelinecomponent@7672.applyl1fil plusbuttoncontroller@4766.waitfacest amenewflowtexttab@32b6.addsticker ti2iloadcomponent@5889.onCreate localconfigsfragment@720d.initview nlistlocalrepository@143f.request outbottomtabfragment@feef.downloadre -filteredassetpool@8672.getassets p@s.a5 7baseclusterstrategy@860d.runpipelin editpreviewviewmodel@f9a1.fetchaimem amebaseloadingtab@e052.injectretr ttliquifyfragmentv2@52bb.onviewcrea ailfragmentviewmodel@c61.onprofileb imgautogeniconhelper@4893.preparerem ittliquifyfragmentv2@52bb.initview	apktool_out/lib/armeabi-v7a/libdex_df_ship.so

asetemplateapplyflow@6e5e.fetchmodel EMAILviewmodelv2@3195.followface fectfeaturecomponent@168f.createfeat	FILE
uploadstatuswavetask@8dac.run ttnewcreatorfragment@9077.observepag eatorstickerfragment@eb94.handlesele aimelauncherfragment@9de9.normalpage perfevent@a4de.record caliconlistviewmodel@4695.createrequ eatoralbumfragmentv2@90fe.setupicont cameraassetfilter@f334.filter tretchpersistentimpl@595d.updateloca stprefabpagefragment@a912.done makeupviewmodel@3113.selectasse componentviewmodelv2@695f.observewor pickloadingcomponent@6ba2.handletask pickloadingcomponent@6ba2.querydraft 0aimeservicesimpl@2ffe.getcurrent gtoolseditcontroller@c679.saveiminn aprefabpagefragment@feb3.observedat templateapplynewflow@e669.upgrade stickerguidefragment@1ac2.lottiecanc localconfigsfragment@720d.applyeffec atortexthomefragment@5114.addsticker eatorstickerfragment@eb94.addsticker 2hubmainfragment@b23d.itemclick ttliquefyviewmodelv2@3195.doapplycle amecorepresenterimpl@6f97.onactivity themeclusterproducer@30fc.producecan imenewcustomizescene@55e6.effecttemp ailfragmentviewmodel@c61.mobdeletep eampipelineexecution@1e2.initialize ttnewcreatorfragment@9077.initlayerl mgcreatorv2viewmodel@7599.commitgree aimakeuprepo@5ae4.remove statebundle@c896.emit makeupviewmodel@3113.checkfiles isdayclusterstrategy@81e2.dogenerate dprefabpanelfragment@ff3c.bindseekba seteditpagecomponent@a788.observevid facefusionrepo@41cc.getfusionm baseclusterstrategy@860d.requestthe componentviewmodelv2@695f.reportstar slistpanelcontroller@51da.changeauto +stickerframeimpl@91f8.changecorn normalhandlerimpl@927f.onmove lbottombarcontroller@1f1b.setupcente kageandscripfetcher@cb75.fetchmainp faceinsetresflowimpl@5b2e.preloadfac atordraftserviceimpl@96ac.packagedra producercoordinator@371.ensureprog aimecreationmanager@e605.aimecreati tservicelistenerimpl@d51a.triggernet eaimattingresfetcher@5768.downloadai aimetabviewmodel@6323.unloginloa liquefyimpl@9f1.refreshmai facestretchviewmodel@bd65.requestdat	

rchcontainerfragment@c389.onviewcrea EMAIL networkapiimpl@b2d9.postaigcge icelistenerproxyimpl@3459.addlistene	FILE
aimeinterview@b693.setbuttons amecorepresenterimpl@6f97.updateproj videocutoutviewmodel@ffde.showcompil 5autopicksession@14df.awaitnexts pickloadingcomponent@6ba2.submitorre 6reeditutils@c260.preloadgre makeupviewmodel@3113.executeame .hubmainfragment@b23d.itemclick bumsingleselectlogic@1ca8.bindholder asrstreamtask@8422.ensuremode ctcreatepipelineimpl@e2ca.writelabel prefabviewmodel@5840.initfeatur meprojectpreparetask@6513.preparev2 lttliquifyfragmentv2@52bb.initseekba aimemodelreporter@b81d.reportstar baseclusterstrategy@860d.timed baseclusterstrategy@860d.consumeacan creatorstylerepoimpl@eb15.clear ibilitydialoghandler@2de2.showcompat ktpromotionfragment@f369.initobserv archloadingcomponent@a395.commitgree 6consumercoordinator@9d43.triggernon bytebenchconnection@a5b1.onservicec reparestagecomponent@58.waitmodeli lprefabeditfragment@56ec.observeval ffectimgcropfragment@6e89.onapplyeff dgifsfragment@3c5.observadat .amerouter@3af6.handlerrou ttnewcreatorfragment@9077.createsubm imagecutoutviewmodel@497d.init alalbumpickermmonitor@fa41.loadercall omptenhancecomponent@5992.enhancepro reparestagecomponent@58.preparefea 4tttoolbarwidget@a9e.addtoolbar nowpostbasecellassem@351e.assembleui companion@98eb.checkandme delivery@5dd5.delivermem inpreviewmusicwidget@e63e.getdraftin ffectimgcropfragment@6e89.geticonbit atorstickereditpanel@52bb.featureupd jganpanelfragment@9fd9.initobserv customizeviewmodelv2@83ed.bubbleclie delivery@5dd5.delivermes tiktokgifrepository@f767.downloadgi 7prefabviewmodel@5840.loadeffect triggerviewmodel@22d9.load eampipelineexecution@1e2.processsyn amecorepresenter@ee9a.bindsurfac defaultfetcherimpl@a191.load creatorstylerepoimpl@eb15.createands creendataresprovider@2dc8.preloadpre ttpromotionviewmodel@b3db.fetchdata ti2illoadingcomponent@5889.shotscreen imationpanelfragment@9f44.initobserv	

cefusionfuncprovider@d4bb.changetrac EMAIL enmarqueetextview@dc03.onvisibili jankframecollector@560d.onframeend	FILE
0verticalmusicview@a7b8.buildrecom ckcliprailpanelscene@f69d.runshowsli redraftmodelwavetask@3d29.run templateapplyoldflow@8f3d.refresheff lbottombarcontroller@1f1b.setupleftb reparestagecomponent@58.oncreate aimakeuprepo@5ae4.removeaima atorofficialrepoimpl@eb36.getrandomo pickloadingcomponent@6ba2.handlenonm tcreatorlayeradapter@bc73.seticon templateapplyoldflow@8f3d.onupgraded recoveryimpl@2170.onrestore filteredassetpool@8672.loadslice prefabitemadapter@7279.performuse kfacestretchfragment@cdc6.initobserv 9baseassethandler@7ec4.newupdatec amebasetooltab@fb4c.movetoscre opickpanelguidescene@80d3.updatescro eutocutoutcomponent@4327.calculateu pickloadingcomponent@6ba2.observevas cefusionfuncprovider@d4bb.changefusi fectpromptinputscene@9194.updateacti af@73d.run 0baseclusterstrategy@860d.checkandtr pickloadingcomponent@6ba2.handleretr owmutualrelationview@6b4b.bindavatar tchcanvasadjustlogic@bb02.adjustcanv ttnewcreatorfragment@9077.startstick promptinputcomponent@dac6.onprompten makeupresfetcher@9b27.getmakeupp terpipelinecomponent@7672.applyl2sec aa@742.run seteditpagecomponent@a788.showsavedr enscreenfuncprovider@4094.checkgreen cbottomtabadapter@976c.onbindview warchivecalendarcell@2337.onbinditem feaimenetworkapiimpl@b2d9.postaimeap prefabviewmodel@5840.createfeat keffecteditorcontext@5cb5.initialize seteditpagecomponent@a788.fetchprese l@7c13.run cutoutcanvasfragment@a1bc.processaut makeupviewmodel@3113.createaima nprefabeditfragment@56ec.observeval delivery@5dd5.dumpmemory kageandscriptfetcher@cb75.fetchmainr ameimagecutouteditor@22c0.copyimage amevesdkinitwavetask@2eac.run enstyleresultmanager@35df.removeload ailfragmentviewmodel@c61.getstylede perfevent@a4de.onframedro econfigpagecomponent@842b.fetchprese -alphavideoscene@9f94.onseg0star angmodeldownloadtask@7c68.startorres	

makeuppresfetcher@9b27.fetchmakeu EMAIL efactoryimpl@3118.createstyl gpicturecropfragment@16c2.onapplyeff	FILE
reparestagecomponent@58.translatep 7collectmusicmanager@f40.initunlimi efabcategoryloadtask@8de0.run gslstpanelviewmodel@c975.changeauto asrstreamtask@8422.preloadint ormigrateserviceimpl@95ca.migratedra ttnewcreatorfragment@9077.initaimake styleselectcomponent@eeed.recorddata longloadingpredictor@973f.countasset hsladjustfragment@cc19.recoverlas ectmediadetectorutil@1704.detectorim effectmediadetector@cd93.detectface facestretchviewmodel@bd65.setupforcr 9messagecarouselvew@c57a.schedulero -amecutouttab@330b.gotocutout imakeuppanelfragment@e4b6.initview animationviewmodel@e3f4.done amecutouttab@330b.getsticker .collectmusicmanager@f40.loadmoreco archloadingcomponent@a395.onsavedraf tgreenscreenhelperv1@b92c.genveframe 0hubmainfragment@b23d.itemclick ceinsetpanelfragment@3e93.initdata aimelauncherfragment@9de9.navigateto canvasactionlistener@ff32.onpointdra enstyleresultmanager@35df.postnaviga autopicksession@14df.repick +stickerframeimpl@91f8.showfacefo idereditpagefragment@c761.onviewcrea oubleclicklikelayout@fa95.doafterani econdobjectviewmodel@9b86.fetchpanel eatorlayerviewholder@b52a.onstatecha fganpagefragment@ccac.observedat picklotteddownloader@294b.ensurelong adjustpanelutiltextkt@cd4.createadju stickerpanelimpl@54a9.showsticke dailyclusterstrategy@ea07.dogenerate stylerepository@15e0.getstyle gprefabpanelfragment@ff3c.initdata opickpanelguidescene@80d3.changestat localconfigsfragment@720d.refreshdat +baseassethandler@7ec4.schedulefr ffectimgcropfragment@6e89.getstyleta perfintervalmonitor@6311.markbegin mttliquifyfragmentv2@52bb.initobserv 6ganpagefragment@ccac.observedat ailfragmentviewmodel@c61.quotacheck ganviewmodel@586e.initfeatur makeupviewmodel@3113.emitparams tickersearchfragment@bb76.addgiphyst amegreenscreentab@f75.applygreen amegreenscreentab@f75.handletabc ctcreatepipelineimpl@e2ca.ondraftore amelaunchtask@d1f1.await	

ttliuefyviewmodelv2@3195.gethandled EMAIL changeobserver@10a.onvolumech yfastclusterstrategy@ab24.dogenerate	FILE
effecteditoractivity@a2af.onCreate ffectimgcropfragment@6e89.stoploadin ideopreviewcomponent@f19c.onCreate lbumpickeralgoloader@82cb.load express4runner@e270.getparsefu imationpanelfragment@9f44.initdata prefabeditviewmodel@58ec.validateph onboardingv3fragment@a2a8.registerob jttliquifyfragmentv2@52bb.initseekba enstyleresultmanager@35df.generateon eeklyclusterstrategy@9057.processnex makeupviewmodel@3113.downloadre eprogresscoordinator@b04d.runrelease keffecteditorcontext@5cb5.ttdoafterr animationviewmodel@e3f4.onpagefixe eautocutoutcomponent@4327.registerob ameautocutoutrepo@8606.chaincallb 1makeupviewmodel@3113.loadeffect secondobjectfetcher@49c2.fetchpanel atorstickerviewmodel@4254.updatelast ourcedownloadnewimpl@4e8a.updatereso nowsharebottomassem@8f07.onhostpaus gtoolseditcontroller@c679.saveoffici aimakeuptophintvm@5ac4.onclosecli ganpanelfragment@9fd9.bindseekba 3phasestackview@ebdd.animatepha ckpanelguidefragment@b009.changestat -customizeviewmodel@8957.getfreecre lectionlistviewmodel@a262.onloadbefo stprefabpagefragment@a912.resetall hsladjustfragment@cc19.resetvalue 2textstickerresflow@3f39.obtainaddf jankframecollector@560d.start nimationpagefragment@b779.observedat amecorepresenterimpl@6f97.awaitproje progresssmoother@1224.startfilli bfourpicturefragment@febe.delstyle hsladjustfragment@cc19.applyadjus 0amecutouttab@330b.preloadfac categoryitemview@b2ec.updatedata ganviewmodel@586e.eecreatefe singledetailfragment@8081.showsaveto 6alphavideoscene@9f94.performsub gmakeuppanelfragment@e4b6.initdata behaviourimpl@96c1.showprevie enstyleresultmanager@35df.styledetai gmakeupviewmodel@3113.loadeffect imgautogeniconhelper@4893.loadrandom +filteredassetpool@8672.getassetsw faceinsetresflowimpl@5b2e.changeface ckedraftextraimpl@fabf.savefile tupublishedrepoimpl@cbec.fetchusers bbottombarcontroller@48f3.setupright customizeviewmodelv2@83ed.newcustomi	

faceinsetresflowimpl@5b2e.getlayerdi EMAIL arebottomassem@8f07.clearconta 8officialconutlskt@8545.loadoffici	FILE
creatorbaseviewmodel@6ca3.emitevent defaultfetcherimpl@a191.doload mestickercutoutfuckt@8cf2.addorrepla fganpanelfragment@9fd9.initview consumercoordinator@9d43.hasonlypre iprailpanelcomponent@65e4.savedrafta inglepicturefragment@9.onviewcrea gonboardingv3tipview@64f2.initview ifacestretchfragment@cdc6.initview 9prefabpagefragment@feb3.observedat 2ganviewmodel@586e.loadfacefu topickserviceapiimpl@43d4.trackuploa cprefabeditfragment@56ec.onviewcrea ttnewcreatorfragment@9077.startameco noweventregistry@2a90.fire acestretchrepository@39dc.applyeffec delivery@5dd5.deliversam ecutoutpanelfragment@2aad.getsticker fectfeaturecomponent@168f.replaceand stylerepository@15e0.usecache loadinggate@35b9.tryfire ntalviewshowctrlimpl@4f40.triggersho inpreviewtitlewidget@434a.reqandupda aimeintroview@b693.setupscrol makeuppanelfragment@e4b6.initview feaimenetworkapiimpl@b2d9.getstylede stprefabpagefragment@a912.resetallva atorstickereditpanel@52bb.reportinsp selectpanelcomponent@4222.sceneactio delivery@5dd5.delivercpu componentviewmodelv2@695f.openstyler amedbinittask@1716.run delivery@5dd5.dumpcpu 3ganviewmodel@586e.setfacefus +editormodelimpl@5d2e.selectandc prefabviewmodel@5840.eecreatefe stickerframeimpl@91f8.alwayshide wabsonboardingv3node@83df.dowhenloca reditpaneladapter@da98.bindselect mestickercutoutfuckt@8cf2.handlesele hubmainfragment@b23d.delaimemod ckcliprailpanelscene@f69d.onshow effectmodeuidelegate@240a.oninit eampipelineexecution@1e2.processasy taskexecutor@f5da.call imagecutoutviewmodel@497d.reverse2db makeupviewmodel@3113.selectpref ickrootslotcomponent@4cb3.warmupalph ameimagecutouteditor@22c0.initmattin amevideocutoutplayer@403b.prepareasn ramepreviewcomponent@482.launchuplo ttpanelhomefragment@8f3f.openpanelo texteditpagefragment@ce45.onviewcrea duplicateinterceptor@cafa.intercept	

hsladjustfragment@cc19.getadjustf EMAILpresenterimpl@6f97.prepareres onboardingv2fragment@d2c5.updaterard	FILE
gcreatoreffecthelper@7d21.loadrafte amecorepresenter@ee9a.updateproj kstickerpagefragment@e4f5.initobserv 2nowsharebottomassem@8f07.startshare hsubverecorderhelper@2fed.initsubver uabsonboardingv3node@83df.dowhenloca ttlquefyviewmodelv2@3195.mirror zemonitorserviceimpl@c952.calculatef verseclusterstrategy@818a.dogenerate ameimagecutouteditor@22c0.init acestretchrepository@39dc.handle repl gganpanelfragment@9fd9.bindseekba effecthintviewmodel@ee0c.load otoseditpagefragment@8917.onviewcrea jarvisuploader@bb4f.reportanr 0draftupgradehelper@28d6.getupdated seteditpagecomponent@a788.setdatatof cutoutbottomfragment@2b85.initprevie themeclusterproducer@ba79.getcluster atortexthomefragment@5114.ontextedit canvasactionlistener@ff32.onmove gaimetabfragment@e8f3.checklogin eimagecutoutactivity@e7b9.initobserv angmodeldownloadtask@7c68.downloadli canvasactionlistener@ff32.onrotation verticalmusicview@a7b8.loadingvie uttpanelhomefragment@8f3f.observecor fyoriginalrepository@defb.doneifiswo ttfeatureoperator@9edd.copy anelcomponentmanager@d39d.initcompon creendataresprovider@2dc8.getgreensc feaimenetworkapiimpl@b2d9.postaimest tservice listenerimpl@d51a.onafterdel ieffectlokicomponent@e537.fetchstyle ttlquefyviewmodelv2@3195.stateselec aimeservicesimpl@2ffe.trycustomi ttnewcreatorfragment@9077.selectobse sicrimpanelfragment@bc06.initview eampipelineexecution@1e2.complete editpreviewviewmodel@f9a1.observerst creendataresprovider@2dc8.preparegre inpreviewmusicwidget@e63e.checkshowm dailyclusterstrategy@ea07.processnex aimetabfragment@e8f3.setviewmod facefusionrepo@41cc.addfacefus imagecutoutviewmodel@497d.redo ceinsetpanelfragment@3e93.updateface secondobjcombinerepo@822a.fetchpanel companion@98eb.warmloadmo archloadingcomponent@a395.oncreate nscreenpromotionimpl@aca7.showwebshe ailfragmentviewmodel@c61.downloadac screenthumbgenerator@4b96.initrecord cefusionfuncprovider@d4bb.handlechan	

-draftupgradehelper@28d6.updatedraf EMAILlayerimpl@3b51.updatelaye freeditpaneladapter@da98.bindstater	FILE
mttpromotionfragment@f369.initobserv draftupgradehelper@28d6.fetcheffec fprefabeditfragment@56ec.observecan ntalviewshowctrlimpl@4f40.init -makeupviewmodel@3113.loadaimake icelisterproxyimpl@3459.onevent 2alphavideoscene@9f94.runsubtitl facefusionrepo@41cc.removeface nowpostbasecellassem@351e.dispatchot eatorstickerfragment@eb94.calculatea templateapplynewflow@e669.handleappl ganviewmodel@586e.emiteditpr ctcreatepipelineimpl@e2ca.cropandsav imgautogeniconhelper@4893.preparecus -stickerresflowimpl@8b68.obtainstic greeditpaneladapter@da98.bindnormal stprefabpagefragment@a912.getadjustf eeffectenvlaunchtask@8b0e.run ngslistpanelfragment@20bf.initview gpicturecropfragment@16c2.initview recapclusterstrategy@674c.generateca customizeviewmodelv2@83ed.fetchaimes canvasactionlistener@ff32.ondown creendataresprovider@2dc8.getprefabb aimemoduleimpl@3a8c.createorfe ti2iloadcomponent@5889.onrecordfi eatorstickerfragment@a9ce.handleitem baseclusterstrategy@860d.initialize draftupdater@ff1a.updatedraf creatorviewmodel@f9f8.triggerlay amecorepresenterimpl@6f97.needrunfet dithitpanelviewmodel@a5bb.commitgree +aimetabviewmodel@6323.checkcusto ctonboardingfragment@7b49.initview topickpanelcomponent@d649.onaiautocu aimelauncherfragment@9de9.redirectst amecorepresenterimpl@6f97.upgradedra gcreatorcamerahelper@1908.takephoto seteditpagecomponent@a788.preloadi2i ourcedownloadnewimpl@4e8a.blockrules -behaviourimpl@96c1.notifycomm .featureoperator@e35d.adjustposi animationviewmodel@e3f4.applyprefa gifsfragment@3c5.initview animationviewmodel@e3f4.reeditanim 2baseclusterstrategy@860d.runpipelin gifsviewmodel@472a.loadtrendg ttemplatefragment@cd72.initbottom ae@73e.run ltiponboardingv3node@2b24.registerne gpicturecropfragment@16c2.geticonbit canvasactionlistener@ff32.onup longloadingpredictor@973f.querytotal metricsmonitor@15b5.updateconf	

componentviewmodelv2@695f.handlestyl EMAIL:refragment@cd72.initbottom verticalmusicview@a7b8.initrecomm	FILE
gcreatoreffecthelper@7d21.fetchdraft enstyleresultmanager@35df.downloadim tracingfilterchain@f11d.filterwith previewpagecomponent@e7db.onconfirml eatorstickerfragment@eb94.addorrepla aimakeuprepo@5ae4.addaimakeu musicpanelcomponent@b870.getmusicpa utopicklogfilewriter@b890.endsession ttlquefyviewmodelv2@3195.deleteloca verticalmusicview@a7b8.showsearch nanimseqshowprovider@6cdd.onseqshow nowsharebottomassem@8f07.onviewcrea amemodesettask@2ae.run ickeroperatefragment@36ad.onchange screenthumbgenerator@4b96.genthumb 0drafhandler@f1f0.openpublis 3producercoordinator@371.awaitchang scenemonitor@e338.flushinter facestretchfragment@cdc6.showbackdi amecorepresenterimpl@6f97.onviewcrea amerouter@3af6.addrouterp -textstickerresflow@3f39.obtainstic ganviewmodel@586e.savelocalf seteditpagecomponent@a788.posthandle 4objectitem@70a2.special imgautogeniconhelper@4893.preparecro makeupviewmodel@3113.preloadaddw 1ameautocutoutrepo@8606.chaincallb facestretchviewmodel@bd65.addorupdat 8ganviewmodel@586e.setfacefus eprefabeditfragment@56ec.onviewcrea kloadingcontentscene@f88d.go2editpag ataprovidercomponent@ba4b.loadmediaf enstyleresultmanager@35df.startgener filteredassetpool@8672.getorloads plusbuttoncontroller@4766.handlecllc amecorepresenter@ee9a.onviewcrea inglepicturefragment@9.showsaveto eampipelineexecution@1e2.waitforall eselectpagecomponent@f889.fetchstyle iadetectorrepository@c873.containfac npostgesturelistener@e05f.checkandha componentviewmodelv2@695f.handlesucc kamelaunchpanellogic@a41c.initseqlau aichoosemusicmanager@da6d.getaipanel attingresfetcherimpl@8fc8.preloadmat ideopreviewcomponent@f19c.choosemode imgautogeniconhelper@4893.prepareran ctcreatepipelineimpl@e2ca.cropiconan ganviewmodel@586e.applyfacef hganpagefragment@ccac.observedat ackingpanelviewmodel@98d3.changetrac 7messagecarouselview@c57a.clearstabl atorstickerviewmodel@4254.requeststi	

ttnewcreatorfragment@9077.observedit EMAILsterstrategy@91c8.scanwindow ttingspanelcomponent@2acc.showsetin slistpanelcontroller@51da.changeport 6officialiconutillskt@8545.loadoffici mestickercutoutfuckt@8cf2.addsticker wvertcalmusicview@a7b8.initsearch languagemodeltask@fc90.forwardsin fectfeaturecomponent@168f.expotteffe tttoolbarwidget@a9e.onconfigur 1drafthandler@f1f0.handleconf feaimenetworkapiimpl@b2d9.getaimelis prefabviewmodel@5840.cancelpref messagecarouselview@c57a.clearswitc ttttoolbarwidget@a9e.rendertool cefusionfuncprovider@d4bb.changetofu ttliquefyviewmodelv2@3195.loadfacest ameimagecutouteditor@22c0.onactionup pickerviewcontroller@a872.initobserv utopicklogfilewriter@b890.onlog ttdataeventreceiver@e70e.ondataeven chestrationscomponent@b9ce.executefix mecovereditviewmodel@c5c4.detectface prefabviewmodel@5840.applyprefa fectpreviewviewmodel@ace0.sendprevie editpreviewviewmodel@f9a1.buildstyle 0secondobjectfetcher@49c2.fetchcombi ttliquefyviewmodelv2@3195.togglepage tylepreviewviewmodel@9526.generatest goalbumpickermonitor@2ce0.loadercall ectimgcreatorveutills@fa0a.renderimag 6filteredassetpool@8672.getorloads ti2iloadcomponent@5889.getresulti 0collectmusicmanager@f40.updatecoll ganpagefragment@ccac.observedit elangdeviceexecution@ad3f.preloadres verticalmusicview@a7b8.showaidata nowpostutillskt@9e4e.roundandad -draftupgradehelper@28d6.refresheff aistylesfetcher@6d7b.getmodelef makeupresfetcher@9b27.getmakeupf ackingpanelviewmodel@98d3.exit ilamaterialsdkimpl@a5d8.downloadmo gslistpanelviewmodel@c975.fetchlist atorstickereditpanel@52bb.showgreens 2ameautocutoutrepo@8606.chaincallb edgeflowmanager@9681.sendtooutp filterchain@7194.filter promptinputcomponent@dac6.onreferenc tservicelisterimpl@d51a.savedeploy ailfragmentviewmodel@c61.onpostbutt mgiconeditcontroller@c62e.fetcheffec amakeuppagefragment@9516.showaimake prefabeditviewmodel@58ec.updatesubm retryimagelayout@8d71.enableagai modelfetcher@5c4a.fetchmodel tretchpersistentimpl@595d.getlocalfa	FILE
---	------

reparestagecomponent@58.expORTEffe EMAIL presenterimpl@6f97.runupgrade asrstreamtask@8422.process	FILE
inglepicturefragment@9.downloadpi eautocutoutcomponent@4327.loadimg asrstreamtask@8422.initchanne 7makeupviewmodel@3113.loadeffect kttlquifyfragmentv2@52bb.observewhe -amegreenscreentab@f75.preparegre amecorepresenter@ee9a.onactivity vadaptershowctrlimpl@8d09.bind amecorepresenterimpl@6f97.runapplyef modelselectcomponent@ef2b.notifysele makeupviewmodel@3113.selectcate bytebenchv2@5dc8.loadbytebe aimetabfragment@e8f3.onviewcrea carouselplayerview@e8e0.scheduletr fectcomponentmanager@3783.checkandad imagecutoutresloader@6fb5.init ommoncustomizeviewktt@aa97.customizee gcreatorcamerahelper@1908.onCreate atordraftserviceimpl@96ac.getProject tservicelisterimpl@d51a.fetchdepo iquefyv2pagefragment@4341.initobserv prefabpagefragment@feb3.observedat 0collectmusicmanager@f40.initcollec mecovereditviewmodel@c5c4.generateco retchdragchildlayout@bf04.setoverlap ffectentranceservice@55a.chechaifea tpreviewmodehandler@bae4.onmodechan aprefabpanelfragment@ff3c.initdata selector@9dcc.notifysele attingresfetcherimpl@8fc8.loadmattin mgcreatorcameratools@c0f6.registerli aimelauncherfragment@9de9.redirectmo creatorviewmodel@f9f8.resetstatu tretchpersistentimpl@595d.addlocalfa selectpanelcomponent@2b29.sceneactio ataprovidercomponent@ba4b.loadassets +amecutouttab@330b.gotomediad ataprovidercomponent@ba4b.loadaluma eshapepanelviewmodel@fe83.changeshap prefabeditviewmodel@58ec.initdata cprefabpagefragment@feb3.observedat edithitpanelfragment@5674.replaymusi inspectoretutis@602c.getplaceho iquefyv2pagefragment@4341.onautojump makeupviewmodel@3113.createfeat mecovereditviewmodel@c5c4.ontouchup tservicelisterimpl@d51a.isdraftlis makeupviewmodel@3113.clearselec kageandscriptfetcher@cb75.needforceu	

EMAIL	FILE
defaultadapter@8c6.async pitayahostdefault@b731.onapplogev 6coredefaultimpl@d2fa.registerap coredefaultimpl@d2fa.runnativet defaultadapter@8c6.asyncafter innerworkhandler@1f72.getherler 1@349b.com_byteda 0defaultadapter@8c6.processcol pitayahostdefault@b731.hostsetup ptysettingsutil@2f5f.updatesett clientaihttpclient@89c8.postinwork -nphstackreporter@c9f.reportalln defaulthttpclient@6245.post +coredefaultimpl@d2fa.releasenat 4coredefaultimpl@d2fa.removeappl tionlifecyclewatcher@4905.registerap 1@6830.call ttnehttpclientimpl@7567.get coredefaultimpl@d2fa.removemess defaultadapter@8c6.timer .coredefaultimpl@d2fa.registerme ttnehttpclientimpl@7567.post -pitayahostdefault@b731.oncustomap 6pitayapluginimpl@80c8.registerpi tionlifecyclewatcher@4905.onappstatu coredefaultimpl@d2fa.runtask	apktool_out/lib/armeabi-v7a/libdex_df_pitaya.so
g@9277.run d0@43b9.call gluetosdkincookie@1cce.setsyscook l0@3ee1.run p@9280.run o@929f.run j@929a.run u@9285.run k@927b.run b0@43f7.run owserpreinitexecutor@4d02.handlemess r@92a2.run j0@42ff.run y@92a9.call c0@3ff8.call m@929d.call n0@3ea3.call v0@418b.run q0@4226.call v@9286.run w0@416c.call m0@3ec2.call x0@414d.call g0@435c.run s@9283.run w@9287.call	

EMAIL	FILE
t0@3de9.run EMAIL chromium@d8d6.onmeasure r0@43d8.call	
b0@4017.run t1@3de8.handlemess e1@4399.call k0@42e0.run h0@3f5d.run a@9271.call q@92a1.run p0@3e65.run i0@431e.call y0@3d4e.run b@9292.allow k0@3f00.run s0@41e8.call m0@42a2.run f1@437a.run i0@3f3e.run g1@3f7b.run i@9299.getusagefo t@92a4.run b@9292.clear o@927f.call g1@435b.run g0@3f7c.run d@9274.call n@927e.call e0@3fba.run w0@3d8c.run f0@437b.call n0@4283.call l@929c.call z@928a.run z0@3d2f.run c1@3ff7.run h1@433c.call i@9279.run x@9288.run h0@433d.run f0@3f9b.run z0@410f.call z@92aa.run a1@4035.call k@929b.run i@9299.deletealld e@9275.run m@927d.call c@9273.call u0@41aa.run android-webview-dev@chromium.org j@927a.call v@92a6.run u0@3dca.call q@9281.call d1@3fd8.run o0@4264.call	apktool_out/lib/armeabi-v7a/libdex_df_ttwebview.so

q0@3e46.run EMAIL EMAIL s1@3e07.run	FILE
b@9272.run y@9289.run i1@3f3d.run t0@41c9.run p0@4245.call x@92a8.run b@9292.getallowed u@92a5.run s@92a3.run t@9284.run b1@4016.call e0@439a.call o0@3e84.call j0@3f1f.run b@9292.getorigins r0@3e27.call p@92a0.run a0@4036.run r0@4207.call l0@42c1.run s0@3e08.call l@927c.run w@92a7.call e1@3fb9.call v0@3dab.run a0@4416.run omiumfactoryprovider@38d1.initialize ebviewruntimeservice@6831.registerda b@9292.clearall x0@3d6d.call y0@412e.call h@9278.call d0@3fd9.run	
zhangke.finn@bytedance.com	apktool_out/lib/armeabi-v7a/libfast_engine.so
6bddlnasourcewrapper@10b1.setplayerl rtceventnotifier@2c05.onfirstvid zzc@c2ed.call dlnasourceimpl@1a94.resume chromecastsourceimpl@71b3.play 8bddlnasourcewrapper@10b1.setplayerl bytemediarecorder@e39e.init chromecastsourceimpl@71b3.add dramali nsdhelper@cdf3.startdisco stopbrowserrunnable@80f7.run rvicediskcachehelper@769c.checkservi zzbr@17e6.run castingmanager@f46d.startbrows castingplayerimpl@f321.addseeklis chromecastsourceimpl@71b3.updatedisc nsdhelper@cdf3.stopdiscov retryexecutor@3f26.onfail	

readerthread@d197.run EMAIL playmanager@89e6.ondramaid astingpanelcomponent@c8ae.onchange	FILE
castingmanager@f46d.emit rtceventnotifier@2c05.onvideoenc videorecordermanager@acb0.preparevid dlnasourceimpl@1a94.pause nsdclient@70a1.handlereso nsdserver@c708.stopsrver rtceventnotifier@2c05.onintofore rtceventnotifier@2c05.onconnect bytecastsourcimpl@9ea6.getsinkdev dlnasourceimpl@1a94.addvolume omecastsourcwrapper@3a80.setplayerl dlnasourceimpl@1a94.play smhandler@e866.handlemess .mirroringmanager@9956.delayendmi chromecastsourcimpl@71b3.playnextdr chromecastsourcimpl@71b3.resume castingmanager@f46d.initsdk zzbe@2161.run dlnasourceimpl@1a94.changereso astingpanelcomponent@c8ae.onparentvi startbrowserrunnable@cc6.run 3bytecastsourcimpl@9ea6.authbylice chromecastsourcimpl@71b3.addvolume tvcasting@552b.initialize dlnasourceimpl@1a94.setvolume chromecastsourcimpl@71b3.swapdevice e@84c7.oncast zzq@bce7.run nsdserver@c708.startserve chromecastsourcimpl@71b3.destroy nsdhelper@cdf3.handlefoun getvolumerunnable@90a7.run dlnasourceimpl@1a94.getdevicei servicelistpanelkt@6531.servicelis dlnasourceimpl@1a94.getmediain -castingmanager@f46d.initsdk chromecastsourcimpl@71b3.playpredra pauserunnable@b7d1.run chromecastsourcimpl@71b3.disconnect decodethread@c0e7.run rtceventnotifier@2c05.onpaused castingmanager@f46d.runonuihr chromecastsourcimpl@71b3.refreshrou zzba@2165.run audiopassiveplayer@bdac.callbackau ssdpsearchsocket@1033.run zzc@8fc7.call nsdhelper@cdf3.onnsdresol 9mirroringmonitor@94c.displaylis mirrorcontroller@933f.startmirro controlpoint@eae5.checkandad castadvertiser@44ac.run zzbp@17e4.run chromecastsourcimpl@71b3.connect	

rtceventnotifier@2c05.onrecvmeta EMAIL castsourcimpl@71b3.subvolume mirroringmonitor@94c.init	FILE
eractinfotvcastassem@7913.onviewcrea castssdpsearchsocket@ef9.run chromecastsourceimpl@71b3.setupnewap renderthread@49f0.run playercontroller@ab13.play writethread@1526.run astingservicemanager@3eb0.startbrows zzbq@45db.run advertiser@631e.run -bddlnasourcewrapper@10b1.getvolume chromecastsourceimpl@71b3.playdramai zsz@bce9.run renewssubscriber@a501.run chromecastsourceimpl@71b3.updatedemedi bytecastsource@596e.init zzr@8534.run zsz@8535.run controlpoint@eae5.search chromecastsourceimpl@71b3.setvolume bddlnasourcewrapper@10b1.send 5bddlnasourcewrapper@10b1.setplayerl zzg@bcdd.run dlnasourceimpl@1a94.send chromecastsourceimpl@71b3.seekto castssdpnotifysocket@ebb6.run astingpanelcomponent@c8ae.startplaya rtceventnotifier@2c05.onsinkstuc zzas@2172.run rtceventnotifier@2c05.onmonitore -networkutil@dfe1.checkandcr zzbo@17e3.run zzbn@17e2.run rvisediskcachehelper@769c.writecache dlnasourceimpl@1a94.getstatusi rtcengineimpl@2d44.playvideo setvolumerunnable@c0a9.run -voipvideorender@6561.notifyvide httpsocketrunnable@df35.run nsdclient@70a1.notifybrow zzbm@17e1.run zzt@8536.run castingutils@42a6.getawemeli laybackcontrollayout@5e8c.maybeshown videorecordermanager@acb0.pause 1bytecastsourceimpl@9ea6.initperfor searchresponsesocket@7471.run zzah@17bd.run videorecordermanager@acb0.stop httpserver@dd9f.run videorecordermanager@acb0.start zzu@8537.run rtceventnotifier@2c05.onstat rtceventnotifier@2c05.onintoback einfo listenerwrapper@18c9.delaysched	

chromecastsourcempl@71b3.init EMAIL rtceventnotifier@2c05.onlogmonit dlnasourcempl@1a94.subvolume	FILE
stingplugininstaller@8e02.oninstallp -rtceventnotifier@2c05.onconnects -bytecastsourcempl@9ea6.connect networkmanager@4f82.start zzbl@17e0.run zzd@c2ee.call transporthandler@d93c.handlemess zzav@1fbc.run concurrentsubject@e489.notifyobse threadcore@9e70.run devicemanager@ae59.clearbrows astingpanelcomponent@c8ae.onconnect rtceventnotifier@2c05.oncastsucc zzl@8d1b.run mainhandler@148c.handlemess devicemanager@ae59.deviceadde rtceventnotifier@2c05.onaudioset stoprunnable@46ac.run astingpanelcomponent@c8ae.startmirro rtceventnotifier@2c05.onkilled dlnasourcempl@1a94.stop dlnasourcempl@1a94.connect e@84c7.onstart videorecordermanager@acb0.resume seekdelayrunnable@9f68.run ssdpnotifysocket@f51d.run zzar@2173.run omecastsourcewrapper@3a80.setbrowser 9bddlnasourcewrapper@10b1.setmessage bytecastsourcempl@596e.startbrows rtceventnotifier@2c05.ondisconne zzq@75d2.run chromecastsourcempl@71b3.pause controlpoint@eae5.handledevi concurrentsubject@e489.notifyexce dlnasourcempl@1a94.changespee .bytecastsourcempl@9ea6.setauthbyl dlnasourcempl@1a94.checkandcr e@84c7.onrecvmeta playdrmaidlistener@ec4c.onfail +dlnasourcempl@1a94.getstatusa chromecastsourcempl@71b3.setrepeatm f@84c8.setvolume e@84c7.onconnect einfoListenerwrapper@18c9.onerror playrunnable@6bf9.run bytecastsourcempl@596e.deinit +bddlnasourcewrapper@10b1.send rtceventnotifier@2c05.onerror chromecastsourcempl@71b3.cleardrama chromecastsourcempl@71b3.playdramal 0bddlnasourcewrapper@10b1.getvolume	
devicemanager@ae59.deviceremo ecardlinkbuttonassem@9885.onviewcrea	

ttdsptablayout@2a64.addtabview EMAIL lyverfragment@28f8.setupviewp foryoulistviewmodel@1ref.loaddata	FILE
edsongslstviewmodel@7b6e.loaddata 6dspauthtokenfetcher@f3a9.requestdsp n@t.jt ryoriginloader@22de.load n@t.j2 tabpageassem@e8f7.subscribev aunchstrategymanager@e163.requestlin mainpagedatamutation@42dd.operate baselyricsview@d7c.reset2star edspplaylistmutation@12cc.operate -addtomymusicmanager@f107.addsongtom addedsongslstassem@a434.onwindowfo azonmusicauthhandler@45cb.refreshama cacesstokenmutation@c4ec.operate tagpanelviewmodel@f282.gettagpane dspfpsreporther@7a.dspsubplay rddetaildatamutation@8893.operate nginelisteneradapter@cbe8.ontimeupda librarylistviewmodel@7bbd.loadsongs tdspplaylistmutation@d215.operate mediaplayer@e4b0.onattach ngtomusicappmutation@1f63.operate tificationcontroller@925b.mhandler dspauthtokenfetcher@f3a9.refreshacc ongcardlistviewmodel@3014.onprepared fanspotlightassem@70ab.initbottom -mdverticalviewpager@8f2e.mendscroll cacesstokenmutation@b5ae.operate ddtomusicdspauthutil@c894.selectdsp 6dspauthtokenfetcher@f3a9.requestref ddtomusicdspauthutil@c894.updatedspp ouoriginloader@bec7.load sicsdpqueuelstassem@3dab.onviewcrea -mymusicsongassem@bd6a.bindexposu +multisongcardassem@64e2.onviewcrea adspfpsreporther@7a.forcedspu queueloadplugin@b85e.loadmore tyoauthmusicreceiver@1868.oncreate baseplayerviewmodel@37a1.loadmore otlightdetailsharevm@1691.onrefresh tailhitlistviewmodel@a699.onrefresh sptackexpiredplugin@2375.showsubscr ddtomusicdspauthutil@c894.addsongtom ixoriginloader@232e.load icdspplayerviewmodel@83f0.checkswipe journeysourceloader@5df4.load journeysourceloader@5df4.loadmore addtodspviewmodel@9231.reportadds dspitemreusedassem@b7ba.onviewcrea lightsharedviewmodel@fb69.saveselect getdspplaylistsquery@f8ff.operate cdetaillistviewmodel@ea91.loaddata librarylistviewmodel@7bbd.loaddata platformssettingpage@9a54.loaddsppla	

ixoriginsourceloader@232e.loadmore EMAIL usicdspauthutil@c894.getdspplat ddtomusicdspauthutil@c894.songcheckf	FILE
2lyricinfo@3645.getlyricin addedsongslistassem@a434.subscribev azonmusicauthhandler@45cb.getamazonm otlightdetailsharevm@1691.onloadmore sptackexpiredplugin@2375.onplayback umtomusicappmutation@f5d8.operate cdspjourneyviewmodel@e737.fetchsongs musicdspstabfragment@f159.oncreatevi songcheckfordspquery@d39e.operate ddtomusicdspauthutil@c894.createdsp lottieguide@f3e7.show preloadplugin@b661.preload sidspsaudiocardassem@3fa1.onviewcrea sidspsheetviewmodel@3e3c.requestpla cketplatformsyncpage@3038.initdata dspaudioseekbarassem@9696.seekbarsho absplayablequeue@1604.loadmore pipedplayablemanager@d256.resetactio usicdsplikeviewmodel@8702.savesongto baselyricsview@d7c.mhandler installdetectmanager@c140.getdspinst moveanimator@6935.run ddtomusicdspauthutil@c894.getdspplay edspplatformmutation@394.operate sicmainpageviewmodel@271e.loaddata lightbottomcomponent@75a.createbott gstomusicappmutation@76c2.operate justtagscachemanager@77d9.writelocal	
asselfiescanfragment@f36d.onmanualca checkoutprocess@fad.presentpim checkouthomekt@de1b.checkoutho 4camerapreview@5543.initcamera 0detailviewmodel@e36a.onclickpre ailablemethodspagekt@df6.availablem billhomeviewmodel@7c13.load paymentconfig@4a3b.initstarli reetfillercontroller@1e6f.onvaluecha veritasidvcameraview@3351.downgradem baseviewmodel@a8bd.loadcashie addressviewmodel@1396.synchroniz mentprepareviewmodel@97b5.getrepayme pimanagementkt@49.handlenavi billhomeviewmodel@7c13.loadcustom asselfiescanfragment@f36d.showcamera baseviewmodel@a8bd.initnoncet payment@a405.presentpim echeckoutviewmodel@de26.startpolli icontextcard@cb18.onbindview tainerassemviewmodel@65ad.createsubc piviewmodel@e244.deletestor piviewmodel@e244.storepayme puxtoastkt@4a5b.puxtoast andingcontainerassem@e692.presentbut	

asselfiescanfragment@f36d.oncapturer EMAIL scnfragment@17f6.onviewcrea ritasidvscanfragment@17f6.doupdate	FILE
dcamerapreview@5543.createcame payresultpagekt@ebf8.payresultp ogressassemviewmodel@10f5.getinstitu +repaymentviewmodel@2076.presentche reementsignviewmodel@4cbe.signagreem animationcontroller@2ab.dismiss 0landingassemvm@e5ad.createcred +baseviewmodel@a8bd.showgenera cardnumbercontroller@eba5.debounce checkoutviewmodel@de26.closecheck 2repaymentviewmodel@daf6.onpreparer asselfiescanfragment@f36d.doliveness example@email.com tainerassemviewmodel@65ad.signagreem detailviewmodel@e36a.onloadmore kycnfcscanningassem@2bbe.showreadyt itasselfiecameraview@347f.downgradem ritasidvscanfragment@17f6.onresume rationdatecontroller@a578.validatewi puxdialogkt@8092.dialogcont piviewmodel@e244.checkbinds tainerassemviewmodel@65ad.requestreg checkoutbarkt@7ee0.checkoutba noncecontainer@4140.getnonce 9checkoutprocess@fad.presentpim pimanagementkt@49.pimanageme andingcontainerassem@e692.initcontai addressviewmodel@1396.preparedat baseviewmodel@a8bd.isnetworka formskt@ec82.forms +checkoutcontainerkt@7c59.handlenavi piviewmodel@e244.getpibasic ritasidvscanfragment@17f6.downgrader +checkoutactivity@41a1.showcompos stagreementviewmodel@417d.getagreeme tainerassemviewmodel@65ad.recordcl ritasidvwelcomeassem@6b26.sessiontim bnplcommonpopup@7d4b.sendreques postartnfcscanmethod@d0e8.handle nfcscanningviewmodel@a548.startnfcsc repaymentviewmodel@2076.getnonce ritasidvscanfragment@17f6.onmanualca checkoutviewmodel@de26.pay -phonenumbert@397.oncountryc ndwalletlandingassem@7d5c.handlecl ycnfcscanningassemv2@7418.showreadyt 2bindcontainerkt@813f.showbindpa piviewmodel@e244.saveasprim 4detailviewmodel@e36a.onclickpre -checkoutactivity@41a1.showcompos asselfiescanfragment@f36d.sessiontim cscanningviewmodelv2@eb11.handlescan checkouthomekt@de1b.imespaceho -camerapreview@5543.initcamera	

piviewmodel@e244.redirectha EMAIL mentmethodnavkt@cf39.navigation tainerassemviewmodel@65ad.created	FILE
ogressassemviewmodel@10f5.getroutein .bnplentryviewmodel@c16.getstepcod apiservice@bd9b.getstarlin tuxdialogkt@608c.tuxdialogc reetfillercontroller@1e6f.debounce ogressassemviewmodel@10f5.createsubc addressviewmodel@1396.ondone reetfillercontroller@1e6f.onfocuscha 3clientaicameraview@ec4c.processfra buttoncard@7e9c.handledata -checkoutviewmodel@de26.storepayme creaselimitviewmodel@9cba.submit bottomsheetkt@3e26.bottomshee ignagreementfragment@3451.onviewcrea animationcontroller@2ab.show selectpikt@1283.selectpi ritasidvscanfragment@17f6.sessiontim +checkoutviewmodel@de26.storepayme selectassemblepikt@73eb.selectasse repaymentviewmodel@daf6.loopforres asselfiescanfragment@f36d.doimageupl bizdataholder@86cc.getconfigu repaymentviewmodel@daf6.load repaymentviewmodel@2076.initpaymen ritasidvscanfragment@17f6.showcamera 1addressviewmodel@1396.synchroniz checkoutprocess@fad.getnonce fcscanningfragmentv2@4475.onviewcrea 4checkoutviewmodel@de26.startpolli checkoutviewmodel@de26.initmethod nfcscanningviewmodel@a548.handlescan baseviewmodel@a8bd.requeststa checkoutviewmodel@de26.getpayment piviewmodel@e244.launchbind ogressassemviewmodel@10f5.createmain pimanagementkt@49.cardlist cscanningviewmodelv2@eb11.startnfcsc piviewmodel@e244.getpimanag retrykt@6b9c.retry landingassemvm@e5ad.signagreem asselfiescanfragment@f36d.downgrader piviewmodel@e244.havestored checkoutviewmodel@de26.storepayme +formskt@ec82.forms postalcodecontroller@cddb.synchroniz ritasidvscanfragment@17f6.oncapturer cnfscanningactivity@ca29.setupbotto configuration@2711.getidempot .camerapreview@5543.initcamera -checkoutcontainerkt@7c59.handlenavi ycnfcscanningassemv2@7418.onviewcrea outbackinterceptortkt@9a2b.showclosed 1billhomeviewmodel@7c13.onpreparer ogressassemviewmodel@10f5.decideuser	lib/arm64-v8a/libdex_df_pipo_bnpl.so

reetfillercontroller@1e6f.onclick EMAIL -addressviewmodel@1396.initdatafo	FILE
statementsviewmodel@5867.onrefresh phonenumberkt@d397.oncountryc ndpaymentmethodnavkt@cf39.bindpaymen .bindcontainerkt@813f.showbottom .repaymentviewmodel@daf6.onpreparer animationcontroller@2ab.startanima fieldcontroller@7de7.validatewi 1clientaicameraview@ec4c.handlecapt cardnumbercontroller@eba5.onvaluecha pipoclientaimanager@79c1.prefetch addressviewmodel@1396.fetchdata repaymentviewmodel@2076.presentche clientaicameraview@ec4c.handlecapt fcscanningfragmentv2@4475.onnewisode livenesscheckhelper@23d.livenessch fcscanningfragmentv2@4475.onCreatevi ritasidvscanfragment@17f6.doimageupl repaymentassem@956f.scrolltobo tuxtoastkt@aeed.tuxtoast -billhomeviewmodel@7c13.onpreparer asselfiescanfragment@f36d.doupdatese addressviewmodel@1396.datainitia asselfiescanfragment@f36d.permission asselfiescanfragment@f36d.releaseres creaselimitviewmodel@9cba.presubmit piviewmodel@e244.closebinds ritasidvscanfragment@17f6.releaseres asselfiescanfragment@f36d.onviewcrea bnplentryviewmodel@c16.getstepcod landingassemvm@e5ad.requestreg rogressanimationview@4d84.initstepvi piviewmodel@e244.dealbindre ritasidvscanfragment@17f6.permission baseviewmodel@a8bd.getnoncewi tainerassemviewmodel@65ad.decideuser +baseviewmodel@a8bd.shownetwor piviewmodel@e244.cancelaspr piviewmodel@e244.initmethod cardnumberkt@6a2f.cardnumber bnplcommonpopup@7d4b.onapierror ogressassemviewmodel@10f5.signagreem clientaicameraview@ec4c.ongetnewim	
nmolifecycleobserver@fb35.onstatecha paypalsdkprocess@6938.clear +httpclient@bac3.notifysucc pallifecycleobserver@fa45.onstatecha httpclient@bac3.notifyerro httpclient@bac3.schedule	lib/arm64-v8a/libdex_df_pipo_external_payments.so
appro@openssl.org	lib/arm64-v8a/libtt_c2pa_sdk_d.so
appro@openssl.org	lib/arm64-v8a/libtt_c2pa_sdk.so

EMAIL	FILE
ffmpeg-devel@ffmpeg.org	lib/arm64-v8a/libttvesdk_plugin.so
.ilililili@7cb8.onsurfacet iilililili@5021.run ilililili@e761.run linkccdcocrviewmodel@5bad.restarttim lilililil@7742.run ardoverlaycontroller@1499.liiililili innerreticleview@c576.ilililili iilililil@2f90.liiililil llililili@f61d.run ilililil@c351.run tooltipmanager@42cd.showtoolti lilililil@9dcb.run ardoverlaycontroller@1499.ilililili llililil@3a5c.ilililil liiililil@c4a4.run lilililili@aef1.run llililil@3a5c.liililil innerreticleview@c576.ilililil llililili@66.liililil liililili@66.ilililil iilililil@41e6.llililil llililil@3b67.run ilililili@ad44.run iilililil@2f90.llililil blinkccdcocractivity@a0d7.initview .ililililil@2341.onsurfacet progressview@d1bc.ilililil llililil@3a5c.ilililil llililil@3a5c.iilililil llilililil@8193.onshakings ilililili@abc1.run llilililil@54ad.run ilililili@7cb8.onsurfacet linkccdcocrviewmodel@5bad.frontsides llilililil@3a5c.llililili llililil@38b7.run llilililil@3a5c.dispose snackbarmanager@7b73.liililil iilililili@48d.run nllilililil@7584.com_microb tooltipmanager@42cd.hidetoolti ilililili@419e.ilililil rdreticleoverlayview@d3ea.createlayo llilililil@5a54.onpicturet lilililil@96bf.run nllilililil@396d.com_microb ililililil@a68a.surfacecha iilililili@c56c.run snackbarmanager@7b73.ilililili ililililil@a728.onimageava llilililil@3a5c.liiililil	lib/arm64-v8a/libdex_df_ccdc_impl_ocr.so

rdreticleoverlayview@d3ea.changestat EMAIL 3@1fe5.run	FILE
iiiiilil@2f90.lliilili ardoverylaycontroller@1499.lliililil 0debugviewhandler@3d30.initialize lliililil@7584.run lliiilil@904d.run rdreticleoverlayview@d3ea.lliililil lliiilil@caaf.run lliiilil@9cd3.run iiiiilil@d9d.run iiiiilil@4550.run progressview@d1bc.iiiililii 3@a98.run iiiiilil@4526.run iiiiilil@2341.onsurfacet iiiiilil@189d.run lliiilil@396d.run lliiilil@396d.iiiililii lliiilil@cc66.run iiiiilil@2f90.dispose lliiilil@9821.run	
styleselectcomponent@eed.getselects ttliuefyviewmodelv2@3195.applyclear secondobjectfragment@25bf.initdata hsladjustfragment@cc19.cancelvalu opickpanelguidescene@80d3.initviews viourpreviewfragment@b187.initaction sthitsviewcontroller@3138.bindobserv ailfragmentviewmodel@c61.downloadpi bverticalmusicview@a7b8.buildcolle jarvis@b146.init seteditpagecomponent@a788.oncreate keffecteditorcontext@5cb5.ttdoaftere ostdeleteserviceimpl@ec46.delete enscreenfuncprovider@4094.switchreal ganviewmodel@586e.removeface bbottombarcontroller@48f3.setupleftb ntiputilskt@10d0.dowhenloca 0eventtrackingextkt@d694.sendeventt tiktokgifrepository@f767.trendgifs facestretchfragment@cdc6.initview eprogresscoordinator@b04d.syncreleas creatorlayerfragment@d93c.calculatea ttpromotionviewmodel@b3db.selectprom 0prefabeditviewmodel@58ec.compresssh .amestickertab@f726.preloadmat cefusionfuncprovider@d4bb.addfusion +nowlikeviewmodel@da60.handlenowp 6filteredassetpool@8672.getassetsw seteditpagecomponent@a788.launchscen creendataresprovider@2dc8.preloadgre archloadingcomponent@a395.observerwor amecorepresenterimpl@6f97.launchawai amedbinitwavetask@901c.run	

ffectimgcropfragment@6e89.startloadi EMAIL utocutoutrepo@8606.chaincallb faceinsetresflowimpl@5b2e.obtainaddf	FILE
makeupviewmodel@3113.initfeatur amakeuppagefragment@9516.observedat makeupviewmodel@3113.updateload eampipelineexecution@1e2.processnod mstickerpagefragment@e4f5.initobserv canvasactionlistener@ff32.ondoublecl elactionreporthelper@7a1f.onoperatio atorofficialrepoimpl@eb36.reqofficia ckcliprailpanelscene@f69d.loadingrot ecutoutpanelfragment@2aad.gotosticke acestretchrepository@575f.apply styleselectcomponent@eeed.downloadst sealbumpickermirror@9b40.changeload alicondirlistadapter@f848.onbindview ecutoutpanelfragment@2aad.gotomediac canvasactionlistener@ff32.singletap modelselectcomponent@ef2b.downloadmo eaimattingresfetcher@5768.loadmattin enstyleresultmanager@35df.showloadin aimetabviewmodel@6323.loginload inpreviewtitlewidget@434a.updaterend fbaseiconlistadapter@8bdc.onbindview iganpanelfragment@9fd9.bindseekba stickerguidefragment@1ac2.onlytipsca localconfigsfragment@720d.submitlist al@737.run imestylepreviewscene@1044.handlesucc editpreviewviewmodel@f9a1.fetchuserp dganpanelfragment@9fd9.initview stickerresflowimpl@8b68.preloadadd amemusictab@d8c.showmusicn tgreenscreenhelperv1@b92c.gengreensc 3ganviewmodel@586e.onfacefusi cutoutcanvasfragment@a1bc.initobserv creendataresprovider@2dc8.downloadgr ti2iloadcomponent@5889.msgcenterl customizeviewmodelv2@83ed.performgen carouselplayerview@e8e0.applycente prefabviewmodel@5840.fetchlokip taskrepositoryimpl@c0e3.getaigtas ckerguideserviceimpl@2357.startstick gifsfragment@3c5.addgifstic ckpanelguidefragment@b009.preloadalp eampipelineexecution@1e2.emit drafthandler@f1f0.showsavadr inpreviewmusicwidget@e63e.onconfigur seteditpagecomponent@a788.prehandlel ganpanelfragment@9fd9.initdata epreupgradedrafttask@a3b4.preupgrade -amecutouttab@330b.gotomediac -amenewflowtexttab@32b6.handleedit ltiponboardingv3node@2b24.launchpane slistpanelcontroller@51da.handleitem texteditpagescreenkt@f833.textinputi	

prefabviewmodel@5840.preloadaddw EMAIL model@472a.loadmoregi aiselfcarouselkt@ac9a.autoscroll	FILE
verseclusterstrategy@91c8.dogenerate perfintervalmonitor@6311.run wcaptioneditfragment@3c1b.initeditvi 0facefusionrepo@41cc.loadfacefu amecovereditfragment@1c20.initview cutoutbottomfragment@2b85.observevie ttlquefyviewmodelv2@3195.initfollow objectcontainer@a25.build hprefabeditfragment@56ec.observecan componentviewmodelv2@695f.performsuc bytebenchv2@5dc8.reportresu stprefabpagefragment@a912.getlayerdi drafhandler@f1f0.handleconf 2aimetrystylemanager@6ec4.shouldshow itionstatustextassem@b2f.startdotup 1ganviewmodel@586e.onmediasel edgeflowmanager@9681.initialize aimetabviewmodel@6323.loadmore tickersearchfragment@bb76.addorrepla ewpager2heighthelper@f55d.pagechange tiktokgifrepository@f767.searchgifs ltiponboardingv3node@2b24.registerpa imagecutoutviewmodel@497d.clearstep ameupgradedrafttask@e63f.run gtoolseditcontroller@c679.compressbi eatorstickerfragment@a9ce.observesea faceinsetresflowimpl@5b2e.obtainface imagecutoutviewmodel@497d.intercepts assetreverseproducer@54de.getcluster dataeventreceiverpro@8b02.ondataeven +ganviewmodel@586e.flushfacef otionrouterprocessor@713a.process scenemonitor@e338.stopintern ffectentranceservice@55a.isaifeatur facefusionrepo@41cc.changeefusi creatorlayerfragment@d676.initlisten ttlquifyfragmentv2@52bb.onattach packagefetchwavetask@bf55.run ramepreviewcomponent@482.startgener ganviewmodel@586e.createfeat 6makeupviewmodel@3113.selectfirs acefusionresprovider@cfcf.preload gfeaturefragment@9411.initaction perfintervalmonitor@6311.flush effectdraftcomponent@138b.savei2vdra editpreviewviewmodel@f9a1.updateaise autopicksession@14df.awaitnexts 6prefabpagefragment@feb3.observedat inpreviewtitlewidget@434a.setviewloc feaimenetworkapiimpl@b2d9.getaimerec 5autopicksession@14df.launchstra enscreenfuncprovider@4094.updategree ltiponboardingv3node@2b24.registerro ganviewmodel@586e.changeefusi	

EMAIL	FILE
canvasactionlistener@ff32.oncscle EMAIL: orserviceimpl@c952.fetcheffec rtliquefyviewmodelv2@3195.initautorch	
gslstpanelviewmodel@c975.changeport aimeservicesimpl@2ffe.fetchaisel eatorstickerfragment@a9ce.initview bytebenchv2@5dc8.stop phasestackview@ebdd.animatepha eselectpagecomponent@f889.sceneactio qlambda@f73a.run aimetabviewmodel@6323.loadinitia drafthandler@f1f0.getdraftsi orstickerpageadapter@f578.bindfuncit faceinsetresflowimpl@5b2e.applyfacei verecordhelper@7eb6.effecthand musictrimviewmodel@3254.getmusicwa imakeuppanelfragment@e4b6.initdata animationviewmodel@e3f4.initfeatur amecovereditfragment@1c20.initchoose languageodeltask@fc90.downloadre editloadingcomponent@f330.onCreate iquefyv2pagefragment@4341.initshowde iprailpanelcomponent@65e4.checktaskr aimeservicesimpl@2ffe.createaime .makeupviewmodel@3113.shownotcon ti2iloadcomponent@5889.starti2ilo orstickerpageadapter@f578.onbindview ualframepreviewscene@5c67.changefram ewpager2heighthelper@f55d.requesthei templateapplyoldflow@8f3d.upgradedra modelpreloadwavetask@8ac2.run ionlatesthitsadapter@788a.onbindview tretchpersistentimpl@595d.deletefile gifsfragment@3c5.observedat nowpostvideoassem@41aa.onhostdest emegenerationsservice@ce2d.generateth aistylesfetcher@6d7b.fetchstyle atorstickerviewmodel@4254.requestrec rtoofficialrepository@5713.request 3prefabviewmodel@5840.loadeffect prefabpanelfragment@ff3c.initview facestretchviewmodel@bd65.setisfaces aimeservicesimpl@2ffe.hasaiself makeupviewmodel@3113.emitsucces +makeupresfetcher@9b27.fetchmakeu aiselfcarouselkt@ac9a.carousel nowbaselistassem@e120.setlistpad officialiconutillskt@8545.loadoffici ourcedownloadnewimpl@4e8a.startcoldb mecovereditviewmodel@c5c4.init facestretchviewmodel@bd65.applyeffec dotmatrixviewkt@eccf.dotmatrixv ameimagecutouteditor@22c0.changeprev faceinsetresflowimpl@5b2e.changetrac imgautogeniconhelper@4893.genbmpbyof canvasactionlistener@ff32.ontoucheve makeupviewmodel@3113.generateai	

iprefabpanelfragment@ff3c.initview EMAIL: customizescene@55e6.successgen objecteffecthandler@657f.inneraddst	FILE
sictrimpanelfragment@bc06.initobserv deuploaduicomponent@4d62.oncreate nativescenemonitor@1ad6.stopintern 1ganviewmodel@586e.clearselec atorstickereditpanel@52bb.handlerreed facestretchviewmodel@bd65.changeface omptenhancecomponent@5992.translatep iprailpanelcomponent@65e4.onaiautocu feaimenetworkapiimpl@b2d9.getaigcquo componentviewmodelv2@695f.handleclie aimelistrepo@d69d.getaimelis kprefabpagefragment@feb3.observedat ctcreatepipelineimpl@e2ca.onexportwh reupdateeventapiimpl@a3d.onfireeven 9aistyleresfetcher@6d7b.getstylera customdownloader@85b1.download +verticalmusicview@a7b8.getrecentm ttnewcreatorfragment@9077.delayloadi timewindowfilter@11c7.filter kloadingcontentscene@f88d.updateprog fectfeaturecomponent@168f.downloadre 6verticalmusicview@a7b8.getsearchm ortitlebarcontroller@3a4.registerli filteredassetpool@8672.getassets nowlikeviewmodel@da60.onclicklik ttnewcreatorfragment@9077.handleinfo eaimetabfragment@e8f3.checklogin videouploadcomponent@95e9.startuploa 8textstickerresflow@3f39.preloaddef ameimagecutouteditor@22c0.addaimatti archloadingcomponent@a395.showresult istadapterviewholder@1d11.bind viourcontentfragment@6376.compatoncl videouploadcomponent@95e9.pickvideo eocutoutplayfragment@c596.initview bytebenchv2@5dc8.loadtaskto ctcreatepipelineimpl@e2ca.logsavedra uefyprefabrepository@5cd4.getorcreat ctimgcreatorfragment@fc30.initlisten imestylepreviewscene@1044.checklogin .aimetabfragment@e8f3.setviewmod owdownloadbottomview@abfa.handler thememarqueeetextview@dc03.applymarqu editloadingcomponent@f330.regenerate otoseditpagefragment@8917.restoresel -aimetabfragment@e8f3.scrolltoto ttliqueryviewmodelv2@3195.startfaces 2collectmusicmanager@f40.loadcollec atorofficialrepoimpl@eb36.preloadran feaimenetworkapiimpl@b2d9.postaistyl makeupviewmodel@3113.launaigc dialogcontentbuilder@336e.createdial lbumpickeralgolader@82cb.getdetectm pickloadingcomponent@6ba2.submitnewt	

istadapterviewholder@50d.bind EMAIL clusterproducer@ba79.producecan hannerviewcontroller@20d0.initobserv	FILE
1animationviewmodel@e3f4.onbehaviou cutoutcanvasfragment@a1bc.showtipifn longloadingpredictor@973f.predict runtimeevent@d9a0.record autopicksession@14df.start previewpagecomponent@e7db.onconfirmc aimetabviewmodel@6323.aihubclick facestretchviewmodel@bd65.setupforex companion@98eb.mergemodel nowlikeviewmodel@da60.handlenowp ganviewmodel@586e.onmediasel selector@9dcc.select bytebenchv2@5dc8.checktestr reparestagecomponent@58.repreparep objectpreparewavetask@36f5.run slistpanelcontroller@51da.back chestrationcomponent@b9ce.repick fyoriginalrepository@defb.followface .dynamichookhelper@e04c.switchtoma rcollectionlistassem@fdbd.onbind slistpanelcontroller@51da.oninit prefabviewmodel@5840.emiteditpr phaseitemholder@dd98.crossfadet amelaunchtask@d1f1.runasync jankframecollector@560d.stop ttnewcreatorfragment@9077.onviewcrea imagecutoutviewmodel@497d.triggeraut eupexchangeviewmodel@7f33.updatemake customdownloader@5e04.download topickpanelcomponent@d649.savedrafta eaimattingresfetcher@5768.preloadmat ttiponboardingv3node@13d5.tryshowani iprailpanelcomponent@65e4.sam makeupviewmodel@3113.clearcateg ttlquefyviewmodelv2@3195.selectloca inspectoretutils@602c.reportgree ttlquefyviewmodelv2@3195.cancel otiontemplateadapter@7abb.onbindview 9amedebugfragment@39de.doinit languagemodeltask@fc90.forward -prefabeditviewmodel@58ec.saveselect picklotteddownloader@294b.downloadto otoseditpagefragment@8917.updatealbu fectfeaturecomponent@168f.preloadloa facestretchviewmodel@bd65.refreshkey componentviewmodelv2@695f.handlegene ctcreatepipelineimpl@e2ca.resolvecro baseclusterstrategy@860d.cvscan editpreviewviewmodel@f9a1.observerre prefabviewmodel@5840.clearselec gifsviiewmodel@472a.downloadgi fectfeaturecomponent@168f.applyprefa enscreenfuncprovider@4094.changetrac bfourpicturefragment@febe.mobdeletep	

stickerguidefragment@1ac2.registerob EMAILlecthandler@50af.autochange lbummultiselectlogi@8114.bindholder	FILE
+prefabviewmodel@5840.loadeffect rtoofficialrepository@5713.createoffi imgautogeniconhelper@4893.applyeffec usionganpagefragment@5dee.initview .alphavideoscene@9f94.animlisten photostorehelper@25da.getphotodi +autopickpanelscene@9db7.adjustcove eatorstickerfragment@a9ce.parseselec amemodelpreloadtask@f983.modelprelo ckerfacefusionloader@46fb.load ltiponboardingv3node@2b24.tryshowani voicerearchviewmodel@8ed6.startdotup tylepreviewviewmodel@9526.getpagesta qpreviewmodeladapter@a893.onbindview textinittaskwavetask@c15a.run 0ganviewmodel@586e.applyfacef enstyleresultmanager@35df.openresult thememarqueetextview@dc03.oncontextchan inpreviewtitlewidget@434a.onconfigur screenthumbgenerator@4b96.tryshotscr atorstickereditpanel@52bb.playmusicw romotionbottomdrawer@6faa.initview ecutoutpanelfragment@2aad.onactivity ttpreviewmodehandler@bae4.initprevie rsecondobjectadapter@a42d.onbindview normalhandlerimpl@927f.update fectpreviewviewmodel@ace0.regenerate Ottlquifyfragmentv2@52bb.mobcategor stickerselecthandler@50af.selectobje ormigrateserviceimpl@95ca.awaitchang selectpanelcomponent@4222.fetchmodel 7nowsharebottomassem@8f07.sharebutto elfawemecachemanager@5c53.deletecach bprefabpanelfragment@ff3c.bindseekba ramepreviewcomponent@482.oncreate hsladjustfragment@cc19.initview localconfigsfragment@720d.observdat uefyprefabrepository@5cd4.eecreatefe ickeroperatefragment@36ad.initobserv autopickpanelscene@9db7.scheduleco fyoriginalrepository@defb.load imationpanelfragment@9f44.initview amevelaunchtask@f810.oncreate ckpanelguidefragment@b009.updatescro actionviewmodel@3d37.filternots ameralaunchcomponent@a0cb.awaitpages viewlazyinittask@9248.run 1baseclusterstrategy@860d.dogenerate gridadapter@5c48.onbindview 4consumercoordinator@9d43.consumeava ickerrouterprocessor@1f13.process xtstickerinputlayout@542c.showinputl kttlquifyfragmentv2@52bb.initobserv amecorepresenterimpl@6f97.runvelaunc	

gpicturecropfragment@16c2.getstyleta EMAIL Emailfragment@9fd9.initview cialiconlistfragment@1f25.startobser	FILE
mainpackagefetchtask@1fcd.run picklotteddownloader@294b.downloadlo eeklyclusterstrategy@9057.dogenerate archloadingcomponent@a395.submitaigc ourcedownloadnewimpl@4e8a.startdownl ickrootslotcomponent@4cb3.showautopi stprefabpagefragment@a912.applyadjus modelmanager@75cd.downloadmo ameprojectcreatetask@5356.run customizeviewmodel@8957.performapp tv2vreeditgroupscene@ac19.initobserv canvasactionlistener@ff32.oncornerdr onboardingv2cardview@b442.initpopove 2customizeviewmodel@8957.reportcl chestrationscomponent@b9ce.startautop meonboardingwavetask@78c8.run ganviewmodel@586e.fetchganli amevesdkinittask@222.run .draftupgradehelper@28d6.updatedraf mainpackagefetchtask@1fcd.needforceu normalhandlerimpl@927f.onscale editpreviewviewmodel@f9a1.discardcur nowcachedelegate@6dbd.ondeleteno ompatibilitytuxsheet@8c3.tasksimage 1facestretchfragment@cdc6.onconfigur lbumpickeruidelegate@b7b1.init ailfragmentviewmodel@c61.oncustomiz gcreatorcamerahelper@1908.opencamera componentpreparatask@b449.run facestretchfragment@cdc6.initobserv +makeupviewmodel@3113.loadeffect 2stickerresflowimpl@8b68.obtainaddf mfacestretchfragment@cdc6.initobserv ontouchdraghandler@960f.ontouch 5prefabeditviewmodel@58ec.notifycont slistpanelcontroller@51da.handlechan omptenhancecomponent@5992.innerreque meprojectpreparatask@6513.processdra ttpromotionfragment@f369.initview animationviewmodel@e3f4.loadeffect calendarmonthview@efb3.enableagai agifsfragment@3c5.initview autopickpanelscene@9db7.tryexitloa odelpictureviewmodel@fa9c.loadmodell ttnewcreatorfragment@9077.mpreviewti ticersearchfragment@bb76.replacegip makeupviewmodel@3113.selectedai fyoriginalrepository@defb.waiteffect tuspublishedrepoimpl@cbec.save2disk lbottombarcontroller@1f1b.setupright voicerearchhelper@9a5c.performvoi 0draftupdater@ff1a.updatedraf ultnavigationhandler@e1fd.navigateto ttnewcreatorfragment@9077.onconfigur	

onboardingv2fragment@d2c5.setdata EMAILlionviewmodel@e3f4.clearselec imenewcustomizescene@55e6.associated	FILE
ttliuefyviewmodelv2@3195.selectpref facestretchviewmodel@bd65.changeprev amestickertab@f726.handlelic bfourpicturefragment@febe.gosinglevi videocutoutviewmodel@ffde.removeback videocutoutviewmodel@ffde.updateprog autopickpanelscene@9db7.onshow previewpagecomponent@e7db.savedraft enscreenfuncprovider@4094.portraitcu +objecteffecthandler@657f.scopedadds econfigpagecomponent@842b.fetchstyle camebasetooltab@fb4c.attachcont qprefabeditfragment@56ec.observecon bytebenchv2@5dc8.start metricschecker@577.run aichoosemusicmanager@da6d.downloadmu ti2iloadcomponent@5889.commitgree ffetaudioscrollview@d2a5.startscrol editpreviewviewmodel@f9a1.loadmodelp aycomponentviewmodel@715b.performpol ttnewcreatorfragment@9077.observedou bgifsfragment@3c5.observedat inpreviewtitlewidget@434a.calculatea fectdownloadhelper@3320.localdownl 9collectmusicmanager@f40.loadmoreco ganviewmodel@586e.oncommitup 2aistyleresfetcher@6d7b.getstylera eatoralbumfragmentv2@90fe.initlisten refabsublistloadtask@dbe7.run .ganviewmodel@586e.createganv amecorepresenter@ee9a.prepareres bfourpicturefragment@febe.onviewcrea isdayclusterstrategy@81e2.scanyearcl imakeuppagefragment@9516.observedat secondobjnormalrepo@d5b7.fetchpanel amevideocutoutplayer@403b.setmatting -widgetlocationimpl@5c3c.recordpane statistichelper@8108.onevent nowmediacachemanager@3ec6.deletcach 1nowareamonitorassem@4391.sam gpicturecropfragment@16c2.initcropvi 6baseclusterstrategy@860d.loadfilter verecordhelper@7eb6.initvereco texteditactivity@468a.update .ganviewmodel@586e.loadfacefu rtofficialrepository@5713.onofficial ttliuefyviewmodelv2@3195.done drafhandler@f1f0.openpublis ffectimgcropfragment@6e89.initlisten lreeditpaneladapter@da98.bindselect otiondataresprovider@6cc3.fetchbanne gcreatorcamerahelper@1908.init languagemodeltask@fc90.preloadint uctcomponentwavetask@509e.run	

aimakeuprepo@5ae4.loadaimake EMAIL ingcomponent@6ba2.observechi asrstreamtask@8422.createinit	FILE
facestretchviewmodel@bd65.changemirr ameupgradedrafttask@e63f.upgrade aganpanelfragment@9fd9.bindseekba omotionbanneradapter@6b1c.onbindview kganviewmodel@586e.onfacefusi delivery@5dd5.deliverloc drafthandler@f1f0.downloadic seteditpagecomponent@a788.downloadai -makeupviewmodel@3113.cancelgene reparestagecomponent@58.ensurestyl mganpanelfragment@9fd9.initphotop amecanvasadjustlogic@563a.adjustamec 7normalhandlerimpl@927f.updatecall secondobjectfetcher@49c2.fetchnorma recapclusterstrategy@674c.generateye uefyprefabrepository@5cd4.doneifiswo hganpanelfragment@9fd9.initobserv seteditpagecomponent@a788.waitmodeli amestickertab@f726.preloadsti gttpromotionfragment@f369.initview effectdraftcomponent@138b.openpublis topickserviceapiimpl@43d4.checkaiaut picklotteddownloader@294b.ensurelott editpreviewviewmodel@f9a1.tryagain ganpanelfragment@9fd9.onactivity stprefabpagefragment@a912.updateenab picklotteddownloader@294b.ensureedit oderationhandlerimpl@1de9.handle makeuppresfetcher@9b27.getaimakeu archloadingcomponent@a395.starti2ilo amecorepresenterimpl@6f97.awaitretry recapclusterstrategy@674c.dogenerate localconfigsfragment@720d.handlerrecl gpicturecropfragment@16c2.stoploadin gpicturecropfragment@16c2.doonfinish baseclusterstrategy@860d.runpipelin feaimenetworkapiimpl@b2d9.postaimecr 5makeuppanelfragment@e4b6.calculatea videouploadcomponent@95e9.fetchststo fectmodelsselectscene@98b.initdata odelpicturereviewmodel@fa9c.select gifsviemodel@472a.searchgifs +taskrepositoryimpl@c0e3.fetchaigct stprefabpagefragment@a912.initdata tservicelistenerimpl@d51a.trytrigger idetaskdialogmanager@215d.showcompat kganpanelfragment@9fd9.initphotop aimetrystylemanager@6ec4.performapp selector@9dcc.ondownload cmakeuppagefragment@9516.observedat makeupviewmodel@3113.selectcolo ttpreviewmodehandler@bae4.swaptomode draftupgradehelper@28d6.upgradedra hubmainviewmodel@a63a.getstylede	

itionstatustextassem@b2f.starttimer EMAILuprepo@5ae4.storetofil assetreverseproducer@54de.produceran	FILE
sttpanelhomefragment@8f3f.observecor imgautogeniconhelper@4893.genicon canvasactionlistener@ff32.onlongpres enscreenfuncprovider@4094.changeplac tretchpersistentimpl@595d.deleteloca ganviewmodel@586e.fetchpanel ideopreviewcomponent@f19c.getlastfra ctsettingspanelscene@878.initview aycomponentviewmodel@715b.loadprevie 7alphavideoscene@9f94.maybestart verticalmusicview@a7b8.buildcolle selectpanelcomponent@2b29.fetchmodel eautocutoutcomponent@4327.autocutout 3aimecreationmanager@e605.aimecreati deletemanager@c8e8.deleteaist 6gifsfragment@3c5.initview atorstickereditpanel@52bb.checkshowg customizeviewmodelv2@83ed.handlefree topickserviceapiimpl@43d4.getautopic 2filteredassetpool@8672.getassetsw imgautogeniconhelper@4893.prepareame draftupgradehelper@28d6.downloaddef ttnewcreatorfragment@9077.onsaveinst seteditpagecomponent@a788.gotoprevie userexpmapmanager@4632.onappexit seteditpagecomponent@a788.startprevi stickerfragmentextkt@8f12.initbottom drafhandler@f1f0.savedraft +amecutouttab@330b.gotocutout prefabeditfragment@56ec.onclose rcollectionlistassem@fdbd.onviewcrea attpanelhomefragment@8f3f.openpanelo 3autopicksession@14df.awaitnexts am@736.run 1autopicksession@14df.awaitnexts inpreviewtitlewidget@434a.pagestateo makeuppanelfragment@e4b6.initdata collectmusicmanager@f40.collectmus ieffectlokicomponent@e537.fetchaigcp archloadingcomponent@a395.getresulti userexpmapmanager@4632.onappenter imagecutoutviewmodel@497d.preview seteditpagecomponent@a788.preloadat atordraftserviceimpl@96ac.getdraftin .customizeviewmodel@8957.reportpage 3ganviewmodel@586e.oncommitup editpreviewviewmodel@f9a1.updateaime facestretchfragment@cdc6.exit imagecutoutviewmodel@497d.changebrus feaimenetworkapiimpl@b2d9.postaigcdi absonboardingv3node@83df.destroy ganviewmodel@586e.setseekbar oderationhandlerimpl@1de9.keepprafto bcarouselplayerview@e8e0.makevideos	

ttpromotionviewmodel@b3db.checkrespa EMAILchrepository@39dc.apply topickpanelcomponent@d649.checktaskr	FILE
slistpanelcontroller@51da.setupbydef imestylepreviewscene@1044.handleload pickloadingcomponent@6ba2.onrunindra autopickpanelscene@9db7.initview ganviewmodel@586e.clearselec ttnewcreatorfragment@9077.initconge ormigrateserviceimpl@95ca.packdrafti prefabeditviewmodel@58ec.done reparestagecomponent@58.preparepro cananalysiscomponent@8894.scanassets +globaleventhelper@930c.emitonboar atorstickereditpanel@52bb.handleswit pickloadingcomponent@6ba2.setupprogr acestretchrepository@39dc.handleaddn estretchresviewmodel@7ac.downloadfa ocaliconlistfragment@8061.initdirlis facestretchfragment@cdc6.onsaveclic makeupviewmodel@3113.updatecate nscreenpromotionimpl@aca7.needshowwe makeupviewmodel@3113.changeacti emanagerinitwavetask@d87b.run imestylepreviewscene@1044.navigateed tickerfeaturehandler@84e5.onsendadds 0aimeimagerepo@b921.downloadim gtoolseditcontroller@c679.saveimg -iamecorepresenter@89d0.runasyncun aycomponentviewmodel@715b.fetchtasks enscreenfuncprovider@4094.applygreen ameimagecutouteditor@22c0.export fyoriginalrepository@defb.apply atorstickereditpanel@52bb.opencutout qlambda@f73a.accept imagecutoutviewmodel@497d.export 8aimecreationmanager@e605.gotoeditpa +makeupviewmodel@3113.saveaimake 6ganviewmodel@586e.toggleface amevelaunttask@f810.dooncreate 5snowsharebottomassem@8f07.sharebutto ffectimgcropfragment@6e89.initcropvi pickloadingcomponent@6ba2.reportsave kmakeuppagefragment@9516.observedit sprefabeditfragment@56ec.observecon baseautocutoutnode@483c.process feaimenetworkapiimpl@b2d9.getaimedis 1facefusionrepo@41cc.changeitem normalhandlerimpl@927f.onrotate 0consumercoordinator@9d43.hasavailab prefabviewmodel@5840.loadeffect perintervalmonitor@6311.flushpart facestretchfragment@cdc6.onbackclic verseclusterstrategy@818a.processnex templateapplynewflow@e669.applytempl bfourpicturefragment@febe.quotacheck uefyprefabrepository@5cd4.apply	

alumpickerrepo@7798.fetchalbum EMAIL fragment@b23d.initdata prefabpanelfragment@ff3c.initdata 2draftupdater@ff1a.updatedraf delivery@5dd5.deliverbin reparestagecomponent@58.waitstylem nowglobalstateutilkt@c142.subscribe umakeuppagefragment@9516.launcheffe transcodenode@bb9a.onprocess voicesearchfragment@47ab.ondisplayw ttnewcreatorfragment@9077.playmusico delivery@5dd5.delivereve iontplviewController@1a31.bindobserv reparestagecomponent@58.setdatatof aimetabviewmodel@6323.updateaime faceinsetresflowimpl@5b2e.waitframeu 1prefabviewmodel@5840.loadeffect htnesschangeobserver@7ddd.onbrightne 7musictrimviewmodel@3254.getmusicwa effectaudiowaveview@f30c.setaudiowa +draftupgradehelper@28d6.prepareupg tpreviewmodehandler@bae4.getorfetch atorofficialrepoimpl@eb36.handlerreqs modelselectimpl@5ce2.fetchfacem pickloadingcomponent@6ba2.ondiscard fyoriginalrepository@defb.createnewf p@w.a5 autopicksession@14df.awaitnextr 9makeuppagefragment@9516.observedat fusionofficialloader@efe7.onofficial ganviewmodel@586e.onfacefusi meprojectpreparetask@6513.getdraftin lmodepicturefragment@490e.initbottom gpicturecropfragment@16c2.downloadta meprojectpreparetask@6513.run 3aistyleresfetcher@6d7b.getmodelef +amenewflowtexttab@32b6.handleedit ackingpanelviewmodel@98d3.downloadan erdonemodeuidelegate@cc84.oninit edithitpanelfragment@5674.onfinishfr ramepreviewcomponent@6cce.oncreate sealumpickermonitor@9b40.loadfinish ttnewcreatorfragment@9077.observefor 2bytebenchv2@5dc8.initcollec imagecutoutviewmodel@497d.downloadre imagecutoutviewmodel@497d.undo draftimpl@6e0f.cleancache pickloadingcomponent@6ba2.getorcreat pickloadingcomponent@6ba2.findprevio stickerframeimpl@91f8.hideallsho ewpager2heighthelper@f55d.updateheig ttliquifyfragmentv2@52bb.initview ffectingcropfragment@6e89.doonfinish tuspublishedrepoimpl@cbec.doload acefusionresprovider@cfcf.getresfrom gpicturecropfragment@16c2.startloadi projectmanager@dca6.createfeat	FILE
---	------

ewpager2heighthelper@f55d.attach Email:lnresprovider@cfcf.getfacefus recapclusterstrategy@674c.generatemo	FILE
ittliquifyfragmentv2@52bb.observewhe makeupviewmodel@3113.removeaima 3ganviewmodel@586e.savelocalf hubmainfragment@b23d.getmoredat cutoutnode@f12.onprocess ttnewcreatorfragment@9077.savedraft iprefabpagefragment@feb3.observedat 6ganviewmodel@586e.fetchpanel perfintervalmonitor@6311.markend stickerselecthandler@50af.replacesti amecutouttab@330b.onactivity amecanvasadjustlogic@563a.updateonbo aimakeuprepo@5ae4.checkandlo musicpanelcomponent@b870.showmusicp picklotteddownloader@294b.awaitdefer 3ganpagefragment@ccac.observedat makeupviewmodel@3113.cancelcate odelresourceprovider@c3f1.getfacemod creenrecordingfilter@43d1.filter seteditpagecomponent@a788.observecam drafhandler@f1f0.onmaineven ganviewmodel@586e.applyprefa eatorstickerfragment@a9ce.initdata reatorcamerafragment@db9c.initview .collectmusicmanager@f40.initcollec visionvisibility@2ff1.record templateapplynewflow@e669.updandsele iktokaigcserviceimpl@ca7b.submitwork reatoralbumtophintvm@c751.onclosecli gcreatorcamerahelper@1908.injectcomp customizeviewmodelv2@83ed.bubblechan mgcreatorv2viewmodel@7599.applyeffec ailfragmentviewmodel@c61.delstyle aimetabviewmodel@6323.getaimemod previewpagecomponent@e7db.onCreate prefabeditviewmodel@58ec.validatest seteditpagecomponent@a788.oncancelbt ckeroperateviewmodel@8eb0.selectfeat terpipelinecomponent@7672.applyl1fil plusbuttoncontroller@4766.waitfacest amenewflowtexttab@32b6.addsticker ti2iloadcomponent@5889.onCreate localconfigsfragment@720d.initview nlistlocalrepository@143f.request outbottomtabfragment@feef.downloadre -filteredassetpool@8672.getassets p@s.a5 7baseclusterstrategy@860d.runpipelin editpreviewviewmodel@f9a1.fetchaimem amebaseloadingtab@e052.injectretr ttliquifyfragmentv2@52bb.onviewcrea ailfragmentviewmodel@c61.onprofileb imgautogeniconhelper@4893.preparerem ittliquifyfragmentv2@52bb.initview	lib/arm64-v8a/libdex_df_ship.so

asetemplateapplyflow@6e5e.fetchmodel EMAIL viewmodelv2@3195.followface fectfeaturecomponent@168f.createfeat	FILE
uploadstatuswavetask@8dac.run ttnewcreatorfragment@9077.observepag eatorstickerfragment@eb94.handlesele aimelauncherfragment@9de9.normalpage perfevent@a4de.record caliconlistviewmodel@4695.createrequ eatoralbumfragmentv2@90fe.setupicont cameraassetfilter@f334.filter tretchpersistentimpl@595d.updateloca stprefabpagefragment@a912.done makeupviewmodel@3113.selectasse componentviewmodelv2@695f.observewor pickloadingcomponent@6ba2.handletask pickloadingcomponent@6ba2.querydraft 0aimeservicesimpl@2ffe.getcurrent gtoolseditcontroller@c679.saveiminn aprefabpagefragment@feb3.observedat templateapplynewflow@e669.upgrade stickerguidefragment@1ac2.lottiecanc localconfigsfragment@720d.applyeffec atortexthomefragment@5114.addsticker eatorstickerfragment@eb94.addsticker 2hubmainfragment@b23d.itemclick ttliquefyviewmodelv2@3195.doapplycle amecorepresenterimpl@6f97.onactivity themeclusterproducer@30fc.producecan imenewcustomizescene@55e6.effecttemp ailfragmentviewmodel@c61.mobdeletep eampipelineexecution@1e2.initialize ttnewcreatorfragment@9077.initlayerl mgcreatorv2viewmodel@7599.commitgree aimakeuprepo@5ae4.remove statebundle@c896.emit makeupviewmodel@3113.checkfiles isdayclusterstrategy@81e2.dogenerate dprefabpanelfragment@ff3c.bindseekba seteditpagecomponent@a788.observevid facefusionrepo@41cc.getfusionm baseclusterstrategy@860d.requestthe componentviewmodelv2@695f.reportstar slistpanelcontroller@51da.changeauto +stickerframeimpl@91f8.changecorn normalhandlerimpl@927f.onmove lbottombarcontroller@1f1b.setupcente kageandscripfetcher@cb75.fetchmainp faceinsetresflowimpl@5b2e.preloadfac atordraftserviceimpl@96ac.packagedra producercoordinator@371.ensureprog aimecreationmanager@e605.aimecreati tservicelisterimpl@d51a.triggernet eaimattingresfetcher@5768.downloadai aimetabviewmodel@6323.unloginloa liquefyimpl@9f1.refreshmai facestretchviewmodel@bd65.requestdat	

rchcontainerfragment@c389.onviewcrea EMAIL networkapiimpl@b2d9.postaigcge icelistenerproxyimpl@3459.addlistene	FILE
aimeinterview@b693.setbuttons amecorepresenterimpl@6f97.updateproj videocutoutviewmodel@ffde.showcompil 5autopicksession@14df.awaitnexts pickloadingcomponent@6ba2.submitorre 6reeditutils@c260.preloadgre makeupviewmodel@3113.executeame .hubmainfragment@b23d.itemclick bumsingleselectlogic@1ca8.bindholder asrstreamtask@8422.ensuremode ctcreatepipelineimpl@e2ca.writelabel prefabviewmodel@5840.initfeatur meprojectpreparetask@6513.preparev2 lttliquifyfragmentv2@52bb.initseekba aimemodelreporter@b81d.reportstar baseclusterstrategy@860d.timed baseclusterstrategy@860d.consumeacan creatorstylerepoimpl@eb15.clear ibilitydialoghandler@2de2.showcompat ktpromotionfragment@f369.initobserv archloadingcomponent@a395.commitgree 6consumercoordinator@9d43.triggernon bytebenchconnection@a5b1.onservicec reparestagecomponent@58.waitmodeli lprefabeditfragment@56ec.observeval ffectimgcropfragment@6e89.onapplyeff dgifsfragment@3c5.observdat .amerouter@3af6.handlerrou ttnewcreatorfragment@9077.createsubm imagecutoutviewmodel@497d.init alalbumpickermmonitor@fa41.loadercall omptenhancecomponent@5992.enhancepro reparestagecomponent@58.preparefea 4tttoolbarwidget@a9e.addtoolbar nowpostbasecellassem@351e.assembleui companion@98eb.checkandme delivery@5dd5.delivermem inpreviewmusicwidget@e63e.getdraftin ffectimgcropfragment@6e89.geticonbit atorstickereditpanel@52bb.featureupd jganpanelfragment@9fd9.initobserv customizeviewmodelv2@83ed.bubbleclie delivery@5dd5.delivermes tiktokgifrepository@f767.downloadgi 7prefabviewmodel@5840.loadeffect triggerviewmodel@22d9.load eampipelineexecution@1e2.processsyn amecorepresenter@ee9a.bindsurfac defaultfetcherimpl@a191.load creatorstylerepoimpl@eb15.createands creendataresprovider@2dc8.preloadpre ttpromotionviewmodel@b3db.fetchdata ti2illoadingcomponent@5889.shotscreen imationpanelfragment@9f44.initobserv	

makeuppresfetcher@9b27.fetchmakeu EMAIL efactoryimpl@3118.createstyl gpicturecropfragment@16c2.onapplyeff	FILE
reparestagecomponent@58.translatep 7collectmusicmanager@f40.initunlimi efabcategoryloadtask@8de0.run gslstpanelviewmodel@c975.changeauto asrstreamtask@8422.preloadint ormigrateserviceimpl@95ca.migratedra ttnewcreatorfragment@9077.initaimake styleselectcomponent@eed.recorddata longloadingpredictor@973f.countasset hsladjustfragment@cc19.recoverlas ectmediadetectorutil@1704.detectorim effectmediadetector@cd93.detectface facestretchviewmodel@bd65.setupforcr 9messagecarouselvew@c57a.schedulero -amecutouttab@330b.gotocutout imakeuppanelfragment@e4b6.initview animationviewmodel@e3f4.done amecutouttab@330b.getsticker .collectmusicmanager@f40.loadmoreco archloadingcomponent@a395.onsavedraf tgreenscreenhelperv1@b92c.genveframe 0hubmainfragment@b23d.itemclick ceinsetpanelfragment@3e93.initdata aimelauncherfragment@9de9.navigateto canvasactionlistener@ff32.onpointdra enstyleresultmanager@35df.postnaviga autopicksession@14df.repick +stickerframeimpl@91f8.showfacefo idereditpagefragment@c761.onviewcrea oubleclicklikelayout@fa95.doafterani econdobjectviewmodel@9b86.fetchpanel eatorlayerviewholder@b52a.onstatecha fganpagefragment@ccac.observedat picklotteddownloader@294b.ensurelong adjustpanelutiltextkt@cd4.createadju stickerpanelimpl@54a9.showsticke dailyclusterstrategy@ea07.dogenerate stylerepository@15e0.getstyle gprefabpanelfragment@ff3c.initdata opickpanelguidescene@80d3.changestat localconfigsfragment@720d.refreshdat +baseassethandler@7ec4.schedulefr ffectimgcropfragment@6e89.getstyleta perfintervalmonitor@6311.markbegin mttliquifyfragmentv2@52bb.initobserv 6ganpagefragment@ccac.observedat ailfragmentviewmodel@c61.quotacheck ganviewmodel@586e.initfeatur makeupviewmodel@3113.emitparams tickersearchfragment@bb76.addgiphyst amegreenscreentab@f75.applygreen amegreenscreentab@f75.handleabc ctcreatepipelineimpl@e2ca.ondraftore amelaunchtask@d1f1.await	

ttliuefyviewmodelv2@3195.gethandled EMAIL changeobserver@10a.onvolumech yfastclusterstrategy@ab24.dogenerate	FILE
effecteditoractivity@a2af.onCreate ffectimgcropfragment@6e89.stoploadin ideopreviewcomponent@f19c.onCreate lbumpickeralgoloader@82cb.load express4runner@e270.getparsefu imationpanelfragment@9f44.initdata prefabeditviewmodel@58ec.validateph onboardingv3fragment@a2a8.registerob jttliquifyfragmentv2@52bb.initseekba enstyleresultmanager@35df.generateon eeklyclusterstrategy@9057.processnex makeupviewmodel@3113.downloadre eprogresscoordinator@b04d.runrelease keffecteditorcontext@5cb5.ttdoafterr animationviewmodel@e3f4.onpagefixe eautocutoutcomponent@4327.registerob ameautocutoutrepo@8606.chaincallb 1makeupviewmodel@3113.loadeffect secondobjectfetcher@49c2.fetchpanel atorstickerviewmodel@4254.updatelast ourcedownloadnewimpl@4e8a.updatereso nowsharebottomassem@8f07.onhostpaus gtoolseditcontroller@c679.saveoffici aimakeuptophintvm@5ac4.onclosecli ganpanelfragment@9fd9.bindseekba 3phasestackview@ebdd.animatepha ckpanelguidefragment@b009.changestat -customizeviewmodel@8957.getfreecre lectionlistviewmodel@a262.onloadbefo stprefabpagefragment@a912.resetall hsladjustfragment@cc19.resetvalue 2textstickerresflow@3f39.obtainaddf jankframecollector@560d.start nimationpagefragment@b779.observedat amecorepresenterimpl@6f97.awaitproje progresssmoother@1224.startfilli bfourpicturefragment@febe.delstyle hsladjustfragment@cc19.applyadjus 0amecutouttab@330b.preloadfac categoryitemview@b2ec.updatedata ganviewmodel@586e.eecreatefe singledetailfragment@8081.showsaveto 6alphavideoscene@9f94.performsub gmakeuppanelfragment@e4b6.initdata behaviourimpl@96c1.showprevie enstyleresultmanager@35df.styledetai gmakeupviewmodel@3113.loadeffect imgautogeniconhelper@4893.loadrandom +filteredassetpool@8672.getassetsw faceinsetresflowimpl@5b2e.changeface ckedraftextraimpl@fabf.savefile tupublishedrepoimpl@cbec.fetchusers bbottombarcontroller@48f3.setupright customizeviewmodelv2@83ed.newcustomi	

faceinsetresflowimpl@5b2e.getlayerdi EMAIL arebottomassem@8f07.clearconta 8officialconutliskt@8545.loadoffici	FILE
creatorbaseviewmodel@6ca3.emitevent defaultfetcherimpl@a191.doload mestickercutoutfuckt@8cf2.addorrepla fganpanelfragment@9fd9.initview consumercoordinator@9d43.hasonlypre iprailpanelcomponent@65e4.savedrafta inglepicturefragment@9.onviewcrea gonboardingv3tipview@64f2.initview ifacestretchfragment@cdc6.initview 9prefabpagefragment@feb3.observedat 2ganviewmodel@586e.loadfacefu topickserviceapiimpl@43d4.trackuploa cprefabeditfragment@56ec.onviewcrea ttnewcreatorfragment@9077.startameco noweventregistry@2a90.fire acestretchrepository@39dc.applyeffec delivery@5dd5.deliversam ecutoutpanelfragment@2aad.getsticker fectfeaturecomponent@168f.replaceand stylerepository@15e0.usecache loadinggate@35b9.tryfire ntalviewshowctrlimpl@4f40.triggersho inpreviewtitlewidget@434a.reqandupda aimeintroview@b693.setupscrol makeuppanelfragment@e4b6.initview feaimenetworkapiimpl@b2d9.getstylede stprefabpagefragment@a912.resetallva atorstickereditpanel@52bb.reportinsp selectpanelcomponent@4222.sceneactio delivery@5dd5.delivercpu componentviewmodelv2@695f.openstyler amedbinittask@1716.run delivery@5dd5.dumpcpu 3ganviewmodel@586e.setfacefus +editormodelimpl@5d2e.selectandc prefabviewmodel@5840.eecreatefe stickerframeimpl@91f8.alwayshide wabsonboardingv3node@83df.dowhenloca reeditpaneladapter@da98.bindselect mestickercutoutfuckt@8cf2.handlesele hubmainfragment@b23d.delaimemod ckcliprailpanelscene@f69d.onshow effectmodeuidelegate@240a.oninit eampipelineexecution@1e2.processasy taskexecutor@f5da.call imagecutoutviewmodel@497d.reverse2db makeupviewmodel@3113.selectpref ickrootslotcomponent@4cb3.warmupalph ameimagecutouteditor@22c0.initmattin amevideocutoutplayer@403b.prepareasn ramepreviewcomponent@482.launchuplo ttpanelhomefragment@8f3f.openpanelo texteditpagefragment@ce45.onviewcrea duplicateinterceptor@cafa.intercept	

hsladjustfragment@cc19.getadjustf EMAILpresenterimpl@6f97.prepareres onboardingv2fragment@d2c5.updatard	FILE
gcreatoreffecthelper@7d21.loadrafte amecorepresenter@ee9a.updateproj kstickerpagefragment@e4f5.initobserv 2nowsharebottomassem@8f07.startshare hsubverecorderhelper@2fed.initsubver uabsonboardingv3node@83df.dowhenloca ttlquefyviewmodelv2@3195.mirror zemonitorserviceimpl@c952.calculatef verseclusterstrategy@818a.dogenerate ameimagecutouteditor@22c0.init acestretchrepository@39dc.handlerepl gganpanelfragment@9fd9.bindseekba effecthintviewmodel@ee0c.load otoseditpagefragment@8917.onviewcrea jarvisuploader@bb4f.reportanr 0draftupgradehelper@28d6.getupdated seteditpagecomponent@a788.setdatatof cutoutbottomfragment@2b85.initprevie themeclusterproducer@ba79.getcluster atortexthomefragment@5114.ontextedit canvasactionlistener@ff32.onmove gaimetabfragment@e8f3.checklogin eimagecutoutactivity@e7b9.initobserv angmodeldownloadtask@7c68.downloadli canvasactionlistener@ff32.onrotation verticalmusicview@a7b8.loadingvie uttpanelhomefragment@8f3f.observecor fyoriginalrepository@defb.doneifiswo ttfeatureoperator@9edd.copy anelcomponentmanager@d39d.initcompon creendataresprovider@2dc8.getgreensc feaimenetworkapiimpl@b2d9.postaimest tservice listenerimpl@d51a.onafterdel ieffectlokicomponent@e537.fetchstyle ttlquefyviewmodelv2@3195.stateselec aimeservicesimpl@2ffe.trycustomi ttnewcreatorfragment@9077.selectobse sicrimpanelfragment@bc06.initview eampipelineexecution@1e2.complete editpreviewviewmodel@f9a1.observerst creendataresprovider@2dc8.preparegre inpreviewmusicwidget@e63e.checkshowm dailyclusterstrategy@ea07.processnex aimetabfragment@e8f3.setviewmod facefusionrepo@41cc.addfacefus imagecutoutviewmodel@497d.redo ceinsetpanelfragment@3e93.updateface secondobjcombinerepo@822a.fetchpanel companion@98eb.warmloadmo archloadingcomponent@a395.oncreate nscreenpromotionimpl@aca7.showwebshe ailfragmentviewmodel@c61.downloadac screenthumbgenerator@4b96.initrecord cefusionfuncprovider@d4bb.handlechan	

-draftupgradehelper@28d6.updatedraf EMAIL layerimpl@3b51.updatelayer freeditpaneladapter@da98.bindstater	FILE
mttpromotionfragment@f369.initobserv draftupgradehelper@28d6.fetcheffec fprefabeditfragment@56ec.observecan ntalviewshowctrlimpl@4f40.init -makeupviewmodel@3113.loadaimake icelisterproxyimpl@3459.onevent 2alphavideoscene@9f94.runsubtitl facefusionrepo@41cc.removeface nowpostbasecellassem@351e.dispatchot eatorstickerfragment@eb94.calculatea templateapplynewflow@e669.handleappl ganviewmodel@586e.emiteditpr ctcreatepipelineimpl@e2ca.cropandsav imgautogeniconhelper@4893.preparecus -stickerresflowimpl@8b68.obtainstic greeditpaneladapter@da98.bindnormal stprefabpagefragment@a912.getadjustf eeffectenvlaunchtask@8b0e.run ngslistpanelfragment@20bf.initview gpicturecropfragment@16c2.initview recapclusterstrategy@674c.generateca customizeviewmodelv2@83ed.fetchaimes canvasactionlistener@ff32.ondown creendataresprovider@2dc8.getprefabb aimemoduleimpl@3a8c.createorfe ti2iloadcomponent@5889.onrecordfi eatorstickerfragment@a9ce.handleitem baseclusterstrategy@860d.initialize draftupdater@ff1a.updatedraf creatorviewmodel@f9f8.triggerlay amecorepresenterimpl@6f97.needrunfet dithitpanelviewmodel@a5bb.commitgree +aimetabviewmodel@6323.checkcusto ctonboardingfragment@7b49.initview topickpanelcomponent@d649.onaiautocu aimelauncherfragment@9de9.redirectst amecorepresenterimpl@6f97.upgradedra gcreatorcamerahelper@1908.takephoto seteditpagecomponent@a788.preloadi2i ourcedownloadnewimpl@4e8a.blockrules -behaviourimpl@96c1.notifycomm .featureoperator@e35d.adjustposi animationviewmodel@e3f4.applyprefa gifsfragment@3c5.initview animationviewmodel@e3f4.reeditanim 2baseclusterstrategy@860d.runpipelin gifsviewmodel@472a.loadtrendg ttemplatefragment@cd72.initbottom ae@73e.run ltiponboardingv3node@2b24.registerne gpicturecropfragment@16c2.geticonbit canvasactionlistener@ff32.onup longloadingpredictor@973f.querytotal metricsmonitor@15b5.updateconf	

componentviewmodelv2@695f.handlestyl EMAIL:refragment@cd72.initbottom verticalmusicview@a7b8.initrecomm	FILE
gcreatoreffecthelper@7d21.fetchdraft enstyleresultmanager@35df.downloadim tracingfilterchain@f11d.filterwith previewpagecomponent@e7db.onconfirml eatorstickerfragment@eb94.addorrepla aimakeuprepo@5ae4.addaimakeu musicpanelcomponent@b870.getmusicpa utopicklogfilewriter@b890.endsession ttlquefyviewmodelv2@3195.deleteloca verticalmusicview@a7b8.showsearch nanimseqshowprovider@6cdd.onseqshow nowsharebottomassem@8f07.onviewcrea amemodesettask@2ae.run ickeroperatefragment@36ad.onchange screenthumbgenerator@4b96.genthumb 0drafhandler@f1f0.openpublis 3producercoordinator@371.awaitchang scenemonitor@e338.flushinter facestretchfragment@cdc6.showbackdi amecorepresenterimpl@6f97.onviewcrea amerouter@3af6.addrouterp -textstickerresflow@3f39.obtainstic ganviewmodel@586e.savelocalf seteditpagecomponent@a788.posthandle 4objectitem@70a2.special imgautogeniconhelper@4893.preparecro makeupviewmodel@3113.preloadaddw 1ameautocutoutrepo@8606.chaincallb facestretchviewmodel@bd65.addorupdat 8ganviewmodel@586e.setfacefus eprefabeditfragment@56ec.onviewcrea kloadingcontentscene@f88d.go2editpag ataprovidercomponent@ba4b.loadmediaf enstyleresultmanager@35df.startgener filteredassetpool@8672.getorloads plusbuttoncontroller@4766.handlelic amecorepresenter@ee9a.onviewcrea inglepicturefragment@9.showsaveto eampipelineexecution@1e2.waitforall eselectpagecomponent@f889.fetchstyle iadetectorrepository@c873.containfac npostgesturelistener@e05f.checkandha componentviewmodelv2@695f.handle succ kamelaunchpanellogic@a41c.initseqlau aichoosemusicmanager@da6d.getaipanel attingresfetcherimpl@8fc8.preloadmat ideopreviewcomponent@f19c.choosemode imgautogeniconhelper@4893.prepareran ctcreatepipelineimpl@e2ca.cropiconan ganviewmodel@586e.applyfacef hganpagefragment@ccac.observedat ackingpanelviewmodel@98d3.changetrac 7messagecarouselview@c57a.clearstabl atorstickerviewmodel@4254.requeststi	

tnewcreatorfragment@9077.observedra EMAILsterstrategy@91c8.scanwindow ttingspanelcomponent@2acc.showsettin slistpanelcontroller@51da.changeport 6officialiconutlskt@8545.loadoffici mestickercutoutfuckt@8cf2.addsticker wvertcalmusicview@a7b8.initsearch languagemodeltask@fc90.forwardsin fectfeaturecomponent@168f.exporteffe tttoolbarwidget@a9e.onconfigur 1drafthandler@f1f0.handleconf feaimenetworkapiimpl@b2d9.getaimelis prefabviewmodel@5840.cancelpref messagecarouselview@c57a.clearswitc ttttoolbarwidget@a9e.rendertool cefusionfuncprovider@d4bb.changetofu ttlquefyviewmodelv2@3195.loadfacest ameimagecutouteditor@22c0.onactionup pickerviewcontroller@a872.initobserv utopicklogfilewriter@b890.onlog ttdataeventreceiver@e70e.ondataeven chestratationcomponent@b9ce.executefix mecovereditviewmodel@c5c4.detectface prefabviewmodel@5840.applyprefa fectpreviewviewmodel@ace0.sendprevie editpreviewviewmodel@f9a1.buildstyle 0secondobjectfetcher@49c2.fetchcombi ttlquefyviewmodelv2@3195.togglepage tylepreviewviewmodel@9526.generatest goalbumpickermonitor@2ce0.loadercall ectimgcreatorveutls@fa0a.renderimag 6filteredassetpool@8672.getorloads ti2ilodingcomponent@5889.getresulti 0collectmusicmanager@f40.updatecoll ganpagefragment@ccac.observedat elangdeviceexecution@ad3f.preloadres verticalmusicview@a7b8.showaidata nowpostutlskt@9e4e.roundandad -draftupgradehelper@28d6.refresheff aistylesfetcher@6d7b.getmodelef makeupresfetcher@9b27.getmakeupf ackingpanelviewmodel@98d3.exit ilamaterialsdkimpl@a5d8.downloadmo gslistpanelviewmodel@c975.fetchlist atorstickereditpanel@52bb.showgreens 2ameautocutoutrepo@8606.chaincallb edgeflowmanager@9681.sendtooutp filterchain@7194.filter promptinputcomponent@dac6.onreferenc tservicelisterimpl@d51a.savedeploy ailfragmentviewmodel@c61.onpostbutt mgiconeditcontroller@c62e.fetcheffec amakeuppagefragment@9516.showaimake prefabeditviewmodel@58ec.updatesubm retryimagelayout@8d71.enableagai modelfetcher@5c4a.fetchmodel tretchpersistentimpl@595d.getlocalfa	FILE
--	------

reparestagecomponent@58.expORTEffe EMAIL presenterimpl@6f97.runupgrade asrstreamtask@8422.process	FILE
inglepicturefragment@9.downloadpi eautocutoutcomponent@4327.loadimg asrstreamtask@8422.initchanne 7makeupviewmodel@3113.loadeffect kttlquifyfragmentv2@52bb.observewhe -amegreenscreentab@f75.preparegre amecorepresenter@ee9a.onactivity vadaptershowctrlimpl@8d09.bind amecorepresenterimpl@6f97.runapplyef modelselectcomponent@ef2b.notifysele makeupviewmodel@3113.selectcate bytebenchv2@5dc8.loadbytebe aimetabfragment@e8f3.onviewcrea carouselplayerview@e8e0.scheduletr fectcomponentmanager@3783.checkandad imagecutoutresloader@6fb5.init ommoncustomizeviewkt@aa97.customizee gcreatorcamerahelper@1908.onCreate atordraftserviceimpl@96ac.getProject tservicelisterimpl@d51a.fetchdepo iquefyv2pagefragment@4341.initobserv prefabpagefragment@feb3.observedat 0collectmusicmanager@f40.initcollec mecovereditviewmodel@c5c4.generateco retchdragchildlayout@bf04.setoverlap ffectentranceservice@55a.chechaifea tpreviewmodehandler@bae4.onmodechan aprefabpanelfragment@ff3c.initdata selector@9dcc.notifysele attingresfetcherimpl@8fc8.loadmattin mgcreatorcameratools@c0f6.registerli aimelauncherfragment@9de9.redirectmo creatorviewmodel@f9f8.resetstatu tretchpersistentimpl@595d.addlocalfa selectpanelcomponent@2b29.sceneactio ataprovidercomponent@ba4b.loadassets +amecutouttab@330b.gotomediad ataprovidercomponent@ba4b.loadaluma eshapepanelviewmodel@fe83.changeshap prefabeditviewmodel@58ec.initdata cprefabpagefragment@feb3.observedat edithitpanelfragment@5674.replaymusi inspectoretutis@602c.getplaceho iquefyv2pagefragment@4341.onautojump makeupviewmodel@3113.createfeat mecovereditviewmodel@c5c4.ontouchup tservicelisterimpl@d51a.isdraftlis makeupviewmodel@3113.clearselec kageandscriptfetcher@cb75.needforceu	

EMAIL	FILE
defaultadapter@8c6.async pitayahostdefault@b731.onapplogev 6coredefaultimpl@d2fa.registerap coredefaultimpl@d2fa.runnativet defaultadapter@8c6.asyncafter innerworkhandler@1f72.gethandler 1@349b.com_byteda 0defaultadapter@8c6.processcol pitayahostdefault@b731.hostsetup ptysettingsutil@2f5f.updatesett clientaihttpclient@89c8.postinwork -nphstackreporter@c9f.reportalln defaulthttpclient@6245.post +coredefaultimpl@d2fa.releasenat 4coredefaultimpl@d2fa.removeappl tionlifecyclewatcher@4905.registerap 1@6830.call ttnehttpclientimpl@7567.get coredefaultimpl@d2fa.removemess defaultadapter@8c6.timer .coredefaultimpl@d2fa.registerme ttnehttpclientimpl@7567.post -pitayahostdefault@b731.oncustomap 6pitayapluginimpl@80c8.registerpi tionlifecyclewatcher@4905.onappstatu coredefaultimpl@d2fa.runtask	lib/arm64-v8a/libdex_df_pitaya.so
g@9277.run d0@43b9.call gluetosdkincookie@1cce.setsyscook l0@3ee1.run p@9280.run o@929f.run j@929a.run u@9285.run k@927b.run b0@43f7.run owserpreinitexecutor@4d02.handlemess r@92a2.run j0@42ff.run y@92a9.call c0@3ff8.call m@929d.call n0@3ea3.call v0@418b.run q0@4226.call v@9286.run w0@416c.call m0@3ec2.call x0@414d.call g0@435c.run s@9283.run w@9287.call	

t0@3de9.run EMAIL chromium@d8d6.onmeasure c0@43d8.call	FILE
b0@4017.run t1@3de8.handlemess e1@4399.call k0@42e0.run h0@3f5d.run a@9271.call q@92a1.run p0@3e65.run i0@431e.call y0@3d4e.run b@9292.allow k0@3f00.run s0@41e8.call m0@42a2.run f1@437a.run i0@3f3e.run g1@3f7b.run i@9299.getusagefo t@92a4.run b@9292.clear o@927f.call g1@435b.run g0@3f7c.run d@9274.call n@927e.call e0@3fba.run w0@3d8c.run f0@437b.call n0@4283.call l@929c.call z@928a.run z0@3d2f.run c1@3ff7.run h1@433c.call i@9279.run x@9288.run h0@433d.run f0@3f9b.run z0@410f.call z@92aa.run a1@4035.call k@929b.run i@9299.deleteallId e@9275.run m@927d.call c@9273.call u0@41aa.run android-webview-dev@chromium.org j@927a.call v@92a6.run u0@3dca.call q@9281.call d1@3fd8.run o0@4264.call	lib/arm64-v8a/libdex_df_ttwbview.so

q0@3e46.run EMAIL s1@3e07.run	FILE
b@9272.run y@9289.run i1@3f3d.run t0@41c9.run p0@4245.call x@92a8.run b@9292.getallowed u@92a5.run s@92a3.run t@9284.run b1@4016.call e0@439a.call o0@3e84.call j0@3f1f.run b@9292.getorigins r0@3e27.call p@92a0.run a0@4036.run r0@4207.call l0@42c1.run s0@3e08.call l@927c.run w@92a7.call e1@3fb9.call v0@3dab.run a0@4416.run omiumfactoryprovider@38d1.initialize ebviewruntimeservice@6831.registerda b@9292.clearall x0@3d6d.call y0@412e.call h@9278.call d0@3fd9.run	
zhangke.finn@bytedance.com	lib/arm64-v8a/libfast_engine.so
6bddlnasourcewrapper@10b1.setplayerl rtceventnotifier@2c05.onfirstvid zzc@c2ed.call dlnasourceimpl@1a94.resume chromecastsourceimpl@71b3.play 8bddlnasourcewrapper@10b1.setplayerl bytemediarecorder@e39e.init chromecastsourceimpl@71b3.add dramali nsdhelper@cdf3.startdisco stopbrowserrunnable@80f7.run rvicediskcachehelper@769c.checkservi zzbr@17e6.run castingmanager@f46d.startbrows castingplayerimpl@f321.addseeklis chromecastsourceimpl@71b3.updatedisc nsdhelper@cdf3.stopdiscov retryexecutor@3f26.onfail	

readerthread@d197.run EMAIL playmanager@89e6.ondramaid astingpanelcomponent@c8ae.onchange	FILE
castingmanager@f46d.emit rtceventnotifier@2c05.onvideoenc videorecordermanager@acb0.preparevid dlnasourceimpl@1a94.pause nsdclient@70a1.handlereso nsdserver@c708.stopsrver rtceventnotifier@2c05.onintofore rtceventnotifier@2c05.onconnect bytecastsourcimpl@9ea6.getsinkdev dlnasourceimpl@1a94.addvolume omecastsourcwrapper@3a80.setplayerl dlnasourceimpl@1a94.play smhandler@e866.handlemess .mirroringmanager@9956.delayendmi chromecastsourcimpl@71b3.playnextdr chromecastsourcimpl@71b3.resume castingmanager@f46d.initsdk zzbe@2161.run dlnasourceimpl@1a94.changereso astingpanelcomponent@c8ae.onparentvi startbrowserrunnable@cc6.run 3bytecastsourcimpl@9ea6.authbylice chromecastsourcimpl@71b3.addvolume tvcasting@552b.initialize dlnasourceimpl@1a94.setvolume chromecastsourcimpl@71b3.swapdevice e@84c7.oncast zzq@bce7.run nsdserver@c708.startserve chromecastsourcimpl@71b3.destroy nsdhelper@cdf3.handlefoun getvolumerunnable@90a7.run dlnasourceimpl@1a94.getdevicei servicelistpanelkt@6531.servicelis dlnasourceimpl@1a94.getmediain -castingmanager@f46d.initsdk chromecastsourcimpl@71b3.playpredra pauserunnable@b7d1.run chromecastsourcimpl@71b3.disconnect decodethread@c0e7.run rtceventnotifier@2c05.onpaused castingmanager@f46d.runonuihr chromecastsourcimpl@71b3.refreshrou zzba@2165.run audiopassiveplayer@bdac.callbackau ssdpsearchsocket@1033.run zzc@8fc7.call nsdhelper@cdf3.onnsdresol 9mirroringmonitor@94c.displaylis mirrorcontroller@933f.startmirro controlpoint@eae5.checkandad castadvertiser@44ac.run zzbp@17e4.run chromecastsourcimpl@71b3.connect	

rtceventnotifier@2c05.onrecvmeta EMAIL castsourcimpl@71b3.subvolume mirroringmonitor@94c.init	FILE
eractinfotvcastassem@7913.onviewcrea castssdpsearchsocket@ef9.run chromecastsourceimpl@71b3.setupnewap renderthread@49f0.run playercontroller@ab13.play writethread@1526.run astingservicemanager@3eb0.startbrows zzbq@45db.run advertiser@631e.run -bddlnasourcewrapper@10b1.getvolume chromecastsourceimpl@71b3.playdramai zsz@bce9.run renewssubscriber@a501.run chromecastsourceimpl@71b3.updatedemedi bytecastsource@596e.init zzr@8534.run zsz@8535.run controlpoint@eae5.search chromecastsourceimpl@71b3.setvolume bddlnasourcewrapper@10b1.send 5bddlnasourcewrapper@10b1.setplayerl zzg@bcdd.run dlnasourceimpl@1a94.send chromecastsourceimpl@71b3.seekto castssdpnotifysocket@ebb6.run astingpanelcomponent@c8ae.startplaya rtceventnotifier@2c05.onsinkstuc zzas@2172.run rtceventnotifier@2c05.onmonitore -networkutil@dfe1.checkandcr zzbo@17e3.run zzbn@17e2.run rvicediskcachehelper@769c.writecache dlnasourceimpl@1a94.getstatusi rtcengineimpl@2d44.playvideo setvolumerunnable@c0a9.run -voipvideorender@6561.notifyvide httpsocketrunnable@df35.run nsdclient@70a1.notifybrow zzbm@17e1.run zzt@8536.run castingutils@42a6.getawemeli laybackcontrollayout@5e8c.maybeshown videorecordermanager@acb0.pause 1bytecastsourceimpl@9ea6.initperfor searchresponsesocket@7471.run zzah@17bd.run videorecordermanager@acb0.stop httpserver@dd9f.run videorecordermanager@acb0.start zzu@8537.run rtceventnotifier@2c05.onstat rtceventnotifier@2c05.onintoback einfo listenerwrapper@18c9.delaysched	

EMAIL	FILE
chromecastsourcempl@71b3.init stingplugininstaller@8e02.oninstallp -rtceventnotifier@2c05.onconnects -bytecastsourcempl@9ea6.connect networkmanager@4f82.start zzbl@17e0.run zzd@c2ee.call transporthandler@d93c.handlemess zzav@1fbc.run concurrentsubject@e489.notifyobse threadcore@9e70.run devicemanager@ae59.clearbrows astingpanelcomponent@c8ae.onconnect rtceventnotifier@2c05.oncastsucc zzl@8d1b.run mainhandler@148c.handlemess devicemanager@ae59.deviceadde rtceventnotifier@2c05.onaudioset stoprunnable@46ac.run astingpanelcomponent@c8ae.startmirro rtceventnotifier@2c05.onkilled dlnasourcempl@1a94.stop dlnasourcempl@1a94.connect e@84c7.onstart videorecordermanager@acb0.resume seekdelayrunnable@9f68.run ssdpnotifysocket@f51d.run zzar@2173.run omecastsourcewrapper@3a80.setbrowser 9bddlnasourcewrapper@10b1.setmessage bytecastsource@596e.startbrows rtceventnotifier@2c05.ondisconne zzq@75d2.run chromecastsourcempl@71b3.pause controlpoint@eae5.handledevi concurrentsubject@e489.notifyexce dlnasourcempl@1a94.changespee .bytecastsourcempl@9ea6.setauthbyl dlnasourcempl@1a94.checkandcr e@84c7.onrecvmeta playdramaidlistener@ec4c.onfail +dlnasourcempl@1a94.getstatusa chromecastsourcempl@71b3.setrepeatm f@84c8.setvolume e@84c7.onconnect einfoListenerwrapper@18c9.onerror playrunnable@6bf9.run bytecastsource@596e.deinit +bddlnasourcewrapper@10b1.send rtceventnotifier@2c05.onerror chromecastsourcempl@71b3.cleardrama chromecastsourcempl@71b3.playdramal 0bddlnasourcewrapper@10b1.getvolume devicemanager@ae59.deviceremo ecardlinkbuttonassem@9885.onviewcrea	

ttdsptablayout@2a64.addtabview EMAIL lyerfragment@28f8.setupviewp foryoulistviewmodel@1ref.loaddata	FILE
edsongslstviewmodel@7b6e.loaddata 6dspauthtokenfetcher@f3a9.requestdsp n@t.jt ryoriginloader@22de.load n@t.j2 tabpageassem@e8f7.subscribev aunchstrategymanager@e163.requestlin mainpagedatamutation@42dd.operate baselyricsview@d7c.reset2star edspplaylistmutation@12cc.operate -addtomymusicmanager@f107.addsongtom addedsongslstassem@a434.onwindowfo azonmusicauthhandler@45cb.refreshama cacesstokenmutation@c4ec.operate tagpanelviewmodel@f282.gettagpane dspfpsreporther@7a.dspsubplay rddetaildatamutation@8893.operate nginelisteneradapter@cbe8.ontimeupda librarylistviewmodel@7bbd.loadsongs tdspplaylistmutation@d215.operate mediaplayer@e4b0.onattach ngtomusicappmutation@1f63.operate tificationcontroller@925b.mhandler dspauthtokenfetcher@f3a9.refreshacc ongcardlistviewmodel@3014.onprepared fanspotlightassem@70ab.initbottom -mdverticalviewpager@8f2e.mendscroll cacesstokenmutation@b5ae.operate ddtomusicdspauthutil@c894.selectdsp 6dspauthtokenfetcher@f3a9.requestref ddtomusicdspauthutil@c894.updatedspp ouoriginloader@bec7.load sicsdpqueuelstassem@3dab.onviewcrea -mymusicsongassem@bd6a.bindexposu +multisongcardassem@64e2.onviewcrea adspfpsreporther@7a.forcedspu queueloadplugin@b85e.loadmore tyoauthmusicreceiver@1868.oncreate baseplayerviewmodel@37a1.loadmore otlightdetailsharevm@1691.onrefresh tailhitlistviewmodel@a699.onrefresh sptackexpiredplugin@2375.showsubscr ddtomusicdspauthutil@c894.addsongtom ixoriginloader@232e.load icdspplayerviewmodel@83f0.checkswipe journeysourceloader@5df4.load journeysourceloader@5df4.loadmore addtodspviewmodel@9231.reportadds dspitemreusedassem@b7ba.onviewcrea lightsharedviewmodel@fb69.saveselect getdspplaylistsquery@f8ff.operate cdetaillistviewmodel@ea91.loaddata librarylistviewmodel@7bbd.loaddata platformssettingpage@9a54.loaddsppla	

mysongssourceloader@3da7.loadmore EMAIL playablenanager@9b00.resetactio ttdspabstrip@aa32.attach	FILE
ddtomusicdspauthutil@c894.getusersele edsongslstviewmodel@7b6e.clicklinkb .campaigncardassem@ea73.bindexposu librarylstviewmodel@7bbd.loadmoreso tabpageassem@e8f7.onwindowfo nginelisteneradapter@cbe8.toggleletime absplayablequeue@1604.load ddtomusicdspauthutil@c894.getinstall -dspauthtokenfetcher@f3a9.refreshacc pplmusicauthhandler@f019.refreshapp haccesstokenmutation@4fee.operate teoriginsourceloader@f51e.load 0dspauthtokenfetcher@f3a9.requestdsp mysongssourceloader@3da7.load 8dspfpsreportheper@a7a.forcedspla +baselyricsviewmodel@c093.getirclyri sicdpsheetviewmodel@3e3c.loadplatfo latformlstmethodidl@d11f.handle guidehelper@f22a.checkswipe ouoriginsourceloader@bec7.loadmore musicplayviewmodel@970a.playmusic reportactionmutation@6d59.operate edsongslstviewmodel@7b6e.reportshow oidsessioncontroller@2942.maudiooutp eekbarchangelistener@11c0.onstoptrac mymusicactivity@4fe3.oncreate +addtomymusicmanager@f107.addsongtom odspnetworkmonitort@e6a0.addsongmus imilarsongsviewmodel@5e01.getsimilar haccesstokenmutation@68bf.operate edspauthtokenfetcher@f3a9.requestref musicdsplikeassem@dd13.onlikeclic mediaplayer@e4b0.play 1addtomymusicmanager@f107.addsongtom ryoriginsourceloader@22de.loadmore zespecificdsphandler@b324.handle ongscheckfordspquery@6a28.operate queueloadplugin@b85e.load getsimilarsongsquery@d509.operate 2dspauthtokenfetcher@f3a9.requestdsp 3dspfpsreportheper@a7a.dsplaunchd threadutil@fcce.sam lottieguide@f3e7.dismiss librarylstviewmodel@7bbd.refreshjou musicsettingpage@e355.initdata dspplatformlstquery@5a00.operate lechangereportplugin@9eed.onplayable teoriginsourceloader@f51e.loadmore reportmanager@d9ac.reportacti +dailypickcardassem@5864.onviewcrea addtopresaveauthutil@7d3.addpresave lechangereportplugin@9eed.doaddrepor similarmusicfragment@feee.oncreatevi caccesstokenmutation@f6d2.operate	lib/arm64-v8a/libdex_df_music_dsp.so

ixoriginsourceloader@232e.loadmore EMAIL usicdspauthutil@c894.getdspplat ddtomusicdspauthutil@c894.songcheckf	FILE
2lyricinfo@3645.getlyricin addedsongslistassem@a434.subscribev azonmusicauthhandler@45cb.getamazonm otlightdetailsharevm@1691.onloadmore sptackexpiredplugin@2375.onplayback umtomusicappmutation@f5d8.operate cdspjourneyviewmodel@e737.fetchsongs musicdspabfragment@f159.oncreatevi songcheckfordspquery@d39e.operate ddtomusicdspauthutil@c894.createdsp lottieguide@f3e7.show preloadplugin@b661.preload sicsdpaudiocardassem@3fa1.onviewcrea sicsdpsheetviewmodel@3e3c.requestpla cketplatformsyncpage@3038.initdata dspaudioseekbarassem@9696.seekbarsho absplayablequeue@1604.loadmore piredplayablemanager@d256.resetactio usicdsplikeviewmodel@8702.savesongto baselyricsview@d7c.mhandler installdetectmanager@c140.getdspinst moveanimator@6935.run ddtomusicdspauthutil@c894.getdspplay edspplatformmutation@394.operate sicmainpageviewmodel@271e.loaddata lightbottomcomponent@75a.createbott gstomusicappmutation@76c2.operate justtagscachemanager@77d9.writelocal	
appro@openssl.org	lib/arm64-v8a/libtccrypto.so
appro@openssl.org	lib/arm64-v8a/libAwebviewbytedance.so
asselfiescanfragment@f36d.onmanualca checkoutprocess@fad.presentpim checkouthomekt@de1b.checkoutho 4camerapreview@5543.initcamera 0detailviewmodel@e36a.onclickpre ailablemethodspagekt@df6.availablen billhomeviewmodel@7c13.load paymentconfig@4a3b.initstarli reetfillercontroller@1e6f.onvaluecha veritasidvcameraview@3351.downgradem baseviewmodel@a8bd.loadcashie addressviewmodel@1396.synchroniz mentprepareviewmodel@97b5.getrepayme pimanagementkt@49.handlenavi billhomeviewmodel@7c13.loadcustom asselfiescanfragment@f36d.showcamera baseviewmodel@a8bd.initnoncet payment@a405.presentpim echeckoutviewmodel@de26.startpolli icontextcard@cb18.onbindview	

tainerassemviewmodel@65ad.createSubc EMAIL Model@e244.deleteStor piviewmodel@e244.storepayme	FILE
puxtoastkt@4a5b.puxtoast andingcontainerassem@e692.presentbut asselfiescanfragment@f36d.oncapturer ritasidvscanfragment@17f6.onviewcrea ritasidvscanfragment@17f6.doupdateSe dcamerapreview@5543.createcame payresultpagekt@ebf8.payresultp ogressassemviewmodel@10f5.getinstitu +repaymentviewmodel@2076.presentche reementsignviewmodel@4cbe.signagreem animationcontroller@2ab.dismiss 0landingassemvm@e5ad.createcred +baseviewmodel@a8bd.showgenera cardnumbercontroller@eba5.debounce checkoutviewmodel@de26.closecheck 2repaymentviewmodel@daf6.onpreparer asselfiescanfragment@f36d.doliveness example@email.com tainerassemviewmodel@65ad.signagreem detailviewmodel@e36a.onloadmore kycnfcscanningassem@2bbe.showreadyt itasselfiecameraview@347f.downgradem ritasidvscanfragment@17f6.onresume rationdatecontroller@a578.validatewi puxdialogkt@8092.dialogcont piviewmodel@e244.checkbinds tainerassemviewmodel@65ad.requestreg checkoutbark@7ee0.checkoutba noncecontainer@4140.getnonce 9checkoutprocess@fad.presentpim pimanagementkt@49.pimanageme andingcontainerassem@e692.initcontai addressviewmodel@1396.preparedat baseviewmodel@a8bd.isnetworka formskt@ec82.forms +checkoutcontainerkt@7c59.handlenavi piviewmodel@e244.getpibasic ritasidvscanfragment@17f6.downgrader +checkoutactivity@41a1.showcompos stagreementviewmodel@417d.getagreeme tainerassemviewmodel@65ad.recordcl ritasidvwelcomesassem@6b26.sessiontim bnplcommonpopup@7d4b.sendreques postartnfcscanmethod@d0e8.handle nfcscanningviewmodel@a548.startnfcsc repaymentviewmodel@2076.getnonce ritasidvscanfragment@17f6.onmanualca checkoutviewmodel@de26.pay -phonenumberkt@d397.oncountryc ndwalletlandingassem@7d5c.handlecl ycnfcscanningassemv2@7418.showreadyt 2bindcontainerkt@813f.showbindpa piviewmodel@e244.saveasprim 4detailviewmodel@e36a.onclickpre	

-checkoutactivity@41a1.showcompos EMAIL	FILE
cscanningviewmodelv2@eb11.handle checkouthomekt@de1b.imespaceho -camerapreview@5543.initcamera piviewmodel@e244.redirectha ndpaymentmethodnavkt@cf39.navigation tainerassemviewmodel@65ad.createcred ogressassemviewmodel@10f5.getroutein .bnplentryviewmodel@c16.getstepcod apiservice@bd9b.getstarlin tuxdialogkt@608c.tuxdialogc reetfillercontroller@1e6f.debounce ogressassemviewmodel@10f5.createsubc addressviewmodel@1396.ondone reetfillercontroller@1e6f.onfocuscha 3clientaicameraview@ec4c.processfra buttoncard@7e9c.handledata -checkoutviewmodel@de26.storepayme creaselimitviewmodel@9cba.submit bottomsheetskt@3e26.bottomshee ignagreementfragment@3451.onviewcrea animationcontroller@2ab.show selectpikt@1283.selectpi ritasidvsanfragment@17f6.sessiontim +checkoutviewmodel@de26.storepayme selectassemblepikt@73eb.selectasse repaymentviewmodel@daf6.loopforres asselfiescanfragment@f36d.doimageupl bizdataholder@86cc.getconfigu repaymentviewmodel@daf6.load repaymentviewmodel@2076.initpaymen ritasidvsanfragment@17f6.showcamera 1addressviewmodel@1396.synchroniz checkoutprocess@fad.getnonce fcscanningfragmentv2@4475.onviewcrea 4checkoutviewmodel@de26.startpolli checkoutviewmodel@de26.initmethod nfcscanningviewmodel@a548.handlecan baseviewmodel@a8bd.requeststa checkoutviewmodel@de26.getpayment piviewmodel@e244.launchbind ogressassemviewmodel@10f5.createmain pimanagementkt@49.cardlist cscanningviewmodelv2@eb11.startnfcsc piviewmodel@e244.getpimanag retrykt@6b9c.retry landingassemvm@e5ad.signagreem asselfiescanfragment@f36d.downgrader piviewmodel@e244.havestored checkoutviewmodel@de26.storepayme +formskt@ec82.forms postalcodecontroller@cdbb.synchroniz ritasidvsanfragment@17f6.oncapturer cnfcscanningactivity@ca29.setupbotto configuration@2711.getidempot .camerapreview@5543.initcamera	lib/armeabi-v7a/libdex_df_pipo_bnpl.so

-checkoutcontainerkt@7c59.handlenavi EMAILanningassemv2@7418.onviewcrea outhackinterceptorkt@9a2b.showclosed	FILE
1billhomeviewmodel@7c13.onpreparer ogressassemviewmodel@10f5.decideuser reetfillercontroller@1e6f.onclick payment@a405.presentche -addressviewmodel@1396.initdatafo statementsviewmodel@5867.onrefresh phonenumberkt@d397.oncountryc ndpaymentmethodnavkt@cf39.bindpaymen .bindcontainerkt@813f.showbottom .repaymentviewmodel@daf6.onpreparer animationcontroller@2ab.startanima fieldcontroller@7de7.validatewi 1clintaicameraview@ec4c.handlecapt cardnumbercontroller@eba5.onvaluecha pipoclientaimanager@79c1.prefetch addressviewmodel@1396.fetchdata repaymentviewmodel@2076.presentche clintaicameraview@ec4c.handlecapt fcscanningfragmentv2@4475.onnewisode livenesscheckhelper@23d.livenessch fcscanningfragmentv2@4475.oncreatevi ritasidvscanfragment@17f6.doimageupl repaymentassem@956f.scrolltobo tuxtoastkt@aeed.tuxtoast -billhomeviewmodel@7c13.onpreparer asselfiescanfragment@f36d.doupdatese addressviewmodel@1396.datainitia asselfiescanfragment@f36d.permission asselfiescanfragment@f36d.releaseres creaselimitviewmodel@9cba.presubmit piviewmodel@e244.closebinds ritasidvscanfragment@17f6.releaseres asselfiescanfragment@f36d.onviewcrea bnplentryviewmodel@c16.getstepcod landingassemvm@e5ad.requestreg rogressanimationview@4d84.initstepvi piviewmodel@e244.dealbindre ritasidvscanfragment@17f6.permission baseviewmodel@a8bd.getnoncewi tainerassemviewmodel@65ad.decideuser +baseviewmodel@a8bd.shownetwor piviewmodel@e244.cancelaspr piviewmodel@e244.initmethod cardnumberkt@6a2f.cardnumber bnplcommonpopup@7d4b.onapierror ogressassemviewmodel@10f5.signagreem	
clintaicameraview@ec4c.ongetnewim nmolifecycleobserver@fb35.onstatecha paypalSdkprocess@6938.clear +httpClient@bac3.notifysucc pallifecycleobserver@fa45.onstatecha httpClient@bac3.notifyerro httpClient@bac3.schedulere	lib/armeabi-v7a/libdex_df_pipo_external_payments.so

EMAIL	FILE
ffmpeg-devel@ffmpeg.org	lib/armeabi-v7a/libttvesdk_plugin.so
.iililili@7cb8.onsurfacet iililili@5021.run ilililii@e761.run linkccdcocrviewmodel@5bad.restarttim ilililil@7742.run ardoverlaycontroller@1499.iililili innerreticleview@c576.ilililii iililil@2f90.iililil ilililii@f61d.run ilililil@c351.run tooltipmanager@42cd.showtoolti ilililil@9dcb.run ardoverlaycontroller@1499.iilililii ilililil@3a5c.ilililil iililil@c4a4.run ilililii@aef1.run ilililil@3a5c.ilililil innerreticleview@c576.ilililil ilililii@66.ilililil ilililii@66.ilililil iililil@41e6.ilililil ilililil@3b67.run ilililii@ad44.run iililil@2f90.ilililil blinkccdcocractivity@a0d7.initview .iilililil@2341.onsurfacet progressview@d1bc.ilililil ilililil@3a5c.ilililil ilililil@3a5c.ilililil ilililil@8193.onshakings ilililii@abc1.run ilililil@54ad.run ilililil@7cb8.onsurfacet linkccdcocrviewmodel@5bad.frontsides ilililil@3a5c.ilililii ilililil@38b7.run ilililil@3a5c.dispose snackbarmanager@7b73.ilililil iilililii@48d.run nllililil@7584.com_microb tooltipmanager@42cd.hidetoolti iilililii@419e.ilililil rdreticleoverlayview@d3ea.createlayo ilililil@5a54.onpicturet ilililil@96bf.run nllililil@396d.com_microb iilililil@a68a.surfacecha iilililii@c56c.run snackbarmanager@7b73.ilililii ilililil@a728.onimageava ilililil@3a5c.iilililil	lib/armeabi-v7a/libdex_df_ccdc_impl_ocr.so

rdreticleoverlayview@d3ea.changestat EMAIL:caaf.run 3@1fe5.run	FILE
ilililil@2f90.lliilili ardoverlaycontroller@1499.lliililil Odebugviewhandler@3d30.initialize lliililil@7584.run lliililil@904d.run rdreticleoverlayview@d3ea.lliililil lliililil@caaf.run lliililil@9cd3.run iilililil@d9d.run iilililil@4550.run progressview@d1bc.iilililili 3@a98.run iilililil@4526.run iilililil@2341.onsurfacet iilililil@189d.run lliililil@396d.run lliililil@396d.iilililili lliililil@cc66.run iilililil@2f90.dispose lliililil@9821.run	
styleselectcomponent@eed.getselects ttliquefyviewmodelv2@3195.applyclear secondobjectfragment@25bf.initdata hsladjustfragment@cc19.cancelvalu opickpanelguidescene@80d3.initviews viourpreviewfragment@b187.initaction sthitsviewcontroller@3138.bindobserv ailfragmentviewmodel@c61.downloadpi bverticalmusicview@a7b8.buildcolle jarvis@b146.init seteditpagecomponent@a788.onCreate keffecteditorcontext@5cb5.ttdoafere ostdeleteserviceimpl@ec46.delete enscreenfuncprovider@4094.switchreal ganviewmodel@586e.removeface bbottombarcontroller@48f3.setupleftb ntiputilskt@10d0.dowhenloca 0eventtrackingextkt@d694.sendeventt tiktokgifrepository@f767.trendgifs facestretchfragment@cdc6.initview eprogresscoordinator@b04d.syncreleas creatorlayerfragment@d93c.calculatea ttpromotionviewmodel@b3db.selectprom 0prefabeditviewmodel@58ec.compresssh .amestickertab@f726.preloadmat cefusionfuncprovider@d4bb.addfusion +nowlikeviewmodel@da60.handlenowp 6filteredassetpool@8672.getassetsw seteditpagecomponent@a788.launchscen creendataresprovider@2dc8.preloadgre archloadingcomponent@a395.observewor amecorepresenterimpl@6f97.launchawai amedbinitwavetask@901c.run	

ffectimgcropfragment@6e89.startloadi EMAIL utocutoutrepo@8606.chaincallb faceinsetresflowimpl@5b2e.obtainaddf	FILE
makeupviewmodel@3113.initfeatur amakeuppagefragment@9516.observedat makeupviewmodel@3113.updateload eampipelineexecution@1e2.processnod mstickerpagefragment@e4f5.initobserv canvasactionlistener@ff32.ondoublecl elactionreportheper@7a1f.onoperatio atorofficialrepoimpl@eb36.reqofficia ckcliprailpanelscene@f69d.loadingrot ecutoutpanelfragment@2aad.gotosticke acestretchrepository@575f.apply styleselectcomponent@eeed.downloadst sealbumpickmonitor@9b40.changeload alicondirlistadapter@f848.onbindview ecutoutpanelfragment@2aad.gotomedi canvasactionlistener@ff32.singletap modelselectcomponent@ef2b.downloadmo eaimattingresfetcher@5768.loadmattin enstyleresultmanager@35df.showloadin aimetabviewmodel@6323.loginload inpreviewtitlewidget@434a.updaterend fbaseiconlistadapter@8bdc.onbindview iganpanelfragment@9fd9.bindseekba stickerguidefragment@1ac2.onlytipsca localconfigsfragment@720d.submitlist al@737.run imestylepreviewscene@1044.handlesucc editpreviewviewmodel@f9a1.fetchuserp dganpanelfragment@9fd9.initview stickerresflowimpl@8b68.preloadadd amemusictab@d8c.showmusicn tgreenscreenhelperv1@b92c.gengreensc 3ganviewmodel@586e.onfacefusi cutoutcanvasfragment@a1bc.initobserv creendataresprovider@2dc8.downloadgr ti2iloadcomponent@5889.msgcenterl customizeviewmodelv2@83ed.performgen carouselplayerview@e8e0.applycente prefabviewmodel@5840.fetchlokip taskrepositoryimpl@c0e3.getaigtas ckerguideserviceimpl@2357.startstick gifsfragment@3c5.addgifstic ckpanelguidefragment@b009.preloadalp eampipelineexecution@1e2.emit drafthandler@f1f0.showsavadr inpreviewmusicwidget@e63e.onconfigur seteditpagecomponent@a788.prehandlel ganpanelfragment@9fd9.initdata epreupgradedrafttask@a3b4.preupgrade -amecutouttab@330b.gotomedi -amenewflowtexttab@32b6.handleedit ltiponboardingv3node@2b24.launchpane slistpanelcontroller@51da.handleitem texteditpagescreenkt@f833.textinputi	

prefabviewmodel@5840.preloadaddw EMAIL model@472a.loadmoregi aiselfcarouselkt@ac9a.autoscroll	FILE
verseclusterstrategy@91c8.dogenerate perfintervalmonitor@6311.run wcaptioneditfragment@3c1b.initeditvi 0facefusionrepo@41cc.loadfacefu amecovereditfragment@1c20.initview cutoutbottomfragment@2b85.observevie ttlquefyviewmodelv2@3195.initfollow objectcontainer@a25.build hprefabeditfragment@56ec.observecan componentviewmodelv2@695f.performsuc bytebenchv2@5dc8.reportresu stprefabpagefragment@a912.getlayerdi drafhandler@f1f0.handleconf 2aimetrystylemanager@6ec4.shouldshow itionstatustextassem@b2f.startdotup 1ganviewmodel@586e.onmediasel edgeflowmanager@9681.initialize aimetabviewmodel@6323.loadmore tickersearchfragment@bb76.addorrepla ewpager2heighthelper@f55d.pagechange tiktokgifrepository@f767.searchgifs ltiponboardingv3node@2b24.registerpa imagecutoutviewmodel@497d.clearstep ameupgradedrafttask@e63f.run gtoolseditcontroller@c679.compressbi eatorstickerfragment@a9ce.observesea faceinsetresflowimpl@5b2e.obtainface imagecutoutviewmodel@497d.intercepts assetreverseproducer@54de.getcluster dataeventreceiverpro@8b02.ondataeven +ganviewmodel@586e.flushfacef otionrouterprocessor@713a.process scenemonitor@e338.stopintern ffectentranceservice@55a.isaifeatur facefusionrepo@41cc.changeefusi creatorlayerfragment@d676.initlisten ttlquifyfragmentv2@52bb.onattach packagefetchwavetask@bf55.run ramepreviewcomponent@482.startgener ganviewmodel@586e.createfeat 6makeupviewmodel@3113.selectfirs acefusionresprovider@cfcf.preload gfeaturefragment@9411.initaction perfintervalmonitor@6311.flush effectdraftcomponent@138b.savei2vdra editpreviewviewmodel@f9a1.updateaise autopicksession@14df.awaitnexts 6prefabpagefragment@feb3.observedat inpreviewtitlewidget@434a.setviewloc feaimenetworkapiimpl@b2d9.getaimerec 5autopicksession@14df.launchstra enscreenfuncprovider@4094.updategree ltiponboardingv3node@2b24.registerro ganviewmodel@586e.changeefusi	

iprefabpanelfragment@ff3c.initview EMAIL customizescene@55e6.successgen objecteffecthandler@657f.inneraddst	FILE
sictrimpanelfragment@bc06.initobserv deuploaduicomponent@4d62.oncreate nativescenemonitor@1ad6.stopintern 1ganviewmodel@586e.clearselec atorstickereditpanel@52bb.handlerreed facestretchviewmodel@bd65.changeface omptenhancecomponent@5992.translatep iprailpanelcomponent@65e4.onaiautocu feaimenetworkapiimpl@b2d9.getaigcquo componentviewmodelv2@695f.handlecllic aimelistrepo@d69d.getaimelis kprefabpagefragment@feb3.observedat ctcreatepipelineimpl@e2ca.onexportwh reupdateeventapiimpl@a3d.onfireeven 9aistyleresfetcher@6d7b.getstylera customdownloader@85b1.download +verticalmusicview@a7b8.getrecentm ttnewcreatorfragment@9077.delayloadi timewindowfilter@11c7.filter kloadingcontentscene@f88d.updateprog fectfeaturecomponent@168f.downloadre 6verticalmusicview@a7b8.getsearchm ortitlebarcontroller@3a4.registerli filteredassetpool@8672.getassets nowlikeviewmodel@da60.onclicklik ttnewcreatorfragment@9077.handleinfo eaimetabfragment@e8f3.checklogin videouploadcomponent@95e9.startuploa 8textstickerresflow@3f39.preloaddef ameimagecutouteditor@22c0.addaimatti archloadingcomponent@a395.showresult istadapterviewholder@1d11.bind viourcontentfragment@6376.compatoncl videouploadcomponent@95e9.pickvideo eocutoutplayfragment@c596.initview bytebenchv2@5dc8.loadtaskto ctcreatepipelineimpl@e2ca.logsavedra uefyprefabrepository@5cd4.getorcreat ctimgcreatorfragment@fc30.initlisten imestylepreviewscene@1044.checklogin .aimetabfragment@e8f3.setviewmod owdownloadbottomview@abfa.handler thememarqueeetextview@dc03.applymarqu editloadingcomponent@f330.regenerate otoseditpagefragment@8917.restoresel -aimetabfragment@e8f3.scrolltoto ttliqueryviewmodelv2@3195.startfaces 2collectmusicmanager@f40.loadcollec atorofficialrepoimpl@eb36.preloadran feaimenetworkapiimpl@b2d9.postaistyl makeupviewmodel@3113.launhaigc dialogcontentbuilder@336e.createdial lbumpickeralgolader@82cb.getdetectm pickloadingcomponent@6ba2.submitnewt	

istadapterviewerholder@50d.bind EMAILclusterproducer@ba79.producecan hannerviewcontroller@20d0.initobserv	FILE
1animationviewmodel@e3f4.onbehaviou cutoutcanvasfragment@a1bc.showtipifn longloadingpredictor@973f.predict runtimeevent@d9a0.record autopicksession@14df.start previewpagecomponent@e7db.onconfirmc aimetabviewmodel@6323.aihubclick facestretchviewmodel@bd65.setupforex companion@98eb.mergemodel nowlikeviewmodel@da60.handlenowp ganviewmodel@586e.onmediasel selector@9dcc.select bytebenchv2@5dc8.checktestr reparestagecomponent@58.repreparep objectpreparewavetask@36f5.run slistpanelcontroller@51da.back chestrationcomponent@b9ce.repick fyoriginalrepository@defb.followface .dynamichookhelper@e04c.switchtoma rcollectionlistassem@fdbd.onbind slistpanelcontroller@51da.oninit prefabviewmodel@5840.emiteditpr phaseitemholder@dd98.crossfadet amelaunchtask@d1f1.runasync jankframecollector@560d.stop ttnewcreatorfragment@9077.onviewcrea imagecutoutviewmodel@497d.triggeraut eupexchangeviewmodel@7f33.updatemake customdownloader@5e04.download topickpanelcomponent@d649.savedrafta eaimattingresfetcher@5768.preloadmat ttiponboardingv3node@13d5.tryshowani iprailpanelcomponent@65e4.sam makeupviewmodel@3113.clearcateg ttlquefyviewmodelv2@3195.selectloca inspectoretutils@602c.reportgree ttlquefyviewmodelv2@3195.cancel otiontemplateadapter@7abb.onbindview 9amedebugfragment@39de.doinit languageodeltask@fc90.forward -prefabeditviewmodel@58ec.saveselect picklotteddownloader@294b.downloadto otoseditpagefragment@8917.updatealbu fectfeaturecomponent@168f.preloadloa facestretchviewmodel@bd65.refreshkey componentviewmodelv2@695f.handlegene ctcreatepipelineimpl@e2ca.resolvecro baseclusterstrategy@860d.cvscan editpreviewviewmodel@f9a1.observerre prefabviewmodel@5840.clearselec gifsviweviewmodel@472a.downloadgi fectfeaturecomponent@168f.applyprefa enscreenfuncprovider@4094.changetrac bfourpicturefragment@febe.mobdeletp	

stickerguidefragment@1ac2.registerob EMAIL lecthandler@50af.autochange lbummultiselectlogi@8114.bindholder	FILE
+prefabviewmodel@5840.loadeffect rtoofficialrepository@5713.createoffi imgautogeniconhelper@4893.applyeffec usionganpagefragment@5dee.initview .alphavideoscene@9f94.animlisten photostorehelper@25da.getphotodi +autopickpanelscene@9db7.adjustcove eatorstickerfragment@a9ce.parseselec amemodelpreloadtask@f983.modelprelo ckerfacefusionloader@46fb.load ltiponboardingv3node@2b24.tryshowani voicesearchviewmodel@8ed6.startdotup tylepreviewviewmodel@9526.getpagesta qpreviewmodeladapter@a893.onbindview textinittaskwavetask@c15a.run 0ganviewmodel@586e.applyfacef enstyleresultmanager@35df.openresult thememarqueetextview@dc03.ontextchan inpreviewtitlewidget@434a.onconfigur screenthumbgenerator@4b96.tryshotscr atorstickereditpanel@52bb.playmusicw romotionbottomdrawer@6faa.initview ecutoutpanelfragment@2aad.onactivity ttpreviewmodehandler@bae4.initprevie rsecondobjectadapter@a42d.onbindview normalhandlerimpl@927f.update fectpreviewviewmodel@ace0.regenerate 0ttlquifyfragmentv2@52bb.mobcategor stickerselecthandler@50af.selectobje ormigrateserviceimpl@95ca.awaitchang selectpanelcomponent@4222.fetchmodel 7nowsharebottomassem@8f07.sharebutto elfawemecachemanager@5c53.deletecach bprefabpanelfragment@ff3c.bindseekba ramepreviewcomponent@482.oncreate hsladjustfragment@cc19.initview localconfigsfragment@720d.observemat uefyprefabrepository@5cd4.eecreatefe ickeroperatefragment@36ad.initobserv autopickpanelscene@9db7.scheduleco fyoriginalrepository@defb.load imationpanelfragment@9f44.initview amevelaunchtask@f810.oncreate ckpanelguidefragment@b009.updatescro actionviewmodel@3d37.filternots ameralaunchcomponent@a0cb.awaitpages viewlazyinittask@9248.run 1baseclusterstrategy@860d.dogenerate gridadapter@5c48.onbindview 4consumercoordinator@9d43.consumeava ickerrouterprocessor@1f13.process xtstickerinputlayout@542c.showinputl ktltquifyfragmentv2@52bb.initobserv amecorepresenterimpl@6f97.runvelaunc	

gpicturecropfragment@16c2.getstyleta EMAIL Helfragment@9fd9.initview cialiconlistfragment@1f25.startobser	FILE
mainpackagefetchtask@1fcd.run picklotteddownloader@294b.downloadlo eeklyclusterstrategy@9057.dogenerate archloadingcomponent@a395.submitaigc ourcedownloadnewimpl@4e8a.startdownl ickrootslotcomponent@4cb3.showautopi stprefabpagefragment@a912.applyadjus modelmanager@75cd.downloadmo ameprojectcreatetask@5356.run customizeviewmodel@8957.performapp tv2vreeditgroupscene@ac19.initobserv canvasactionlistener@ff32.oncornerdr onboardingv2cardview@b442.initpopove 2customizeviewmodel@8957.reportcl chestrationscomponent@b9ce.startautop meonboardingwavetask@78c8.run ganviewmodel@586e.fetchganli amevesdkinittask@222.run .draftupgradehelper@28d6.updatedraf mainpackagefetchtask@1fcd.needforceu normalhandlerimpl@927f.onscale editpreviewviewmodel@f9a1.discardcur nowcachedelegate@6dbd.ondeleteno ompatibilitytuxsheet@8c3.tasksimage 1facestretchfragment@cdc6.onconfigur lbumpickeruidelegate@b7b1.init ailfragmentviewmodel@c61.oncustomiz gcreatorcamerahelper@1908.opencamera componentpreparer@b449.run facestretchfragment@cdc6.initobserv +makeupviewmodel@3113.loadeffect 2stickerresflowimpl@8b68.obtainaddf mfacestretchfragment@cdc6.initobserv ontouchdraghandler@960f.ontouch 5prefabeditviewmodel@58ec.notifycont slistpanelcontroller@51da.handlechan omptenhancecomponent@5992.innerreque meprojectpreparer@6513.processdra ttpromotionfragment@f369.initview animationviewmodel@e3f4.loadeffect calendarmonthview@efb3.enableagai agifsfragment@3c5.initview autopickpanelscene@9db7.tryexitloa odelpictureviewmodel@fa9c.loadmodell ttnewcreatorfragment@9077.mpreviewti ticersearchfragment@bb76.replacegip makeupviewmodel@3113.selectedai fyoriginalrepository@defb.waiteffect tuspublishedrepoimpl@cbec.save2disk lbottombarcontroller@1f1b.setupright voicerearchhelper@9a5c.performvoi 0draftupdater@ff1a.updatedraf ultnavigationhandler@e1fd.navigateto ttnewcreatorfragment@9077.onconfigur	

onboardingv2fragment@d2c5.setdata EMAILlionviewmodel@e3f4.clearselec imenewcustomizescene@55e6.associated	FILE
ttliuefyviewmodelv2@3195.selectpref facestretchviewmodel@bd65.changeprev amestickertab@f726.handlelic bfourpicturefragment@febe.gosinglevi videocutoutviewmodel@ffde.removeback videocutoutviewmodel@ffde.updateprog autopickpanelscene@9db7.onshow previewpagecomponent@e7db.savedraft enscreenfuncprovider@4094.portraitcu +objecteffecthandler@657f.scopedadds econfigpagecomponent@842b.fetchstyle camebasetooltab@fb4c.attachcont qprefabeditfragment@56ec.observecon bytebenchv2@5dc8.start metricschecker@577.run aichoosemusicmanager@da6d.downloadmu ti2iloadcomponent@5889.commitgree ffectaudioscrollview@d2a5.startscrol editpreviewviewmodel@f9a1.loadmodelp aycomponentviewmodel@715b.performpol ttnewcreatorfragment@9077.observedou bgifsfragment@3c5.observedat inpreviewtitlewidget@434a.calculatea fectdownloaderhelper@3320.localdownl 9collectmusicmanager@f40.loadmoreco ganviewmodel@586e.oncommitup 2aistyleresfetcher@6d7b.getstylera eatoralbumfragmentv2@90fe.initlisten refabsublistloadtask@dbe7.run .ganviewmodel@586e.createganv amecorepresenter@ee9a.prepareres bfourpicturefragment@febe.onviewcrea isdayclusterstrategy@81e2.scanyearcl imakeuppagefragment@9516.observedat secondobjnormalrepo@d5b7.fetchpanel amevideocutoutplayer@403b.setmatting -widgetlocationimpl@5c3c.recordpane statistichelper@8108.onevent nowmediacachemanager@3ec6.deletcach 1nowareamonitorassem@4391.sam gpicturecropfragment@16c2.initcropvi 6baseclusterstrategy@860d.loadfilter vererecordhelper@7eb6.initvereco texteditactivity@468a.update .ganviewmodel@586e.loadfacefu rtoofficialrepository@5713.onofficial ttliuefyviewmodelv2@3195.done drafthandler@f1f0.openpublis ffectimgcropfragment@6e89.initlisten lreeditpaneladapter@da98.bindselect otiondataresprovider@6cc3.fetchbanne gcreatorcamerahelper@1908.init languagemodeltask@fc90.preloadint uctcomponentwavetask@509e.run	

aimakeuprepo@5ae4.loadaimake EMAIL loadingcomponent@6ba2.observechi asrstreamtask@8422.createinit	FILE
facestretchviewmodel@bd65.changemirr ameupgradedrafttask@e63f.upgrade aganpanelfragment@9fd9.bindseekba omotionbanneradapter@6b1c.onbindview kganviewmodel@586e.onfacefusi delivery@5dd5.deliverloc drafthandler@f1f0.downloadic seteditpagecomponent@a788.downloadai -makeupviewmodel@3113.cancelgene reparestagecomponent@58.ensurestyl mganpanelfragment@9fd9.initphotop amecanvasadjustlogic@563a.adjustamec 7normalhandlerimpl@927f.updatecall secondobjectfetcher@49c2.fetchnorma recapclusterstrategy@674c.generateye uefyprefabrepository@5cd4.doneifiswo hganpanelfragment@9fd9.initobserv seteditpagecomponent@a788.waitmodeli amestickertab@f726.preloadsti gttpromotionfragment@f369.initview effectdraftcomponent@138b.openpublis topickserviceapiimpl@43d4.checkaiaut picklotteddownloader@294b.ensurelott editpreviewviewmodel@f9a1.tryagain ganpanelfragment@9fd9.onactivity stprefabpagefragment@a912.updateenab picklotteddownloader@294b.ensureedit oderationhandlerimpl@1de9.handle makeupresfetcher@9b27.getaimakeu archloadingcomponent@a395.starti2ilo amecorepresenterimpl@6f97.awaitretry recapclusterstrategy@674c.dogenerate localconfigsfragment@720d.handlerrecl gpicturecropfragment@16c2.stoploadin gpicturecropfragment@16c2.doonfinish baseclusterstrategy@860d.runpipelin feaimenetworkapiimpl@b2d9.postaimecr 5makeuppanelfragment@e4b6.calculatea videouploadcomponent@95e9.fetchststo fectmodelsselectscene@98b.initdata odelpicturereviewmodel@fa9c.select gifsviemodel@472a.searchgifs +taskrepositoryimpl@c0e3.fetchaigct stprefabpagefragment@a912.initdata tservicelistenerimpl@d51a.trytrigger idetaskdialogmanager@215d.showcompat kganpanelfragment@9fd9.initphotop aimetrystylemanager@6ec4.performapp selector@9dcc.ondownload cmakeuppagefragment@9516.observedat makeupviewmodel@3113.selectcolo tpreviewmodehandler@bae4.swaptomode draftupgradehelper@28d6.upgradedra hubmainviewmodel@a63a.getstylede	

itionstatustextassem@b2f.starttimer EMAILuprepo@5ae4.storetofil assetreverseproducer@54de.produceran	FILE
sttpanelhomefragment@8f3f.observecor imgautogeniconhelper@4893.genicon canvasactionlistener@ff32.onlongpres enscreenfuncprovider@4094.changeplac tretchpersistentimpl@595d.deleteloca ganviewmodel@586e.fetchpanel ideopreviewcomponent@f19c.getlastfra ctsettingspanelscene@878.initview aycomponentviewmodel@715b.loadprevie 7alphavideoscene@9f94.maybestart verticalmusicview@a7b8.buildcolle selectpanelcomponent@2b29.fetchmodel eautocutoutcomponent@4327.autocutout 3aimecreationmanager@e605.aimecreati deletemanager@c8e8.deleteaist 6gifsfragment@3c5.initview atorstickereditpanel@52bb.checkshowg customizeviewmodelv2@83ed.handlefree topickserviceapiimpl@43d4.getautopic 2filteredassetpool@8672.getassetsw imgautogeniconhelper@4893.prepareame draftupgradehelper@28d6.downloaddef ttnewcreatorfragment@9077.onsaveinst seteditpagecomponent@a788.gotoprevie userexpmapmanager@4632.onappexit seteditpagecomponent@a788.startprevi stickerfragmentextkt@8f12.initbottom drafhandler@f1f0.savedraft +amecutouttab@330b.gotocutout prefabeditfragment@56ec.onclose rcollectionlistassem@fdbd.onviewcrea attpanelhomefragment@8f3f.openpanelo 3autopicksession@14df.awaitnexts am@736.run 1autopicksession@14df.awaitnexts inpreviewtitlewidget@434a.pagestateo makeuppanelfragment@e4b6.initdata collectmusicmanager@f40.collectmus ieffectlokicomponent@e537.fetchaigcp archloadingcomponent@a395.getresulti userexpmapmanager@4632.onappenter imagecutoutviewmodel@497d.preview seteditpagecomponent@a788.preloadat atordraftserviceimpl@96ac.getdraftin .customizeviewmodel@8957.reportpage 3ganviewmodel@586e.oncommitup editpreviewviewmodel@f9a1.updateaime facestretchfragment@cdc6.exit imagecutoutviewmodel@497d.changebrus feaimenetworkapiimpl@b2d9.postaigcdi absonboardingv3node@83df.destroy ganviewmodel@586e.setseekbar oderationhandlerimpl@1de9.keepprafto bcarouselplayerview@e8e0.makevideos	

ttpromotionviewmodel@b3db.checkrespa MAHchrepository@39dc.apply topickpanelcomponent@d649.checktaskr	FILE
slistpanelcontroller@51da.setupbydef imestylepreviewscene@1044.handleload pickloadingcomponent@6ba2.onrunindra autopickpanelscene@9db7.initview ganviewmodel@586e.clearselec ttnewcreatorfragment@9077.initconge ormigrateserviceimpl@95ca.packdrafti prefabeditviewmodel@58ec.done reparestagecomponent@58.preparepro canalysiscomponent@8894.scanassets +globaleventhelper@930c.emitonboar atorstickereditpanel@52bb.handleswit pickloadingcomponent@6ba2.setupprogr acestretchrepository@39dc.handleaddn estretchresviewmodel@7ac.downloadfa ocaliconlistfragment@8061.initdirlis facestretchfragment@cdc6.onsavecllic makeupviewmodel@3113.updatecate nscreenpromotionimpl@aca7.needshowwe makeupviewmodel@3113.changeacti emanagerinitwavetask@d87b.run imestylepreviewscene@1044.navigateed tickerfeaturehandler@84e5.onsendadds 0aimeimagerepo@b921.downloadim gtoolseditcontroller@c679.saveimg -iamecorepresenter@89d0.runasyncun aycomponentviewmodel@715b.fetchtasks enscreenfuncprovider@4094.applygreen ameimagecutouteditor@22c0.export fyoriginalrepository@defb.apply atorstickereditpanel@52bb.opencutout qlambda@f73a.accept imagecutoutviewmodel@497d.export 8aimecreationmanager@e605.gotoeditpa +makeupviewmodel@3113.saveaimake 6ganviewmodel@586e.toggleface amevelaunttask@f810.dooncreate 5snowsharebottomassem@8f07.sharebutto ffectimgcropfragment@6e89.initcropvi pickloadingcomponent@6ba2.reportsave kmakeuppagefragment@9516.observedit sprefabeditfragment@56ec.observecon baseautocutoutnode@483c.process feaimenetworkapiimpl@b2d9.getaimedis 1facefusionrepo@41cc.changeitem normalhandlerimpl@927f.onrotate 0consumercoordinator@9d43.hasavailab prefabviewmodel@5840.loadeffect perintervalmonitor@6311.flushpart facestretchfragment@cdc6.onbackcllic verseclusterstrategy@818a.processnex templateapplynewflow@e669.applytempl bfourpicturefragment@febe.quotacheck uefyprefabrepository@5cd4.apply	

albumpickerrepo@7798.fetchalbum EMAIL fragment@b23d.initdata prefabpanelfragment@ff3c.initdata 2draftupdater@ff1a.updatedraf delivery@5dd5.deliverbin reparestagecomponent@58.waitstylem nowglobalstateutilkt@c142.subscribe umakeuppagefragment@9516.launcheffe transcodenode@bb9a.onprocess voicesearchfragment@47ab.ondisplayw ttnewcreatorfragment@9077.playmusico delivery@5dd5.delivereve iontplviewController@1a31.bindobserv reparestagecomponent@58.setdatatof aimetabviewmodel@6323.updateaime faceinsetresflowimpl@5b2e.waitframeu 1prefabviewmodel@5840.loadeffect htnesschangeobserver@7ddd.onbrightne 7musictrimviewmodel@3254.getmusicwa effectaudiowaveview@f30c.setaudiowa +draftupgradehelper@28d6.prepareupg ttpreviewmodehandler@bae4.getorfetch atorofficialrepoimpl@eb36.handlerreqs modelselectimpl@5ce2.fetchfacem pickloadingcomponent@6ba2.ondiscard fyoriginalrepository@defb.createnewf p@w.a5 autopicksession@14df.awaitnextr 9makeuppagefragment@9516.observedat fusionofficialloader@efe7.onofficial ganviewmodel@586e.onfacefusi meprojectpreparetask@6513.getdraftin lmodepicturefragment@490e.initbottom gpicturecropfragment@16c2.downloadta meprojectpreparetask@6513.run 3aistyleresfetcher@6d7b.getmodelef +amenewflowtexttab@32b6.handleedit ackingpanelviewmodel@98d3.downloadan erdonemodeuidelegate@cc84.oninit edithitpanelfragment@5674.onfinishfr ramepreviewcomponent@6cce.oncreate sealbumpickermonitor@9b40.loadfinish ttnewcreatorfragment@9077.observefor 2bytebenchv2@5dc8.initcollec imagecutoutviewmodel@497d.downloadre imagecutoutviewmodel@497d.undo draftimpl@6e0f.cleancache pickloadingcomponent@6ba2.getorcreat pickloadingcomponent@6ba2.findprevio stickerframeimpl@91f8.hideallsho ewpager2heighthelper@f55d.updateheig ttliquifyfragmentv2@52bb.initview ffectingcropfragment@6e89.doonfinish tuspublishedrepoimpl@cbec.doload acefusionresprovider@cfcf.getresfrom gpicturecropfragment@16c2.startloadi projectmanager@dca6.createfeat	FILE
--	------

ewpager2heighthelper@f55d.attach Emaillnresprovider@cfcf.getfacefus recapclusterstrategy@674c.generatemo	FILE
ittliquifyfragmentv2@52bb.observewhe makeupviewmodel@3113.removeaima 3ganviewmodel@586e.savelocalf hubmainfragment@b23d.getmoredat cutoutnode@f12.onprocess ttnewcreatorfragment@9077.savedraft iprefabpagefragment@feb3.observedat 6ganviewmodel@586e.fetchpanel perfintervalmonitor@6311.markend stickerselecthandler@50af.replacesti amecutouttab@330b.onactivity amecanvasadjustlogic@563a.updateonbo aimakeuprepo@5ae4.checkandlo musicpanelcomponent@b870.showmusicp picklotteddownloader@294b.awaitdefer 3ganpagefragment@ccac.observedat makeupviewmodel@3113.cancelcate odelresourceprovider@c3f1.getfacemod creenrecordingfilter@43d1.filter seteditpagecomponent@a788.observecam drafhandler@f1f0.onmaineven ganviewmodel@586e.applyprefa eatorstickerfragment@a9ce.initdata reatorcamerafragment@db9c.initview .collectmusicmanager@f40.initcollec visionvisibility@2ff1.record templateapplynewflow@e669.updandsele iktokaigcserviceimpl@ca7b.submitwork reatoralbumtophintvm@c751.onclosecli gcreatorcamerahelper@1908.injectcomp customizeviewmodelv2@83ed.bubblechan mgcreatorv2viewmodel@7599.applyeffec ailfragmentviewmodel@c61.delstyle aimetabviewmodel@6323.getaimemod previewpagecomponent@e7db.onCreate prefabeditviewmodel@58ec.validatest seteditpagecomponent@a788.oncancelbt ckeroperateviewmodel@8eb0.selectfeat terpipelinecomponent@7672.applyl1fil plusbuttoncontroller@4766.waitfacest amenewflowtexttab@32b6.addsticker ti2iloadcomponent@5889.onCreate localconfigsfragment@720d.initview nlistlocalrepository@143f.request outbottomtabfragment@feef.downloadre -filteredassetpool@8672.getassets p@s.a5 7baseclusterstrategy@860d.runpipelin editpreviewviewmodel@f9a1.fetchaimem amebaseloadingtab@e052.injectretr ttliquifyfragmentv2@52bb.onviewcrea ailfragmentviewmodel@c61.onprofileb imgautogeniconhelper@4893.preparerem ittliquifyfragmentv2@52bb.initview	lib/armeabi-v7a/libdex_df_ship.so

asetemplateapplyflow@6e5e.fetchmodel EMAIL viewmodelv2@3195.followface fectfeaturecomponent@168f.createfeat	FILE
uploadstatuswavetask@8dac.run ttnewcreatorfragment@9077.observepag eatorstickerfragment@eb94.handlesele aimelauncherfragment@9de9.normalpage perfevent@a4de.record caliconlistviewmodel@4695.createrequ eatoralbumfragmentv2@90fe.setupicont cameraassetfilter@f334.filter tretchpersistentimpl@595d.updateloca stprefabpagefragment@a912.done makeupviewmodel@3113.selectasse componentviewmodelv2@695f.observewor pickloadingcomponent@6ba2.handletask pickloadingcomponent@6ba2.querydraft 0aimeservicesimpl@2ffe.getcurrent gtoolseditcontroller@c679.saveiminn aprefabpagefragment@feb3.observedat templateapplynewflow@e669.upgrade stickerguidefragment@1ac2.lottiecanc localconfigsfragment@720d.applyeffec atortexthomefragment@5114.addsticker eatorstickerfragment@eb94.addsticker 2hubmainfragment@b23d.itemclick ttliquefyviewmodelv2@3195.doapplycle amecorepresenterimpl@6f97.onactivity themeclusterproducer@30fc.producecan imenewcustomizescene@55e6.effecttemp ailfragmentviewmodel@c61.mobdeletep eampipelineexecution@1e2.initialize ttnewcreatorfragment@9077.initlayerl mgcreatorv2viewmodel@7599.commitgree aimakeuprepo@5ae4.remove statebundle@c896.emit makeupviewmodel@3113.checkfiles isdayclusterstrategy@81e2.dogenerate dprefabpanelfragment@ff3c.bindseekba seteditpagecomponent@a788.observevid facefusionrepo@41cc.getfusionm baseclusterstrategy@860d.requestthe componentviewmodelv2@695f.reportstar slistpanelcontroller@51da.changeauto +stickerframeimpl@91f8.changecorn normalhandlerimpl@927f.onmove lbottombarcontroller@1f1b.setupcente kageandscripfetcher@cb75.fetchmainp faceinsetresflowimpl@5b2e.preloadfac atordraftserviceimpl@96ac.packagedra producercoordinator@371.ensureprog aimecreationmanager@e605.aimecreati tservicelistenerimpl@d51a.triggernet eaimattingresfetcher@5768.downloadai aimetabviewmodel@6323.unloginloa liquefyimpl@9f1.refreshmai facestretchviewmodel@bd65.requestdat	

rchcontainerfragment@c389.onviewcrea EMAIL networkapiimpl@b2d9.postaigcge icelistenerproxyimpl@3459.addlistene	FILE
aimeinterview@b693.setbuttons amecorepresenterimpl@6f97.updateproj videocutoutviewmodel@ffde.showcompil 5autopicksession@14df.awaitnexts pickloadingcomponent@6ba2.submitorre 6reeditutils@c260.preloadgre makeupviewmodel@3113.executeame .hubmainfragment@b23d.itemclick bumsingleselectlogic@1ca8.bindholder asrstreamtask@8422.ensuremode ctcreatepipelineimpl@e2ca.writelabel prefabviewmodel@5840.initfeatur meprojectpreparetask@6513.preparev2 lttliquifyfragmentv2@52bb.initseekba aimemodelreporter@b81d.reportstar baseclusterstrategy@860d.timed baseclusterstrategy@860d.consumeacan creatorstylerepoimpl@eb15.clear ibilitydialoghandler@2de2.showcompat ktpromotionfragment@f369.initobserv archloadingcomponent@a395.commitgree 6consumercoordinator@9d43.triggernon bytebenchconnection@a5b1.onservicec reparestagecomponent@58.waitmodeli lprefabeditfragment@56ec.observeval ffectimgcropfragment@6e89.onapplyeff dgifsfragment@3c5.observadat .amerouter@3af6.handlerrou ttnewcreatorfragment@9077.createsubm imagecutoutviewmodel@497d.init alalbumpickermmonitor@fa41.loadercall omptenhancecomponent@5992.enhancepro reparestagecomponent@58.preparefea 4tttoolbarwidget@a9e.addtoolbar nowpostbasecellassem@351e.assembleui companion@98eb.checkandme delivery@5dd5.delivermem inpreviewmusicwidget@e63e.getdraftin ffectimgcropfragment@6e89.geticonbit atorstickereditpanel@52bb.featureupd jganpanelfragment@9fd9.initobserv customizeviewmodelv2@83ed.bubbleclie delivery@5dd5.delivermes tiktokgifrepository@f767.downloadgi 7prefabviewmodel@5840.loadeffect triggerviewmodel@22d9.load eampipelineexecution@1e2.processsyn amecorepresenter@ee9a.bindsurfac defaultfetcherimpl@a191.load creatorstylerepoimpl@eb15.createands creendataresprovider@2dc8.preloadpre ttpromotionviewmodel@b3db.fetchdata ti2illoadingcomponent@5889.shotscreen imationpanelfragment@9f44.initobserv	

makeuppresfetcher@9b27.fetchmakeu EMAIL efactoryimpl@3118.createstyl gpicturecropfragment@16c2.onapplyeff	FILE
reparestagecomponent@58.translatep 7collectmusicmanager@f40.initunlimi efabcategoryloadtask@8de0.run gslstpanelviewmodel@c975.changeauto asrstreamtask@8422.preloadint ormigrateserviceimpl@95ca.migratedra ttnewcreatorfragment@9077.initaimake styleselectcomponent@eed.recorddata longloadingpredictor@973f.countasset hsladjustfragment@cc19.recoverlas ectmediadetectorutil@1704.detectorim effectmediadetector@cd93.detectface facestretchviewmodel@bd65.setupforcr 9messagecarouselvew@c57a.schedulero -amecutouttab@330b.gotocutout imakeuppanelfragment@e4b6.initview animationviewmodel@e3f4.done amecutouttab@330b.getsticker .collectmusicmanager@f40.loadmoreco archloadingcomponent@a395.onsavedraf tgreenscreenhelperv1@b92c.genveframe 0hubmainfragment@b23d.itemclick ceinsetpanelfragment@3e93.initdata aimelauncherfragment@9de9.navigateto canvasactionlistener@ff32.onpointdra enstyleresultmanager@35df.postnaviga autopicksession@14df.repick +stickerframeimpl@91f8.showfacefo idereditpagefragment@c761.onviewcrea oubleclicklikelayout@fa95.doafterani econdobjectviewmodel@9b86.fetchpanel eatorlayerviewholder@b52a.onstatecha fganpagefragment@ccac.observedat picklotteddownloader@294b.ensurelong adjustpanelutiltextkt@cd4.createadju stickerpanelimpl@54a9.showsticke dailyclusterstrategy@ea07.dogenerate stylerepository@15e0.getstyle gprefabpanelfragment@ff3c.initdata opickpanelguidescene@80d3.changestat localconfigsfragment@720d.refreshdat +baseassethandler@7ec4.schedulefr ffectimgcropfragment@6e89.getstyleta perfintervalmonitor@6311.markbegin mttliquifyfragmentv2@52bb.initobserv 6ganpagefragment@ccac.observedat ailfragmentviewmodel@c61.quotacheck ganviewmodel@586e.initfeatur makeupviewmodel@3113.emitparams tickersearchfragment@bb76.addgiphyst amegreenscreentab@f75.applygreen amegreenscreentab@f75.handleabc ctcreatepipelineimpl@e2ca.ondraftore amelaunchtask@d1f1.await	

ttliuefyviewmodelv2@3195.gethandled EMAILchangeobserver@10a.onvolumech yfastclusterstrategy@ab24.dogenerate	FILE
effecteditoractivity@a2af.onCreate ffectimgcropfragment@6e89.stoploadin ideopreviewcomponent@f19c.onCreate lbumpickeralgoloader@82cb.load express4runner@e270.getparsefu imationpanelfragment@9f44.initdata prefabeditviewmodel@58ec.validateph onboardingv3fragment@a2a8.registerob jttliquifyfragmentv2@52bb.initseekba enstyleresultmanager@35df.generateon eeklyclusterstrategy@9057.processnex makeupviewmodel@3113.downloadre eprogresscoordinator@b04d.runrelease keffecteditorcontext@5cb5.ttdoafterr animationviewmodel@e3f4.onpagefixe eautocutoutcomponent@4327.registerob ameautocutoutrepo@8606.chaincallb 1makeupviewmodel@3113.loadeffect secondobjectfetcher@49c2.fetchpanel atorstickerviewmodel@4254.updatelast ourcedownloadnewimpl@4e8a.updatereso nowsharebottomassem@8f07.onhostpaus gtoolseditcontroller@c679.saveoffici aimakeuptophintvm@5ac4.onclosecli ganpanelfragment@9fd9.bindseekba 3phasestackview@ebdd.animatepha ckpanelguidefragment@b009.changestat -customizeviewmodel@8957.getfreecre lectionlistviewmodel@a262.onloadbefo stprefabpagefragment@a912.resetall hsladjustfragment@cc19.resetvalue 2textstickerresflow@3f39.obtainaddf jankframecollector@560d.start nimationpagefragment@b779.observedat amecorepresenterimpl@6f97.awaitproje progresssmoother@1224.startfilli bfourpicturefragment@febe.delstyle hsladjustfragment@cc19.applyadjus 0amecutouttab@330b.preloadfac categoryitemview@b2ec.updatedata ganviewmodel@586e.eecreatefe singledetailfragment@8081.showsaveto 6alphavideoscene@9f94.performsub gmakeuppanelfragment@e4b6.initdata behaviourimpl@96c1.showprevie enstyleresultmanager@35df.styledetai gmakeupviewmodel@3113.loadeffect imgautogeniconhelper@4893.loadrandom +filteredassetpool@8672.getassetsw faceinsetresflowimpl@5b2e.changeface ckedraftextraimpl@fabf.savefile tupublishedrepoimpl@cbec.fetchusers bbottombarcontroller@48f3.setupright customizeviewmodelv2@83ed.newcustomi	

faceinsetresflowimpl@5b2e.getlayerdi EMAIL arebottomassem@8f07.clearconta 8officialconutlskt@8545.loadoffici	FILE
creatorbaseviewmodel@6ca3.emitevent defaultfetcherimpl@a191.doload mestickercutoutfuckt@8cf2.addorrepla fganpanelfragment@9fd9.initview consumercoordinator@9d43.hasonlypre iprailpanelcomponent@65e4.savedrafta inglepicturefragment@9.onviewcrea gonboardingv3tipview@64f2.initview ifacestretchfragment@cdc6.initview 9prefabpagefragment@feb3.observedat 2ganviewmodel@586e.loadfacefu topickserviceapiimpl@43d4.trackuploa cprefabeditfragment@56ec.onviewcrea ttnewcreatorfragment@9077.startameco noweventregistry@2a90.fire acestretchrepository@39dc.applyeffec delivery@5dd5.deliversam ecutoutpanelfragment@2aad.getsticker fectfeaturecomponent@168f.replaceand stylerepository@15e0.usecache loadinggate@35b9.tryfire ntalviewshowctrlimpl@4f40.triggersho inpreviewtitlewidget@434a.reqandupda aimeintroview@b693.setupscrol makeuppanelfragment@e4b6.initview feaimenetworkapiimpl@b2d9.getstylede stprefabpagefragment@a912.resetallva atorstickereditpanel@52bb.reportinsp selectpanelcomponent@4222.sceneactio delivery@5dd5.delivercpu componentviewmodelv2@695f.openstyler amedbinittask@1716.run delivery@5dd5.dumpcpu 3ganviewmodel@586e.setfacefus +editormodelimpl@5d2e.selectandc prefabviewmodel@5840.eecreatefe stickerframeimpl@91f8.alwayshide wabsonboardingv3node@83df.dowhenloca reditpaneladapter@da98.bindselect mestickercutoutfuckt@8cf2.handlesele hubmainfragment@b23d.delaimemod ckcliprailpanelscene@f69d.onshow effectmodeuidelegate@240a.oninit eampipelineexecution@1e2.processasy taskexecutor@f5da.call imagecutoutviewmodel@497d.reverse2db makeupviewmodel@3113.selectpref ickrootslotcomponent@4cb3.warmupalph ameimagecutouteditor@22c0.initmattin amevideocutoutplayer@403b.prepareasn ramepreviewcomponent@482.launchuplo tpanelhomefragment@8f3f.openpanelo texteditpagefragment@ce45.onviewcrea duplicateinterceptor@cafa.intercept	

hsladjustfragment@cc19.getadjustf EMAILpresenterimpl@6f97.prepareres onboardingv2fragment@d2c5.updatard	FILE
gcreatoreffecthelper@7d21.loadrafte amecorepresenter@ee9a.updateproj kstickerpagefragment@e4f5.initobserv 2nowsharebottomassem@8f07.startshare hsubverecorderhelper@2fed.initsubver uabsonboardingv3node@83df.dowhenloca ttlquefyviewmodelv2@3195.mirror zemonitorserviceimpl@c952.calculatef verseclusterstrategy@818a.dogenerate ameimagecutouteditor@22c0.init acestretchrepository@39dc.handle repl gganpanelfragment@9fd9.bindseekba effecthintviewmodel@ee0c.load otoseditpagefragment@8917.onviewcrea jarvisuploader@bb4f.reportanr 0draftupgradehelper@28d6.getupdated seteditpagecomponent@a788.setdatatof cutoutbottomfragment@2b85.initprevie themeclusterproducer@ba79.getcluster atortexthomefragment@5114.ontextedit canvasactionlistener@ff32.onmove gaimetabfragment@e8f3.checklogin eimagecutoutactivity@e7b9.initobserv angmodeldownloadtask@7c68.downloadli canvasactionlistener@ff32.onrotation verticalmusicview@a7b8.loadingvie uttpanelhomefragment@8f3f.observecor fyoriginalrepository@defb.doneifiswo ttfeatureoperator@9edd.copy anelcomponentmanager@d39d.initcompon creendataresprovider@2dc8.getgreensc feaimenetworkapiimpl@b2d9.postaimest tservice listenerimpl@d51a.onafterdel ieffectlokicomponent@e537.fetchstyle ttlquefyviewmodelv2@3195.stateselec aimeservicesimpl@2ffe.trycustomi ttnewcreatorfragment@9077.selectobse sicrimpanelfragment@bc06.initview eampipelineexecution@1e2.complete editpreviewviewmodel@f9a1.observerst creendataresprovider@2dc8.preparegre inpreviewmusicwidget@e63e.checkshowm dailyclusterstrategy@ea07.processnex aimetabfragment@e8f3.setviewmod facefusionrepo@41cc.addfacefus imagecutoutviewmodel@497d.redo ceinsetpanelfragment@3e93.updateface secondobjcombinerepo@822a.fetchpanel companion@98eb.warmloadmo archloadingcomponent@a395.oncreate nscreenpromotionimpl@aca7.showwebshe ailfragmentviewmodel@c61.downloadac screenthumbgenerator@4b96.initrecord cefusionfuncprovider@d4bb.handlechan	

-draftupgradehelper@28d6.updatedraf EMAIL layerimpl@3b51.updatelaye freeditpaneladapter@da98.bindstater	FILE
mttpromotionfragment@f369.initobserv draftupgradehelper@28d6.fetcheffec fprefabeditfragment@56ec.observecan ntalviewshowctrlimpl@4f40.init -makeupviewmodel@3113.loadaimake icelistenerproxyimpl@3459.onevent 2alphavideoscene@9f94.runsubtitl facefusionrepo@41cc.removeface nowpostbasecellassem@351e.dispatchot eatorstickerfragment@eb94.calculatea templateapplynewflow@e669.handleappl ganviewmodel@586e.emiteditpr ctcreatepipelineimpl@e2ca.cropandsav imgautogeniconhelper@4893.preparecus -stickerresflowimpl@8b68.obtainstic greeditpaneladapter@da98.bindnormal stprefabpagefragment@a912.getadjustf eeffectenvlaunchtask@8b0e.run ngslstpanelfragment@20bf.initview gpicturecropfragment@16c2.initview recapclusterstrategy@674c.generateca customizeviewmodelv2@83ed.fetchaimes canvasactionlistener@ff32.ondown creendataresprovider@2dc8.getprefabb aimemoduleimpl@3a8c.createorfe ti2iloadcomponent@5889.onrecordfi eatorstickerfragment@a9ce.handleitem baseclusterstrategy@860d.initialize draftupdater@ff1a.updatedraf creatorviewmodel@f9f8.triggerlay amecorepresenterimpl@6f97.needrunfet dithitpanelviewmodel@a5bb.commitgree +aimetabviewmodel@6323.checkcusto ctonboardingfragment@7b49.initview topickpanelcomponent@d649.onaiautocu aimelauncherfragment@9de9.redirectst amecorepresenterimpl@6f97.upgradedra gcreatorcamerahelper@1908.takephoto seteditpagecomponent@a788.preloadi2i ourcedownloadnewimpl@4e8a.blockrules -behaviourimpl@96c1.notifycomm .featureoperator@e35d.adjustposi animationviewmodel@e3f4.applyprefa gifsfragment@3c5.initview animationviewmodel@e3f4.reeditanim 2baseclusterstrategy@860d.runpipelin gifsviewmodel@472a.loadtrendg ttemplatefragment@cd72.initbottom ae@73e.run ltiponboardingv3node@2b24.registerne gpicturecropfragment@16c2.geticonbit canvasactionlistener@ff32.onup longloadingpredictor@973f.querytotal metricsmonitor@15b5.updateconf	

componentviewmodelv2@695f.handlestyl EMAIL:refragment@cd72.initbottom 9verticalmusicview@a7b8.initrecomm	FILE
gcreatoreffecthelper@7d21.fetchdraft enstyleresultmanager@35df.downloadim tracingfilterchain@f11d.filterwith previewpagecomponent@e7db.onconfirml eratorstickerfragment@eb94.addorrepla aimakeuprepo@5ae4.addaimakeu musicpanelcomponent@b870.getmusicpa utopicklogfilewriter@b890.endsession ttlquefyviewmodelv2@3195.deleteloca verticalmusicview@a7b8.showsearch nanimseqshowprovider@6cdd.onseqshow nowsharebottomassem@8f07.onviewcrea amemodesettask@2ae.run ickeroperatefragment@36ad.onchange screenthumbgenerator@4b96.genthumb 0drafthandler@f1f0.openpublis 3producercoordinator@371.awaitchang scenemonitor@e338.flushinter facestretchfragment@cdc6.showbackdi amecorepresenterimpl@6f97.onviewcrea amerouter@3af6.addrouterp -textstickerresflow@3f39.obtainstic ganviewmodel@586e.savelocalf seteditpagecomponent@a788.posthandle 4objectitem@70a2.special imgautogeniconhelper@4893.preparecro makeupviewmodel@3113.preloadaddw 1ameautocutoutrepo@8606.chaincallb facestretchviewmodel@bd65.addorupdat 8ganviewmodel@586e.setfacefus eprefabeditfragment@56ec.onviewcrea kloadingcontentscene@f88d.go2editpag ataprovidercomponent@ba4b.loadmediaf enstyleresultmanager@35df.startgener filteredassetpool@8672.getorloads plusbuttoncontroller@4766.handlelic amecorepresenter@ee9a.onviewcrea inglepicturefragment@9.showsaveto eampipelineexecution@1e2.waitforall eselectpagecomponent@f889.fetchstyle iadectorrepository@c873.containfac npostgesturelistener@e05f.checkandha componentviewmodelv2@695f.handlesucc kamelaunchpanellogic@a41c.initseqlau aichoosemusicmanager@da6d.getaipanel attingresfetcherimpl@8fc8.preloadmat ideopreviewcomponent@f19c.choosemode imgautogeniconhelper@4893.prepareran ctcreatepipelineimpl@e2ca.cropiconan ganviewmodel@586e.applyfacef hganpagefragment@ccac.observedat ackingpanelviewmodel@98d3.changetrac 7messagecarouselview@c57a.clearstabl atorstickerviewmodel@4254.requeststi	

ttnewcreatorfragment@9077.observedit EMAIL sterstrategy@91c8.scanwindow ttingspanelcomponent@2acc.showsetin	FILE
slistpanelcontroller@51da.changeport 6officialiconutillskt@8545.loadoffici mestickercutoutfuckt@8cf2.addsticker wvertcalmusicview@a7b8.initsearch languagemodeltask@fc90.forwardsin fectfeaturecomponent@168f.expotteffe tttoolbarwidget@a9e.onconfigur 1drafthandler@f1f0.handleconf feaimenetworkapiimpl@b2d9.getaimelis prefabviewmodel@5840.cancelpref messagecarouselview@c57a.clearswitc ttttoolbarwidget@a9e.rendertool cefusionfuncprovider@d4bb.changetofu ttliquefyviewmodelv2@3195.loadfacest ameimagecutouteditor@22c0.onactionup pickerviewcontroller@a872.initobserv utopicklogfilewriter@b890.onlog ttdataeventreceiver@e70e.ondataeven chestrationscomponent@b9ce.executefix mecovereditviewmodel@c5c4.detectface prefabviewmodel@5840.applyprefa fectpreviewviewmodel@ace0.sendprevie editpreviewviewmodel@f9a1.buildstyle 0secondobjectfetcher@49c2.fetchcombi ttliquefyviewmodelv2@3195.togglepage tylepreviewviewmodel@9526.generatest goalbumpickermonitor@2ce0.loadercall ectimgcreatorveutills@fa0a.renderimag 6filteredassetpool@8672.getorloads ti2iloadcomponent@5889.getresulti 0collectmusicmanager@f40.updatecoll ganpagefragment@ccac.observedit elangdeviceexecution@ad3f.preloadres verticalmusicview@a7b8.showaidata nowpostutillskt@9e4e.roundandad -draftupgradehelper@28d6.refresheff aistylesfetcher@6d7b.getmodelef makeupresfetcher@9b27.getmakeupf ackingpanelviewmodel@98d3.exit ilamaterialsdkimpl@a5d8.downloadmo gslistpanelviewmodel@c975.fetchlist atorstickereditpanel@52bb.showgreens 2ameautocutoutrepo@8606.chaincallb edgeflowmanager@9681.sendtooutp filterchain@7194.filter promptinputcomponent@dac6.onreferenc tservicelisterimpl@d51a.savedeploy ailfragmentviewmodel@c61.onpostbutt mgiconeditcontroller@c62e.fetcheffec amakeuppagefragment@9516.showaimake prefabeditviewmodel@58ec.updatesubm retryimagelayout@8d71.enableagai modelfetcher@5c4a.fetchmodel tretchpersistentimpl@595d.getlocalfa	

reparestagecomponent@58.expORTEffe EMAIL presenterimpl@6f97.runupgrade asrstreamtask@8422.process	FILE
inglepicturefragment@9.downloadpi eautocutoutcomponent@4327.loadimg asrstreamtask@8422.initchanne 7makeupviewmodel@3113.loadeffect kttlquifyfragmentv2@52bb.observewhe -amegreenscreentab@f75.preparegre amecorepresenter@ee9a.onactivity vaptershowctrlimpl@8d09.bind amecorepresenterimpl@6f97.runapplyef modelselectcomponent@ef2b.notifysele makeupviewmodel@3113.selectcate bytebenchv2@5dc8.loadbytebe aimetabfragment@e8f3.onviewcrea carouselplayerview@e8e0.scheduletr fectcomponentmanager@3783.checkandad imagecutoutresloader@6fb5.init ommoncustomizeviewktt@aa97.customizee gcreatorcamerahelper@1908.onCreate atordraftserviceimpl@96ac.getProject tservicelisterimpl@d51a.fetchdepo iquefyv2pagefragment@4341.initobserv prefabpagefragment@feb3.observedat 0collectmusicmanager@f40.initcollec mecovereditviewmodel@c5c4.generateco retchdragchildlayout@bf04.setoverlap ffectentranceservice@55a.chechaifea tpreviewmodehandler@bae4.onmodechan aprefabpanelfragment@ff3c.initdata selector@9dcc.notifysele attingresfetcherimpl@8fc8.loadmattin mgcreatorcameratools@c0f6.registerli aimelauncherfragment@9de9.redirectmo creatorviewmodel@f9f8.resetstatu tretchpersistentimpl@595d.addlocalfa selectpanelcomponent@2b29.sceneactio ataprovidercomponent@ba4b.loadassets +amecutouttab@330b.gotomediad ataprovidercomponent@ba4b.loadaluma eshapepanelviewmodel@fe83.changeshap prefabeditviewmodel@58ec.initdata cprefabpagefragment@feb3.observedat edithitpanelfragment@5674.replaymusi inspectoretutis@602c.getplaceho iquefyv2pagefragment@4341.onautojump makeupviewmodel@3113.createfeat mecovereditviewmodel@c5c4.ontouchup tservicelisterimpl@d51a.isdraftlis makeupviewmodel@3113.clearselec kageandscriptfetcher@cb75.needforceu	

EMAIL	FILE
defaultadapter@8c6.async pitayahostdefault@b731.onapplogev 6coredefaultimpl@d2fa.registerap coredefaultimpl@d2fa.runnativet defaultadapter@8c6.asyncafter innerworkhandler@1f72.getherler 1@349b.com_byteda 0defaultadapter@8c6.processcol pitayahostdefault@b731.hostsetup ptysettingsutil@2f5f.updatesett clientaihttpclient@89c8.postinwork -nphstackreporter@c9f.reportalln defaulthttpclient@6245.post +coredefaultimpl@d2fa.releasenat 4coredefaultimpl@d2fa.removeappl tionlifecyclewatcher@4905.registerap 1@6830.call ttnehttpclientimpl@7567.get coredefaultimpl@d2fa.removemess defaultadapter@8c6.timer .coredefaultimpl@d2fa.registerme ttnehttpclientimpl@7567.post -pitayahostdefault@b731.oncustomap 6pitayapluginimpl@80c8.registerpi tionlifecyclewatcher@4905.onappstatu coredefaultimpl@d2fa.runtask	lib/armeabi-v7a/libdex_df_pitaya.so
g@9277.run d0@43b9.call gluetosdkincookie@1cce.setsyscook l0@3ee1.run p@9280.run o@929f.run j@929a.run u@9285.run k@927b.run b0@43f7.run owserpreinitexecutor@4d02.handlemess r@92a2.run j0@42ff.run y@92a9.call c0@3ff8.call m@929d.call n0@3ea3.call v0@418b.run q0@4226.call v@9286.run w0@416c.call m0@3ec2.call x0@414d.call g0@435c.run s@9283.run w@9287.call	

t0@3de9.run EMAIL chromium@d8d6.onmeasure c0@43d8.call	FILE
b0@4017.run t1@3de8.handlemess e1@4399.call k0@42e0.run h0@3f5d.run a@9271.call q@92a1.run p0@3e65.run i0@431e.call y0@3d4e.run b@9292.allow k0@3f00.run s0@41e8.call m0@42a2.run f1@437a.run i0@3f3e.run g1@3f7b.run i@9299.getusagefo t@92a4.run b@9292.clear o@927f.call g1@435b.run g0@3f7c.run d@9274.call n@927e.call e0@3fba.run w0@3d8c.run f0@437b.call n0@4283.call l@929c.call z@928a.run z0@3d2f.run c1@3ff7.run h1@433c.call i@9279.run x@9288.run h0@433d.run f0@3f9b.run z0@410f.call z@92aa.run a1@4035.call k@929b.run i@9299.deleteallid e@9275.run m@927d.call c@9273.call u0@41aa.run android-webview-dev@chromium.org j@927a.call v@92a6.run u0@3dca.call q@9281.call d1@3fd8.run o0@4264.call	lib/armeabi-v7a/libdex_df_ttwbview.so

q0@3e46.run EMAIL EMAIL s1@3e07.run	FILE
b@9272.run y@9289.run i1@3f3d.run t0@41c9.run p0@4245.call x@92a8.run b@9292.getallowed u@92a5.run s@92a3.run t@9284.run b1@4016.call e0@439a.call o0@3e84.call j0@3f1f.run b@9292.getorigins r0@3e27.call p@92a0.run a0@4036.run r0@4207.call l0@42c1.run s0@3e08.call l@927c.run w@92a7.call e1@3fb9.call v0@3dab.run a0@4416.run omiumfactoryprovider@38d1.initialize ebviewruntimeservice@6831.registerda b@9292.clearall x0@3d6d.call y0@412e.call h@9278.call d0@3fd9.run	
zhangke.finn@bytedance.com	lib/armeabi-v7a/libfast_engine.so
6bddlnasourcewrapper@10b1.setplayerl rtceventnotifier@2c05.onfirstvid zzc@c2ed.call dlnasourceimpl@1a94.resume chromecastsourceimpl@71b3.play 8bddlnasourcewrapper@10b1.setplayerl bytemediarecorder@e39e.init chromecastsourceimpl@71b3.add dramali nsdhelper@cdf3.startdisco stopbrowserrunnable@80f7.run rvicediskcachehelper@769c.checkservi zzbr@17e6.run castingmanager@f46d.startbrows castingplayerimpl@f321.addseeklis chromecastsourceimpl@71b3.updatedisc nsdhelper@cdf3.stopdiscov retryexecutor@3f26.onfail	

readerthread@d197.run EMAIL playmanager@89e6.ondramaid astingpanelcomponent@c8ae.onchange	FILE
castingmanager@f46d.emit rtceventnotifier@2c05.onvideoenc videorecordermanager@acb0.preparevid dlnasourceimpl@1a94.pause nsdclient@70a1.handlereso nsdserver@c708.stopsrver rtceventnotifier@2c05.onintofore rtceventnotifier@2c05.onconnect bytecastsourcimpl@9ea6.getsinkdev dlnasourceimpl@1a94.addvolume omecastsourcwrapper@3a80.setplayerl dlnasourceimpl@1a94.play smhandler@e866.handlemess .mirroringmanager@9956.delayendmi chromecastsourcimpl@71b3.playnextdr chromecastsourcimpl@71b3.resume castingmanager@f46d.initsdk zzbe@2161.run dlnasourceimpl@1a94.changereso astingpanelcomponent@c8ae.onparentvi startbrowserrunnable@cc6.run 3bytecastsourcimpl@9ea6.authbylice chromecastsourcimpl@71b3.addvolume tvcasting@552b.initialize dlnasourceimpl@1a94.setvolume chromecastsourcimpl@71b3.swapdevice e@84c7.oncast zzq@bce7.run nsdserver@c708.startserve chromecastsourcimpl@71b3.destroy nsdhelper@cdf3.handlefoun getvolumerunnable@90a7.run dlnasourceimpl@1a94.getdevicei servicelistpanelkt@6531.servicelis dlnasourceimpl@1a94.getmediain -castingmanager@f46d.initsdk chromecastsourcimpl@71b3.playpredra pauserunnable@b7d1.run chromecastsourcimpl@71b3.disconnect decodethread@c0e7.run rtceventnotifier@2c05.onpaused castingmanager@f46d.runonuihr chromecastsourcimpl@71b3.refreshrou zzba@2165.run audiopassiveplayer@bdac.callbackau ssdpsearchsocket@1033.run zzc@8fc7.call nsdhelper@cdf3.onnsdresol 9mirroringmonitor@94c.displaylis mirrorcontroller@933f.startmirro controlpoint@eae5.checkandad castadvertiser@44ac.run zzbp@17e4.run chromecastsourcimpl@71b3.connect	

rtceventnotifier@2c05.onrecvmeta EMAIL castsourceimpl@71b3.subvolume mirroringmonitor@94c.init	FILE
eractinfotvcastassem@7913.onviewcrea castssdpsearchsocket@ef9.run chromecastsourceimpl@71b3.setupnewap renderthread@49f0.run playercontroller@ab13.play writethread@1526.run astingservicemanager@3eb0.startbrows zzbq@45db.run advertiser@631e.run -bddlnasourcewrapper@10b1.getvolume chromecastsourceimpl@71b3.playdramai zsz@bce9.run renewssubscriber@a501.run chromecastsourceimpl@71b3.updatedemedi bytecastsource@596e.init zzr@8534.run zsz@8535.run controlpoint@eae5.search chromecastsourceimpl@71b3.setvolume bddlnasourcewrapper@10b1.send 5bddlnasourcewrapper@10b1.setplayerl zzg@bcdd.run dlnasourceimpl@1a94.send chromecastsourceimpl@71b3.seekto castssdpnotifysocket@ebb6.run astingpanelcomponent@c8ae.startplaya rtceventnotifier@2c05.onsinkstuc zzas@2172.run rtceventnotifier@2c05.onmonitore -networkutil@dfe1.checkandcr zzbo@17e3.run zzbn@17e2.run rvisediskcachehelper@769c.writecache dlnasourceimpl@1a94.getstatusi rtcengineimpl@2d44.playvideo setvolumerunnable@c0a9.run -voipvideorender@6561.notifyvide httpsocketrunnable@df35.run nsdclient@70a1.notifybrow zzbm@17e1.run zzt@8536.run castingutils@42a6.getawemeli laybackcontrollayout@5e8c.maybeshown videorecordermanager@acb0.pause 1bytecastsourceimpl@9ea6.initperfor searchresponsesocket@7471.run zzah@17bd.run videorecordermanager@acb0.stop httpserver@dd9f.run videorecordermanager@acb0.start zzu@8537.run rtceventnotifier@2c05.onstat rtceventnotifier@2c05.onintoback einfo listenerwrapper@18c9.delaysched	

chromeCastSourceImpl@71b3.init EMAIL: notifier@2c05.onlogmonit dlNasourceImpl@1a94.subvolume	FILE
stingPluginInstaller@8e02.oninstallp -rtceventnotifier@2c05.onconnects -byteCastSourceImpl@9ea6.connect networkManager@4f82.start zzbl@17e0.run zzd@c2ee.call transportHandler@d93c.handlemess zzav@1fbc.run concurrentsSubject@e489.notifyobse threadCore@9e70.run deviceManager@ae59.clearbrows aStingPanelComponent@c8ae.onconnect rtceventnotifier@2c05.oncastsucc zzl@8d1b.run mainHandler@148c.handlemess deviceManager@ae59.deviceadde rtceventnotifier@2c05.onaudioSet stopRunnable@46ac.run aStingPanelComponent@c8ae.startmirro rtceventnotifier@2c05.onkilled dlNasourceImpl@1a94.stop dlNasourceImpl@1a94.connect e@84c7.onStart videoRecorderManager@acb0.resume seekDelayRunnable@9f68.run ssdpNotifySocket@f51d.run zzar@2173.run omecastSourceWrapper@3a80.setbrowser 9bddlNasourceWrapper@10b1.setmessage byteCastSource@596e.startbrows rtceventnotifier@2c05.ondisconne zzq@75d2.run chromeCastSourceImpl@71b3.pause controlPoint@eae5.handledevi concurrentsSubject@e489.notifyexce dlNasourceImpl@1a94.changespee .byteCastSourceImpl@9ea6.setauthbyl dlNasourceImpl@1a94.checkandcr e@84c7.onrecvmeta playDramaIdListener@ec4c.onfail +dlNasourceImpl@1a94.getStatusa chromeCastSourceImpl@71b3.setrepeatm f@84c8.setvolume e@84c7.onconnect einfoListenerWrapper@18c9.onerror playRunnable@6bf9.run byteCastSource@596e.deinit +bddlNasourceWrapper@10b1.send rtceventnotifier@2c05.onerror chromeCastSourceImpl@71b3.cleardrama chromeCastSourceImpl@71b3.playdramal 0bddlNasourceWrapper@10b1.getvolume	
deviceManager@ae59.deviceremo eCardLinkButtonAssem@9885.onViewcrea	

ttdsptablayout@2a64.addtabview EMAIL lyverfragment@28f8.setupviewp foryoulistviewmodel@1ref.loaddata	FILE
edsongslstviewmodel@7b6e.loaddata 6dspauthtokenfetcher@f3a9.requestdsp n@t.jt ryoriginloader@22de.load n@t.j2 tabpageassem@e8f7.subscribev aunchstrategymanager@e163.requestlin mainpagedatamutation@42dd.operate baselyricsview@d7c.reset2star edspplaylistmutation@12cc.operate -addtomymusicmanager@f107.addsongtom addedsongslstassem@a434.onwindowfo azonmusicauthhandler@45cb.refreshama cacesstokenmutation@c4ec.operate tagpanelviewmodel@f282.gettagpane dspfpsreporther@7a.dspsubplay rddetaildatamutation@8893.operate nginelisteneradapter@cbe8.ontimeupda librarylistviewmodel@7bbd.loadsongs tdspplaylistmutation@d215.operate mediaplayer@e4b0.onattach ngtomusicappmutation@1f63.operate tificationcontroller@925b.mhandler dspauthtokenfetcher@f3a9.refreshacc ongcardlistviewmodel@3014.onprepared fanspotlightassem@70ab.initbottom -mdverticalviewpager@8f2e.mendscroll cacesstokenmutation@b5ae.operate ddtomusicdspauthutil@c894.selectdsp 6dspauthtokenfetcher@f3a9.requestref ddtomusicdspauthutil@c894.updateddsp ouoriginloader@bec7.load sicsdpqueuelstassem@3dab.onviewcrea -mymusicsongassem@bd6a.bindexposu +multisongcardassem@64e2.onviewcrea adspfpsreporther@7a.forcedspu queueloadplugin@b85e.loadmore tyoauthmusicreceiver@1868.oncreate baseplayerviewmodel@37a1.loadmore otlightdetailsharevm@1691.onrefresh tailhitlistviewmodel@a699.onrefresh sptackexpiredplugin@2375.showsubscr ddtomusicdspauthutil@c894.addsongtom ixoriginloader@232e.load icdspplayerviewmodel@83f0.checkswipe journeysourceloader@5df4.load journeysourceloader@5df4.loadmore addtodspviewmodel@9231.reportadds dspitemreusedassem@b7ba.onviewcrea lightsharedviewmodel@fb69.saveselect getdspplaylistsquery@f8ff.operate cdetaillistviewmodel@ea91.loaddata librarylistviewmodel@7bbd.loaddata platformssettingpage@9a54.loaddsppla	

FILE	FILE
my songssource loader@3da7.load more enablemanager@9b00.resetactio trdsptabstrip@aa32.attach ddtomusicdspauthutil@c894.getusersel edsongslstviewmodel@7b6e.clicklinkb .campaigncardassem@ea73.bindexposu librarylstviewmodel@7bbd.loadmoreso tabpageassem@e8f7.onwindowfo nginelisteneradapter@cbe8.togglelime absplayablequeue@1604.load ddtomusicdspauthutil@c894.getinstall -dspauthtokenfetcher@f3a9.refreshacc pplemusicauthhandler@f019.refreshapp haccesstokenmutation@4fee.operate teoriginsource loader@f51e.load 0dspauthtokenfetcher@f3a9.requestdsp my songssource loader@3da7.load 8dspfpsreportheper@a7a.forcedspla +baselyricsviewmodel@c093.getirclyri sicdspsheetviewmodel@3e3c.loadplatfo latformlistmethodidl@d11f.handle guidehelper@f22a.checkswipe ouoriginsource loader@bec7.loadmore musicplayviewmodel@970a.playmusic reportactionmutation@6d59.operate edsongslstviewmodel@7b6e.reportshow oidsessioncontroller@2942.maudiooutp eekbarchangelistener@11c0.onstoptrac mymusicactivity@4fe3.oncreate +addtomymusicmanager@f107.addsongtom odspnetworkmonitortk@e6a0.addsongmus imilar songsviewmodel@5e01.getsimilar haccesstokenmutation@68bf.operate edspauthtokenfetcher@f3a9.requestref musicdsplikeassem@dd13.onlikeclie mediaplayer@e4b0.play 1addtomymusicmanager@f107.addsongtom ryoriginsource loader@22de.loadmore zespecificdsphandler@b324.handle ongscheckfordspquery@6a28.operate queueloadplugin@b85e.load getsimilar songsquery@d509.operate 2dspauthtokenfetcher@f3a9.requestdsp 3dspfpsreportheper@a7a.dsplaunchd threadutil@fcce.sam lottieguide@f3e7.dismiss librarylstviewmodel@7bbd.refreshjou musicsettingpage@e355.initdata dspplatformlistquery@5a00.operate lechangereportplugin@9eed.onplayable teoriginsource loader@f51e.loadmore reportmanager@d9ac.reportacti +dailypickcardassem@5864.onviewcrea addtopresaveauthutil@7d3.addpresave lechangereportplugin@9eed.doaddrepor similar musicfragment@feee.oncreatevi caccesstokenmutation@f6d2.operate	lib/armeabi-v7a/libdex_df_music_dsp.so

ixoriginloader@232e.loadmore EMAIL musicdspauthutil@c894.getdspplat ddtomusicdspauthutil@c894.songcheckf	FILE
2lyricinfo@3645.getlyricin addedsongslistassem@a434.subscribev azonmusicauthhandler@45cb.getamazonm otlightdetailsharevm@1691.onloadmore sptackexpiredplugin@2375.onplayback umtomusicappmutation@f5d8.operate cdspjourneyviewmodel@e737.fetchsongs musicdspabfragment@f159.oncreatevi songcheckfordspquery@d39e.operate ddtomusicdspauthutil@c894.createdsp lottieguide@f3e7.show preloadplugin@b661.preload sicspaudiocardassem@3fa1.onviewcrea sicspsheetviewmodel@3e3c.requestpla cketplatformsyncpage@3038.initdata dspaudioseekbarassem@9696.seekbarsho absplayablequeue@1604.loadmore pipedplayablemanager@d256.resetactio usicdsplikeviewmodel@8702.savesongto baselyricsview@d7c.mhandler installdetectmanager@c140.getdspinst moveanimator@6935.run ddtomusicdspauthutil@c894.getdspplay edspplatformmutation@394.operate sicmainpageviewmodel@271e.loaddata lightbottomcomponent@75a.createbott gstomusicappmutation@76c2.operate justtagscachemanager@77d9.writelocal	

TRACKERS

TRACKER	CATEGORIES	URL
AppsFlyer	Analytics	https://reports.exodus-privacy.eu.org/trackers/12
Facebook Analytics	Analytics	https://reports.exodus-privacy.eu.org/trackers/66
Facebook Login	Identification	https://reports.exodus-privacy.eu.org/trackers/67
Facebook Share		https://reports.exodus-privacy.eu.org/trackers/70
Google Firebase Analytics	Analytics	https://reports.exodus-privacy.eu.org/trackers/49
IAB Open Measurement	Advertisement, Identification	https://reports.exodus-privacy.eu.org/trackers/328
Pangle	Advertisement	https://reports.exodus-privacy.eu.org/trackers/363

POSSIBLE SECRETS
dzBzEgAjS8/YVFKiQFyFaHCZkp+e+K86yefGjBq+yNSOFwQP8ns+BPcUYzxLpNgZVAXiSYfLg+HHg==
KyohZy0qPCAoKCEwLWstjyshJywoZyM6PiA/LSR9HELIOSOCA+JCYgOywjj2EDLTchIDwgISoiDz0yLygpjzs=
KyohZy0qPCAoKCEwLWsILDx9OyQqLCI8LCBiGilyOjEcOyAnLSHELIOsY4LCt9LiQ/PS08JzFiDy4gPACjjSBLSEIOyowPAQvPSYIITE1
5dad71914d894800389238d8

PLAYSTORE INFORMATION

Title: TikTok - Videos, Shop & LIVE

Score: 3.9987473 **Installs:** 1,000,000,000+ **Price:** 0 **Android Version Support:** **Category:** Social **Play Store URL:** [com.zhiliaoapp.musically](https://play.google.com/store/apps/details?id=com.zhiliaoapp.musically)

Developer Details: TikTok Pte. Ltd., TikTok+Pte.+Ltd., None, <https://www.tiktok.com/>, feedback@tiktok.com,

Release Date: Jul 9, 2015 **Privacy Policy:** [Privacy link](#)

Description:

TikTok is the global discovery platform for videos, streaming on LIVE, shopping, and more. Our mission is to inspire creativity and bring joy. Over a billion people come to TikTok to share what they love, learn new things, and find ideas that make everyday life more interesting. Your experience on TikTok is built around what you're into, not who you know. Just watch, like, and scroll to discover videos, creators, and communities you did not know you were looking for. From quick recipes to game highlights, fashion tips to music and trending sounds, your For You feed reflects you and changes based on what inspires you. Creating is simple. Capture from your phone and turn everyday moments into something special with easy editing tools, effects, sounds, and music. Use a large library of sounds and music for free in your videos, plus filters and creative tools that help your content stand out. On TikTok, anyone can create, and ideas that inspire, pick up momentum. TikTok is also where discovery becomes part of your everyday life. Find creators to follow, new ideas to try, and products you will love from small businesses and brands around the world. TikTok offers more than 50 preset safety and privacy features, from private accounts and content filters to screen time tools and Family Pairing, so you can choose an experience that works for you. TikTok provides extra support for teens and families on the app, letting you set time and content preferences that feel right for your family. ■ Personalized discovery A For You feed that learns what you enjoy. Discover videos, creators, LIVE streams, shopping, and communities based on what you watch, like, and share. ■ Entertainment, learning, and everything in between Comedy, gaming, DIY, beauty, sports, music, lifestyle, education, and more. Find content that makes you laugh, think, and try something new. ■ Simple, powerful creation tools Record in clips, pause and resume, trim and merge, add text and stickers, and fine tune your video without leaving the app. ■ Sounds, music, and effects Use our free library of sounds and music in your videos, plus filters, effects, and creative tools that help you express yourself and make your videos stand out. ■ A global community of creators Follow your favorite creators and discover new voices every day. Share your own story or support the people who inspire you. ■ Discover and shop with TikTok Shop Explore trending products, exclusive deals, and seamless shopping experiences inspired by creators and brands you love, all in one place. Shop directly from videos, LIVE, and the Shop tab, track your orders, and enjoy a safe, secure shopping and transaction process. ■ Go LIVE and connect in real time Start a LIVE to chat with your community, share moments as they happen, and unlock special features and benefits where available. ■ Tools to shape your experience Use more than 50 safety and privacy features, from private accounts and content filters to screen time tools, Family Pairing, and other controls, to choose how TikTok works for you and your family. Ready to see what you discover next? Download TikTok to start watching, creating, and exploring your world in a new way. Learn more about our safety tools, resources, and policies at the TikTok Safety Center: <https://www.tiktok.com/safety/en> Terms of Service: <https://www.tiktok.com/legal/terms-of-service> Privacy Policy: <https://www.tiktok.com/legal/privacy-policy> Feedback? Contact us at <https://www.tiktok.com/legal/report/feedback> or tweet us @tiktok_us

SCAN LOGS

Timestamp	Event	Error
-----------	-------	-------

2026-05-27 11:25:58	Generating Hashes	OK
2026-05-27 11:25:58	Extracting APK	OK
2026-05-27 11:25:58	Unzipping	OK
2026-05-27 11:26:05	Parsing APK with androguard	OK
2026-05-27 11:26:09	Extracting APK features using aapt/aapt2	OK
2026-05-27 11:26:10	Getting Hardcoded Certificates/Keystores	OK
2026-05-27 11:26:25	Parsing AndroidManifest.xml	OK
2026-05-27 11:26:25	Extracting Manifest Data	OK
2026-05-27 11:26:25	Manifest Analysis Started	OK
2026-05-27 11:26:25	Reading Network Security config from u.xml	OK
2026-05-27 11:26:25	Parsing Network Security config	OK
2026-05-27 11:26:25	Performing Static Analysis on: TikTok (com.zhiliaoapp.musically)	OK
2026-05-27 11:26:28	Fetching Details from Play Store: com.zhiliaoapp.musically	OK
2026-05-27 11:26:34	Checking for Malware Permissions	OK
2026-05-27 11:26:34	Fetching icon path	OK

2026-05-27 11:26:34	Library Binary Analysis Started	OK
2026-05-27 11:26:34	Analyzing apktool_out/lib/arm64-v8a/libbyteVC2dec.so	OK
2026-05-27 11:26:34	Analyzing apktool_out/lib/arm64-v8a/libreschecker.so	OK
2026-05-27 11:26:34	Analyzing apktool_out/lib/arm64-v8a/libtt_ugen_layout.so	OK
2026-05-27 11:26:34	Analyzing apktool_out/lib/arm64-v8a/liborbuculumadapter.so	OK
2026-05-27 11:26:34	Analyzing apktool_out/lib/arm64-v8a/liblens.so	OK
2026-05-27 11:26:34	Analyzing apktool_out/lib/arm64-v8a/libavocadoguard.so	OK
2026-05-27 11:26:34	Analyzing apktool_out/lib/arm64-v8a/libbase_live.so	OK
2026-05-27 11:26:34	Analyzing apktool_out/lib/arm64-v8a/libbdhm_native.so	OK
2026-05-27 11:26:34	Analyzing apktool_out/lib/arm64-v8a/libvcnverify.so	OK
2026-05-27 11:26:34	Analyzing apktool_out/lib/arm64-v8a/libpumbaa-network.so	OK
2026-05-27 11:26:34	Analyzing apktool_out/lib/arm64-v8a/libstarship_sdk.so	OK
2026-05-27 11:26:34	Analyzing apktool_out/lib/arm64-v8a/libv8_libfull.cr.so	OK
2026-05-27 11:26:34	Analyzing apktool_out/lib/arm64-v8a/libttmverify.so	OK
2026-05-27 11:26:34	Analyzing apktool_out/lib/arm64-v8a/libvcn.so	OK

2026-05-27 11:26:34	Analyzing apktool_out/lib/arm64-v8a/libfly-main-color-lib.so	OK
2026-05-27 11:26:34	Analyzing apktool_out/lib/arm64-v8a/libshadowhook_nothing.so	OK
2026-05-27 11:26:34	Analyzing apktool_out/lib/arm64-v8a/libarccore_sdk_c.so	OK
2026-05-27 11:26:34	Analyzing apktool_out/lib/arm64-v8a/libByteAlNN.so	OK
2026-05-27 11:26:34	Analyzing apktool_out/lib/arm64-v8a/libdex_df_pipo_bnpl.so	OK
2026-05-27 11:26:34	Analyzing apktool_out/lib/arm64-v8a/libbytebench.so	OK
2026-05-27 11:26:34	Analyzing apktool_out/lib/arm64-v8a/libCepProxy.so	OK
2026-05-27 11:26:34	Analyzing apktool_out/lib/arm64-v8a/libconfigcenter.so	OK
2026-05-27 11:26:34	Analyzing apktool_out/lib/arm64-v8a/libartshadowhook.so	OK
2026-05-27 11:26:34	Analyzing apktool_out/lib/arm64-v8a/libjazz.so	OK
2026-05-27 11:26:34	Analyzing apktool_out/lib/arm64-v8a/libdex_df_pipo_external_payments.so	OK
2026-05-27 11:26:34	Analyzing apktool_out/lib/arm64-v8a/libnpth_tls_monitor.so	OK
2026-05-27 11:26:34	Analyzing apktool_out/lib/arm64-v8a/libttc2pa.so	OK
2026-05-27 11:26:34	Analyzing apktool_out/lib/arm64-v8a/libonetex.so	OK
2026-05-27 11:26:34	Analyzing apktool_out/lib/arm64-v8a/libtt_c2pa_sdk_d.so	OK

2026-05-27 11:26:34	Analyzing apktool_out/lib/arm64-v8a/libEffectCreatorJni.so	OK
2026-05-27 11:26:34	Analyzing apktool_out/lib/arm64-v8a/libvideodec.so	OK
2026-05-27 11:26:34	Analyzing apktool_out/lib/arm64-v8a/libnpth_dumper.so	OK
2026-05-27 11:26:34	Analyzing apktool_out/lib/arm64-v8a/liblynxstarlight.so	OK
2026-05-27 11:26:34	Analyzing apktool_out/lib/arm64-v8a/libmotion.so	OK
2026-05-27 11:26:34	Analyzing apktool_out/lib/arm64-v8a/libpy-cv-numpycv.so	OK
2026-05-27 11:26:34	Analyzing apktool_out/lib/arm64-v8a/libtboringsl.so	OK
2026-05-27 11:26:34	Analyzing apktool_out/lib/arm64-v8a/libnetecho.so	OK
2026-05-27 11:26:34	Analyzing apktool_out/lib/arm64-v8a/libjazz_plugin.so	OK
2026-05-27 11:26:34	Analyzing apktool_out/lib/arm64-v8a/libsimba.so	OK
2026-05-27 11:26:34	Analyzing apktool_out/lib/arm64-v8a/libArchive.so	OK
2026-05-27 11:26:34	Analyzing apktool_out/lib/arm64-v8a/libres_memory.so	OK
2026-05-27 11:26:34	Analyzing apktool_out/lib/arm64-v8a/libaudioeffect.so	OK
2026-05-27 11:26:34	Analyzing apktool_out/lib/arm64-v8a/libsscronet.so	OK
2026-05-27 11:26:34	Analyzing apktool_out/lib/arm64-v8a/liblynxsuit.so	OK

2026-05-27 11:26:34	Analyzing apktool_out/lib/arm64-v8a/libstatic-webp.so	OK
2026-05-27 11:26:34	Analyzing apktool_out/lib/arm64-v8a/libtr.so	OK
2026-05-27 11:26:34	Analyzing apktool_out/lib/arm64-v8a/libspeechsdk.so	OK
2026-05-27 11:26:34	Analyzing apktool_out/lib/arm64-v8a/liblynxsecurity.so	OK
2026-05-27 11:26:34	Analyzing apktool_out/lib/arm64-v8a/liblynx_krypton.so	OK
2026-05-27 11:26:34	Analyzing apktool_out/lib/arm64-v8a/libshadowhook.so	OK
2026-05-27 11:26:34	Analyzing apktool_out/lib/arm64-v8a/libtexturerender_native.so	OK
2026-05-27 11:26:35	Analyzing apktool_out/lib/arm64-v8a/libt_c2pa_sdk.so	OK
2026-05-27 11:26:35	Analyzing apktool_out/lib/arm64-v8a/libLAMaterialSDK.so	OK
2026-05-27 11:26:35	Analyzing apktool_out/lib/arm64-v8a/libworker.so	OK
2026-05-27 11:26:35	Analyzing apktool_out/lib/arm64-v8a/libnxreword.so	OK
2026-05-27 11:26:35	Analyzing apktool_out/lib/arm64-v8a/libbytenn.so	OK
2026-05-27 11:26:35	Analyzing apktool_out/lib/arm64-v8a/liblink_mic_sdk.so	OK
2026-05-27 11:26:35	Analyzing apktool_out/lib/arm64-v8a/libstarship_wrapper.so	OK
2026-05-27 11:26:35	Analyzing apktool_out/lib/arm64-v8a/libvolcenginertc.so	OK

2026-05-27 11:26:35	Analyzing apktool_out/lib/arm64-v8a/libByteAIDT.so	OK
2026-05-27 11:26:35	Analyzing apktool_out/lib/arm64-v8a/libjato.so	OK
2026-05-27 11:26:35	Analyzing apktool_out/lib/arm64-v8a/libbytevc1enc.so	OK
2026-05-27 11:26:35	Analyzing apktool_out/lib/arm64-v8a/libbytennllm-jni.so	OK
2026-05-27 11:26:35	Analyzing apktool_out/lib/arm64-v8a/libmonitorcollector-lib.so	OK
2026-05-27 11:26:35	Analyzing apktool_out/lib/arm64-v8a/lib_jhmp.so	OK
2026-05-27 11:26:35	Analyzing apktool_out/lib/arm64-v8a/libkryptonaudio.so	OK
2026-05-27 11:26:35	Analyzing apktool_out/lib/arm64-v8a/libgeckox_bspatch.so	OK
2026-05-27 11:26:35	Analyzing apktool_out/lib/arm64-v8a/liborbuculum.so	OK
2026-05-27 11:26:35	Analyzing apktool_out/lib/arm64-v8a/libyoga.so	OK
2026-05-27 11:26:35	Analyzing apktool_out/lib/arm64-v8a/libnpth_unw.so	OK
2026-05-27 11:26:35	Analyzing apktool_out/lib/arm64-v8a/libNLEditorjni.so	OK
2026-05-27 11:26:35	Analyzing apktool_out/lib/arm64-v8a/libttvesdk_plugin.so	OK
2026-05-27 11:26:35	Analyzing apktool_out/lib/arm64-v8a/libfile_lock.so	OK
2026-05-27 11:26:35	Analyzing apktool_out/lib/arm64-v8a/libgodzilla-mem sponge.so	OK

2026-05-27 11:26:35	Analyzing apktool_out/lib/arm64-v8a/libfdk-aac.so	OK
2026-05-27 11:26:35	Analyzing apktool_out/lib/arm64-v8a/libjarvis-trace.so	OK
2026-05-27 11:26:35	Analyzing apktool_out/lib/arm64-v8a/lib_jbmf.so	OK
2026-05-27 11:26:35	Analyzing apktool_out/lib/arm64-v8a/libanimax_bytevc1.so	OK
2026-05-27 11:26:35	Analyzing apktool_out/lib/arm64-v8a/libminizip.so	OK
2026-05-27 11:26:35	Analyzing apktool_out/lib/arm64-v8a/libCutSameJni.so	OK
2026-05-27 11:26:35	Analyzing apktool_out/lib/arm64-v8a/libEncryptor.so	OK
2026-05-27 11:26:35	Analyzing apktool_out/lib/arm64-v8a/libwatson.so	OK
2026-05-27 11:26:35	Analyzing apktool_out/lib/arm64-v8a/libotis_attrib.so	OK
2026-05-27 11:26:35	Analyzing apktool_out/lib/arm64-v8a/liblynxbase.so	OK
2026-05-27 11:26:35	Analyzing apktool_out/lib/arm64-v8a/libwcd.db.so	OK
2026-05-27 11:26:35	Analyzing apktool_out/lib/arm64-v8a/libttdemux.so	OK
2026-05-27 11:26:35	Analyzing apktool_out/lib/arm64-v8a/libNLETemplateModelJni_plugin.so	OK
2026-05-27 11:26:35	Analyzing apktool_out/lib/arm64-v8a/libpipo-security-sdk.so	OK
2026-05-27 11:26:35	Analyzing apktool_out/lib/arm64-v8a/libCepFast.so	OK

2026-05-27 11:26:35	Analyzing apktool_out/lib/arm64-v8a/libanrrrelief.so	OK
2026-05-27 11:26:35	Analyzing apktool_out/lib/arm64-v8a/libDavinciResourceJni.so	OK
2026-05-27 11:26:35	Analyzing apktool_out/lib/arm64-v8a/libfileprotect.so	OK
2026-05-27 11:26:35	Analyzing apktool_out/lib/arm64-v8a/libnpth_repair.so	OK
2026-05-27 11:26:35	Analyzing apktool_out/lib/arm64-v8a/libkrypton_sar.so	OK
2026-05-27 11:26:35	Analyzing apktool_out/lib/arm64-v8a/libbmf_hydra_lite.so	OK
2026-05-27 11:26:35	Analyzing apktool_out/lib/arm64-v8a/libquick.so	OK
2026-05-27 11:26:35	Analyzing apktool_out/lib/arm64-v8a/libfastcv.so	OK
2026-05-27 11:26:35	Analyzing apktool_out/lib/arm64-v8a/libBlinkCard.so	OK
2026-05-27 11:26:35	Analyzing apktool_out/lib/arm64-v8a/libbdzstd.so	OK
2026-05-27 11:26:35	Analyzing apktool_out/lib/arm64-v8a/libdex_df_ccdc_impl_ocr.so	OK
2026-05-27 11:26:35	Analyzing apktool_out/lib/arm64-v8a/libbytelink.so	OK
2026-05-27 11:26:35	Analyzing apktool_out/lib/arm64-v8a/libforestx_native_buffer.so	OK
2026-05-27 11:26:35	Analyzing apktool_out/lib/arm64-v8a/libttmverifylite.so	OK
2026-05-27 11:26:35	Analyzing apktool_out/lib/arm64-v8a/libbmf_mods.so	OK

2026-05-27 11:26:35	Analyzing apktool_out/lib/arm64-v8a/libresource_monitor.so	OK
2026-05-27 11:26:35	Analyzing apktool_out/lib/arm64-v8a/libkryptoneffect.so	OK
2026-05-27 11:26:35	Analyzing apktool_out/lib/arm64-v8a/libptyjemalloc.so	OK
2026-05-27 11:26:35	Analyzing apktool_out/lib/arm64-v8a/libtffmpeg.so	OK
2026-05-27 11:26:35	Analyzing apktool_out/lib/arm64-v8a/libanimax_textra.so	OK
2026-05-27 11:26:35	Analyzing apktool_out/lib/arm64-v8a/liblynxtrace.so	OK
2026-05-27 11:26:35	Analyzing apktool_out/lib/arm64-v8a/libpythonA.so	OK
2026-05-27 11:26:35	Analyzing apktool_out/lib/arm64-v8a/libgifimage.so	OK
2026-05-27 11:26:35	Analyzing apktool_out/lib/arm64-v8a/libsysoptimizer.so	OK
2026-05-27 11:26:35	Analyzing apktool_out/lib/arm64-v8a/libtailor.so	OK
2026-05-27 11:26:35	Analyzing apktool_out/lib/arm64-v8a/libkryptonaurem.so	OK
2026-05-27 11:26:35	Analyzing apktool_out/lib/arm64-v8a/libdex_df_ship.so	OK
2026-05-27 11:26:36	Analyzing apktool_out/lib/arm64-v8a/libbdmpg123.so	OK
2026-05-27 11:26:36	Analyzing apktool_out/lib/arm64-v8a/libbd-install.so	OK
2026-05-27 11:26:36	Analyzing apktool_out/lib/arm64-v8a/libNLEMediajni_plugin.so	OK

2026-05-27 11:26:36	Analyzing apktool_out/lib/arm64-v8a/libiesapplogger.so	OK
2026-05-27 11:26:36	Analyzing apktool_out/lib/arm64-v8a/libpsp_engine.so	OK
2026-05-27 11:26:36	Analyzing apktool_out/lib/arm64-v8a/libdelta.so	OK
2026-05-27 11:26:36	Analyzing apktool_out/lib/arm64-v8a/libNLEditorJni_plugin.so	OK
2026-05-27 11:26:36	Analyzing apktool_out/lib/arm64-v8a/libclient_ai_impl_jni.so	OK
2026-05-27 11:26:36	Analyzing apktool_out/lib/arm64-v8a/libnpth_fp_unw.so	OK
2026-05-27 11:26:36	Analyzing apktool_out/lib/arm64-v8a/libkeva.so	OK
2026-05-27 11:26:36	Analyzing apktool_out/lib/arm64-v8a/libflipped.so	OK
2026-05-27 11:26:36	Analyzing apktool_out/lib/arm64-v8a/libbat.so	OK
2026-05-27 11:26:36	Analyzing apktool_out/lib/arm64-v8a/libAwplatsupport.so	OK
2026-05-27 11:26:36	Analyzing apktool_out/lib/arm64-v8a/libttmplayer.so	OK
2026-05-27 11:26:36	Analyzing apktool_out/lib/arm64-v8a/libBDPythonVM.so	OK
2026-05-27 11:26:36	Analyzing apktool_out/lib/arm64-v8a/libgaia_lib.so	OK
2026-05-27 11:26:36	Analyzing apktool_out/lib/arm64-v8a/libsliver.so	OK
2026-05-27 11:26:36	Analyzing apktool_out/lib/arm64-v8a/libTTMStrategyCenter.so	OK

2026-05-27 11:26:36	Analyzing apktool_out/lib/arm64-v8a/libbytennllm.so	OK
2026-05-27 11:26:36	Analyzing apktool_out/lib/arm64-v8a/liblynx_v8_bridge.so	OK
2026-05-27 11:26:36	Analyzing apktool_out/lib/arm64-v8a/libnativeaudio.so	OK
2026-05-27 11:26:36	Analyzing apktool_out/lib/arm64-v8a/libskity.so	OK
2026-05-27 11:26:36	Analyzing apktool_out/lib/arm64-v8a/libropaencrypt.so	OK
2026-05-27 11:26:36	Analyzing apktool_out/lib/arm64-v8a/libstorage-hook.so	OK
2026-05-27 11:26:36	Analyzing apktool_out/lib/arm64-v8a/libjson_opt.so	OK
2026-05-27 11:26:36	Analyzing apktool_out/lib/arm64-v8a/libdex_df_pitaya.so	OK
2026-05-27 11:26:36	Analyzing apktool_out/lib/arm64-v8a/libavmdlp2pv2.so	OK
2026-05-27 11:26:36	Analyzing apktool_out/lib/arm64-v8a/libskbase.so	OK
2026-05-27 11:26:36	Analyzing apktool_out/lib/arm64-v8a/libbdsword.so	OK
2026-05-27 11:26:36	Analyzing apktool_out/lib/arm64-v8a/libttpreload.so	OK
2026-05-27 11:26:36	Analyzing apktool_out/lib/arm64-v8a/libarcore_sdk_jni.so	OK
2026-05-27 11:26:36	Analyzing apktool_out/lib/arm64-v8a/libttheif_dec.so	OK
2026-05-27 11:26:36	Analyzing apktool_out/lib/arm64-v8a/libfast_engine_api_loader.so	OK

2026-05-27 11:26:36	Analyzing apktool_out/lib/arm64-v8a/libalog.so	OK
2026-05-27 11:26:36	Analyzing apktool_out/lib/arm64-v8a/libavmdlbase.so	OK
2026-05-27 11:26:36	Analyzing apktool_out/lib/arm64-v8a/libEffectEditorJni.so	OK
2026-05-27 11:26:36	Analyzing apktool_out/lib/arm64-v8a/libhelios_bm.so	OK
2026-05-27 11:26:36	Analyzing apktool_out/lib/arm64-v8a/libnpth_bt.so	OK
2026-05-27 11:26:36	Analyzing apktool_out/lib/arm64-v8a/libtttext_lite.so	OK
2026-05-27 11:26:36	Analyzing apktool_out/lib/arm64-v8a/libqmiVsyncHook.so	OK
2026-05-27 11:26:36	Analyzing apktool_out/lib/arm64-v8a/libttmcmaf.so	OK
2026-05-27 11:26:36	Analyzing apktool_out/lib/arm64-v8a/libNLEResourcesDAVJni_plugin.so	OK
2026-05-27 11:26:36	Analyzing apktool_out/lib/arm64-v8a/libAGFX.so	OK
2026-05-27 11:26:36	Analyzing apktool_out/lib/arm64-v8a/libnpth_unwind.so	OK
2026-05-27 11:26:36	Analyzing apktool_out/lib/arm64-v8a/libandroidx.graphics.path.so	OK
2026-05-27 11:26:36	Analyzing apktool_out/lib/arm64-v8a/liblynx_service_api.so	OK
2026-05-27 11:26:36	Analyzing apktool_out/lib/arm64-v8a/libbytehook.so	OK
2026-05-27 11:26:36	Analyzing apktool_out/lib/arm64-v8a/libbmf_module_sdk.so	OK

2026-05-27 11:26:36	Analyzing apktool_out/lib/arm64-v8a/libpns_ttmachine_adapter.so	OK
2026-05-27 11:26:36	Analyzing apktool_out/lib/arm64-v8a/libotisoapt.so	OK
2026-05-27 11:26:36	Analyzing apktool_out/lib/arm64-v8a/libpunch.so	OK
2026-05-27 11:26:36	Analyzing apktool_out/lib/arm64-v8a/libvegasdk.so	OK
2026-05-27 11:26:36	Analyzing apktool_out/lib/arm64-v8a/libbmf_hydra.so	OK
2026-05-27 11:26:36	Analyzing apktool_out/lib/arm64-v8a/liblynx.so	OK
2026-05-27 11:26:36	Analyzing apktool_out/lib/arm64-v8a/libanimax.so	OK
2026-05-27 11:26:36	Analyzing apktool_out/lib/arm64-v8a/libpreload.so	OK
2026-05-27 11:26:36	Analyzing apktool_out/lib/arm64-v8a/libimagepipeline.so	OK
2026-05-27 11:26:36	Analyzing apktool_out/lib/arm64-v8a/libPitayaBdComponent.so	OK
2026-05-27 11:26:36	Analyzing apktool_out/lib/arm64-v8a/librex.so	OK
2026-05-27 11:26:36	Analyzing apktool_out/lib/arm64-v8a/libAndroidPitayaCore.so	OK
2026-05-27 11:26:36	Analyzing apktool_out/lib/arm64-v8a/libbdheif.so	OK
2026-05-27 11:26:36	Analyzing apktool_out/lib/arm64-v8a/libbytevc1enc10b.so	OK
2026-05-27 11:26:36	Analyzing apktool_out/lib/arm64-v8a/liblynx_text_service.so	OK

2026-05-27 11:26:36	Analyzing apktool_out/lib/arm64-v8a/libSmartMoviejni.so	OK
2026-05-27 11:26:36	Analyzing apktool_out/lib/arm64-v8a/libNLEMediaRemotejni_plugin.so	OK
2026-05-27 11:26:36	Analyzing apktool_out/lib/arm64-v8a/libnpth_logcat.so	OK
2026-05-27 11:26:36	Analyzing apktool_out/lib/arm64-v8a/libnpth_xasan.so	OK
2026-05-27 11:26:36	Analyzing apktool_out/lib/arm64-v8a/libc++_shared.so	OK
2026-05-27 11:26:36	Analyzing apktool_out/lib/arm64-v8a/libzoin.so	OK
2026-05-27 11:26:36	Analyzing apktool_out/lib/arm64-v8a/libalignpage.so	OK
2026-05-27 11:26:36	Analyzing apktool_out/lib/arm64-v8a/libh3-java.so	OK
2026-05-27 11:26:36	Analyzing apktool_out/lib/arm64-v8a/libnapi.so	OK
2026-05-27 11:26:36	Analyzing apktool_out/lib/arm64-v8a/libkrypton.so	OK
2026-05-27 11:26:36	Analyzing apktool_out/lib/arm64-v8a/libnpth_ref_monitor.so	OK
2026-05-27 11:26:36	Analyzing apktool_out/lib/arm64-v8a/libByteVC1_dec.so	OK
2026-05-27 11:26:36	Analyzing apktool_out/lib/arm64-v8a/libvebytevc1enc8bwrapper.so	OK
2026-05-27 11:26:37	Analyzing apktool_out/lib/arm64-v8a/libCepAuth.so	OK
2026-05-27 11:26:37	Analyzing apktool_out/lib/arm64-v8a/libvctfo.so	OK

2026-05-27 11:26:37	Analyzing apktool_out/lib/arm64-v8a/libcybertron_base.so	OK
2026-05-27 11:26:37	Analyzing apktool_out/lib/arm64-v8a/libp2plivevdp.so	OK
2026-05-27 11:26:37	Analyzing apktool_out/lib/arm64-v8a/libffmpeg_dashdec.so	OK
2026-05-27 11:26:37	Analyzing apktool_out/lib/arm64-v8a/libwasm.so	OK
2026-05-27 11:26:37	Analyzing apktool_out/lib/arm64-v8a/libbytemonitor.so	OK
2026-05-27 11:26:37	Analyzing apktool_out/lib/arm64-v8a/libserval_svg.so	OK
2026-05-27 11:26:37	Analyzing apktool_out/lib/arm64-v8a/libartlog_monitor.so	OK
2026-05-27 11:26:37	Analyzing apktool_out/lib/arm64-v8a/libvolcenginertc_plugin.so	OK
2026-05-27 11:26:37	Analyzing apktool_out/lib/arm64-v8a/libCepEngine.so	OK
2026-05-27 11:26:37	Analyzing apktool_out/lib/arm64-v8a/libttnisnative.so	OK
2026-05-27 11:26:37	Analyzing apktool_out/lib/arm64-v8a/libdex_df_ttwebview.so	OK
2026-05-27 11:26:37	Analyzing apktool_out/lib/arm64-v8a/libttquic.so	OK
2026-05-27 11:26:37	Analyzing apktool_out/lib/arm64-v8a/libspeechspg.so	OK
2026-05-27 11:26:37	Analyzing apktool_out/lib/arm64-v8a/libnpath_dl.so	OK
2026-05-27 11:26:37	Analyzing apktool_out/lib/arm64-v8a/libbytedt.so	OK

2026-05-27 11:26:37	Analyzing apktool_out/lib/arm64-v8a/libfast_engine.so	OK
2026-05-27 11:26:37	Analyzing apktool_out/lib/arm64-v8a/libbytevc1enc10bwrapper.so	OK
2026-05-27 11:26:37	Analyzing apktool_out/lib/arm64-v8a/libdex_df_live_cast.so	OK
2026-05-27 11:26:37	Analyzing apktool_out/lib/arm64-v8a/libbytevc0.so	OK
2026-05-27 11:26:37	Analyzing apktool_out/lib/arm64-v8a/libhmp.so	OK
2026-05-27 11:26:37	Analyzing apktool_out/lib/arm64-v8a/libpns_crypto.so	OK
2026-05-27 11:26:37	Analyzing apktool_out/lib/arm64-v8a/libPitayaTTPPolicy.so	OK
2026-05-27 11:26:37	Analyzing apktool_out/lib/arm64-v8a/libopus.so	OK
2026-05-27 11:26:37	Analyzing apktool_out/lib/arm64-v8a/libTTMachineCore.so	OK
2026-05-27 11:26:37	Analyzing apktool_out/lib/arm64-v8a/libNLEMediaRemoteJni.so	OK
2026-05-27 11:26:37	Analyzing apktool_out/lib/arm64-v8a/libvcbasekit.so	OK
2026-05-27 11:26:37	Analyzing apktool_out/lib/arm64-v8a/libug_share_sort.so	OK
2026-05-27 11:26:37	Analyzing apktool_out/lib/arm64-v8a/libBDMicroPythonVM.so	OK
2026-05-27 11:26:37	Analyzing apktool_out/lib/arm64-v8a/liblivestrategy.so	OK
2026-05-27 11:26:37	Analyzing apktool_out/lib/arm64-v8a/libspeechepg.so	OK

2026-05-27 11:26:37	Analyzing apktool_out/lib/arm64-v8a/libbdvideouploader.so	OK
2026-05-27 11:26:37	Analyzing apktool_out/lib/arm64-v8a/librtmglobal.so	OK
2026-05-27 11:26:37	Analyzing apktool_out/lib/arm64-v8a/libbuffer.so	OK
2026-05-27 11:26:37	Analyzing apktool_out/lib/arm64-v8a/libfast_engine_api.so	OK
2026-05-27 11:26:37	Analyzing apktool_out/lib/arm64-v8a/libworkerv8.so	OK
2026-05-27 11:26:37	Analyzing apktool_out/lib/arm64-v8a/libeffect_plugin.so	OK
2026-05-27 11:26:37	Analyzing apktool_out/lib/arm64-v8a/libbytennwrapper.so	OK
2026-05-27 11:26:37	Analyzing apktool_out/lib/arm64-v8a/libicu.so	OK
2026-05-27 11:26:37	Analyzing apktool_out/lib/arm64-v8a/libdex_df_music_dsp.so	OK
2026-05-27 11:26:37	Analyzing apktool_out/lib/arm64-v8a/libnative-filters.so	OK
2026-05-27 11:26:37	Analyzing apktool_out/lib/arm64-v8a/libpsienrcrypt.so	OK
2026-05-27 11:26:37	Analyzing apktool_out/lib/arm64-v8a/liblynx_markdown.so	OK
2026-05-27 11:26:37	Analyzing apktool_out/lib/arm64-v8a/libjniidispach.so	OK
2026-05-27 11:26:37	Analyzing apktool_out/lib/arm64-v8a/libmedia.so	OK
2026-05-27 11:26:38	Analyzing apktool_out/lib/arm64-v8a/libttcrypto.so	OK

2026-05-27 11:26:38	Analyzing apktool_out/lib/arm64-v8a/libspeechengine.so	OK
2026-05-27 11:26:38	Analyzing apktool_out/lib/arm64-v8a/libxtrace.so	OK
2026-05-27 11:26:38	Analyzing apktool_out/lib/arm64-v8a/libpy-numpy.so	OK
2026-05-27 11:26:38	Analyzing apktool_out/lib/arm64-v8a/liboecsec_ov.so	OK
2026-05-27 11:26:38	Analyzing apktool_out/lib/arm64-v8a/libvoip.so	OK
2026-05-27 11:26:38	Analyzing apktool_out/lib/arm64-v8a/liburiparser.so	OK
2026-05-27 11:26:38	Analyzing apktool_out/lib/arm64-v8a/libmemrelief.so	OK
2026-05-27 11:26:38	Analyzing apktool_out/lib/arm64-v8a/libCepAST.so	OK
2026-05-27 11:26:38	Analyzing apktool_out/lib/arm64-v8a/libEffectEditorABTestJni.so	OK
2026-05-27 11:26:38	Analyzing apktool_out/lib/arm64-v8a/libNLEResourcesDAVJni.so	OK
2026-05-27 11:26:38	Analyzing apktool_out/lib/arm64-v8a/libNLEMediaPublicJni.so	OK
2026-05-27 11:26:38	Analyzing apktool_out/lib/arm64-v8a/libbtch_collection.so	OK
2026-05-27 11:26:38	Analyzing apktool_out/lib/arm64-v8a/libaudio_fingerprint_sdk.so	OK
2026-05-27 11:26:38	Analyzing apktool_out/lib/arm64-v8a/libart_sym.so	OK
2026-05-27 11:26:38	Analyzing apktool_out/lib/arm64-v8a/libnpth_fd_tracker.so	OK

2026-05-27 11:26:38	Analyzing apktool_out/lib/arm64-v8a/libkomprese-decompressor.so	OK
2026-05-27 11:26:38	Analyzing apktool_out/lib/arm64-v8a/libmmt.so	OK
2026-05-27 11:26:38	Analyzing apktool_out/lib/arm64-v8a/libapplog_rust.so	OK
2026-05-27 11:26:38	Analyzing apktool_out/lib/arm64-v8a/libwhisper.so	OK
2026-05-27 11:26:38	Analyzing apktool_out/lib/arm64-v8a/libnpth.so	OK
2026-05-27 11:26:38	Analyzing apktool_out/lib/arm64-v8a/libprofiler.so	OK
2026-05-27 11:26:38	Analyzing apktool_out/lib/arm64-v8a/libanimax_napi.so	OK
2026-05-27 11:26:38	Analyzing apktool_out/lib/arm64-v8a/libyuv.so	OK
2026-05-27 11:26:38	Analyzing apktool_out/lib/arm64-v8a/libbach-sdk-jni.so	OK
2026-05-27 11:26:38	Analyzing apktool_out/lib/arm64-v8a/libmetasec_ov.so	OK
2026-05-27 11:26:38	Analyzing apktool_out/lib/arm64-v8a/libanrthanos.so	OK
2026-05-27 11:26:38	Analyzing apktool_out/lib/arm64-v8a/libAwebviewbytedance.so	OK
2026-05-27 11:26:39	Analyzing apktool_out/lib/arm64-v8a/libnewep.so	OK
2026-05-27 11:26:39	Analyzing apktool_out/lib/arm64-v8a/libNLETemplateModeljni.so	OK
2026-05-27 11:26:39	Analyzing apktool_out/lib/arm64-v8a/libNLEMediaPublicjni_plugin.so	OK

2026-05-27 11:26:39	Analyzing apktool_out/lib/arm64-v8a/libvcnverifylite.so	OK
2026-05-27 11:26:39	Analyzing apktool_out/lib/arm64-v8a/libNLEMediajni.so	OK
2026-05-27 11:26:39	Analyzing apktool_out/lib/arm64-v8a/libflock-lib.so	OK
2026-05-27 11:26:39	Analyzing apktool_out/lib/arm64-v8a/libnapi_v8.so	OK
2026-05-27 11:26:39	Analyzing apktool_out/lib/arm64-v8a/libbvcparser.so	OK
2026-05-27 11:26:39	Analyzing apktool_out/lib/arm64-v8a/libjarvis-metrics.so	OK
2026-05-27 11:26:39	Analyzing apktool_out/lib/arm64-v8a/libcrashpad_handler_trampoline.so	OK
2026-05-27 11:26:39	Analyzing apktool_out/lib/arm64-v8a/libkryptonremote.so	OK
2026-05-27 11:26:39	Analyzing apktool_out/lib/arm64-v8a/libgodzilla-sysopt.so	OK
2026-05-27 11:26:39	Analyzing apktool_out/lib/arm64-v8a/libTTNativeML.so	OK
2026-05-27 11:26:39	Analyzing apktool_out/lib/armeabi-v7a/libbyteVC2dec.so	OK
2026-05-27 11:26:39	Analyzing apktool_out/lib/armeabi-v7a/libreschecker.so	OK
2026-05-27 11:26:39	Analyzing apktool_out/lib/armeabi-v7a/libtt_uugen_layout.so	OK
2026-05-27 11:26:39	Analyzing apktool_out/lib/armeabi-v7a/liborbuculumadapter.so	OK
2026-05-27 11:26:39	Analyzing apktool_out/lib/armeabi-v7a/liblens.so	OK

2026-05-27 11:26:39	Analyzing apktool_out/lib/armeabi-v7a/libavocadoguard.so	OK
2026-05-27 11:26:39	Analyzing apktool_out/lib/armeabi-v7a/libbase_live.so	OK
2026-05-27 11:26:39	Analyzing apktool_out/lib/armeabi-v7a/libbdhm_native.so	OK
2026-05-27 11:26:39	Analyzing apktool_out/lib/armeabi-v7a/libbcnverify.so	OK
2026-05-27 11:26:39	Analyzing apktool_out/lib/armeabi-v7a/libpumbaa-network.so	OK
2026-05-27 11:26:39	Analyzing apktool_out/lib/armeabi-v7a/libstarship_sdk.so	OK
2026-05-27 11:26:39	Analyzing apktool_out/lib/armeabi-v7a/libv8_libfull.cr.so	OK
2026-05-27 11:26:39	Analyzing apktool_out/lib/armeabi-v7a/libttmverify.so	OK
2026-05-27 11:26:39	Analyzing apktool_out/lib/armeabi-v7a/libvcn.so	OK
2026-05-27 11:26:39	Analyzing apktool_out/lib/armeabi-v7a/libfly-main-color-lib.so	OK
2026-05-27 11:26:39	Analyzing apktool_out/lib/armeabi-v7a/libshadowhook_nothing.so	OK
2026-05-27 11:26:39	Analyzing apktool_out/lib/armeabi-v7a/libarcore_sdk_c.so	OK
2026-05-27 11:26:39	Analyzing apktool_out/lib/armeabi-v7a/libByteA1NN.so	OK
2026-05-27 11:26:39	Analyzing apktool_out/lib/armeabi-v7a/libdex_df_pipo_bnpl.so	OK
2026-05-27 11:26:39	Analyzing apktool_out/lib/armeabi-v7a/libbytebench.so	OK

2026-05-27 11:26:39	Analyzing apktool_out/lib/armeabi-v7a/libCepProxy.so	OK
2026-05-27 11:26:39	Analyzing apktool_out/lib/armeabi-v7a/libconfigcenter.so	OK
2026-05-27 11:26:39	Analyzing apktool_out/lib/armeabi-v7a/libartshadowhook.so	OK
2026-05-27 11:26:39	Analyzing apktool_out/lib/armeabi-v7a/libjazz.so	OK
2026-05-27 11:26:39	Analyzing apktool_out/lib/armeabi-v7a/libdex_df_pipo_external_payments.so	OK
2026-05-27 11:26:39	Analyzing apktool_out/lib/armeabi-v7a/libnpth_tls_monitor.so	OK
2026-05-27 11:26:39	Analyzing apktool_out/lib/armeabi-v7a/libtcc2pa.so	OK
2026-05-27 11:26:39	Analyzing apktool_out/lib/armeabi-v7a/libonetex.so	OK
2026-05-27 11:26:40	Analyzing apktool_out/lib/armeabi-v7a/libtcc2pa_sdk_d.so	OK
2026-05-27 11:26:40	Analyzing apktool_out/lib/armeabi-v7a/libEffectCreatorJni.so	OK
2026-05-27 11:26:40	Analyzing apktool_out/lib/armeabi-v7a/libvideodec.so	OK
2026-05-27 11:26:40	Analyzing apktool_out/lib/armeabi-v7a/libnpth_dumper.so	OK
2026-05-27 11:26:40	Analyzing apktool_out/lib/armeabi-v7a/liblynxstarlight.so	OK
2026-05-27 11:26:40	Analyzing apktool_out/lib/armeabi-v7a/libmotion.so	OK
2026-05-27 11:26:40	Analyzing apktool_out/lib/armeabi-v7a/libpy-cv-numpycv.so	OK

2026-05-27 11:26:40	Analyzing apktool_out/lib/armeabi-v7a/libtbtboringsl.so	OK
2026-05-27 11:26:40	Analyzing apktool_out/lib/armeabi-v7a/libnetecho.so	OK
2026-05-27 11:26:40	Analyzing apktool_out/lib/armeabi-v7a/libjazz_plugin.so	OK
2026-05-27 11:26:40	Analyzing apktool_out/lib/armeabi-v7a/libsimba.so	OK
2026-05-27 11:26:40	Analyzing apktool_out/lib/armeabi-v7a/libArchive.so	OK
2026-05-27 11:26:40	Analyzing apktool_out/lib/armeabi-v7a/libres_memory.so	OK
2026-05-27 11:26:40	Analyzing apktool_out/lib/armeabi-v7a/libaudioeffect.so	OK
2026-05-27 11:26:40	Analyzing apktool_out/lib/armeabi-v7a/libsscronet.so	OK
2026-05-27 11:26:40	Analyzing apktool_out/lib/armeabi-v7a/liblynxsuit.so	OK
2026-05-27 11:26:40	Analyzing apktool_out/lib/armeabi-v7a/libstatic-webp.so	OK
2026-05-27 11:26:40	Analyzing apktool_out/lib/armeabi-v7a/libttr.so	OK
2026-05-27 11:26:40	Analyzing apktool_out/lib/armeabi-v7a/libspeechsdk.so	OK
2026-05-27 11:26:40	Analyzing apktool_out/lib/armeabi-v7a/liblynxsecurity.so	OK
2026-05-27 11:26:40	Analyzing apktool_out/lib/armeabi-v7a/liblynx_krypton.so	OK
2026-05-27 11:26:40	Analyzing apktool_out/lib/armeabi-v7a/libshadowhook.so	OK

2026-05-27 11:26:40	Analyzing apktool_out/lib/armeabi-v7a/libtexturerender_native.so	OK
2026-05-27 11:26:40	Analyzing apktool_out/lib/armeabi-v7a/libtt_c2pa_sdk.so	OK
2026-05-27 11:26:40	Analyzing apktool_out/lib/armeabi-v7a/libLAMaterialSDK.so	OK
2026-05-27 11:26:40	Analyzing apktool_out/lib/armeabi-v7a/libworker.so	OK
2026-05-27 11:26:40	Analyzing apktool_out/lib/armeabi-v7a/libnxreword.so	OK
2026-05-27 11:26:40	Analyzing apktool_out/lib/armeabi-v7a/libbytenn.so	OK
2026-05-27 11:26:40	Analyzing apktool_out/lib/armeabi-v7a/liblink_mic_sdk.so	OK
2026-05-27 11:26:40	Analyzing apktool_out/lib/armeabi-v7a/libstarship_wrapper.so	OK
2026-05-27 11:26:40	Analyzing apktool_out/lib/armeabi-v7a/libvolcenginertc.so	OK
2026-05-27 11:26:40	Analyzing apktool_out/lib/armeabi-v7a/libByteAIDT.so	OK
2026-05-27 11:26:40	Analyzing apktool_out/lib/armeabi-v7a/libjato.so	OK
2026-05-27 11:26:40	Analyzing apktool_out/lib/armeabi-v7a/libbytevc1enc.so	OK
2026-05-27 11:26:40	Analyzing apktool_out/lib/armeabi-v7a/libbytenllm-jni.so	OK
2026-05-27 11:26:40	Analyzing apktool_out/lib/armeabi-v7a/libmonitorcollector-lib.so	OK
2026-05-27 11:26:40	Analyzing apktool_out/lib/armeabi-v7a/lib_jhmp.so	OK

2026-05-27 11:26:40	Analyzing apktool_out/lib/armeabi-v7a/libkryptonaudio.so	OK
2026-05-27 11:26:40	Analyzing apktool_out/lib/armeabi-v7a/libgeckox_bspatch.so	OK
2026-05-27 11:26:40	Analyzing apktool_out/lib/armeabi-v7a/liborbuculum.so	OK
2026-05-27 11:26:40	Analyzing apktool_out/lib/armeabi-v7a/libyoga.so	OK
2026-05-27 11:26:40	Analyzing apktool_out/lib/armeabi-v7a/libnpth_unw.so	OK
2026-05-27 11:26:40	Analyzing apktool_out/lib/armeabi-v7a/libNLEditorjni.so	OK
2026-05-27 11:26:41	Analyzing apktool_out/lib/armeabi-v7a/libttvesdk_plugin.so	OK
2026-05-27 11:26:41	Analyzing apktool_out/lib/armeabi-v7a/libfile_lock.so	OK
2026-05-27 11:26:41	Analyzing apktool_out/lib/armeabi-v7a/libgodzilla-mem sponge.so	OK
2026-05-27 11:26:41	Analyzing apktool_out/lib/armeabi-v7a/libfdk-aac.so	OK
2026-05-27 11:26:41	Analyzing apktool_out/lib/armeabi-v7a/lib_jbmf.so	OK
2026-05-27 11:26:41	Analyzing apktool_out/lib/armeabi-v7a/libanimax_bytevc1.so	OK
2026-05-27 11:26:41	Analyzing apktool_out/lib/armeabi-v7a/libminizip.so	OK
2026-05-27 11:26:41	Analyzing apktool_out/lib/armeabi-v7a/libCutSamejni.so	OK
2026-05-27 11:26:41	Analyzing apktool_out/lib/armeabi-v7a/libEncryptor.so	OK

2026-05-27 11:26:41	Analyzing apktool_out/lib/armeabi-v7a/libwatson.so	OK
2026-05-27 11:26:41	Analyzing apktool_out/lib/armeabi-v7a/libotis_attrib.so	OK
2026-05-27 11:26:41	Analyzing apktool_out/lib/armeabi-v7a/liblynxbase.so	OK
2026-05-27 11:26:41	Analyzing apktool_out/lib/armeabi-v7a/libwcdb.so	OK
2026-05-27 11:26:41	Analyzing apktool_out/lib/armeabi-v7a/libttdemux.so	OK
2026-05-27 11:26:41	Analyzing apktool_out/lib/armeabi-v7a/libNLETemplateModelJni_plugin.so	OK
2026-05-27 11:26:41	Analyzing apktool_out/lib/armeabi-v7a/libpipo-security-sdk.so	OK
2026-05-27 11:26:41	Analyzing apktool_out/lib/armeabi-v7a/libCepFast.so	OK
2026-05-27 11:26:41	Analyzing apktool_out/lib/armeabi-v7a/libanrrrelief.so	OK
2026-05-27 11:26:41	Analyzing apktool_out/lib/armeabi-v7a/libDavinciResourceJni.so	OK
2026-05-27 11:26:41	Analyzing apktool_out/lib/armeabi-v7a/libfileprotect.so	OK
2026-05-27 11:26:41	Analyzing apktool_out/lib/armeabi-v7a/libnpth_repair.so	OK
2026-05-27 11:26:41	Analyzing apktool_out/lib/armeabi-v7a/libkrypton_sar.so	OK
2026-05-27 11:26:41	Analyzing apktool_out/lib/armeabi-v7a/libbmf_hydra_lite.so	OK
2026-05-27 11:26:41	Analyzing apktool_out/lib/armeabi-v7a/libquick.so	OK

2026-05-27 11:26:41	Analyzing apktool_out/lib/armeabi-v7a/libfastcv.so	OK
2026-05-27 11:26:41	Analyzing apktool_out/lib/armeabi-v7a/libBlinkCard.so	OK
2026-05-27 11:26:41	Analyzing apktool_out/lib/armeabi-v7a/libbdzstd.so	OK
2026-05-27 11:26:41	Analyzing apktool_out/lib/armeabi-v7a/libdex_df_ccdc_impl_ocr.so	OK
2026-05-27 11:26:41	Analyzing apktool_out/lib/armeabi-v7a/libbytelink.so	OK
2026-05-27 11:26:41	Analyzing apktool_out/lib/armeabi-v7a/libforestx_native_buffer.so	OK
2026-05-27 11:26:41	Analyzing apktool_out/lib/armeabi-v7a/libttmverifylite.so	OK
2026-05-27 11:26:41	Analyzing apktool_out/lib/armeabi-v7a/libbmf_mods.so	OK
2026-05-27 11:26:41	Analyzing apktool_out/lib/armeabi-v7a/libresource_monitor.so	OK
2026-05-27 11:26:41	Analyzing apktool_out/lib/armeabi-v7a/libkryptoneffect.so	OK
2026-05-27 11:26:41	Analyzing apktool_out/lib/armeabi-v7a/libptyjemalloc.so	OK
2026-05-27 11:26:41	Analyzing apktool_out/lib/armeabi-v7a/libtffmpeg.so	OK
2026-05-27 11:26:41	Analyzing apktool_out/lib/armeabi-v7a/libanimax_textra.so	OK
2026-05-27 11:26:41	Analyzing apktool_out/lib/armeabi-v7a/liblynxtrace.so	OK
2026-05-27 11:26:41	Analyzing apktool_out/lib/armeabi-v7a/libpythonA.so	OK

2026-05-27 11:26:41	Analyzing apktool_out/lib/armeabi-v7a/libgifimage.so	OK
2026-05-27 11:26:41	Analyzing apktool_out/lib/armeabi-v7a/libsysoptimizer.so	OK
2026-05-27 11:26:41	Analyzing apktool_out/lib/armeabi-v7a/libtailor.so	OK
2026-05-27 11:26:41	Analyzing apktool_out/lib/armeabi-v7a/libkryptonaum.so	OK
2026-05-27 11:26:41	Analyzing apktool_out/lib/armeabi-v7a/libdex_df_ship.so	OK
2026-05-27 11:26:41	Analyzing apktool_out/lib/armeabi-v7a/libbdmpg123.so	OK
2026-05-27 11:26:41	Analyzing apktool_out/lib/armeabi-v7a/libbd-install.so	OK
2026-05-27 11:26:41	Analyzing apktool_out/lib/armeabi-v7a/libNLEMediajni_plugin.so	OK
2026-05-27 11:26:41	Analyzing apktool_out/lib/armeabi-v7a/libiesapplogger.so	OK
2026-05-27 11:26:41	Analyzing apktool_out/lib/armeabi-v7a/libpsp_engine.so	OK
2026-05-27 11:26:41	Analyzing apktool_out/lib/armeabi-v7a/libdelta.so	OK
2026-05-27 11:26:41	Analyzing apktool_out/lib/armeabi-v7a/libNLEEditorjni_plugin.so	OK
2026-05-27 11:26:42	Analyzing apktool_out/lib/armeabi-v7a/libclient_ai_impl_jni.so	OK
2026-05-27 11:26:42	Analyzing apktool_out/lib/armeabi-v7a/libkeva.so	OK
2026-05-27 11:26:42	Analyzing apktool_out/lib/armeabi-v7a/libflipped.so	OK

2026-05-27 11:26:42	Analyzing apktool_out/lib/armeabi-v7a/libbat.so	OK
2026-05-27 11:26:42	Analyzing apktool_out/lib/armeabi-v7a/libAwplatssupport.so	OK
2026-05-27 11:26:42	Analyzing apktool_out/lib/armeabi-v7a/libttmplayer.so	OK
2026-05-27 11:26:42	Analyzing apktool_out/lib/armeabi-v7a/libBDPythonVM.so	OK
2026-05-27 11:26:42	Analyzing apktool_out/lib/armeabi-v7a/libgaia_lib.so	OK
2026-05-27 11:26:42	Analyzing apktool_out/lib/armeabi-v7a/libsliver.so	OK
2026-05-27 11:26:42	Analyzing apktool_out/lib/armeabi-v7a/libTTMStrategyCenter.so	OK
2026-05-27 11:26:42	Analyzing apktool_out/lib/armeabi-v7a/libbytennllm.so	OK
2026-05-27 11:26:42	Analyzing apktool_out/lib/armeabi-v7a/liblynx_v8_bridge.so	OK
2026-05-27 11:26:42	Analyzing apktool_out/lib/armeabi-v7a/libnativeaudio.so	OK
2026-05-27 11:26:42	Analyzing apktool_out/lib/armeabi-v7a/libskity.so	OK
2026-05-27 11:26:42	Analyzing apktool_out/lib/armeabi-v7a/libropaencrypt.so	OK
2026-05-27 11:26:42	Analyzing apktool_out/lib/armeabi-v7a/libstorage-hook.so	OK
2026-05-27 11:26:42	Analyzing apktool_out/lib/armeabi-v7a/libjson_opt.so	OK
2026-05-27 11:26:42	Analyzing apktool_out/lib/armeabi-v7a/libdex_df_pitaya.so	OK

2026-05-27 11:26:42	Analyzing apktool_out/lib/armeabi-v7a/libavmdlp2pv2.so	OK
2026-05-27 11:26:42	Analyzing apktool_out/lib/armeabi-v7a/libskbase.so	OK
2026-05-27 11:26:42	Analyzing apktool_out/lib/armeabi-v7a/libbdsword.so	OK
2026-05-27 11:26:42	Analyzing apktool_out/lib/armeabi-v7a/libttpreload.so	OK
2026-05-27 11:26:42	Analyzing apktool_out/lib/armeabi-v7a/libarcore_sdk_jni.so	OK
2026-05-27 11:26:42	Analyzing apktool_out/lib/armeabi-v7a/libttheif_dec.so	OK
2026-05-27 11:26:42	Analyzing apktool_out/lib/armeabi-v7a/libfast_engine_api_loader.so	OK
2026-05-27 11:26:42	Analyzing apktool_out/lib/armeabi-v7a/libalog.so	OK
2026-05-27 11:26:42	Analyzing apktool_out/lib/armeabi-v7a/libavmdlbase.so	OK
2026-05-27 11:26:42	Analyzing apktool_out/lib/armeabi-v7a/libEffectEditorJni.so	OK
2026-05-27 11:26:42	Analyzing apktool_out/lib/armeabi-v7a/libhelios_bm.so	OK
2026-05-27 11:26:42	Analyzing apktool_out/lib/armeabi-v7a/libnpth_bt.so	OK
2026-05-27 11:26:42	Analyzing apktool_out/lib/armeabi-v7a/libttext_lite.so	OK
2026-05-27 11:26:42	Analyzing apktool_out/lib/armeabi-v7a/libqmiVsyncHook.so	OK
2026-05-27 11:26:42	Analyzing apktool_out/lib/armeabi-v7a/libttmcaf.so	OK

2026-05-27 11:26:42	Analyzing apktool_out/lib/armeabi-v7a/libNLEResourcesDAVjni_plugin.so	OK
2026-05-27 11:26:42	Analyzing apktool_out/lib/armeabi-v7a/libAGFX.so	OK
2026-05-27 11:26:42	Analyzing apktool_out/lib/armeabi-v7a/libnpth_unwind.so	OK
2026-05-27 11:26:42	Analyzing apktool_out/lib/armeabi-v7a/libandroidx.graphics.path.so	OK
2026-05-27 11:26:42	Analyzing apktool_out/lib/armeabi-v7a/liblynx_service_api.so	OK
2026-05-27 11:26:42	Analyzing apktool_out/lib/armeabi-v7a/libbytehook.so	OK
2026-05-27 11:26:42	Analyzing apktool_out/lib/armeabi-v7a/libbmf_module_sdk.so	OK
2026-05-27 11:26:42	Analyzing apktool_out/lib/armeabi-v7a/libpns_ttmachine_adapter.so	OK
2026-05-27 11:26:42	Analyzing apktool_out/lib/armeabi-v7a/libbotsopt.so	OK
2026-05-27 11:26:42	Analyzing apktool_out/lib/armeabi-v7a/libpunch.so	OK
2026-05-27 11:26:42	Analyzing apktool_out/lib/armeabi-v7a/libvegasdk.so	OK
2026-05-27 11:26:42	Analyzing apktool_out/lib/armeabi-v7a/libbmf_hydra.so	OK
2026-05-27 11:26:42	Analyzing apktool_out/lib/armeabi-v7a/liblynx.so	OK
2026-05-27 11:26:42	Analyzing apktool_out/lib/armeabi-v7a/libanimax.so	OK
2026-05-27 11:26:42	Analyzing apktool_out/lib/armeabi-v7a/libpreload.so	OK

2026-05-27 11:26:42	Analyzing apktool_out/lib/armeabi-v7a/libimagepipeline.so	OK
2026-05-27 11:26:42	Analyzing apktool_out/lib/armeabi-v7a/libPitayaBdComponent.so	OK
2026-05-27 11:26:42	Analyzing apktool_out/lib/armeabi-v7a/librex.so	OK
2026-05-27 11:26:42	Analyzing apktool_out/lib/armeabi-v7a/libAndroidPitayaCore.so	OK
2026-05-27 11:26:42	Analyzing apktool_out/lib/armeabi-v7a/libbdheif.so	OK
2026-05-27 11:26:42	Analyzing apktool_out/lib/armeabi-v7a/libbytevc1enc10b.so	OK
2026-05-27 11:26:42	Analyzing apktool_out/lib/armeabi-v7a/liblynx_text_service.so	OK
2026-05-27 11:26:43	Analyzing apktool_out/lib/armeabi-v7a/libSmartMoviejni.so	OK
2026-05-27 11:26:43	Analyzing apktool_out/lib/armeabi-v7a/libNLEMediaRemotejni_plugin.so	OK
2026-05-27 11:26:43	Analyzing apktool_out/lib/armeabi-v7a/libnpth_logcat.so	OK
2026-05-27 11:26:43	Analyzing apktool_out/lib/armeabi-v7a/libnpth_xasan.so	OK
2026-05-27 11:26:43	Analyzing apktool_out/lib/armeabi-v7a/libc++_shared.so	OK
2026-05-27 11:26:43	Analyzing apktool_out/lib/armeabi-v7a/libzoin.so	OK
2026-05-27 11:26:43	Analyzing apktool_out/lib/armeabi-v7a/libalignpage.so	OK
2026-05-27 11:26:43	Analyzing apktool_out/lib/armeabi-v7a/libh3-java.so	OK

2026-05-27 11:26:43	Analyzing apktool_out/lib/armeabi-v7a/libnapi.so	OK
2026-05-27 11:26:43	Analyzing apktool_out/lib/armeabi-v7a/libkrypton.so	OK
2026-05-27 11:26:43	Analyzing apktool_out/lib/armeabi-v7a/libnpth_ref_monitor.so	OK
2026-05-27 11:26:43	Analyzing apktool_out/lib/armeabi-v7a/libByteVC1_dec.so	OK
2026-05-27 11:26:43	Analyzing apktool_out/lib/armeabi-v7a/libvebytevc1enc8bwrapper.so	OK
2026-05-27 11:26:43	Analyzing apktool_out/lib/armeabi-v7a/libCepAuth.so	OK
2026-05-27 11:26:43	Analyzing apktool_out/lib/armeabi-v7a/libvctfo.so	OK
2026-05-27 11:26:43	Analyzing apktool_out/lib/armeabi-v7a/libcybertron_base.so	OK
2026-05-27 11:26:43	Analyzing apktool_out/lib/armeabi-v7a/libp2plivevdp.so	OK
2026-05-27 11:26:43	Analyzing apktool_out/lib/armeabi-v7a/libffmpeg_dashdec.so	OK
2026-05-27 11:26:43	Analyzing apktool_out/lib/armeabi-v7a/libwasm.so	OK
2026-05-27 11:26:43	Analyzing apktool_out/lib/armeabi-v7a/libbytemonitor.so	OK
2026-05-27 11:26:43	Analyzing apktool_out/lib/armeabi-v7a/libserval_svg.so	OK
2026-05-27 11:26:43	Analyzing apktool_out/lib/armeabi-v7a/libartlog_monitor.so	OK
2026-05-27 11:26:43	Analyzing apktool_out/lib/armeabi-v7a/libvolcenginertc_plugin.so	OK

2026-05-27 11:26:43	Analyzing apktool_out/lib/armeabi-v7a/libCepEngine.so	OK
2026-05-27 11:26:43	Analyzing apktool_out/lib/armeabi-v7a/libttnisnative.so	OK
2026-05-27 11:26:43	Analyzing apktool_out/lib/armeabi-v7a/libdex_df_ttwbview.so	OK
2026-05-27 11:26:43	Analyzing apktool_out/lib/armeabi-v7a/libttquic.so	OK
2026-05-27 11:26:43	Analyzing apktool_out/lib/armeabi-v7a/libspeechspg.so	OK
2026-05-27 11:26:43	Analyzing apktool_out/lib/armeabi-v7a/libnpth_dl.so	OK
2026-05-27 11:26:43	Analyzing apktool_out/lib/armeabi-v7a/libbytedt.so	OK
2026-05-27 11:26:43	Analyzing apktool_out/lib/armeabi-v7a/libfast_engine.so	OK
2026-05-27 11:26:43	Analyzing apktool_out/lib/armeabi-v7a/libbytevc1enc10bwrapper.so	OK
2026-05-27 11:26:43	Analyzing apktool_out/lib/armeabi-v7a/libdex_df_live_cast.so	OK
2026-05-27 11:26:43	Analyzing apktool_out/lib/armeabi-v7a/libbytevc0.so	OK
2026-05-27 11:26:43	Analyzing apktool_out/lib/armeabi-v7a/libhmp.so	OK
2026-05-27 11:26:43	Analyzing apktool_out/lib/armeabi-v7a/libpns_crypto.so	OK
2026-05-27 11:26:43	Analyzing apktool_out/lib/armeabi-v7a/libPitayaTTPPolicy.so	OK
2026-05-27 11:26:43	Analyzing apktool_out/lib/armeabi-v7a/libopus.so	OK

2026-05-27 11:26:43	Analyzing apktool_out/lib/armeabi-v7a/libTTMachineCore.so	OK
2026-05-27 11:26:43	Analyzing apktool_out/lib/armeabi-v7a/libNLEMediaRemotejni.so	OK
2026-05-27 11:26:43	Analyzing apktool_out/lib/armeabi-v7a/libvcbasekit.so	OK
2026-05-27 11:26:43	Analyzing apktool_out/lib/armeabi-v7a/libug_share_sort.so	OK
2026-05-27 11:26:43	Analyzing apktool_out/lib/armeabi-v7a/libBDMicroPythonVM.so	OK
2026-05-27 11:26:43	Analyzing apktool_out/lib/armeabi-v7a/liblivestrategy.so	OK
2026-05-27 11:26:43	Analyzing apktool_out/lib/armeabi-v7a/libspeechepg.so	OK
2026-05-27 11:26:43	Analyzing apktool_out/lib/armeabi-v7a/libbdvideouploader.so	OK
2026-05-27 11:26:43	Analyzing apktool_out/lib/armeabi-v7a/librtmglobal.so	OK
2026-05-27 11:26:44	Analyzing apktool_out/lib/armeabi-v7a/libbuffer.so	OK
2026-05-27 11:26:44	Analyzing apktool_out/lib/armeabi-v7a/libfast_engine_api.so	OK
2026-05-27 11:26:44	Analyzing apktool_out/lib/armeabi-v7a/libworkerv8.so	OK
2026-05-27 11:26:44	Analyzing apktool_out/lib/armeabi-v7a/libeffect_plugin.so	OK
2026-05-27 11:26:44	Analyzing apktool_out/lib/armeabi-v7a/libbytennwrapper.so	OK
2026-05-27 11:26:44	Analyzing apktool_out/lib/armeabi-v7a/libicu.so	OK

2026-05-27 11:26:44	Analyzing apktool_out/lib/armeabi-v7a/libdex_df_music_dsp.so	OK
2026-05-27 11:26:44	Analyzing apktool_out/lib/armeabi-v7a/libnative-filters.so	OK
2026-05-27 11:26:44	Analyzing apktool_out/lib/armeabi-v7a/libpsiencript.so	OK
2026-05-27 11:26:44	Analyzing apktool_out/lib/armeabi-v7a/liblynx_markdown.so	OK
2026-05-27 11:26:44	Analyzing apktool_out/lib/armeabi-v7a/libjniidispach.so	OK
2026-05-27 11:26:44	Analyzing apktool_out/lib/armeabi-v7a/libmedia.so	OK
2026-05-27 11:26:44	Analyzing apktool_out/lib/armeabi-v7a/libttcrypto.so	OK
2026-05-27 11:26:44	Analyzing apktool_out/lib/armeabi-v7a/libspeechengine.so	OK
2026-05-27 11:26:44	Analyzing apktool_out/lib/armeabi-v7a/libxtrace.so	OK
2026-05-27 11:26:44	Analyzing apktool_out/lib/armeabi-v7a/libpy-numpy.so	OK
2026-05-27 11:26:44	Analyzing apktool_out/lib/armeabi-v7a/liboecsec_ov.so	OK
2026-05-27 11:26:44	Analyzing apktool_out/lib/armeabi-v7a/libvoip.so	OK
2026-05-27 11:26:44	Analyzing apktool_out/lib/armeabi-v7a/liburiparser.so	OK
2026-05-27 11:26:44	Analyzing apktool_out/lib/armeabi-v7a/libmemrelief.so	OK
2026-05-27 11:26:44	Analyzing apktool_out/lib/armeabi-v7a/libCepAST.so	OK

2026-05-27 11:26:44	Analyzing apktool_out/lib/armeabi-v7a/libEffectEditorABTestjni.so	OK
2026-05-27 11:26:44	Analyzing apktool_out/lib/armeabi-v7a/libNLEResourcesDAVjni.so	OK
2026-05-27 11:26:44	Analyzing apktool_out/lib/armeabi-v7a/libNLEMediaPublicjni.so	OK
2026-05-27 11:26:44	Analyzing apktool_out/lib/armeabi-v7a/libbtch_collection.so	OK
2026-05-27 11:26:44	Analyzing apktool_out/lib/armeabi-v7a/libaudio_fingerprint_sdk.so	OK
2026-05-27 11:26:44	Analyzing apktool_out/lib/armeabi-v7a/libart_sym.so	OK
2026-05-27 11:26:44	Analyzing apktool_out/lib/armeabi-v7a/libnpth_fd_tracker.so	OK
2026-05-27 11:26:44	Analyzing apktool_out/lib/armeabi-v7a/libkomprese-decompressor.so	OK
2026-05-27 11:26:44	Analyzing apktool_out/lib/armeabi-v7a/libmmt.so	OK
2026-05-27 11:26:44	Analyzing apktool_out/lib/armeabi-v7a/libapplog_rust.so	OK
2026-05-27 11:26:44	Analyzing apktool_out/lib/armeabi-v7a/libwhisper.so	OK
2026-05-27 11:26:44	Analyzing apktool_out/lib/armeabi-v7a/libnpth.so	OK
2026-05-27 11:26:44	Analyzing apktool_out/lib/armeabi-v7a/libprofiler.so	OK
2026-05-27 11:26:44	Analyzing apktool_out/lib/armeabi-v7a/libanimax_napi.so	OK
2026-05-27 11:26:44	Analyzing apktool_out/lib/armeabi-v7a/libyuv.so	OK

2026-05-27 11:26:44	Analyzing apktool_out/lib/armeabi-v7a/libbach-sdk-jni.so	OK
2026-05-27 11:26:44	Analyzing apktool_out/lib/armeabi-v7a/libmetasec_ov.so	OK
2026-05-27 11:26:44	Analyzing apktool_out/lib/armeabi-v7a/libanrthanos.so	OK
2026-05-27 11:26:44	Analyzing apktool_out/lib/armeabi-v7a/libAwebviewbytedance.so	OK
2026-05-27 11:26:45	Analyzing apktool_out/lib/armeabi-v7a/libnewep.so	OK
2026-05-27 11:26:45	Analyzing apktool_out/lib/armeabi-v7a/libNLETemplateModeljni.so	OK
2026-05-27 11:26:45	Analyzing apktool_out/lib/armeabi-v7a/libNLEMediaPublicjni_plugin.so	OK
2026-05-27 11:26:45	Analyzing apktool_out/lib/armeabi-v7a/libvcnverifylite.so	OK
2026-05-27 11:26:45	Analyzing apktool_out/lib/armeabi-v7a/libNLEMediajni.so	OK
2026-05-27 11:26:45	Analyzing apktool_out/lib/armeabi-v7a/libflock-lib.so	OK
2026-05-27 11:26:45	Analyzing apktool_out/lib/armeabi-v7a/libnapi_v8.so	OK
2026-05-27 11:26:45	Analyzing apktool_out/lib/armeabi-v7a/libbvcparser.so	OK
2026-05-27 11:26:45	Analyzing apktool_out/lib/armeabi-v7a/libjarvis-metrics.so	OK
2026-05-27 11:26:45	Analyzing apktool_out/lib/armeabi-v7a/libcrashpad_handler_trampoline.so	OK
2026-05-27 11:26:45	Analyzing apktool_out/lib/armeabi-v7a/libkryptonremote.so	OK

2026-05-27 11:26:45	Analyzing apktool_out/lib/armeabi-v7a/libgodzilla-sysopt.so	OK
2026-05-27 11:26:45	Analyzing apktool_out/lib/armeabi-v7a/libTTNativeML.so	OK
2026-05-27 11:26:45	Analyzing lib/arm64-v8a/libbyteVC2dec.so	OK
2026-05-27 11:26:45	Analyzing lib/arm64-v8a/libreschecker.so	OK
2026-05-27 11:26:45	Analyzing lib/arm64-v8a/libtt_uken_layout.so	OK
2026-05-27 11:26:45	Analyzing lib/arm64-v8a/liborbuculumadapter.so	OK
2026-05-27 11:26:45	Analyzing lib/arm64-v8a/liblens.so	OK
2026-05-27 11:26:45	Analyzing lib/arm64-v8a/libavocadoguard.so	OK
2026-05-27 11:26:46	Analyzing lib/arm64-v8a/libbase_live.so	OK
2026-05-27 11:26:46	Analyzing lib/arm64-v8a/libbdhm_native.so	OK
2026-05-27 11:26:46	Analyzing lib/arm64-v8a/libcnverify.so	OK
2026-05-27 11:26:46	Analyzing lib/arm64-v8a/libpumbaa-network.so	OK
2026-05-27 11:26:46	Analyzing lib/arm64-v8a/libstarship_sdk.so	OK
2026-05-27 11:26:46	Analyzing lib/arm64-v8a/libv8_libfull.cr.so	OK
2026-05-27 11:26:46	Analyzing lib/arm64-v8a/libttmverify.so	OK

2026-05-27 11:26:46	Analyzing lib/arm64-v8a/libvcn.so	OK
2026-05-27 11:26:46	Analyzing lib/arm64-v8a/libfly-main-color-lib.so	OK
2026-05-27 11:26:46	Analyzing lib/arm64-v8a/libshadowhook_nothing.so	OK
2026-05-27 11:26:46	Analyzing lib/arm64-v8a/libarccore_sdk_c.so	OK
2026-05-27 11:26:46	Analyzing lib/arm64-v8a/libByteAlNN.so	OK
2026-05-27 11:26:46	Analyzing lib/arm64-v8a/libdex_df_pipo_bnpl.so	OK
2026-05-27 11:26:46	Analyzing lib/arm64-v8a/libbytebench.so	OK
2026-05-27 11:26:46	Analyzing lib/arm64-v8a/libCepProxy.so	OK
2026-05-27 11:26:46	Analyzing lib/arm64-v8a/libconfigcenter.so	OK
2026-05-27 11:26:46	Analyzing lib/arm64-v8a/libartshadowhook.so	OK
2026-05-27 11:26:46	Analyzing lib/arm64-v8a/libjazz.so	OK
2026-05-27 11:26:46	Analyzing lib/arm64-v8a/libdex_df_pipo_external_payments.so	OK
2026-05-27 11:26:46	Analyzing lib/arm64-v8a/libnpth_tls_monitor.so	OK
2026-05-27 11:26:46	Analyzing lib/arm64-v8a/libttc2pa.so	OK
2026-05-27 11:26:46	Analyzing lib/arm64-v8a/libonetex.so	OK

2026-05-27 11:26:46	Analyzing lib/arm64-v8a/libtt_c2pa_sdk_d.so	OK
2026-05-27 11:26:46	Analyzing lib/arm64-v8a/libEffectCreatorJni.so	OK
2026-05-27 11:26:46	Analyzing lib/arm64-v8a/libvideodec.so	OK
2026-05-27 11:26:46	Analyzing lib/arm64-v8a/libnpth_dumper.so	OK
2026-05-27 11:26:46	Analyzing lib/arm64-v8a/liblynxstarlight.so	OK
2026-05-27 11:26:46	Analyzing lib/arm64-v8a/libmotion.so	OK
2026-05-27 11:26:46	Analyzing lib/arm64-v8a/libpy-cv-numpycv.so	OK
2026-05-27 11:26:46	Analyzing lib/arm64-v8a/libtbboringssl.so	OK
2026-05-27 11:26:46	Analyzing lib/arm64-v8a/libnetecho.so	OK
2026-05-27 11:26:47	Analyzing lib/arm64-v8a/libjazz_plugin.so	OK
2026-05-27 11:26:47	Analyzing lib/arm64-v8a/libsimba.so	OK
2026-05-27 11:26:47	Analyzing lib/arm64-v8a/libArchive.so	OK
2026-05-27 11:26:47	Analyzing lib/arm64-v8a/libres_memory.so	OK
2026-05-27 11:26:47	Analyzing lib/arm64-v8a/libaudioeffect.so	OK
2026-05-27 11:26:47	Analyzing lib/arm64-v8a/libsscronet.so	OK

2026-05-27 11:26:47	Analyzing lib/arm64-v8a/liblynxsuit.so	OK
2026-05-27 11:26:47	Analyzing lib/arm64-v8a/libstatic-webp.so	OK
2026-05-27 11:26:47	Analyzing lib/arm64-v8a/libttr.so	OK
2026-05-27 11:26:47	Analyzing lib/arm64-v8a/libspeechsdk.so	OK
2026-05-27 11:26:47	Analyzing lib/arm64-v8a/liblynxsecurity.so	OK
2026-05-27 11:26:47	Analyzing lib/arm64-v8a/liblynx_krypton.so	OK
2026-05-27 11:26:47	Analyzing lib/arm64-v8a/libshadowhook.so	OK
2026-05-27 11:26:47	Analyzing lib/arm64-v8a/libtexturerender_native.so	OK
2026-05-27 11:26:47	Analyzing lib/arm64-v8a/libtt_c2pa_sdk.so	OK
2026-05-27 11:26:47	Analyzing lib/arm64-v8a/libLAMaterialSDK.so	OK
2026-05-27 11:26:47	Analyzing lib/arm64-v8a/libworker.so	OK
2026-05-27 11:26:47	Analyzing lib/arm64-v8a/libnxreword.so	OK
2026-05-27 11:26:47	Analyzing lib/arm64-v8a/libbytenn.so	OK
2026-05-27 11:26:47	Analyzing lib/arm64-v8a/liblink_mic_sdk.so	OK
2026-05-27 11:26:47	Analyzing lib/arm64-v8a/libstarship_wrapper.so	OK

2026-05-27 11:26:47	Analyzing lib/arm64-v8a/libvolcenginertc.so	OK
2026-05-27 11:26:47	Analyzing lib/arm64-v8a/libByteAIDT.so	OK
2026-05-27 11:26:47	Analyzing lib/arm64-v8a/libjato.so	OK
2026-05-27 11:26:47	Analyzing lib/arm64-v8a/libbytevc1enc.so	OK
2026-05-27 11:26:47	Analyzing lib/arm64-v8a/libbytennllm-jni.so	OK
2026-05-27 11:26:47	Analyzing lib/arm64-v8a/libmonitorcollector-lib.so	OK
2026-05-27 11:26:47	Analyzing lib/arm64-v8a/lib_jhmp.so	OK
2026-05-27 11:26:47	Analyzing lib/arm64-v8a/libkryptonaudio.so	OK
2026-05-27 11:26:47	Analyzing lib/arm64-v8a/libgeckox_bspatch.so	OK
2026-05-27 11:26:47	Analyzing lib/arm64-v8a/liborbuculum.so	OK
2026-05-27 11:26:47	Analyzing lib/arm64-v8a/libyoga.so	OK
2026-05-27 11:26:47	Analyzing lib/arm64-v8a/libnpth_unw.so	OK
2026-05-27 11:26:47	Analyzing lib/arm64-v8a/libNLEditorjni.so	OK
2026-05-27 11:26:47	Analyzing lib/arm64-v8a/libtvesdk_plugin.so	OK
2026-05-27 11:26:48	Analyzing lib/arm64-v8a/libfile_lock.so	OK

2026-05-27 11:26:48	Analyzing lib/arm64-v8a/libgodzilla-mem sponge.so	OK
2026-05-27 11:26:48	Analyzing lib/arm64-v8a/libfdk-aac.so	OK
2026-05-27 11:26:48	Analyzing lib/arm64-v8a/libjarvis-trace.so	OK
2026-05-27 11:26:48	Analyzing lib/arm64-v8a/lib_jbmf.so	OK
2026-05-27 11:26:48	Analyzing lib/arm64-v8a/libanimax_bytevc1.so	OK
2026-05-27 11:26:48	Analyzing lib/arm64-v8a/libminizip.so	OK
2026-05-27 11:26:48	Analyzing lib/arm64-v8a/libCutSameJni.so	OK
2026-05-27 11:26:48	Analyzing lib/arm64-v8a/libEncryptor.so	OK
2026-05-27 11:26:48	Analyzing lib/arm64-v8a/libwatson.so	OK
2026-05-27 11:26:48	Analyzing lib/arm64-v8a/libotis_attrib.so	OK
2026-05-27 11:26:48	Analyzing lib/arm64-v8a/liblynxbase.so	OK
2026-05-27 11:26:48	Analyzing lib/arm64-v8a/libwcdm.so	OK
2026-05-27 11:26:48	Analyzing lib/arm64-v8a/libttdemux.so	OK
2026-05-27 11:26:48	Analyzing lib/arm64-v8a/libNLETemplateModelJni_plugin.so	OK
2026-05-27 11:26:48	Analyzing lib/arm64-v8a/libpipo-security-sdk.so	OK

2026-05-27 11:26:48	Analyzing lib/arm64-v8a/libCepFast.so	OK
2026-05-27 11:26:48	Analyzing lib/arm64-v8a/libanrrelief.so	OK
2026-05-27 11:26:48	Analyzing lib/arm64-v8a/libDavinciResourceJni.so	OK
2026-05-27 11:26:48	Analyzing lib/arm64-v8a/libfileprotect.so	OK
2026-05-27 11:26:48	Analyzing lib/arm64-v8a/libnpth_repair.so	OK
2026-05-27 11:26:48	Analyzing lib/arm64-v8a/libkrypton_sar.so	OK
2026-05-27 11:26:48	Analyzing lib/arm64-v8a/libbmf_hydra_lite.so	OK
2026-05-27 11:26:48	Analyzing lib/arm64-v8a/libquick.so	OK
2026-05-27 11:26:48	Analyzing lib/arm64-v8a/libfastcv.so	OK
2026-05-27 11:26:48	Analyzing lib/arm64-v8a/libBlinkCard.so	OK
2026-05-27 11:26:48	Analyzing lib/arm64-v8a/libbdzstd.so	OK
2026-05-27 11:26:48	Analyzing lib/arm64-v8a/libdex_df_ccdc_impl_ocr.so	OK
2026-05-27 11:26:48	Analyzing lib/arm64-v8a/libbytelink.so	OK
2026-05-27 11:26:48	Analyzing lib/arm64-v8a/libforestx_native_buffer.so	OK
2026-05-27 11:26:48	Analyzing lib/arm64-v8a/libttmverifylite.so	OK

2026-05-27 11:26:48	Analyzing lib/arm64-v8a/libbmf_mods.so	OK
2026-05-27 11:26:48	Analyzing lib/arm64-v8a/libresource_monitor.so	OK
2026-05-27 11:26:48	Analyzing lib/arm64-v8a/libkryptoneffect.so	OK
2026-05-27 11:26:48	Analyzing lib/arm64-v8a/libptyjemalloc.so	OK
2026-05-27 11:26:48	Analyzing lib/arm64-v8a/libtffmpeg.so	OK
2026-05-27 11:26:48	Analyzing lib/arm64-v8a/libanimax_extra.so	OK
2026-05-27 11:26:48	Analyzing lib/arm64-v8a/liblynxtrace.so	OK
2026-05-27 11:26:48	Analyzing lib/arm64-v8a/libpythonA.so	OK
2026-05-27 11:26:48	Analyzing lib/arm64-v8a/libgifimage.so	OK
2026-05-27 11:26:48	Analyzing lib/arm64-v8a/libsysoptimizer.so	OK
2026-05-27 11:26:48	Analyzing lib/arm64-v8a/libtailor.so	OK
2026-05-27 11:26:48	Analyzing lib/arm64-v8a/libkryptonaurem.so	OK
2026-05-27 11:26:49	Analyzing lib/arm64-v8a/libdex_df_ship.so	OK
2026-05-27 11:26:49	Analyzing lib/arm64-v8a/libbdmpg123.so	OK
2026-05-27 11:26:49	Analyzing lib/arm64-v8a/libbd-install.so	OK

2026-05-27 11:26:49	Analyzing lib/arm64-v8a/libNLEMediajni_plugin.so	OK
2026-05-27 11:26:49	Analyzing lib/arm64-v8a/libiesapplogger.so	OK
2026-05-27 11:26:49	Analyzing lib/arm64-v8a/libpsp_engine.so	OK
2026-05-27 11:26:49	Analyzing lib/arm64-v8a/libdelta.so	OK
2026-05-27 11:26:49	Analyzing lib/arm64-v8a/libNLEEditorjni_plugin.so	OK
2026-05-27 11:26:49	Analyzing lib/arm64-v8a/libclient_ai_impl_jni.so	OK
2026-05-27 11:26:49	Analyzing lib/arm64-v8a/libnpth_fp_unw.so	OK
2026-05-27 11:26:49	Analyzing lib/arm64-v8a/libkeva.so	OK
2026-05-27 11:26:49	Analyzing lib/arm64-v8a/libflipped.so	OK
2026-05-27 11:26:49	Analyzing lib/arm64-v8a/libbat.so	OK
2026-05-27 11:26:49	Analyzing lib/arm64-v8a/libAwplatssupport.so	OK
2026-05-27 11:26:49	Analyzing lib/arm64-v8a/libttmplayer.so	OK
2026-05-27 11:26:49	Analyzing lib/arm64-v8a/libBDPythonVM.so	OK
2026-05-27 11:26:49	Analyzing lib/arm64-v8a/libgaia_lib.so	OK
2026-05-27 11:26:49	Analyzing lib/arm64-v8a/libsliver.so	OK

2026-05-27 11:26:49	Analyzing lib/arm64-v8a/libTTMStrategyCenter.so	OK
2026-05-27 11:26:49	Analyzing lib/arm64-v8a/libbytennllm.so	OK
2026-05-27 11:26:49	Analyzing lib/arm64-v8a/liblynx_v8_bridge.so	OK
2026-05-27 11:26:49	Analyzing lib/arm64-v8a/libnativeaudio.so	OK
2026-05-27 11:26:49	Analyzing lib/arm64-v8a/libskity.so	OK
2026-05-27 11:26:49	Analyzing lib/arm64-v8a/libropaencrypt.so	OK
2026-05-27 11:26:49	Analyzing lib/arm64-v8a/libstorage-hook.so	OK
2026-05-27 11:26:49	Analyzing lib/arm64-v8a/libjson_opt.so	OK
2026-05-27 11:26:49	Analyzing lib/arm64-v8a/libdex_df_pitaya.so	OK
2026-05-27 11:26:49	Analyzing lib/arm64-v8a/libavmdlp2pv2.so	OK
2026-05-27 11:26:49	Analyzing lib/arm64-v8a/libskbase.so	OK
2026-05-27 11:26:49	Analyzing lib/arm64-v8a/libbdsword.so	OK
2026-05-27 11:26:49	Analyzing lib/arm64-v8a/libttpreload.so	OK
2026-05-27 11:26:49	Analyzing lib/arm64-v8a/libarc_core_sdk_jni.so	OK
2026-05-27 11:26:49	Analyzing lib/arm64-v8a/libttheif_dec.so	OK

2026-05-27 11:26:49	Analyzing lib/arm64-v8a/libfast_engine_api_loader.so	OK
2026-05-27 11:26:49	Analyzing lib/arm64-v8a/libalog.so	OK
2026-05-27 11:26:49	Analyzing lib/arm64-v8a/libavmdlbase.so	OK
2026-05-27 11:26:49	Analyzing lib/arm64-v8a/libEffectEditorJni.so	OK
2026-05-27 11:26:49	Analyzing lib/arm64-v8a/libhelios_bm.so	OK
2026-05-27 11:26:49	Analyzing lib/arm64-v8a/libnpth_bt.so	OK
2026-05-27 11:26:49	Analyzing lib/arm64-v8a/libtttext_lite.so	OK
2026-05-27 11:26:49	Analyzing lib/arm64-v8a/libqmiVsyncHook.so	OK
2026-05-27 11:26:49	Analyzing lib/arm64-v8a/libttmcmf.so	OK
2026-05-27 11:26:49	Analyzing lib/arm64-v8a/libNLEResourcesDAVJni_plugin.so	OK
2026-05-27 11:26:49	Analyzing lib/arm64-v8a/libAGFX.so	OK
2026-05-27 11:26:50	Analyzing lib/arm64-v8a/libnpth_unwind.so	OK
2026-05-27 11:26:50	Analyzing lib/arm64-v8a/libandroidx.graphics.path.so	OK
2026-05-27 11:26:50	Analyzing lib/arm64-v8a/liblynx_service_api.so	OK
2026-05-27 11:26:50	Analyzing lib/arm64-v8a/libbytehook.so	OK

2026-05-27 11:26:50	Analyzing lib/arm64-v8a/libbmf_module_sdk.so	OK
2026-05-27 11:26:50	Analyzing lib/arm64-v8a/libpns_ttmachine_adapter.so	OK
2026-05-27 11:26:50	Analyzing lib/arm64-v8a/libotisoapt.so	OK
2026-05-27 11:26:50	Analyzing lib/arm64-v8a/libpunch.so	OK
2026-05-27 11:26:50	Analyzing lib/arm64-v8a/libvegasdk.so	OK
2026-05-27 11:26:50	Analyzing lib/arm64-v8a/libbmf_hydra.so	OK
2026-05-27 11:26:50	Analyzing lib/arm64-v8a/liblynx.so	OK
2026-05-27 11:26:50	Analyzing lib/arm64-v8a/libanimax.so	OK
2026-05-27 11:26:50	Analyzing lib/arm64-v8a/libpreload.so	OK
2026-05-27 11:26:50	Analyzing lib/arm64-v8a/libimagepipeline.so	OK
2026-05-27 11:26:50	Analyzing lib/arm64-v8a/libPitayaBdComponent.so	OK
2026-05-27 11:26:50	Analyzing lib/arm64-v8a/librex.so	OK
2026-05-27 11:26:50	Analyzing lib/arm64-v8a/libAndroidPitayaCore.so	OK
2026-05-27 11:26:50	Analyzing lib/arm64-v8a/libbdheif.so	OK
2026-05-27 11:26:50	Analyzing lib/arm64-v8a/libbytevc1enc10b.so	OK

2026-05-27 11:26:50	Analyzing lib/arm64-v8a/liblynx_text_service.so	OK
2026-05-27 11:26:50	Analyzing lib/arm64-v8a/libSmartMoviejni.so	OK
2026-05-27 11:26:50	Analyzing lib/arm64-v8a/libNLEMediaRemotejni_plugin.so	OK
2026-05-27 11:26:50	Analyzing lib/arm64-v8a/libnpth_logcat.so	OK
2026-05-27 11:26:50	Analyzing lib/arm64-v8a/libnpth_xasan.so	OK
2026-05-27 11:26:50	Analyzing lib/arm64-v8a/libc++_shared.so	OK
2026-05-27 11:26:50	Analyzing lib/arm64-v8a/libzoin.so	OK
2026-05-27 11:26:50	Analyzing lib/arm64-v8a/libalignpage.so	OK
2026-05-27 11:26:50	Analyzing lib/arm64-v8a/libh3-java.so	OK
2026-05-27 11:26:50	Analyzing lib/arm64-v8a/libnapi.so	OK
2026-05-27 11:26:50	Analyzing lib/arm64-v8a/libkrypton.so	OK
2026-05-27 11:26:50	Analyzing lib/arm64-v8a/libnpth_ref_monitor.so	OK
2026-05-27 11:26:50	Analyzing lib/arm64-v8a/libByteVC1_dec.so	OK
2026-05-27 11:26:50	Analyzing lib/arm64-v8a/libbytevc1enc8bwrapper.so	OK
2026-05-27 11:26:50	Analyzing lib/arm64-v8a/libCepAuth.so	OK

2026-05-27 11:26:50	Analyzing lib/arm64-v8a/libvctfo.so	OK
2026-05-27 11:26:51	Analyzing lib/arm64-v8a/libcybertron_base.so	OK
2026-05-27 11:26:51	Analyzing lib/arm64-v8a/libp2plivevdp.so	OK
2026-05-27 11:26:51	Analyzing lib/arm64-v8a/libffmpeg_dashdec.so	OK
2026-05-27 11:26:51	Analyzing lib/arm64-v8a/libwasm.so	OK
2026-05-27 11:26:51	Analyzing lib/arm64-v8a/libbyteonitor.so	OK
2026-05-27 11:26:51	Analyzing lib/arm64-v8a/libserval_svg.so	OK
2026-05-27 11:26:51	Analyzing lib/arm64-v8a/libartlog_monitor.so	OK
2026-05-27 11:26:51	Analyzing lib/arm64-v8a/libvolcenginertc_plugin.so	OK
2026-05-27 11:26:51	Analyzing lib/arm64-v8a/libCepEngine.so	OK
2026-05-27 11:26:51	Analyzing lib/arm64-v8a/libttninisnative.so	OK
2026-05-27 11:26:51	Analyzing lib/arm64-v8a/libdex_df_ttwebview.so	OK
2026-05-27 11:26:51	Analyzing lib/arm64-v8a/libttquic.so	OK
2026-05-27 11:26:51	Analyzing lib/arm64-v8a/libspeechspg.so	OK
2026-05-27 11:26:51	Analyzing lib/arm64-v8a/libnpth_dl.so	OK

2026-05-27 11:26:51	Analyzing lib/arm64-v8a/libbytedt.so	OK
2026-05-27 11:26:51	Analyzing lib/arm64-v8a/libfast_engine.so	OK
2026-05-27 11:26:51	Analyzing lib/arm64-v8a/libbytevc1enc10bwrapper.so	OK
2026-05-27 11:26:51	Analyzing lib/arm64-v8a/libdex_df_live_cast.so	OK
2026-05-27 11:26:51	Analyzing lib/arm64-v8a/libbytevc0.so	OK
2026-05-27 11:26:51	Analyzing lib/arm64-v8a/libhmp.so	OK
2026-05-27 11:26:51	Analyzing lib/arm64-v8a/libpns_crypto.so	OK
2026-05-27 11:26:51	Analyzing lib/arm64-v8a/libPitayaTTPPolicy.so	OK
2026-05-27 11:26:51	Analyzing lib/arm64-v8a/libopus.so	OK
2026-05-27 11:26:51	Analyzing lib/arm64-v8a/libTTMachineCore.so	OK
2026-05-27 11:26:51	Analyzing lib/arm64-v8a/libNLEMediaRemotejni.so	OK
2026-05-27 11:26:51	Analyzing lib/arm64-v8a/libvcbasekit.so	OK
2026-05-27 11:26:51	Analyzing lib/arm64-v8a/libug_share_sort.so	OK
2026-05-27 11:26:51	Analyzing lib/arm64-v8a/libBDMicroPythonVM.so	OK
2026-05-27 11:26:51	Analyzing lib/arm64-v8a/liblivestrategy.so	OK

2026-05-27 11:26:51	Analyzing lib/arm64-v8a/libspeechepg.so	OK
2026-05-27 11:26:51	Analyzing lib/arm64-v8a/libbdvideouploader.so	OK
2026-05-27 11:26:51	Analyzing lib/arm64-v8a/librtmglobal.so	OK
2026-05-27 11:26:52	Analyzing lib/arm64-v8a/libbuffer.so	OK
2026-05-27 11:26:52	Analyzing lib/arm64-v8a/libfast_engine_api.so	OK
2026-05-27 11:26:52	Analyzing lib/arm64-v8a/libworkerv8.so	OK
2026-05-27 11:26:52	Analyzing lib/arm64-v8a/libeffect_plugin.so	OK
2026-05-27 11:26:52	Analyzing lib/arm64-v8a/libbytennwrapper.so	OK
2026-05-27 11:26:52	Analyzing lib/arm64-v8a/libicu.so	OK
2026-05-27 11:26:52	Analyzing lib/arm64-v8a/libdex_df_music_dsp.so	OK
2026-05-27 11:26:52	Analyzing lib/arm64-v8a/libnative-filters.so	OK
2026-05-27 11:26:52	Analyzing lib/arm64-v8a/libpsiencript.so	OK
2026-05-27 11:26:52	Analyzing lib/arm64-v8a/liblynx_markdown.so	OK
2026-05-27 11:26:52	Analyzing lib/arm64-v8a/libjnidispatch.so	OK
2026-05-27 11:26:52	Analyzing lib/arm64-v8a/libmedia.so	OK

2026-05-27 11:26:52	Analyzing lib/arm64-v8a/libttcrypto.so	OK
2026-05-27 11:26:52	Analyzing lib/arm64-v8a/libspeechengine.so	OK
2026-05-27 11:26:52	Analyzing lib/arm64-v8a/libxtrace.so	OK
2026-05-27 11:26:52	Analyzing lib/arm64-v8a/libpy-numpy.so	OK
2026-05-27 11:26:52	Analyzing lib/arm64-v8a/liboecsec_ov.so	OK
2026-05-27 11:26:52	Analyzing lib/arm64-v8a/libvoip.so	OK
2026-05-27 11:26:52	Analyzing lib/arm64-v8a/liburiparser.so	OK
2026-05-27 11:26:52	Analyzing lib/arm64-v8a/libmemrelief.so	OK
2026-05-27 11:26:52	Analyzing lib/arm64-v8a/libCepAST.so	OK
2026-05-27 11:26:52	Analyzing lib/arm64-v8a/libEffectEditorABTestjni.so	OK
2026-05-27 11:26:52	Analyzing lib/arm64-v8a/libNLEResourcesDAVjni.so	OK
2026-05-27 11:26:52	Analyzing lib/arm64-v8a/libNLEMediaPublicjni.so	OK
2026-05-27 11:26:52	Analyzing lib/arm64-v8a/libbtch_collection.so	OK
2026-05-27 11:26:52	Analyzing lib/arm64-v8a/libaudio_fingerprint_sdk.so	OK
2026-05-27 11:26:53	Analyzing lib/arm64-v8a/libart_sym.so	OK

2026-05-27 11:26:53	Analyzing lib/arm64-v8a/libnpth_fd_tracker.so	OK
2026-05-27 11:26:53	Analyzing lib/arm64-v8a/libkomprese-decompressor.so	OK
2026-05-27 11:26:53	Analyzing lib/arm64-v8a/libmmt.so	OK
2026-05-27 11:26:53	Analyzing lib/arm64-v8a/libapplog_rust.so	OK
2026-05-27 11:26:53	Analyzing lib/arm64-v8a/libwhisper.so	OK
2026-05-27 11:26:53	Analyzing lib/arm64-v8a/libnpth.so	OK
2026-05-27 11:26:53	Analyzing lib/arm64-v8a/libprofiler.so	OK
2026-05-27 11:26:53	Analyzing lib/arm64-v8a/libanimax_napi.so	OK
2026-05-27 11:26:53	Analyzing lib/arm64-v8a/libyuv.so	OK
2026-05-27 11:26:53	Analyzing lib/arm64-v8a/libbach-sdk-jni.so	OK
2026-05-27 11:26:53	Analyzing lib/arm64-v8a/libmetasec_ov.so	OK
2026-05-27 11:26:53	Analyzing lib/arm64-v8a/libanrthanos.so	OK
2026-05-27 11:26:53	Analyzing lib/arm64-v8a/libAwebviewbytedance.so	OK
2026-05-27 11:26:54	Analyzing lib/arm64-v8a/libnewep.so	OK
2026-05-27 11:26:54	Analyzing lib/arm64-v8a/libNLETemplateModeljni.so	OK

2026-05-27 11:26:54	Analyzing lib/arm64-v8a/libNLEMediaPublicjni_plugin.so	OK
2026-05-27 11:26:54	Analyzing lib/arm64-v8a/libvcnverifylite.so	OK
2026-05-27 11:26:54	Analyzing lib/arm64-v8a/libNLEMediajni.so	OK
2026-05-27 11:26:54	Analyzing lib/arm64-v8a/libflock-lib.so	OK
2026-05-27 11:26:54	Analyzing lib/arm64-v8a/libnapi_v8.so	OK
2026-05-27 11:26:54	Analyzing lib/arm64-v8a/libbvcparser.so	OK
2026-05-27 11:26:54	Analyzing lib/arm64-v8a/libjarvis-metrics.so	OK
2026-05-27 11:26:54	Analyzing lib/arm64-v8a/libcrashpad_handler_trampoline.so	OK
2026-05-27 11:26:54	Analyzing lib/arm64-v8a/libkryptonremote.so	OK
2026-05-27 11:26:54	Analyzing lib/arm64-v8a/libgodzilla-sysopt.so	OK
2026-05-27 11:26:54	Analyzing lib/arm64-v8a/libTTNativeML.so	OK
2026-05-27 11:26:54	Analyzing lib/armeabi-v7a/libbyteVC2dec.so	OK
2026-05-27 11:26:54	Analyzing lib/armeabi-v7a/libreschecker.so	OK
2026-05-27 11:26:54	Analyzing lib/armeabi-v7a/libtt_uغن_layout.so	OK
2026-05-27 11:26:54	Analyzing lib/armeabi-v7a/liborbuculumadapter.so	OK

2026-05-27 11:26:54	Analyzing lib/armeabi-v7a/liblens.so	OK
2026-05-27 11:26:54	Analyzing lib/armeabi-v7a/libavocadoguard.so	OK
2026-05-27 11:26:54	Analyzing lib/armeabi-v7a/libbase_live.so	OK
2026-05-27 11:26:54	Analyzing lib/armeabi-v7a/libbdhm_native.so	OK
2026-05-27 11:26:54	Analyzing lib/armeabi-v7a/libvcnverify.so	OK
2026-05-27 11:26:54	Analyzing lib/armeabi-v7a/libpumbaa-network.so	OK
2026-05-27 11:26:54	Analyzing lib/armeabi-v7a/libstarship_sdk.so	OK
2026-05-27 11:26:54	Analyzing lib/armeabi-v7a/libv8_libfull.cr.so	OK
2026-05-27 11:26:54	Analyzing lib/armeabi-v7a/libttmverify.so	OK
2026-05-27 11:26:54	Analyzing lib/armeabi-v7a/libvcn.so	OK
2026-05-27 11:26:54	Analyzing lib/armeabi-v7a/libfly-main-color-lib.so	OK
2026-05-27 11:26:54	Analyzing lib/armeabi-v7a/libshadowhook_nothing.so	OK
2026-05-27 11:26:54	Analyzing lib/armeabi-v7a/libarc_core_sdk_c.so	OK
2026-05-27 11:26:54	Analyzing lib/armeabi-v7a/libByteAlNN.so	OK
2026-05-27 11:26:55	Analyzing lib/armeabi-v7a/libdex_df_pipo_bnpl.so	OK

2026-05-27 11:26:55	Analyzing lib/armeabi-v7a/libbytebench.so	OK
2026-05-27 11:26:55	Analyzing lib/armeabi-v7a/libCepProxy.so	OK
2026-05-27 11:26:55	Analyzing lib/armeabi-v7a/libconfigcenter.so	OK
2026-05-27 11:26:55	Analyzing lib/armeabi-v7a/libartshadowhook.so	OK
2026-05-27 11:26:55	Analyzing lib/armeabi-v7a/libjazz.so	OK
2026-05-27 11:26:55	Analyzing lib/armeabi-v7a/libdex_df_pipo_external_payments.so	OK
2026-05-27 11:26:55	Analyzing lib/armeabi-v7a/libnpth_tls_monitor.so	OK
2026-05-27 11:26:55	Analyzing lib/armeabi-v7a/libttc2pa.so	OK
2026-05-27 11:26:55	Analyzing lib/armeabi-v7a/libonetex.so	OK
2026-05-27 11:26:55	Analyzing lib/armeabi-v7a/libtt_c2pa_sdk_d.so	OK
2026-05-27 11:26:55	Analyzing lib/armeabi-v7a/libEffectCreatorJni.so	OK
2026-05-27 11:26:55	Analyzing lib/armeabi-v7a/libvideodec.so	OK
2026-05-27 11:26:55	Analyzing lib/armeabi-v7a/libnpth_dumper.so	OK
2026-05-27 11:26:55	Analyzing lib/armeabi-v7a/liblynxstarlight.so	OK
2026-05-27 11:26:55	Analyzing lib/armeabi-v7a/libmotion.so	OK

2026-05-27 11:26:55	Analyzing lib/armeabi-v7a/libpy-cv-numpycv.so	OK
2026-05-27 11:26:55	Analyzing lib/armeabi-v7a/libtbboringssl.so	OK
2026-05-27 11:26:55	Analyzing lib/armeabi-v7a/libnetecho.so	OK
2026-05-27 11:26:55	Analyzing lib/armeabi-v7a/libjazz_plugin.so	OK
2026-05-27 11:26:55	Analyzing lib/armeabi-v7a/libsimba.so	OK
2026-05-27 11:26:55	Analyzing lib/armeabi-v7a/libArchive.so	OK
2026-05-27 11:26:55	Analyzing lib/armeabi-v7a/libres_memory.so	OK
2026-05-27 11:26:55	Analyzing lib/armeabi-v7a/libaudioeffect.so	OK
2026-05-27 11:26:55	Analyzing lib/armeabi-v7a/libsscronet.so	OK
2026-05-27 11:26:55	Analyzing lib/armeabi-v7a/liblynxsuit.so	OK
2026-05-27 11:26:55	Analyzing lib/armeabi-v7a/libstatic-webp.so	OK
2026-05-27 11:26:55	Analyzing lib/armeabi-v7a/libttr.so	OK
2026-05-27 11:26:55	Analyzing lib/armeabi-v7a/libspeechsdk.so	OK
2026-05-27 11:26:55	Analyzing lib/armeabi-v7a/liblynxsecurity.so	OK
2026-05-27 11:26:55	Analyzing lib/armeabi-v7a/liblynx_krypton.so	OK

2026-05-27 11:26:55	Analyzing lib/armeabi-v7a/libshadowhook.so	OK
2026-05-27 11:26:55	Analyzing lib/armeabi-v7a/libtexturerender_native.so	OK
2026-05-27 11:26:55	Analyzing lib/armeabi-v7a/libtt_c2pa_sdk.so	OK
2026-05-27 11:26:56	Analyzing lib/armeabi-v7a/libLAMaterialSDK.so	OK
2026-05-27 11:26:56	Analyzing lib/armeabi-v7a/libworker.so	OK
2026-05-27 11:26:56	Analyzing lib/armeabi-v7a/libnxreword.so	OK
2026-05-27 11:26:56	Analyzing lib/armeabi-v7a/libbytenn.so	OK
2026-05-27 11:26:56	Analyzing lib/armeabi-v7a/liblink_mic_sdk.so	OK
2026-05-27 11:26:56	Analyzing lib/armeabi-v7a/libstarship_wrapper.so	OK
2026-05-27 11:26:56	Analyzing lib/armeabi-v7a/libvolcenginertc.so	OK
2026-05-27 11:26:56	Analyzing lib/armeabi-v7a/libByteAIDT.so	OK
2026-05-27 11:26:56	Analyzing lib/armeabi-v7a/libjato.so	OK
2026-05-27 11:26:56	Analyzing lib/armeabi-v7a/libbytevc1enc.so	OK
2026-05-27 11:26:56	Analyzing lib/armeabi-v7a/libbytennllm-jni.so	OK
2026-05-27 11:26:56	Analyzing lib/armeabi-v7a/libmonitorcollector-lib.so	OK

2026-05-27 11:26:56	Analyzing lib/armeabi-v7a/lib_jhmp.so	OK
2026-05-27 11:26:56	Analyzing lib/armeabi-v7a/libkryptonaudio.so	OK
2026-05-27 11:26:56	Analyzing lib/armeabi-v7a/libgeckox_bspatch.so	OK
2026-05-27 11:26:56	Analyzing lib/armeabi-v7a/liborbuculum.so	OK
2026-05-27 11:26:56	Analyzing lib/armeabi-v7a/libyoga.so	OK
2026-05-27 11:26:56	Analyzing lib/armeabi-v7a/libnpth_unw.so	OK
2026-05-27 11:26:56	Analyzing lib/armeabi-v7a/libNLEditorJni.so	OK
2026-05-27 11:26:56	Analyzing lib/armeabi-v7a/libttesdk_plugin.so	OK
2026-05-27 11:26:56	Analyzing lib/armeabi-v7a/libfile_lock.so	OK
2026-05-27 11:26:56	Analyzing lib/armeabi-v7a/libgodzilla-mem sponge.so	OK
2026-05-27 11:26:56	Analyzing lib/armeabi-v7a/libfdk-aac.so	OK
2026-05-27 11:26:56	Analyzing lib/armeabi-v7a/lib_jbmf.so	OK
2026-05-27 11:26:56	Analyzing lib/armeabi-v7a/libanimax_bytevc1.so	OK
2026-05-27 11:26:56	Analyzing lib/armeabi-v7a/libminizip.so	OK
2026-05-27 11:26:56	Analyzing lib/armeabi-v7a/libCutSameJni.so	OK

2026-05-27 11:26:56	Analyzing lib/armeabi-v7a/libEncryptor.so	OK
2026-05-27 11:26:56	Analyzing lib/armeabi-v7a/libwatson.so	OK
2026-05-27 11:26:56	Analyzing lib/armeabi-v7a/libotis_attrib.so	OK
2026-05-27 11:26:57	Analyzing lib/armeabi-v7a/liblynxbase.so	OK
2026-05-27 11:26:57	Analyzing lib/armeabi-v7a/libwcdm.so	OK
2026-05-27 11:26:57	Analyzing lib/armeabi-v7a/libttmux.so	OK
2026-05-27 11:26:57	Analyzing lib/armeabi-v7a/libNLETemplateModeljni_plugin.so	OK
2026-05-27 11:26:57	Analyzing lib/armeabi-v7a/libpipo-security-sdk.so	OK
2026-05-27 11:26:57	Analyzing lib/armeabi-v7a/libCepFast.so	OK
2026-05-27 11:26:57	Analyzing lib/armeabi-v7a/libanrrrelief.so	OK
2026-05-27 11:26:57	Analyzing lib/armeabi-v7a/libDavinciResourcejni.so	OK
2026-05-27 11:26:57	Analyzing lib/armeabi-v7a/libfileprotect.so	OK
2026-05-27 11:26:57	Analyzing lib/armeabi-v7a/libnpth_repair.so	OK
2026-05-27 11:26:57	Analyzing lib/armeabi-v7a/libkrypton_sar.so	OK
2026-05-27 11:26:57	Analyzing lib/armeabi-v7a/libbmf_hydra_lite.so	OK

2026-05-27 11:26:57	Analyzing lib/armeabi-v7a/libquick.so	OK
2026-05-27 11:26:57	Analyzing lib/armeabi-v7a/libfastcv.so	OK
2026-05-27 11:26:57	Analyzing lib/armeabi-v7a/libBlinkCard.so	OK
2026-05-27 11:26:57	Analyzing lib/armeabi-v7a/libbdzstd.so	OK
2026-05-27 11:26:57	Analyzing lib/armeabi-v7a/libdex_df_ccdc_impl_ocr.so	OK
2026-05-27 11:26:57	Analyzing lib/armeabi-v7a/libbytelink.so	OK
2026-05-27 11:26:57	Analyzing lib/armeabi-v7a/libforestx_native_buffer.so	OK
2026-05-27 11:26:57	Analyzing lib/armeabi-v7a/libttmverifylite.so	OK
2026-05-27 11:26:57	Analyzing lib/armeabi-v7a/libbmf_mods.so	OK
2026-05-27 11:26:57	Analyzing lib/armeabi-v7a/libresource_monitor.so	OK
2026-05-27 11:26:57	Analyzing lib/armeabi-v7a/libkryptoneffect.so	OK
2026-05-27 11:26:57	Analyzing lib/armeabi-v7a/libptyjemalloc.so	OK
2026-05-27 11:26:57	Analyzing lib/armeabi-v7a/libttffmpeg.so	OK
2026-05-27 11:26:57	Analyzing lib/armeabi-v7a/libanimax_textra.so	OK
2026-05-27 11:26:57	Analyzing lib/armeabi-v7a/liblynxtrace.so	OK

2026-05-27 11:26:57	Analyzing lib/armeabi-v7a/libpythonA.so	OK
2026-05-27 11:26:57	Analyzing lib/armeabi-v7a/libgifimage.so	OK
2026-05-27 11:26:57	Analyzing lib/armeabi-v7a/libsysoptimizer.so	OK
2026-05-27 11:26:57	Analyzing lib/armeabi-v7a/libtailor.so	OK
2026-05-27 11:26:57	Analyzing lib/armeabi-v7a/libkryptonaum.so	OK
2026-05-27 11:26:57	Analyzing lib/armeabi-v7a/libdex_df_ship.so	OK
2026-05-27 11:26:57	Analyzing lib/armeabi-v7a/libbdmpg123.so	OK
2026-05-27 11:26:57	Analyzing lib/armeabi-v7a/libbd-install.so	OK
2026-05-27 11:26:58	Analyzing lib/armeabi-v7a/libNLEMediajni_plugin.so	OK
2026-05-27 11:26:58	Analyzing lib/armeabi-v7a/libiesapplogger.so	OK
2026-05-27 11:26:58	Analyzing lib/armeabi-v7a/libpsp_engine.so	OK
2026-05-27 11:26:58	Analyzing lib/armeabi-v7a/libdelta.so	OK
2026-05-27 11:26:58	Analyzing lib/armeabi-v7a/libNLEEditorjni_plugin.so	OK
2026-05-27 11:26:58	Analyzing lib/armeabi-v7a/libclient_ai_impl_jni.so	OK
2026-05-27 11:26:58	Analyzing lib/armeabi-v7a/libkeva.so	OK

2026-05-27 11:26:58	Analyzing lib/armeabi-v7a/libflipped.so	OK
2026-05-27 11:26:58	Analyzing lib/armeabi-v7a/libbat.so	OK
2026-05-27 11:26:58	Analyzing lib/armeabi-v7a/libAwplatsupport.so	OK
2026-05-27 11:26:58	Analyzing lib/armeabi-v7a/libttmplayer.so	OK
2026-05-27 11:26:58	Analyzing lib/armeabi-v7a/libBDPythonVM.so	OK
2026-05-27 11:26:58	Analyzing lib/armeabi-v7a/libgaia_lib.so	OK
2026-05-27 11:26:58	Analyzing lib/armeabi-v7a/libsliver.so	OK
2026-05-27 11:26:58	Analyzing lib/armeabi-v7a/libTTMStrategyCenter.so	OK
2026-05-27 11:26:58	Analyzing lib/armeabi-v7a/libbytennllm.so	OK
2026-05-27 11:26:58	Analyzing lib/armeabi-v7a/liblynx_v8_bridge.so	OK
2026-05-27 11:26:58	Analyzing lib/armeabi-v7a/libnativeaudio.so	OK
2026-05-27 11:26:58	Analyzing lib/armeabi-v7a/libskity.so	OK
2026-05-27 11:26:58	Analyzing lib/armeabi-v7a/libropaencrypt.so	OK
2026-05-27 11:26:58	Analyzing lib/armeabi-v7a/libstorage-hook.so	OK
2026-05-27 11:26:58	Analyzing lib/armeabi-v7a/libjson_opt.so	OK

2026-05-27 11:26:58	Analyzing lib/armeabi-v7a/libdex_df_pitaya.so	OK
2026-05-27 11:26:58	Analyzing lib/armeabi-v7a/libavmdlp2pv2.so	OK
2026-05-27 11:26:58	Analyzing lib/armeabi-v7a/libskbase.so	OK
2026-05-27 11:26:58	Analyzing lib/armeabi-v7a/libbdsword.so	OK
2026-05-27 11:26:58	Analyzing lib/armeabi-v7a/libttpreload.so	OK
2026-05-27 11:26:58	Analyzing lib/armeabi-v7a/libarc_sdk_jni.so	OK
2026-05-27 11:26:58	Analyzing lib/armeabi-v7a/libttheif_dec.so	OK
2026-05-27 11:26:58	Analyzing lib/armeabi-v7a/libfast_engine_api_loader.so	OK
2026-05-27 11:26:58	Analyzing lib/armeabi-v7a/libalog.so	OK
2026-05-27 11:26:58	Analyzing lib/armeabi-v7a/libavmdlbase.so	OK
2026-05-27 11:26:58	Analyzing lib/armeabi-v7a/libEffectEditorjni.so	OK
2026-05-27 11:26:58	Analyzing lib/armeabi-v7a/libhelios_bm.so	OK
2026-05-27 11:26:58	Analyzing lib/armeabi-v7a/libnpth_bt.so	OK
2026-05-27 11:26:58	Analyzing lib/armeabi-v7a/libtttext_lite.so	OK
2026-05-27 11:26:58	Analyzing lib/armeabi-v7a/libqmiVsyncHook.so	OK

2026-05-27 11:26:58	Analyzing lib/armeabi-v7a/libttmcmf.so	OK
2026-05-27 11:26:58	Analyzing lib/armeabi-v7a/libNLEResourcesDAVjni_plugin.so	OK
2026-05-27 11:26:59	Analyzing lib/armeabi-v7a/libAGFX.so	OK
2026-05-27 11:26:59	Analyzing lib/armeabi-v7a/libnpth_unwind.so	OK
2026-05-27 11:26:59	Analyzing lib/armeabi-v7a/libandroidx.graphics.path.so	OK
2026-05-27 11:26:59	Analyzing lib/armeabi-v7a/liblynx_service_api.so	OK
2026-05-27 11:26:59	Analyzing lib/armeabi-v7a/libbytehook.so	OK
2026-05-27 11:26:59	Analyzing lib/armeabi-v7a/libbmf_module_sdk.so	OK
2026-05-27 11:26:59	Analyzing lib/armeabi-v7a/libpns_ttmachine_adapter.so	OK
2026-05-27 11:26:59	Analyzing lib/armeabi-v7a/libotisopt.so	OK
2026-05-27 11:26:59	Analyzing lib/armeabi-v7a/libpunch.so	OK
2026-05-27 11:26:59	Analyzing lib/armeabi-v7a/libvegasdk.so	OK
2026-05-27 11:26:59	Analyzing lib/armeabi-v7a/libbmf_hydra.so	OK
2026-05-27 11:26:59	Analyzing lib/armeabi-v7a/liblynx.so	OK
2026-05-27 11:26:59	Analyzing lib/armeabi-v7a/libanimax.so	OK

2026-05-27 11:26:59	Analyzing lib/armeabi-v7a/libpreload.so	OK
2026-05-27 11:26:59	Analyzing lib/armeabi-v7a/libimagepipeline.so	OK
2026-05-27 11:26:59	Analyzing lib/armeabi-v7a/libPitayaBdComponent.so	OK
2026-05-27 11:26:59	Analyzing lib/armeabi-v7a/librex.so	OK
2026-05-27 11:26:59	Analyzing lib/armeabi-v7a/libAndroidPitayaCore.so	OK
2026-05-27 11:26:59	Analyzing lib/armeabi-v7a/libbdheif.so	OK
2026-05-27 11:26:59	Analyzing lib/armeabi-v7a/libbytevc1enc10b.so	OK
2026-05-27 11:26:59	Analyzing lib/armeabi-v7a/liblynx_text_service.so	OK
2026-05-27 11:26:59	Analyzing lib/armeabi-v7a/libSmartMovieJni.so	OK
2026-05-27 11:26:59	Analyzing lib/armeabi-v7a/libNLEMediaRemoteJni_plugin.so	OK
2026-05-27 11:26:59	Analyzing lib/armeabi-v7a/libnpth_logcat.so	OK
2026-05-27 11:26:59	Analyzing lib/armeabi-v7a/libnpth_xasan.so	OK
2026-05-27 11:26:59	Analyzing lib/armeabi-v7a/libc++_shared.so	OK
2026-05-27 11:26:59	Analyzing lib/armeabi-v7a/libzoin.so	OK
2026-05-27 11:26:59	Analyzing lib/armeabi-v7a/libalignpage.so	OK

2026-05-27 11:27:00	Analyzing lib/armeabi-v7a/libh3-java.so	OK
2026-05-27 11:27:00	Analyzing lib/armeabi-v7a/libnapi.so	OK
2026-05-27 11:27:00	Analyzing lib/armeabi-v7a/libkrypton.so	OK
2026-05-27 11:27:00	Analyzing lib/armeabi-v7a/libnpth_ref_monitor.so	OK
2026-05-27 11:27:00	Analyzing lib/armeabi-v7a/libByteVC1_dec.so	OK
2026-05-27 11:27:00	Analyzing lib/armeabi-v7a/libvebytevc1enc8bwrwrapper.so	OK
2026-05-27 11:27:00	Analyzing lib/armeabi-v7a/libCepAuth.so	OK
2026-05-27 11:27:00	Analyzing lib/armeabi-v7a/libvctfo.so	OK
2026-05-27 11:27:00	Analyzing lib/armeabi-v7a/libcybertron_base.so	OK
2026-05-27 11:27:00	Analyzing lib/armeabi-v7a/libp2plivevdp.so	OK
2026-05-27 11:27:00	Analyzing lib/armeabi-v7a/libffmpeg_dashdec.so	OK
2026-05-27 11:27:00	Analyzing lib/armeabi-v7a/libwasm.so	OK
2026-05-27 11:27:00	Analyzing lib/armeabi-v7a/libbytemonitor.so	OK
2026-05-27 11:27:00	Analyzing lib/armeabi-v7a/libserval_svg.so	OK
2026-05-27 11:27:00	Analyzing lib/armeabi-v7a/libartlog_monitor.so	OK

2026-05-27 11:27:00	Analyzing lib/armeabi-v7a/libvolcenginertc_plugin.so	OK
2026-05-27 11:27:00	Analyzing lib/armeabi-v7a/libCepEngine.so	OK
2026-05-27 11:27:00	Analyzing lib/armeabi-v7a/libttnisnative.so	OK
2026-05-27 11:27:00	Analyzing lib/armeabi-v7a/libdex_df_ttwebview.so	OK
2026-05-27 11:27:00	Analyzing lib/armeabi-v7a/libttquic.so	OK
2026-05-27 11:27:00	Analyzing lib/armeabi-v7a/libspeechspg.so	OK
2026-05-27 11:27:00	Analyzing lib/armeabi-v7a/libnptl_dl.so	OK
2026-05-27 11:27:00	Analyzing lib/armeabi-v7a/libbytedt.so	OK
2026-05-27 11:27:00	Analyzing lib/armeabi-v7a/libfast_engine.so	OK
2026-05-27 11:27:00	Analyzing lib/armeabi-v7a/libbytevc1enc10bwrapper.so	OK
2026-05-27 11:27:00	Analyzing lib/armeabi-v7a/libdex_df_live_cast.so	OK
2026-05-27 11:27:00	Analyzing lib/armeabi-v7a/libbytevc0.so	OK
2026-05-27 11:27:00	Analyzing lib/armeabi-v7a/libhmp.so	OK
2026-05-27 11:27:01	Analyzing lib/armeabi-v7a/libpns_crypto.so	OK
2026-05-27 11:27:01	Analyzing lib/armeabi-v7a/libPitayaTTPPolicy.so	OK

2026-05-27 11:27:01	Analyzing lib/armeabi-v7a/libopus.so	OK
2026-05-27 11:27:01	Analyzing lib/armeabi-v7a/libTTMachineCore.so	OK
2026-05-27 11:27:01	Analyzing lib/armeabi-v7a/libNLEMediaRemotejni.so	OK
2026-05-27 11:27:01	Analyzing lib/armeabi-v7a/libvcbasekit.so	OK
2026-05-27 11:27:01	Analyzing lib/armeabi-v7a/libug_share_sort.so	OK
2026-05-27 11:27:01	Analyzing lib/armeabi-v7a/libBDMicroPythonVM.so	OK
2026-05-27 11:27:01	Analyzing lib/armeabi-v7a/liblivestrategy.so	OK
2026-05-27 11:27:01	Analyzing lib/armeabi-v7a/libspeechepg.so	OK
2026-05-27 11:27:01	Analyzing lib/armeabi-v7a/libbdvideouploader.so	OK
2026-05-27 11:27:01	Analyzing lib/armeabi-v7a/librtmglobal.so	OK
2026-05-27 11:27:01	Analyzing lib/armeabi-v7a/libbuffer.so	OK
2026-05-27 11:27:01	Analyzing lib/armeabi-v7a/libfast_engine_api.so	OK
2026-05-27 11:27:01	Analyzing lib/armeabi-v7a/libworkerv8.so	OK
2026-05-27 11:27:01	Analyzing lib/armeabi-v7a/libeffect_plugin.so	OK
2026-05-27 11:27:01	Analyzing lib/armeabi-v7a/libbytennwrapper.so	OK

2026-05-27 11:27:01	Analyzing lib/armeabi-v7a/libicu.so	OK
2026-05-27 11:27:01	Analyzing lib/armeabi-v7a/libdex_df_music_dsp.so	OK
2026-05-27 11:27:01	Analyzing lib/armeabi-v7a/libnative-filters.so	OK
2026-05-27 11:27:01	Analyzing lib/armeabi-v7a/libpsienccrypt.so	OK
2026-05-27 11:27:01	Analyzing lib/armeabi-v7a/liblynx_markdown.so	OK
2026-05-27 11:27:01	Analyzing lib/armeabi-v7a/libjniidispach.so	OK
2026-05-27 11:27:01	Analyzing lib/armeabi-v7a/libmedia.so	OK
2026-05-27 11:27:01	Analyzing lib/armeabi-v7a/libttcrypto.so	OK
2026-05-27 11:27:02	Analyzing lib/armeabi-v7a/libspeechengine.so	OK
2026-05-27 11:27:02	Analyzing lib/armeabi-v7a/libxtrace.so	OK
2026-05-27 11:27:02	Analyzing lib/armeabi-v7a/libpy-numpy.so	OK
2026-05-27 11:27:02	Analyzing lib/armeabi-v7a/liboecsec_ov.so	OK
2026-05-27 11:27:02	Analyzing lib/armeabi-v7a/libvoip.so	OK
2026-05-27 11:27:02	Analyzing lib/armeabi-v7a/liburiparser.so	OK
2026-05-27 11:27:02	Analyzing lib/armeabi-v7a/libmemrelief.so	OK

2026-05-27 11:27:02	Analyzing lib/armeabi-v7a/libCepAST.so	OK
2026-05-27 11:27:02	Analyzing lib/armeabi-v7a/libEffectEditorABTestjni.so	OK
2026-05-27 11:27:02	Analyzing lib/armeabi-v7a/libNLEResourcesDAVjni.so	OK
2026-05-27 11:27:02	Analyzing lib/armeabi-v7a/libNLEMediaPublicjni.so	OK
2026-05-27 11:27:02	Analyzing lib/armeabi-v7a/libbtch_collection.so	OK
2026-05-27 11:27:02	Analyzing lib/armeabi-v7a/libaudio_fingerprint_sdk.so	OK
2026-05-27 11:27:02	Analyzing lib/armeabi-v7a/libart_sym.so	OK
2026-05-27 11:27:02	Analyzing lib/armeabi-v7a/libnpth_fd_tracker.so	OK
2026-05-27 11:27:02	Analyzing lib/armeabi-v7a/libkomprese-decompressor.so	OK
2026-05-27 11:27:02	Analyzing lib/armeabi-v7a/libmmt.so	OK
2026-05-27 11:27:02	Analyzing lib/armeabi-v7a/libapplog_rust.so	OK
2026-05-27 11:27:02	Analyzing lib/armeabi-v7a/libwhisper.so	OK
2026-05-27 11:27:02	Analyzing lib/armeabi-v7a/libnpth.so	OK
2026-05-27 11:27:02	Analyzing lib/armeabi-v7a/libprofiler.so	OK
2026-05-27 11:27:02	Analyzing lib/armeabi-v7a/libanimax_napi.so	OK

2026-05-27 11:27:02	Analyzing lib/armeabi-v7a/libyuv.so	OK
2026-05-27 11:27:02	Analyzing lib/armeabi-v7a/libbach-sdk-jni.so	OK
2026-05-27 11:27:02	Analyzing lib/armeabi-v7a/libmetasec_ov.so	OK
2026-05-27 11:27:02	Analyzing lib/armeabi-v7a/libanrthanos.so	OK
2026-05-27 11:27:02	Analyzing lib/armeabi-v7a/libAwebviewbytedance.so	OK
2026-05-27 11:27:03	Analyzing lib/armeabi-v7a/libnewep.so	OK
2026-05-27 11:27:03	Analyzing lib/armeabi-v7a/libNLETemplateModeljni.so	OK
2026-05-27 11:27:03	Analyzing lib/armeabi-v7a/libNLEMediaPublicjni_plugin.so	OK
2026-05-27 11:27:03	Analyzing lib/armeabi-v7a/libvcnverifylite.so	OK
2026-05-27 11:27:03	Analyzing lib/armeabi-v7a/libNLEMediajni.so	OK
2026-05-27 11:27:03	Analyzing lib/armeabi-v7a/libflock-lib.so	OK
2026-05-27 11:27:03	Analyzing lib/armeabi-v7a/libnapi_v8.so	OK
2026-05-27 11:27:03	Analyzing lib/armeabi-v7a/libbvcparser.so	OK
2026-05-27 11:27:03	Analyzing lib/armeabi-v7a/libjarvis-metrics.so	OK
2026-05-27 11:27:03	Analyzing lib/armeabi-v7a/libcrashpad_handler_trampoline.so	OK

2026-05-27 11:27:03	Analyzing lib/armeabi-v7a/libkryptonremote.so	OK
2026-05-27 11:27:03	Analyzing lib/armeabi-v7a/libgodzilla-sysopt.so	OK
2026-05-27 11:27:03	Analyzing lib/armeabi-v7a/libTTNativeML.so	OK
2026-05-27 11:27:03	Reading Code Signing Certificate	OK
2026-05-27 11:27:10	Running APKID 3.0.0	OK
2026-05-27 11:27:53	Detecting Trackers	OK
2026-05-27 11:28:21	Decompiling APK to Java with JADX	OK
2026-05-27 11:45:03	Decompiling with JADX timed out	TimeoutExpired(['/home/mobsf/.MobSF/tools/jadx/jadx-1.5.0/bin/jadx', '-ds', '/home/mobsf/.MobSF/uploads/669f7a60b777f04d7719949da140df72/java_source', '-q', '-r', '--show-bad-code', '/home/mobsf/.MobSF/uploads/669f7a60b777f04d7719949da140df72/669f7a60b777f04d7719949da140df72.apk'], 999.9999785560067)
2026-05-27 11:45:03	Converting DEX to Smali	OK
2026-05-27 11:45:07	Code Analysis Started on - java_source	OK
2026-05-27 11:47:29	Android SBOM Analysis Completed	OK
2026-05-27 11:47:46	Android SAST Completed	OK
2026-05-27 11:47:46	Android API Analysis Started	OK
2026-05-27 11:48:02	Android API Analysis Completed	OK
2026-05-27 11:48:02	Android Permission Mapping Started	OK

2026-05-27 11:53:23	Android Permission Mapping Completed	OK
2026-05-27 11:53:24	Android Behaviour Analysis Started	OK
2026-05-27 11:53:56	Android Behaviour Analysis Completed	OK
2026-05-27 11:53:56	Extracting Emails and URLs from Source Code	OK
2026-05-27 11:54:00	Email and URL Extraction Completed	OK
2026-05-27 11:54:00	Extracting String data from APK	OK
2026-05-27 11:54:00	Extracting String data from SO	OK
2026-05-27 11:54:15	Extracting String data from Code	OK
2026-05-27 11:54:15	Extracting String values and entropies from Code	OK
2026-05-27 11:54:17	Performing Malware check on extracted domains	OK
2026-05-27 11:55:35	Saving to Database	OK

Report Generated by - MobSF v4.5.0

Mobile Security Framework (MobSF) is an automated, all-in-one mobile application (Android/iOS/Windows) pen-testing, malware analysis and security assessment framework capable of performing static and dynamic analysis.

© 2026 Mobile Security Framework - MobSF | [Ajin Abraham](#) | [OpenSecurity](#).