



ANDROID STATIC ANALYSIS REPORT



 VK (8.180)

File Name: `com.vkontakte.android_53441_rs.apk`


Package Name: `com.vkontakte.android`

Scan Date: May 30, 2026, 3:55 p.m.

App Security Score:

49/100 (MEDIUM RISK)

Grade:



Trackers Detection:

13/432

 FINDINGS SEVERITY

 HIGH	 MEDIUM	 INFO	 SECURE	 HOTSPOT
3	100	2	1	2

FILE INFORMATION

File Name: com.vkontakte.android_53441_rs.apk

Size: 162.13MB

MD5: 9c0362fbcaaab425cf63fdb8419fcbe8

SHA1: 639c74eeeb077fa46af4eefe73c7e546a8cc215e

SHA256: bfbfef2b84ea79c9ea8dcebe6e3bf8e7c9ad5ec7f72dccc6d05a60278cac7b38

APP INFORMATION

App Name: VK

Package Name: com.vkontakte.android

Main Activity: com.vkontakte.android.MainActivity

Target SDK: 35

Min SDK: 28

Max SDK:

Android Version Name: 8.180

Android Version Code: 53441

APP COMPONENTS

Activities: 169

Services: 66

Receivers: 54

Providers: 16

Exported Activities: 60

Exported Services: 11

Exported Receivers: 14

Exported Providers: 1

CERTIFICATE INFORMATION

Binary is signed

v1 signature: False

v2 signature: False

v3 signature: True

v4 signature: False

X.509 Subject: O=VKontakte

Signature Algorithm: rsassa_pkcs1v15

Valid From: 2011-06-06 16:08:14+00:00

Valid To: 3010-10-07 16:08:14+00:00

Issuer: O=VKontakte
Serial Number: 0x4decfb6e
Hash Algorithm: sha1
md5: 76d6039f6e24d891df05b130be01217d
sha1: 48761eef50ee53afc4cc9c5f10e6bde7f8f5b82f
sha256: 057d974412032066f1b5edb1fdb550f71854189815c806b27c4d486fb4f1ef32
sha512: 2ae003d521fcebfa20f49fe4105ca37d293b4e9aa79c4ec4a55dcceb136f86d820ea96ac5e328b2423f2c731147144ac2a51383254aa37460ad7bb7f4449f689
PublicKey Algorithm: rsa
Bit Size: 1024
Fingerprint: 8d6415b88d65a1d413cd26ef6be0579fc8dc199fd762fff315b036bee5ae7b4e
Found 1 unique certificates

≡ APPLICATION PERMISSIONS

PERMISSION	STATUS	INFO	DESCRIPTION
com.vk.calls.usersstore.permission.SAVE	unknown	Unknown permission	Unknown permission from android reference
com.vk.calls.usersstore.permission.LOAD	unknown	Unknown permission	Unknown permission from android reference
com.vk.clips.usersstore.permission.SAVE	unknown	Unknown permission	Unknown permission from android reference
com.vk.clips.usersstore.permission.LOAD	unknown	Unknown permission	Unknown permission from android reference
com.vk.vkvideo.usersstore.permission.SAVE	unknown	Unknown permission	Unknown permission from android reference
com.vk.vkvideo.usersstore.permission.LOAD	unknown	Unknown permission	Unknown permission from android reference
com.vk.im.usersstore.permission.SAVE	unknown	Unknown permission	Unknown permission from android reference
com.vk.im.usersstore.permission.LOAD	unknown	Unknown permission	Unknown permission from android reference
ru.vk.store.usersstore.permission.SAVE	unknown	Unknown permission	Unknown permission from android reference
ru.vk.store.usersstore.permission.LOAD	unknown	Unknown permission	Unknown permission from android reference
com.vk.love.usersstore.permission.SAVE	unknown	Unknown permission	Unknown permission from android reference
com.vk.love.usersstore.permission.LOAD	unknown	Unknown permission	Unknown permission from android reference
com.uma.musicvk.usersstore.permission.SAVE	unknown	Unknown permission	Unknown permission from android reference

PERMISSION	STATUS	INFO	DESCRIPTION
com.uma.musicvk.usersstore.permission.LOAD	unknown	Unknown permission	Unknown permission from android reference
ru.mail.mailapp.usersstore.permission.SAVE	unknown	Unknown permission	Unknown permission from android reference
ru.mail.mailapp.usersstore.permission.LOAD	unknown	Unknown permission	Unknown permission from android reference
live.vkplay.app.usersstore.permission.SAVE	unknown	Unknown permission	Unknown permission from android reference
live.vkplay.app.usersstore.permission.LOAD	unknown	Unknown permission	Unknown permission from android reference
android.permission.FOREGROUND_SERVICE	normal	enables regular apps to use Service.startForeground.	Allows a regular application to use Service.startForeground.
android.permission.FOREGROUND_SERVICE_MEDIA_PLAYBACK	normal	enables foreground services for media playback.	Allows a regular application to use Service.startForeground with the type "mediaPlayback".
android.permission.RECORD_AUDIO	dangerous	record audio	Allows application to access the audio record path.
android.permission.CAMERA	dangerous	take pictures and videos	Allows application to take pictures and videos with the camera. This allows the application to collect images that the camera is seeing at any time.
android.permission.MODIFY_AUDIO_SETTINGS	normal	change your audio settings	Allows application to modify global audio settings, such as volume and routing.
com.android.launcher.permission.INSTALL_SHORTCUT	unknown	Unknown permission	Unknown permission from android reference
com.android.vending.BILLING	normal	application has in-app purchases	Allows an application to make in-app purchases from Google Play.
android.permission.INTERNET	normal	full Internet access	Allows an application to create network sockets.
android.permission.POST_NOTIFICATIONS	dangerous	allows an app to post notifications.	Allows an app to post notifications
android.permission.ACCESS_COARSE_LOCATION	dangerous	coarse (network-based) location	Access coarse location sources, such as the mobile network database, to determine an approximate phone location, where available. Malicious applications can use this to determine approximately where you are.

PERMISSION	STATUS	INFO	DESCRIPTION
android.permission.ACCESS_FINE_LOCATION	dangerous	fine (GPS) location	Access fine location sources, such as the Global Positioning System on the phone, where available. Malicious applications can use this to determine where you are and may consume additional battery power.
android.permission.ACCESS_MEDIA_LOCATION	dangerous	access any geographic locations	Allows an application to access any geographic locations persisted in the user's shared collection.
android.permission.READ_MEDIA_VISUAL_USER_SELECTED	dangerous	allows reading user-selected image or video files from external storage.	Allows an application to read image or video files from external storage that a user has selected via the permission prompt photo picker. Apps can check this permission to verify that a user has decided to use the photo picker, instead of granting access to READ_MEDIA_IMAGES or READ_MEDIA_VIDEO . It does not prevent apps from accessing the standard photo picker manually. This permission should be requested alongside READ_MEDIA_IMAGES and/or READ_MEDIA_VIDEO , depending on which type of media is desired.
android.permission.READ_MEDIA_IMAGES	dangerous	allows reading image files from external storage.	Allows an application to read image files from external storage.
android.permission.READ_MEDIA_VIDEO	dangerous	allows reading video files from external storage.	Allows an application to read video files from external storage.
android.permission.READ_EXTERNAL_STORAGE	dangerous	read external storage contents	Allows an application to read from external storage.
android.permission.WRITE_EXTERNAL_STORAGE	dangerous	read/modify/delete external storage contents	Allows an application to write to external storage.
android.permission.VIBRATE	normal	control vibrator	Allows the application to control the vibrator.
android.permission.WAKE_LOCK	normal	prevent phone from sleeping	Allows an application to prevent the phone from going to sleep.
android.permission.READ_SYNC_SETTINGS	normal	read sync settings	Allows an application to read the sync settings, such as whether sync is enabled for Contacts.
android.permission.WRITE_SYNC_SETTINGS	normal	write sync settings	Allows an application to modify the sync settings, such as whether sync is enabled for Contacts.

PERMISSION	STATUS	INFO	DESCRIPTION
android.permission.READ_CONTACTS	dangerous	read contact data	Allows an application to read all of the contact (address) data stored on your phone. Malicious applications can use this to send your data to other people.
android.permission.WRITE_CONTACTS	dangerous	write contact data	Allows an application to modify the contact (address) data stored on your phone. Malicious applications can use this to erase or modify your contact data.
android.permission.ACCESS_NETWORK_STATE	normal	view network status	Allows an application to view the status of all networks.
android.permission.ACCESS_WIFI_STATE	normal	view Wi-Fi status	Allows an application to view the information about the status of Wi-Fi.
com.vkontakte.android.permission.MAPS_RECEIVE	unknown	Unknown permission	Unknown permission from android reference
com.google.android.providers.gsf.permission.READ_GSERVICES	unknown	Unknown permission	Unknown permission from android reference
com.vkontakte.android.permission.ACCESS_DATA	unknown	Unknown permission	Unknown permission from android reference
android.permission.SYSTEM_ALERT_WINDOW	dangerous	display system-level alerts	Allows an application to show system-alert windows. Malicious applications can take over the entire screen of the phone.
android.permission.BLUETOOTH	normal	create Bluetooth connections	Allows applications to connect to paired bluetooth devices.
android.permission.USE_BIOMETRIC	normal	allows use of device-supported biometric modalities.	Allows an app to use device supported biometric modalities.
com.google.android.gms.permission.AD_ID	normal	application shows advertisements	This app uses a Google advertising ID and can possibly serve advertisements.
android.gms.permission.ACTIVITY_RECOGNITION	dangerous	allow application to recognize physical activity	Allows an application to recognize physical activity.
android.permission.ACTIVITY_RECOGNITION	dangerous	allow application to recognize physical activity	Allows an application to recognize physical activity.
android.permission.READ_CALL_LOG	dangerous	grants read access to the user's call log.	Allows an application to read the user's call log.

PERMISSION	STATUS	INFO	DESCRIPTION
android.permission.READ_CALENDAR	dangerous	read calendar events	Allows an application to read all of the calendar events stored on your phone. Malicious applications can use this to send your calendar events to other people.
android.permission.WRITE_CALENDAR	dangerous	add or modify calendar events and send emails to guests	Allows an application to add or change the events on your calendar, which may send emails to guests. Malicious applications can use this to erase or modify your calendar events or to send emails to guests.
com.vk.blockstore.permission.DELETE	unknown	Unknown permission	Unknown permission from android reference
android.permission.READ_PHONE_NUMBERS	dangerous	allows reading of the device's phone number(s).	Allows read access to the device's phone number(s). This is a subset of the capabilities granted by READ_PHONE_STATE but is exposed to instant applications.
android.permission.FOREGROUND_SERVICE_MEDIA_PROJECTION	normal	allows foreground services for media projection.	Allows a regular application to use Service.startForeground with the type "mediaProjection".
android.permission.FOREGROUND_SERVICE_MICROPHONE	normal	permits foreground services with microphone use.	Allows a regular application to use Service.startForeground with the type "microphone".
android.permission.USE_FULL_SCREEN_INTENT	normal	required for full screen intents in notifications.	Required for apps targeting Build.VERSION_CODES.Q that want to use notification full screen intents.
com.google.android.c2dm.permission.RECEIVE	normal	recieve push notifications	Allows an application to receive push notifications from cloud.
android.permission.FOREGROUND_SERVICE_DATA_SYNC	normal	permits foreground services for data synchronization.	Allows a regular application to use Service.startForeground with the type "dataSync".
com.vkontakte.android.permission.APP_REDIRECT	unknown	Unknown permission	Unknown permission from android reference
android.permission.RECEIVE_BOOT_COMPLETED	normal	automatically start at boot	Allows an application to start itself as soon as the system has finished booting. This can make it take longer to start the phone and allow the application to slow down the overall phone by always running.
android.permission.AUTHENTICATE_ACCOUNTS	dangerous	act as an account authenticator	Allows an application to use the account authenticator capabilities of the Account Manager, including creating accounts as well as obtaining and setting their passwords.

PERMISSION	STATUS	INFO	DESCRIPTION
android.permission.health.READ_DISTANCE	unknown	Unknown permission	Unknown permission from android reference
android.permission.health.READ_STEPS	unknown	Unknown permission	Unknown permission from android reference
android.permission.health.READ_EXERCISE	unknown	Unknown permission	Unknown permission from android reference
android.permission.health.READ_TOTAL_CALORIES_BURNED	unknown	Unknown permission	Unknown permission from android reference
com.huawei.permission.SECURITY_DIAGNOSE	unknown	Unknown permission	Unknown permission from android reference
android.permission.DETECT_SCREEN_CAPTURE	normal	notifies when a screen capture of the app's windows is attempted.	Allows an application to get notified when a screen capture of its windows is attempted.
android.permission.READ_PHONE_STATE	dangerous	read phone state and identity	Allows the application to access the phone features of the device. An application with this permission can determine the phone number and serial number of this phone, whether a call is active, the number that call is connected to and so on.
android.provider.Telephony.SMS_RECEIVED	unknown	Unknown permission	Unknown permission from android reference
android.permission.GET_ACCOUNTS	dangerous	list accounts	Allows access to the list of accounts in the Accounts Service.
android.permission.QUICKBOOT_POWERON	unknown	Unknown permission	Unknown permission from android reference
android.permission.CHANGE_WIFI_STATE	normal	change Wi-Fi status	Allows an application to connect to and disconnect from Wi-Fi access points and to make changes to configured Wi-Fi networks.
android.permission.ACCESS_AD SERVICES_TOPICS	normal	allow applications to access advertising service topics	This enables the app to retrieve information related to advertising topics or interests, which can be used for targeted advertising purposes.
android.permission.ACCESS_AD SERVICES_ATTRIBUTION	normal	allow applications to access advertising service attribution	This enables the app to retrieve information related to advertising attribution, which can be used for targeted advertising purposes. App can gather data about how users interact with ads, such as clicks or impressions, to measure the effectiveness of advertising campaigns.
android.permission.CHANGE_NETWORK_STATE	normal	change network connectivity	Allows applications to change network connectivity state.

PERMISSION	STATUS	INFO	DESCRIPTION
android.permission.CALL_PHONE	dangerous	directly call phone numbers	Allows the application to call phone numbers without your intervention. Malicious applications may cause unexpected calls on your phone bill. Note that this does not allow the application to call emergency numbers.
android.permission.USE_FINGERPRINT	normal	allow use of fingerprint	This constant was deprecated in API level 28. Applications should request USE_BIOMETRIC instead.
com.google.android.finsky.permission.BIND_GET_INSTALL_REFERRER_SERVICE	normal	permission defined by google	A custom permission defined by Google.
com.vkontakte.android.DYNAMIC_RECEIVER_NOT_EXPORTED_PERMISSION	unknown	Unknown permission	Unknown permission from android reference
com.sec.android.provider.badge.permission.READ	normal	show notification count on app	Show notification count or badge on application launch icon for samsung phones.
com.sec.android.provider.badge.permission.WRITE	normal	show notification count on app	Show notification count or badge on application launch icon for samsung phones.
com.htc.launcher.permission.READ_SETTINGS	normal	show notification count on app	Show notification count or badge on application launch icon for htc phones.
com.htc.launcher.permission.UPDATE_SHORTCUT	normal	show notification count on app	Show notification count or badge on application launch icon for htc phones.
com.sonyericsson.home.permission.BROADCAST_BADGE	normal	show notification count on app	Show notification count or badge on application launch icon for sony phones.
com.sonymobile.home.permission.PROVIDER_INSERT_BADGE	normal	show notification count on app	Show notification count or badge on application launch icon for sony phones.
com.anddoes.launcher.permission.UPDATE_COUNT	normal	show notification count on app	Show notification count or badge on application launch icon for apex.
com.majeur.launcher.permission.UPDATE_BADGE	normal	show notification count on app	Show notification count or badge on application launch icon for solid.
com.huawei.android.launcher.permission.CHANGE_BADGE	normal	show notification count on app	Show notification count or badge on application launch icon for huawei phones.

PERMISSION	STATUS	INFO	DESCRIPTION
com.huawei.android.launcher.permission.READ_SETTINGS	normal	show notification count on app	Show notification count or badge on application launch icon for huawei phones.
com.huawei.android.launcher.permission.WRITE_SETTINGS	normal	show notification count on app	Show notification count or badge on application launch icon for huawei phones.
android.permission.READ_APP_BADGE	normal	show app notification	Allows an application to show app icon badges.
com.oppo.launcher.permission.READ_SETTINGS	normal	show notification count on app	Show notification count or badge on application launch icon for oppo phones.
com.oppo.launcher.permission.WRITE_SETTINGS	normal	show notification count on app	Show notification count or badge on application launch icon for oppo phones.
me.everything.badger.permission.BADGE_COUNT_READ	unknown	Unknown permission	Unknown permission from android reference
me.everything.badger.permission.BADGE_COUNT_WRITE	unknown	Unknown permission	Unknown permission from android reference



FILE	DETAILS
------	---------

FILE	DETAILS	
classes.dex	FINDINGS	DETAILS
	yara_issue	yara issue - dex file recognized by apkid but not yara module
	Anti-VM Code	Build.FINGERPRINT check Build.MODEL check Build.MANUFACTURER check Build.PRODUCT check Build.HARDWARE check Build.BOARD check Build.TAGS check SIM operator check network operator name check possible VM check
	Anti Debug Code	Debug.isDebuggerConnected() check
	Compiler	unknown (please file detection issue!)
classes10.dex	FINDINGS	DETAILS
	yara_issue	yara issue - dex file recognized by apkid but not yara module
	Anti-VM Code	Build.FINGERPRINT check Build.MANUFACTURER check Build.BOARD check possible Build.SERIAL check Build.TAGS check
	Anti Debug Code	Debug.isDebuggerConnected() check
	Compiler	unknown (please file detection issue!)
	Anti Disassembly Code	illegal class name

FILE	DETAILS	
classes11.dex	FINDINGS	DETAILS
	yara_issue	yara issue - dex file recognized by apkid but not yara module
	Anti-VM Code	Build.FINGERPRINT check Build.MODEL check Build.MANUFACTURER check Build.PRODUCT check Build.BOARD check Build.TAGS check network operator name check possible VM check
	Anti Debug Code	Debug.isDebuggerConnected() check
	Compiler	unknown (please file detection issue!)
	Anti Disassembly Code	illegal class name
classes12.dex	FINDINGS	DETAILS
	yara_issue	yara issue - dex file recognized by apkid but not yara module
	Anti-VM Code	Build.FINGERPRINT check Build.MODEL check Build.MANUFACTURER check Build.PRODUCT check Build.HARDWARE check Build.TAGS check SIM operator check network operator name check
	Compiler	unknown (please file detection issue!)
	Anti Disassembly Code	illegal class name

FILE	DETAILS	
classes13.dex	FINDINGS	DETAILS
	yara_issue	yara issue - dex file recognized by apkid but not yara module
	Anti-VM Code	Build.FINGERPRINT check Build.MODEL check Build.MANUFACTURER check Build.PRODUCT check Build.HARDWARE check Build.BOARD check Build.TAGS check SIM operator check
	Anti Debug Code	Debug.isDebuggerConnected() check
	Compiler	unknown (please file detection issue!)
classes14.dex	FINDINGS	DETAILS
	yara_issue	yara issue - dex file recognized by apkid but not yara module
	Anti-VM Code	Build.FINGERPRINT check Build.MODEL check Build.MANUFACTURER check Build.PRODUCT check Build.BOARD check
	Compiler	unknown (please file detection issue!)

FILE	DETAILS	
classes15.dex	FINDINGS	DETAILS
	yara_issue	yara issue - dex file recognized by apkid but not yara module
	Anti-VM Code	Build.MANUFACTURER check Build.BOARD check possible Build.SERIAL check
	Compiler	unknown (please file detection issue!)
	Anti Disassembly Code	illegal class name
classes16.dex	FINDINGS	DETAILS
	yara_issue	yara issue - dex file recognized by apkid but not yara module
	Anti-VM Code	Build.FINGERPRINT check SIM operator check network operator name check
	Compiler	unknown (please file detection issue!)
	Anti Disassembly Code	illegal class name

FILE	DETAILS	
classes17.dex	FINDINGS	DETAILS
	yara_issue	yara issue - dex file recognized by apkid but not yara module
	Anti-VM Code	Build.FINGERPRINT check Build.MANUFACTURER check
	Compiler	unknown (please file detection issue!)
classes2.dex	FINDINGS	DETAILS
	yara_issue	yara issue - dex file recognized by apkid but not yara module
	Anti-VM Code	Build.FINGERPRINT check Build.MANUFACTURER check
	Compiler	unknown (please file detection issue!)
	Anti Disassembly Code	illegal class name
classes3.dex	FINDINGS	DETAILS
	yara_issue	yara issue - dex file recognized by apkid but not yara module
	Anti-VM Code	Build.MANUFACTURER check
	Compiler	unknown (please file detection issue!)
	Anti Disassembly Code	illegal class name

FILE	DETAILS	
classes4.dex	FINDINGS	DETAILS
	yara_issue	yara issue - dex file recognized by apkid but not yara module
	Anti-VM Code	Build.MANUFACTURER check
	Compiler	unknown (please file detection issue!)
	Anti Disassembly Code	illegal class name
classes5.dex	FINDINGS	DETAILS
	yara_issue	yara issue - dex file recognized by apkid but not yara module
	Anti-VM Code	Build.MANUFACTURER check
	Compiler	unknown (please file detection issue!)
classes6.dex	FINDINGS	DETAILS
	yara_issue	yara issue - dex file recognized by apkid but not yara module
	Anti-VM Code	Build.MANUFACTURER check Build.BOARD check possible Build.SERIAL check
	Compiler	unknown (please file detection issue!)
	Anti Disassembly Code	illegal class name

FILE	DETAILS	
classes7.dex	FINDINGS	DETAILS
	yara_issue	yara issue - dex file recognized by apkid but not yara module
	Anti-VM Code	Build.FINGERPRINT check Build.MODEL check Build.MANUFACTURER check Build.PRODUCT check Build.BOARD check possible VM check
	Compiler	unknown (please file detection issue!)
	Anti Disassembly Code	illegal class name
classes8.dex	FINDINGS	DETAILS
	yara_issue	yara issue - dex file recognized by apkid but not yara module
	Anti Debug Code	Debug.isDebuggerConnected() check
	Anti-VM Code	Build.MANUFACTURER check Build.HARDWARE check SIM operator check network operator name check subscriber ID check
	Compiler	unknown (please file detection issue!)
	Anti Disassembly Code	illegal class name

FILE	DETAILS	
classes9.dex	FINDINGS	DETAILS
	yara_issue	yara issue - dex file recognized by apkid but not yara module
	Anti-VM Code	Build.FINGERPRINT check Build.MODEL check Build.MANUFACTURER check Build.PRODUCT check Build.HARDWARE check Build.BOARD check Build.TAGS check network operator name check emulator file check
	Compiler	unknown (please file detection issue!)
lib/arm64-v8a/libcrashlytics-common.so	FINDINGS	DETAILS
	anti_hook	syscalls
lib/arm64-v8a/libjingle_peerconnection_so.so	FINDINGS	DETAILS
	anti_hook	syscalls

 BROWSABLE ACTIVITIES

ACTIVITY	INTENT
----------	--------

ACTIVITY	INTENT
com.vkontakte.android.LinkRedirActivity	Schemes: vklink://, vkontakte://, vk://, http://, https://, content://, Hosts: vk.com, m.vk.com, vk.me, vk.link, vk.ru, m.vk.ru, vkvideo.ru, m.vkvideo.ru, qr.vk.com, qr.vk.ru, multiqr.vk.com, multiqr.vk.ru, sportmailru.vk.com, sportmailru.m.vk.com, sportmailru.vk.ru, sportmailru.m.vk.ru, Mime Types: @string/vnd_sendmsg, @string/vnd_profile, @string/vnd_voipcall, Path Patterns: /.*, /playlist.*, /video.*, /live.*, /landings.*, /legal.*, /app.*, /subscriptions.*, /lives.*, /videos.*, /groups.*, /@.*, /ca.*, /w2a.*, /rustore.*,
com.vkontakte.android.TestActivity	Schemes: vkontakte://, Hosts: test,
ru.ok.android.sdk.OkAuthActivity	Schemes: okauth://, Hosts: ok1258261760,
com.vk.superapp.logs.SuperappLogsActivity	Schemes: com.vkontakte.android.sak://, Hosts: logs,
com.vk.auth.external.VkExternalAuthActivity	Schemes: com.vkontakte.android://, Hosts: vkceexternalauth, vkceexternalauth-codeflow,
com.vk.confirmaccount.impl.VkConfirmUserByServiceActivity	Schemes: vk2274003://, Hosts: handle_external_user_confirmation,
com.vk.oauth.sber.verification.VkSberVerificationActivity	Schemes: vkid://, Hosts: @string/vk_sber_deeplink_host,
com.vk.auth.smartflow.impl.maxmessenger.MaxMessengerReturnActivity	Schemes: vk2274003://, Hosts: max_back_redirect,
com.vk.oauth.vtb.verification.VkVtbVerificationActivity	Schemes: vkid://, Hosts: @string/vk_vtb_deeplink_host,
com.vk.oauth.alfa.verification.VkAlfaVerificationActivity	Schemes: vkid://, Hosts: @string/vk_alfa_deeplink_host,
com.vk.oauth.esia.VkEsiaOAuthActivity	Schemes: com.vkontakte.android://, Hosts: @string/vk_esia_redirect_host,
com.vk.oauth.tinkoff.verification.VkTinkoffVerificationActivity	Schemes: vkid://, Hosts: @string/vk_tinkoff_deeplink_host,

ACTIVITY	INTENT
com.vk.auth.oauth.passkey.VkPasskeyWebAuthActivity	Schemes: vk2274003://, Hosts: vk.ru,

NETWORK SECURITY

HIGH: 1 | WARNING: 1 | INFO: 1 | SECURE: 0

NO	SCOPE	SEVERITY	DESCRIPTION
1	*	warning	Base config is configured to trust system certificates.
2	*	info	Base config is configured to trustbundled certs @raw/russian_trusted_root_ca.
3	127.0.0.1 localhost mobileid.megafon.ru idgw.mobileid.mts.ru he-mc.tele2.ru he-mc.t2.ru beeline.ru	high	Domain config is insecurely configured to permit clear text traffic to these domains in scope.

CERTIFICATE ANALYSIS

HIGH: 1 | WARNING: 0 | INFO: 1

TITLE	SEVERITY	DESCRIPTION
Signed Application	info	Application is signed with a code signing certificate
Certificate algorithm vulnerable to hash collision	high	Application is signed with SHA1withRSA. SHA1 hash algorithm is known to have collision issues.

MANIFEST ANALYSIS

HIGH: 0 | WARNING: 98 | INFO: 0 | SUPPRESSED: 0

NO	ISSUE	SEVERITY	DESCRIPTION
1	App can be installed on a vulnerable Android version 9, minSdk=28]	warning	This application can be installed on an older version of android that has multiple vulnerabilities. Support an Android version => 10, API 29 to receive reasonable security updates.
2	App has a Network Security Configuration[android:networkSecurityConfig=@xml/network_security_config]	info	The Network Security Configuration feature lets apps customize their network security settings in a safe, declarative configuration file without modifying app code. These settings can be configured for specific domains and for a specific app.
3	Application Data can be Backed up [android:allowBackup=true]	warning	This flag allows anyone to backup your application data via adb. It allows users who have enabled USB debugging to copy application data off of the device.
4	Activity-Alias (com.vk.android.launcher.icons.IconAlias.SpecialEventIcon1) is not Protected. [android:exported=true]	warning	An Activity-Alias is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
5	Activity-Alias (com.vk.android.launcher.icons.IconAlias.EventIconDuplicate9) is not Protected. [android:exported=true]	warning	An Activity-Alias is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
6	Activity-Alias (com.vk.android.launcher.icons.IconAlias.EventIconDuplicate8) is not Protected. [android:exported=true]	warning	An Activity-Alias is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
7	Activity-Alias (com.vk.android.launcher.icons.IconAlias.EventIconDuplicate7) is not Protected. [android:exported=true]	warning	An Activity-Alias is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
8	Activity-Alias (com.vk.android.launcher.icons.IconAlias.EventIconDuplicate6) is not Protected. [android:exported=true]	warning	An Activity-Alias is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
9	Activity-Alias (com.vk.android.launcher.icons.IconAlias.EventIconDuplicate5) is not Protected. [android:exported=true]	warning	An Activity-Alias is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
10	Activity-Alias (com.vk.android.launcher.icons.IconAlias.EventIconDuplicate4) is not Protected. [android:exported=true]	warning	An Activity-Alias is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
11	Activity-Alias (com.vk.android.launcher.icons.IconAlias.EventIconDuplicate3) is not Protected. [android:exported=true]	warning	An Activity-Alias is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
12	Activity-Alias (com.vk.android.launcher.icons.IconAlias.EventIconDuplicate2) is not Protected. [android:exported=true]	warning	An Activity-Alias is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
13	Activity-Alias (com.vk.android.launcher.icons.IconAlias.EventIconDuplicate1) is not Protected. [android:exported=true]	warning	An Activity-Alias is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.

[illegible]

NO	ISSUE	SEVERITY	DESCRIPTION
28	Activity-Alias (com.vk.android.launcher.icons.IconAlias.StaticIconDev5) is not Protected. [android:exported=true]	warning	An Activity-Alias is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
29	Activity-Alias (com.vk.android.launcher.icons.IconAlias.StaticIconDev4) is not Protected. [android:exported=true]	warning	An Activity-Alias is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
30	Activity-Alias (com.vk.android.launcher.icons.IconAlias.StaticIconDev3) is not Protected. [android:exported=true]	warning	An Activity-Alias is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
31	Activity-Alias (com.vk.android.launcher.icons.IconAlias.StaticIconDev2) is not Protected. [android:exported=true]	warning	An Activity-Alias is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
32	Activity-Alias (com.vk.android.launcher.icons.IconAlias.StaticIconDev) is not Protected. [android:exported=true]	warning	An Activity-Alias is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
33	Activity-Alias (com.vk.android.launcher.icons.IconAlias.StaticIcon6) is not Protected. [android:exported=true]	warning	An Activity-Alias is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
34	Activity-Alias (com.vk.android.launcher.icons.IconAlias.StaticIcon5) is not Protected. [android:exported=true]	warning	An Activity-Alias is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
35	Activity-Alias (com.vk.android.launcher.icons.IconAlias.StaticIcon4) is not Protected. [android:exported=true]	warning	An Activity-Alias is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
36	Activity-Alias (com.vk.android.launcher.icons.IconAlias.StaticIcon3) is not Protected. [android:exported=true]	warning	An Activity-Alias is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
37	Activity-Alias (com.vk.android.launcher.icons.IconAlias.StaticIcon2) is not Protected. [android:exported=true]	warning	An Activity-Alias is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
38	Activity-Alias (com.vk.android.launcher.icons.IconAlias.StaticIcon1) is not Protected. [android:exported=true]	warning	An Activity-Alias is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
39	Activity-Alias (com.vk.android.launcher.icons.IconAlias.DefaultIcon) is not Protected. [android:exported=true]	warning	An Activity-Alias is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
40	TaskAffinity is set for activity (com.vkontakte.android.FragmentWrapperActivity)	warning	If taskAffinity is set, then other application could read the Intents sent to Activities belonging to another task. Always use the default setting keeping the affinity as the package name in order to prevent sensitive information inside sent or received Intents from being read by another application.

NO	ISSUE	SEVERITY	DESCRIPTION
41	Activity (com.vkontakte.android.FragmentWrapperActivity) is Protected by a permission. Permission: com.vk.permission.INTERNAL</br>protectionLevel: signature [android:exported=true]	info	An Activity is found to be exported, but is protected by permission.
42	Activity (com.vk.auth.personalaccount.VkPersonalAccountActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
43	Activity (com.vk.auth.changepassword.VkChangePasswordActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
44	Activity (com.vkontakte.android.LinkRedirActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
45	TaskAffinity is set for activity (com.vk.libvideo.pip.VideoPipActivity)	warning	If taskAffinity is set, then other application could read the Intents sent to Activities belonging to another task. Always use the default setting keeping the affinity as the package name in order to prevent sensitive information inside sent or received Intents from being read by another application.
46	TaskAffinity is set for activity (com.vk.libvideo.pip.v2.activity.VideoContainerActivityWithPip)	warning	If taskAffinity is set, then other application could read the Intents sent to Activities belonging to another task. Always use the default setting keeping the affinity as the package name in order to prevent sensitive information inside sent or received Intents from being read by another application.
47	Activity (com.vkontakte.android.sharing.SharingExternalActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
48	Activity (com.vk.stories.StoryShareActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
49	Activity (com.vkontakte.android.SDKAuthActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
50	Activity (com.vkontakte.android.sdk.SDKInviteActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
51	Activity (com.vkontakte.android.TestActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
52	Activity (ru.ok.android.sdk.OkAuthActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.

NO	ISSUE	SEVERITY	DESCRIPTION
53	Activity (com.vkontakte.android.activities.AssistantSendMsgActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
54	Activity (com.vk.superapp.vkhealth.permissions.impl.policy.HealthConnectPolicyActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
55	Activity-Alias (com.vkontakte.android.ViewPermissionUsageActivity) is Protected by a permission, but the protection level of the permission should be checked. Permission: android.permission.START_VIEW_PERMISSION_USAGE [android:exported=true]	warning	An Activity-Alias is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.
56	Service (com.vkontakte.android.auto.MusicAndroidAutoMediaService) is not Protected. [android:exported=true]	warning	A Service is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
57	Broadcast Receiver (com.vkontakte.android.DebugBroadcastReceiver) is not Protected. [android:exported=true]	warning	A Broadcast Receiver is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
58	Broadcast Receiver (com.vkontakte.android.PackageAddedReceiver) is not Protected. [android:exported=true]	warning	A Broadcast Receiver is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
59	Broadcast Receiver (com.my.tracker.campaign.CampaignReceiver) is not Protected. [android:exported=true]	warning	A Broadcast Receiver is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
60	Broadcast Receiver (com.vk.usersstore.blockstore.deletereceiver.BlockstoreDeleteReceiver) is Protected by a permission.Permission: com.vk.blockstore.permission.DELETE</br>protectionLevel: signature [android:exported=true]	info	A Broadcast Receiver is found to be exported, but is protected by permission.
61	Activity (com.vk.superapp.logs.SuperappLogsActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
62	Broadcast Receiver (com.vk.superapp.logs.SuperappLogsBroadcastReceiver) is not Protected. [android:exported=true]	warning	A Broadcast Receiver is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
63	TaskAffinity is set for activity (com.vk.voip.VoipCallActivity)	warning	If taskAffinity is set, then other application could read the Intents sent to Activities belonging to another task. Always use the default setting keeping the affinity as the package name in order to prevent sensitive information inside sent or received Intents from being read by another application.

NO	ISSUE	SEVERITY	DESCRIPTION
64	Broadcast Receiver (ru.mail.libverify.platform.firebase.sms.SmsRetrieverReceiver) is Protected by a permission, but the protection level of the permission should be checked. Permission: com.google.android.gms.auth.api.phone.permission.SEND [android:exported=true]	warning	A Broadcast Receiver is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.
65	Broadcast Receiver (com.vk.companion.receiver.AccountInfoBroadcastReceiver) is Protected by a permission.Permission: com.vkontakte.android.permission.ACCESS_DATA</br>protectionLevel: signature [android:exported=true]	info	A Broadcast Receiver is found to be exported, but is protected by permission.
66	Content Provider (com.vk.companion.provider.AccountInfoContentProvider) is Protected by a permission.Permission: com.vkontakte.android.permission.ACCESS_DATA</br>protectionLevel: signature [android:exported=true]	info	A Content Provider is found to be exported, but is protected by permission.
67	Broadcast Receiver (com.vk.upload.impl.LoadingBroadcastReceiver) is not Protected. [android:exported=true]	warning	A Broadcast Receiver is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
68	Content Provider (com.vk.appredirects.provider.AppRedirectContentProvider) is Protected by a permission.Permission: com.vkontakte.android.permission.APP_REDIRECT</br>protectionLevel: signature [android:exported=true]	info	A Content Provider is found to be exported, but is protected by permission.
69	Service (androidx.media3.exoplayer.scheduler.PlatformScheduler\$PlatformSchedulerService) is Protected by a permission, but the protection level of the permission should be checked. Permission: android.permission.BIND_JOB_SERVICE [android:exported=true]	warning	A Service is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.
70	Service (com.vk.contacts.ContactSyncAdapterService) is not Protected. [android:exported=true]	warning	A Service is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.

NO	ISSUE	SEVERITY	DESCRIPTION
71	Broadcast Receiver (com.google.firebase.iid.FirebaseInstanceIdReceiver) is Protected by a permission, but the protection level of the permission should be checked. Permission: com.google.android.c2dm.permission.SEND [android:exported=true]	warning	A Broadcast Receiver is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.
72	Service (com.vk.push.rustore.impl.RuStorePushService) is not Protected. [android:exported=true]	warning	A Service is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
73	Service (com.vk.accountmanager.domain.interactor.VkAccountAuthenticatorService) is not Protected. [android:exported=true]	warning	A Service is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
74	TaskAffinity is set for activity (com.vk.auth.external.VkExternalAuthActivity)	warning	If taskAffinity is set, then other application could read the Intents sent to Activities belonging to another task. Always use the default setting keeping the affinity as the package name in order to prevent sensitive information inside sent or received Intents from being read by another application.
75	Activity (com.vk.auth.external.VkExternalAuthActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
76	Activity (com.vk.superapp.browser.internal.ui.shortcuts.ShortcutActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
77	Broadcast Receiver (com.vk.superapp.browser.utils.SuperAppLoadingBroadcastReceiver) is not Protected. [android:exported=true]	warning	A Broadcast Receiver is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
78	Activity (com.vk.confirmaccount.impl.VkConfirmUserByServiceActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
79	Activity (com.vk.oauth.sber.verificaiton.VkSberVerificationActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
80	Content Provider (com.vk.usersstore.contentprovider.UsersContentProvider) is not Protected. [android:exported=true]	warning	A Content Provider is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
81	Activity (com.vk.auth.smartflow.impl.maxmessenger.MaxMessengerReturnActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
82	Activity (com.vk.oauth.vtb.verificaiton.VkVtbVerificationActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.

NO	ISSUE	SEVERITY	DESCRIPTION
83	Service (com.vk.silentauth.host.SilentAuthService) is not Protected. [android:exported=true]	warning	A Service is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
84	Activity (com.vk.oauth.alfa.verifcation.VkAlfaVerificationActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
85	Activity (com.vk.oauth.esia.VkEsiaOAuthActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
86	Activity (com.vk.oauth.tinkoff.verifcation.VkTinkoffVerificationActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
87	Activity (com.vk.auth.oauth.passkey.VkPasskeyWebAuthActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
88	Content Provider (com.vk.core.deviceid.contentprovider.DeviceIdContentProvider) is Protected by a permission.Permission: com.vkontakte.android.permission.ACCESS_DATA</br>protectionLevel: signature [android:exported=true]	info	A Content Provider is found to be exported, but is protected by permission.
89	Broadcast Receiver (ru.rustore.sdk.pushclient.internal.arbiter.ArbiterBroadcastReceiver) is not Protected. [android:exported=true]	warning	A Broadcast Receiver is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
90	Broadcast Receiver (ru.mail.libverify.notifications.ChangePushPermissionsReceiver) is not Protected. [android:exported=true]	warning	A Broadcast Receiver is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
91	Broadcast Receiver (ru.mail.libverify.sms.IncomingSmsReceiver) is Protected by a permission, but the protection level of the permission should be checked. Permission: android.permission.BROADCAST_SMS [android:exported=true]	warning	A Broadcast Receiver is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.
92	Broadcast Receiver (ru.mail.libverify.sms.IncomingCallReceiver) is Protected by a permission, but the protection level of the permission should be checked. Permission: android.permission.READ_PHONE_STATE [android:exported=true]	warning	A Broadcast Receiver is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.

NO	ISSUE	SEVERITY	DESCRIPTION
93	Service (ru.mail.libverify.ipc.IpcMessageService) is Protected by a permission, but the protection level of the permission should be checked. Permission: android.permission.INTERNET [android:exported=true]	warning	A Service is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.
94	Service (ru.mail.libverify.ipc.IpcNotificationService) is Protected by a permission, but the protection level of the permission should be checked. Permission: android.permission.INTERNET [android:exported=true]	warning	A Service is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.
95	TaskAffinity is set for activity (ru.mail.libverify.notifications.SettingsActivity)	warning	If taskAffinity is set, then other application could read the Intents sent to Activities belonging to another task. Always use the default setting keeping the affinity as the package name in order to prevent sensitive information inside sent or received Intents from being read by another application.
96	TaskAffinity is set for activity (ru.mail.libverify.notifications.SmsCodeNotificationActivity)	warning	If taskAffinity is set, then other application could read the Intents sent to Activities belonging to another task. Always use the default setting keeping the affinity as the package name in order to prevent sensitive information inside sent or received Intents from being read by another application.
97	Service (androidx.work.impl.background.systemjob.SystemJobService) is Protected by a permission, but the protection level of the permission should be checked. Permission: android.permission.BIND_JOB_SERVICE [android:exported=true]	warning	A Service is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.
98	Broadcast Receiver (androidx.work.impl.diagnostics.DiagnosticsReceiver) is Protected by a permission, but the protection level of the permission should be checked. Permission: android.permission.DUMP [android:exported=true]	warning	A Broadcast Receiver is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.
99	Activity (androidx.compose.ui.tooling.PreviewActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.

NO	ISSUE	SEVERITY	DESCRIPTION
100	Service (com.google.android.gms.auth.api.signin.RevocationBoundService) is Protected by a permission, but the protection level of the permission should be checked. Permission: com.google.android.gms.auth.api.signin.permission.REVOCATION_NOTIFICATION [android:exported=true]	warning	A Service is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.
101	Service (androidx.health.platform.client.impl.sdkservice.HealthDataSdkService) is not Protected. [android:exported=true]	warning	A Service is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
102	Broadcast Receiver (androidx.profileinstaller.ProfileInstallReceiver) is Protected by a permission, but the protection level of the permission should be checked. Permission: android.permission.DUMP [android:exported=true]	warning	A Broadcast Receiver is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.
103	Dailer Code: \ 856682583 Found [android:scheme="android_secret_code"]	warning	A secret code was found in the manifest. These codes, when entered into the dialer grant access to hidden content that may contain sensitive information.
104	Dailer Code: *725 Found [android:scheme="android_secret_code"]	warning	A secret code was found in the manifest. These codes, when entered into the dialer grant access to hidden content that may contain sensitive information.
105	High Intent Priority (999) - {2} Hit(s) [android:priority]	warning	By setting an intent priority higher than another intent, the app effectively overrides other requests.

</> CODE ANALYSIS

NO	ISSUE	SEVERITY	STANDARDS	FILES
----	-------	----------	-----------	-------

🚩 SHARED LIBRARY BINARY ANALYSIS

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
1	armeabi-v7a/libgl-effects.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['_vsnprintf_chk', '__vsprintf_chk', '__memcpy_chk', '__strchr_chk', '__strlen_chk', '__read_chk', '__FD_SET_chk', '__FD_ISSET_chk', '__FD_CLR_chk', '__strcpy_chk', '__strcat_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
2	armeabi-v7a/libvkchronicle.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
3	armeabi-v7a/libtensorflowlite_gpu_delegate.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
4	armeabi-v7a/libvideo-message-stencils.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
5	armeabi-v7a/libtensorflowlite_jni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Partial RELRO warning This shared object has partial RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In partial RELRO, the non-PLT part of the GOT section is read only but .got.plt is still writeable. Use the option -z,relro,-z,now to enable full RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
6	armeabi-v7a/libgifimage.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
7	armeabi-v7a/libvk-jpeg-coder.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
8	armeabi-v7a/libtensorflowlite.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	\$ORIGIN:\$ORIGIN/..:\$ORIGIN/../../ high The binary has RUNPATH set. In certain cases, an attacker can abuse this feature and or modify environment variables to run arbitrary libraries for code execution and privilege escalation. The only time a library should set RUNPATH is when it is linked to private libraries in the same package. Remove the compiler option --enable-new-dtags,-rpath to remove RUNPATH.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
9	armeabi-v7a/libcnet.140.0.7339.52.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__read_chk', '__vsprintf_chk', '__memcpy_chk', '__pread64_chk', '__strncat_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
10	armeabi-v7a/libxhook.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
11	armeabi-v7a/libvkqrcode.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['_strchr_chk', '_memcpy_chk', '_vsnprintf_chk', '_memset_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
12	armeabi-v7a/libandroidx.graphics.path.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
13	armeabi-v7a/libcrashlytics.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
14	armeabi- v7a/libEnhancementLibShared.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', '__strlen_chk', '__memmove_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
15	armeabi-v7a/libnative-tensorflow-core-lib.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
16	armeabi-v7a/libzstd-jni-1.5.7-4.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Partial RELRO warning This shared object has partial RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In partial RELRO, the non-PLT part of the GOT section is read only but .got.plt is still writeable. Use the option -z,relro,-z,now to enable full RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
17	armeabi-v7a/libc++_shared.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
18	armeabi-v7a/libsqlite3x.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', '__memcpy_chk', '__strlen_chk', '__memset_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
19	armeabi-v7a/libopencv_java4.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strchr_chk', '__strlen_chk', '__vsprintf_chk', '__vsnprintf_chk', '__memcpy_chk', '__memset_chk', '__strcpy_chk', '__strcat_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
20	armeabi-v7a/libcrashlytics-trampoline.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Position Independent Executable (PIE) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
21	armeabi-v7a/libnative_tools.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk', '__vsprintf_chk', '__vsnprintf_chk', '__strchr_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
22	armeabi-v7a/libimagepipeline.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
23	armeabi-v7a/libnative-filters.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
24	armeabi-v7a/liblaplayer.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', '_vsnprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
25	armeabi-v7a/libcrashlytics-handler.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
26	armeabi-v7a/librtmp-jni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
27	armeabi-v7a/libvkrlottie.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strncpy_chk', '__vsnprintf_chk', '__memcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
28	armeabi-v7a/libjingle_peerconnection_so.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', '__strchr_chk', '__memcpy_chk', '__FD_SET_chk', '__FD_ISSET_chk', '__FD_CLR_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
29	armeabi-v7a/libaudio-effects.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
30	armeabi-v7a/libcrashlytics-common.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk', '__strlen_chk', '__read_chk', '__vsnprintf_chk', '__strchr_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
31	armeabi-v7a/libverify.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', '_vsnprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
32	armeabi-v7a/libstatic-webp.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', '__memcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
33	armeabi-v7a/libdatastore_shared_counter.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
34	armeabi-v7a/libvkmedia.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk', '__memset_chk', '__vsnprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
35	armeabi-v7a/libnative-imagetranscoder.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', '__strlen_chk', '__memcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
36	armeabi-v7a/libsqliteobserver.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
37	armeabi-v7a/libnative-net.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', '__read_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
38	armeabi-v7a/libvcore.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
39	armeabi-v7a/libtrhook2.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strcat_chk', '__vsprintf_chk', '__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
40	arm64-v8a/libgl-effects.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['_vsnprintf_chk', '__vsprintf_chk', '__memcpy_chk', '__strchr_chk', '__strlen_chk', '__read_chk', '__FD_SET_chk', '__FD_ISSET_chk', '__FD_CLR_chk', '__strcpy_chk', '__strcat_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
41	arm64-v8a/libvkchronicle.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
42	arm64-v8a/libtensorflowlite_gpu_delegate.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memmove_chk', '__strlen_chk', '__vsnprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
43	arm64-v8a/libvideo-message-stencils.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
44	arm64-v8a/libtensorflowlite_jni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Partial RELRO warning This shared object has partial RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In partial RELRO, the non-PLT part of the GOT section is read only but .got.plt is still writeable. Use the option -z,relro,-z,now to enable full RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
45	arm64-v8a/libgifimage.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
46	arm64-v8a/libvk-jpeg-coder.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
47	arm64-v8a/libtensorflowlite.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	\$ORIGIN:\$ORIGIN/..:\$ORIGIN/../../high The binary has RUNPATH set. In certain cases, an attacker can abuse this feature and or modify environment variables to run arbitrary libraries for code execution and privilege escalation. The only time a library should set RUNPATH is when it is linked to private libraries in the same package. Remove the compiler option --enable-new-dtags,-rpath to remove RUNPATH.	True info The binary has the following fortified functions: ['__memmove_chk', '__strlen_chk', '__vsnprintf_chk', '__read_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
48	arm64- v8a/libcnet.140.0.7339.52.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__read_chk', '__vsprintf_chk', '__memcpy_chk', '__pread64_chk', '__strncat_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
49	arm64-v8a/libxhook.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
50	arm64-v8a/libvkqrcode.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strchr_chk', '__memcpy_chk', '__memset_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
51	arm64-v8a/libandroidx.graphics.path.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
52	arm64-v8a/libcrashlytics.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
53	arm64-v8a/libEnhancementLibShared.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk', '__vsnprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
54	arm64-v8a/libnative-tensorflow-core-lib.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
55	arm64-v8a/libzstd-jni-1.5.7-4.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
56	arm64-v8a/libc++_shared.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
57	arm64-v8a/libsqlite3x.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['_vsnprintf_chk', ['__memcpy_chk', ['__strlen_chk', ['__memset_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
58	arm64-v8a/libopencv_java4.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strchr_chk', '__strlen_chk', '__vsprintf_chk', '__vsnprintf_chk', '__memcpy_chk', '__memset_chk', '__strcpy_chk', '__strcat_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
59	arm64-v8a/libcrashlytics-trampoline.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Position Independent Executable (PIE) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
60	arm64-v8a/libnative_tools.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk', '__vsprintf_chk', '__strchr_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
61	arm64-v8a/libimagepipeline.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
62	arm64-v8a/libnative-filters.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
63	arm64-v8a/liblaplayer.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['_vsprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
64	arm64-v8a/libcrashlytics-handler.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
65	arm64-v8a/librtmp-jni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strchr_chk', '__vsprintf_chk', '__memcpy_chk', '__strchr_chk', '__vsprintf_chk', '__strncpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
66	arm64-v8a/libvkrottie.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strncpy_chk', '__vsprintf_chk', '__memcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
67	arm64-v8a/libjingle_peerconnection_so.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', '__strchr_chk', '__memcpy_chk', '__FD_SET_chk', '__FD_ISSET_chk', '__FD_CLR_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
68	arm64-v8a/libaudio-effects.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
69	arm64-v8a/libcrashlytics-common.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk', '__strlen_chk', '__read_chk', '__strchr_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
70	arm64-v8a/libverify.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk', '__vsprintf_chk', '__read_chk', '__memmove_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
71	arm64-v8a/libstatic-webp.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
72	arm64-v8a/libdatastore_shared_counter.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
73	arm64-v8a/libvkmedia.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk', '__memset_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
74	arm64-v8a/libnative-imagetranscoder.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', '__strlen_chk', '__memcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
75	arm64-v8a/libsqliteobserver.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
76	arm64-v8a/libnative-net.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__read_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
77	arm64-v8a/libvcore.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
78	arm64-v8a/libtrhook2.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strcat_chk', '__vsprintf_chk', '__strlen_chk', '__memmove_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
79	armeabi-v7a/libgl-effects.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', '__vsprintf_chk', '__memcpy_chk', '__strchr_chk', '__strlen_chk', '__read_chk', '__FD_SET_chk', '__FD_ISSET_chk', '__FD_CLR_chk', '__strcpy_chk', '__strcat_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
80	armeabi-v7a/libvkchronicle.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
81	armeabi-v7a/libtensorflowlite_gpu_delegate.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
82	armeabi-v7a/libvideo-message-stencils.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
83	armeabi-v7a/libtensorflowlite_jni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Partial RELRO warning This shared object has partial RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In partial RELRO, the non-PLT part of the GOT section is read only but .got.plt is still writeable. Use the option -z,relro,-z,now to enable full RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
84	armeabi-v7a/libgifimage.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
85	armeabi-v7a/libvk-jpeg-coder.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
86	armeabi-v7a/libtensorflowlite.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	\$ORIGIN:\$ORIGIN/..:\$ORIGIN/../../ high The binary has RUNPATH set. In certain cases, an attacker can abuse this feature and or modify environment variables to run arbitrary libraries for code execution and privilege escalation. The only time a library should set RUNPATH is when it is linked to private libraries in the same package. Remove the compiler option --enable-new-dtags,-rpath to remove RUNPATH.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
87	armeabi-v7a/libcnet.140.0.7339.52.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__read_chk', '__vsprintf_chk', '__memcpy_chk', '__pread64_chk', '__strncat_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
88	armeabi-v7a/libxhook.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
89	armeabi-v7a/libvkqrcode.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['_strchr_chk', '_memcpy_chk', '_vsnprintf_chk', '_memset_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
90	armeabi-v7a/libandroidx.graphics.path.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
91	armeabi-v7a/libcrashlytics.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
92	armeabi-v7a/libEnhancementLibShared.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', '__strlen_chk', '__memmove_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
93	armeabi-v7a/libnative-tensorflow-core-lib.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
94	armeabi-v7a/libzstd-jni-1.5.7-4.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Partial RELRO warning This shared object has partial RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In partial RELRO, the non-PLT part of the GOT section is read only but .got.plt is still writeable. Use the option -z,relro,-z,now to enable full RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
95	armeabi-v7a/libc++_shared.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
96	armeabi-v7a/libsqlite3x.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['_vsnprintf_chk', ['__memcpy_chk', ['__strlen_chk', ['__memset_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
97	armeabi-v7a/libopencv_java4.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strchr_chk', '__strlen_chk', '__vsprintf_chk', '__vsnprintf_chk', '__memcpy_chk', '__memset_chk', '__strcpy_chk', '__strcat_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
98	armeabi-v7a/libcrashlytics-trampoline.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Position Independent Executable (PIE) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
99	armeabi-v7a/libnative_tools.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk', '__vsprintf_chk', '__vsnprintf_chk', '__strchr_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
100	armeabi-v7a/libimagepipeline.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
101	armeabi-v7a/libnative-filters.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
102	armeabi-v7a/liblaplayer.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', '_vsnprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
103	armeabi-v7a/libcrashlytics-handler.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
104	armeabi-v7a/librtmp-jni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
105	armeabi-v7a/libvkrlottie.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strncpy_chk', '__vsprintf_chk', '__memcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
106	armeabi-v7a/libjingle_peerconnection_so.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', '__strchr_chk', '__memcpy_chk', '__FD_SET_chk', '__FD_ISSET_chk', '__FD_CLR_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
107	armeabi-v7a/libaudio-effects.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
108	armeabi-v7a/libcrashlytics-common.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk', '__strlen_chk', '__read_chk', '__vsnprintf_chk', '__strchr_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
109	armeabi-v7a/libverify.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', '_vsnprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
110	armeabi-v7a/libstatic-webp.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', '__memcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
111	armeabi-v7a/libdatastore_shared_counter.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
112	armeabi-v7a/libvkmedia.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk', '__memset_chk', '__vsnprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
113	armeabi-v7a/libnative-imagetranscoder.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', '__strlen_chk', '__memcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
114	armeabi-v7a/libsqliteobserver.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
115	armeabi-v7a/libnative-net.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', '__read_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
116	armeabi-v7a/libvcore.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
117	armeabi-v7a/libtrhook2.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strcat_chk', '__vsprintf_chk', '__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
118	arm64-v8a/libgl-effects.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['_vsnprintf_chk', '__vsprintf_chk', '__memcpy_chk', '__strchr_chk', '__strlen_chk', '__read_chk', '__FD_SET_chk', '__FD_ISSET_chk', '__FD_CLR_chk', '__strcpy_chk', '__strcat_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
119	arm64-v8a/libvkchronicle.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
120	arm64-v8a/libtensorflowlite_gpu_delegate.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memmove_chk', '__strlen_chk', '__vsnprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
121	arm64-v8a/libvideo-message-stencils.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
122	arm64-v8a/libtensorflowlite_jni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Partial RELRO warning This shared object has partial RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In partial RELRO, the non-PLT part of the GOT section is read only but .got.plt is still writeable. Use the option -z,relro,-z,now to enable full RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
123	arm64-v8a/libgifimage.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
124	arm64-v8a/libvk-jpeg-coder.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
125	arm64-v8a/libtensorflowlite.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	\$ORIGIN:\$ORIGIN/..:\$ORIGIN/../../high The binary has RUNPATH set. In certain cases, an attacker can abuse this feature and or modify environment variables to run arbitrary libraries for code execution and privilege escalation. The only time a library should set RUNPATH is when it is linked to private libraries in the same package. Remove the compiler option --enable-new-dtags,-rpath to remove RUNPATH.	True info The binary has the following fortified functions: ['__memmove_chk', '__strlen_chk', '__vsnprintf_chk', '__read_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
126	arm64-v8a/libcnet.140.0.7339.52.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__read_chk', '__vsprintf_chk', '__memcpy_chk', '__pread64_chk', '__strncat_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
127	arm64-v8a/libxhook.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
128	arm64-v8a/libvkqrcode.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strchr_chk', '__memcpy_chk', '__memset_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
129	arm64-v8a/libandroidx.graphics.path.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
130	arm64-v8a/libcrashlytics.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
131	arm64-v8a/libEnhancementLibShared.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk', '__vsnprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
132	arm64-v8a/libnative-tensorflow-core-lib.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
133	arm64-v8a/libzstd-jni-1.5.7-4.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
134	arm64-v8a/libc++_shared.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
135	arm64-v8a/libsqlite3x.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['_vsnprintf_chk', ['__memcpy_chk', ['__strlen_chk', ['__memset_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
136	arm64-v8a/libopencv_java4.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strchr_chk', '__strlen_chk', '__vsprintf_chk', '__vsnprintf_chk', '__memcpy_chk', '__memset_chk', '__strcpy_chk', '__strcat_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
137	arm64-v8a/libcrashlytics-trampoline.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Position Independent Executable (PIE) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
138	arm64-v8a/libnative_tools.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk', '__vsprintf_chk', '__strchr_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
139	arm64-v8a/libimagepipeline.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
140	arm64-v8a/libnative-filters.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
141	arm64-v8a/liblaplayer.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['_vsprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
142	arm64-v8a/libcrashlytics-handler.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
143	arm64-v8a/librtmp-jni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strchr_chk', '__vsprintf_chk', '__memcpy_chk', '__strchr_chk', '__vsprintf_chk', '__strncpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
144	arm64-v8a/libvkrottie.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strncpy_chk', '__vsprintf_chk', '__memcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
145	arm64-v8a/libjingle_peerconnection_so.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', '__strchr_chk', '__memcpy_chk', '__FD_SET_chk', '__FD_ISSET_chk', '__FD_CLR_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
146	arm64-v8a/libaudio-effects.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
147	arm64-v8a/libcrashlytics-common.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk', '__strlen_chk', '__read_chk', '__strchr_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
148	arm64-v8a/libverify.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk', '__vsprintf_chk', '__read_chk', '__memmove_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
149	arm64-v8a/libstatic-webp.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
150	arm64-v8a/libdatastore_shared_counter.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
151	arm64-v8a/libvkmedia.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk', '__memset_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
152	arm64-v8a/libnative-imagetranscoder.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', '__strlen_chk', '__memcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
153	arm64-v8a/libsqliteobserver.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
154	arm64-v8a/libnative-net.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__read_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
155	arm64-v8a/libvcore.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
156	arm64-v8a/libtrhook2.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strcat_chk', '__vsprintf_chk', '__strlen_chk', '__memmove_chk']	True info Symbols are stripped.

NIAP ANALYSIS v1.3

NO	IDENTIFIER	REQUIREMENT	FEATURE	DESCRIPTION
----	------------	-------------	---------	-------------

FIREBASE DATABASES ANALYSIS

TITLE	SEVERITY	DESCRIPTION
App talks to a Firebase database	info	The app talks to Firebase database at https://api-project-841415684880.firebaseio.com
Firebase Remote Config disabled	secure	Firebase Remote Config is disabled for https://firebaseremoteconfig.googleapis.com/v1/projects/841415684880/namespaces/firebase:fetch?key=AlzaSyCL17U2Q5i1NVwlcXgMOZMidSRFHyGYgWM. This is indicated by the response: The response code is 403

ABUSED PERMISSIONS

TYPE	MATCHES	PERMISSIONS
Malware Permissions	17/25	android.permission.RECORD_AUDIO, android.permission.CAMERA, android.permission.INTERNET, android.permission.ACCESS_COARSE_LOCATION, android.permission.ACCESS_FINE_LOCATION, android.permission.READ_EXTERNAL_STORAGE, android.permission.WRITE_EXTERNAL_STORAGE, android.permission.VIBRATE, android.permission.WAKE_LOCK, android.permission.READ_CONTACTS, android.permission.ACCESS_NETWORK_STATE, android.permission.ACCESS_WIFI_STATE, android.permission.SYSTEM_ALERT_WINDOW, android.permission.READ_CALL_LOG, android.permission.RECEIVE_BOOT_COMPLETED, android.permission.READ_PHONE_STATE, android.permission.GET_ACCOUNTS
Other Common Permissions	14/44	android.permission.FOREGROUND_SERVICE, android.permission.MODIFY_AUDIO_SETTINGS, com.android.launcher.permission.INSTALL_SHORTCUT, android.permission.WRITE_CONTACTS, android.permission.BLUETOOTH, com.google.android.gms.permission.AD_ID, android.permission.ACTIVITY_RECOGNITION, android.permission.READ_CALENDAR, com.google.android.c2dm.permission.RECEIVE, android.permission.AUTHENTICATE_ACCOUNTS, android.permission.CHANGE_WIFI_STATE, android.permission.CHANGE_NETWORK_STATE, android.permission.CALL_PHONE, com.google.android.finsky.permission.BIND_GET_INSTALL_REFERRER_SERVICE

Malware Permissions:

Top permissions that are widely abused by known malware.

Other Common Permissions:

Permissions that are commonly abused by known malware.

OFAC SANCTIONED COUNTRIES

This app may communicate with the following OFAC sanctioned list of countries.

DOMAIN	COUNTRY/REGION
--------	----------------

DOMAIN MALWARE CHECK

DOMAIN	STATUS	GEOLOCATION
vk.cc	ok	IP: 198.18.0.25 Country: - Region: - City: - Latitude: 0.000000 Longitude: 0.000000 View: Google Map
dnsnl.alekberg.net	ok	IP: 198.18.0.26 Country: - Region: - City: - Latitude: 0.000000 Longitude: 0.000000 View: Google Map
chromium.dns.nextdns.io	ok	IP: 198.18.0.27 Country: - Region: - City: - Latitude: 0.000000 Longitude: 0.000000 View: Google Map
dns.sb	ok	IP: 198.18.0.28 Country: - Region: - City: - Latitude: 0.000000 Longitude: 0.000000 View: Google Map
www.w3.org	ok	IP: 198.18.0.29 Country: - Region: - City: - Latitude: 0.000000 Longitude: 0.000000 View: Google Map

DOMAIN	STATUS	GEOLOCATION
doh-01.spectrum.com	ok	IP: 198.18.0.30 Country: - Region: - City: - Latitude: 0.000000 Longitude: 0.000000 View: Google Map
id.vk.com	ok	IP: 198.18.0.31 Country: - Region: - City: - Latitude: 0.000000 Longitude: 0.000000 View: Google Map
developers.cloudflare.com	ok	IP: 198.18.0.32 Country: - Region: - City: - Latitude: 0.000000 Longitude: 0.000000 View: Google Map
www.webrtc.org	ok	IP: 198.18.0.33 Country: - Region: - City: - Latitude: 0.000000 Longitude: 0.000000 View: Google Map
cleanbrowsing.org	ok	IP: 198.18.0.34 Country: - Region: - City: - Latitude: 0.000000 Longitude: 0.000000 View: Google Map

DOMAIN	STATUS	GEOLOCATION
www.tensorflow.org	ok	IP: 198.18.0.35 Country: - Region: - City: - Latitude: 0.000000 Longitude: 0.000000 View: Google Map
doh.quickline.ch	ok	IP: 198.18.0.36 Country: - Region: - City: - Latitude: 0.000000 Longitude: 0.000000 View: Google Map
perfetto.dev	ok	IP: 198.18.0.37 Country: - Region: - City: - Latitude: 0.000000 Longitude: 0.000000 View: Google Map
dns.google	ok	IP: 198.18.0.38 Country: - Region: - City: - Latitude: 0.000000 Longitude: 0.000000 View: Google Map
odvr.nic.cz	ok	IP: 198.18.0.39 Country: - Region: - City: - Latitude: 0.000000 Longitude: 0.000000 View: Google Map

DOMAIN	STATUS	GEOLOCATION
alekberg.net	ok	IP: 198.18.0.40 Country: - Region: - City: - Latitude: 0.000000 Longitude: 0.000000 View: Google Map
dns64.dns.google	ok	IP: 198.18.0.41 Country: - Region: - City: - Latitude: 0.000000 Longitude: 0.000000 View: Google Map
dns11.quad9.net	ok	IP: 198.18.0.42 Country: - Region: - City: - Latitude: 0.000000 Longitude: 0.000000 View: Google Map
id.vk.ru	ok	IP: 198.18.0.43 Country: - Region: - City: - Latitude: 0.000000 Longitude: 0.000000 View: Google Map
chrome.cloudflare-dns.com	ok	IP: 198.18.0.44 Country: - Region: - City: - Latitude: 0.000000 Longitude: 0.000000 View: Google Map

DOMAIN	STATUS	GEOLOCATION
doh-02.spectrum.com	ok	IP: 198.18.0.45 Country: - Region: - City: - Latitude: 0.000000 Longitude: 0.000000 View: Google Map
developers.google.com	ok	IP: 198.18.0.46 Country: - Region: - City: - Latitude: 0.000000 Longitude: 0.000000 View: Google Map
nextdns.io	ok	IP: 198.18.0.47 Country: - Region: - City: - Latitude: 0.000000 Longitude: 0.000000 View: Google Map
m.vk.ru	ok	IP: 198.18.0.48 Country: - Region: - City: - Latitude: 0.000000 Longitude: 0.000000 View: Google Map
crashpad.chromium.org	ok	IP: 198.18.0.49 Country: - Region: - City: - Latitude: 0.000000 Longitude: 0.000000 View: Google Map

DOMAIN	STATUS	GEOLOCATION
www.google.com	ok	IP: 198.18.0.227 Country: - Region: - City: - Latitude: 0.000000 Longitude: 0.000000 View: Google Map
www.cisco.com	ok	IP: 198.18.0.50 Country: - Region: - City: - Latitude: 0.000000 Longitude: 0.000000 View: Google Map
m.vk.com	ok	IP: 198.18.0.51 Country: - Region: - City: - Latitude: 0.000000 Longitude: 0.000000 View: Google Map
webrtc.googleusercontent.com	ok	IP: 198.18.0.52 Country: - Region: - City: - Latitude: 0.000000 Longitude: 0.000000 View: Google Map
doh.xfinity.com	ok	IP: 198.18.0.53 Country: - Region: - City: - Latitude: 0.000000 Longitude: 0.000000 View: Google Map

DOMAIN	STATUS	GEOLOCATION
doh.dns.sb	ok	IP: 198.18.0.54 Country: - Region: - City: - Latitude: 0.000000 Longitude: 0.000000 View: Google Map
doh.cox.net	ok	IP: 198.18.0.55 Country: - Region: - City: - Latitude: 0.000000 Longitude: 0.000000 View: Google Map
dns10.quad9.net	ok	IP: 198.18.0.56 Country: - Region: - City: - Latitude: 0.000000 Longitude: 0.000000 View: Google Map
vk.com	ok	IP: 198.18.0.242 Country: - Region: - City: - Latitude: 0.000000 Longitude: 0.000000 View: Google Map
www.ietf.org	ok	IP: 198.18.0.57 Country: - Region: - City: - Latitude: 0.000000 Longitude: 0.000000 View: Google Map

DOMAIN	STATUS	GEOLOCATION
example.com	ok	IP: 198.18.0.58 Country: - Region: - City: - Latitude: 0.000000 Longitude: 0.000000 View: Google Map
crbug.com	ok	IP: 198.18.0.59 Country: - Region: - City: - Latitude: 0.000000 Longitude: 0.000000 View: Google Map
www.quad9.net	ok	IP: 198.18.0.60 Country: - Region: - City: - Latitude: 0.000000 Longitude: 0.000000 View: Google Map
public.dns.iij.jp	ok	IP: 198.18.0.61 Country: - Region: - City: - Latitude: 0.000000 Longitude: 0.000000 View: Google Map
vk.ru	ok	IP: 198.18.0.73 Country: - Region: - City: - Latitude: 0.000000 Longitude: 0.000000 View: Google Map

DOMAIN	STATUS	GEOLOCATION
vkvideo.ru	ok	IP: 198.18.0.62 Country: - Region: - City: - Latitude: 0.000000 Longitude: 0.000000 View: Google Map
doh.cleanbrowsing.org	ok	IP: 198.18.0.63 Country: - Region: - City: - Latitude: 0.000000 Longitude: 0.000000 View: Google Map
policy.public.dns.ijj.jp	ok	IP: 198.18.0.64 Country: - Region: - City: - Latitude: 0.000000 Longitude: 0.000000 View: Google Map
doh.familyshield.opendns.com	ok	IP: 198.18.0.65 Country: - Region: - City: - Latitude: 0.000000 Longitude: 0.000000 View: Google Map
www.gstatic.com	ok	IP: 198.18.0.66 Country: - Region: - City: - Latitude: 0.000000 Longitude: 0.000000 View: Google Map

DOMAIN	STATUS	GEOLOCATION
m.vkvideo.ru	ok	IP: 198.18.0.67 Country: - Region: - City: - Latitude: 0.000000 Longitude: 0.000000 View: Google Map
www.nic.cz	ok	IP: 198.18.0.68 Country: - Region: - City: - Latitude: 0.000000 Longitude: 0.000000 View: Google Map
dns.quad9.net	ok	IP: 198.18.0.69 Country: - Region: - City: - Latitude: 0.000000 Longitude: 0.000000 View: Google Map
music.vk.com	ok	IP: 198.18.0.70 Country: - Region: - City: - Latitude: 0.000000 Longitude: 0.000000 View: Google Map
api-project-841415684880.firebaseio.com	ok	IP: 198.18.0.22 Country: - Region: - City: - Latitude: 0.000000 Longitude: 0.000000 View: Google Map

DOMAIN	STATUS	GEOLOCATION
doh.opendns.com	ok	IP: 198.18.0.71 Country: - Region: - City: - Latitude: 0.000000 Longitude: 0.000000 View: Google Map
aomediadecodec.github.io	ok	IP: 198.18.0.72 Country: - Region: - City: - Latitude: 0.000000 Longitude: 0.000000 View: Google Map
dns.levonet.sk	ok	IP: 198.18.0.73 Country: - Region: - City: - Latitude: 0.000000 Longitude: 0.000000 View: Google Map

EMAILS

EMAIL	FILE
info@sportmail.ru	Android String Resource
appro@openssl.org	lib/arm64-v8a/libcronet.140.0.7339.52.so
appro@openssl.org	lib/arm64-v8a/libjingle_peerconnection_so.so
appro@openssl.org	apktool_out/lib/arm64-v8a/libcronet.140.0.7339.52.so
appro@openssl.org	apktool_out/lib/arm64-v8a/libjingle_peerconnection_so.so

TRACKERS

TRACKER	CATEGORIES	URL
AppMonet		https://reports.exodus-privacy.eu.org/trackers/163
Fyber	Advertisement	https://reports.exodus-privacy.eu.org/trackers/104
Google CrashLytics	Crash reporting	https://reports.exodus-privacy.eu.org/trackers/27
Google Firebase Analytics	Analytics	https://reports.exodus-privacy.eu.org/trackers/49
Huawei Mobile Services (HMS) Core	Location, Advertisement, Analytics	https://reports.exodus-privacy.eu.org/trackers/333
IAB Open Measurement	Advertisement, Identification	https://reports.exodus-privacy.eu.org/trackers/328
Mintegral	Advertisement, Analytics	https://reports.exodus-privacy.eu.org/trackers/200
OpenTelemetry (OpenCensus, OpenTracing)	Analytics	https://reports.exodus-privacy.eu.org/trackers/412
Unity3d Ads	Advertisement	https://reports.exodus-privacy.eu.org/trackers/121
Vkontakte SDK	Identification	https://reports.exodus-privacy.eu.org/trackers/382
Yandex Ad	Advertisement	https://reports.exodus-privacy.eu.org/trackers/124
myTarget	Advertisement	https://reports.exodus-privacy.eu.org/trackers/198
myTracker		https://reports.exodus-privacy.eu.org/trackers/175

HARDCODED SECRETS

POSSIBLE SECRETS
"vk_auth_sign_up_gender_male" : "Чоловіча"
"clips_coauthors_selected_single_subtitle" : "Co-creator"

POSSIBLE SECRETS
"clips_coauthors_select_button" : "Պահպանել"
"comment_author" : "Müəllif"
"stickers_cancel_unsubscribe_author_menu" : "Назад"
"clips_coauthors_accessibility_list_item_select_click_label" : "ընտրել"
"audiobook_author" : "muallif"
"vk_auth_accessibility_close" : "Yopish"
"clips_coauthors_select_button" : "Saxlamaq"
"vk_auth_max_messenger_check_button" : "Մտնել"
"comment_channel_author" : "Canal"
"vk_auth_register" : "Registrarse"
"vk_auth_retry" : "Atualizar"
"vk_auth_retry" : "Yeniləmək"
"clips_coauthors_pending_list_item_selected_accessibility_group" : "Seleccionado"
"voip_session_room_admin_participant_move" : "Перемясціць"
"music_audio_book_author" : "müəllif"
"clip_grid_author_tell_about_yourself_description" : "Description"
"attached_clips_clip_has_coauthors" : "Cocreado"
"vk_auth_log_in" : "Entrar"
"accessibility_video_author_avatar_tap_action" : "Перейти"
"voip_session_room_admin_room_participant_status_pending" : "Kutulmoqda..."

POSSIBLE SECRETS
"live_broadcast_settings_header_author_title" : "Айтап"
"clips_edit_coauthors_selected_multi_subtitle" : "Համահեղինակներ"
"clips_coauthors_bs_user_unsubscribe_accessibility" : "жазылмай"
"voip_session_room_admin_room_close_all_dialog_cancel" : "Ləğv"
"vk_auth_related_user_pin_close_talkback" : "Cerrar"
"catalog_sport_widget_match_hockey_full_time" : "Natija"
"clips_publish_with_coauthors_alert_cancel" : "Cancel"
"vk_qr_auth_location" : "Location"
"voip_session_room_admin_set_time_limit_min_pattern" : "%d мин"
"catalog_sport_widget_match_hockey_full_time" : "Resultado"
"vk_qr_auth_service" : "Сервис"
"clips_coauthors_accept_invite" : "Nhận"
"clips_coauthors_bs_user_not_subscribed" : "Підписатися"
"coauthor_restriction_privacy_dialog_cancel" : "Huỷ"
"vk_auth_remove_user_title" : "Tasdiqlash"
"clips_coauthors_select_button" : "Salvar"
"vk_auth_phone_permissions_grant" : "Продовжити"
"voip_session_room_admin_room_participant_status_admin" : "Адміністратор"
"clips_coauthors_bs_user_subscribed" : "Following"
"tracer_app_token" : "Y2EZ8uSPZfZnH9FcZSTpPnDKu8nY0vIm7TrBkE2GnbA0"

POSSIBLE SECRETS
"vk_auth_sign_up_choose_gender_title" : "Жыныс"
"coauthor_restriction_privacy_dialog_save" : "Зберегти"
"catalog_sport_widget_match_hockey_extra_time" : "Оվերтайм"
"vk_auth_accessibility_back" : "Voltar"
"vk_auth_use_smart_lock_data_positive" : "Yes"
"clip_grid_author_tell_about_yourself_description" : "Նկարագրություն"
"vk_auth_sign_up_gender_male" : "Kişi"
"clips_coauthors_pending_list_item_selected_accessibility_female" : "Выбрана"
"vk_auth_code_by_push" : "Code"
"live_author" : "Autor"
"coauthor_restriction_privacy_dialog_cancel" : "Cancel"
"vk_auth_use_smart_lock_data_positive" : "Так"
"vk_auth_max_messenger_check_button" : "Войти"
"catalog_sport_widget_match_hockey_after_match_penalties" : "Буліты"
"vk_auth_remove_cancel" : "Cancelar"
"voip_session_room_admin_room_participant_status_admin" : "Ադմինիստրատոր"
"voip_session_room_admin_set_time_limit_min_pattern" : "%d хв"
"clip_grid_author_information_bottomsheet_title" : "Informações"
"clips_coauthors_accept_invite" : "Ընդունել"
"voip_session_room_admin_room_countdown_timer_close_dialog_cancel" : "Болдырмай"

POSSIBLE SECRETS

"voip_session_room_admin_room_participant_status_pending" : "Ожидание..."

"voip_session_room_admin_room_participant_status_pending" : "Күтүдө..."

"coauthor_restriction_privacy_dialog_cancel" : "Cancelar"

"voip_session_room_admin_participant_move" : "Перемістити"

"video_filters_authors" : "Авторы"

"coauthor_restriction_privacy_dialog_ok" : "Editar"

"story_question_option_block_user" : "Արգելափակել"

"vk_auth_phone_permissions_grant" : "Շարունակել"

"vk_auth_account_continue" : "Продовжити"

"vk_auth_sign_up_last_name" : "Sobrenome"

"stickers_cancel_unsubscribe_author_menu" : "Հեռ"

"voip_session_room_admin_set_time_limit_min_pattern" : "%d phút"

"music_audio_book_author" : "авторы"

"vk_qr_auth_ip_address" : "IP-адреса"

"attached_clips_clip_has_coauthors_button_cancel" : "Tushunarli"

"vk_auth_retry" : "Actualizar"

"clips_coauthors_decline_invite" : "Decline"

"libverify_application_key" : "Pnxo7xcRjuXSldlh"

"voip_session_room_admin_room_countdown_timer_close_dialog_cancel" : "Ləğv"

"vk_auth_sign_up_last_name" : "Familiya"

POSSIBLE SECRETS

"vk_auth_phone_bind_phone" : "Байластыру"

"vk_auth_account_continue" : "Продолжить"

"vk_auth_use_smart_lock_data_positive" : "Да"

"vk_auth_use_smart_lock_data_positive" : "Sı"

"vk_auth_related_user_pin_close_talkback" : "Bağlamaq"

"menu_item_ban_user" : "Block"

"audiobook_author" : "автор"

"clip_grid_author_tell_about_yourself_retry" : "Təkrarlamaq"

"clips_coauthors_pending_list_item_select_click_label" : "Tanlash"

"voip_session_room_admin_room_participant_status_admin" : "Администратор"

"vk_auth_register" : "Зарегистрироваться"

"clips_coauthors_selected_multi_subtitle" : "Hammualiflar"

"vk_auth_related_pin_code_cancel" : "Нуъ"

"clips_coauthors_pending_list_item_select_click_label" : "таңдау"

"clips_coauthors_select_button" : "Сақтау"

"clips_coauthors_accessibility_list_item_select_click_label" : "tanlash"

"clips_coauthors_bs_user_unsubscribe_accessibility" : "отписаться"

"vkim_contact_unblock_user" : "Разблакаваць"

"voip_session_room_leave_watch_together_submit_no" : "Cancel"

"vk_auth_remove_cancel" : "Скасувати"

POSSIBLE SECRETS

"accessibility_video_author_avatar_tap_action" : "Keçmək"

"vk_auth_or" : "o"

"voip_session_room_leave_watch_together_submit_no" : "Ləğv"

"vk_auth_accessibility_close" : "Cerrar"

"vk_auth_phone_permissions_grant" : "Продолжить"

"clips_coauthors_accessibility_list_item_select_click_label" : "выбращь"

"clips_coauthors_selected_single_subtitle" : "Cocreator"

"clips_coauthors_select_button" : "Save"

"attached_clips_clip_has_coauthors" : "Co-created"

"vk_auth_enter_email_continue" : "Continue"

"ads_easy_promote_user" : "Рекламировать"

"vk_auth_phone_bind_phone" : "Привязать"

"vk_mv_k_auth_title" : "Confirmación"

"coauthor_restriction_privacy_dialog_save" : "Захаваць"

"vk_auth_sign_up_gender_female" : "Qadin"

"vk_auth_sign_up_gender_male" : "Male"

"clips_coauthors_selected_single_subtitle" : "Coautor"

"vk_auth_phone_bind_phone" : "Bog'lash"

"vk_mv_k_auth_title" : "Confirmation"

"clips_coauthors_selection_accessibility_close" : "Bağlamaq"

POSSIBLE SECRETS
"coauthor_restriction_privacy_dialog_cancel" : "Չեղարկել"
"menu_item_unban_user" : "Unblock"
"clips_publish_with_coauthors_alert_delete" : "Edit"
"clips_edit_coauthors_selected_single_subtitle" : "Авторлас"
"voip_session_room_admin_room_participant_status_pending" : "Waiting..."
"vk_auth_accessibility_close" : "Закреть"
"voip_session_room_admin_room_participant_status_creator" : "Ստեղծող"
"clips_edit_privacy_with_coauthors_cancel" : "Отмена"
"clips_coauthors_refuse_dialog_cancel" : "Адмена"
"clips_coauthors_pending_list_item_selected_accessibility_group" : "Вибрано"
"vk_auth_or" : "yoki"
"vk_auth_related_pin_code_cancel" : "Болдырмау"
"vk_qr_auth_location" : "Місцезнаходження"
"clips_coauthors_selected_single_subtitle" : "Համահեղինակ"
"voip_session_room_admin_participants_not_in_room" : "Тағайындалмаған"
"clips_edit_coauthors_selected_multi_subtitle" : "Снівавтори"
"vk_auth_phone_bind_phone" : "Birləşdirmək"
"voip_session_room_admin_room_close_all_dialog_cancel" : "Болдырмау"
"voip_session_room_admin_room_participant_status_admin" : "Administrador"
"vk_auth_phone_bind_phone" : "Чыауել"

POSSIBLE SECRETS

"coauthor_restriction_privacy_dialog_save" : "Guardar"

"catalog_sport_widget_match_hockey_after_match_penalties" : "Буллиты"

"clips_edit_privacy_with_coauthors_change" : "Змяніць"

"clip_grid_author_tell_about_yourself_exit" : "Выйти"

"voip_session_room_admin_spread_participants_randomly_dialog_cancel" : "Զեղարկել"

"vk_auth_password" : "Пароль"

"coauthor_restriction_privacy_dialog_save" : "Saxlamaq"

"vk_auth_code_by_push" : "Код"

"voip_session_room_admin_room_participant_status_creator" : "Стваральнік"

"voip_session_room_admin_set_time_limit_min_pattern" : "%d min"

"voip_session_room_admin_spread_participants_randomly_dialog_cancel" : "Cancel"

"vk_qr_auth_ip_address" : "IP-manzil"

"clips_coauthors_accessibility_author_selected_female" : "seleccionada"

"vk_qr_auth_open_internal_camera_alert_cancel_btn" : "Адмена"

"vk_auth_retry" : "Обновить"

"subscriptions_donut_category_authors" : "Müəlliflər"

"clips_edit_privacy_with_coauthors_change" : "Cambiar"

"voip_session_room_admin_save_room_participants" : "Salvar"

"coauthor_restriction_privacy_dialog_cancel" : "Скасувати"

"clips_coauthors_bs_user_not_subscribed" : "Seguir"

POSSIBLE SECRETS
"ads_easy_promote_user" : "Promocionar"
"live_broadcast_settings_header_author_title" : "Авторы"
"clip_grid_author_tell_about_yourself_cancel" : "Չեղարկել"
"vkim_contact_unblock_user" : "Արգելաբացել"
"clips_coauthors_pending_list_item_select_click_label" : "выбращь"
"voip_call_user" : "Չախզել"
"video_donate_author" : "Підтримати"
"music_audio_book_author" : "muallif"
"story_question_option_block_user" : "Block"
"vk_auth_retry" : "Yangilash"
"vk_auth_related_user_pin_close_talkback" : "Закрити"
"clip_grid_author_tell_about_yourself_exit" : "Thoát"
"vk_auth_continue" : "Continue"
"vk_auth_account_continue" : "Жалғастыру"
"vk_auth_continue" : "Жалғастыру"
"live_author" : "Müəllif"
"clips_publish_with_coauthors_alert_cancel" : "Скасувати"
"vk_auth_use_smart_lock_data_positive" : "Sim"
"vk_auth_remove_accept" : "Hoá"
"vk_qr_auth_service" : "Serviço"

POSSIBLE SECRETS
"vk_auth_sign_up_gender_male" : "Nam"
"vk_auth_enter_email_skip" : "Пропустити"
"voip_call_user" : "Позвонить"
"clips_coauthors_invitation_fullscreen_button" : "Responder"
"firebase_database_url" : "https://api-project-841415684880.firebaseio.com"
"posting_author_source_type_community" : "Համայնքում"
"voip_session_room_admin_room_participant_status_creator" : "Criador"
"vk_auth_related_user_pin_close_talkback" : "Đóng"
"clip_grid_author_tell_about_yourself_description" : "Descripción"
"catalog_sport_widget_match_hockey_after_match_penalties" : "Bullitt"
"audiobook_author" : "author"
"clips_coauthors_invitation_fullscreen_button" : "Відповісти"
"voip_session_room_admin_save_room_participants" : "Зберегти"
"clips_coauthors_selection_accessibility_close" : "Закрыць"
"audiobook_author" : "հեղինակ"
"voip_session_room_admin_set_time_limit_min_pattern" : "%d daq"
"clips_coauthors_accessibility_author_selected_group" : "seleccionado"
"vk_auth_enter_email_skip" : "Pular"
"vk_auth_remove_user_title" : "Подтверждение"
"audiobook_author" : "аўтар"

POSSIBLE SECRETS
"ads_easy_promote_user" : "Жарнамалау"
"vk_auth_help_button" : "Help"
"clips_coauthors_accessibility_list_item_select_click_label" : "выбрати"
"voip_session_room_admin_participant_move" : "Mover"
"video_analytics_author" : "Վերլուծություն"
"voip_session_room_admin_room_close_all_dialog_cancel" : "Адмена"
"vk_auth_sign_up_gender_male" : "Արական"
"voip_session_room_admin_room_participant_status_admin" : "Адміністратор"
"voip_session_room_admin_room_participant_status_creator" : "Creator"
"voip_session_room_admin_save_room_participants" : "Захаваць"
"vk_auth_account_continue" : "Continuar"
"clips_edit_coauthors_selected_multi_subtitle" : "Сааўтары"
"comment_channel_author" : "Channel"
"voip_session_room_admin_spread_participants_randomly_dialog_cancel" : "Адмена"
"vk_qr_auth_open_internal_camera_alert_cancel_btn" : "Отмена"
"vk_auth_choose_country_title" : "Perion"
"clip_grid_author_tell_about_yourself_retry" : "Паўтарыць"
"vk_qr_auth_location" : "Месцазнаходжанне"
"clips_coauthors_decline_invite" : "Отклонить"
"vk_auth_sign_up_gender_female" : "Իգական"

POSSIBLE SECRETS
"vk_auth_sign_up_last_name" : "Прозвішча"
"clips_coauthors_select_button" : "Захаваць"
"vk_auth_code_by_push" : "Mă"
"catalog_sport_widget_match_hockey_after_match_penalties" : "Bullitlər"
"clips_coauthors_selected_multi_subtitle" : "Cocreadores"
"catalog_sport_widget_match_hockey_full_time" : "Результат"
"clips_edit_coauthors_selected_single_subtitle" : "Համահեղինակ"
"clips_coauthors_accessibility_author_selected_group" : "таңдалған"
"clips_coauthors_bs_user_not_subscribed" : "Yazılmaq"
"vk_qr_auth_service" : "Xidmət"
"vk_auth_sign_up_gender_male" : "Мужской"
"vk_auth_help_button" : "OqunLəjnLü"
"clips_coauthors_accessibility_list_item_select_click_label" : "chọn"
"vk_qr_auth_service" : "Xizmat"
"clips_coauthors_selected_single_subtitle" : "Авторлас"
"modal_post_donut_user" : "%dP"
"vk_auth_choose_country_title" : "Região"
"clips_edit_coauthors_selected_multi_subtitle" : "Авторластар"
"vk_auth_continue" : "Продолжить"
"clip_grid_author_tell_about_yourself_retry" : "Повторити"

POSSIBLE SECRETS
"vk_qr_auth_service" : "Сэpvic"
"video_filters_authors" : "Автори"
"clips_coauthors_accept_invite" : "Аceptar"
"vk_auth_continue" : "Продовжити"
"voip_session_room_admin_spread_participants_randomly_dialog_cancel" : "Отмена"
"vk_auth_use_smart_lock_data_negative" : "Không"
"clips_coauthors_accessibility_author_selected_female" : "seçilib"
"attached_clips_clip_has_coauthors_button_cancel" : "Зразумела"
"clips_coauthors_bs_user_not_subscribed" : "Inscrever-se"
"voip_session_room_admin_participant_move" : "Переместить"
"vk_qr_auth_service" : "Ծառայություն"
"voip_session_room_admin_room_participant_status_pending" : "Gözləmə..."
"vk_auth_use_smart_lock_data_negative" : "Yo'q"
"posting_step2_coauthor_title" : "Авторлас"
"vk_auth_accessibility_back" : "Atrás"
"clips_coauthors_invitation_fullscreen_button" : "Ответить"
"accessibility_video_author_avatar_tap_action" : "O'tish"
"voip_call_user" : "Ligar"
"vk_auth_or" : "or"
"clips_coauthors_bs_user_unsubscribe_accessibility" : "ապարաժնեգրվել"

POSSIBLE SECRETS

"vk_auth_remove_cancel" : "Отменить"

"clips_coauthors_pending_list_item_select_click_label" : "вибрати"

"ads_easy_promote_user" : "Рекламувати"

"vk_auth_sign_up_first_name" : "Ім'я"

"vk_auth_sign_up_last_name" : "Apellido"

"voip_session_room_admin_room_participant_status_creator" : "Творець"

"clips_coauthors_selected_multi_subtitle" : "Համահեղինակներ"

"video_subscribe_author" : "Подписаться"

"clips_edit_privacy_with_coauthors_cancel" : "Скасувати"

"vk_auth_sign_up_first_name" : "Ім'я"

"subscriptions_donut_category_authors" : "Creators"

"clips_edit_privacy_with_coauthors_cancel" : "Болдырымау"

"clips_coauthors_bs_user_subscribed" : "Siguiendo"

"clips_coauthors_pending_list_item_selected_accessibility_group" : "Selected"

"article_tab_user" : "Profildan"

"vk_auth_enter_email_continue" : "Prosseguir"

"vk_auth_enter_email_skip" : "Пропусціць"

"clips_coauthors_pending_list_item_selected_accessibility_group" : "Tanlandi"

"ads_easy_promote_user" : "Promote"

"audiobook_person_author_toolbar" : "Автор"

POSSIBLE SECRETS
"coauthor_restriction_privacy_dialog_ok" : "Баттай"
"modal_post_donut_user" : "%d P"
"clip_grid_author_tell_about_yourself_cancel" : "Отмена"
"vk_auth_related_pin_code_cancel" : "Отмена"
"vk_auth_use_smart_lock_data_positive" : "Bəli"
"voip_session_room_leave_watch_together_submit_no" : "Скасувати"
"voip_session_room_admin_set_time_limit_min_suffix" : "хв"
"clips_publish_with_coauthors_alert_delete" : "Alterar"
"voip_session_room_admin_room_participant_status_pending" : "Чаканне..."
"vk_auth_sign_up_gender_male" : "Мужчинскі"
"vkim_contact_unblock_user" : "Unblock"
"audiobook_author" : "müəllif"
"subscriptions_donut_category_authors" : "Аўтары"
"clips_coauthors_pending_list_item_selected_accessibility_male" : "Seçilib"
"vk_auth_sign_up_gender_male" : "Masculino"
"video_donate_author" : "Աջակցել"
"ads_easy_promote_user" : "Գովազդել"
"vk_auth_phone_permissions_grant" : "Continuar"
"vk_auth_remove_user_title" : "Растай"
"clips_coauthors_accept_invite" : "Aceitar"

POSSIBLE SECRETS

"live_author" : "Аўтар"

"audiobook_person_author_toolbar" : "Autor"

"catalog_sport_widget_match_hockey_full_time" : "Resultados"

"clip_grid_author_tell_about_yourself_cancel" : "Адмена"

"live_author" : "Հեղինակ"

"vk_auth_enter_email_continue" : "Continuar"

"vk_auth_continue" : "Працягнуць"

"clips_coauthors_selection_accessibility_close" : "Жабу"

"voip_session_room_admin_save_room_participants" : "Guardar"

"clips_edit_privacy_with_coauthors_change" : "Փոխել"

"clips_coauthors_accessibility_author_selected_group" : "вибрано"

"attached_clips_clip_has_coauthors_button_cancel" : "Зрозуміло"

"article_tab_user" : "Պրոֆիլից"

"vk_auth_password" : "Contraseña"

"voip_session_room_admin_save_room_participants" : "Сақтау"

"unblock_user" : "Unblock"

"comment_channel_author" : "Kênh"

"voip_session_room_admin_room_rename" : "Перайменаваць"

"vk_qr_auth_open_internal_camera_alert_cancel_btn" : "Չեղարկել"

"voip_session_room_admin_room_close_all_dialog_cancel" : "Скасувати"

POSSIBLE SECRETS
"vk_auth_code_by_app" : "Ծածկագիրը"
"vk_auth_remove_accept" : "Չնջել"
"clip_grid_author_tell_about_yourself_cancel" : "Скасувати"
"comment_author" : "Автор"
"vk_auth_sign_up_first_name" : "Ad"
"catalog_sport_widget_match_hockey_after_match_penalties" : "Булѝти"
"voip_session_room_admin_room_rename" : "Renomear"
"voip_session_room_admin_room_rename" : "Վերանվանել"
"vk_auth_vk_id" : "VK ID"
"vk_auth_accessibility_close" : "Փակել"
"voip_session_room_admin_room_countdown_timer_close_dialog_cancel" : "Չեղարկել"
"vk_auth_log_in" : "Kirish"
"clips_coauthors_bs_user_not_subscribed" : "Подписаться"
"clip_grid_author_tell_about_yourself_description" : "Опис"
"clips_coauthors_selected_multi_subtitle" : "Авторластар"
"clips_coauthors_pending_list_item_selected_accessibility_female" : "Selected"
"vk_auth_related_user_pin_close_talkback" : "Закрѝть"
"clips_edit_privacy_with_coauthors_cancel" : "Адмена"
"vk_auth_sign_up_last_name" : "Ազգանունը"
"vk_auth_choose_country_title" : "Регион"

POSSIBLE SECRETS
"clips_coauthors_pending_list_item_select_click_label" : "ընտրել"
"vk_auth_or" : "կամ"
"voip_session_room_admin_room_participant_status_admin" : "İnzibatçı"
"subscriptions_donut_category_authors" : "Mualliflar"
"clips_coauthors_pending_list_item_selected_accessibility_male" : "Выбраны"
"story_question_option_block_user" : "Chắn"
"subscriptions_donut_category_authors" : "Հեղինակներ"
"clip_grid_author_tell_about_yourself_title" : "Haqqınızda"
"vk_auth_help_button" : "Kömək"
"video_analytics_author" : "Analitika"
"clip_grid_author_tell_about_yourself_exit" : "Вийти"
"vk_auth_related_pin_code_cancel" : "Զեղարկել"
"clips_edit_coauthors_selected_multi_subtitle" : "Hammualliflar"
"clips_publish_with_coauthors_alert_cancel" : "Cancelar"
"stickers_cancel_unsubscribe_author_menu" : "Orqaga"
"vk_auth_or" : "ou"
"clips_coauthors_pending_list_item_selected_accessibility_male" : "Выбран"
"posting_author_source_type_profile" : "Պրոֆիլում"
"clips_coauthors_pending_list_item_selected_accessibility_group" : "Выбрана"
"music_audio_book_author" : "аўтар"

POSSIBLE SECRETS

"vk_auth_related_pin_code_cancel" : "Адмена"

"voip_session_room_admin_spread_participants_randomly_dialog_cancel" : "Болдырмай"

"ads_easy_promote_user" : "Рэкламаваць"

"clips_coauthors_accessibility_author_selected_group" : "выбрана"

"clips_coauthors_pending_list_item_selected_accessibility_group" : "Выбрано"

"clips_publish_with_coauthors_alert_cancel" : "Нұй"

"coauthor_restriction_privacy_dialog_save" : "Сохранить"

"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "Passkey"

"voip_session_room_admin_room_participant_status_pending" : "Уцшунлф..."

"clips_coauthors_accessibility_author_selected_female" : "таңдалған"

"clips_coauthors_selection_accessibility_close" : "Fechar"

"clips_publish_with_coauthors_alert_cancel" : "Болдырымай"

"vk_qr_auth_open_internal_camera_alert_cancel_btn" : "Скасувати"

"vk_auth_account_continue" : "Շարունակել"

"vk_auth_sign_up_first_name" : "Անունը"

"unblock_user" : "Desbloquear"

"clips_coauthors_pending_list_item_selected_accessibility_female" : "seçilib"

"comment_author" : "Author"

"clips_coauthors_accessibility_author_not_selected_group" : "Tanlanmadi"

"voip_session_room_admin_room_close_all_dialog_cancel" : "Չեղարկել"

POSSIBLE SECRETS

"vk_auth_call_in_flag_emoji_kz" : "👉👉👉👉👉👉👉👉👉👉"

"posting_step2_coauthor_title" : "Hammualif"

"vk_auth_account_continue" : "Continue"

"vk_auth_phone_permissions_grant" : "Працягнуць"

"article_tab_user" : "Profildən"

"video_filters_authors" : "Аўтары"

"clips_edit_privacy_with_coauthors_change" : "Өзгөртү"

"clips_coauthors_accessibility_author_selected_male" : "выбраны"

"vk_auth_accessibility_close" : "Fechar"

"voip_session_room_admin_room_rename" : "Перейменувати"

"voip_call_user" : "Llamar"

"clips_coauthors_selected_multi_subtitle" : "Соавторы"

"clips_publish_with_coauthors_alert_cancel" : "Адмена"

"live_broadcast_settings_header_author_title" : "Автор"

"catalog_sport_widget_match_hockey_full_time" : "Results"

"clips_coauthors_pending_list_item_select_click_label" : "seleccionar"

"vk_auth_password" : "Senha"

"clips_edit_privacy_with_coauthors_change" : "Изменить"

"clip_grid_author_information_bottomsheet_title" : "Məlumat"

"vk_auth_sign_up_first_name" : "Esim"

POSSIBLE SECRETS

"coauthor_restriction_privacy_dialog_save" : "Luu"

"voip_session_room_admin_set_time_limit_min_suffix" : "мин"

"vk_auth_sign_up_choose_gender_title" : "Sexo"

"vk_auth_related_user_pin_close_talkback" : "Жабы"

"video_filters_authors" : "Հեղինակներ"

"stickers_unsubscribe_author_menu" : "Жазылмай"

"voip_session_room_admin_set_time_limit_min_suffix" : "min"

"vk_auth_sign_up_enter_profile_info_birthday_title" : "Birthday"

"vk_auth_max_messenger_check_button" : "Kirish"

"attached_clips_clip_has_coauthors_button_cancel" : "OK"

"clips_coauthors_bs_user_unsubscribe_accessibility" : "unfollow"

"vk_auth_use_smart_lock_data_negative" : "Não"

"clips_coauthors_selected_single_subtitle" : "Соавтор"

"story_question_option_block_user" : "Blokash"

"vk_auth_use_smart_lock_data_negative" : "Жоқ"

"clips_coauthors_pending_list_item_select_click_label" : "seleccionar"

"clips_edit_privacy_with_coauthors_change" : "Dəyişmək"

"catalog_sport_widget_match_hockey_period_3" : "3-кезең"

"voip_session_room_join_title" : "Войти"

"clips_coauthors_accessibility_author_selected_female" : "tanlandi"

POSSIBLE SECRETS

"clips_edit_coauthors_selected_single_subtitle" : "Hammuallif"

"voip_session_room_admin_room_close_all_dialog_cancel" : "Cancelar"

"vk_auth_related_user_pin_close_talkback" : "Yopish"

"clips_coauthors_selected_multi_subtitle" : "Сааўтары"

"voip_session_room_admin_room_participant_status_creator" : "Muallif"

"coauthor_restriction_privacy_dialog_ok" : "Налаштувати"

"voip_session_room_admin_set_time_limit_min_suffix" : "п"

"voip_session_room_admin_save_room_participants" : "Saxlamaq"

"vk_file_provider_authority" : "com.vk.common.VKFileProvider"

"clips_edit_coauthors_selected_single_subtitle" : "Соавтор"

"vk_qr_auth_open_internal_camera_alert_cancel_btn" : "Cancelar"

"clip_grid_author_tell_about_yourself_description" : "Описание"

"vk_auth_remove_accept" : "Удалить"

"stickers_unsubscribe_author_menu" : "Ապրաժնեգրվել"

"voip_session_room_admin_room_participant_status_admin" : "Administrator"

"stickers_cancel_unsubscribe_author_menu" : "Geri"

"voip_call_user" : "Потелефонувати"

"clips_coauthors_pending_list_item_select_click_label" : "seçmək"

"vk_auth_sign_up_last_name" : "Фамилия"

"clips_coauthors_invitation_fullscreen_button" : "Պատասխանել"

POSSIBLE SECRETS

"video_subscribe_author" : "Падпісцаца"

"attached_clips_clip_has_coauthors" : "Hammuallifikda"

"voip_session_room_admin_spread_participants_randomly_dialog_cancel" : "Скасувати"

"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Contraseña"

"vk_auth_enter_email_continue" : "Жалғастыру"

"vk_auth_enter_email_skip" : "Saltar"

"vk_qr_auth_ip_address" : "IP-huugb"

"catalog_sport_widget_match_hockey_full_time" : "Нәтиже"

"vk_auth_log_in" : "Увійти"

"vk_auth_help_button" : "Данамога"

"clips_coauthors_bs_user_not_subscribed" : "Follow"

"clip_grid_author_tell_about_yourself_cancel" : "Болдырмау"

"vk_auth_sign_up_gender_female" : "Әйел"

"vk_auth_remove_user_title" : "Confirmar"

"vk_auth_accessibility_back" : "Orqaga"

"live_broadcast_settings_header_author_title" : "Autor"

"clip_grid_author_tell_about_yourself_retry" : "Takrorlash"

"vk_auth_sign_up_gender_female" : "Ayol"

"clips_coauthors_accessibility_author_selected_female" : "вибрано"

"voip_call_user" : "Пазваніць"

POSSIBLE SECRETS

"voip_session_room_admin_room_rename" : "Rename"

"catalog_sport_widget_match_hockey_period_3" : "3-davr"

"unlock_user" : "Разблокировать"

"vk_auth_sign_up_gender_female" : "Жіноча"

"vk_auth_choose_country_title" : "Տարածաշրջան"

"vk_auth_remove_cancel" : "Cancel"

"vk_auth_remove_user_title" : "Пацвярджэнне"

"story_question_option_block_user" : "Заблакаваць"

"vk_auth_choose_country_title" : "Аймақ"

"voip_session_room_admin_room_close_all_dialog_cancel" : "Отмена"

"vk_auth_sign_up_first_name" : "Ism"

"vk_auth_log_in" : "Kipy"

"vk_auth_related_pin_code_cancel" : "Cancel"

"video_filters_authors" : "Mualliflar"

"clips_coauthors_selection_accessibility_close" : "Фалқт"

"clips_coauthors_accessibility_list_item_select_click_label" : "select"

"subscriptions_donut_category_authors" : "Авторлар"

"voip_session_room_admin_participant_move" : "Move"

"vk_auth_phone_permissions_grant" : "Жалғастыру"

"catalog_sport_widget_match_hockey_extra_time" : "Овертайм"

POSSIBLE SECRETS

"clips_coauthors_accessibility_author_selected_female" : "selected"

"video_analytics_author" : "Análisis"

"voip_session_room_admin_participant_move" : "Տեղափոխել"

"stickers_cancel_unsubscribe_author_menu" : "Huỷ"

"story_question_option_block_user" : "Заблокувати"

"vk_auth_accessibility_back" : "Απτκα"

"clips_edit_coauthors_selected_single_subtitle" : "Cocreator"

"comment_channel_author" : "Ալիք"

"vk_auth_password" : "Գաղտնաբառ"

"stickers_unsubscribe_author_menu" : "Unfollow"

"clips_coauthors_decline_invite" : "Rejeitar"

"voip_session_room_admin_room_countdown_timer_close_dialog_cancel" : "Huỷ"

"catalog_sport_widget_match_hockey_extra_time" : "Overtime"

"vk_auth_accessibility_back" : "Назад"

"vk_auth_accessibility_back" : "Back"

"vkim_contact_unblock_user" : "Розблокувати"

"video_subscribe_author" : "Բաժնեգրվել"

"voip_call_user" : "Call"

"clips_publish_with_coauthors_alert_cancel" : "Զեղարկել"

"voip_session_room_admin_spread_participants_randomly_dialog_cancel" : "Ləğv"

POSSIBLE SECRETS
"subscriptions_donut_category_authors" : "Авторы"
"live_broadcast_settings_header_author_title" : "Muallif"
"vk_auth_use_smart_lock_data_negative" : "Њџ"
"vk_auth_sign_up_enter_profile_info_birthday_title" : "Cumpleaños"
"clips_coauthors_accessibility_list_item_select_click_label" : "seçmæk"
"clips_coauthors_pending_list_item_selected_accessibility_group" : "Таңдалды"
"clip_grid_author_tell_about_yourself_description" : "Təsvir"
"vk_auth_register" : "Тіркелу"
"vk_auth_enter_email_continue" : "Շարունակել"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Parol"
"clips_coauthors_accessibility_list_item_unselect_click_label" : "unselect"
"stickers_cancel_unsubscribe_author_menu" : "Volar"
"story_question_option_unblock_user" : "Արգելաբացել"
"vk_auth_remove_cancel" : "Скасаваць"
"voip_session_room_admin_save_room_participants" : "Сохранить"
"voip_session_room_admin_room_name_pattern" : "Sala %d"
"google_api_key" : "AlzaSyCL17U2Q5i1NVwlcXgMOZMidSRFHyGYgWM"
"catalog_sport_widget_match_hockey_after_match_penalties" : "Буллиттер"
"clips_edit_privacy_with_coauthors_change" : "Змінити"
"coauthor_restriction_privacy_dialog_ok" : "Наладзіць"

POSSIBLE SECRETS

"clips_coauthors_refuse_dialog_cancel" : "Отмена"

"clip_grid_author_tell_about_yourself_cancel" : "Cancel"

"video_subscribe_author" : "Seguir"

"voip_session_room_join_title" : "Join"

"vk_auth_max_messenger_check_button" : "Kipy"

"live_broadcast_settings_header_author_title" : "Creator"

"stickers_cancel_unsubscribe_author_menu" : "Артқа"

"posting_author_source_type_community" : "Бірлестікте"

"vk_auth_help_button" : "Ajuda"

"story_question_option_block_user" : "Bloklaşdırmaq"

"vk_qr_auth_open_internal_camera_alert_cancel_btn" : "Ləğv"

"vk_auth_log_in" : "Увайсці"

"vk_auth_retry" : "Refresh"

"vk_qr_auth_ip_address" : "IP-адрес"

"voip_session_room_join_title" : "Kipy"

"vk_qr_auth_open_internal_camera_alert_cancel_btn" : "Болдырымай"

"clips_coauthors_refuse_dialog_cancel" : "Cancelar"

"vk_auth_max_messenger_check_button" : "Girmək"

"attached_clips_clip_has_coauthors" : "Авторластықта"

"vk_auth_sign_up_first_name" : "Nome"

POSSIBLE SECRETS

"clips_publish_with_coauthors_alert_cancel" : "Ləğv"

"clips_coauthors_accessibility_author_selected_group" : "selected"

"com.google.firebase.crashlytics.mapping_file_id" : "9377e7f9330144d1acec7e7b7eb40c4c"

"video_subscribe_author" : "Жазылу"

"clips_coauthors_restriction_blacklisted_by_me" : "Bloqueado"

"clips_edit_privacy_with_coauthors_cancel" : "Cancelar"

"vk_auth_retry" : "Оновити"

"clips_coauthors_accessibility_list_item_unselect_click_label" : "deseleccionar"

"voip_session_room_admin_set_time_limit_min_suffix" : "dəq"

"clips_coauthors_accessibility_author_selected_group" : "выбрано"

"clips_coauthors_accessibility_author_not_selected_female" : "tanlanmagan"

"vk_auth_sign_up_gender_male" : "Erkak"

"voip_session_room_join_title" : "Girmək"

"vk_auth_register" : "Գրանցվել"

"posting_step2_coauthor_title" : "Co-creator"

"music_audio_book_author" : "автор"

"vk_auth_code_by_push" : "Kod"

"vk_auth_sign_up_gender_female" : "Mujer"

"clips_publish_with_coauthors_alert_delete" : "Змяніць"

"coauthor_restriction_privacy_dialog_ok" : "Կարգավորել"

POSSIBLE SECRETS
"video_donate_author" : "Donate"
"music_audio_book_author" : "author"
"subscriptions_donut_category_authors" : "Autores"
"catalog_sport_widget_match_hockey_full_time" : "Вынік"
"voip_session_room_admin_set_time_limit_min_suffix" : "daq"
"clips_coauthors_restriction_blacklisted_by_me" : "Blocked"
"vkim_contact_unblock_user" : "Desbloquear"
"clips_coauthors_accessibility_author_selected_male" : "вибрано"
"clips_edit_privacy_with_coauthors_change" : "O'zgartirish"
"clips_edit_coauthors_selected_single_subtitle" : "Co-creator"
"video_subscribe_author" : "Підписатися"
"coauthor_restriction_privacy_dialog_ok" : "Sazlamaq"
"clip_grid_author_tell_about_yourself_exit" : "Sair"
"vk_auth_accessibility_back" : "⬅️"
"vk_auth_remove_cancel" : "Болдырмай"
"clips_coauthors_pending_list_item_select_click_label" : "выбрать"
"vk_auth_sign_up_choose_gender_title" : "Gender"
"clips_coauthors_pending_list_item_selected_accessibility_female" : "Seleccionada"
"vk_auth_choose_country_title" : "Region"
"vk_auth_phone_permissions_grant" : "Continue"

POSSIBLE SECRETS

"vk_auth_sign_up_gender_female" : "Nữ"

"story_question_option_unblock_user" : "Desbloquear"

"voip_session_room_admin_participants_not_in_room" : "Bölüşdürülməyiblər"

"vk_qr_auth_location" : "Ubicación"

"vk_auth_help_button" : "Yordam"

"clips_coauthors_accessibility_author_selected_female" : "seleccionada"

"live_author" : "Автор"

"video_analytics_author" : "Аналітика"

"story_question_option_unblock_user" : "Розблокувати"

"clips_coauthors_accept_invite" : "Принять"

"vk_auth_use_smart_lock_data_negative" : "Нет"

"clip_grid_author_tell_about_yourself_exit" : "Chiqish"

"clips_coauthors_bs_user_not_subscribed" : "Բաժնետիր"Է

"clips_coauthors_selected_single_subtitle" : "Hammuallif"

"vk_auth_code_by_app" : "Code"

"vk_auth_or" : "или"

"vk_auth_help_button" : "Көмек"

"vk_auth_remove_accept" : "Delete"

"vk_auth_retry" : "Абнавіць"

"vk_auth_register" : "Зарэгістравацца"

POSSIBLE SECRETS
"voip_session_room_join_title" : "Увайсці"
"vk_auth_related_pin_code_cancel" : "Скасувати"
"coauthor_restriction_privacy_dialog_save" : "Сақтау"
"vk_auth_sign_up_choose_gender_title" : "Стать"
"vk_qr_auth_service" : "Сервис"
"menu_item_ban_user" : "Bloqueado"
"clip_grid_author_tell_about_yourself_cancel" : "Ләğв"
"clip_grid_author_information_bottomsheet_title" : "Ma'lumot"
"clips_coauthors_accessibility_author_selected_male" : "tanlandi"
"vk_auth_related_user_pin_close_talkback" : "Фωλϋτἶ"
"clips_publish_with_coauthors_alert_delete" : "Dəyişməк"
"vk_auth_log_in" : "Үтүнἵтἶ"
"voip_session_room_leave_watch_together_submit_no" : "Զեղարկἵтἶ"
"google_crash_reporting_api_key" : "AlzaSyCL17U2Q5i1NVwlcXgMOZMidSRFHyGYgwM"
"vk_auth_accessibility_close" : "Жабы"
"clip_grid_author_tell_about_yourself_description" : "Tavsif"
"video_donate_author" : "Поддержать"
"clips_coauthors_accessibility_author_not_selected_male" : "seçilməyib"
"catalog_sport_widget_match_hockey_period_1" : "1-кезең"
"clips_edit_privacy_with_coauthors_change" : "Alterar"

POSSIBLE SECRETS
"posting_step2_coauthor_title" : "Cocreator"
"vk_auth_sign_up_choose_gender_title" : "Jins"
"clip_grid_author_tell_about_yourself_description" : "Апісанне"
"audiobook_person_author_toolbar" : "Аўтар"
"unlock_user" : "Արդելարացել"
"catalog_sport_widget_match_hockey_full_time" : "Nəticə"
"story_question_option_unlock_user" : "Разблокировать"
"clip_grid_author_tell_about_yourself_description" : "Сипаттама"
"clips_edit_privacy_with_coauthors_cancel" : "Չեղարկել"
"clips_coauthors_select_button" : "Сохранить"
"catalog_sport_widget_match_hockey_extra_time" : "Overtaym"
"vk_auth_remove_accept" : "Жою"
"clips_coauthors_selection_accessibility_close" : "Đóng"
"vk_auth_remove_cancel" : "Չեղարկել"
"comment_channel_author" : "Kanal"
"clips_coauthors_invitation_fullscreen_button" : "Адказаць"
"voip_session_room_join_title" : "Entrar"
"vk_auth_sign_up_last_name" : "Тек"
"modal_post_donut_user" : "%d P"
"clip_grid_author_information_bottomsheet_title" : "Информация"

POSSIBLE SECRETS

"clips_coauthors_selection_accessibility_close" : "Cerrar"

"vk_qr_auth_location" : "Տեղադրություն"

"voip_session_room_admin_set_time_limit_min_pattern" : "%d dəq"

"clip_grid_author_tell_about_yourself_description" : "Descrição"

"vk_auth_accessibility_close" : "Close"

"coauthor_restriction_privacy_dialog_cancel" : "Ləğv"

"vk_qr_auth_location" : "Localização"

"audiobook_person_author_toolbar" : "Author"

"vkim_contact_unblock_user" : "Разблокировать"

"vk_auth_code_by_app" : "Код"

"posting_step2_coauthor_title" : "Caaŷtap"

"clips_coauthors_selection_accessibility_close" : "Close"

"clips_edit_privacy_with_coauthors_cancel" : "Huỷ"

"clips_edit_coauthors_selected_multi_subtitle" : "Cocreadores"

"video_filters_authors" : "Creadores"

"vk_auth_remove_user_title" : "Confirmation"

"catalog_sport_widget_match_hockey_period_1" : "1-davr"

"voip_session_room_admin_room_name_pattern" : "Room %d"

"coauthor_restriction_privacy_dialog_cancel" : "Отмена"

"live_broadcast_settings_header_author_title" : "Հեղինակ"

POSSIBLE SECRETS
"clips_coauthors_bs_user_subscribed" : "Բաժնետիրված եք"
"vk_auth_sign_up_last_name" : "Прізвище"
"vk_auth_code_by_app" : "Mã"
"catalog_sport_widget_match_hockey_after_match_penalties" : "Penalti"
"clips_coauthors_accessibility_list_item_select_click_label" : "таңдау"
"clips_coauthors_select_button" : "Guardar"
"vk_auth_remove_accept" : "Remover"
"subscriptions_donut_category_authors" : "Автори"
"vk_auth_choose_country_title" : "Bölgə"
"voip_session_room_leave_watch_together_submit_no" : "Болдырмау"
"story_question_option_unblock_user" : "Разблакаваць"
"clips_coauthors_bs_user_not_subscribed" : "Падпісацца"
"clips_coauthors_pending_list_item_selected_accessibility_male" : "Seleccionado"
"vk_auth_sign_up_gender_female" : "Female"
"vk_auth_max_messenger_check_button" : "Увійти"
"voip_session_room_admin_room_countdown_timer_close_dialog_cancel" : "Отмена"
"vk_auth_retry" : "Жаңарту"
"clips_edit_privacy_with_coauthors_change" : "Change"
"vk_auth_remove_user_title" : "Հաստատում"
"accessibility_video_author_avatar_tap_action" : "Ir"

POSSIBLE SECRETS
"clip_grid_author_information_bottomsheet_title" : "Інформація"
"voip_session_room_admin_save_room_participants" : "Պահպանել"
"voip_session_room_admin_room_participant_status_admin" : "Әкімші"
"accessibility_video_author_avatar_tap_action" : "Անցնել"
"vk_auth_use_smart_lock_data_negative" : "No"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Password"
"voip_session_room_admin_room_close_all_dialog_cancel" : "Нуж"
"clips_publish_with_coauthors_alert_delete" : "Изменить"
"vk_auth_use_smart_lock_data_negative" : "Xeyr"
"clips_coauthors_pending_list_item_selected_accessibility_female" : "Таңдалды"
"clips_coauthors_bs_user_unsubscribe_accessibility" : "Відписатися"
"clips_coauthors_accessibility_author_selected_group" : "tanlandi"
"clip_grid_author_tell_about_yourself_exit" : "Выйсці"
"voip_session_room_admin_participants_not_in_room" : "Taqsimlanmagan"
"vk_auth_related_user_pin_close_talkback" : "Close"
"video_donate_author" : "Qollab-quvvatlash"
"coauthor_restriction_privacy_dialog_ok" : "Configurar"
"voip_session_room_admin_room_participant_status_pending" : "Aguardando..."
"posting_author_source_type_community" : "Cəmiyyətdə"
"clips_coauthors_invitation_fullscreen_button" : "Reply"

POSSIBLE SECRETS
"clip_grid_author_information_bottomsheet_title" : "Инфармацыя"
"catalog_sport_widget_match_hockey_period_2" : "2-davr"
"vk_auth_register" : "Зареєструватися"
"clips_coauthors_selected_multi_subtitle" : "Coautores"
"audiobook_person_author_toolbar" : "Հեղինակ"
"clips_coauthors_accessibility_author_selected_male" : "таңдалған"
"clips_coauthors_accessibility_author_selected_male" : "seçilib"
"vk_auth_remove_accept" : "O'chirish"
"story_question_option_block_user" : "Заблокировать"
"clips_coauthors_accessibility_author_selected_male" : "selected"
"vk_auth_use_smart_lock_data_positive" : "Иә"
"vk_auth_enter_email_skip" : "Өткізу"
"clips_coauthors_selection_accessibility_close" : "Yopish"
"clips_coauthors_decline_invite" : "Rechazar"
"vk_auth_sign_up_choose_gender_title" : "Սեռ"
"attached_clips_clip_has_coauthors" : "Համահեղինակությունում"
"clips_publish_with_coauthors_alert_delete" : "Өзгөртү"
"clip_grid_author_information_bottomsheet_title" : "Տեղեկություններ"
"voip_session_room_admin_room_participant_status_pending" : "Очікування..."
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Senha"

POSSIBLE SECRETS
"vk_auth_related_pin_code_cancel" : "Ləğv"
"video_analytics_author" : "Analytics"
"vk_auth_enter_email_skip" : "Пропустить"
"video_filters_authors" : "Creators"
"clips_coauthors_pending_list_item_selected_accessibility_male" : "Таңдалды"
"posting_step2_coauthor_title" : "Співавтор"
"voip_session_room_admin_save_room_participants" : "Save"
"voip_session_room_admin_room_close_all_dialog_cancel" : "Cancel"
"clips_edit_coauthors_selected_multi_subtitle" : "Co-creators"
"clips_edit_privacy_with_coauthors_cancel" : "Cancel"
"vk_auth_remove_accept" : "Выдаліць"
"voip_session_room_join_title" : "Увійти"
"posting_author_source_type_profile" : "Profildə"
"catalog_sport_widget_match_hockey_extra_time" : "Авертайм"
"audiobook_person_author_toolbar" : "Müəllif"
"vk_auth_sign_up_choose_gender_title" : "Género"
"clip_grid_author_information_bottomsheet_title" : "Info"
"voip_session_room_admin_save_room_participants" : "Luru"
"stickers_cancel_unsubscribe_author_menu" : "Volver"
"vk_auth_password" : "Parol"

POSSIBLE SECRETS

"vk_auth_use_smart_lock_data_positive" : "Ha"

"vk_auth_login_by_password" : "Parol yordamida kirish"

"story_question_option_block_user" : "Бўғаттай"

"coauthor_restriction_privacy_dialog_save" : "Ўлҳуқулҳл"

"vk_auth_remove_accept" : "Silmək"

"catalog_sport_widget_match_hockey_after_match_penalties" : "Penalty"

"vk_auth_choose_country_title" : "Pəriēh"

"vk_auth_related_pin_code_cancel" : "Cancelar"

"vk_auth_sign_up_gender_male" : "Hombre"

"vk_auth_or" : "або"

"posting_author_source_type_profile" : "Profilda"

"vk_auth_sign_up_last_name" : "Hq"

"clips_edit_coauthors_selected_single_subtitle" : "Співавтор"

"vk_qr_auth_open_internal_camera_alert_cancel_btn" : "Cancel"

"voip_session_room_join_title" : "Kirish"

"vk_auth_log_in" : "Войти"

"vk_auth_sign_up_last_name" : "Soyad"

"video_analytics_author" : "Аналитика"

"catalog_sport_widget_match_hockey_full_time" : "Ўлҳлҳлҳл"

"voip_session_room_admin_room_participant_status_creator" : "Қўрушы"

POSSIBLE SECRETS
"stickers_unsubscribe_author_menu" : "Отписаться"
"clips_coauthors_bs_user_subscribed" : "Yazılmısınız"
"voip_session_room_join_title" : "Unirse"
"vk_auth_phone_bind_phone" : "Прив'язати"
"video_donate_author" : "Apoiar"
"clips_publish_with_coauthors_alert_delete" : "Editor"
"voip_session_room_admin_room_rename" : "Renombrar"
"vk_qr_auth_location" : "Местоположение"
"clips_coauthors_pending_list_item_select_click_label" : "select"
"vk_auth_enter_email_continue" : "Працягнуць"
"clips_coauthors_accept_invite" : "Прыняць"
"clips_edit_coauthors_selected_multi_subtitle" : "Соавторы"
"menu_item_unban_user" : "Desbloquear"
"vk_auth_or" : "немесе"
"clips_coauthors_selected_multi_subtitle" : "Співавтори"
"video_filters_authors" : "Autores"
"vk_auth_sign_up_gender_male" : "Er"
"stickers_unsubscribe_author_menu" : "Відписатися"
"video_donate_author" : "Donar"
"posting_author_source_type_community" : "Jamiyatda"

POSSIBLE SECRETS
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Գաղտնիաբառ"
"clips_coauthors_accessibility_author_selected_male" : "Выбран"
"live_broadcast_settings_header_author_title" : "Creador"
"clips_coauthors_decline_invite" : "Адхіліць"
"voip_session_room_admin_set_time_limit_min_suffix" : "phút"
"vk_auth_remove_user_title" : "Підтвердження"
"vk_qr_auth_location" : "Joylashuv"
"clips_coauthors_pending_list_item_selected_accessibility_female" : "Seleccionada"
"vk_auth_code_by_app" : "Kod"
"coauthor_restriction_privacy_dialog_ok" : "Sozlash"
"vk_auth_remove_cancel" : "Huỷ"
"video_donate_author" : "Падтрымаць"
"vk_auth_max_messenger_check_button" : "Entrar"
"coauthor_restriction_privacy_dialog_cancel" : "Болдырмау"
"clips_coauthors_selection_accessibility_close" : "Закрыць"
"clips_coauthors_accessibility_author_selected_group" : "seleccionado"
"music_audio_book_author" : "հեղինակ"
"vk_auth_enter_email_continue" : "Продовжити"
"comment_channel_author" : "Канал"
"vk_auth_code_by_app" : "Código"

POSSIBLE SECRETS
"vk_auth_continue" : "Continuar"
"vk_auth_help_button" : "Помощь"
"vk_auth_enter_email_continue" : "Продолжить"
"vk_auth_related_user_pin_close_talkback" : "Fechar"
"vk_auth_phone_bind_phone" : "Associar"
"clips_coauthors_accept_invite" : "Accept"
"music_audio_book_author" : "autor"
"posting_step2_coauthor_title" : "Соавтор"
"accessibility_video_author_avatar_tap_action" : "Go"
"clips_coauthors_accessibility_author_selected_male" : "seleccionado"
"voip_session_room_admin_spread_participants_randomly_dialog_cancel" : "Cancelar"
"clip_grid_author_tell_about_yourself_cancel" : "Cancelar"
"menu_item_ban_user" : "Chặn"
"clips_coauthors_decline_invite" : "Ўтхрџтл"
"vk_auth_code_by_push" : "Código"
"vk_auth_related_user_pin_close_talkback" : "Закрыць"
"comment_author" : "Аўтар"
"vk_auth_log_in" : "Girmək"
"clips_coauthors_bs_user_unsubscribe_accessibility" : "адпісацца"
"clips_coauthors_decline_invite" : "Қабылдамай"

POSSIBLE SECRETS

"vk_auth_accessibility_close" : "Закрыць"

"voip_session_room_leave_watch_together_submit_no" : "Отмена"

"ads_easy_promote_user" : "Anunciar"

"attached_clips_clip_has_coauthors_button_cancel" : "Aydındır"

"clips_coauthors_accessibility_author_selected_group" : "seçilib"

"clips_coauthors_accessibility_list_item_select_click_label" : "seleccionar"

"story_question_option_unblock_user" : "Unblock"

"vk_auth_max_messenger_check_button" : "Увайсці"

"video_subscribe_author" : "Follow"

"vk_auth_accessibility_close" : "Đóng"

"vk_auth_remove_user_title" : "Təsdiq"

"vk_auth_enter_email_skip" : "Skip"

"vk_auth_sign_up_gender_female" : "Feminino"

"coauthor_restriction_privacy_dialog_save" : "Save"

"vk_auth_sign_up_first_name" : "Имя"

"clips_coauthors_refuse_dialog_cancel" : "Չեղարկել"

"live_broadcast_settings_header_author_title" : "Müəllif"

"vk_auth_account_continue" : "Працягнуць"

"video_filters_authors" : "Авторлар"

"story_question_option_block_user" : "Bloquear"

POSSIBLE SECRETS
"coauthor_restriction_privacy_dialog_ok" : "Edit"
"clips_coauthors_accessibility_author_selected_female" : "выбрана"
"clips_coauthors_pending_list_item_selected_accessibility_group" : "Seleccionado"
"clips_coauthors_selection_accessibility_close" : "Закрити"
"vk_qr_auth_service" : "Service"
"clips_coauthors_accessibility_author_selected_male" : "seleccionado"
"clips_coauthors_refuse_dialog_cancel" : "Cancel"
"voip_session_room_admin_spread_participants_randomly_dialog_cancel" : "Huỷ"
"vk_auth_password" : "Құпиясөз"
"voip_session_room_admin_room_countdown_timer_close_dialog_cancel" : "Скасувати"
"posting_step2_coauthor_title" : "Համահեղինակ"
"vk_auth_sign_up_gender_female" : "Жаночы"
"posting_step2_coauthor_title" : "Coautor"
"clip_grid_author_tell_about_yourself_retry" : "Повторить"
"vk_auth_remove_user_title" : "Confirmación"
"clips_coauthors_accept_invite" : "Прийняти"
"voip_session_room_admin_room_rename" : "Переименовать"
"vk_auth_sign_up_first_name" : "Tên"
"attached_clips_clip_has_coauthors_button_cancel" : "Түсінікті"
"clips_coauthors_selected_multi_subtitle" : "Co-creators"

POSSIBLE SECRETS
"clips_publish_with_coauthors_alert_delete" : "O'zgartirish"
"video_donate_author" : "Dəstəkləmək"
"clips_coauthors_selected_single_subtitle" : "Сааӱтаp"
"clips_publish_with_coauthors_alert_delete" : "Φη̣υ̣τ̣ι̣"
"clips_coauthors_selected_single_subtitle" : "Співавтор"
"clips_coauthors_refuse_dialog_cancel" : "Ləğv"
"clip_grid_author_information_bottomsheet_title" : "Ақпарат"
"video_filters_authors" : "Müəlliflər"
"clip_grid_author_tell_about_yourself_exit" : "Leave"
"vk_auth_remove_accept" : "Eliminar"
"vk_auth_enter_email_skip" : "Buraxmaq"
"vk_mvκ_auth_success_title" : "Girmisiniz"
"modal_post_donut_user" : "Ѕ%d"
"clips_coauthors_refuse_dialog_cancel" : "Скасувати"
"vk_auth_use_smart_lock_data_negative" : "He"
"clips_coauthors_accessibility_list_item_select_click_label" : "выбрать"
"coauthor_restriction_privacy_dialog_ok" : "Настроить"
"vk_auth_phone_bind_phone" : "Прывязаць"
"vk_qr_auth_open_internal_camera_alert_cancel_btn" : "Huỷ"
"voip_session_room_admin_set_time_limit_min_pattern" : "%d п"

POSSIBLE SECRETS

"video_subscribe_author" : "Inscrever-se"

"clips_coauthors_pending_list_item_selected_accessibility_male" : "Selected"

"voip_session_room_admin_room_countdown_timer_close_dialog_cancel" : "Cancel"

"vk_qr_auth_service" : "Servicio"

"clips_coauthors_accessibility_author_not_selected_group" : "seçilməyib"

"clips_edit_privacy_with_coauthors_cancel" : "Ləğv"

"posting_author_source_type_profile" : "Бейінде"

"clip_grid_author_tell_about_yourself_retry" : "Repetir"

"comment_author" : "Հեղինակ"

"vk_auth_help_button" : "Допомога"

"clips_edit_coauthors_selected_multi_subtitle" : "Co-autores"

"vk_auth_use_smart_lock_data_positive" : "Ын"

"accessibility_video_author_avatar_tap_action" : "Өту"

"clips_edit_coauthors_selected_single_subtitle" : "Co-autor"

"vk_qr_auth_ip_address" : "IP-адрес"

"vk_auth_sign_up_gender_female" : "Женский"

"stickers_cancel_unsubscribe_author_menu" : "Back"

"clips_coauthors_refuse_dialog_cancel" : "Нұў"

"clips_coauthors_select_button" : "Зберегти"

"attached_clips_clip_has_coauthors_button_cancel" : "Понятно"

POSSIBLE SECRETS

"accessibility_video_author_avatar_tap_action" : "Перайсці"

"live_author" : "Muallif"

"vk_auth_help_button" : "Ayuda"

"clip_grid_author_tell_about_yourself_cancel" : "Нуў"

"clips_coauthors_pending_list_item_selected_accessibility_female" : "Вибрано"

"unblock_user" : "Разблакаваць"

"clip_grid_author_tell_about_yourself_retry" : "Қайталау"

"vk_auth_avatar_camera" : "Fotografar"

"menu_item_ban_user" : "Արգելափակել"

"voip_session_room_admin_room_countdown_timer_close_dialog_cancel" : "Адмена"

"vk_qr_auth_location" : "Yerləşmə"

"clips_coauthors_decline_invite" : "Скасувати"

"video_analytics_author" : "Аналітика"

"clips_coauthors_pending_list_item_selected_accessibility_female" : "Tanlandi"

"article_tab_user" : "Бейіннен"

"clips_coauthors_accessibility_author_not_selected_female" : "seçilməyib"

"clips_coauthors_select_button" : "Lüü"

"clips_coauthors_pending_list_item_selected_accessibility_male" : "Вибрано"

"voip_session_room_admin_room_participant_status_creator" : "Creador"

"voip_session_room_leave_watch_together_submit_no" : "Нуў"

POSSIBLE SECRETS

"vk_auth_accessibility_close" : "Bağlamaq"

"accessibility_video_author_avatar_tap_action" : "Acessar"

"clips_coauthors_accessibility_list_item_select_click_label" : "seleccionar"

"vk_auth_retry" : "Əwərləşdirmə"

"voip_session_room_join_title" : "Ünvan"

"coauthor_restriction_privacy_dialog_cancel" : "Адмена"

"video_subscribe_author" : "Yazılmaq"

"unblock_user" : "Розблокувати"

"clips_coauthors_accept_invite" : "Қабылдау"

"coauthor_restriction_privacy_dialog_save" : "Salvar"

"clips_coauthors_accessibility_author_not_selected_male" : "tanlanmagan"

"clips_coauthors_pending_list_item_select_click_label" : "chọn"

"comment_author" : "Muallif"

"vk_auth_accessibility_back" : "Geri"

"vk_auth_or" : "həç"

"audiobook_person_author_toolbar" : "Muallif"

"comment_author" : "Автор"

"voip_session_room_leave_watch_together_submit_no" : "Cancelar"

"vk_auth_continue" : "Dəwam etdirməyə davam et"

"voip_session_room_admin_room_participant_status_creator" : "Создатель"

POSSIBLE SECRETS

"audiobook_author" : "autor"

"clip_grid_author_tell_about_yourself_exit" : "Шығу"

"vk_auth_use_smart_lock_data_negative" : "Hi"

"vk_auth_register" : "Cadastrar-se"

"vk_auth_password" : "Password"

"clips_coauthors_pending_list_item_selected_accessibility_group" : "Seçilib"

"voip_call_user" : "Gqi"

"clips_coauthors_bs_user_subscribed" : "Жазылғансыз"

"clips_publish_with_coauthors_alert_delete" : "Змінити"

"clips_edit_coauthors_selected_single_subtitle" : "Сааӳтап"

"comment_channel_author" : "Арна"

"vk_auth_choose_country_title" : "Región"

"voip_session_room_admin_room_countdown_timer_close_dialog_cancel" : "Cancelar"

"attached_clips_clip_has_coauthors_button_cancel" : "Ӧшрп Ң"

"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Пароль"

"vk_auth_accessibility_close" : "Закрити"

"clips_coauthors_pending_list_item_selected_accessibility_male" : "Tanlandi"

"stickers_unsubscribe_author_menu" : "Адпісацца"

"clip_grid_author_tell_about_yourself_exit" : "Abandonar"

"clips_coauthors_bs_user_not_subscribed" : "Жазылу"

POSSIBLE SECRETS
"clips_coauthors_pending_list_item_selected_accessibility_male" : "Seleccionado"
"voip_session_room_leave_watch_together_submit_no" : "Адмена"
"clip_grid_author_tell_about_yourself_exit" : "Çıxmaq"
"vk_auth_remove_accept" : "Видалити"
"clips_publish_with_coauthors_alert_cancel" : "Отмена"
"voip_session_room_admin_room_participant_status_creator" : "Qurucu"
"vk_auth_code_by_push" : "Ծածկագիրը"
"voip_session_room_admin_room_participant_status_pending" : "Esperando..."
"catalog_sport_widget_match_hockey_period_2" : "2-кезең"
"vk_auth_sign_up_choose_gender_title" : "Cins"
"vk_auth_use_smart_lock_data_positive" : "Có"
"vk_auth_sign_up_choose_gender_title" : "Пол"

 SCAN LOGS

Timestamp	Event	Error
2026-05-30 15:55:01	Generating Hashes	OK
2026-05-30 15:55:01	Extracting APK	OK
2026-05-30 15:55:01	Unzipping	OK

2026-05-30 15:55:05	Parsing APK with androguard	OK
2026-05-30 15:55:09	Extracting APK features using aapt/aapt2	OK
2026-05-30 15:55:11	Getting Hardcoded Certificates/Keystores	OK
2026-05-30 15:55:25	Parsing AndroidManifest.xml	OK
2026-05-30 15:55:25	Extracting Manifest Data	OK
2026-05-30 15:55:25	Manifest Analysis Started	OK
2026-05-30 15:55:26	Reading Network Security config from network_security_config.xml	OK
2026-05-30 15:55:26	Parsing Network Security config	OK
2026-05-30 15:55:26	Performing Static Analysis on: VK (com.vkontakte.android)	OK
2026-05-30 15:55:31	Checking for Malware Permissions	OK
2026-05-30 15:55:31	Fetching icon path	OK
2026-05-30 15:55:31	Library Binary Analysis Started	OK
2026-05-30 15:55:31	Analyzing lib/armeabi-v7a/libgl-effects.so	OK
2026-05-30 15:55:31	Analyzing lib/armeabi-v7a/libvkchronicle.so	OK

2026-05-30 15:55:31	Analyzing lib/armeabi-v7a/libtensorflowlite_gpu_delegate.so	OK
2026-05-30 15:55:31	Analyzing lib/armeabi-v7a/libvideo-message-stencils.so	OK
2026-05-30 15:55:31	Analyzing lib/armeabi-v7a/libtensorflowlite_jni.so	OK
2026-05-30 15:55:31	Analyzing lib/armeabi-v7a/libgifimage.so	OK
2026-05-30 15:55:31	Analyzing lib/armeabi-v7a/libvk-jpeg-coder.so	OK
2026-05-30 15:55:31	Analyzing lib/armeabi-v7a/libtensorflowlite.so	OK
2026-05-30 15:55:31	Analyzing lib/armeabi-v7a/libcronet.140.0.7339.52.so	OK
2026-05-30 15:55:31	Analyzing lib/armeabi-v7a/libxhook.so	OK
2026-05-30 15:55:31	Analyzing lib/armeabi-v7a/libvkqrcode.so	OK
2026-05-30 15:55:31	Analyzing lib/armeabi-v7a/libandroidx.graphics.path.so	OK
2026-05-30 15:55:31	Analyzing lib/armeabi-v7a/libcrashlytics.so	OK
2026-05-30 15:55:31	Analyzing lib/armeabi-v7a/libEnhancementLibShared.so	OK
2026-05-30 15:55:31	Analyzing lib/armeabi-v7a/libnative-tensorflow-core-lib.so	OK

2026-05-30 15:55:31	Analyzing lib/armeabi-v7a/libzstd-jni-1.5.7-4.so	OK
2026-05-30 15:55:31	Analyzing lib/armeabi-v7a/libc++_shared.so	OK
2026-05-30 15:55:31	Analyzing lib/armeabi-v7a/libsqlite3x.so	OK
2026-05-30 15:55:31	Analyzing lib/armeabi-v7a/libopencv_java4.so	OK
2026-05-30 15:55:32	Analyzing lib/armeabi-v7a/libcrashlytics-trampoline.so	OK
2026-05-30 15:55:32	Analyzing lib/armeabi-v7a/libnative_tools.so	OK
2026-05-30 15:55:32	Analyzing lib/armeabi-v7a/libimagepipeline.so	OK
2026-05-30 15:55:32	Analyzing lib/armeabi-v7a/libnative-filters.so	OK
2026-05-30 15:55:32	Analyzing lib/armeabi-v7a/liblplayer.so	OK
2026-05-30 15:55:32	Analyzing lib/armeabi-v7a/libcrashlytics-handler.so	OK
2026-05-30 15:55:32	Analyzing lib/armeabi-v7a/librtmp-jni.so	OK
2026-05-30 15:55:32	Analyzing lib/armeabi-v7a/libvkrottie.so	OK
2026-05-30 15:55:32	Analyzing lib/armeabi-v7a/libjingle_peerconnection_so.so	OK

2026-05-30 15:55:32	Analyzing lib/armeabi-v7a/libaudio-effects.so	OK
2026-05-30 15:55:32	Analyzing lib/armeabi-v7a/libcrashlytics-common.so	OK
2026-05-30 15:55:32	Analyzing lib/armeabi-v7a/libverify.so	OK
2026-05-30 15:55:32	Analyzing lib/armeabi-v7a/libstatic-webp.so	OK
2026-05-30 15:55:32	Analyzing lib/armeabi-v7a/libdatastore_shared_counter.so	OK
2026-05-30 15:55:32	Analyzing lib/armeabi-v7a/libvkmedia.so	OK
2026-05-30 15:55:32	Analyzing lib/armeabi-v7a/libnative-imagetranscoder.so	OK
2026-05-30 15:55:32	Analyzing lib/armeabi-v7a/libsqliteobserver.so	OK
2026-05-30 15:55:32	Analyzing lib/armeabi-v7a/libnative-net.so	OK
2026-05-30 15:55:32	Analyzing lib/armeabi-v7a/libvkcore.so	OK
2026-05-30 15:55:32	Analyzing lib/armeabi-v7a/libtrhook2.so	OK
2026-05-30 15:55:32	Analyzing lib/arm64-v8a/libgl-effects.so	OK
2026-05-30 15:55:32	Analyzing lib/arm64-v8a/libvkchronicle.so	OK

2026-05-30 15:55:32	Analyzing lib/arm64-v8a/libtensorflowlite_gpu_delegate.so	OK
2026-05-30 15:55:32	Analyzing lib/arm64-v8a/libvideo-message-stencils.so	OK
2026-05-30 15:55:32	Analyzing lib/arm64-v8a/libtensorflowlite_jni.so	OK
2026-05-30 15:55:32	Analyzing lib/arm64-v8a/libgifimage.so	OK
2026-05-30 15:55:32	Analyzing lib/arm64-v8a/libvk-jpeg-coder.so	OK
2026-05-30 15:55:32	Analyzing lib/arm64-v8a/libtensorflowlite.so	OK
2026-05-30 15:55:33	Analyzing lib/arm64-v8a/libcronet.140.0.7339.52.so	OK
2026-05-30 15:55:33	Analyzing lib/arm64-v8a/libxhook.so	OK
2026-05-30 15:55:33	Analyzing lib/arm64-v8a/libvkqrcode.so	OK
2026-05-30 15:55:33	Analyzing lib/arm64-v8a/libandroidx.graphics.path.so	OK
2026-05-30 15:55:33	Analyzing lib/arm64-v8a/libcrashlytics.so	OK
2026-05-30 15:55:33	Analyzing lib/arm64-v8a/libEnhancementLibShared.so	OK
2026-05-30 15:55:33	Analyzing lib/arm64-v8a/libnative-tensorflow-core-lib.so	OK

2026-05-30 15:55:33	Analyzing lib/arm64-v8a/libzstd-jni-1.5.7-4.so	OK
2026-05-30 15:55:33	Analyzing lib/arm64-v8a/libc++_shared.so	OK
2026-05-30 15:55:33	Analyzing lib/arm64-v8a/libsqlite3x.so	OK
2026-05-30 15:55:33	Analyzing lib/arm64-v8a/libopencv_java4.so	OK
2026-05-30 15:55:33	Analyzing lib/arm64-v8a/libcrashlytics-trampoline.so	OK
2026-05-30 15:55:33	Analyzing lib/arm64-v8a/libnative_tools.so	OK
2026-05-30 15:55:33	Analyzing lib/arm64-v8a/libimagepipeline.so	OK
2026-05-30 15:55:33	Analyzing lib/arm64-v8a/libnative-filters.so	OK
2026-05-30 15:55:33	Analyzing lib/arm64-v8a/liblplayer.so	OK
2026-05-30 15:55:33	Analyzing lib/arm64-v8a/libcrashlytics-handler.so	OK
2026-05-30 15:55:33	Analyzing lib/arm64-v8a/librtmp-jni.so	OK
2026-05-30 15:55:33	Analyzing lib/arm64-v8a/libvkrottie.so	OK
2026-05-30 15:55:33	Analyzing lib/arm64-v8a/libjingle_peerconnection_so.so	OK

2026-05-30 15:55:33	Analyzing lib/arm64-v8a/libaudio-effects.so	OK
2026-05-30 15:55:33	Analyzing lib/arm64-v8a/libcrashlytics-common.so	OK
2026-05-30 15:55:33	Analyzing lib/arm64-v8a/libverify.so	OK
2026-05-30 15:55:34	Analyzing lib/arm64-v8a/libstatic-webp.so	OK
2026-05-30 15:55:34	Analyzing lib/arm64-v8a/libdatastore_shared_counter.so	OK
2026-05-30 15:55:34	Analyzing lib/arm64-v8a/libvkmedia.so	OK
2026-05-30 15:55:34	Analyzing lib/arm64-v8a/libnative-imagetranscoder.so	OK
2026-05-30 15:55:34	Analyzing lib/arm64-v8a/libsqliteobserver.so	OK
2026-05-30 15:55:34	Analyzing lib/arm64-v8a/libnative-net.so	OK
2026-05-30 15:55:34	Analyzing lib/arm64-v8a/libvkcore.so	OK
2026-05-30 15:55:34	Analyzing lib/arm64-v8a/libtrhook2.so	OK
2026-05-30 15:55:34	Analyzing apktool_out/lib/armeabi-v7a/libgl-effects.so	OK
2026-05-30 15:55:34	Analyzing apktool_out/lib/armeabi-v7a/libvkchronicle.so	OK

2026-05-30 15:55:34	Analyzing apktool_out/lib/armeabi-v7a/libtensorflowlite_gpu_delegate.so	OK
2026-05-30 15:55:34	Analyzing apktool_out/lib/armeabi-v7a/libvideo-message-stencils.so	OK
2026-05-30 15:55:34	Analyzing apktool_out/lib/armeabi-v7a/libtensorflowlite_jni.so	OK
2026-05-30 15:55:34	Analyzing apktool_out/lib/armeabi-v7a/libgifimage.so	OK
2026-05-30 15:55:34	Analyzing apktool_out/lib/armeabi-v7a/libvk-jpeg-coder.so	OK
2026-05-30 15:55:34	Analyzing apktool_out/lib/armeabi-v7a/libtensorflowlite.so	OK
2026-05-30 15:55:34	Analyzing apktool_out/lib/armeabi-v7a/libcronet.140.0.7339.52.so	OK
2026-05-30 15:55:34	Analyzing apktool_out/lib/armeabi-v7a/libxhook.so	OK
2026-05-30 15:55:34	Analyzing apktool_out/lib/armeabi-v7a/libvkqrcode.so	OK
2026-05-30 15:55:34	Analyzing apktool_out/lib/armeabi-v7a/libandroidx.graphics.path.so	OK
2026-05-30 15:55:34	Analyzing apktool_out/lib/armeabi-v7a/libcrashlytics.so	OK
2026-05-30 15:55:34	Analyzing apktool_out/lib/armeabi-v7a/libEnhancementLibShared.so	OK
2026-05-30 15:55:34	Analyzing apktool_out/lib/armeabi-v7a/libnative-tensorflow-core-lib.so	OK

2026-05-30 15:55:34	Analyzing apktool_out/lib/armeabi-v7a/libzstd-jni-1.5.7-4.so	OK
2026-05-30 15:55:34	Analyzing apktool_out/lib/armeabi-v7a/libc++_shared.so	OK
2026-05-30 15:55:34	Analyzing apktool_out/lib/armeabi-v7a/libsqlite3x.so	OK
2026-05-30 15:55:34	Analyzing apktool_out/lib/armeabi-v7a/libopencv_java4.so	OK
2026-05-30 15:55:35	Analyzing apktool_out/lib/armeabi-v7a/libcrashlytics-trampoline.so	OK
2026-05-30 15:55:35	Analyzing apktool_out/lib/armeabi-v7a/libnative_tools.so	OK
2026-05-30 15:55:35	Analyzing apktool_out/lib/armeabi-v7a/libimagepipeline.so	OK
2026-05-30 15:55:35	Analyzing apktool_out/lib/armeabi-v7a/libnative-filters.so	OK
2026-05-30 15:55:35	Analyzing apktool_out/lib/armeabi-v7a/libblplayer.so	OK
2026-05-30 15:55:35	Analyzing apktool_out/lib/armeabi-v7a/libcrashlytics-handler.so	OK
2026-05-30 15:55:35	Analyzing apktool_out/lib/armeabi-v7a/librtmp-jni.so	OK
2026-05-30 15:55:35	Analyzing apktool_out/lib/armeabi-v7a/libvkrottie.so	OK
2026-05-30 15:55:35	Analyzing apktool_out/lib/armeabi-v7a/libjingle_peerconnection_so.so	OK

2026-05-30 15:55:35	Analyzing apktool_out/lib/armeabi-v7a/libaudio-effects.so	OK
2026-05-30 15:55:35	Analyzing apktool_out/lib/armeabi-v7a/libcrashlytics-common.so	OK
2026-05-30 15:55:35	Analyzing apktool_out/lib/armeabi-v7a/libverify.so	OK
2026-05-30 15:55:35	Analyzing apktool_out/lib/armeabi-v7a/libstatic-webp.so	OK
2026-05-30 15:55:35	Analyzing apktool_out/lib/armeabi-v7a/libdatastore_shared_counter.so	OK
2026-05-30 15:55:35	Analyzing apktool_out/lib/armeabi-v7a/libvkmedia.so	OK
2026-05-30 15:55:35	Analyzing apktool_out/lib/armeabi-v7a/libnative-imagetranscoder.so	OK
2026-05-30 15:55:35	Analyzing apktool_out/lib/armeabi-v7a/libsqliteobserver.so	OK
2026-05-30 15:55:35	Analyzing apktool_out/lib/armeabi-v7a/libnative-net.so	OK
2026-05-30 15:55:35	Analyzing apktool_out/lib/armeabi-v7a/libvkcore.so	OK
2026-05-30 15:55:35	Analyzing apktool_out/lib/armeabi-v7a/libtrhook2.so	OK
2026-05-30 15:55:35	Analyzing apktool_out/lib/arm64-v8a/libgl-effects.so	OK
2026-05-30 15:55:35	Analyzing apktool_out/lib/arm64-v8a/libvkchronicle.so	OK

2026-05-30 15:55:35	Analyzing apktool_out/lib/arm64-v8a/libtensorflowlite_gpu_delegate.so	OK
2026-05-30 15:55:35	Analyzing apktool_out/lib/arm64-v8a/libvideo-message-stencils.so	OK
2026-05-30 15:55:36	Analyzing apktool_out/lib/arm64-v8a/libtensorflowlite_jni.so	OK
2026-05-30 15:55:36	Analyzing apktool_out/lib/arm64-v8a/libgifimage.so	OK
2026-05-30 15:55:36	Analyzing apktool_out/lib/arm64-v8a/libvk-jpeg-coder.so	OK
2026-05-30 15:55:36	Analyzing apktool_out/lib/arm64-v8a/libtensorflowlite.so	OK
2026-05-30 15:55:36	Analyzing apktool_out/lib/arm64-v8a/libcronet.140.0.7339.52.so	OK
2026-05-30 15:55:36	Analyzing apktool_out/lib/arm64-v8a/libxhook.so	OK
2026-05-30 15:55:36	Analyzing apktool_out/lib/arm64-v8a/libvkqrcode.so	OK
2026-05-30 15:55:36	Analyzing apktool_out/lib/arm64-v8a/libandroidx.graphics.path.so	OK
2026-05-30 15:55:36	Analyzing apktool_out/lib/arm64-v8a/libcrashlytics.so	OK
2026-05-30 15:55:36	Analyzing apktool_out/lib/arm64-v8a/libEnhancementLibShared.so	OK
2026-05-30 15:55:36	Analyzing apktool_out/lib/arm64-v8a/libnative-tensorflow-core-lib.so	OK

2026-05-30 15:55:36	Analyzing apktool_out/lib/arm64-v8a/libzstd-jni-1.5.7-4.so	OK
2026-05-30 15:55:36	Analyzing apktool_out/lib/arm64-v8a/libc++_shared.so	OK
2026-05-30 15:55:36	Analyzing apktool_out/lib/arm64-v8a/libsqlite3x.so	OK
2026-05-30 15:55:36	Analyzing apktool_out/lib/arm64-v8a/libopencv_java4.so	OK
2026-05-30 15:55:36	Analyzing apktool_out/lib/arm64-v8a/libcrashlytics-trampoline.so	OK
2026-05-30 15:55:36	Analyzing apktool_out/lib/arm64-v8a/libnative_tools.so	OK
2026-05-30 15:55:36	Analyzing apktool_out/lib/arm64-v8a/libimagepipeline.so	OK
2026-05-30 15:55:36	Analyzing apktool_out/lib/arm64-v8a/libnative-filters.so	OK
2026-05-30 15:55:36	Analyzing apktool_out/lib/arm64-v8a/liblaplayer.so	OK
2026-05-30 15:55:36	Analyzing apktool_out/lib/arm64-v8a/libcrashlytics-handler.so	OK
2026-05-30 15:55:36	Analyzing apktool_out/lib/arm64-v8a/librtmp-jni.so	OK
2026-05-30 15:55:36	Analyzing apktool_out/lib/arm64-v8a/libvkrottie.so	OK
2026-05-30 15:55:36	Analyzing apktool_out/lib/arm64-v8a/libjingle_peerconnection_so.so	OK

2026-05-30 15:55:37	Analyzing apktool_out/lib/arm64-v8a/libaudio-effects.so	OK
2026-05-30 15:55:37	Analyzing apktool_out/lib/arm64-v8a/libcrashlytics-common.so	OK
2026-05-30 15:55:37	Analyzing apktool_out/lib/arm64-v8a/libverify.so	OK
2026-05-30 15:55:37	Analyzing apktool_out/lib/arm64-v8a/libstatic-webp.so	OK
2026-05-30 15:55:37	Analyzing apktool_out/lib/arm64-v8a/libdatastore_shared_counter.so	OK
2026-05-30 15:55:37	Analyzing apktool_out/lib/arm64-v8a/libvkmmedia.so	OK
2026-05-30 15:55:37	Analyzing apktool_out/lib/arm64-v8a/libnative-imagetranscoder.so	OK
2026-05-30 15:55:37	Analyzing apktool_out/lib/arm64-v8a/libsqliteobserver.so	OK
2026-05-30 15:55:37	Analyzing apktool_out/lib/arm64-v8a/libnative-net.so	OK
2026-05-30 15:55:37	Analyzing apktool_out/lib/arm64-v8a/libvkcore.so	OK
2026-05-30 15:55:37	Analyzing apktool_out/lib/arm64-v8a/libtrhook2.so	OK
2026-05-30 15:55:37	Reading Code Signing Certificate	OK
2026-05-30 15:55:38	Running APKiD 3.0.0	OK

2026-05-30 15:55:52	Detecting Trackers	OK
2026-05-30 15:56:17	Decompiling APK to Java with JADX	OK
2026-05-30 15:56:17	Decompiling with JADX failed	FileNotFoundException(2, 'No such file or directory')
2026-05-30 15:56:17	Converting DEX to Smali	OK
2026-05-30 15:56:17	Code Analysis Started on - java_source	OK
2026-05-30 15:56:18	Android SBOM Analysis Completed	OK
2026-05-30 15:56:19	Android SAST Completed	OK
2026-05-30 15:56:19	Android API Analysis Started	OK
2026-05-30 15:56:23	Android API Analysis Completed	OK
2026-05-30 15:56:39	Android Permission Mapping Started	OK
2026-05-30 15:56:51	Android Permission Mapping Completed	OK
2026-05-30 15:56:56	Android Behaviour Analysis Started	OK
2026-05-30 15:57:07	Android Behaviour Analysis Completed	OK

2026-05-30 15:57:07	Extracting Emails and URLs from Source Code	OK
2026-05-30 15:57:07	Email and URL Extraction Completed	OK
2026-05-30 15:57:07	Extracting String data from APK	OK
2026-05-30 15:58:09	Extracting String data from SO	OK
2026-05-30 15:58:13	Extracting String data from Code	OK
2026-05-30 15:58:13	Extracting String values and entropies from Code	OK
2026-05-30 15:58:13	Performing Malware check on extracted domains	OK
2026-05-30 15:58:20	Saving to Database	OK

Report Generated by - MobSF v4.5.0

Mobile Security Framework (MobSF) is an automated, all-in-one mobile application (Android/iOS/Windows) pen-testing, malware analysis and security assessment framework capable of performing static and dynamic analysis.

© 2026 Mobile Security Framework - MobSF | [Ajin Abraham](#) | [OpenSecurity](#).