

## 0. Видове deploy-ване

Два варианта:

### 0.1. On-Premise (On-Prem)

имаме собствен сървър или си ко-локираме купената от нас машина в специално наето помещение.

### 0.2. Cloud

Ние не притежаваме такива сървърни машини, но си плащаме да ползваме

#### Unmanaged Solution

Имаме достъп до виртуална cloud машина (лимит за трафик, ядра на машината, и т.н.)

Например Tier plan – първоначално безплатно, и когато имаме повече потребители/трафик, то си плащаме

#### Managed Solution

Не само не се грижим за физически за ядрата и машината, но направо си качваме проекта някъде.


#### *Server application*


API Rest application – Back4Up, SoftUni server, database services, etc.

#### *Client-Side application*

## 1. Deploying site in Host Github.io (GitHub pages) + VSC (JS Node)

### 1.1. Настройки в GitHub





## Create a new repository



A repository contains all project files, including the revision history. Already have a project repository elsewhere? [Import a repository.](#)

Owner \* ≡ Repository name \*

quizfever / quizfever.github.io ✓

Great repository names are short and memorable. Need inspiration? How about literate-memory?

Description (optional)

- ☒  **Public**  
Anyone on the internet can see this repository. You choose who can commit.
- ☐  **Private**  
You choose who can see and commit to this repository.

### Initialize this repository with:

Skip this step if you're importing an existing repository.

- ☐ **Add a README file**  
This is where you can write a long description for your project. [Learn more.](#)

### Add .gitignore

Choose which files not to track from a list of templates. [Learn more.](#)

.gitignore template: None ▾

### Choose a license


A license tells others what they can and can't do with your code. [Learn more.](#)

License: None ▾

 You are creating a public repository in the quizfever organization.

Create repository

### Quick setup — if you've done this kind of thing before

 Set up in Desktop

or

**HTTPS** SSH



Get started by [creating a new file](#) or [uploading an existing file](#). We recommend every repository include a [README](#), [LICENSE](#), and [.gitignore](#).

### ...or create a new repository on the command line

```
echo "# quizfever.github.io" >> README.md
git init
git add README.md
git commit -m "first commit"
git branch -M main
git remote add origin https://github.com/quizfever/quizfever.github.io.git
git push -u origin main
```



### ...or push an existing repository from the command line

```
git remote add origin https://github.com/quizfever/quizfever.github.io.git
git branch -M main
git push -u origin main
```



### ...or import code from another repository

You can initialize this repository with code from a Subversion, Mercurial, or TFS project.

[Import code](#)

## 1.2. Инициализиране на GitHub в VSC(Node.js)

TERMINAL

DEBUG CONSOLE

PROBLEMS

OUTPUT

Copyright (C) Microsoft Corporation. All rights reserved.

Try the new cross-platform PowerShell <https://aka.ms/pscore6>

PS C:\Temp projects\21-22 - Workshop End-to-End Application - Feb'21\quiz> git init

## 1.3. Добавяне на .gitignore файл

```
.gitignore U X JS r
src > .gitignore
1 node_modules
```

```
PS C:\Temp projects\21-22 - Workshop End-to-End Application - Feb'21\quiz> git init
Initialized empty Git repository in C:/Temp projects/21-22 - Workshop End-to-End Application - Feb'21/quiz/.git/
PS C:\Temp projects\21-22 - Workshop End-to-End Application - Feb'21\quiz> git add .gitignore ✓
PS C:\Temp projects\21-22 - Workshop End-to-End Application - Feb'21\quiz> git commit -m "added ignore file" ✓
[master (root-commit) f7b3c11] added ignore file
1 file changed, 1 insertion(+)
create mode 100644 .gitignore
```

#### 1.4. Добавяне на readme.md файл

Ние сме си го създали вече този файл локално – описание/документация на проекта

#### 1.5. Определяне на главна директория на репо-то и свързването й с GitHub

...or push an existing repository from the command line

```
PS C:\Temp projects\21-22 - Workshop End-to-End Application - Feb'21\quiz> git branch -M master
PS C:\Temp projects\21-22 - Workshop End-to-End Application - Feb'21\quiz> git remote add origin https://github.com/quizfever/quizfeve
o.git
git remote add origin https://github.com/movies-softuni/movies-softuni.github.io.git
```


`git branch -M main`    да не го правим – да си сменим master на main

#### 1.6. Push

```
PS C:\Temp projects\21-22 - Workshop End-to-End Application - Feb'21\quiz> git push -u origin master
info: please complete authentication in your browser...
```

#### 1.7. Initial commit from VSC interface

**Ctrl + Enter** – за да ги качи всичките файлове



## 1.8. We can see the result in the web of GitHub

quizfever / quizfever.github.io (Public)

<> Code Issues Pull requests Actions Projects Wiki Security Insights Settings

master 1 branch 0 tags

Go to file Add file Code

About No description, website, or topics provided.

Readme 0 stars 0 watching 0 forks

Releases No releases published Create a new release

Packages No packages published Publish your first package

Environments 1

github-pages Active

Initial commit

|            |                   |                |
|------------|-------------------|----------------|
| assets     | Initial commit    | 6 minutes ago  |
| src        | Initial commit    | 6 minutes ago  |
| static     | Initial commit    | 6 minutes ago  |
| .gitignore | added ignore file | 18 minutes ago |
| 404.html   | Initial commit    | 6 minutes ago  |
| index.html | Initial commit    | 6 minutes ago  |
| readme.md  | Initial commit    | 6 minutes ago  |

readme.md

#Quiz system - Quiz fever Система за създаване, управление и попълване на тестове със свободен достъп.

**Функционалност**

- Регистрация на потребители

Deployments / History

Show: github-pages

github-pages at b44ebd2

Deployed by github-pages 7 minutes ago Active

View deployment

## 1.9. Back4Up или друг BaaS – тестване на http заявки

1. x Initialize project
2. x Copy / api
3. x Create Back4Up app
4. View documentation on Users
5. x Adjust api.js to include AppID, APIKey, correct headers, register/login/logout routes and bodies
6. x Test register/login/logout
7. Examine Database Browser, create Quiz collection
8. x Create CRUD functions for Quiz collection
9. x Test Quiz collection, confirm it is public for read/write, NO Add field CLP
10. View documentation on security, ACL, CLP
11. x Configure public read, authenticated write, NO add field CLP
12. x Test read/write
13. x Configure owner pointer
14. x Adjust data.js to include owner pointer on create - { \_\_type: 'Pointer', className: 'User' }

- 15. x Test owner protection
- 16. x Add query to include owner on GET
- 17. x Create Question collection, configure CLP, owner pointer, Quiz pointer
- 18. x Create CRUD functions for Question collection, with owner protection
- 19. x Test Question collection
- (20. Proceed with implementation of views)

## 1.10. Generating the package.json file and installing external libraries

npm init -y

npm install -E lit-html page -E е за запазване


```
{
  "name": "quiz",
  "version": "1.0.0",
  "description": "Система за създаване, управление и попълване на тестове със свободен достъп.",
  "main": "index.html",
  "scripts": {
    "test": "echo \"Error: no test specified\" && exit 1"
  },
  "repository": {
    "type": "git",
    "url": "git+https://github.com/quizfever/quizfever.github.io.git" //автоматично се генерира и път към git репото
  },
  "keywords": [],
  "author": "",
  "license": "ISC",
  "bugs": {
    "url": "https://github.com/quizfever/quizfever.github.io/issues"
  },
  "homepage": "https://github.com/quizfever/quizfever.github.io#readme",
  "dependencies": {
    "lit-html": "2.2.3",
    "page": "1.11.6"
  }
}
```

## 1.11. Re-commit from VSC interface

**Ctrl + Enter** – за да ги качи всичките файлове

## 1.12. How to deploy external libraries

Option 1) Копираме само определени файлове от node-modules



Налага се да докопираме допълнителни 2-3 файла, за да не хвърля грешка

Option 2) Вземаме директно от online CDN-а в уеб пространството

Не е добра идея защото CDN-а може да се промени

```
import page from 'unpkg.com/page/page.mjs';
import {html, render} from 'unpkg.com/lit-html?module';

export {
  page,
  html,
  render
}
```

Option 3) Най-правилния production вариант с build стъпка

Работим си локално, и след това минава скрипт, който пакетира външните библиотеки.


- **Webpack**
- Minify.js
- Browerify
- RollUp

File 404.html - we can manually add from <https://github.com/rafgraph/spa-github-pages> - когато рефрешнем дадена страница на SPA, то дава грешка. И затова трябва да използваме 404.html

<https://github.com/rafgraph/spa-github-pages>

<https://github.com/rafgraph/spa-github-pages>

To easily copy it



На негово място слагаме този от <https://github.com/rafgraph/spa-github-pages>

```
<!DOCTYPE html>
<html>
  <head>
    <meta charset="utf-8">
    <title>Single Page Apps for GitHub Pages</title>
    <script type="text/javascript">
      // Single Page Apps for GitHub Pages
      // MIT License
      // https://github.com/rafgraph/spa-github-pages
      // This script takes the current url and converts the path and query
      // string into just a query string, and then redirects the browser
      // to the new url with only a query string and hash fragment,
      // e.g. https://www.foo.tld/one/two?a=b&c=d#qwe, becomes
      // https://www.foo.tld/?/one/two&a=b~and~c=d#qwe
      // Note: this 404.html file must be at least 512 bytes for it to work
      // with Internet Explorer (it is currently > 512 bytes)

      // If you're creating a Project Pages site and NOT using a custom domain,
      // then set pathSegmentsToKeep to 1 (enterprise users may need to set it to > 1).
      // This way the code will only replace the route part of the path, and not
      // the real directory in which the app resides, for example:
      // https://username.github.io/repo-name/one/two?a=b&c=d#qwe becomes
      // https://username.github.io/repo-name/?/one/two&a=b~and~c=d#qwe
      // Otherwise, leave pathSegmentsToKeep as 0.
      var pathSegmentsToKeep = 0;

      var l = window.location;
      l.replace(
        l.protocol + '//' + l.hostname + (l.port ? ':' + l.port : '') +
        l.pathname.split('/').slice(0, 1 + pathSegmentsToKeep).join('/') + '/?/' +
        l.pathname.slice(1).split('/').slice(pathSegmentsToKeep).join('/').replace(/&/g,
        '~and~') +
        (l.search ? '&' + l.search.slice(1).replace(/&/g, '~and~') : '') +
        l.hash
      );

    </script>
  </head>
  <body>
  </body>
</html>
```



И слагаме в index.html, преди всички други script-ове, този скрипт от <https://github.com/rafgraph/spa-github-pages>:

- 1) 

```
<!-- Start Single Page Apps for GitHub Pages -->
<script type="text/javascript">
  // Single Page Apps for GitHub Pages
  // MIT License
  // https://github.com/rafgraph/spa-github-pages
  // This script checks to see if a redirect is present in the query string,
  // converts it back into the correct url and adds it to the
  // browser's history using window.history.replaceState(...),
  // which won't cause the browser to attempt to load the new url.
  // When the single page app is loaded further down in this file,
  // the correct url will be waiting in the browser's history for
  // the single page app to route accordingly.
  (function(l) {
    if (l.search[1] === '/' ) {
      var decoded = l.search.slice(1).split('&').map(function(s) {
        return s.replace(/~and~/g, '&')
      }).join('?');
      window.history.replaceState(null, null,
        l.pathname.slice(0, -1) + decoded + l.hash
      );
    }
  })(window.location))
</script>
<!-- End Single Page Apps for GitHub Pages -->
```
- 2) 

```
<script src="src/app.js" type="module"></script>
```


## 2. Deploying in Host Heroku + VSC (JS Node) – we can deploy the RestApi backend softuni server

<https://www.heroku.com/>

### 2.1. Регистриране в heroku

- ➔ Register in Heroku
- ➔ Create New App

Deployment method




GitHub  
Connect to GitHub



Container Registry  
Use Heroku CLI

Download and install the [Heroku CLI](#). - Command-Line interface



## 2.2. Нагласяне на SoftUni server-a

В папката apiRest\_SoftUniServer

**npm init -y**

package.json

```
{
  "name": "apiRest_SoftUniServer",
  "version": "1.0.0",
  "description": "",
  "main": "server.js",
  "scripts": {
    "start": "node server.js"
  },
  "keywords": [],
  "author": "",
  "license": "ISC"
}
```

npm run start или npm start работи.

## 2.3. Да влезем в профила си в Heroku CLI

С тази команда в Shell-a, която пак ще ни отведе до login страницата на Heroku.

**heroku login**

To install heroku-repo:

```
heroku plugins:install heroku-repo
```

## 2.4. Create a new Git repository and deploy it

**git init**

heroku git:remote -a movies-softuni

git add .

git status

git commit -am "Initial commit" - -a означава всичко, което е модифицирано, го качвай

git push heroku master

```
svilk@SVILKATA MINGW64 ~/OneDrive/Soft Engineer/JAVA & JS path/PROJECTS/21-22 - Worskhop End to End app - .fetch.then - heroku - firebase/apiRest_SoftUniServer (master)
```

```
$ git push heroku master
```


```
Enumerating objects: 5, done.
Counting objects: 100% (5/5), done.
Delta compression using up to 20 threads
Compressing objects: 100% (3/3), done.
Writing objects: 100% (3/3), 386 bytes | 386.00 KiB/s, done.
Total 3 (delta 1), reused 0 (delta 0), pack-reused 0
remote: Updated 10 paths from d037df0
remote: Compressing source files... done.
remote: Building source:
remote:
remote: -----> Building on the Heroku-20 stack
remote: -----> Using buildpack: heroku/nodejs
remote: -----> Node.js app detected
remote:
remote: -----> Creating runtime environment
remote:
remote:       NPM_CONFIG_LOGLEVEL=error
remote:       NODE_VERBOSE=false
remote:       NODE_ENV=production
remote:       NODE_MODULES_CACHE=true
remote:
remote: -----> Installing binaries
remote:       engines.node (package.json):  unspecified
remote:       engines.npm (package.json):   unspecified (use default)
remote:
remote:       Resolving node version 20.x...
remote:       Downloading and installing node 20.11.0...
remote:       Using default npm version: 10.2.4
remote:
remote: -----> Restoring cache
remote:       Cached directories were not restored due to a change in version of node, npm,
yarn or stack
remote:       Module installation may take longer for this build
remote:
remote: -----> Installing dependencies
remote:       Installing node modules (package.json)
remote:
remote:       up to date, audited 1 package in 638ms
remote:
remote:       found 0 vulnerabilities
remote:
remote: -----> Build
remote:
remote: -----> Caching build
remote:       - node_modules (nothing to cache)
remote:
remote: -----> Pruning devDependencies
remote:
remote:       up to date, audited 1 package in 300ms
remote:
remote:       found 0 vulnerabilities
remote:
remote: -----> Build succeeded!
remote: -----> Discovering process types
remote:       Procfile declares types      -> (none)
remote:       Default types for buildpack -> web
remote:
remote: -----> Compressing...
remote:       Done: 44.7M
```

```

remote: ----> Launching...
remote:      Released v5
remote:      https://movies-softuni.herokuapp.com/ deployed to Heroku
remote:
remote: This app is using the Heroku-20 stack, however a newer stack is available.
remote: To upgrade to Heroku-22, see:
remote: https://devcenter.heroku.com/articles/upgrading-to-the-latest-stack
remote:
remote: Verifying deploy... done.
To https://git.heroku.com/movies-softuni.git
   2d16b74..0ecc0b4  master -> master

```

Също така трябва и ръчно да активираме даденото приложение от Heroku:



Нашият софтуни сървър не е направен да се качва в Heroku, затова трябва да му зададем автоматичен порт, и heroku сам да си определя на кой порт да се рънва.

```

const server = http__default['default'].createServer(requestHandler(plugins, services));

const port = 3030;
const port = process.env.PORT || 3030; //така ще тръгне в Heroku, и ще бачка и без да
използваме heroku

server.listen(port);
console.log(`Server started on port ${port}. You can make requests to
http://localhost:${port}/`);
console.log(`Admin panel located at http://localhost:${port}/admin`);

var softuniPracticeServer = {


};

return softuniPracticeServer;

```

git add .     може и без тази команда, защото следващата команда е -а (-а означава всичко, което е  
модифицирано, го качвай)  
git commit -am "Add port env. variable"  
git push heroku master

<https://movies-softuni.herokuapp.com/>



Loading...

Request throttling: false

- recipes
- comments
- records
- catches
- furniture
- orders
- movies
- likes
- ideas

Select collection to view records

И вече softUni сървър работи стартиран от интернет пространството

GET <https://movies-softuni.herokuapp.com/data>

Params Authorization Headers (8) Body ● Pre-request Script Tests Settings

| KEY | VALUE | DESCRIPTION |
|-----|-------|-------------|
| Key | Value | Description |

Body Cookies Headers (7) Test Results 🌐 Status: 200 OK Time: 516 ms Size: 1

Pretty Raw Preview Visualize JSON

1

2.5. Front-End/Client server we make via github pages -> new organization

Сменяме и base URL адреса на backend услугата:

```
// export const baseUrl = 'http://localhost:3030';  
export const baseUrl = 'https://movies-softuni.herokuapp.com'; //URL-то на SoftUni  
server, който качихме в Heroku.
```

## CORS - Access-Control-Allow-Origin

Няма нужда

```
options.headers['Access-Control-Allow-Origin'] = '*';
```


re-run on the local lite-server for example

```
Access-Control-Allow-Origin: *  
Access-Control-Allow-Origin: <origin>  
Access-Control-Allow-Origin: null
```

Ако имаме в requester.js console.log(response) и се чупи.

## 2.6. Procfile and system.properties for Java web application

- Before running our project, we should add **3 important keys** to deploy the project
- Create 2 new files in our **project folder**
  - **Procfile**
  - **system.properties**



### System.properties

- system.properties
  - Holds **all of the system configuration properties** needed to run the project
  - By default, Heroku uses JDK Version 1.8
  - To specify specific version:

```
java.runtime.version={version}  
java.runtime.version=17  
java.runtime.version=11
```

### Procfile

- Procfile
  - Holds the executed commands by the application on startup
  - Should include:


Където се намира jar-a

```
web: java -jar target/{name}-{version}.jar    - за Maven  
web: java -jar build/libs/{name}-{version}.jar - за Gradle
```

```
web: java -jar build/libs/books.jar
```

```
build.gradle
group = 'bg.softuni'
version = '0.0.1-SNAPSHOT'
sourceCompatibility = '17'
```


```
pom.xml
<version>1.0.0-SNAPSHOT</version>
<name>project_name</name>
```




### 3. Deploying in Host Railway

<https://railway.app>

```
application.yml
# railway deployment
driverClassName: org.postgresql.Driver
url: jdbc:postgresql://${PG_HOST}:${PG_PORT}/${POSTGRES_DB_NAME}
username: ${POSTGRES_USER}
password: ${POSTGRES_PASSWORD}
hikari:
  connection-timeout: 30000
  maximum-pool-size: 10
```



За лесно менџжиране – да се видят базите какво записи има в момента.




App sleeping only for [Priority Boarding](#) members.

<https://docs.railway.app/reference/app-sleeping>

To become a priority boarding, you should only connect to Discord and enter that channel priority boarding.

Then, all you need to do is to activate the sleeping feature from here:






Heroku and Railway accept hosting Node JS applications, in particular a Node JS server application.

#### 4. Deploying in Host Firebase + VSC (JS Node) – we can deploy front-end client server

<https://console.firebase.google.com> - login with gmail account

##### movies-softuni

Към един проект, може да има няколко вида front-end – за мобилно устройство Android, за web, за apple,



The screenshot shows the Firebase console interface. At the top, there's a blue header with the text "movies-softuni". Below it, a message says "Към един проект, може да има няколко вида front-end – за мобилно устройство Android, за web, за apple,". The main part of the image is a dialog box titled "Add Firebase to your web app". It has a close button (X) in the top left. The dialog is divided into two steps: "1 Register app" and "2 Add Firebase SDK". In the "1 Register app" section, there's a field for "App nickname" with the value "movies-softuni". Below this, there's a checkbox labeled "Also set up **Firebase Hosting** for this app. [Learn more](#)". A note below the checkbox says "Hosting can also be set up later. There is no cost to get started anytime". At the bottom of the "1 Register app" section is a blue button labeled "Register app". The "2 Add Firebase SDK" section is partially visible at the bottom.

## × Set up Firebase Hosting

### 1 Install Firebase CLI

To host your site with Firebase Hosting, you need the Firebase CLI (a command line tool).

Run the following [npm](#) command to install the CLI or update to the latest CLI version.

```
$ npm install -g firebase-tools
```



Command-Line interface



### Install Firebase CLI

2

### Initialize your project

Open a terminal window and navigate to or create a root director

Sign in to Google

```
$ firebase login
```



Initiate your project

Run this command from your app's root directory:

```
$ firebase init
```



Next

```
PS C:\Temp projects\21-22 - Worskhop End to End app - .fetch.then - heroku\movies> firebase init
Debugger listening on ws://127.0.0.1:58254/4ea050e9-62b6-46b5-a8f7-be6ed812412b
For help, see: https://nodejs.org/en/docs/inspector
Debugger attached.
```

```
#####  ###  #####  #####  #####  ###  #####  #####
##      ##  ##  ##  ##  ##  ##  ##  ##  ##
#####  ##  #####  #####  #####  #####  #####  #####
##      ##  ##  ##  ##  ##  ##  ##  ##  ##
##      #####  ##  #####  #####  ##  ##  #####  #####
```

You're about to initialize a Firebase project in this directory:

C:\Temp projects\21-22 - Worskhop End to End app - .fetch.then - heroku\movies

Before we get started, keep in mind:

\* You are currently outside your home directory

```
? Are you ready to proceed? Yes
? Which Firebase features do you want to set up for this directory? Press Space to select features, then Enter to confirm your c
es. (Press <space> to select, <a> to toggle all, <i> to invert selection, and <enter> to proceed)
( ) Realtime Database: Configure a security rules file for Realtime Database and (optionally) provision default instance
( ) Firestore: Configure security rules and indexes files for Firestore
( ) Functions: Configure a Cloud Functions directory and its files
>(*) Hosting: Configure files for Firebase Hosting and (optionally) set up GitHub Action deploys
( ) Hosting: Set up GitHub Action deploys
( ) Storage: Configure a security rules file for Cloud Storage
( ) Emulators: Set up local emulators for Firebase products
(Move up and down to reveal more choices)
```

---

Enter

```
? Please select an option:
> Use an existing project
Create a new project
Add Firebase to an existing Google Cloud Platform project
Don't set up a default project
```

Enter


```
? Please select an option: Use an existing project
? Select a default Firebase project for this directory:
> movies-softuni-7ea72 (movies-softuni) ✓
svilenproject (SvilenProject)
```

Enter

Точката представлява, че нашата public directory е текущата директория.

```
? What do you want to use as your public directory? . ✓
? Configure as a single-page app (rewrite all urls to /index.html)? No ✓
? Set up automatic builds and deploys with GitHub? No ✓
+ Wrote ./404.html
? File ./index.html already exists. Overwrite? No ✓
i Skipping write of ./index.html

i Writing configuration info to firebase.json...
i Writing project information to .firebaserc...
```



✓ Install Firebase CLI

✓ Initialize your project

3 Deploy to Firebase Hosting ✓

**When you're ready, deploy your web app**

Put your static files (e.g., HTML, CSS, JS) in your app's deploy director

Then, run this command from your app's root directory:

```
$ firebase deploy
```



After deploying, view your app at [movies-softuni-7ea72.web.app](https://movies-softuni-7ea72.web.app) [↗](#)

Need help? Check out the [Hosting docs](#) [↗](#)

[Continue to console](#)

Тази папка .firebase трябва да я ignore-нем.

```
.gitignore M X
.gitignore
1 node_modules
2 | .firebase
```

Два домейна ни прави – могат да се ползват и те

movies-softuni-7ea72 domains

[Add custom domain](#)

Domain

Status

movies-softuni-7ea72.web.app  
Default

movies-softuni-7ea72.firebaseio.com  
Default


File 404.html - automatically generated by firebase – когато рефрешнем дадена страница на SPA, то дава грешка. И затова трябва да използваме 404.html

```
<!DOCTYPE html>
<html>
  <head>
    <meta charset="utf-8">
    <meta name="viewport" content="width=device-width, initial-scale=1">
    <title>Page Not Found</title>

    <style media="screen">
      body { background: #ECEFF1; color: rgba(0,0,0,0.87); font-family: Roboto,
Helvetica, Arial, sans-serif; margin: 0; padding: 0; }
      #message { background: white; max-width: 360px; margin: 100px auto 16px; padding:
32px 24px 16px; border-radius: 3px; }
      #message h3 { color: #888; font-weight: normal; font-size: 16px; margin: 16px 0
12px; }
      #message h2 { color: #ffa100; font-weight: bold; font-size: 16px; margin: 0 0 8px;
}
      #message h1 { font-size: 22px; font-weight: 300; color: rgba(0,0,0,0.6); margin: 0
0 16px;}
      #message p { line-height: 140%; margin: 16px 0 24px; font-size: 14px; }
      #message a { display: block; text-align: center; background: #039be5; text-
transform: uppercase; text-decoration: none; color: white; padding: 16px; border-radius:
4px; }
      #message, #message a { box-shadow: 0 1px 3px rgba(0,0,0,0.12), 0 1px 2px
rgba(0,0,0,0.24); }
      #load { color: rgba(0,0,0,0.4); text-align: center; font-size: 13px; }
      @media (max-width: 600px) {
        body, #message { margin-top: 0; background: white; box-shadow: none; }
        body { border-top: 16px solid #ffa100; }
      }
    </style>
  </head>
  <body>
    <div id="message">
      <h2>404</h2>
      <h1>Page Not Found</h1>
      <p>The specified file was not found on this website. Please check the URL for
mistakes and try again.</p>
      <h3>Why am I seeing this?</h3>
      <p>This page was generated by the Firebase Command-Line Interface. To modify it,
edit the <code>404.html</code> file in your project's configured <code>public</code>
directory.</p>
    </div>
  </body>
</html>
```

<https://github.com/rafgraph/spa-github-pages>

To easily copy it



На негово място слагаме този от <https://github.com/rafgraph/spa-github-pages>

```
<!DOCTYPE html>
<html>
  <head>
    <meta charset="utf-8">
    <title>Single Page Apps for GitHub Pages</title>
    <script type="text/javascript">
      // Single Page Apps for GitHub Pages
      // MIT License
      // https://github.com/rafgraph/spa-github-pages
      // This script takes the current url and converts the path and query
      // string into just a query string, and then redirects the browser
      // to the new url with only a query string and hash fragment,
      // e.g. https://www.foo.tld/one/two?a=b&c=d#qwe, becomes
      // https://www.foo.tld/?/one/two&a=b~and~c=d#qwe
      // Note: this 404.html file must be at least 512 bytes for it to work
      // with Internet Explorer (it is currently > 512 bytes)

      // If you're creating a Project Pages site and NOT using a custom domain,
      // then set pathSegmentsToKeep to 1 (enterprise users may need to set it to > 1).
      // This way the code will only replace the route part of the path, and not
      // the real directory in which the app resides, for example:
      // https://username.github.io/repo-name/one/two?a=b&c=d#qwe becomes
      // https://username.github.io/repo-name/?/one/two&a=b~and~c=d#qwe
      // Otherwise, leave pathSegmentsToKeep as 0.
      var pathSegmentsToKeep = 0;

      var l = window.location;
      l.replace(
        l.protocol + '//' + l.hostname + (l.port ? ':' + l.port : '') +
        l.pathname.split('/').slice(0, 1 + pathSegmentsToKeep).join('/') + '/?/' +
        l.pathname.slice(1).split('/').slice(pathSegmentsToKeep).join('/').replace(/&/g,
        '~and~') +
        (l.search ? '&' + l.search.slice(1).replace(/&/g, '~and~') : '') +
        l.hash
      );
    </script>
```

```
</head>
<body>
</body>
</html>
```

И слагаме в index.html, преди всички други script-ове, този скрипт от <https://github.com/rafgraph/spa-github-pages>:

- 1) 

```
<!-- Start Single Page Apps for GitHub Pages -->
<script type="text/javascript">
  // Single Page Apps for GitHub Pages
  // MIT License
  // https://github.com/rafgraph/spa-github-pages
  // This script checks to see if a redirect is present in the query string,
  // converts it back into the correct url and adds it to the
  // browser's history using window.history.replaceState(...),
  // which won't cause the browser to attempt to load the new url.
  // When the single page app is loaded further down in this file,
  // the correct url will be waiting in the browser's history for
  // the single page app to route accordingly.
  (function(l) {
    if (l.search[1] === '/' ) {
      var decoded = l.search.slice(1).split('&').map(function(s) {
        return s.replace(/~and~/g, '&')
      }).join('?');
      window.history.replaceState(null, null,
        l.pathname.slice(0, -1) + decoded + l.hash
      );
    }
  })(window.location)
</script>
<!-- End Single Page Apps for GitHub Pages -->
```
- 2) 

```
<script src="src/app.js" type="module"></script>
```

firebase deploy и готово.

5. Deploying site in Host <https://www.netlify.com/>