

Spring Web

1. How to run

We can run the application from the IntelliJ Idea Run/Debug/Stop services.

Or we can run it with maven CLI command:

`mvn spring-boot:run`

1. Internet Explained

1.1. Internet – History

- Begins with the development of electronic computers in the 1950s.
- **Packet** switching networks were developed in the late 1960s
- The **internet protocol** was developed in the 1970s
- In the 1980s at CERN Tim Berners-Lee created the [**World Wide Web**](#) – the first website, linking hypertext documents into an information system, accessible from any node on the network

1.2. How Does the Internet Work?

Web Server Work Model




Important Definitions

- To understand how **the Internet works**, first we need to get acquainted with a few definitions
- **What is?**
 - Server and Client
 - Network Protocol
 - Packets
 - TCP vs UDP

Servers and Clients

- All of the machines on the Internet are either **servers** or **clients**
- **Servers** are the machines that provide services to other machines
- **Clients** are the machines that are used to connect to those services



Network Protocol

- **Network Protocol** – a set of rules and standards, that allow communication between network devices
- Network protocols include **mechanisms** for devices to identify and make **connections** with each other
- Example for standard network protocols:
 - TCP, UDP, IP, ARP
 - HTTP, FTP, TFTP, SMTP, SSH


1.3. Packets (late 1960s)

- Everything that is created on a computer is translated into digital information using **bits**
- Bits need to have a way to be transmitted over the internet
- Every message, file or stream of information is broken down into small chunks called **packets**
- When packets are sent on the internet, they usually travel the network together
- But they might have to take a different route to get to the destination
- Each packet contains some **important information** inside of it called **the header**:
 - Where it came from
 - Where is it going
 - How long it is
 - This is how the packet is known to be complete
 - All the packets in the message are the same size
 - How many packets there are in the overall message

1.4. Internet Protocol (1970s) - IPv4, IPv6 and DNS

Internet Protocol

- One of the most important protocols used in Internet communication is the **Internet Protocol (IP)**
- All the devices on the Internet have **addresses**
- They are called **IP Addresses**
- The IP address is **unique** to each computer or a device at the edge of the network



IPv4

- IPv4 is a sequence of four, three-digit numbers separated by a period
 - Each number can be a number from 0 to 255
 - IPv4 is not enough for all network devices connected to the internet
 - In 1995, a new version of the internet protocol was created, it's called IPv6

IP Address

- An IP Address has many parts, organized in a hierarchy
 - Subnetworks

168.14.120

 - Device address
 - This version of IP Addressing is called IPv4
 - Provides more than 4 billion 32 bits unique addresses

IP address classes

What Is CIDR (Classless Inter-Domain Routing)

- Classless Inter-Domain Routing, is an IP addressing scheme that **improves the allocation of IP addresses**.
- **It replaces the old system based on classes A, B, and C.**
- This scheme also helped greatly **extend the life of IPv4** as well as slow the growth of routing tables

IPv4 Private Address Space and Filtering

CIDR	IP address range	Class
10.0.0.0/8	10.0.0.0 – 10.255.255.255	A
172.16.0.0/12	172.16.0.0 – 172.31.255.255	B
192.168.0.0/16	192.168.0.0 – 192.168.255.255	C

IPv6

- **IPV6 uses 128 bits** - 340 undecillion unique addresses
 - That's more than the atoms on the surface of the Earth
- These **128 bits** are organized into eight 16 bit sections
- Each 16 bit block is converted to hexadecimal and it's separated with a colon
- This is a full IPV6 address:
 - **3FFE:F200:0234:AB00:0123:4567:8901:ABCD**
- The **leading zeros** in IPv6 can usually be left out



What is a DNServer (Domain Name Server)?

- The **domain name** is a **human way to access IP addresses** for devices and websites around the world



- It is a sequence of phrases that **map** to a giant **Internet-wide database of IP addresses**
- When a domain name is entered in the browser, a request is made to something called a **DNS (Domain Name Server)**
- This server holds a **cache of tons of domain names, and their matching IP addresses**

DNS (Domain Name Server) Example




1.5. Reliability and TCP (Transmission Control Protocol)

Reliability (надеждност/сигурност)

- When packets are transmitted from one location to another, they can take different paths
- When they get to the destination, they are unorganized and sometimes not complete
- So the message needs to be audited and reviewed in order to put it together in the right way
- The **Transmission Control Protocol** or **TCP** does exactly that

TCP - Transmission Control Protocol

- **TCP** uses a process, where it looks at all the packets in a message and checks them
- Using the **header information** in **each packet** it knows:
 - How many there are
 - How large they should be
 - In which order the packets should be in
- Using this checklist, **it is able to rearrange the packets**
- If it finds that a packet doesn't match the expected characteristic, it is discarded (захвърлен)
- **TCP** has to **verify** that all the packets are:
 - In the right order
 - Free of any issues
- After that it **certifies the data** and the packets are **merged** together to recreate the **original** file that was on the sender's device



TCP vs UDP

- TCP places **reliability** in a higher priority than speed or latency
- For instances where reliability isn't as important, but **speed** is, there is another protocol called **UDP** or **User Datagram Protocol**
- UDP doesn't do excessive reliability checks, but it can send information at a faster rate
- TCP is the foundation of how a majority of data is transmitted over networks



UDP (User Datagram Protocol)

- UDP does not establish a session and it does not guarantee data delivery
- It is known as the "**fire-and-forget**" protocol
 - It sends data and it doesn't really care if the data is received at the other end



1.6. The OSI Model (Open System Interconnect)


What is the OSI Model?

- **OSI** model stands for **Open System Interconnect**
- It consists of 7 layers
 - Each layer serves the layer above it and in return, is served by the layer below it
- Understanding each layer of the model helps us with:
 - Troubleshooting
 - Communicating better with technical and non-technical individuals about any system


OSI Layers

- OSI Model consists of 7 layers:

I OSI Model consists of 7 layers:



TCP/IP model mapping to OSI



Application Layer – level 7

- Enables different applications like the browser to use the network and **present it to the End User**
- Protocol examples:
 - Domain Name System (**DNS**ystem)
 - File Transfer Protocol (**FTP**)
 - HyperText Transfer Protocol (**HTTP**)
 - Simple Mail Transfer Protocol (**SMTP**)




Presentation Layer – level 6

- This layer is a part of an operating system (OS)
- Converts incoming and outgoing **data** from **one presentation format to another**
- Example:
 - From clear text to **encrypted** (or compressed) text
 - Back to clear text



Session Layer – level 5

- This layer sets up coordinates and terminates conversations
- Its services include authentication and reconnection after an interruption
- e.g.: Sockets




Transport Layer – level 4

- Responsible for end-to-end communication over a network
- Provides logical communication between application processes
- Responsible for the management of error correction, providing quality and reliability to the end user
- Protocol examples:
 - Transmission Control Protocol (TCP)**

- User Datagram Protocol (UDP)


Network Layer – level 3

- Provides the functional and procedural means of **transferring packets from one node to another**
- Responds to service requests from the transport layer and issues service requests to the data link layer
- Protocol examples:
 - **Internet Protocol (IP)**
 - **IPSec (IP + Auth)**



Data Link Layer – level 2

- Provides node-to-node data transfer
- It **detects** and possibly **corrects** errors that may occur in the **physical layer**
- Divides into two sublayers:
 - **Medium access control (MAC)** layer - controlling how devices in a network gain access to a medium and permission to transmit data
 - **Logical link control (LLC)** layer – identifying and encapsulating network layer protocols, controls error checking and frame synchronization
- Protocol examples:
 - **Asynchronous Transfer Mode (ATM)**
 - **Ethernet**
 - **MAC**



Physical Layer – level 1

- The things you can actually physically touch
- Converts the **binary** from the upper layers into **signals**, **transmits** them over local media (electrical, light, or radio signals)
- Examples:
 - **Ethernet**
 - **USB**
 - **Bluetooth**
 - **802.11a/b/g/n**



1.7. Network Hardware

Network Hardware

- Basic Hardware Components
 - Cables
 - Routers
 - Repeaters, Hubs and Switches
 - Bridges
 - Gateways
 - Network Interface Cards

Cables and Routers

- Network Cables – the **transmission media** to transfer data from one device to another



- Router – **connecting device** that transfers data packets between different computer networks (operates on level 3 of OSI)



Repeaters, Hubs and Switches

- **Repeaters, hubs and switches connect network devices** together so that they can function as a single segment
 - Repeater – **receives a signal** and regenerates it before re-transmitting, so that it can travel longer distances
 - Hub – multiport **repeater** (operates on level 1 of the OSI model)
 - Switch – **receives data** from a port, uses packet switching to resolve the destination device and forwards the data to the particular destination (operates on level 2 of the OSI model)

Bridges and Gateways

- **Bridge**
 - Connects two separate but **similar** Ethernet network segments
 - Forwards packets from the source network to the destined network (operates on level 2 of OSI)
- **Gateway**

- **Connects networks** that work upon **different** protocols
- The entry and the exit point of a network (**controls the access to other networks**) Level 4, 5, 6 or 7 of the OSI model (same as Firewalls)

Network Interface Cards – NIC

- **NIC** – a computer component that connects it to the network
- There are two types of network cards:
 - Internal
 - External



1.8. The Future of the Internet

- The "**Internet of Things**" will expand
 - Healthcare, agriculture, wearables, manufacturing
 - Smart homes, cars and cities (pollution, parking, energy)
 - In 2030 there will be **50 billion devices** connected to the Internet of Things

2. HTTP Protocol

Изначало HTTP Protocol е бил stateless – backend-server-а не трябва да пази информацията от предходната заявка на предхония или същия клиент. След това, с времето, обаче се променят нещата.


- Stateless – няма състояние, на практика не е така – има кукита, и .т.н.

<https://blog.restcase.com/4-maturity-levels-of-rest-api-design/>

If you are building REST (REpresentational State Transfer) APIs or REST (REpresentational State Transfer) Services you're using HTTP. Technically, REST services can be provided over any application layer protocol as long as they conform to certain properties. In practice, basically, everyone uses HTTP Protocol.

2.1. HTTP Basics

Hyper Text Transfer Protocol



HTTP Request Methods

- **HTTP** defines **methods** to indicate the desired action to be performed on the identified resource

Method	Description
GET	Retrieve / load a resource
POST	Create / store a resource
PUT	Update a resource by replacing it with a new one
PATCH	Update partial parts of the item
DELETE	Remove a resource

HTTP Conversation: Example

! HTTP request:

GET /courses/javascript HTTP/1.1

Host: www.softuni.bg

User-Agent: Mozilla/5.0

<CRLF>

The empty line denotes the end of the request header

! HTTP response:

HTTP/1.1 200 OK

Date: Mon, 5 Jul 2020 13:09:03 GMT

Server: Microsoft-HTTPAPI/2.0

Last-Modified: Mon, 12 Jul 2014 15:33:23 GMT

Content-Length: 54

<CRLF>

<html><title>Hello</title>

Welcome to our site</html>

The empty line denotes the end of the response header

2.2. URL - Uniform Resource Locator

Uniform Resource Locator (URL)



- URL is a formatted string, consisting of:
- Protocol for communicating (**http**, **ftp**, **https**, ...) – HTTP in most cases
- **Host(Domain name Server = DNServer)** or IP address (**www.softuni.bg**, **gmail.com**, **127.0.0.1**, **web**)
- Port (the default port is **80**) – a number in range [0...65535]
- Path (**/forum**, **/path/index.html**)
- Query string (**?id=27&lang=en**) – не се използва за парола 😊
- Fragment (**#lectures**) – used on the client to navigate to some section – за позициониране в даден документ. Не пътува по мрежата – за user friendliness!!!

URI and URL

A Uniform Resource Identifier (URI) is a unique sequence of characters that identifies a logical or physical resource used by web technologies. URIs may be used to identify anything, including real-world objects, such as people and places, concepts, or information resources such as web pages and books. Some URIs provide a means of locating and retrieving information resources on a network (either on the Internet or on another private network, such as a computer filesystem or an Intranet); these are Uniform Resource Locators (URLs). A URL provides the location of the resource. A URI identifies the resource by name at the specified location or URL. Other URIs provide only a unique name, without a means of locating or retrieving the resource or information about it, these are Uniform Resource Names (URNs).

URL е подмножество на URI.

URN е подмножество на URI също.

Механизъм за вземане на ресурс.

URL Encoding

- URLs are encoded according RFC 1738:
 - Safe URL characters: [0-9a-zA-Z], \$, -, _, ., +, *, ', (,), ,, !
- All other characters are escaped by:

%[character hex code]

Char	URL Encoding
space	%20
щ	%D1%89
"	%22
#	%23
\$	%24
%	%25
&	%26

- Space is encoded as "+" or "%20"

Когато е в дясното от въпросчето, може да се encode-не с +

- URL-encoded string:

%D0%9D%D0%B0%D0%BA%D0%BE%D0%B2-%E7%88%B1-SoftUni

<https://www.punycoder.com/>

Punycode is a special encoding used to convert Unicode characters to ASCII, which is a smaller, restricted character set. Punycode is used to encode internationalized domain names (IDN).

Valid and Invalid URLs – Examples

- Some valid URLs:

http://www.google.bg/search?sourceid=navclient&ie=UTF-8&rlz=1T4GGLL_enBG369BG369&q=http+get+vs+post

http://bg.wikipedia.org/wiki/%D0%A1%D0%BE%D1%84%D1%82%D1%83%D0%B5%D1%80%D0%BD%D0%B0_%D0%BD%D0%BA%D0%B0%D0%BD%D0%BC%D0%BC%D0%BD%D1%8F

- Some invalid URLs:

<http://www.google.bg/search?&q=C# .NET 4.0>

<http://www.google.bg/search?&q=%D0%91%D0%BB%D0%B7%D0%AA%D0%BD%D0%BA%D0%BA%D0%BD%D0%BC%D0%BC%D0%BD%D1%8F>

написана е на български бира, а трябва да е с %-та

2.3. HTTP Request

HTTP Request Message

- Request message sent by a client consists of:
 - **HTTP request line**
 - Request method (**GET / POST / PUT / DELETE / ...**)
 - Resource URI (**URL**)
 - Protocol version
 - **HTTP request headers**
 - Additional parameters
 - **HTTP request body** – optional data, e.g. posted form fields

```
<method> <resource> HTTP/<version>
<headers>
(empty line)
<body>
```

HTTP GET Request – Example

```
GET /index.html HTTP/1.1      HTTP request line
Host: localhost              HTTP request headers
<CRLF>                      The request body is empty
```

HTTP POST Request – Example

```
POST /login.html HTTP/1.1      HTTP request line
Host: localhost              HTTP request headers
Content-Length: 59
Content-Type: application/x-www-form-urlencoded    който пътува в бодито
<CRLF>
username=testUser&password=topSecret           The request body holds the submitted form data
<CRLF>
```

2.4. HTTP Response

HTTP Response Message

- The **response message** sent by the HTTP server consists of:
 - **HTTP response status line**
 - Protocol version
 - Status code
 - Status phrase
 - **Response headers**
 - Provide meta data about the returned resource
 - **Response body**

- The content of the HTTP response (data)

```
HTTP/<version> <status code> <status text>
<headers>
(empty line)
<response body – the requested resource>
```

HTTP Response – Example

```
HTTP/1.1 200 OK                                HTTP response status line
Date: Fri, 17 Jul 2020 16:09:18 GMT+2          HTTP response headers
Server: Apache/2.2.14 (Linux)
Accept-Ranges: bytes
Content-Length: 84
Content-Type: text/html
<CRLF>
<html>
  <head><title>Test</title></head>
  <body>Test HTML page.</body>
</html>
```

HTTP response body

HTTP Response Codes

- HTTP response code classes
 - **1xx: informational** (e.g., "**100 Continue**")
 - **2xx: successful** (e.g., "**200 OK**", "**201 Created**")
 - **3xx: redirection** (e.g., "**304 Not Modified**", "**301 Moved Permanently**", "**302 Found**")
 - **4xx: client error** (e.g., "**400 Bad Request**", "**404 Not Found**", "**401 Unauthorized**", "**409 Conflict**")
 - **5xx: server error** (e.g., "**500 Internal Server Error**", "**503 Service Unavailable**")

HTTP Error Response – Example

```
HTTP/1.1 404 Not Found                                HTTP response status line
Date: Fri, 17 Nov 2020 16:09:18 GMT+2
Server: Apache/2.2.14 (Linux)                         HTTP response headers
Connection: close
Content-Type: text/html
<CRLF>
<html><head><title>404 Not Found</title></head>
<body>
  <h1>Not Found</h1>
  <p>The requested URL /img/logo.gif was not found on this server.</p>
  <hr><address>Apache/2.2.14 Server at Port
  80</address>
</body></html>
```

The HTTP response body

Browser Redirection

Content-Type and Disposition

The **Content-Type** response header the server specifies how the output should be processed

Content-Type: **text/html; charset=utf-8**

Content-Type: application/pdf

Content-Disposition: attachment; filename="Report-April-2020.pdf" This will download a PDF file named Report-April-2020.pdf

Content-Type: application/json

Content-Type: application/xml

2.5. HTTP verbs

GET, POST, PUT, PATCH, DELETE

2.6. MIME (Multi-Purpose Internet Mail Extensions) and Media Types

Multi-Purpose Internet Mail Extensions

What is MIME?

- **MIME** == Multi-Purpose Internet Mail Extensions
 - Internet standard for encoding resources
 - Originally developed for email attachments
 - Used in many Internet protocols like HTTP and SMTP
- MIME defines several concepts
 - **Content-Type**, e.g. **text/html**, **image/gif**, **application/pdf**
 - Content **charset**, e.g. **utf-8**, **ascii**, **windows-1251**
 - **Content-Disposition**, e.g. **attachment; filename=logo.jpg**
 - Multipart messages (multiple resources in a single document)

Common MIME Media Types

Content-Type:


MIME Type / Subtype	Description
application/json	JSON data
image/png	PNG image
image/gif	GIF image
text/html	HTML
text/plain	Text
text/xml	XML
video/mp4	MP4 video

application/pdf	PDF document
multipart/form-data; boundary	

2.7. HTTP Tools


HTTP Tools for Developers:

- През IntelliJ



- Browser – Chrome DevTools, Firefox DevTools, Microsoft Edge DevTools

Ако искаме да видим как ни върви сайта при бавна връзка на клиента





- Telnet
- През Ubuntu (Linux) и SSL връзка
- [Insomnia Rest](#)
- [Postman](#)
- [RESTClient](#)


2.8. Web Server

What is a Web Server?


- Computer system that processes requests via **HTTP**, the basic network protocol

Web Server Work Model





Most Popular Web Servers (W3Techs)



2.9. HTML Forms

Form.html

```
<!DOCTYPE html>
<html>
<body>

<h2>HTML Forms</h2>
```

```

<form action="http://postman-echo.com/post" method="post">
  <label for="fname">First name:</label><br>
  <input type="text" id="fname" name="fname" value="John"><br>
  <label for="lname">Last name:</label><br>
  <input type="text" id="lname" name="lname" value="Doe"><br><br>
  <input type="submit" value="Submit">
</form>

<button onclick="testMe()">CLICK ME</button>

<script>
  function testMe() {
    for (let i = 0; i < 10; i++) {
      console.log("Test " + i);
    }

    console.log("Test " + i);
  }
</script>

</body>
</html>

```

На .html файл излизат тези иконки на браузъри, и си зареждаме оттам web страницата.



HTML Forms – Action Attribute

- Defines **where to submit** the form data:

```

<form action="home.html">
  <input type="submit" value="Go to homepage"/>
</form>

```




HTML Forms – Method Attribute

- Specifies the HTTP method to use when sending form-data


Get

```
<form action="/" method="get">  
  Name: <input type="text" name="name">  
  <br>  
  <input type="submit" value="Submit">  
</form>
```



Post

```
<form action="/" method="post">  
  Name: <input type="text" name="name">  
  <br>  
  <input type="submit" value="Submit">  
</form>
```



POST http://localhost/index.html HTTP/1.1

Host: localhost

Content-Type: application/x-www-form-urlencoded

Content-Length: 10

name=Pesho

HTTP request body holds the form data

URL Encoded Form Data – Example

```
<form action="/" method="post">  
  Name: <input type="text" name="name"/> <br/>  
  Age: <input type="text" name="age"/> <br/>  
  <input type="submit" />  
</form>
```

A screenshot of a web browser window titled "index.cgi". It contains a form with two input fields. The first field is labeled "Name:" and has the value "Maria Smith". The second field is labeled "Age:" and has the value "19" with a small red checkmark next to it. Below the fields is a "Submit Query" button.



POST http://localhost/cgi-bin/index.cgi HTTP/1.1

Host: localhost

Content-Type: application/x-www-form-urlencoded

Content-Length: 23

name=Maria+Smith&age=19

File uploads are
not supported

2.10. HTTP/2

Old HTTP/1.1

What's HTTP/2

- Speedy е бащата/експерименталната версия на HTTP2
- **HTTP/2** (originally named **HTTP/2.0**) major revision of the **HTTP** network protocol used by the **World Wide Web**.
 - Supported by most of the popular web browsers (Chrome, Mozilla, Opera...)
 - **Fast & Optimized**. Meets modern web usage requirements.
 - Completely **Backwards-Compatible**
- As of Jan 2021, **50%** of all the websites support **HTTP/2** (W3Techs statistics).

What's New?


- **HTTP/2** is meant to erase the need of maintaining complex server infrastructures in order to perform well.
- **HTTP/2** communicates in binary data frames.
- **HTTP/2** introduces several **new important** elements
 - **HTTP/2 Multiplexing**
 - **HTTP/2 Header Compression**
 - **HTTP/2 Server Push**



HTTP/2 Multiplexing


- The art of handling multiple streams over a **single** TCP connection.

Multiplexing



HTTP/2 Header Compression


- HTTP/2** maintains a **HTTP Header Table** across requests.
- Optimizes communication drastically.**
- The process is essentially a **de-duplication**, rather than compression – не се изпращат части, които са redundant(излишни).



HTTP/2 Server Push – **TCP 3-way handshake**

HTTP/2 Server Push – TCP 3-way handshake – с един request ти връща много response-и за зареждане на нещата от страницата (в head-а на html-а каквото има да се зарежда примерно)

- **HTTP/2 Server Push** is the process of sending resources to clients, without them having to ask for it.



2.11. What's HTTP/3

- **HTTP/3** is a new standard in development that will affect how web browsers and servers communicate.
- Significant upgrades for user experience
- **Performance, Reliability, and Security**
- **HTTP/3** runs on **QUIC**, a new transport protocol designed for **mobile-heavy** Internet usage.

2.12. Два основни вида криптиранни алгоритми + катинарче

Transport Layer Security (TLS) the successor of the now-deprecated Secure Sockets Layer (**SSL**) is a cryptographic protocol designed to provide communications security over a computer network. The protocol is widely used in applications such as email, instant messaging, and voice over IP, but its use in securing HTTPS remains the most publicly visible.

Симетрични алгоритми за криптиране - бързи – разчитат на един и същи ключ от двете страни за осъществяване на криптираания канал – AES (Advanced Encryption Standard), 3DES, Blowfish is a symmetric-key block cipher, и много други.

Асиметрични алгоритми за криптиране -бавни

Публичен ключ на сървъра – дава се на всеки

Private ключ на сървъра – само на конкретния потребител

Ако нещо се криптира Public key, то може да се декриптира само с private ключа.

И ако нещо се криптира с Private key (моят цифров подпись), то може да се декриптира само с Public Key и всеки който иска да знае, че това съм аз.

При осъществена криптирана връзка, излиза ключето в браузъра.

SHA256 и хеширащи алгоритми за пазене на пароли....

За разлика от хеширането, което е необратим процес, то криптирането е обратим процес и може да се декриптира.

SHA256 – криптира бързо, и не е добре да криптираме с него пароли. Всяка буква се замества с друга буква. Всеки път резултата от криптирането е един и същ.

Pbkdf2PasswordEncoder – една парола се криптира по различни начини
Hash(salt+password) → salt + hash(salt + password)

BCryptPasswordEncoder


SCryptPasswordEncoder

3. Spring Boot Introduction

3.1. What is Spring Boot?

Spring Boot

- Opinionated view of building production-ready Spring applications



Creating Spring Boot Project

- Just go to <https://start.spring.io/> or open IntelliJ
- Create it via Spring initializer



Project Language

Maven Project Gradle Project Java Kotlin Groovy

Spring Boot

3.0.0 (SNAPSHOT) 3.0.0 (M3) 2.7.1 (SNAPSHOT) 2.7.0 2.6.9 (SNAPSHOT) 2.6.8

Project Metadata

Group: bg.softuni
Artifact: intro
Name: intro
Description: Demo project for Spring Boot
Package name: bg.softuni.intro
Packaging: Jar War
Java: 18 17 11 8

Dependencies

Spring Web WEB
Build web, including RESTful, applications using Spring MVC. Uses Apache Tomcat as the default embedded container.

Spring Boot DevTools DEVELOPER TOOLS
Provides fast application restarts, LiveReload, and configurations for enhanced development experience.

Spring Data JPA SQL
Persist data in SQL stores with Java Persistence API using Spring Data and Hibernate.

ADD DEPENDENCIES... CTRL + B

GENERATE CTRL + ⌘ | **EXPLORE** CTRL + SPACE | **SHARE...**

Jar = uberjar = stand alone = може да се стартира от java-.. = в него има сървър
War = webarchive

Spring Dev Tools

- Spring Web
- Thymeleaf
- Spring Boot DevTools **X**
- Spring Data JPA
- MySQL Driver
- Validation

- Additional set of **tools** that can make the application development **faster** and more **enjoyable**
- In **Maven**:

Pom.xml

```
<dependency>
  <groupId>org.springframework.boot</groupId>
  <artifactId>spring-boot-devtools</artifactId>
  <scope>runtime</scope>
</dependency>
```

- In **Gradle**:


```
dependencies {
  compileOnly("org.springframework.boot:spring-boot-devtools")
}
```

Example of Gradle

<https://docs.gradle.org/current/userguide/userguide.html>

В терминала пишем:

./gradlew dependencies > deps.txt - да видим всичките dependences



```
ives - Configuration for Spring Boot archive artifacts. (n)
encies
```

```
lasspath - Compile classpath for source set 'main'.
.springframework.boot:spring-boot-starter-data-jpa -> 2.7.0
- org.springframework.boot:spring-boot-starter-aop:2.7.0
  +--- org.springframework.boot:spring-boot-starter:2.7.0
  |   +--- org.springframework.boot:spring-boot:2.7.0
  |   |   +--- org.springframework:spring-core:5.3.20
  |   |   |   \--- org.springframework:spring-jcl:5.3.20
  |   |   \--- org.springframework:spring-context:5.3.20
```

build.gradle file

```
plugins {
    id 'org.springframework.boot' version '2.7.0'
    id 'io.spring.dependency-management' version '1.0.11.RELEASE'
    id 'java'
}

group = 'bg.softuni'
version = '0.0.1-SNAPSHOT'
sourceCompatibility = '17'

repositories {
    mavenCentral()
}

dependencies {
    implementation 'org.springframework.security:spring-security-crypto:5.5.2'
    implementation 'org.springframework.boot:spring-boot-starter-validation'
    implementation 'org.modelmapper:modelmapper:3.0.0'

    implementation 'org.springframework.boot:spring-boot-starter-data-jpa'
    implementation 'org.springframework.boot:spring-boot-starter-web'
    developmentOnly 'org.springframework.boot:spring-boot-devtools'
    testImplementation 'org.springframework.boot:spring-boot-starter-test'
    runtimeOnly 'mysql:mysql-connector-java'

}

tasks.named('test') {
```

```
    useJUnitPlatform()
}
```

Example of Maven

```
<?xml version="1.0" encoding="UTF-8"?>
<project xmlns="http://maven.apache.org/POM/4.0.0" xmlns:xsi="http://www.w3.org/2001/XMLSchema-
instance"
          xsi:schemaLocation="http://maven.apache.org/POM/4.0.0
https://maven.apache.org/xsd/maven-4.0.0.xsd">
    <modelVersion>4.0.0</modelVersion>
    <parent>
        <groupId>org.springframework.boot</groupId>
        <artifactId>spring-boot-starter-parent</artifactId>
        <version>2.7.0</version>
        <relativePath/> <!-- Lookup parent from repository --&gt;
    &lt;/parent&gt;
    &lt;groupId&gt;bg.softuni&lt;/groupId&gt;
    &lt;artifactId&gt;pathfinder&lt;/artifactId&gt;
    &lt;version&gt;0.0.1-SNAPSHOT&lt;/version&gt;
    &lt;name&gt;pathfinder&lt;/name&gt;
    &lt;description&gt;pathfinder&lt;/description&gt;
    &lt;properties&gt;
        &lt;java.version&gt;17&lt;/java.version&gt;
    &lt;/properties&gt;
    &lt;dependencies&gt;
        &lt;dependency&gt;
            &lt;groupId&gt;org.springframework.boot&lt;/groupId&gt;
            &lt;artifactId&gt;spring-boot-starter-data-jpa&lt;/artifactId&gt;
        &lt;/dependency&gt;
        &lt;dependency&gt;
            &lt;groupId&gt;org.springframework.boot&lt;/groupId&gt;
            &lt;artifactId&gt;spring-boot-starter-thymeleaf&lt;/artifactId&gt;
        &lt;/dependency&gt;
        &lt;dependency&gt;
            &lt;groupId&gt;org.springframework.boot&lt;/groupId&gt;
            &lt;artifactId&gt;spring-boot-starter-web&lt;/artifactId&gt;
        &lt;/dependency&gt;

        &lt;dependency&gt;
            &lt;groupId&gt;mysql&lt;/groupId&gt;
            &lt;artifactId&gt;mysql-connector-java&lt;/artifactId&gt;
            &lt;scope&gt;runtime&lt;/scope&gt;
        &lt;/dependency&gt;
        &lt;dependency&gt;
            &lt;groupId&gt;org.springframework.boot&lt;/groupId&gt;
            &lt;artifactId&gt;spring-boot-starter-test&lt;/artifactId&gt;
            &lt;scope&gt;test&lt;/scope&gt;
        &lt;/dependency&gt;

        &lt;!-- https://mvnrepository.com/artifact/org.springframework.boot/spring-boot-devtools --&gt;
        &lt;dependency&gt;
            &lt;groupId&gt;org.springframework.boot&lt;/groupId&gt;
            &lt;artifactId&gt;spring-boot-devtools&lt;/artifactId&gt;
            &lt;version&gt;2.7.0&lt;/version&gt;
        &lt;/dependency&gt;
        &lt;dependency&gt;</pre>
```

```

<groupId>org.springframework.boot</groupId>
<artifactId>spring-boot-starter-validation</artifactId>
</dependency>


</dependencies>

<build>
  <plugins>
    <plugin>
      <groupId>org.springframework.boot</groupId>
      <artifactId>spring-boot-maven-plugin</artifactId>
    </plugin>
  </plugins>
</build>

</project>

```


Spring Resources



Spring Boot Main Components

- Some main components:
 - **Spring Boot Starters** - combine a group of common or related dependencies into single dependency
 - **Spring Boot Auto-Configuration** - reduce the Spring Configuration
 - **Spring Boot Actuator** – provides EndPoints and Metrics
 - **Spring Data** – unify and ease the access to different kinds of database systems

Spring Boot Starters



Spring Boot CLI (Command Line Interface)

- **Command Line Interface** - Spring Boot software to run and test Spring Boot applications
Още един начин да се стартира проект.

```
C:\WINDOWS\system32\cmd.exe
C:\Users\teodo\Desktop\spring-1.5.2.RELEASE\bin>spring init -d=web, data-jpa
Using service at https://start.spring.io
Project extracted to 'C:\Users\teodo\Desktop\spring-1.5.2.RELEASE\bin\data-jpa'
C:\Users\teodo\Desktop\spring-1.5.2.RELEASE\bin>
```

A screenshot of a Windows Command Prompt window titled "cmd.exe". The command entered is `spring init -d=web, data-jpa`. The output shows the project is being initialized with "web" and "data-jpa" dependencies, and the project is extracted to the specified directory. The prompt then returns to the command line.

Spring Boot Actuator

- Expose different types of information about the **running application**

build.gradle

```
dependencies {
    compileOnly("org.springframework.boot:spring-boot-starter-actuator")
}
```

localhost:8080/health

```
{"status":"UP","diskSpace": {"status":"UP","total":160571584512,"free":31d":10485760}, "db": {"status":"UP","database":"MySQL","hello":1}}
```

A screenshot of a browser window showing the response from the `/health` endpoint of a Spring Boot Actuator application. The response is a JSON object containing the status of the application and its components. It includes disk space information and a database connection to MySQL.


Inversion of Control

- Spring provides **Inversion of Control** and **Dependency Injection**

<p style="text-align: center;">UserServiceImpl.java</p> <pre>//Traditional Way public class UserServiceImpl implements UserService { private UserRepository userRepository = new UserRepositoryImpl(); }</pre>	<p style="text-align: center;">UserServiceImpl.java</p> <pre>//Dependency Injection @Service public class UserServiceImpl implements UserService { @Autowired private UserRepository userRepository; }</pre>
---	---

@Autowired – an annotation responsible for injecting a bean by its type

В новите версии на Spring, не е необходимо да слагаме @Autowired
Spring IoC (Inversion of Control principle)



Beans

- Object that is **instantiated**, **assembled**, and otherwise managed by a **Spring IoC** container

Т.е. не е необходимо да използваме `new` оператора.

```
public class Dog implements Animal {

    private String name;

    public Dog() {}

    //GETTERS AND SETTERS
}
```

Bean Declaration

```
@SpringBootApplication
public class MainApplication {
```

```

...
@Bean
public Animal getDog(){
    return new Dog();
}
}

```

Get Bean from Application Context

```

@SpringBootApplication
public class MainApplication {
    public static void main(String[] args) {
        ApplicationContext context = SpringApplication.run(MainApplication.class, args);
        Animal dog = context.getBean(Dog.class); //глобалния контекст
        System.out.println("DOG: " + dog.getClass().getSimpleName());
    }
}

```

DOG: Dog

Beans Scopes in Spring Framework

Ако инжектираме едно и също куче на 2 места в проекта, то какво ще стане? – Отговорът е, че зависи от scope на bean-a.

- There are part of **Beans scopes**:
 - **Singleton** – една и съща инстанция на кученцето в целия проект
 - **Prototype** – еквивалента на new оператора – всеки път нова инстанция – използват се рядко
- In web-aware application, 4 more scopes:
- **Request** - в рамките на http request
 - **Session** – да пазим неща специфични за даден user
 - **Application**
 - **websocket**

Singleton Scope

- Container creates a **single instance** of that bean, and all requests for that bean name will return the **same object**, which is cached
- This is **default** scope

```

@Bean
@Scope("singleton")<-Can be omitted (може да се пропусне)
public Student student(){
    return new Student();
}

```

Prototype Scope

- Will return a different instance every time it is requested from the container


```

@Bean
@Scope("prototype")
public Student student() {
    return new Student();
}

```

Bean Scope

- The default one is **Singleton**. It is easy to change to **Prototype**
- State-less / state-full



Demo with Beans

IntelliJ средата ни дава препратка към двата bean-а

Вариант 1 при повече bean-ове – с обхождане на всеки от bean-овете

```

public class Cat implements Animal{
    @Override
    public void makeNoise() {
        System.out.println("Meoue mew");
    }
}

```

```

@Configuration
public class ZooConfig {
    @Bean
    public Animal cat() {
        return new Cat();
    }

    @Bean
    public Animal dog() {
        return new Dog();
    }
}

```

```

22     public ZooService(List<Animal> animals) {
23         this.animals = animals;
24     }
25
26     public void doWork() {
27         animals.forEach(Animal::makeNoise);
28     }
29
30     public ZooService(List<Animal> animals) {
31         Choose Bean
32         m cat() (ZooConfig.java) intro.main
33         m dog() (ZooConfig.java) intro.main
34     }
35
36     public void doWork() {
37         animals.forEach(Animal::makeNoise);
38     }
39
40     @Service
41     public class ZooService {
42         private final List<Animal> animals;
43         public ZooService(List<Animal> animals) {
44             this.animals = animals;
45         }
46
47         public void doWork() {
48             animals.forEach(Animal::makeNoise);
49         }
50     }

```

Вариант 2 при повече bean-ове – с използване на анотацията @Primary

```

public class Cat implements Animal{
    @Override
    public void makeNoise() {
        System.out.println("Meoue mew");
    }
}

```

```

@Configuration
public class ZooConfig {
    @Bean
    public Animal cat() {
        return new Cat();
    }

    @Primary
    @Bean
    public Animal dog() {
        return new Dog();
    }
}

```

```

@Service
public class ZooService {

    private final Animal animal;

    @Autowired
    public ZooService(Animal animal) {
        this.animal = animal;
    }

    public void doWork() {
        animal.makeNoise();
    }
}

```

Вариант 3 при повече bean-ове – с използване на qualifier / BeanNameAware Interface

```

public class Dog implements Animal{
    private final boolean superDog;

    public Dog(){
        this(false);
    }

    public Dog(boolean superDog){
        this.superDog = superDog;
    }

    @Override
    public void makeNoise() {
        if (superDog) {
            System.out.println("Super Bark super bark");
        } else {
            System.out.println("Bark bark");
        }
    }
}

```

```

@Configuration
public class ZooConfig {
    @Bean("cat")
    public Animal cat() {
        return new Cat();
    }

    @Bean("normalDog")
    public Animal dog() {
        return new Dog();
    }

    @Bean("mySuperDog")
    public Animal superDog() {
        //todo: add superpower to this dog
        return new Dog(true);
    }
}

```

```

@Service
public class ZooService {
    private final Animal animal;

    @Autowired
    public ZooService(@Qualifier("mySuperDog") Animal animal) {
        this.animal = animal;
    }

    public void doWork() {
        animal.makeNoise();
    }
}

```

ИЛИ така

```


@Service
public class ZooService {
    private final Animal animal1;
    private final Animal animal2;

    @Autowired
    public ZooService(@Qualifier("mySuperDog") Animal animal1,
                      @Qualifier("normalDog") Animal animal2) {
        this.animal1 = animal1;
        this.animal2 = animal2;
    }

    public void doWork() {
        animal1.makeNoise();
        animal2.makeNoise();
    }
}

```

Bean Lifecycle



Bean Lifecycle Demo

По default, инициализацията на всички beans е eager. Щом сме създали анотацията и тя се ползва, то няма логика да го правим lazy (но има опция и за lazy).

PostConstruct Annotation

- Spring calls methods annotated with **@PostConstruct** only once, just after the initialization of bean

```
import javax.annotation.PostConstruct;

public class Dog implements Animal{
    private final boolean superDog;

    public Dog(){
        this(false);
    }

    public Dog(boolean superDog){
        this.superDog = superDog;
    }

    @Override
    public void makeNoise() {
        if (superDog) {
            System.out.println("Super Bark super bark");
        } else {
            System.out.println("Bark bark");
        }
    }

    @PostConstruct
    public void afterInit() {
        System.out.println("Dog is ready to bite");
    }
}
```

По-добре да ползваме **@PostConstruct** анотацията (която е извън Spring – идва от package javax.annotation; вместо BeanNameAware, BeanFactoryAware или InitializingBean (които са изцяло Spring).

Най-често използваме по този начин – или през **@Component** или през **@Configuration**

```
@Component
public class AppInit {
    private final UserService userService;
    private final RimService rimService;

    public AppInit(UserService userService, RimService rimService) {
        this.userService = userService;
        this.rimService = rimService;
    }

    @PostConstruct
    public void beginInit(){
        userService.init();
        rimService.init();
```

```
    }
}
```

BeanNameAware Interface

- BeanNameAware makes the object aware of the bean name defined in the container

```
import javax.annotation.PostConstruct;

public class Dog implements Animal, BeanNameAware {
    private final boolean superDog;

    public Dog() {
        this(false);
    }

    public Dog(boolean superDog) {
        this.superDog = superDog;
    }

    @Override
    public void makeNoise() {
        if (superDog) {
            System.out.println("Super Bark super bark");
        } else {
            System.out.println("Bark bark");
        }
    }

    @PostConstruct
    public void afterInit() {
        System.out.println("Dog is ready to bite");
    }
}

@Override
public void setBeanName(String name) {
    System.out.println("The name of this Dog bean is: " + name);
}

@Configuration
public class ZooConfig {
    @Bean(name = "cat")
    public Animal cat() {
        return new Cat();
    }

    @Bean("normalDog")
    public Animal dog() {
        return new Dog();
    }

    @Bean(name = "mySuperDog")
    public Animal superDog() {
```

```

    //todo: add superpower to this dog
    return new Dog(true);
}
}

```

BeanFactoryAware Interface

- BeanFactoryAware is used to **inject** the **BeanFactory** object
- With the **setBeanFactory()** method, we assign the BeanFactory reference from the IoC container to the beanFactory property

```

public class MyBeanFactory implements BeanFactoryAware {
    private BeanFactory beanFactory;

    @Override
    public void setBeanFactory(BeanFactory beanFactory) throws BeansException {
        this.beanFactory = beanFactory;
    }

    public void getMyBeanName() {
        MyBeanName myBeanName = beanFactory.getBean(MyBeanName.class);
        System.out.println(beanFactory.isSingleton("myCustomBeanName"));
    }
}

public class MyBeanName implements BeanNameAware {
    @Override
    public void setBeanName(String beanName) {
        System.out.println(beanName);
    }
}
@Configuration
public class Config {
    @Bean (name = "myCustomBeanName")
    public MyBeanName getMyBeanName() {
        return new MyBeanName();
    }
}

```

InitializingBean Interface

- For bean implemented **InitializingBean**, it will run **afterPropertiesSet()** after all bean properties have been set

```

@Component
public class InitializingBeanExampleBean implements InitializingBean {
    private static final Logger LOG
        = Logger.getLogger(InitializingBeanExampleBean.class);

    @Autowired
    private Environment environment;

    @Override
    public void afterPropertiesSet() throws Exception {
        LOG.info(Arrays.asList(environment.getDefaultProfiles()));
    }
}

```

PreDestroy Annotation

- A method annotated with `@PreDestroy` runs only once, just before Spring removes our bean from the application context

```
import javax.annotation.PreDestroy;

@Component
public class UserRepository {
    private DbConnection dbConnection;

    @PreDestroy
    public void preDestroy() {
        dbConnection.close();
    }
}
```

По-добре да ползваме `@PreDestroy` анотацията (която е извън Spring) вместо `DisposableBean` (които са части Spring).

DisposableBean Interface

- For bean implemented `DisposableBean`, it will run `destroy()` after Spring container releases the bean

```
public class Dog implements Animal, BeanNameAware, DisposableBean {
    private final boolean superDog;

    public Dog() {
        this(false);
    }

    public Dog(boolean superDog) {
        this.superDog = superDog;
    }

    @Override
    public void makeNoise() {
        if (superDog) {
            System.out.println("Super Bark super bark");
        } else {
            System.out.println("Bark bark");
        }
    }

    @PostConstruct
    public void afterInit() {
        System.out.println("Dog is ready to bite");
    }

    @Override
    public void setBeanName(String name) {
        System.out.println("The name of this Dog bean is: " + name);
    }
}
```

```

@Override
public void destroy() throws Exception {
    System.out.println("Dog is about to die... Bye!");
}
}

```

Common Application Properties

- Various properties can be specified inside your **application.yaml** file
- Property contributions can come from **additional jar files**
- You can define your **own properties**
- [Link to documentation](#)

<https://docs.spring.io/spring-boot/docs/current/reference/html/application-properties.html>

Application Properties Example

```

application.properties
spring.datasource.driverClassName=com.mysql.cj.jdbc.Driver
spring.datasource.url=jdbc:mysql://localhost:3306/thymeleaf_adv_lab_exam_db?createDatabaseIfNotExist=true
spring.datasource.username=root
spring.datasource.password=12345
spring.jpa.properties.hibernate.dialect = org.hibernate.dialect.MySQL8Dialect
spring.jpa.properties.hibernate.format_sql = TRUE
spring.jpa.hibernate.ddl-auto = update
spring.jpa.open-in-view=false
logging.level.org = WARN
logging.level.blog = WARN
logging.level.org.hibernate.SQL = DEBUG
logging.level.org.hibernate.type.descriptor = TRACE
server.port=8000

```

Изпълняване на SQL заявки при стартиране (execute SQL / run SQL automatically)

```

#spring.datasource.initialization-mode = always
#spring.sql.init.mode = always

#spring.datasource.data=classpath:insert-data.sql
#spring.sql.init.data-locations=classpath:insert-data.sql

```

```
spring.mvc.hiddenmethod.filter.enabled=true //ще ни позволи да използваме delete
```

Application Yaml Example 1

По-лесно се чете .yaml формата

```

Application.yaml
spring:
  datasource:
    driverClassName: com.mysql.cj.jdbc.Driver
    url: url:
jdbc:mysql://localhost:3306/intro?allowPublicKeyRetrieval=true&useSSL=false&createDatabaseIfNotExist=true&serverTimezone=UTC&useUnicode=true&characterEncoding=UTF-8

```

```

username: root
password:
jpa:
# Choose either MySQL8 or MySQL5 below

# for MySQL 5
# database-platform: org.hibernate.dialect.MySQL5InnoDBialect

database-platform: org.hibernate.dialect.MySQL8Dialect
hibernate:
  ddl-auto: create-drop
  open-in-view: false
  properties:
    hibernate:
      format_sql: true

```

Application Yaml Example 2

```

application.yml

spring:
  datasource:
    driverClassName: com.mysql.cj.jdbc.Driver
    url:
      "jdbc:mysql://localhost:3306/pathfinder?allowPublicKeyRetrieval=true&useSSL=false&createDatabaseIfNotExist=true&serverTimezone=UTC&useUnicode=true&characterEncoding=UTF-8"
    username: root
    password:
  servlet:
    multipart:
      max-file-size: 1MB
      max-request-size: 5MB
  mvc:
    hiddenmethod:
      filter:
        enabled: true
    sql:          //execute SQL / run SQL from the resources folder - always
    init:
      mode: always never      embedded/only for in-memory database/
jpa:
# Choose either MySQL 8 or MySQL 5 below
# For MySQL 8
  database-platform: org.hibernate.dialect.MySQL8Dialect
#For MySQL 5
#database-platform: org.hibernate.dialect.MySQL5InnoDBialect
  hibernate:
    ddl-auto: create-drop
    open-in-view: false
    properties:
      hibernate:
        format_sql: true
    defer-datasource-initialization: true      //първо се създават таблиците с връзките, и чак
след това се изпълнява SQL скрипта за наливане на данните
    show_sql: true

```

```

#Cloudinary Properties
#cloudinary:
  #api-key:
  #api-secret:
  #cloud-name:

logging:
  level:
    org:
      hibernate:
        sql: debug
      type:
        descriptor:
          sql: trace

logging:
  level:
    org.springframework: DEBUG  #debugging SPRING while Logging more info
    org.hibernate.SQL: DEBUG
    org.hibernate.type.descriptor.sql.BasicBinder: TRACE

```

Convert YAML and Properties file

Има plugin, който може да обръща от .properties към .yml и обратно

DDL-AUTO

So the list of possible options are,

validate: validate the schema, makes no changes to the database.

update: update the schema.


create: creates the schema, destroying previous data.

create-drop: drop the schema when the SessionFactory is closed explicitly, typically when the application is stopped.

none: does nothing with the schema, makes no changes to the database

3.2. Spring Data

Overall Architecture



Entities

- Entity is a lightweight persistence domain object

Добре е всички DTO (data transfer object), които записват в базата данни или четат от базата данни, то в името им да се съдържа Entity.

```
@Entity  
 @Table(name = "cats")  
 public class CatEntity {  
  
     @Id  
     @GeneratedValue(strategy = GenerationType.IDENTITY)  
     private long id;  
  
     private String name;  
     //GETTERS AND SETTERS  
 }
```

Repositories

- Persistence layer that works with entities

```
@Repository  
 public interface CatRepository extends JpaRepository<CatEntity, Long> {  
 }
```

Services

- Business Layer - All the business logic is here.

```
@Service  
 public class CatServiceImpl implements CatService {  
     private final CatRepository catRepository;  
  
     @Autowired //не е задължително, даже е излишно  
     public CatServiceImpl(CatRepository catRepository) {  
         this.catRepository = catRepository;
```

```

    }

    @Override
    public void buyCat(CatModel catModel) { //TODO Implement the method }
}

}


```

4. MVC Spring Introduction

4.1. What is Spring MVC?

What is Spring MVC?

- **Model-view-controller (MVC)** framework is designed around a **DispatcherServlet** that dispatches requests to handlers



Най-често handler е контролер.

В нашите приложения приемаме, че handler = controller

What is servlet? – A front-end controller


A servlet is a Java programming language class that is used to extend the capabilities of servers that host applications accessed by means of a request-response programming model. Although servlets can respond to any type of request, they are commonly used to extend the applications hosted by web servers. For such applications, Java Servlet technology defines HTTP-specific servlet classes.

The `javax.servlet` and `javax.servlet.http` packages provide interfaces and classes for writing servlets. All servlets must implement the `Servlet` interface, which defines life-cycle methods. When implementing a generic service, you can use or extend the `GenericServlet` class provided with the Java Servlet API. The `HttpServlet` class provides methods, such as `doGet` and `doPost`, for handling HTTP-specific services.

This chapter focuses on writing servlets that generate responses to HTTP requests.

Tomcat Demo

- 1) Unzip Apache Tomcat
- 2) Create new project



3) What we generated

```

import java.io.*;
import javax.servlet.http.*;
import javax.servlet.annotation.*;

@WebServlet(name = "helloServlet", value = "/hello-servlet")
public class HelloServlet extends HttpServlet {
    private String message;

    public void init() {
        message = "Hello World!";
    }


    public void doGet(HttpServletRequest request, HttpServletResponse response) throws
IOException {
        response.setContentType("text/html");
        response.setStatus(HttpStatus.NotFound)

        // Hello
        PrintWriter out = response.getWriter();
        out.println("<html><body>");
        out.println("<h1>" + message + "</h1>");
        out.println("</body></html>");
    }


    public void destroy() {
}
}

```

MVC – Control Flow



<https://www.upgrad.com/blog/spring-mvc-flow-diagram/#:~:text=Spring%20MVC%20is%20a%20Java,Dependency%2C%20Inversion%20of%20Control.>



4.2. Spring Controllers

Spring Controllers

- Defined with the **@Controller** annotation

```
@Controller
public class HelloController {

    @GetMapping("/hello")
    public String hello(){
        return "helloworld"; //името на template файла
        return "helloworld.html"; //името на template-a
    }
}
```

- Controllers can contain multiple actions on different routes

Request Mapping

- Annotated with **@RequestMapping(...)**

```
@RequestMapping("/home")
public String home(Model model) {
    model.addAttribute("message", "Welcome!");
    return "home-view";
}
```

- Or

```
@RequestMapping("/home")
public ModelAndView home(ModelAndView mav) {
    mav.addObject("message", "Welcome!");
    mav.setViewName("home-view");
    return mav;
}
```

- Problem when using **@RequestMapping** is that it accepts all types of request methods (get, post, put, delete, head, patch)
- Example - execute on **GET** requests only. We can also use .POST, .PUT, и т.н.


```
@RequestMapping(value="/home", method=RequestMethod.GET)
public String home() {
    return "home-view";
}
```

Get Mapping

- Easier way to create route for a GET request
- This is alias (псевдоним/същото) for **RequestMapping** with method GET

```
@GetMapping("/home")
public String home() {
    return "home-view"; //името на template файла
    return "home-view.html"; //како работим с thymeleaf, то .html не е необходимо
}
```

Actions – Get Requests



Controllers - `@ResponseBody` – за REST request

```
@Controller
public class DogController {

    @GetMapping("/dog")
    @ResponseBody //сериализирай кучето като json формат
    public Dog getDogHomePage(){
        Dog dog = dogService.getBestDog();
        return dog;
    }
}
```

Post Mapping

- Similar to the `GetMapping` there is also an alias for `RequestMapping` with method POST
`@PostMapping("/register")`
`public String register(UserDTO userDto) {`
...
`}`
- Similar annotations exist for all other types of request methods

Actions – Post Requests – анотираме целият контролер

```
@Controller
@RequestMapping("/cat")
public class CatController {

    @GetMapping("")
    public String addCat(){
        return "new-cat.html";
    }
}
```

Вземане на данни от html формата

```
@Controller
@RequestMapping("/cat")
public class CatController {

    @PostMapping("") //post заявка с /cat
    public String addCatConfirm(@RequestParam String catName, @RequestParam int catAge){
        System.out.println(String.format(
            "Cat Name: %s, Cat Age: %d", catName, catAge));
        return "redirect:/cat"; //редиректваме към този URL, не към html страница
    }
}
```

Cat Name: Tom, Cat Age: 20

Dto вземане на данни от html формата към UserDto

Трябва да съвпадат имената Dto класа полетата и на атрибут name от html кода.

Пример 1

Вариант 1 за първоначални стойности

```
@GetMapping("/users/register")
public String register(Model model){
    if (!model.containsAttribute("userRegistrationDto")) {
        model.addAttribute("userRegistrationDto", new UserRegistrationDto());
    }

    return "register";
}
```

Вариант 2 за първоначални стойности

```
@ModelAttribute
public UserRegistrationDto initRegistrationDto(){
    return new UserRegistrationDto();
}

@GetMapping("/users/register")
public String register(Model model){
//    if (!model.containsAttribute("userRegistrationDto")) {
//        model.addAttribute("userRegistrationDto", new UserRegistrationDto());
//    }
```

```
        return "register";
    }
```

register.html файла

```
<form
    th:action="@{/users/register}"
    th:method="POST"
    th:object="${userRegistrationDto}"
    class="text-center text-light">

    <div class="form-group row">
        <label for="username" class="col-sm-2 col-form-label">Username</label>
        <div class="col-sm-10">
            <input type="text"
                class="form-control"
                th:field="*{username}"
                th:errorclass="is-invalid"
                id="username"
                aria-describedby="usernameHelpInline" placeholder="Username">
            <small id="usernameHelpInline"
                class="invalid-feedback bg-danger text-light rounded">
                Username length must be between 5 and 20 characters.
            </small>
        </div>
    </div>
</div>
```

```

<form
    th:action="@{/home}"
    th:method="POST"
    th:object="${fireModel}"
    class="row mb-2">
    <div class="col-md-6">
        <div class="card flex-md-row bg-blur mb-4 box-shadow h-md-250">
            <div class="card-body d-flex flex-column align-items-start">
                <strong class="d-inline-block mb-2 text-primary">Attacker</strong>
                <span style="color: yellow" th:text="${@loggedUser.getFullName()}"></span>

                <h3 class="mb-0 text-white">
                    Select the attacker
                </h3>
                <div class="mb-1 text-white">Select one of the ships that are owned by the current user</div>
                <select
                    th:field="*{attackerShipId}" or howd
                    class="form-select mt-5 aria-label="Default select example">
                    <option value="" selected>Select one of the ships that are owned by the current user</option>
                    <option
                        th:each="ship : ${ownShips}"
                        th:value="${ship.id}"
                        th:text="|${ship.name} -- ${ship.health} -- ${ship.power}|"
                        th:selected="*{attackerShipId} == ${ship.id}">
                </option>
            </select>
        </div>
    </div>

```

Пример 2 – Plain taking info from the form

```

public class UserDto {
    private String fname;
    private String lname;

    @Override
    public String toString() {
        return "UserDto{" +
            "fname='" + fname + '\'' +
            ", lname='" + lname + '\'' +
            '}';
    }
}

@Controller
@RequestMapping("/user")
public class UserController {
    @PostMapping
    public String createUser(UserDto userDto){
        System.out.println("Creating new user ..." + userDto);
        return "usercreated.html";
    }
}

```

```

newuser.html
<body>
  <form th:action="@{/user}" method="post">
    <label for="fname">First name:</label><br>
    <input for="text" id="fname" name="fname" value="John"><br>

    <label for="lname">Last name:</label><br>
    <input for="text" id="lname" name="lname" value="Doe"><br><br>
    <input type="submit" value="Submit">
  </form>
</body>

```

Creating new user ...UserDto{fname='John', lname='Doe'}

Passing Attributes to View

Passing a String model to the view

```

@GetMapping("/")
public String welcome(Model model) {
  model.addAttribute("name", "Pesho");
  return "index.html";
}

```

- The **Model** object will be automatically passed to the view as context variables
- Attributes can be accessed from Thymeleaf
- **Model** са данните, които наливаме на View-то (финалната html страница)

Passing a String ModelMap object to the view

```

@GetMapping("/")
public String welcome(ModelMap modelMap) {
  modelMap.addAttribute("name", "Pesho");
  modelMap.put("name", "Pesho");
  return "index";
}

@GetMapping("/hello")
public String hello(ModelMap modelMap){
  modelMap.addAttribute("num", 3);
  modelMap.put("num", 3); //втори вариант за добавяне на атрибут
  return "helloworld.html"; //името на template-a
}

```

- The **ModelMap** object will be automatically passed to the view as context variables
- Attributes can be accessed from Thymeleaf

Passing a ModelAndView object to the view

```

@GetMapping("/")
public ModelAndView welcome(ModelAndView modelAndView) {
  modelAndView.addObject("name", "Pesho");
}

```

```

modelAndView.setViewName("index")
return modelAndView;
}

```

- The **ModelAndView** object will be automatically passed to the view as context variables
- Attributes can be accessed from Thymeleaf
- **ModelAndView** е комбиниран вариант, реално View-то е финалната html страница

Models and Views

```

@Controller
public class DogController {

    @GetMapping("/dog")
    public ModelAndView getDogHomePage(ModelAndView modelAndView){
        modelAndView.setViewName("dog-page.html");
        return modelAndView;
    }
}

```



Request Parameters – query, form data and parts in multipart requests

In Spring MVC, "request parameters" map to **query parameters**, **form data**, and **parts in multipart requests**. This is because the Servlet API combines query parameters and form data into a single map called "parameters", and that includes automatic parsing of the request body.

In Spring WebFlux, "request parameters" map to query parameters only. To work with all 3, query, form data, and multipart data, you can use data binding to a command object annotated with `ModelAttribute`.

Request Parameters – query case example

- Getting a parameter from the query string

В нашето URL ще излиза така: localhost:8080/details?id=5

Или в Thymeleaf го пишем по този начин

```
<a class="ml-3 text-danger" th:href="@{/products/buy(id = *{id})}">Buy</a>
```

```

@GetMapping("/details")
public String details(@RequestParam("id") Long id) {
...
}

```

Пример 2:


```

@GetMapping("/hello")
public String hello(Model model, @RequestParam("num") Integer num){
    model.addAttribute("num", num);
}

```

```
    return "helloworld.html"; //името на template-a  
}
```

Пишем в браузъра <http://localhost:8080/hello?num=5>



Hello World

The number you passed to me is
5 ✓

- `@RequestParam` can also be used to get POST parameters (по-добре да използваме тук Dto)

```
@PostMapping("/register")  
public String register(@RequestParam("name") String name) {  
...  
}
```

Request Parameters – query case with Default Value

- Getting a parameter from the query string when the query parameter is missing

```
@GetMapping("/comment")  
public String comment(@RequestParam(name="author", defaultValue = "Anonymous") String author) {  
...  
}
```

Making parameter optional – може да го има/може да го няма

```
@GetMapping("/search")  
public String search(@RequestParam(name="sort", required = false) String sort) {  
...  
}
```

Path Variable

В Thymeleaf го пишем така:

```
<a class="ml-3 text-danger" th:href="@{/products/buy/{id}(id = *{id})}">Buy</a>
```

- Getting a parameter from the `path` part of the URL – в пътя на URL-то

```
@GetMapping("/details/{id}")  
public String details(@PathVariable("id") Long id) {  
...  
}
```

```

@GetMapping("/offers/{id}/details")
public String showOfferDetail(@PathVariable String id){      //Може и без "id"
    return "details";
}

@GetMapping("/hello/{id}/test")
public String hello(Model model, @PathVariable("id") Integer pathId){
    model.addAttribute("num", pathId);
    return "hello.html";
}

```

Form Objects

- Spring will automatically try to fill objects with a form data – това го показвахме вече с Dto по-горе.
- ```

@PostMapping("/register")
public String register(UserDTO userDto) {
...
}

• The input field names must be the same as the object field names – Трябва да съвпадат имената Dto класа
полетата и на атрибут name от html кода.

```

## Redirecting

- Redirecting after POST request
- ```

@PostMapping("/register")
public String register(UserDTO userDto) {
...
    return "redirect:/login"; //редиректваме към този URL, не към html страница
}

```

Redirecting with Query Parameters

- Redirecting with query string parameters
- ```

@PostMapping("/register")
public String register(UserDTO userDto,
 RedirectAttributes redirectAttributes) {

 redirectAttributes.addAttribute("errorId", 3);
 return "redirect:/login"; //?errorId = 3 //редиректваме към този URL, не към html
страница
}

```

## Redirecting with Attributes

- Keeping objects after redirect
- ```

@PostMapping("/register")
public String register(@ModelAttribute UserDTO userDto,

```

```

        RedirectAttributes redirectAttributes) {
...
    redirectAttributes.addFlashAttribute("userDto", userDto);
    return "redirect:/register"; //редиректваме към този URL, не към html страница
}

```

4.3. Inversion of Control


Field Injection

- Easy to write
- Easy to add new dependencies
- It **hides** potential architectural **problems!**

```

@Autowired
private ServiceA serviceA
@Autowired
private ServiceB serviceB
@Autowired
private ServiceC serviceC

```



Constructor Injection

- Time Consuming
- Harder to add dependencies
- It **shows** potential architectural problems!



```

@Autowired
public ControllerA(ServiceA serviceA, ServiceB serviceB, ServiceC serviceC) {
    this.serviceA = serviceA;
    this.serviceB = serviceB;
    this.serviceC = serviceC;
}

```

Setter Injection

- Create setters for dependencies
- Can be combined easily with constructor injection
- Flexibility in dependency resolution or object reconfiguration!




```

@Service
public class HomeController(){
    ...
    @Autowired
    public void setServiceA(ServiceA serviceA) {
        this.serviceA = serviceA;
    }
}


```

4.4. Layers - The Correct Project Structure

- We are used to **splitting** our code based **on its functionality**:
- It gets **hard to navigate** in bigger applications



- **Splitting** the project into **different modules**
 - Each module corresponding to the application layer
 - Makes it easier to navigate



4.5. Thin Controllers

- Controllers should follow well known principles such as **DRY** (Do not Repeat Yourself) and **KISS** (keep it simple, stupid)
- Should delegate functionality to the **service** layer
- The **service layer** consists of application logic, e.g. services, executors, strategies, mappers, DTOs, entities, etc.

5. State Management

5.1. HTTP Cookies

What Are Cookies?

- A **small file of plain text** with no executable code
 - Sent by the server to the client's browser
 - Stored by the browser on the client's device (computer, tablet, etc.)
 - Hold small piece of data for a particular client and a website

What Are Cookies Used for?

- **Session management**
 - Logins, shopping carts, game scores, or anything else the server should remember
- **Personalization**
 - User preferences, themes, and other custom settings
- **Tracking**
 - Recording and analyzing user behavior
- Breakfast
 - But that's not what we are currently talking about 😊

В incognito не се пази cookie-то.

Session Management

- The HTTP object is **stateless** – всеки следващ request не пази нищо за предишните requests
 - It **doesn't store** information about the requests



Stateless HTTP – the Problem

- The **server does not know** if two requests come from the same client
- **State management** problems
 - Navigation through pages requires **authentication each time**
 - Information about the pages is lost **between the requests**
 - **Harder personalization** of page functionality

Stateless HTTP – the Cookie Solution

- A reliable **mechanism** for websites to **remember stateful information**
 - to know whether the user is **logged in or not**
 - to know **which account** the user is logged in with
 - to record the user's **browsing activity**
 - to remember pieces of information **previously entered** into form fields (usernames, passwords(паролата няма да я запишем в cookie 😊), etc.)

How Are Cookies Used?

Пазим езика на сайта в cookie-то например:

- The request holds the specific web site cookie within the **Cookie** header

GET /index HTTP/1.1

Cookie: lang=en

- The response holds the cookies to be saved within the **Set-Cookie** header

HTTP/1.1 200 OK

Set-Cookie: lang=en

Server-Client Cookies Exchange



Cookie Structure

- The cookie consists of **Name**, **Value** and **Attributes** (optional)
- The attributes are **key-value pairs** with additional information
- Attributes are not included in the requests
- Attributes are used by the client to control the cookies

Name=Value

Attributes

Set-Cookie: SSID=Ap4P...GTEq; Domain=foo.com; Path=/;
Expires=Wed, 13 Jan 2021 22:23:01 GMT; Secure; HttpOnly

Датата и часа когато cookie-то ще бъде изтрито автоматично.

Scope

- Defined by the attributes **Domain** and **Path**
- **Domain** – defines the website that the cookie belongs to
- **Path** – Indicates a URL path that must exist in the requested resource before sending the **Cookie** header

Set-Cookie: SSID=Ap4P...GTEq; Domain=foo.com; Path=/;
Expires=Wed, 13 Jan 2021 22:23:01 GMT; Secure; HttpOnly

By Default – домейна идва оттам откъдето идват cookie-тата. Например docs.google.com

Ако пътят ти е главен (Path=/) – то на всички пътища (от URL-и) ще се предава cookie-то, което е сетнато за главния път.

Ако зададения път е Path=foo.com/test, а ние като заредим foo.com/Pesho, то cookie-то няма да се предаде на/за този път.

Lifetime

- Defined by the attributes **Expires** and **Max-Age**(секундите, които може да живее това cookie)
- **Expires** – defines the date that the browser should delete the cookie
- **By default the cookies are deleted after the end of the session**
- **Max-Age** – interval of seconds before the cookie is deleted

Set-Cookie: SSID=Ap4P...GTEq; Domain=foo.com; Path=/;
Expires=Wed, 13 Jan 2021 22:23:01 GMT; Secure; HttpOnly

Security

- Security flags do not have associated values
- **Security** - tells the browser to use cookies only via **secure/encrypted** connections (с катинарче или https)
- **HttpOnly** – defines that the cookie cannot be accessed via client-side scripting languages – недостъпно за всякакъв вид script-ови езици!

Set-Cookie: SSID=Ap4P...GTEq; Domain=foo.com; Path=/;
Expires=Wed, 13 Jan 2021 22:23:01 GMT; Secure; HttpOnly

httpOnly – ако се помъчим да го прочетем с JS например, то няма да ни разреши. Това е много важно – защото например при CrossSide от другия IP адрес може да изпълнят JS команда, и да ни вземат cookie-тата 😊

What is in the Cookie?

- The cookie file contains a table with **key-value** pairs

Plug-in to view cookies

Name:	ELOQUA
Content:	GUID=50B3A712CDAA4A208FE95CE1F2BA7063
Domain:	.oracle.com
Path:	/
Send for:	Any kind of connection
Accessible to script:	Yes
Created:	Monday, August 15, 2016 at 11:38:50 PM
Expires:	Wednesday, August 15, 2018 at 11:38:51 PM
Remove	

Examine Your Cookies 1

- Most cookies are stored in a RDBMS, usually **SQLite**
- Download DB Browser for SQLite (the **SQLite browser**) from [here - https://sqlitebrowser.org](https://sqlitebrowser.org)
- Location of Mozilla cookies

C:\Users\{username}\AppData\Roaming\Mozilla\Firefox\Profiles\{name}.default\cookies.sqlite

- Location of Chrome cookies

C:\Users\{username}\AppData\Local\Google\Chrome\User Data\Default\Cookies

- Open the file with the **SQLite browser**

The screenshot shows the SQLite browser window with the 'Open Database' tab selected. Below the tabs, it says 'Database Structure' and 'Browse Data'. Under 'Table:', 'moz_cookies' is selected. The table has columns: baseDomain, originAttributes, name, value, host, path, expiry, lastAccessed, and creationTime.

baseDomain	originAttributes	name	value	host	path	expiry	lastAccessed	creationTime
1 softuni.bg		_ga	GA1.2.14749...	.softuni.bg	/	1548331112	1485259173536000	1472458246652000
2 softuni.bg		cb-enabled	enabled	platform.soft...	/	1512124532	1485213524987000	1480588532898000
3 softuni.bg		cookies-notifi...	ok	judge.softuni...	/	1787818276	1485259172447000	1472458276862000
4 softuni.bg		cb-enabled	accepted	softuni.bg	/	1503994248	1485214353890000	1472458248921000

- Browse the cookies table

Name	Host	Expiration date	Created on
baseDomain	originAttributes		
Filter	Filter	Filter	New Record Delete R
1 softuni.bg			
2 softuni.bg			
3 softuni.bg			
4 softuni.bg			
Value	Paths	Last accessed on	

Examine Your Cookies 2

Using the EditThisCookie

<https://chrome.google.com/webstore/detail/editthiscookie/fngmhnnplhplaeedifhcceomclgfbg?hl=en>

The screenshot shows the 'EditThisCookie' extension interface in a browser window. The title bar says 'Kypc Spring Fundamentals - Document'. The toolbar includes icons for trash, refresh, add, forward, back, search, and a wrench. A red checkmark is placed over the wrench icon.

The main area displays a list of cookies for 'http://localhost:8080/session':

- localhost | Idea-924ed50e
- localhost | Idea-eee8a77a
- localhost | io
- localhost | JSESSIONID

For the 'JSESSIONID' cookie, the details are:

- Value:** 4A8A684F579F51771F5F7DE1C2E82CC4
- Domain:** localhost
- Path:** /
- Expiration:** Sun Jun 04 2023 15:25:03 GMT+0300 (Eastern European Summer Time)
- SameSite:** (dropdown menu)
- HostOnly:**
- Session:**
- Secure:**
- HttpOnly:**

A large green checkmark is overlaid on the bottom left of the interface.

Control Your Cookies – Firefox Browser

The screenshot shows the 'Privacy & Security' section of the Firefox preferences. It includes options for tracking protection, sending a 'Do Not Track' signal, and managing cookies and site data. A red box highlights the 'Cookies and Site Data' section, which shows stored data usage and provides options to clear or manage data.

Custom
Choose which trackers and scripts to block.

Send websites a "Do Not Track" signal that you don't want to be tracked [Learn more](#)

Always
 Only when LibreWolf is set to block known trackers

Cookies and Site Data

Your stored cookies, site data, and cache are currently using 46.0 KB of disk space. [Learn more](#)

Delete cookies and site data when LibreWolf is closed [Manage Exceptions...](#)

Logins and Passwords

Ask to save logins and passwords for websites [Exceptions...](#)
 Autofill logins and passwords [Saved Logins...](#)
 Suggest and generate strong passwords
 Show alerts about passwords for breached websites [Learn more](#)
 Use a Primary Password [Learn more](#) [Change Primary Password...](#)
Formerly known as Master Password

History

LibreWolf will [Use custom settings for history](#)

Always use private browsing mode [Clear History...](#)

The screenshot shows the 'Cookies' dialog box. A search bar at the top contains 'softuni'. Below it, a table lists cookies from various sites, with one row for 'softuni.bg' selected. A blue box highlights the 'Remove Selected' button at the bottom left of the dialog.

Site	Cookie Name
judge.softuni.bg	cookies-notification
judge.softuni.bg	cookies-notification
platform.softuni.bg	cb-enabled
platform.softuni.bg	idsrv.session
platform.softuni.bg	idsrv
softuni.bg	_ym_uid


Name: _ym_uid
Content: 1501864502607682706
Domain: .softuni.bg
Path: /
Send For: Any type of connection
Expires: 25 July 2019, 19:35:01

[Remove Selected](#) [Remove All Shown](#) [Close](#)


Browse cookies from a selected website

Delete a particular cookie or all cookies

Control Your Cookies – Chrome Browser



Или оттуда:



Cookies in use

Allowed Blocked

The following cookies were set when you viewed this page

github.com

- ▶ Cookies
- ▶ Local storage
- ▶ Service Workers
- ▶ Session storage
- ▶ Shared Workers

Name	no cookie selected
Content	no cookie selected
Domain	no cookie selected
Path	no cookie selected

Block **Remove** **Done**

Third Party Cookies

- Cookies stored by an **external party** (different domain)
- Mainly used for advertising and tracking (събират privacy инфо за мен което не е ок) across the web
- By the end of 2023, Google will stop the use of these advertising and tracking third-party cookies **ONLY!**

5.2. HTTP Sessions


What Are Sessions?

- A way to store information about a user to be used across **multiple pages**




Session Management


- The exchange mechanism be used between the user and the web application



- The exchange mechanism be used between the user and the web application



- The exchange mechanism be used between the user and the web application (when server is restarted)




Relation with Cookies

На back-end server-a има SessionStore и оттам се изпраща към клиента персонализирана информация/персонализирана web страница за всеки логнат потребител.



Session Structure



5.3. Summary

Cookies are **client based** stored information
 They are created by web applications
 Browser sends them back to the application

Sessions are **server based** information
 They are used across multiple pages
 Stores important info about the client

5.4. Demo cookies

screenshot

Добавено lang при заявка GET

The screenshot shows a browser developer tools window with the Network tab selected. In the Cookies section, there is a list of cookies under the 'Allowed' tab. One cookie named 'lang' is highlighted. Below it, the cookie details are shown: Name is 'lang', Content is 'de', Domain is 'localhost', Path is '/', and Send for is 'Same-site connections only'. At the bottom of this panel are 'Block' and 'Remove' buttons, and a 'Done' button. To the right of the cookies list, the Response Headers section is visible, showing the 'Set-Cookie: lang=de' header.

cookies.html

```
<!doctype html>
<html lang="en"
      xmlns:th="http://www.thymeleaf.org" >
<head>
    <meta charset="UTF-8">
    <meta name="viewport"
          content="width=device-width, user-scalable=no, initial-scale=1.0, maximum-scale=1.0,
minimum-scale=1.0">
    <meta http-equiv="X-UA-Compatible" content="ie=edge">
    <title>Document</title>
</head>
<body>

    Current language is <span th:text="${lang}"></span>
    <form th:action="@{/cookies}" th:method="post">
        Choose language:
        <select id="language" name="language">
            <option value="en" th:selected="${lang} == 'en'">English</option>
            <option value="de" th:selected="${lang} == 'de'">Deutsch</option>
            <option value="bg" th:selected="${lang} == 'bg'">Български</option>
        </select>
        <input type="submit" value="Submit">
    </form>

</body>
</html>
```

CookieController

```
import org.springframework.stereotype.Controller;
import org.springframework.ui.Model;
import org.springframework.web.bind.annotation.CookieValue;
```

```

import org.springframework.web.bind.annotation.GetMapping;
import org.springframework.web.bind.annotation.PostMapping;
import org.springframework.web.bind.annotation.RequestParam;

import javax.servlet.http.Cookie;
import javax.servlet.http.HttpServletResponse;

@Controller
public class CookieController {
    private static final String LANG_COOKIE_NAME = "lang";

    @GetMapping("/cookies")
    public String cookies(Model model,
        @CookieValue(
            name = LANG_COOKIE_NAME,
            defaultValue = "en"
        ) String language) { //We take the cookie value with
        @CookieValue(), and we set the default value to "en"
        model.addAttribute("lang", language);

        return "cookies.html";
    }

    @PostMapping("/cookies")
    public String cookies(
        HttpServletResponse response,
        @RequestParam("language") String language
    ) {


        Cookie cookie = new Cookie(LANG_COOKIE_NAME, language); //how we set a cookie - new
        Cookie(name, value)
        response.addCookie(cookie);
    response.setStatus(HttpStatus.NotFound)
        return "redirect:/cookies"; //редиректваме към този URL, не към html страница
    }
}

```

5.4. Demo HTTP session

screenshot

Добавено JSessionID при заявкa GET



session.html

```

<!doctype html>
<html lang="en"
      xmlns:th="http://www.thymeleaf.org">
<head>
    <meta charset="UTF-8">
    <meta name="viewport"
          content="width=device-width, user-scalable=no, initial-scale=1.0, maximum-scale=1.0,
minimum-scale=1.0">
    <meta http-equiv="X-UA-Compatible" content="ie=edge">
    <title>Document</title>
</head>
<body>

    Current language is <span th:text="${language}"></span>
    <form th:action="@{/session}" th:method="post">
        Choose language:
        <select id="language" name="language">
            <option value="en" th:selected="${language} == 'en'">English</option>
            <option value="de" th:selected="${language} == 'de'">Deutsch</option>
            <option value="bg" th:selected="${language} == 'bg'">Български</option>
        </select>
        <input type="submit" value="Submit">
    </form>

</body>
</html>
    
```

SessionController

```

import javax.servlet.http.HttpSession;
    
```

```

@Controller
public class SessionController {
    private static final String LANG_SESSION_ATTRIBUTE = "lang";
    private static final String DEFAULT_LANG = "en";

    @GetMapping("/session")
    public String session(HttpSession session, Model model) {
        //сесия кода
        var sessionLang = session.getAttribute(LANG_SESSION_ATTRIBUTE);
        sessionLang = sessionLang != null ? sessionLang : DEFAULT_LANG;

        model.addAttribute("language", sessionLang); //към HTML кода

        return "session.html";
    }

    @PostMapping("/session")
    public String session(
        HttpSession session,
        @RequestParam("language") String language
    ) {
        //сесия кода - атрибута LANG_SESSION_ATTRIBUTE реално не е видим в браузъра, но в режим
        debug в IntelliJ можем да го видим, че се празаписва реално
        session.setAttribute(LANG_SESSION_ATTRIBUTE, language);

        return "redirect:/session"; //редиректваме към този URL, не към html страница
    }
}

```

6. Spring Essentials

6.0. Kotlin example

KotlinApplication.kt

```

import org.springframework.boot.autoconfigure.SpringBootApplication
import org.springframework.boot.runApplication

@SpringBootApplication
class KotlinApplication

fun main(args: Array<String>) {
    runApplication<KotlinApplication>(*args)
}

```

hello.html

```

<!doctype html>
<html lang="en">
<head>
    <meta charset="UTF-8">
    <meta name="viewport"
          content="width=device-width, user-scalable=no, initial-scale=1.0, maximum-scale=1.0,
          minimum-scale=1.0">
    <meta http-equiv="X-UA-Compatible" content="ie=edge">
    <title>Document</title>

```

```

</head>
<body>
    <h1 th:text="${greeting}"></h1>

</body>
</html>

```

GreetingService.kt

```

interface GreetingService {
    fun greeting(person: String = "Anonymous") : String //функция greeting, която връща String.
Parameter person, Който е от тип String и има дефалтна стойност
}

```

GreetingServiceImpl.kt

```

import org.springframework.stereotype.Service

@Service
class GreetingServiceImpl : GreetingService { //GreetingServiceImpl имплементира
GreetingService
    override fun greeting(person: String): String {
        return "Hello, $person"
    }
}

```

GreeterController.kt

```

import bg.softuni.kotlin.service.GreetingService
import org.springframework.stereotype.Controller
import org.springframework.ui.Model
import org.springframework.web.bind.annotation.GetMapping
import org.springframework.web.bind.annotation.RequestParam

@Controller
class GreeterController(val greetingService: GreetingService) { //конструктор в Kotlin

    @GetMapping("/greet")
    fun greet(@RequestParam(name = "person", defaultValue = "Anonymous") person: String, model : Model)
        : String {

        model.addAttribute("greeting", greetingService.greeting(person = person)); //възможност
за задаване на име на параметър

        return "hello.html";
    }
}

```

6.0.0. Thymeleaf without Spring

Test.java

```

import org.thymeleaf.TemplateEngine;
import org.thymeleaf.context.Context;
import org.thymeleaf.templateresolver.ClassLoaderTemplateResolver;
import java.io.StringWriter;

```

```

public class Test {
    public static void main(String[] args) {
        TemplateEngine engine = createEngine();
        Context ctx = new Context();
        ctx.setVariable("name", "Pesho");
        StringWriter sw = new StringWriter();

        engine.process("test.html", ctx, sw);

        System.out.println(sw.toString());
    }

    private static TemplateEngine createEngine(){
        TemplateEngine engine = new TemplateEngine();
        engine.setTemplateResolver(new ClassLoaderTemplateResolver()); //test.html ще бъде в
пътя на класа когато се стартира
        return engine;
    }
}

```

test.html

```

<!doctype html>
<html lang="en">
<head>
    <meta charset="UTF-8">
    <meta name="viewport"
          content="width=device-width, user-scalable=no, initial-scale=1.0, maximum-scale=1.0,
minimum-scale=1.0">
    <meta http-equiv="X-UA-Compatible" content="ie=edge">
    <title>Document</title>
</head>
<body>
    Hello, <span th:text="${name}">someone</span>
</body>
</html>

```

console result:

```

<!doctype html>
<html lang="en">
<head>
    <meta charset="UTF-8">
    <meta name="viewport"
          content="width=device-width, user-scalable=no, initial-scale=1.0, maximum-scale=1.0, minimum-scale=1.0">
    <meta http-equiv="X-UA-Compatible" content="ie=edge">
    <title>Document</title>
</head>
<body>
    Hello, <span>Pesho</span>
</body>
</html>

```

6.1. Thymeleaf – the template engine

What is Thymeleaf?

- Thymeleaf is a modern **server-side** Java **template engine** used in Spring
- It allows us to
 - Use variables in our views
 - Execute operations on our variables
 - Iterate over collections
 - Make our views dynamical

<https://www.thymeleaf.org/doc/tutorials/3.0/usingthymeleaf.html>

How to Use Thymeleaf?

- Use Spring Initializer to import Thymeleaf, or use a dependency

In Maven:

```
<dependency>
    <groupId>org.springframework.boot</groupId>
    <artifactId>spring-boot-starter-thymeleaf</artifactId>
</dependency>
```

In Gradle:

```
dependencies {
    implementation 'org.springframework.boot:spring-boot-starter-thymeleaf'
}

dependencies {
    compile("org.springframework.boot:spring-boot-starter-thymeleaf")
}
```

- Define the Thymeleaf library in your html

```
<html lang="en" xmlns:th="http://www.thymeleaf.org">
```

Thymeleaf without th:

Реално браузъра си чете HTML кода чист, и за визуална стилизация разкрасителите могат да си работят с th без реално th: да работи.

Escaping in html – като String.format подобно

```
<h3 class="mySticky bg-gray text-light rounded" th:text="|Time to prepare all orders(in min): ${totalTime}|"></h3>

<div class="card-text"><span th:text="|Seller - First and Last name: *{seller.getFirstName()} ${seller.getLastName()}|">• Seller - First and Last name</span></div>
```

```
<h5 class="card-title" th:text="${year} + ' ' + ${model.getName()} + ' ' +  
${model.brand.getName()}">
```

Може да вземаме по field на DTO-то или по метод на DTO-то.

```
  

```

Thymeleaf Tags and Attributes

- All Thymeleaf tags and attributes begin with **th:** by default
- Example of Thymeleaf attribute

```
<p th:text="${user.name}">Some text</p>
```

- Example of Thymeleaf tag(element processor) – един блок изчезва **като оставя съдържанието си**

```
<th:block>
```

```
...
```

```
</th:block>
```

- **th:block** is an attribute container that **disappears** in the HTML

Thymeleaf Standard Expressions

Variable Expressions

```
${...}
```

Link (URL) Expressions

```
@{...}
```

Selection Expressions

```
*{...}
```

Accessing Bean

```
 ${@...}
```

```
<span th:text="${@loggedUser.getFullName()}"></span>
```

Fragment Expressions

~{...} с тилда ако е по-навътре в пътя/йерархията на дървото на папките/директориите

```
<header th:replace="~{fragments/commons::headernav}"></header>
```

Web context object - неща, които винаги ги има в контекста (19 Appendix B: Expression Utility Objects)

```
 ${#session.getAttribute('foo')}
```

```
 ${#session.user.name}
```

```

${#request.getAttribute('foo')}

${#dates.}

${#calendars.}

<small th:if="#{#fields.hasErrors('fullname')}"> Some custom errors </small>

```

Thymeleaf Variable Expressions

- Variable Expressions are executed on the context variables
\${...}

▪ Examples

```

${#session.user.name}
${title}
${game.id}

```

If else & switch

If - else

```

<div th:if="${student.passExam}">Show results</div>  ако е true ќе се покаже само
<div th:unless="${student.passExam}">Not pass</div>  ако е false ќе се покаже само

```

```

<strong th:if="${badCredentials}">  ако съществува badCredentials със стойност ще се покаже само
<strong th:if="${badCredentials} != null">  ако съществува badCredentials със стойност ще се покаже само
class="rounded pl-3 text-danger">Enter valid username and password</strong>

```

Switch

```

<div th:switch="${user.role}">
  <p th:case="'admin'">User is an administrator</p>
  <p th:case="#{roles.manager}">User is a manager</p>
</div>

```

Default expressions (Elvis operator)

- A special kind of conditional value **without a 'then' part**. It is equivalent to the **Elvis** operator present in some languages

```

<p>Age:<br/>
  <span th:text="*{age} ?: 'missing age'"> </span>
</p>

```

- Equivalent to:

```

<p>Age:<br/>
  <span th:text="*{age != null} ? *{age} : 'missing age'"></span>
</p>

```

Thymeleaf Link Expressions

- Link Expressions are used to build URLs
@{...}

- Example

```
<a th:href="@{/register}">Register</a>
```

- You can also pass query string parameters

```
<a th:href="@{/details(id=${game.id})}">Details</a>      Result -> /details?id=3
```

- Create dynamic URLs

```
<a th:href="@{/games/{id}/edit(id=${game.id})}">Edit</a>      Result -> /games/3/edit
```

```
<a th:href="@{/orders/ready/{id}(id = *{id})}">Ready</a>
```

Iteration

When we want to *iterate* over collection

Ако има 50 студента, то ще се генерираат 50 реда като всеки ред ще съдържа name, score и age

```
<tr th:each="s : ${students}">
    <td th:text="${s.name}"></td>
    <td th:text="${s.score}"></td>
    <td th:text="${s.age}"></td>
</tr>
```

We can attach the *object* to the parent element

Използваме * като по този начин достъпваме property-то на обекта – за по-съкратен запис се използва реално

```
<tr th:each="s : ${students}" th:object="${s}">
    <td th:text="*{name}"></td>
    <td th:text="*{score}"></td>
    <td th:text="*{age}"></td>
</tr>
```

Пример с dropdown menu:

```
<div class="col-sm-10">
    <select id="category" name="category" class="custom-select"
        th:field="*{category}"
        th:errorclass="is-invalid"          aria-describedby="categoryHelpInline">
        <option value="" selected>Category</option>
        <option value="">Coffee</option>
        <option value="">Cake</option>
        <option value="">Drink</option>
        <option value="">Other</option>
```

typecasting - можем да го направим по следния начин – за dropdown меню:

```
<select id="category" name="category" class="custom-select"
        th:field="*{category}"
        th:errorclass="is-invalid">
```

```

        aria-describedby="categoryHelpInline">
    <option value="" selected>Category</option>
Започваме от root папката
    <option th:each = "c : ${T(com.example.coffeeshop.model.enums.CategoryNameEnum).values()}">
        th:value="${c}" th:text="${c}"></option>
    </select>

```

Кастваме пътят до Java класа, който разглеждаме, вземаме масив от стойности, и задаваме th:value и th:text
 value атрибута заминава към сървъра (== name)
 text атрибута визуализира на клиента

Още един пример за dropdown

```

<div class="form-group col-md-6 mb-3">
    <label class="text-center text-white font-weight-bold" for="transmission">Transmission</label>
    <select id="transmission" name="transmission" th:errorclass="is-invalid" class="form-control">
        <option value="">- Select transmission type -</option>
        <option th:each="e : ${T(bg.softuni.mobilele.model.enums.TransmissionEnum).values()}">
            th:text="${e}"
            th:value="${e}"
            th:selected="${e} == *{transmission}">
        >
            Transmission type
        </option>
    </select>
    <p class="invalid-feedback errors alert alert-danger">
        Transmission type is required.
    </p>
</div>

```

Nested dropdown

```


<form th:action="@{/offers/add}" th:method="POST" th:object="${addOfferModel}" class="main-form mx-auto col-md-8 d-flex flex-column justify-content-center">
    <div class="row">
        <div class="form-group col-md-6 mb-3">
            <label class="text-center text-white font-weight-bold" for="modelId">Model</label>
            <select id="modelId" name="modelId" th:errorclass="is-invalid" class="form-control">
                <option value="">- Select a model -</option>
                <optgroup th:each="brand : ${brands}" th:label="${brand.name}">
                    <option th:each="model : ${brand.models}" th:text="${model.name}">
                </option>
            </select>
        </div>
    </div>

```

```

        th:value="${model.id}"
        th:selected="*{modelId} == ${model.id}">
    </option>
</optgroup>
</select>
<p class="invalid-feedback errors alert alert-danger">
    Vechicle model is required.
</p>
</div>

```



Appending and prepending

- **th:attrappend** and **th:attrprepend** attributes, which append (suffix) or prepend (prefix) the result of their evaluation to the existing attribute values

Добавяне на допълнително свойство/стил на даден съществуващ атрибут.

```
<input type="button" value="Play" class="btn" th:attrappend="class='${' ' + cssStyle}' />
```

- **th:classappend**

Добавяне на допълнително свойство/стил на съществуващ атрибут class (тук изрично става въпрос само за атрибута class).

```
<li th:classappend="${module == 'home' ? 'active' : ''}">
```

Forms in Thymeleaf

- In Thymeleaf you can create almost normal HTML forms

```
<form th:action="@{/users}" th:method="post">
    <input type="number" name="id"/>
    <input type="text" name="name"/>
    <button type="submit"/>
</form>
```

- You can have a controller that will accept an object of given type

```
@PostMapping("/user")
public ModelAndView register(User user) { ... }
```

Fragments in Thymeleaf

Create Fragment with `th:fragment`

- Often we want to include in our templates **fragments** from other **templates**
 - Common uses for this are footers, headers, menus
 - Define the fragments available for inclusion, which we can do by using the **th:fragment** attribute
 - After than we can easily include in our home page using one of the **th:include** or **th:replace** attributes

Правим си navbar.html с менюто в случая, и във всяка от другите template pages го извикваме така:

index.html

```
<div th:replace="fragments/navbar.html">Navbar</div>
```

navbar.html

```
<!doctype html>
<html lang="en" xmlns:th="http://www.thymeleaf.org">
<head>
    <meta charset="UTF-8">
    <meta name="viewport"
        content="width=device-width, user-scalable=no, initial-scale=1.0, maximum-scale=1.0,
        minimum-scale=1.0">
    <meta http-equiv="X-UA-Compatible" content="ie=edge">
    <title>Document</title>
</head>
<body>
<div>
    <nav class="navbar navbar-expand-lg bg-dark navbar-dark fixed-top">
        <a class="navbar-brand" href="/"></a>
        <button class="navbar-toggler" type="button" data-toggle="collapse" data-target="#navbarSupportedContent"
            aria-controls="navbarSupportedContent" aria-expanded="false" aria-label="Toggle navigation">
            <span class="navbar-toggler-icon"></span>
        </button>

        <div class="collapse navbar-collapse" id="navbarSupportedContent">
            <ul class="navbar-nav mr-auto col-12 justify-content-between">
                <li class="nav-item">
                    >
                    <a class="nav-link" href="/brands/all">All Brands</a>
                </li>
                <li class="nav-item">
                    <a class="nav-link" href="/offers/add">Add Offer</a>
                </li>
                <li class="nav-item">
                    <a class="nav-link" href="/offers/all">All Offers</a>
                </li>
                <li class="nav-item dropdown">
                    <a class="nav-link dropdown-toggle" href="/" id="navbarDropdown" role="button"
                        data-toggle="dropdown" aria-haspopup="true" aria-expanded="false">
                        Admin
                    </a>
                    <div class="dropdown-menu" aria-labelledby="navbarDropdown">
                        <a class="dropdown-item" href="/">Action</a>
                        <a class="dropdown-item" href="/">Another action</a>
                    </div>
                </li>
            </ul>
        </div>
    </nav>
</div>
</body>
</html>
```

```

        <div class="dropdown-divider"></div>
        <a class="dropdown-item" href="/">Something else here</a>
    </div>
</li>
<li class="nav-item" th:if="${@currentUser.isLoggedIn()}">
    <div class="form-inline my-2 my-lg-0 border px-3">
        <div class="logged-user"
            text="Welcome, Gosho"></div>
        <a class="nav-link" th:href="@{/users/logout}">Logout</a>
    </div>
</li>

<li class="nav-item" th:if="${@currentUser.isAnonymous()}">
    <a class="nav-link" th:href="@{/users/register}">Register</a>
</li>
<li class="nav-item" th:if="${@currentUser.isAnonymous()}">
    <a class="nav-link" th:href="@{/users/login}">Login</a>
</li>

</ul>
</div>
</nav>
</div>
</body>
</html>

```

- Create class with fragments

```

<html xmlns="http://www.w3.org/1999/xhtml"
      xmlns:th="http://www.thymeleaf.org">
<body>
<div th:fragment="copy">
    &copy; Spring Team 2021
</div>
</body>
</html>

```

- Easily include in our home page using one of the **th:include** or **th:replace** attributes

```

<body>
...
<footer th:include="footer::copy"></footer>
//OR
<footer th:replace="footer::copy"></footer>
...
</body>

```

- Difference between include and replace

```

<footer th:include="footer :: copy"></footer>
<footer th:replace="footer :: copy"></footer>

```

The result is

```

<footer>
    &copy; Spring Team 2021
</footer>

```

```
<div>
    &copy; Spring Team 2021
</div>
```

Create Fragment with `th:fragment - extended`

```
index.html
<!DOCTYPE html>
<html lang="en" xmlns:th="http://www.thymeleaf.org">
<head th:replace="fragments/commons::head"></head>

<body class="bg-secondary">
    <header th:replace="fragments/commons::nav"></header>

    <main role="main" class="bg-secondary"></main>

    <footer th:replace="fragments/commons::footer"></footer>
</body>
</html>
```

commons.html

```
<!doctype html>
<html lang="en" xmlns:th="http://www.thymeleaf.org">
<head th:fragment="head">
    <meta charset="UTF-8"/>
    <meta name="viewport" content="width=device-width, initial-scale=1.0"/>
    <title>Coffee Shop Application</title>
    <link rel="stylesheet" href="/css/reset-css.css"/>
    <link rel="stylesheet" href="/css/bootstrap.min.css"/>
    <link rel="stylesheet" href="/css/style.css"/>
</head>
<body>

<header th:fragment="nav">
    <nav class="navbar navbar-expand-md navbar-dark fixed-top bg-info rounded">
        <div class="collapse navbar-collapse" id="navbarsExampleDefault">
            <ul class="navbar-nav mr-auto">
                <li class="nav-item active">
                    <a class="nav-link" href="/">Home</a>
                </li>
                <li class="nav-item">
                    <a class="nav-link" href="/users/login">Login</a>
                </li>
                <li class="nav-item">
                    <a class="nav-link" href="/users/register">Register</a>
                </li>
                <li class="nav-item">
                    <a class="nav-link" href="/orders/add">Add Order</a>
                </li>
                <li class="nav-item">
                    <a class="nav-link" href="/users/logout">Logout</a>
                </li>
            </ul>
        </div>
    </nav>
</header>
```

```

        
    </div>
</nav>
</header>

<footer th:fragment="footer" class="container">
    <p>&copy;SoftUni Spring Team 2021. All rights reserved.</p>
</footer>

</body>
</html>

```

Create Fragment without `th:fragment` – не е добра практика да се прави

`footer.html`

```

<th:block>
    <footer> Spring Team 2020 </footer>
</th:block>

```

- Use Fragment

`index.html`

```

...
<th:block th:include="~/fragments/footer.html"> </th:block>
...

```

6.2. Additional Spring Functionalities

`@ModelAttribute`

- When the annotation is used at the **method level**, it indicates **the purpose of that method**
 - to add one or more model attributes
- In the example, a method adds an attribute named **message** to all models defined in the controller class

method level

Пример 1:

```

@ModelAttribute
public void addAttributes(Model model) {
    model.addAttribute("message", "Welcome to SoftUni!");
}

```

Пример 2:

```

// The name of the model attribute to bind to.
// The default model attribute name is inferred from the declared attribute type
// (i.e. the method parameter type or method return type), based on the non-qualified class
name:
// e.g. "orderAddress" for class "mypackage.OrderAddress",
// or "orderAddressList" for "List<mypackage.OrderAddress>".

```

```

@ModelAttribute() //тук името на атрибута идва автоматично от името на класа
public OrderAddBindingModelDTO orderAddBindingModelDTO(){
    return new OrderAddBindingModelDTO();
}

@PostMapping("/add")
public String addConfirm(@Valid OrderAddBindingModelDTO orderAddBindingModelDTO, BindingResult
bindingResult,
                        RedirectAttributes redirectAttributes) {

    if (bindingResult.hasErrors()) {
        redirectAttributes.addFlashAttribute("orderAddBindingModelDTO",
                orderAddBindingModelDTO);

        redirectAttributes.addFlashAttribute("org.springframework.validation.BindingResult.orderAddBindi
ngModelDTO", bindingResult);

        return "redirect:add";
    }

    //add to the DB
    return "redirect:/";
}

```

```
<form th:action="@{/orders/add}" th:method="POST" th:object="orderAddBindingModelDTO"
```

Пример 3:

```

@ModelAttribute("userModel") //изпълнява се в рамките на текущия контролер само!!!
public void initUserModel(Model model){
    model.addAttribute("userModel", new UserRegisterDto());
}

@GetMapping("/register")
public String register() {
    // когато зареждаме за първи път страницата, то автоматично ще влезе към модела атрибут
    userModel == празен new UserRegisterDto()
    return "auth-register.html";
}

```

method argument

- When used as a **method argument**, it **indicates the argument** should be retrieved from the model
- When **not present**, it should be **first instantiated** and then added to the model.
- Once **present in the model**, the arguments **fields should be populated** from all request parameters that have matching names.
- Example of using **@ModelAttribute as a method argument**

```

@RequestMapping(value = "/cars/add",
    method = RequestMethod.POST)
public String submit(@ModelAttribute("car") Car car) {
// Some code ...

```

```

        return "carView.html";
    }

алтернатива на modelAttribute
@GetMapping("/offers/add")
public String addOffer(Model model){
    if (!model.containsAttribute("addOfferModel")) {
        model.addAttribute("addOfferModel", new AddOfferDTO());
    }
    return "offer-add";
}

```

@CrossOrigin
 ▪ **@CrossOrigin**
 ▪ marks the annotated method or type as permitting cross origin requests

```

@CrossOrigin(origins = "http://example.com")
@RequestMapping("/hello")
public String hello() {
    return "Hello World!";
}

```

Same Origin Policy – само JS заявки от същия сайт на банката могат да изпращат заявки към сървъра на банката. Ако е позволен CrossOrigin, и сме цъкнали на фалшив сайт в нов tab/page примерно на нашия браузър, то фалшивия сайт има достъп до нашите cookie-та, и може да изпрати легитимна заявка, с която да ни вземе парите.

CORS – разрешение от сървъра да се извикват някакви JS кодове

При 3ply заявки, винаги се пускат 2 http заявки – един път request method е OPTIONS като предварително разрешение, и втора заявка вече реалната заявка.

Access-Control-Allow-Origin: *
 Access-Control-Allow-Origin: името на сайта / IP адреса, който да има достъп

```

import org.springframework.stereotype.Controller
import org.springframework.ui.Model
import org.springframework.web.bind.annotation.CrossOrigin
import org.springframework.web.bind.annotation.PostMapping
import org.springframework.web.bind.annotation.RequestParam

@Controller
class BankController {

//    @CrossOrigin(origins = arrayOf("http://example.com"))
//    @CrossOrigin("*") //отвсякъде да има достъп
    @PostMapping("/transfer")
    fun transferMoney(@RequestParam("from") from : String,
                      @RequestParam("to") to : String,
                      model: Model
    )
}

```

```

) : String {
    model.addAttribute("from", from);
    model.addAttribute("to", to);
    return "transfer.html"
}
}

<!doctype html>
<html lang="en">
<head>
    <meta charset="UTF-8">
    <meta name="viewport"
        content="width=device-width, user-scalable=no, initial-scale=1.0, maximum-scale=1.0,
minimum-scale=1.0">
    <meta http-equiv="X-UA-Compatible" content="ie=edge">
    <title>Document</title>
</head>
<body>
    Money transferred from <span th:text="${from}">FROM</span>
    to <span th:text="${to}">TO</span>
</body>
</html>

```

@Qualifier

- We use **@Qualifier** along with **@Autowired** to provide the bean id or bean name

```

@Component
@Qualifier("bike")
class Bike implements Vehicle {
    private String make;
    private String model;
}

```

```

@Component
@Qualifier("car")
class Car implements Vehicle {
    private String make;
    private String model;
    private Integer seats;
}

```

- If we want to get Bike, we need to specify it with adding **@Qualifier("bike")** before injecting Vehicle

```

@.Autowired
Biker(@Qualifier("bike") Vehicle vehicle) {
    this.vehicle = vehicle;
}

```

@Primary

- We can use **@Primary** to simplify this case:
 - if we mark the most frequently used bean with **@Primary**

```

@Component
@Qualifier("bike")
class Bike implements Vehicle {

```

```

    private String make;
    private String model;
}

@Component
@Primary
class Car implements Vehicle {
    private String make;
    private String model;
    private Integer seats;
}

```

- The example of **@Primary** use case

```

@Component
class Driver {
    @Autowired
    Vehicle vehicle;
}

```

```

@Component
class Biker {
    @Autowired
    @Qualifier("bike")
    Vehicle vehicle;
}

```

6.3. Scope of the URL

```

@Controller
@RequestMapping("/users")
public class UserController {

    return "redirect:/users/login"; // е същото като
    return "redirect:login"; // redirect-ва към текущия път /user плюс Login, като ни връща и
    // сесията JSessionId
}

```

6.4. Working with Http Sessions, Cookies and Headers

HTTP session и Cookies се ползват впоследствие в Headers на Http REST/AJAX заявките.

Working with the Session

- The session will be **injected from the IoC container** when called

```

@GetMapping("/")
public String home(HttpSession httpSession) {
    ...
    httpSession.setAttribute("id", 2);
    ...
}

```

```
@Controller
public class HomeController {

    @GetMapping("/")
    public String index(HttpServletRequest httpSession) {

        return httpSession.getAttribute("user") == null
            ? "index" : "home";
    }
}
```

Така го логваме потребителя:

```
httpSession.setAttribute("user", userServiceModel);
```

Така го разлогваме - invalidate

```
@GetMapping("/logout")
public String logout(HttpServletRequest httpSession){
    httpSession.invalidate();

    return "redirect:/";
}
```

- Later the session attributes can be accessed from Thymeleaf using the expression syntax and the `#session` object

Reading HTTP Cookie

- The annotation `@CookieValue`

От браузъра към вървъра

```
@GetMapping("/")
public String readCookie(@CookieValue(название или value (едно и също е) = "username", defaultValue
= "Guest") String username) {
    return "login";
}
```

- Using the `ResponseCookie` object

```
ResponseCookie cookie = ResponseCookie.from("username", "pesho")
    .httpOnly(true)
    .secure(true)
    .path("/")
    .maxAge(60)
```

```

.domain("softuni.bg")
.build(); //builder for cookies

 ResponseEntity
    .ok()
    .header(HttpHeaders.SET_COOKIE, cookie.toString())
    .build();

```

- **@CookieValue** – по по-нормален начин е тук

```

@GetMapping("/change-username")
public String setCookie(HttpServletRequest response) {
    // create a cookie
    Cookie cookie = new Cookie("username", "Pesho");
    //add cookie to response
    response.addCookie(cookie);
    response.setStatus(HttpStatus.NotFound)
    return "index";
}

```

RequestHeader

- Reading **HTTP Header**

```

@GetMapping("/greeting")
public ResponseEntity<String> greeting(
    @RequestHeader("accept-language") String language) {
    // code that uses the language variable
    return new ResponseEntity<String>("greeting", HttpStatus.OK);
}

```

ResponseStatus

- We can specify the desired **HTTP status** of the response

```

@RequestMapping(method = RequestMethod.POST)
@ResponseStatus(HttpStatus.CREATED)
public void storeEmployee(@RequestBody Employee employee) {
    ...
}

```

6.5. Request & Response Body

@RequestBody

- Maps the **HttpRequest body** to a transfer or domain object, enabling automatic deserialization of the inbound HttpRequest body on to a Java objects – **десериализация на body-то до Java обект**

```

@PostMapping("/students/add")
public ResponseEntity postController(
    @RequestBody StudentAddBindingModel bindingModel){
    myService.add(bindingModel);
    return ResponseEntity.ok(HttpStatus.OK);
}

```

Въпреки че много често http request body-то е JSON обект.

What is the function of annotation `@RequestBody`? - To bind the HTTP body request to a domain/transfer object enabling automatic deserialization.

`@ResponseBody`

- Tells a controller that the object returned is automatically serialized into **JSON** and passed back into the **HttpServletResponse object**

Сериализирай го като JSON и го сложи като част/цялото body на http response-a

```
@GetMapping("/response")
@ResponseBody
public Exercise getLastEx() {
    // Get exercise from service
    return exercise;
}
{"id":"0b5963eb-4f4d-4718-bd34-
d0206d80046a","name":"SPRING DATA
INTRO","startedOn":"2021-01-
14T19:26:00","dueDate":"2021-02-05T19:26:00"}
```

6.6. Session as @Bean - Security access requirements - Example

The **Security Requirements** are mainly access requirements. Configurations about which users can access specific functionalities and pages. – **backend functionality checkings / validations** – във всичките контролери да добавим `currentUser`-а и да направим if-ове дали е логнат – и готово.

```
@Component
@SessionScope
public class LoggedUser {
    private Long id;
    private String username;

    public void login(UserEntity user){
        this.id = user.getId();
        this.username = user.getUsername();
    }

    public LoggedUser() {
        this.id = null;
        this.username = null;
    }

    public void logout(){
        this.id = null;
        this.username = null;
    }

    public Long getId() {
        return id;
    }

    public void setId(Long id) {
        this.id = id;
    }
}
```

```

public String getUsername() {
    return username;
}

public void setUsername(String username) {
    this.username = username;
}
}

@Controller
public class HomeController {
    private final LoggedUser loggedUser;

    public HomeController(LoggedUser loggedUser) {
        this.loggedUser = loggedUser;
    }

    @GetMapping("/")
    public String loggedOutIndex(){
        //if user is already Logged-in
        if (loggedUser.getId() != null) {
            return "redirect:/home";
        }
        return "index";
    }

    @GetMapping("/home")
    public String loggedInIndex(){
        //if user is Logged-out
        if (loggedUser.getId() == null) {
            return "redirect:/";
        }
        return "home";
    }
}

```

Задължително слагаме и на Get заявката, и на Post заявката!!!

```

@GetMapping("/login")
public String login(Model model) {
    //If user has already logged in
    if (loggedUser.getId() != null) {
        return "redirect:/home";
    }

    if (!model.containsAttribute( attributeName: "userLoginBindingDto")) {
        model.addAttribute( attributeName: "userLoginBindingDto", new UserLoginBindingDto());
        model.addAttribute( attributeName: "notFound", attributeValue: false);
    }

    return "login";
}

@PostMapping("/login")
public String loginConfirm(@Valid UserLoginBindingDto userLoginBindingDto,
                           BindingResult bindingResult, RedirectAttributes redirectAttributes){
    //If user has already logged in
    if (loggedUser.getId() != null) {
        return "redirect:/home";
    }

<a th:if="${@loggedUser.getId() != null}" class="nav-link text-white active h5" href="/">Add
Product</a>

```

7. Thymeleaf & Validation

<https://www.thymeleaf.org/doc/tutorials/3.0/usingthymeleaf.html>

Server-side validation

Gradle dependency

```

implementation 'org.springframework.boot:spring-boot-starter-validation'
===
javax.validation.constraints
| \--- org.hibernate.validator:hibernate-validator:6.2.3.Final
|     +--- jakarta.validation:jakarta.validation-api:2.0.2
|     +--- org.jboss.logging:jboss-logging:3.4.1.Final -> 3.4.3.Final

```

```

2 import javax.validation.constraints.Email;
3 import javax.validation.constraints.NotEmpty;
4 import javax.validation.constraints.NotNull;
5 import javax.validation.constraints.Positive;
6 import javax.validation.constraints.Size;
7
8 public class User {
9     @NotEmpty
10    @Email
11    private String email;
12
13    @NotEmpty
14    @Size(min = 2, max = 50)
15    private String name;
16
17    @NotEmpty
18    @Size(min = 2, max = 50)
19    private String password;
20
21    @NotEmpty
22    @Size(min = 2, max = 50)
23    private String confirmPassword;
24
25    public String getEmail() {
26        return email;
27    }
28
29    public void setEmail(String email) {
30        this.email = email;
31    }
32
33    public String getName() {
34        return name;
35    }
36
37    public void setName(String name) {
38        this.name = name;
39    }
40
41    public String getPassword() {
42        return password;
43    }
44
45    public void setPassword(String password) {
46        this.password = password;
47    }
48
49    public String getConfirmPassword() {
50        return confirmPassword;
51    }
52
53    public void setConfirmPassword(String confirmPassword) {
54        this.confirmPassword = confirmPassword;
55    }
56
57    @Override
58    public String toString() {
59        return "User{" +
60            "email=" + email +
61            ", name=" + name +
62            ", password=" + password +
63            ", confirmPassword=" + confirmPassword +
64            '}';
65    }
66
67}

```

Pom.xml

```

<dependency>
    <groupId>org.springframework.boot</groupId>
    <artifactId>spring-boot-starter-validation</artifactId>
</dependency>

```

Client-side validation

```

<div class="form-group">
    <label for="username" class="text-white font-weight-bold">E-mail(username)</label>
    <input value="username" id="username" name="username" type="text" min="2" max="50"
           class="form-control"
           placeholder="Username"/>
</div>


```

7.1. Thymeleaf Helpers

Helpers

- Objects that provide built-in functionalities that helps you enhance your view

Enhance your view




Date – Custom Format

```
WhiskeyController.java
@GetMapping("/home")
public String getHomePage(Model model){
    model.addAttribute("myDate", new Date());
    return "whiskey-home.html";
}
```

whiskey-home.html

```
<div th:text="#{#dates.format(myDate, 'yyyy-MMM-dd')}"></div>
```




Date – Week Name of Day

```
WhiskeyController.java
@GetMapping("/home")
public String getHomePage(Model model){
    model.addAttribute("myDate", new Date());
    return "whiskey-home.html";
}
```

whiskey-home.html

```
<div th:text="#{#dates.dayOfWeekName(myDate)}"></div>
```




Date – List Days

WhiskeyController.java

```
@GetMapping("/home")
public String getHomePage(Model model){
    // List of dates -> 2016-12-12, 2017-04-09 -> yyyy-MM-dd
    model.addAttribute("myDates", myDates);
    return "whiskey-home";
}
```

whiskey-home.html

```
<div th:text="#{#dates.listDay(myDates)}"></div>
```




Date – Get Current Date

WhiskeyController.java

```
@GetMapping("/home")
public String getHomePage() {
    return "whiskey-home";
}
```

whiskey-home.html

```
<div th:text="#{#dates.createNow()}"/></div>
```



LocalDate and Thymeleaf

WhiskeyController.java

```
@GetMapping("/home")
public String getHomePage(Model model){
    model.addAttribute("myDate", LocalDate.now());
    return "whiskey-home";
}
```

```
whiskey-home.html  
${#temporals.format(myDate, 'dd-MMM-yyyy')}|
```

- To use **LocalDate** we need to add new **dependency** (for old versions only needed)

```
<dependency>  
    <groupId>org.thymeleaf.extras</groupId>  
    <artifactId>thymeleaf-extras-java8time</artifactId>  
    <version>3.0.4.RELEASE</version>  
</dependency>
```


Strings – is Empty

WhiskeyController.java

```
@GetMapping("/home")  
public String getHomePage(Model model) {  
    String whiskeyNull = null;  
    model.addAttribute("whiskey", whiskeyNull);  
    return "whiskey-home";  
}
```

whiskey-home.html

```
<div th:text="${#strings.isEmpty(whiskey)}"></div>
```




Strings – Substring

WhiskeyController.java

```
@GetMapping("/home")  
public String getHomePage(Model model) {  
    String whiskey = "Jack Daniels";  
    model.addAttribute("whiskey", whiskey);  
    return "whiskey-home";  
}
```

whiskey-home.html

```
<div th:text="${#strings.substring(whiskey,0,4)}"></div>
```



Strings – Join

WhiskeyController.java

```
@GetMapping("/home")
public String getHomePage(Model model) {
    List<String> whiskeys = List.of("Jack Daniels", "Jameson");
    model.addAttribute("whiskeys", whiskeys);
    return "whiskey-home";
}
```

whiskey-home.html

```
<div th:text="#{#strings.listJoin(whiskeys, '-')}"/></div> раздели със запетая
```




Strings – Capitalize

WhiskeyController.java

```
@GetMapping("/home")
public String getHomePage(Model model) {
    String whiskey = "jameson";
    model.addAttribute("whiskey", whiskey);
    return "whiskey-home";
}
```

whiskey-home.html

```
<div th:text="#{#strings.capitalize(whiskey)}"/></div> - само първата буква капитализира
```




Numbers – Format

MathController.java

```
@GetMapping("/home")
public String getHomePage(Model model) {
    double num = 3.14159;
    model.addAttribute("num", num);
    return "home";
}
```

home.html

```
<div th:text="#{#numbers.formatDecimal(num,1,2)}"/></div>
```



Numbers – Sequence

MathController.java

```
@GetMapping("/home")
public String getHomePage(Model model) {
    return "home";
}
```

home.html

```
<span th:each="number: ${#numbers.sequence(0,2)}">
    <span th:text="${number}"></span>
</span>
```




Aggregates – Sum

WhiskeyController.java

```
@GetMapping("/home")
public String getHomePage(Model model) {
    double[] whiskeyPrices = new double[]{29.23, 21.22, 33.50};
    model.addAttribute("whiskeyPrices", whiskeyPrices);
    return "whiskey-home";
}
```

whiskey-home.html

```
<div th:text="#{#aggregates.sum(whiskeyPrices)}
```



Text inlining

Although the Standard Dialect allows us to do almost everything we might need by using tag attributes, there are situations in which we could prefer writing expressions directly into our HTML texts. For example, we could prefer writing this:

```
p>Hello, [[${session.user.name}]] !</p>
```

...instead of this:

```
p>Hello, <span th:text="${session.user.name}">Sebastian</span>!</p>
```

Expressions between [[. . .]] are considered expression inlining in Thymeleaf, and in them you can use any kind of expression that would also be valid in a `th:text` attribute.

In order for inlining to work, we must activate it by using the `th:inline` attribute, which has three possible values or modes (`text`, `javascript` and `none`). Let's try `text`:

```
<p th:inline="text">Hello, [[${session.user.name}]]!</p>
```

The tag holding the `th:inline` does not have to be the one containing the inlined expression/s, any parent tag would do:

```
<body th:inline="text">
...
<p>Hello, [[${session.user.name}]]!</p>
...
</body>
```

So you might now be asking: *Why aren't we doing this from the beginning? It's less code than all those `th:text` attributes!* Well, be careful there, because although you might find inlining quite interesting, you should always remember that inlined expressions will be displayed verbatim in your HTML files when you open them statically, so you probably won't be able to use them as prototypes anymore!

The difference between how a browser would statically display our fragment of code without using inlining...

```
Hello, Sebastian!
```

...and using it...

```
Hello, [[${session.user.name}]]!
```

...is quite clear.

When [inlining](#), [[. . .]] corresponds to `th:text` and [(. . .)] corresponds to `th:utext`.

Thymeleaf in JavaScript - text inlining

```
JSController.java
@GetMapping("/js")
public String getMapPage(Model model){
    String message = "Hi JS!";
    model.addAttribute("message", message);
    return "page.html";
}
```

```
script.js
<script th:inline="javascript">
    let message = [[${message}]];
</script>
```

Text inlining

Извикване на source js файл може да стане и през th:src

```
<script th:inline="javascript" th:src="@{/js/viewAndSearchOrders.js}"
type="text/javascript"></script>
```

7.2. How to Validate?

Spring Validation & Thymeleaf

- Making a simple **Model validation** and **Error rendering**

Пример 1:

```
public class SomeModel {

    @NotNull
    @Size(min = 3, max = 10,
          message = "Invalid name")
    private String name;
}

@Controller
public class SomeController {
    @GetMapping("/add")
    public String getPage(Model model) {

        if(!model.containsAttribute("bindingModel")){
            model.addAttribute("bindingModel",
                              new BindingModel());
        }

        return "add";
    }
}
```

//поредността на параметрите на add метода са в строга последователност!!! – Spring inject-ва валидирания модел, който и веднага се bind-ва.

```
@PostMapping("/add")
public String add(@Valid @ModelAttribute("bindingModel") SomeModel bindingModel,
BindingResult bindingResult, RedirectAttributes rAtt) {
    if (bindingResult.hasErrors()) {
        rAtt.addFlashAttribute("bindingModel", bindingModel); //flash – ще рече след
презареждане на URL-то на страницата да предадем данните на template. Нещо, което живее в
рамките на следващия един http request.
        rAtt.addFlashAttribute("org.springframework.validation.BindingResult.bindingModel",
bindingResult);
        return "redirect:/add"; //редиректваме към този URL, не към html страница
```

```

    }

    this.someService.save(bindingModel);

    return "redirect:/home"; //редиректваме към този URL, не към html страница
}

```

add.html

Когато имаме атрибут `th:field`, то нямаме нужда от атрибут `name` в html кода.

```

<div th:object="${ bindingModel }">
    <div class="justify-content-center">
        <label for="name" class="h4 mb-2 text-white">Name</label>
    </div>
    <input th:field="*{name}" th:errorclass="bg-danger" type="text" class="form-control"
id="name" name="name"/>
    <small th:if="#fields.hasErrors('name')"
        th:errors="*{name}" class="text-danger"> Name error</small>
</div>

```

The screenshot shows a simple HTML form element. It is a text input field with the placeholder 'Name'. The field is currently empty and has a red border around it, which is a standard visual cue for validation errors in many frameworks. Below the input field, the text 'Invalid name' is displayed in a smaller font, further indicating that the input is invalid.

Пример 2:

AuthController.java

```

@Controller
public class AuthController {

    //Ако го има вече инициализиран userToRegister, то го прескача и не го инициализира отново с
    //празни стойности
    @ModelAttribute(name = "userToRegister")
    public UserRegisterBindingModelDTO userRegisterBindingModelDTO(){
        return new UserRegisterBindingModelDTO();
    }

    @GetMapping("/register")
    public String register(Model model) {
        //      this.userRepo
        return "register.html";
    }

    @PostMapping("/register")
    public String registerConfirm(@Valid UserRegisterBindingModelDTO userRegisterBindingModelDTO,
                                  BindingResult bindingResult, RedirectAttributes
    redirectAttributes){

        System.out.println(userRegisterBindingModelDTO);

        if (bindingResult.hasErrors() ||

```

```

!userRegisterBindingModelDTO.getPassword().equals(userRegisterBindingModelDTO.getConfirmPassword())
)) {
    //pass dto to template
    redirectAttributes.addFlashAttribute("userToRegister", userRegisterBindingModelDTO);

    //pass errors to template
    redirectAttributes.addFlashAttribute(
        "org.springframework.validation.BindingResult.userToRegister",
        bindingResult);

    //Добавяне на custom грешка чрез reject
    bindingResult.reject("password", new String[]{"passwords.matching"}, "Password id
not match");

    return "redirect:/users/register";
}

//TODO: save in db
//check if passwords are the same
// check if username/email exists in the db
//insert in DB

return "redirect:/users/login";
}

```

register.html

```

<form
    th:action="@{/register}"
    th:method="post"
    th:object="${userToRegister}"
    class="registration-form"
>
    <div>
        <div class="col-auto">
            <label for="inputUsername" class="col-form-label">Username</label>
        </div>
        <div class="col-auto">
            <input name="username"
                   th:field="*{username}"
                   th:errorclass="is-invalid" добавя се след това в class
атрибута чрез Bootstrap
                   type="text"
                   id="inputUsername"
                   class="form-control"
                   aria-describedby="usernameHelpInline">
            <small id="usernameError"
                   class="invalid-feedback bg-danger rounded">Username length must be more
than 3
                   characters</small>
            <small id="usernameUniqueError"
                   class=" bg-danger rounded">Username is already occupied</small>
        </div>
    </div>

```

```

        </div>

        <div>
            <div class="col-auto">
                <label for="inputFullName" class="col-form-label ">Full Name</label>
            </div>
            <div class="col-auto">
                <input name="fullname" //служи за формиране на FormData на браузъра
                    th:field="*{fullname}"
                    th:errorclass="is-invalid"
                    type="text"
                    id="inputFullName"
                    class="form-control"
                    aria-describedby="fullNameHelpInline">
                <small id="fullNameError"
                    class="invalid-feedback form-text bg-danger rounded">Full name length
                must be more than
                    3 characters</small>
                <small th:if="#fields.hasErrors('fullname')"> Some custom errors
            </small>
            </div>
        </div>

        <div>
            <div class="col-auto">
                <label for="inputEmail" class="col-form-label ">Email</label>
            </div>
            <div class="col-auto">
                <input name="email"
                    th:field="*{email}"
                    th:errorclass="is-invalid"
                    type="email"
                    id="inputEmail"
                    class="form-control"
                    aria-describedby="emailHelpInline">
                <small id="emailError" th:if="#fields.hasErrors('email')"
                    class="invalid-feedback form-text bg-danger rounded">Must be valid
                email</small>
            </div>
        </div>
        <div>
            <div class="col-auto">
                <label for="inputAge" class="col-form-label ">Age</label>
            </div>
            <div class="col-auto">
                <input name="age" required
                    th:field="*{age}"
                    th:errorclass="is-invalid"
                    type="number"
                    id="inputAge"
                    class="form-control"
                    min="0" max="90"
                    aria-describedby="ageHelpInline">
                <small id="ageError"
                    class="invalid-feedback form-text bg-danger rounded">Must be valid
                age</small>
            </div>
        </div>
    
```

```

        </div>
    </div>
<div>
    <div class="col-auto">
        <label for="inputPassword" class="col-form-label">Password</label>
    </div>
    <div class="col-auto">
        <input name="password"
            th:field="*{password}"
            th:errorclass="is-invalid"
            required minlength="5" maxlength="20"
            type="password"
            id="inputPassword"
            class="form-control"
            aria-describedby="passwordHelpInline">
        <small id="passwordError"
            class="invalid-feedback form-text bg-danger rounded">
            Password length must be between 5 and 20 characters and passwords should match.
        </small>
    </div>
</div>

<div class="d-flex justify-content-center mt-4">
    <button class="btn btn-primary btn-block w-50" type="submit">Register</button>
</div>

</form>

```

List/render All Errors

add.html

```

<ul th:if="${#fields.hasErrors('*')}">
    <li th:each="err : ${#fields.errors('*')}" th:text="${err}">
        Input is incorrect
    </li>
</ul>

```

add.html

```

<ul th:if="${#fields.hasErrors('${someModel.*}')}">
    <li th:each="err : ${#fields.errors('${someModel.*}')}" th:text="${err}">
        Input is incorrect
    </li>
</ul>

```

- Invalid creator
- Invalid name
- Mutation cannot be null
- Invalid description
- Invalid hours
- You must select capitals

Пример

login.html

```
<!DOCTYPE html>
<html lang="en" xmlns:th="http://www.thymeleaf.org">
<head th:replace="fragments/commons::head"></head>
<body class="bg-secondary">
<header th:replace="fragments/commons::nav"></header>

<main role="main" class="bg-secondary">
    <div class="jumbotron">
        <div class="container text-light">
            <h1 class="display-3">
                <strong class="bg-blur rounded border-left border-white pl-3 border-bottom">Login</strong></h1>
                <h3 class="mt-5 text-center"><strong class="bg-blur rounded border-white pl-3 border-bottom">Enter valid
                    username and
                    password</strong>
                </h3>
            </div>

            <div class="container bg-blur rounded p-5 mt-5 w-75">
                <form th:action="@{/users/login}" method="POST" th:object="${userToLogin}"
                      class="text-center text-light">
                    <h3 th:if="${isFound == false}" class="mt-5 text-center">
                        <strong class="bg-blur rounded text-danger">
                            Wrong username and password combination.
                        </strong>
                    </h3>

                    <div class="form-group row">
                        <label for="username" class="col-sm-2 col-form-label">Username</label>
                        <div class="col-sm-10">
                            <input type="text"
                                  class="form-control"
                                  th:field="*{username}"
                                  th:errorclass="bg-danger"
                                  id="username"
                                  aria-describedby="usernameHelpInline" placeholder="Username">
                            <small id="usernameHelpInline"
                                  th:if="#{fields.hasErrors('username')}"
                                  th:errors="*{username}"
                                  class="bg-danger text-light rounded">
                                Username length must be between 5 and 20 characters.
                            </small>
                        </div>
                    </div>

                    <div class="form-group row">
                        <label for="password" class="col-sm-2 col-form-label">Password</label>
                        <div class="col-sm-10">
                            <input type="password"
                                  class="form-control"
                                  th:field="*{password}">
                        </div>
                    </div>
                </form>
            </div>
        </div>
    </div>
</main>
```

```

        th:errorclass="bg-danger"      from bootstrap - background-danger
        id="password"
        aria-describedby="passwordHelpInline" placeholder="Password">
        <small id="passwordHelpInline"
        th:if="#{fields.hasErrors('password')}"
        th:errors="*{password}"
        class="bg-danger text-light rounded">
            Password length must be more than 3 characters.
        </small>
    </div>
</div>
<button type="submit" class="btn btn-info w-50">Login</button>
</form>
<hr class="bg-light">
</div>
</div>
</main>

<footer th:replace="fragments/commons::footer"></footer>

</body>
</html>

```

login.html – листване на грешките отгоре

```
<div th:each="e : ${fields.errors()}" th:text="${e}"></div>
```

UserLoginBindingModelDTO.java


```

public class UserLoginBindingModelDTO {
    @Size(min = 5, max = 20, message = "My username error message")
    private String username;

    @Size(min = 3, message = "My password error message")
    private String password;

    public UserLoginBindingModelDTO() {
    }
}
```

The display result



Custom Annotations

- You can also implement **custom validation annotations**
 - Sometimes it is necessary due to complex validation functionality

Пример 1 – проверка сега или в бъдещето

```
@Retention(RetentionPolicy.RUNTIME)
@Target(ElementType.FIELD)
@Constraint(validatedBy = PresentOrFutureValidator.class)
public @interface PresentOrFuture {

    String message() default "Invalid Date";

    Class<?>[] groups() default {};

    Class<? extends Payload>[] payload() default {};

}
```

- You can also use the **@PresentOrFuture** validation annotations.

```
public class SomeModel {
    @NotNull
    @PresentOrFuture
    @DateTimeFormat(pattern = "dd/MM/yyyy")
    @DateTimeFormat(pattern = "yyyy-MM-dd'T'HH:mm")  за LocalDateTime
    private Date startDate;
}
```

- You will have to implement a **custom validator** too

```
public class PresentOrFutureValidator implements ConstraintValidator<PresentOrFuture, Date> {
    @Override
    public boolean isValid(Date date,
                          ConstraintValidatorContext constraintValidatorContext) {
```

```

        Date today = new Date();
        return date.after(today); //True = No Error; False = Error
    }
}

```

Пример 2 – проверка на e-mail

```

@Retention(RetentionPolicy.RUNTIME)
@Target(ElementType.FIELD)
@Constraint(validatedBy = UniqueUserEmailValidator.class)
public @interface UniqueUserEmail {
    String message() default "Invalid Email";

    Class<?>[] groups() default {};
    Class<? extends Payload>[] payload() default {};
}

public class UniqueUserEmailValidator implements ConstraintValidator<UniqueUserEmail, String> {
    private UserRepository userRepository;

    public UniqueUserEmailValidator(UserRepository userRepository) {
        this.userRepository = userRepository;
    }

    //    @Override
    //    public void initialize(UniqueUserName constraintAnnotation) {
    //        ConstraintValidator.super.initialize(constraintAnnotation);
    //    }

    @Override
    public boolean isValid(String value, ConstraintValidatorContext context) {
        return this.userRepository.findByEmail(value).isEmpty();
    }
}

public class UserRegisterDto {
    @NotEmpty(message = "User email should be provided") //we override here the default error
    message
    @Email(message = "User email should be valid") //we override here the default error message
    @UniqueUserEmail(message = "User email should be unique") //we override here the default
    error message
    private String email;
}

```

Render errors

```

<form th:action="@{/users/register}"
      th:method="post"
      th:object="${userModel}">

    <div class="form-group col-md-6 mb-3">
        <label for="email" class="text-white font-weight-bold">E-mail</label>
        <input id="email"
               th:field="*{email}">
    </div>

```

```
    th:errorclass="is-invalid"
    type="text"
    class="form-control"
    placeholder="email"/>
```

В)

//валидира се от сложната custom анотация за паролите – работи само с таг div и дълбоко съобщение за грешка – колекции от грешки

```
<div class="invalid-feedback errors alert alert-danger">
    <div th:each="err : ${#fields.errors('email')}" th:text="${err}" /> искаме листа от
всички грешки
</div>
</div>
```

С)

Още един вариант за изкарване на дълбоко съобщение за грешка – колекции от грешки

```
<div class="form-group row">
    <label for="email" class="col-sm-2 col-form-label">Email</label>
    <div class="col-sm-10">
        <input type="text" class="form-control" id="email"
            th:field="*{email}"
            th:errorclass="bg-danger"
            aria-describedby="emailHelpInline" placeholder="email@example.com">
        <small id="emailHelpInline"
            th:if="${#fields.hasErrors('email')}" //проверява за грешки
            th:errorclass="is-valid" – можем и без този ред
            th:error = "*{email}" //показва всичките грешки
            class="bg-danger text-light rounded">
            Enter valid email address.
        </small>
    </div>
</div>
```

Пример 3 – сложна проверка на password и confirmPassword

Render errors

```
<form th:action="@{/users/register}"
    th:method="post"
    th:object="${userModel}">

    <div class="form-group col-md-6 mb-3">
        <label for="password" class="text-white font-weight-bold">Password</label>
        <input id="password"
            th:field="*{password}"
            th:errorclass="is-invalid"
            type="password"
            class="form-control"
            placeholder="Password"/>
        <p class="invalid-feedback errors alert alert-danger">
            Password is required and should be at least 5 symbols long. //валидира се от @Valid
анотацията, и @Size(min = 5)
        </p>
    </div>

    <div class="form-group col-md-6 mb-3">
```

```

<label for="confirmPassword" class="text-white font-weight-bold">Confirm Password</label>
<input
    type="password"
    id="confirmPassword"
    name="confirmPassword"
    th:field="*{confirmPassword}"
    th:errorclass="is-invalid"

    class="form-control"
    placeholder="confirmPassword"/>

```

A)

Съобщение за грешка спрямо какво сме записали в HTML елемента р

```

<p class="invalid-feedback errors alert alert-danger">
    Passwords should match. //валидира се от сложната custom анотация за паролите - с таг
    елемент р и без дълбоко съобщение за грешка/грешки
</p>

```

B)

С използване на message-а от клас Анотацията @FieldMatch на UserRegisterDto

```

<div class="invalid-feedback errors alert alert-danger">
    <div th:each="err : ${#fields.errors('confirmPassword')}" th:text="${err}"/> //валидира се
    от сложната custom анотация за паролите - работи само с таг div и дълбоко съобщение за грешка -
    колекции от грешки искаеме листа от всички грешки
</div>

```


C)

Още един вариант за изкарване на дълбоко съобщение за грешка – колекции от грешки

```

<div class="col-sm-10">
    <input type="password"
        th:field="*{confirmPassword}"
        th:errorclass="bg-danger"
        class="form-control" id="confirmPassword"
        aria-describedby="confirmPasswordHelpInline" placeholder="Confirm Password">
    <small
        th:if="${#fields.hasErrors('confirmPassword')}"
        th:errorclass="is-valid" - можем и без този ред
        th:errors="*{confirmPassword}" //показва всичките грешки
        id="confirmPasswordHelpInline" class="bg-danger text-light rounded">
        Password length must be more than 3 characters long.
    </small>
</div>
</div>

```



```

@FieldMatch(firstField = "password",
            secondField = "confirmPassword",
            message = "Passwords do not match" //we override here the default error message
)
public class UserRegisterDto {
    @NotEmpty
    @Size(min = 5)
    private String password;

    private String confirmPassword;
}

@Retention(RetentionPolicy.RUNTIME)
@Target(ElementType.TYPE)
@Constraint(validatedBy = FieldMatchValidator.class)
public @interface FieldMatch {
    String firstField();
    String secondField();

    String message() default "Some default message about password";

    Class<?>[] groups() default {};
    Class<? extends Payload>[] payload() default {};
}

import javax.validation.ConstraintValidator;
import javax.validation.ConstraintValidatorContext;

public class FieldMatchValidator implements ConstraintValidator<FieldMatch, Object> {
    private String first;
    private String second;
    private String message;

    @Override
    public void initialize(FieldMatch constraintAnnotation) {
        this.first = constraintAnnotation.firstField();
        this.second = constraintAnnotation.secondField();
        this.message = constraintAnnotation.message();
    }

    @Override
    public boolean isValid(Object value, ConstraintValidatorContext context) {
        //В случая Object value ще е целия модел UserRegisterDTO
        BeanWrapper beanWrapper = PropertyAccessorFactory.forBeanPropertyAccess(value);
        Object firstValue = beanWrapper.getPropertyValue(this.first);
        Object secondValue = beanWrapper.getPropertyValue(this.second);

        boolean valid;

        if (firstValue == null) { //ако password от html формуларя е null
            //ако първото е null и второто е null, то не хвърляй грешка
            //ако първото е null а второто има стойност, то хвърли грешка
            valid = secondValue == null;
        } else { //има въведен password от html формуларя
            valid = firstValue.equals(secondValue); //единакви ли са password и confirmPassword
        }
    }
}

```

```

от html формуляра
}

if (!valid) { //ако не са еднакви паролите, върни error message
    context
        .buildConstraintViolationWithTemplate(message) //error message-а от клас
Анотацията @FieldMatch на UserRegisterDto
        .addPropertyNode(this.second) //задай грешката на второто поле от класа
UserRegisterDto
        .addConstraintViolation()
        .disableDefaultConstraintViolation(); //без default message при грешка
    }

    return valid;
}
}

```

7.3. Mapstruct library (alternative to ModelMapper)

Готиното е, че MapStruct не ползва Reflection, И затова е по-бърз от ModelMapper.

<https://mapstruct.org/>

Download

Apache Maven

.....

```

<properties>
    <org.mapstruct.version>1.5.3.Final</org.mapstruct.version>
</properties>

...
<dependencies>
    <dependency>
        <groupId>org.mapstruct</groupId>
        <artifactId>mapstruct</artifactId>
        <version>${org.mapstruct.version}</version>
    </dependency>
</dependencies>
...
<build>
    <plugins>
        <plugin>
            <groupId>org.apache.maven.plugins</groupId>
            <artifactId>maven-compiler-plugin</artifactId>
            <version>3.8.1</version>
            <configuration>
                <source>1.8</source> <!-- depending on your project -->
                <target>1.8</target> <!-- depending on your project -->
            <annotationProcessorPaths>
                <path>
                    <groupId>org.mapstruct</groupId>
                    <artifactId>mapstruct-processor</artifactId>

```

```

        <version>${org.mapstruct.version}</version>
    </path>
    <!-- other annotation processors -->
</annotationProcessorPaths>
</configuration>
</plugin>
</plugins>
</build>

```


Gradle

```

build.gradle
dependencies {
    implementation 'org.mapstruct:mapstruct:1.5.1.Final'
    #compileOnly 'org.mapstruct:mapstruct-processor:1.5.1.Final'
    annotationProcessor 'org.mapstruct:mapstruct-processor:1.5.1.Final'
}

```

Автоматично да ни генерира bean анотация



Пишем следния interface

```

import org.mapstruct.Mapper;
import org.mapstruct.Mapping;

@Mapper(componentModel = "spring") //може да бъде експозирана като Spring bean
public interface UserMapper {

    @Mapping(target = "active", constant = "true")
    UserEntity userDtoToUserEntity(UserRegisterDto registerDto);

}

```

Даваме Build project,
и от този бутон

```
8     @Mapper(componentModel = "spring")
9     public interface UserMapper {
10        Navigate to autowired candidates
11        Navigate to the Spring bean declaration(s)
12         * UserEntity userDtoToUserEntity(UserRegisterDto registerDto);
13
14    }
15
```

може да ни се генерира следната имплементация за bean

UserMapperImpl.java

```
import javax.annotation.processing.Generated;
import org.springframework.stereotype.Component;

@Generated(
    value = "org.mapstruct.ap.MappingProcessor",
    date = "2022-06-13T20:05:09+0300",
    comments = "version: 1.5.1.Final, compiler: IncrementalProcessingEnvironment from gradle-language-java-7.4.1.jar, environment: Java 17.0.2 (Oracle Corporation)"
)
@Component
public class UserMapperImpl implements UserMapper {

    @Override
    public UserEntity userDtoToUserEntity(UserRegisterDto registerDto) {
        if ( registerDto == null ) {
            return null;
        }

        UserEntity userEntity = new UserEntity();

        userEntity.setEmail( registerDto.getEmail() );
        userEntity.setPassword( registerDto.getPassword() );
        userEntity.setFirstName( registerDto.getFirstName() );
        userEntity.setLastName( registerDto.getLastName() );

        userEntity.setActive( true );

        return userEntity;
    }
}
```

Реално работим само с интерфейси!!!

И да речем го използваме в UserService.java класа

```
@Service
public class UserService {
    private UserRepository userRepository;
    private CurrentUser currentUser;
    private PasswordEncoder passwordEncoder;
    private UserMapper userMapper;
    private Logger LOGGER = LoggerFactory.getLogger(UserService.class);
```

```

public UserService(UserRepository userRepository,
                  CurrentUser currentUser,
                  PasswordEncoder passwordEncoder,
                  UserMapper userMapper) {
    this.userRepository = userRepository;
    this.currentUser = currentUser;
    this.passwordEncoder = passwordEncoder;
    this.userMapper = userMapper;
}

public void registerAndLogin(UserRegisterDto userRegisterDto) {
    UserEntity newUser = userMapper.userDtoToUserEntity(userRegisterDto);
    newUser.setPassword(passwordEncoder.encode(userRegisterDto.getPassword()));

    //      UserEntity newUser = new UserEntity()
    //          .setActive(true)
    //          .setEmail(userRegisterDto.getEmail())
    //          .setFirstName(userRegisterDto.getFirstName())
    //          .setLastName(userRegisterDto.getLastName())
    //          .setPassword(passwordEncoder.encode(userRegisterDto.getPassword()));

    newUser = userRepository.save(newUser);

    login(newUser);
}
}

```

Можем да променяме името на даден field – в обекта/инстанцията car, която е source, имаме "numberOfSeats", а в target-а можем да променим полето на "seatCount"


```

@Mapper
public interface CarMapper {

    CarMapper INSTANCE = Mappers.getMapper( CarMapper.class ); 3

    @Mapping(source = "numberOfSeats", target = "seatCount")
    CarDto carToCarDto(Car car); 2
}

```



declare/implement a mapping method

```
//using default mapper method
default String map(PictureEntity photo){
    return photo.getUrl();
}

//може по няколко мапинги да правим
@Mapping(source = "ivan", target = "petkan")
@Mapping(source = "photo", target = "photoUrl")
ComputerViewGeneralModel computerEntityToComputerSalesViewGeneralModel(ComputerEntity
computerEntity);
```

7.4. HTML Forms requests with Thymeleaf and Spring

Чистите HTML форми могат да имат само method GET и POST!!!

GET

Два варианта за препратка от HTML

```
<div class="card-body">
    <div class="row">
        <a class="btn btn-link" th:href="@{/offers/{id}/edit(id={id})}">Update</a>

        <form th:action="@{/offers/{id}(id={id})}"
              th:method="delete">
            <input type="submit" class="btn btn-link" value="Delete"></input>
        </form>
    </div>
</div>
```

POST

<form

```
    th:action="@{/offers/add}"
    th:method="POST"
    th:object="${addOfferModel}"
    class="main-form mx-auto col-md-8 d-flex flex-column justify-content-center">
```

```
@PostMapping("/offers/add")
public String addOffer(@Valid AddOfferDTO addOfferModel,
                      BindingResult bindingResult,
                      RedirectAttributes redirectAttributes){

    if (bindingResult.hasErrors()) {
        redirectAttributes.addFlashAttribute("addOfferModel", addOfferModel);

        redirectAttributes.addFlashAttribute("org.springframework.validation.BindingResult.addOfferModel",
                                             bindingResult);
        return "redirect:/offers/add";
    }

    //Save in the DB
    this.offerService.addOffer(addOfferModel);

    return "redirect:/offers/all";
}

public void addOffer(AddOfferDTO addOfferDTO) {
    OfferEntity newOffer = this.offerMapper.addOfferDtoToOfferEntity(addOfferDTO);

    //TODO - current user should be logged in

    //
    //UserEntity seller = userRepository.findByEmail(currentUser.getEmail()).orElseThrow();
    Optional<UserEntity> seller = userRepository.findById(1L);
    ModelEntity model = modelRepository.findById(addOfferDTO.getModelId()).orElseThrow();

    newOffer.setModel(model);
    newOffer.setSeller(seller.get());

    offerRepository.save(newOffer);
}
```

DELETE

Накро́йка в application.yml

spring:

```
  datasource:
    driverClassName: com.mysql.cj.jdbc.Driver
    url:
      jdbc:mysql://localhost:3306/mobilele?allowPublicKeyRetrieval=true&useSSL=false&createDatabaseIfNotExist=true&serverTimezone=UTC
    username: root
    password:
  mvc:
```

```
hiddenmethod:  
filter:  
enabled: true
```

Какво hue пишем

```
<form th:action="@{/offers/{id}(id={id})}"  
      th:method="delete">  
    <input type="submit" class="btn btn-link" value="Delete"></input>  
</form>  
  
@Controller  
public class OfferController {  
    private final OfferService offerService;  
    private final BrandService brandService;  
  
    public OfferController(OfferService offerService, BrandService brandService) {  
        this.offerService = offerService;  
        this.brandService = brandService;  
    }  
  
    @GetMapping("/offers/{id}/details")  
    public String showOfferDetail(@PathVariable Long id, Model model){  
        model.addAttribute("currOfferDetail", offerService.findById(id));  
  
        return "details";  
    }  
  
    @DeleteMapping("/offers/{id}")  
    public String deleteOffer(@PathVariable Long id){  
        offerService.deleteOffer(id);  
  
        return "redirect:/offers/all";  
    }  
  
}  
  
@Service  
public class OfferService {  
    private final OfferRepository offerRepository;  
    private final OfferMapper offerMapper;  
    private final ModelRepository modelRepository;  
    private final UserRepository userRepository;  
    private final CurrentUser currentUser;  
  
    public OfferService(OfferRepository offerRepository, OfferMapper offerMapper,  
ModelRepository modelRepository,  
                      UserRepository userRepository, CurrentUser currentUser) {  
        this.offerRepository = offerRepository;  
        this.offerMapper = offerMapper;  
        this.modelRepository = modelRepository;  
        this.userRepository = userRepository;  
        this.currentUser = currentUser;  
    }
```

```

    public void deleteOffer(Long id){
        offerRepository.deleteById(id);
    }
}

```

Какво излиза като HTML код

```

<form action="/offers/1" method="post">
    <input type="hidden" name="_method" value="delete">
    <input type="submit" class="btn btn-link" value="Delete">
</form>

```

PUT – целия запис го изтриваме и записваме нов на негово място

Override-ваме всичко. Номерът на записа в базата се запазва, но ако подадем по-малко неща за записа, за тези полета, за които не сме дали инфо ще се запишат като null в базата данни.

PATCH – частичен Update

В случая не редактираме марка и модел на колата само...

Подход с едно DTO за валидация на данни и едно DTO за презаписване на данните

Насстройка в application.yml

```

spring:
  datasource:
    driverClassName: com.mysql.cj.jdbc.Driver
    url:
      jdbc:mysql://localhost:3306/mobilele?allowPublicKeyRetrieval=true&useSSL=false&createDatabaseIfNotExist=true&serverTimezone=UTC
    username: root
    password:
  mvc:
    hiddenMethod:
      filter:
        enabled: true

```

Какво ние пишем

```

<div class="container">
    <h2 class="text-center text-white">Update Offer</h2>
    <form
        th:object="${offerModel}"
        th:action="@{/offers/{id}/edit(id={*{id}})}"
        th:method="PATCH"
        class="main-form mx-auto col-md-8 d-flex flex-column justify-content-center">
        <div class="row">
            <div class="form-group col-md-6 mb-3">
                <label for="mileage" class="text-white font-weight-bold">Mileage</label>
                <input
                    id="mileage"
                    th:field="*{mileage}">

```

```

        th:errorclass="is-invalid"
        type="number"
        min="0" max="900000" step="1000"
        class="form-control"
        placeholder="Mileage in kilometers"/>
    <p class="invalid-feedback errors alert alert-danger">
        Mileage in kilometers is required.
    </p>
</div>

<div class="form-group col-md-6 mb-3">
    <label for="price" class="text-white font-weight-bold">Price</label>
    <input id="price"
        th:field="*{price}"
        th:errorclass="is-invalid"
        type="number"
        min="0" step="100" class="form-control"
        placeholder="Suggested price"/>
    <p class="invalid-feedback errors alert alert-danger">
        Suggested price is required.
    </p>
</div>
</div>

<div class="row">
    <div class="form-group col-md-6 mb-3">
        <label class="text-center text-white font-weight-bold"
for="engine">Engine</label>
        <select id="engine"
            name="engine"
            th:errorclass="is-invalid"
            class="form-control">
            <option value="">- Select engine type -</option>
            <!-- We pre-select here what is saved until now - на
BindingDTO модела полето сравняваме дали е равно с текущото поле ${anEngine} *{engine}-->
            <option th:each="anEngine : ${engines}"
                th:value="${anEngine}"
                th:text="${anEngine}"
                th:selected="${anEngine} == *{engine}">- Select engine type -
            </option>
        </select>
        <p class="invalid-feedback errors alert alert-danger">
            Engine type is required.
        </p>
    </div>

    <div class="form-group col-md-6 mb-3">
        <label class="text-center text-white font-weight-bold"
for="transmission">Transmission</label>
        <select id="transmission"
            name="transmission"
            th:errorclass="is-invalid"
            class="form-control">
            <option value="">- Select transmission type -</option>
            <!-- We pre-select here what is saved until now - на
BindingDTO модела полето сравняваме дали е равно с текущото поле *{transmission}-->
            <option th:each="aTransmission : ${transmissions}">

```

```

                th:value="${aTransmission}"
                th:text="${aTransmission}"
                th:selected="${aTransmission} == *{transmission}">- Select engine
type - 
            </option>
        </select>
        <p class="invalid-feedback errors alert alert-danger">
            Transmission type is required.
        </p>
    </div>
</div>

<div class="row">
    <div class="form-group col-md-6 mb-3">
        <label for="year" class="text-white font-weight-bold">Year</label>
        <input id="year"
            th:field="*{year}"
            th:errorclass="is-invalid"
            type="number"
            min="1900" max="2099" step="1"
            class="form-control"
            placeholder="Manufacturing year"/>
        <p class="invalid-feedback errors alert alert-danger">
            Manufacturing year is required.
        </p>
    </div>
</div>

<div class="form-group">
    <label class="text-white font-weight-bold" for="description">Description</label>
    <textarea id="description"
        th:field="*{description}"
        th:errorclass="is-invalid"
        type="textarea"
        class="form-control" rows="3"
        placeholder="Description"></textarea>
    <p class="invalid-feedback errors alert alert-danger">
        Description is required.
    </p>
</div>
<div class="form-group">
    <label class="text-white font-weight-bold" for="imageUrl">Image URL</label>
    <input id="imageUrl"
        th:field="*{imageUrl}"
        th:errorclass="is-invalid"
        type="url"
        class="form-control"
        placeholder="Put vehicle image URL here">
    <p class="invalid-feedback errors alert alert-danger">
        Vehicle image URL is required.
    </p>
</div>

<div class="row">
    <div class="col col-md-4">
        <div class="button-holder d-flex">
            <input type="submit" class="btn btn-info btn-lg" value="Update Offer"/>

```

```

        </div>
    </div>
</div>
</form>
</div>

@Controller
public class OfferController {
    private final OfferService offerService;
    private final BrandService brandService;
    private final ModelMapper modelMapper;

    public OfferController(OfferService offerService, BrandService brandService, ModelMapper
modelMapper) {
        this.offerService = offerService;
        this.brandService = brandService;
        this.modelMapper = modelMapper;
    }

    @GetMapping("/offers/{id}/edit")
    public String editOffer(@PathVariable Long id, Model model) {
        OfferDetailsViewDTO offerDetailsView = offerService.findById(id);
        OfferUpdateBindingFlashAttrModelDTO offerUpdateModelDTO =
modelMapper.map(offerDetailsView,
                OfferUpdateBindingFlashAttrModelDTO.class);

        model.addAttribute("engines", EngineEnum.values());
        model.addAttribute("transmissions", TransmissionEnum.values());
        model.addAttribute("offerModel", offerUpdateModelDTO);

        return "update";
    }

    @GetMapping("/offers/{id}/edit/errors") //за да не се пренамажат грешките добавяме /errors
    public String editOfferErrors(@PathVariable Long id, Model model) {
        model.addAttribute("engines", EngineEnum.values());
        model.addAttribute("transmissions", TransmissionEnum.values());

        return "update";
    }

    @PatchMapping("/offers/{id}/edit")
    public String editOffer(@PathVariable Long id,
                           @Valid OfferUpdateBindingFlashAttrModelDTO offerModel,
                           BindingResult bindingResult,
                           RedirectAttributes redirectAttributes) {

        //TODO validation of OfferUpdateBindingFlashAttrModelDTO object
        Тук можем сега реално и redirectAttributes и AddFlashAttribute да използваме – когато
        валидацията е грешна, то да помни какво потребителят е въвел до момента.

        //validation of OfferUpdateBindingFlashAttrModelDTO object
        if (bindingResult.hasErrors()) {
            redirectAttributes.addFlashAttribute("offerModel", offerModel);

            redirectAttributes.addFlashAttribute("org.springframework.validation.BindingResult.offerModel",

```

```

bindingResult);
        return "redirect:/offers/" + id + "/edit/errors"; //за да не се пренамажат грешките
        добавяме наклонена /errors
    } else {
        // Валидирания модел инстанция на OfferUpdateBindingFlashAttrModelDTO го записваме
        както инстанция на OfferUpdateModelDTO
        OfferUpdateModelDTO modelUpdateService = modelMapper.map(offerModel,
OfferUpdateModelDTO.class);
        modelUpdateService.setId(id);
        offerService.updateOffer(modelUpdateService);

        return "redirect:/offers/" + id + "/details";
    }
}
}

```

```

@Service
public class OfferService {
    public void updateOffer(OfferUpdateModelDTO offerModel){
        OfferEntity offerEntity = offerRepository.findById(offerModel.getId()).orElseThrow(() ->
            new ObjectNotFoundException("Offer with id " + offerModel.getId() + " not found!"));

        offerEntity.setPrice(offerModel.getPrice())
            .setDescription(offerModel.getDescription())
            .setEngine(offerModel.getEngine())
            .setImageUrl(offerModel.getImageUrl())
            .setMileage(offerModel.getMileage())
            .setTransmission(offerModel.getTransmission())
            .setYear(offerModel.getYear());

        offerRepository.save(offerEntity);
    }
}

```

```

@ResponseStatus(HttpStatus.NOT_FOUND)
public class ObjectNotFoundException extends RuntimeException{
    public ObjectNotFoundException(String message) {
        super(message);
    }
}

```

Какво излиза като HTML код

```

<form action="/offers/2/edit" method="post"
class="main-form mx-auto col-md-8 d-flex flex-column justify-content-center">
<input type="hidden" name="_method" value="PATCH">

```

Details

1903 Yaris Toyota

Mileage: 4000
 Price: 1000
 Engine type: ELECTRIC
 Transmission type: AUTOMATIC

- Offer created
- Offer modified

Seller - First and Last name: Svilen Velikov



[Update](#)
[Delete](#)

7.5. PasswordEncoder

build.gradle

```
dependencies {
    implementation 'org.springframework.security:spring-security-crypto:5.5.2'
```

pom.xml

```
<dependency>
    <groupId>org.springframework.security</groupId>
    <artifactId>spring-security-core</artifactId>
    <version>5.2.2.RELEASE</version>
</dependency>
```

```
@Configuration
public class ApplicationBeanConfiguration {

    @Bean
    public PasswordEncoder passwordEncoder(){
        return new Pbkdf2PasswordEncoder();
    }

    @Bean
    public ModelMapper modelMapper(){
        return new ModelMapper();
    }

}
```


8. Bootstrap, Front-End Basics

8.1. JavaScript

- **Undefined** - automatically assigned to variables
- **Null** - represents the **intentional absence** of any object value

8.2. Bootstrap

What is a Responsive Design?



Bootstrap

- World's most popular front-end **component library**
- Open source toolkit for developing with **HTML, CSS, and JS**
- Works with
 - Responsive **grid system**
 - Extensive prebuilt **components**
 - Powerful plugins built on jQuery

Колекция от CSS

Include from a Bootstrap CDN – JS

- Be sure to place **jQuery** and **Popper** first, as the Bootstrap code depends on them

```
<!DOCTYPE html>
<html lang="en">

<head>
  <meta charset="UTF-8">
  <meta http-equiv="X-UA-Compatible" content="IE=edge">
  <meta name="viewport" content="width=device-width, initial-scale=1.0">
  <title>Document</title>
  <!-- Първо зареждам Bootstrap CSS-а -->
  <link href="https://cdn.jsdelivr.net/npm/bootstrap@5.2.0-beta1/dist/css/bootstrap.min.css"
        rel="stylesheet"
        integrity="sha384-0evHe/X+R7YkIZDRvuzKMRqM+OrBnVFBL6DOitfPri4tjfHxaWutUpFmBp4vmVor"
        crossorigin="anonymous" />
```

```

<!-- След това зареждаме нашия CSS, за да override-нем-->
<link rel="stylesheet" href="styles.css" />

</head>

<body>

    // когато нямаме defer и async – то трябва да сложим в края на <body> то.

    <!-- Първо зареждаме JQuery и Popper, и последно Boostrap скрипта.
        Bootstrap скрипта ще чете от предходните 2 библиотеки -->
    <script src="https://code.jquery.com/jquery3.3.1.slim.min.js"></script>

    <script src="https://cdn.jsdelivr.net/npm/@popperjs/core@2.11.5/dist/umd/popper.min.js"
    integrity="sha384-Xe+8cL9oJa6tN/veChSP7q+mnSPaj5Bcu9mPX5F5xIGE0DVittaqt5lorf0EI7Vk"
    crossorigin="anonymous"></script>

    <script src="https://cdn.jsdelivr.net/npm/bootstrap@5.2.0-
beta1/dist/js/bootstrap.bundle.min.js"
    integrity="sha384-pprn3073KE6tl6bjs2QrFaJGz5/SUsLqktiwsUTF55Jfv3qYSDhgCecCxMW52nD2"
    crossorigin="anonymous"></script>

    <!-- И чак накрая нашия скрипт – каквото ние пишем това да стане, ако има съвпадение с
Bootstrap, да се изпълнява нашето -->
    <script src="js/main.js"></script>
</body>

</html>

<script src="demo_defer.js" defer></script>
<script src="demo_async.js" async></script>
```

The defer attribute is a boolean attribute.

If the defer attribute is set, it specifies that the script is downloaded in parallel to parsing the page, and executed after the page has finished parsing. Ако го има този атрибут то дори да го сложим в head-а, пак браузъра ще зареди този скрипт накрая.

Note: The defer attribute is only for external scripts (should only be used if the src attribute is present).

Note: There are several ways an external script can be executed:

- If `async` is present: The script is downloaded **in parallel** to parsing the page, and executed as soon as it is available (before parsing completes)
- If `defer` is present (and not `async`): The script is downloaded in parallel to parsing the page, and executed after the page has finished parsing
- If neither `async` or `defer` is present: The script is downloaded and executed immediately, blocking parsing until the script is completed – **в този случай скрипта трябва да е сложен в края на <body> то.**

<https://getbootstrap.com/> - интегриран с JS

Минуси: само с div са дадени примерите.

<https://tailwindcss.com/> - само надгражда CSS – да пишем CSS по различен начин

JQuery все по-малко се използва, защото все повече се ползват React, Vue, Angular. Някои неща в JQuery са тъло написани, някои неща в React, Vue и Angular вземат/копират JQuery.

8.3. Bootstrap Grid System

Build Layouts with Grid – Twelve Column System

Bootstrap Grid System Demo

Use our powerful mobile-first flexbox grid to build layouts of all shapes and sizes thanks to a twelve column system, six default responsive tiers, Sass variables and mixins, and dozens of predefined classes.

```
<div class="container">
    <div class="row">
        <div class="col-sm-6 col-md-4">Column one</div>    <!-- 6 колони при small, 4
 колони при md т.е. за два екрана го правим сега, но реално автоматично работи за всеки
 экран 😊 --&gt;
        &lt;div class="col-sm-6 col-md-4"&gt;Column two&lt;/div&gt;
        &lt;div class="col-xs m-3"&gt;Column three&lt;/div&gt;
    &lt;/div&gt;
&lt;/div&gt;</pre>
```



Column one

Column two

Column three

Bootstrap Containers

- Rows must be placed in **containers**
 - **.container** has one fixed width for each screen size in bootstrap (**xs, sm, md, lg**)
 - **.container-fluid** expands to fill the available width

<https://getbootstrap.com/docs/5.2/layout/grid/>

Column Classes

Extra small (xs)

Small (sm)

Medium (md)

Large (lg)

Extra large (xl)

Extra extra large (xxl)

- **.col-xs**: width less than 576px
- **.col-sm**: width between 576px and 768px
- **.col-md**: width between 768px and 992px
- **.col-lg**: width over 992px

	xs ≤ 576px	sm ≥ 576px	md ≥ 768px	lg ≥ 992px	xl ≥ 1200px	xxl ≥ 1400px
Container <code>max-width</code>	None (auto)	540px	720px	960px	1140px	1320px
Class prefix	<code>.col-</code>	<code>.col-sm-</code>	<code>.col-md-</code>	<code>.col-lg-</code>	<code>.col-xl-</code>	<code>.col-xxl-</code>
# of columns	12					
Gutter width	1.5rem (.75rem on left and right)					
Custom gutters	Yes					
Nestable	Yes					
Column ordering	Yes					

Columns and gutters

Gutters е разстоянието между колоните

Color

- Handful of **color utility classes**

```

<p class="text-primary">.text-primary</p>
<p class="text-secondary">.text-secondary</p>
<p class="text-success">.text-success</p>
<p class="text-danger">.text-danger</p>
<p class="text-warning">.text-warning</p>
<p class="text-info">.text-info</p>
<p class="text-light bg-dark">.text-light</p>
<p class="text-dark">.text-dark</p>
<p class="text-muted">.text-muted</p>
<p class="text-white bg-dark">.text-white</p>

```

Background Color

- Easily set the **background** of an element to any contextual **class**

```

<div class="bg-primary text-white">.bg-primary</div>
<div class="bg-secondary text-white">.bg-secondary</div>
<div class="bg-success text-white">.bg-success</div>
<div class="bg-danger text-white">.bg-danger</div>
<div class="bg-warning text-dark">.bg-warning</div>
<div class="bg-info text-white">.bg-info</div>
<div class="bg-light text-dark">.bg-light</div>
<div class="bg-dark text-white">.bg-dark</div>
<div class="bg-white text-dark">.bg-white</div>

```

8.4. CSS Grid System

```

.customGrid {
    max-width: 1140px;
    margin: 0 auto;
    padding: 0 15px;
    display: grid;
    grid-gap: 15px;
}

@media screen and (min-width: 560px){
    .customGrid{
        grid-gap: 15px;
        grid-template-columns: repeat(2, 1fr);
    }
}

@media screen and (min-width: 768px){
    .customGrid{
        grid-template-columns: repeat(3, 1fr);
    }
}

```

8.5. Bootstrap Components

Button Groups

- Custom **button styles** with support for multiple sizes, states, and more




```
<button type="button" class="btn btn-primary">Primary</button>
<button type="button" class="btn btn-secondary">Secondary</button>
<button type="button" class="btn btn-success">Success</button>
<button type="button" class="btn btn-danger">Danger</button>
```

Alerts


```
<div class="alert alert-success alert-dismissible">
  <a class="close" data-dismiss="alert" aria-label="close">x</a>
  <strong>Success!</strong> This alert box could indicate a successful or positive
action.
</div>
```

И затваряме/изтриваме дом елемента без JS!



Nav and Navbar

- Require a wrapping **.navbar**
- **Responsive** by default
- Come with built-in support for a handful of **sub-components**
 - **.navbar-brand** for your company, product, or project name
 - **.navbar-nav** for a full-height and lightweight navigation
 - **.nav-item** for every item in navigation



Forms

- Form **control styles**, **layout options** and custom **components** for creating a wide variety of forms
- Use **type** attribute on all inputs to take advantage of newer input controls

- Email verification
- Number selection

Email address

Please include an '@' in the email address. 'nakov' is missing an '@'.

Password

Check me out

Submit

Jumbotron

- Lightweight, flexible component for showcasing hero unit style content

```
<div class="jumbotron">
  <h1 class="display-4">Hello,
  world!</h1>
  <p class="lead">This is a ...</p>
  <hr class="my-4"><p>It uses ...</p>
  <p class="lead">
    <a class="btn btn-primary btn-lg">
      Learn more</a>
  </p>
</div>
```

Hello, world!

This is a simple hero unit, a simple jumbotron-style component for calling extra attention to featured content or information.

It uses utility classes for typography and spacing to space content out within the larger container.

[Learn more](#)

See more at: <https://getbootstrap.com/docs/4.0/components/jumbotron/>

Carousel

A slideshow component for cycling through elements—images or slides of text—like a carousel.

```
<div id="carouselExampleCaptions" class="carousel slide" data-bs-ride="false">
  <div class="carousel-indicators">
    <button type="button" data-bs-target="#carouselExampleCaptions" data-bs-slide-to="0"
    class="active"
      aria-current="true" aria-label="Slide 1"></button>
    <button type="button" data-bs-target="#carouselExampleCaptions" data-bs-slide-to="1"
    aria-label="Slide 2"></button>
    <button type="button" data-bs-target="#carouselExampleCaptions" data-bs-slide-to="2"
    aria-label="Slide 3"></button>
  </div>
  <div class="carousel-inner">
    <div class="carousel-item active">
      
    </div>
    <div class="carousel-item">
      
    </div>
    <div class="carousel-item">
      
    </div>
  </div>
  <div class="carousel-caption d-none d-md-block">
    <h3>Slides of text</h3>
    <p>Nulla vitae elit libero, a pharetra augue. Praesent commodo cursus magna, vel scelerisque nisl consectetur et. Nulla vitae elit libero, a pharetra augue. Praesent commodo cursus magna, vel scelerisque nisl consectetur et.</p>
  </div>
</div>
```

```

<div class="carousel-caption d-none d-md-block">
  <h5>First slide label</h5>
  <p>Some representative placeholder content for the first slide.</p>
</div>
</div>
<div class="carousel-item">
  
  <div class="carousel-caption d-none d-md-block">
    <h5>Second slide label</h5>
    <p>Some representative placeholder content for the second slide.</p>
  </div>
</div>
<div class="carousel-item">
  
  <div class="carousel-caption d-none d-md-block">
    <h5>Third slide label</h5>
    <p>Some representative placeholder content for the third slide.</p>
  </div>
</div>
</div>
<button class="carousel-control-prev" type="button" data-bs-target="#carouselExampleCaptions" data-bs-slide="prev">
  <span class="carousel-control-prev-icon" aria-hidden="true"></span>
  <span class="visually-hidden">Previous</span>
</button>
<button class="carousel-control-next" type="button" data-bs-target="#carouselExampleCaptions" data-bs-slide="next">
  <span class="carousel-control-next-icon" aria-hidden="true"></span>
  <span class="visually-hidden">Next</span>
</button>
</div>

```

8.6. jQuery

What is jQuery?

Cross-browser JavaScript library

- Dramatically simplifies **DOM manipulation**
- jQuery is **more expressive/declarative and easy to read** than JS pure Vanilla
- Simplifies **AJAX calls** and working with RESTful services
- Free, open-source software: <https://jquery.com>

Web консорциум относно какви неща всеки един браузър трябва да поддържа. При това положение, няма нужда вече от ползването толкова много на jQuery.

```
$(‘li’).css(‘background’, ‘#DDD’); // Change the CSS for all <li> tags
```

Using jQuery locally

```
npm install jquery
```

Using jQuery from CDN

CDN:

```
<script src="https://code.jquery.com/jquery-3.1.1.min.js"></script>

<script src="https://code.jquery.com/jquery-3.1.1.min.js"
integrity="sha256-hVnYaiADRT02PzUGmuLJr8BLUSjGIZsDYGmIJLv2b8=
" crossorigin="anonymous"></script>
```

```
$(function () {
    $("a").on('click', (event) => {
        alert("Link forbidden!");
        event.preventDefault();
    });
});
```

jQuery demo

page.js

```
$(document).ready(function() {
    $("#my-button").click(function() {
        console.log("Button clicked");

        $("#my-text").text('My custom now text JQuery here');
        $("#my-text").addClass('text-secondary');
    })
});
```

Или така

```
function myCustomClick() {
    console.log("Custom button click");

    $("#my-text").text('My custom now text JQuery here');
    $("#my-text").addClass('text-secondary');
}
```

demojQuery.html

```
<!DOCTYPE html>
<html lang="en">
```

```

<head>
  <meta charset="UTF-8">
  <meta http-equiv="X-UA-Compatible" content="IE=edge">
  <meta name="viewport" content="width=device-width, initial-scale=1.0">
  <title>Document</title>
  <link href="https://cdn.jsdelivr.net/npm/bootstrap@5.2.0-beta1/dist/css/bootstrap.min.css" ></head>

<body>
  <button type="button" id="my-button" class="btn btn-primary">Button</button>
или така
  <button type="button" onclick="myCustomClick()" id="my-button" class="btn btn-primary">Button</button>
  <p id="my-text">My static text here.</p>

  <script src="https://code.jquery.com/jquery-3.6.0.min.js" />
  <script
src="https://cdn.jsdelivr.net/npm/@popperjs/core@2.11.5/dist/umd/popper.min.js"></script>
  <script src="https://cdn.jsdelivr.net/npm/bootstrap@5.2.0-beta1/dist/js/bootstrap.bundle.min.js"></script>
  <script src="page.js"></script>

</body>
</html>

```

jQuery Selectors

jQuery selection is the same as the **querySelector** in Vanilla JS

- All selector `$('*') // Selects all elements`
- Class selector `$('.class') // Select by class name`
- Element selector `($('section') // Select by tag name`
- Id selector `$('#id') // Selects a element by given id`
- Multi-selector `($('selector1, selector2') // Combined`

```

$('.list .list-item a'); //<ul class="list"> <li class="list-item"> <a> </a></li></ul>
$('.list.list-item a'); //<ul class="list list-item"></ul>

```

Adding Elements with jQuery

Select the parent element, then use:

- `append()` / `prepend()`
- `appendTo()` / `prependTo()`

```
<div id="wrapper">
```

```

<div>Hello, student!</div>
<div>Goodbye, student!</div>
</div>

$('#wrapper div').append("<p>It's party time :)</p>");
$('<h1>Greetings</h1>').prependTo('body');
<h1>Greetings</h1>
▼ <div id="wrapper">
  ▼ <div>
    "Hello, student!"
    <p>It's party time :)</p>
  </div>
  ▼ <div>
    "Goodbye, student!"
    <p>It's party time :)</p>
  </div>
</div>

```

Creating / Removing Elements

```

let div = $('

');
div.text('I am a new div.');
div.css('background', 'blue');
div.css('color', 'white');
$(document.body).append(div);


```

With JS

```

document.getElementById("btn-add")
  .addEventListener('click', () => {
    const listNode = document.createElement('li');
    listNode.innerHTML = 'NEW technology';
    document.getElementById('technologies-list')
      .appendChild(listNode);
  });

```

With jQuery

```

$('#btn-add')
  .on('click', () => {
    $('#technologies-list')
      .append($('<li>New Technology with jQuery</li>'));
  });

```

Removing

```
$('#technologies-list')
  .on('click', 'li', function() {
    $(this).remove();
 });
```

jQuery Events: Attach / Remove

- Attaching events on certain elements

```
$('.button').on('click', buttonClicked);
function buttonClicked() {
  $('.selected').removeClass('selected');
  $(this).addClass('selected');
  // "this" is the event source (the hyperlink clicked)
}
```

- Removing event handler from certain elements

```
$('.button').off('click', buttonClicked);
```

//Mouse events

//Form events

//Keyboard events

jQuery Methods

- **text()** - reads and writes text

```
let text = $('#theElement').text();
$('#theElement').text('New text for element.');
```

- **html()** - returns the HTML of a given element

```
let html = $('#theElement').html();
$('#theElement').html('New text for element.');
```

- **val()** - gets and sets value

```
let theValue = $('#theFormField').val();
$('#theFormField').val('New value');
```

- **attr()** - reads and writes attributes of HTML elements. Also can take an object as parameter

```
let attrValue = $('#theFormField').attr('height');
$('#theFormField').attr({height : attrValue});
```

- **removeAttr()** - removes an attribute from an HTML element

```
$('#theFormField').removeAttr('height');
```

- **wrap()** - wraps the selected element in another HTML element
`$('#someElement').wrap('<div style='border: 1px solid black;'></div>');`
 - **replaceWith()** - replaces the selected HTML element with a new one
`$('#theElement').replaceWith('<div style='border: 1px solid black;'></div>');`
 - **remove()** - removes the selected HTML element from the DOM
`$('#theElement').remove();`
 - **empty()** - removes all child elements of the selected HTML element
`$('#theElement').empty();`
- var selectVal = \$('option:selected', formSelect).val(); //we get here the selected option from the <select> of the current form**

9. Web-API-and-REST-Controllers

9.1. REST API

Изначало HTTP Protocol е бил stateless – backend-server-а не трябва да пази информацията от предходната заявка на предхония или същия клиент. След това, с времето, обаче се променят нещата.

- Statelessness – няма състояние, на практика не е така – има кукита, и .т.н.

REST работи на база на HTTP протокола

Rest работи по Default с данни формат JSON. Може и да е с XML също.

За разлика от HTTP, което ползва както JSON формат, така и други тип данни като html данни, и други.

REST протокола може да обменя информация:

- между 2 сървъра
- или между сървър и клиент (без браузър)
- между сървър и браузър клиент

REST не е различно от MVC (Model-View-Controller), но без view-то примерно.

Versioning in REST API – 1.1. за стари клиенти, и примерно v.2.2. за нови клиенти.

Пример:

```
HomeController.java
@GetMapping('/')
public ModelAndView index(ModelAndView modelAndView) {
    modelAndView.setViewName('index');
    return modelAndView;
}

@GetMapping(value = '/fetch', produces = 'application/json')
```


```

@GetMapping(value = '/fetch', produces = 'application/xml')
@ResponseBody
public Object fetchData() {
    return new ArrayList<Product>() {{
        add(new Product() {{
            setName('Chewing Gum');
            setPrice(new BigDecimal(1.00));
            setBarcode('133242556222');
       }});
        ...
    }};
}

```

RESTful Design

Rest предава информация от различни езици. Най-често чрез JSON формат.



RESTful API - Representational state transfer API

True RESTful API, is a **web service** that must adhere to the following six **REST architectural constraints**

- Use of a **uniform interface** (UI)
- **Client-server based**
- **Stateless** operations – backend-server-a не помни предишната заявка каква е била и от кого
- **RESTful resource caching**
- **Layered system** – примерно web сървър-а на една машина, базите данни на една машина, аутентикация да се случва на трета машина.
- **Code on demand** – един response на http rest api може да върне код, който да се изпълни

SOAP and RPC

- **Simple Object Access Protocol (SOAP)**
 - Standardized protocol that **sends messages** using other protocols such as **HTTP** and **SMTP**
 - The SOAP specifications are official web standards, maintained and developed by the World Wide Web Consortium (W3C)
- **Remote Procedure Call (RPC)**

- A way to describe a mechanism that lets you **call a procedure in another process and exchange data by message passing**

HTTP GET

- Used to retrieve single data entities or data arrays

```
{
  'id': 32,
  'name': 'Read Book',
  'deadline': 1362268800000, 'categoryName': 'Work', 'enabled': false
}
```

```
[{
  'id': 32,
  'name': 'Read Book',
  'deadline': 1362268800000,      'categoryName': 'Work',      'enabled': false
},
...
]
```

HTTP POST

HTTP PUT

HTTP PATCH

HTTP DELETE

9.2. REST (Representational state transfer) with Spring

Response Body On MVC Controller

- **Returning plain-text** in MVC controller:

```
@GetMapping('/info/{id}')      //MVC controller
@ResponseBody           //Спри да търсиш Thymeleaf
public String getInfo(@PathVariable Long id) {
...
  return 'Plain text';
}
```

```
@GetMapping('/info/{id}')      //MVC controller
@ResponseBody           //Спри да търсиш Thymeleaf
public Student getInfo(@PathVariable Long id) {
...
  return new Student().setName("Joro");
}
```

Response Status

- Setting the correct Response Code

```
@GetMapping('{id}/info')
@ResponseBody(HttpStatus.OK)
public GameInfoView getInfo(@PathVariable Long id){
    GameInfoView gameInfo = this.gameService.getInfoById(id);

    return new Gson().toJson(gameInfo);
}
```

```
(HttpServletResponse response)
response.setStatus(HttpStatus.NotFound)
```

REST Controllers

- **@RestController** is essentially **@Controller + @ResponseBody**

```
@RestController /controller + response body/
public class OrderController {
    @GetMapping('{id}/info')
    public ResponseEntity<Game> getGame(@PathVariable Long id) {
        ...
    }
}
```

Response Entity

```
@GetMapping('{id}/title')
public ResponseEntity<Game> getTitle(...){
    ...
    return new ResponseEntity(gameService.getGame(id));
}
```

- The **ResponseEntity**<> object allows you to change the response body, response headers and response code

Spring Data REST

- Maven Dependency

Обикновено не се прави така. Понеже се expose-ва всичко.

```
<dependency>
<groupId>org.springframework.boot</groupId>
<artifactId>spring-boot-starter-data-rest</artifactId>
</dependency>
```

- Spring Data REST scans your project and provides REST API for your application using HAL as media type

Configuring Repositories

По-добре бази данни да вземаме с обикновен @Controller. Голяма боза и допълнителни настройки е ако използваме @RepositoryRestResource

- You can configure repository settings using the `@RepositoryRestResource` annotation:

```
@RepositoryRestResource(path = 'gameIssues')
public interface IssueRepository extends JpaRepository<Issue, Long> {

    Issue getById(@Param('id') Long id);

    List<Issue> getAllByOrderByDateDesc();
}
```

Example 1

```
import bg.softuni.books.model.dto.BookDTO;
import bg.softuni.books.service.BookServiceImpl;
import org.springframework.http.ResponseEntity;
import org.springframework.web.bind.annotation.GetMapping;
import org.springframework.web.bind.annotation.PathVariable;
import org.springframework.web.bind.annotation.RequestMapping;
import org.springframework.web.bind.annotation.RestController;

@RestController
@RequestMapping("/books")
public class BooksController {
    private BookServiceImpl bookService;

    public BooksController(BookServiceImpl bookService) {
        this.bookService = bookService;
    }

    //called on http://localhost:8080/books
    @GetMapping
    public ResponseEntity<List<BookDTO>> getAllBooks(){
        List<BookDTO> allBooks = this.bookService.getAllBooks();

        return ResponseEntity.ok(allBooks); //with body allBooks
    }

    @GetMapping("/{id}")
    public ResponseEntity<BookDTO> getBookById(@PathVariable("id") Long id) {
        Optional<BookDTO> bookOpt = this.bookService.getByBookId(id);
        if (bookOpt.isEmpty()) {
            return ResponseEntity.notFound().build();
        } else {
            return ResponseEntity.ok(bookOpt.get());
        }
    }

    @DeleteMapping("/{id}")
    public ResponseEntity<BookDTO> deleteBookById(@PathVariable("id") Long id) {
        bookService
            .deleteBook(id);

        return ResponseEntity.noContent().build();
    }
}
```

```

//called on http://localhost:8080/books
//  @PutMapping("")
@PostMapping("") //В случая работи за добавяне на нова книга, и за промяна на
//съществуваща книга в базата (bookRepository.save() или добавя нова книга или презаписва)
public ResponseEntity<BookDTO> create(
    @RequestBody BookDTO bookDTO, //десериализация на body-то до Java обект –
//пропъртита на боди-то на нашата заявка ще бъдат популирани върху нашето bookDTO
    UriComponentsBuilder builder
) {
    //http://localhost:8080/books/{id}
    long bookId = bookService.createBook(bookDTO);
    URI location = builder.path("/books/{id}")
        .buildAndExpand(bookId)
        .toUri();

    return ResponseEntity.created(location).build();
}

ResponseEntity.status(HttpStatus.OK).build();

//called on http://localhost:8080/books
@PostMapping("/{id}")
public ResponseEntity<BookDTO> update(
    @PathVariable("id") long bookId,
    @Valid @RequestBody BookDTO bookDTO){
    //todo
    throw new UnsupportedOperationException("coming soon");
}
}

```

9.3. Rest Template not reactive

Rest Template

- Accessing a **third-party REST service** inside a Spring application revolves around the use of the Spring **RestTemplate** class
- Class is **designed to call REST services**
- Its **main methods** are closely tied to REST's **underpinnings**, which are the **HTTP protocol's methods: HEAD, GET, POST, PUT, DELETE**
- **Recommended** to use the non-blocking, **reactive WebClient**.
- RestTemplate will be **deprecated in a future version**

Spring казват, че в бъдещите версии ще се deprecate-не Rest template, и ще се използва само Reactive WebClient.

Rest Template Demo – когато четем от един port 8080 като работим с втори порт 8000

Задаваме нов порт **8000**, защото TomCat е заел вече port 8080

application.yml

server:

port: 8000

```

import org.springframework.boot.web.client.RestTemplateBuilder;
import org.springframework.context.annotation.Bean;
import org.springframework.context.annotation.Configuration;
import org.springframework.web.client.RestTemplate;
@Configuration
public class RestConfig {

    @Bean
    public RestTemplate create(RestTemplateBuilder restTemplateBuilder){
        return restTemplateBuilder.build();
    }
}

import bg.softuni.restTemplate.model.dto.BookDTO;
import org.springframework.boot.CommandLineRunner;
import org.springframework.http.ResponseEntity;
import org.springframework.stereotype.Component;
import org.springframework.web.client.RestTemplate;
@Component
public class RestTemplateDemo implements CommandLineRunner {
    private RestTemplate restTemplate; //нашия Bean

    public RestTemplateDemo(RestTemplate restTemplate) {
        this.restTemplate = restTemplate;
    }

    @Override
    public void run(String... args) throws Exception {
        ResponseEntity<BookDTO[]> allBooksResponse = restTemplate
            .getForEntity("http://localhost:8080/api/books", BookDTO[].class);

        if (allBooksResponse.hasBody()) {
            for (BookDTO book : allBooksResponse.getBody()) {
                System.out.println("Book: " + book);
            }
        }
    }
}

@JsonIgnoreProperties(ignoreUnknown = true) //да игнорира непознато
@JsonInclude(Include.NON_NULL)
public class BookDTO {
    private AuthorDTO author;
    private Long id;
    private String title;
    private String isbn;
}

```

HTTP GET Method Examples

- **getForObject(url, classType)**
 - Retrieves a representation by doing a GET on the URL.
 - The response (if any) is unmarshalled to given class type and returned

- **getForEntity(url, responseType)**
 - Retrieve a **representation as ResponseEntity** by doing a GET on the **URL**
- ```
ResponseEntity<BookDTO[]> allBooksResponse = restTemplate
 .getForEntity("http://localhost:8080/api/books", BookDTO[].class);
```
- 
- **exchange(requestEntity, responseType)**
    - **Executes the specified request and returns the response as ResponseEntity**
- 
- **execute(url, httpMethod, requestCallback, responseExtractor)**
    - **Executes the httpMethod to the given URI template and preparing the request with the RequestCallback**

#### HTTP POST Method Examples

- **postForObject(url, request, classType)**
  - **POSTs the given object to the URL and returns the representation found in the response as given class type**
- **postForEntity(url, request, responseType)**
  - **POSTs the given object to the URL and returns the response as ResponseEntity**

```
@Component
public class AppInit implements CommandLineRunner {
 private final RimService rimService;
 private final RestTemplate restTemplate; //нашия Bean

 public AppInit(RimService rimService, RestTemplate restTemplate) {
 this.rimService = rimService;
 this.restTemplate = restTemplate;
 }

 @PostConstruct
 public void beginInit(){
 rimService.init();
 }

 @Override
 public void run(String... args) throws Exception {
 addOneRim();
 }

 private void addOneRim() {
 HttpHeaders headers = new HttpHeaders();
 headers.setContentType(MediaType.APPLICATION_JSON);

 // MultiValueMap<String, String> map= new LinkedMultiValueMap<>();
 // //
 }
}
```

```

// "metalKind": "bronze",
// "inches": "15"
// }
// map.add("metalKind", "bronze");
// map.add("inches", "15");

RimJsonDTO newRimJsonToAdd =
 new RimJsonDTO()
 .setMetalKind("bronze")
 .setInches("15");

RimEntity newRimEntity = new RimEntity()
 .setMetalKind(newRimJsonToAdd.getMetalKind())
 .setInches(newRimJsonToAdd.getInches());

HttpEntity<RimEntity> request = new HttpEntity<>(newRimEntity, headers);

//caught by the @RestController :)
ResponseEntity<RimEntity> oneRimPost = restTemplate
 .postForEntity("http://localhost:8000/spareparts/rims", request,
RimEntity.class);

//If we do not have the @RestController with @PostMapping("/spareparts/rims") in class
RimController,
// then we can update the db with the below line
// rimService.addNewRim(newRimJsonToAdd);
}

```

- **postForLocation(url, request, responseType)**
  - POSTs the given object **to the URL** and **returns** the value of the **Location header**
- **exchange(url, requestEntity, responseType)**
- **execute(url, httpMethod, requestCallback, responseExtractor)**

#### HTTP PUT and HTTP DELETE Method Examples

- **put(url, request)**
  - PUTs the given request object to URL
- **delete(url)**
  - Deletes the resource at the specified URL

## 9.4. Spring Reactive WebClient as a Rest Template

The screenshot shows the Spring Initializr interface. In the 'Project' section, 'Maven Project' is selected. Under 'Language', 'Java' is selected. In the 'Spring Boot' section, '2.7.1' is selected. The 'Dependencies' section has 'Spring Web' checked, which is highlighted with a red box and a checkmark. Other options like 'Spring Reactive Web' are also listed. Project metadata includes Group (bg.softuni), Artifact (webclient), Name (webclient), Description (Demo for webclient), and Package name (bg.softuni.webclient). Buttons at the bottom include 'GENERATE' (CTRL + D), 'EXPLORE' (CTRL + SPACE), and 'SHARE...'.

Spring Reactive е non-blocking - //нишката няма да се задържи и ще бъде release-вана и ще може тя да изчака, за да се експонира за обслужването на някой друг request.

application.yml

```
server:
 port: 8005
```

Rest Template Reactive Demo + Jackson parser (part of Spring MVC)

<https://reqres.in/>

GET this: <https://reqres.in/api/users/2>

```
{
 "data": {
 "id": 2,
 "email": "janet.weaver@reqres.in",
 "first_name": "Janet",
 "last_name": "Weaver",
 "avatar": "https://reqres.in/img/faces/2-image.jpg"
 },
 "support": {
 "url": "https://reqres.in/#support-heading",
 "text": "To keep ReqRes free, contributions towards server costs are appreciated!"
 }
}
```

```
import bg.softuni.webclient.model.UserDTO;
import org.springframework.boot.CommandLineRunner;
import org.springframework.http.MediaType;
import org.springframework.stereotype.Component;
import org.springframework.web.reactive.function.client.WebClient;
```

```
@Component
```

```

public class WebClientDemo implements CommandLineRunner {
 @Override
 public void run(String... args) {

 WebClient client = WebClient.create("https://reqres.in/");
 UserDTO user = client.get()
 .uri("api/users/2")
 .accept(MediaType.APPLICATION_JSON)
 .retrieve()
 .bodyToFlux(UserDTO[].class) - масив от обекти
 .bodyToMono(UserDTO.class)//връща само 1 или 0 обекти
 .block(); //нишката няма да се задържи и ще бъде release-вана и ще може да
 изчака, за да се expose-не за обслужването на някой друг request

 System.out.println(user);
 }
}

import com.fasterxml.jackson.annotation.JsonProperty;
import com.fasterxml.jackson.annotation.JsonInclude;

@JsonInclude(JsonInclude.Include.NON_NULL)
public class UserDTO {
 @JsonProperty("data") //ако името съвпада, то няма нужда
 private DataDTO data;
 @JsonProperty("support") //ако името съвпада, то няма нужда
 private SupportDTO support;

 public UserDTO() {
 }

 @JsonProperty("data") //ако името съвпада, то няма нужда
 public DataDTO getData() {
 return data;
 }

 @JsonProperty("data") //ако името съвпада, то няма нужда
 public void setData(DataDTO data) {
 this.data = data;
 }

 @JsonProperty("support") //ако името съвпада, то няма нужда
 public SupportDTO getSupport() {
 return support;
 }

 @JsonProperty("support") //ако името съвпада, то няма нужда
 public void setSupport(SupportDTO support) {
 this.support = support;
 }

 @Override
 public String toString() {
 return "User{" +
 "data=" + data +

```

```
 ", support=" + support +
 '}';
}

import com.fasterxml.jackson.annotation.JsonInclude;
import com.fasterxml.jackson.annotation.JsonProperty;

@JsonInclude(JsonInclude.Include.NON_NULL)
public class DataDTO {
 @JsonProperty("id") //ако името съвпада, то няма нужда
 private Integer id;
 @JsonProperty("email") //ако името съвпада, то няма нужда
 private String email;
 @JsonProperty("first_name") //ако името съвпада, то няма нужда
 private String firstName;
 @JsonProperty("last_name") //ако името съвпада, то няма нужда
 private String lastName;
 @JsonProperty("avatar") //ако името съвпада, то няма нужда
 private String avatar;

 public DataDTO() {
 }

 @JsonProperty("id") //ако името съвпада, то няма нужда
 public Integer getId() {
 return id;
 }

 @JsonProperty("id") //ако името съвпада, то няма нужда
 public void setId(Integer id) {
 this.id = id;
 }

 @JsonProperty("email") //ако името съвпада, то няма нужда
 public String getEmail() {
 return email;
 }

 @JsonProperty("email") //ако името съвпада, то няма нужда
 public void setEmail(String email) {
 this.email = email;
 }

 @JsonProperty("first_name") //ако името съвпада, то няма нужда
 public String getFirstName() {
 return firstName;
 }

 @JsonProperty("first_name") //ако името съвпада, то няма нужда
 public void setFirstName(String firstName) {
 this.firstName = firstName;
 }

 @JsonProperty("last_name") //ако името съвпада, то няма нужда
```

```

public String getLastName() {
 return lastName;
}

@JsonProperty("last_name") //ако името съвпада, то няма нужда
public void setLastName(String lastName) {
 this.lastName = lastName;
}

@JsonProperty("avatar") //ако името съвпада, то няма нужда
public String getAvatar() {
 return avatar;
}

@JsonProperty("avatar") //ако името съвпада, то няма нужда
public void setAvatar(String avatar) {
 this.avatar = avatar;
}

@Override
public String toString() {
 return "Data{" +
 "id=" + id +
 ", email='" + email + '\'' +
 ", firstName='" + firstName + '\'' +
 ", lastName='" + lastName + '\'' +
 ", avatar='" + avatar + '\'' +
 '}';
}
}

```

```

import com.fasterxml.jackson.annotation.JsonInclude;
import com.fasterxml.jackson.annotation.JsonProperty;

@JsonInclude(JsonInclude.Include.NON_NULL)
public class SupportDTO {

 @JsonProperty("url") //ако името съвпада, то няма нужда
 private String url;
 @JsonProperty("text") //ако името съвпада, то няма нужда
 private String text;

 @JsonProperty("url") //ако името съвпада, то няма нужда
 public String getUrl() {
 return url;
 }

 @JsonProperty("url") //ако името съвпада, то няма нужда
 public void setUrl(String url) {
 this.url = url;
 }

 @JsonProperty("text") //ако името съвпада, то няма нужда
 public String getText() {
 return text;
 }
}

```

```

}

@JsonProperty("text") //ако името съвпада, то няма нужда
public void setText(String text) {
 this.text = text;
}

@Override
public String toString() {
 return "Support{" +
 "url='" + url + '\'' +
 ", text='" + text + '\'' +
 '}';
}
}

```

## 9.5. DOM Manipulations – plain Vanilla JS

### Creating DOM Elements

- Create with document.createElement

```
let p = document.createElement('p');
```

- Append text to the <p> element

```
let text = document.createTextNode('Random Text');
p.appendChild(text);
```

- Text added to textContent will be escaped.

- Text added to innerHTML will be parsed and turned into actual HTML elements - beware of XSS attacks!

```
let list = document.createElement('ul');
let liPeter = document.createElement('li');
liPeter.textContent = 'Peter';
list.appendChild(liPeter);
let liMaria = document.createElement('li');
liMaria.innerHTML = 'Maria';
list.appendChild(liMaria);

document.body.appendChild(list);
```

```

▼
 Peter
 ▼
 Maria


```

### Deleting DOM Elements

- To remove an HTML element, you must know his parent

```
<div id='div1'>
 <p id='p1'>This is a paragraph.</p>
 <p id='p2'>This is another paragraph.</p>
</div>
```

```
let parent = document.getElementById('div1');
let child = document.getElementById('p1');
parent.removeChild(child);
```

## 9.6. Browser Events and DOM Events – plain Vanilla JS


### Handling Events in JS

- Browsers send events to notify the JS code of interesting things that have taken place

```
<div id='text'>Some text</div>
```

```
let div = document.getElementById('text');
div.onmouseover = function(event) {
 event.target.style.border = '3px solid green';
}
div.onmouseout = function() {
 this.style.border = ''; // this === event.target
}
```

### Event Types in DOM API



Focus event – когато имаме поле input и пишем в него

### Attach / Remove Events

- Attach an event to an element.

```
let textbox = document.createElement('input');
textbox.type = 'text';
textbox.value = 'I am a text box';
document.body.appendChild(textbox);
textbox.addEventListener('focus', focusHandler);
```

- Remove an event.

```
function focusHandler(event) {
 textbox.value = 'Event handler removed';
 textbox.removeEventListener('focus', focusHandler);
}
```

## Multiple Events

- The **addEventListener()** method also allows you to add many events to the same element, without overwriting existing events:

```
element.addEventListener('click', function);
element.addEventListener('click', myFunction);
element.addEventListener('mouseover', mySecondFunction);
element.addEventListener('mouseout', myThirdFunction);
```

- Note that you don't use the 'on' prefix for the event; use 'click' instead of 'onclick'.

## 9.7. Fetch API

### Fetch API

- Fetch provides a generic definition of Request and Response objects
- Fetch API allows you to make network requests similar to **XMLHttpRequest** (XHR).
- The response of a **fetch()** is a Stream object.

Example:

```
HomeController.java
@GetMapping('/')
public ModelAndView index(ModelAndView modelAndView) {
 modelAndView.setViewName('index');
 return modelAndView;
}

@GetMapping(value = '/fetch', produces = 'application/json')
@ResponseBody
public Object fetchData() {
 return new ArrayList<Product>() {{
 add(new Product(){
 setName('Chewing Gum');
 setPrice(new BigDecimal(1.00));
 setBarcode('133242556222');
 });
 ...
 }};
}

public class Product {
 private String name;
 private BigDecimal price;
 private String barcode;

 // Getters & Setters
 ...
}
```

- Now let's head to the view
  - There is no need for a separate .js file for one-time use

### index.html

```

...
<div class='container-fluid'>
 <h1 class='text-center mt-5 display-1'>Data Fetch</h1>
 <div class='data-container mt-5'></div>
 <div class='button-holder mt-5'>
 <button id='fetch-button' class='btn btn-info'>Fetch Data</button>
 <button id='clear-button' class='btn btn-secondary'>Clear Data</button>
 </div>
</div>
<script>
 // jQuery Event handlers
 $('#fetch-button').click(() => {...}); // Fetch and render the data
 $('#clear-button').click(() => $('.data-container').empty()); // Clear the data
</script>

$('#fetch-button').click(() => {
 fetch('http://localhost:8000/fetch') // Fetch the data (GET request)
 .then((response) => response.json()) // Extract the JSON from the Response
 .then((json) => json.forEach((x, y) => { // Render the JSON data to the HTML
 if (y % 4 === 0) {
 $('.data-container').append('<div class="row d-flex justify-content-around mt-4">');
 }

 let divColumn =
 '<div class="col-md-3">' +
 '<h3 class="text-center font-weight-bold">' + x.name + '</h3>' +
 '<h4 class="text-center">Price: $' + x.price + '</h4>' +
 '<h4 class="text-center">Barcode: $' + x.barcode + '</h4>' +
 '</div>';

 $('.data-container .row:last-child').append(divColumn);
 }));
});

```

## 10. Spring Security


### 10.1. Filters and Interceptors

Филтрите работят върху Servlet-и.

#### Filters

- A filter is an object used to **intercept** the HTTP **requests** and **responses** of your application
- We can perform two operations at two instances:
  - Before sending the **request** to the controller
  - Before sending a **response** to the client
  - Всеки по пътя филтър 1 -> филтър 2 може да променя нещо

## Filters Diagram



## Filter Example

```
import javax.servlet.*;
import javax.servlet.http.HttpServletRequest;
import javax.servlet.http.HttpServletResponse;
import java.io.IOException;

@Component
public class GreetingFilter implements Filter {

 @Override
 public void doFilter(ServletRequest servletRequest, ServletResponse servletResponse,
 FilterChain filterChain) throws IOException, ServletException {
 HttpServletRequest request = (HttpServletRequest) servletRequest;
 HttpServletResponse response = (HttpServletResponse) servletResponse;

 request.getSession().setAttribute('name', 'Pesho');

 filterChain.doFilter(request, response);
 }
}

import javax.servlet.http.HttpSession;


@Controller
public class HomeController {

 @GetMapping('/')
 public ModelAndView index(ModelAndView modelAndView, HttpSession session) {
 modelAndView.setViewName('index');
 modelAndView.addObject('name', session.getAttribute('name'));

 return modelAndView;
 }
}
```

```
 }
}
```

```
index.html
<!DOCTYPE html>
<html lang='en' xmlns='http://www.w3.org/1999/xhtml' xmlns:th='http://www.thymeleaf.org'>
<head>
 <meta charset='UTF-8'>
 <title>Filter Demo</title>
</head>
<body>
 <h1 th:text='|Hello, ${name}!|'></h1>
</body>
</html>
```




## Hello, Pesho!

### Interceptor

- A **Filter** is used in the **web layer only** as it is defined in web.xml. We can not use it out of web context
- While Spring **Interceptors** are defined in the **Spring context** за прихващане на неща
- The **interceptor** include **three main methods**:
  - **preHandle**: executed before the execution of the target resource – преди да пристигне http заявката до контролера
  - **afterCompletion**: executed after the execution of the target resource (after rendering the view) – след като http заявката е минала през контролера
  - **postHandle**: Intercept the execution of a handler – извиква се най-накрая

Interceptors можем да използваме за **статистика**, за поставяне на http headers, за филтриране на http headers

## Interceptor Diagram



## Interceptor Example

```
import org.springframework.web.servlet.HandlerInterceptor;
import javax.servlet.FilterChain;
import javax.servlet.ServletException;
import javax.servlet.http.HttpServletRequest;
import javax.servlet.http.HttpServletResponse;
import java.io.IOException;

@Component
public class LoggingInterceptor implements HandlerInterceptor {

 @Override
 public boolean preHandle(HttpServletRequest request, HttpServletResponse response,
 FilterChain filterChain, Object handler) throws IOException, ServletException {
 //Log some information ...
 //да си пазим статистика колко request-a и response-a са минали примерно.

 return true;
 }
}
```

## Register Interceptor in Configuration

- To use interceptors we need to register them

```
import org.springframework.context.annotation.Configuration;
import org.springframework.web.servlet.config.annotation.InterceptorRegistry;
import org.springframework.web.servlet.config.annotation.WebMvcConfigurer;
```

```
@Configuration
public class WebConfiguration implements WebMvcConfigurer {
```

```

private final MyInterceptor myInterceptor;

public WebConfiguration(MyInterceptor myInterceptor) {
 this.myInterceptor = myInterceptor;
}

@Override
public void Spring Security (InterceptorRegistry registry) {
 registry.addInterceptor(myInterceptor);
}
}

```

## 10.2. Spring Security

What is Spring Security?


- A **powerful** and **highly customizable** authentication and access-control framework
- It is the de-facto **standard** for securing **Spring-based** applications
- Focuses on providing both **authentication** and **authorization** to Java applications
  
- **Authentication**
  - Who is logged in
  

  
- **Authorization**
  - What you are allowed to do

**ACCESS  
DENIED**

Spring Security Filter Chain

Spring Security реално е един филтър.




#### Security Context and Authentication

- At the heart of Spring Security's authentication model is the **SecurityContextHolder**
- It contains the **SecurityContext**



## Spring Security Mechanism



## Spring Security Maven/Gradle

*build.gradle*

```
implementation 'org.springframework.boot:spring-boot-starter-security'
implementation 'org.thymeleaf.extras:thymeleaf-extras-springsecurity5'
```

*pom.xml*

```
<dependency>
<groupId>org.springframework.boot</groupId>
<artifactId>spring-boot-starter-security</artifactId>
</dependency>

<dependency>
 <groupId>org.thymeleaf.extras</groupId>
 <artifactId>thymeleaf-extras-springsecurity5</artifactId>
</dependency>
```

## Spring Security Configuration

*Deprecated*

- Extending the **WebSecurityConfigurerAdapter** class - deprecate-HAT

```
@Configuration
@EnableWebSecurity //Can be omitted because of WebSecurityConfigurerAdapter
public class SecurityConfiguration extends WebSecurityConfigurerAdapter {
//Configuration goes here
```

- **Override configure(HttpSecurity http)**

```
@Override
protected void configure(HttpSecurity http) throws Exception {
 http
```

```

 .authorizeRequests() // Authorize Requests
 .antMatchers('/', '/register').permitAll() // Permit Routes
 .anyRequest().authenticated() // Require Authentication
 }
}

}

```

*Up-to-Date way*

- Creating the **SecurityFilterChain** bean.

```

@Configuration
public class SecurityConfiguration {
 @Bean
 public SecurityFilterChain filterChain(HttpSecurity httpSecurity) {
 httpSecurity
 .authorizeRequests() // Authorize Requests
 .antMatchers('/', '/register').permitAll() // Permit Routes
 .anyRequest().authenticated() // Require Authentication
 ...
 return http.build();
 }
}

```

Registration User

*With interface*

```

public interface UserDetails {
 Collection<? extends GrantedAuthority> getAuthorities();

 String getPassword();

 String getUsername();

 boolean isAccountNonExpired();

 boolean isAccountNonLocked();

 boolean isCredentialsNonExpired();

 boolean isEnabled();
}

@Entity
public class UserEntity implements UserDetails {
 private String username;
 private String password;
 private boolean isAccountNonExpired;
 private boolean isAccountNonLocked;
 private boolean isCredentialsNonExpired;
 private boolean isEnabled;
 private Set<Role> authorities;
}

```

```

UserDetails ud =
User.

```

```
 withUsername(..).
password(..).
authorities(..).
build();
```

## Registration – Roles

- Implementing the **GrantedAuthority** interface.

```
import org.springframework.security.core.GrantedAuthority;

public class Role implements GrantedAuthority {
 private String authority;

 @Override
 public String getAuthority() {
 return null;
 }
}
```

## SimpleGrantedAuthority

- If we want, we can use **SimpleGrantedAuthority** instead of creating Role class
- Is a basic concrete **implementation** of a **GrantedAuthority**
- Stores a **String representation** of an **authority** granted to the Authentication object

## UserDetailsService

- Implementing the **UserDetailsService** interface.

```
import org.springframework.security.core.userdetails.UserDetails;
import org.springframework.security.core.userdetails.UserDetailsService;

@Service
public class UserDetailsServiceImpl implements UserDetailsService {
 public UserDetailsServiceImpl() {
 ...
 }

 @Override
 public UserDetails loadUserByUsername(String userName) {
 // get the user and map to UserDetails
 }
}
```

```
@Autowired
private BCryptPasswordEncoder bCryptPasswordEncoder

public void register(RegisterModel registerModel) {
 bCryptPasswordEncoder.encode(password));
}
```

```

}

- Expose as a bean

@Configuration
public class SecurityConfig {

 @Bean
 public UserDetailsService userDetailsService(UserRepository
 userRepository) {
 return new UserDetailsServiceImpl(userRepository);
 }

 @Bean
 public PasswordEncoder passwordEncoder() {
 return new Pbkdf2PasswordEncoder();
 }

}

...

```

#### Register User In memory with overriding configure

Едва ли ще се наложи в практиката да ги съхраняваме в паметта register и login

```

@Override
protected void configure(AuthenticationManagerBuilder auth) throws Exception {
 auth
 .inMemoryAuthentication().withUser("user")
 .password(bCryptPasswordEncoder.encode("user"))
 .roles("USER")

 .and().withUser("admin").password(bCryptPasswordEncoder.encode("admin")).roles("ADMIN")
}
...
```

#### Registration – Configuration

- Disabling **CSRF** protection temporarily.

```

@Configuration
public class SecurityConfiguration {
 @Bean
 public SecurityFilterChain filterChain(HttpSecurity httpSecurity){
 //Configuration goes here
 @Bean
 public SecurityFilterChain filterChain(HttpSecurity httpSecurity) {
 http.authorizeRequests()
 .antMatchers('/', '/register').permitAll()
 .anyRequest().authenticated();

 ...
 return http.build();
 }

 @Override

```

```

protected void configure(HttpSecurity http) throws Exception {
 http
 .and()
 .csrf()
 .disable();
}
}
}

```

## Login Mechanism



## Login – Configuration

*SecurityConfiguration.java*

```

.and()
 .formLogin().loginPage('/login').permitAll()
 .usernameParameter('username')
 .passwordParameter('password')

```

*login.html*

```

<input type='text' name='username' />
<input type='text' name='password' />

```

## Login – UserService

```

@Service
public class UserServiceImpl implements UserDetailsService {
 // Some userServiceImpl logic
 @Override
 public UserDetails loadUserByUsername(String username) throws UsernameNotFoundException {
 //...
 }
}

```

## Login – Controller

```
@Controller
public class LoginController {
 @GetMapping('/login')
 public String getLoginPage(@RequestParam(required = false) String error, Model model) {
 if (error != null) {
 model.addAttribute('error', 'Error');
 }

 return 'login';
 }
}
```

## Logout

```
SecurityConfiguration.java
.and()
.logout().logoutSuccessUrl('/login?logout').permitAll()
```

## Remember Me

```
SecurityConfiguration.java
.and()
.rememberMe()
.rememberMeParameter('remember')
.key('remember Me Encryption Key')
.rememberMeCookieName('rememberMeCookieName')
.tokenValiditySeconds(10000)
```

## login.html

```
<input name='remember' type='checkbox' />
```

## Principal

- This is the **currently logged user**

Можем да го инжектнем само в контролера

## UserController.java

```
@GetMapping('/user')
public String getUser(Principal principal) {
 System.out.println(principal.getName());
 return 'user';
}
```

## Demo using principal

```
import org.springframework.security.core.GrantedAuthority;
import org.springframework.security.core.userdetails.User;

import java.util.Collection;

public class MobileUser extends User {
```

```

 public MobileUser(String username, String password, Collection<? extends GrantedAuthority>
authorities) {
 super(username, password, authorities);
}

 public MobileUser(String username, String password, boolean enabled, boolean
accountNonExpired, boolean credentialsNonExpired, boolean accountNonLocked, Collection<? extends
GrantedAuthority> authorities) {
 super(username, password, enabled, accountNonExpired, credentialsNonExpired,
accountNonLocked, authorities);
}

//some own methods
 public String getUserIdentifier(){
 return getUsername();
 }
}

import bg.softuni.mobilele.model.entity.UserEntity;
import bg.softuni.mobilele.repository.UserRepository;
import bg.softuni.mobilele.user.MobileUser;
import org.springframework.security.core.GrantedAuthority;
import org.springframework.security.core.authority.SimpleGrantedAuthority;
import org.springframework.security.core.userdetails.User;
import org.springframework.security.core.userdetails.UserDetails;
import org.springframework.security.core.userdetails.UserDetailsService;
import org.springframework.security.core.userdetails.UsernameNotFoundException;
import org.springframework.stereotype.Service;

import java.util.List;
import java.util.stream.Collectors;

@Service
public class MobileUserServiceImpl implements UserDetailsService {
 private final UserRepository userRepository;

 public MobileUserServiceImpl(UserRepository userRepository) {
 this.userRepository = userRepository;
 }

 @Override
 public UserDetails loadUserByUsername(String username) throws UsernameNotFoundException {
 UserEntity userEntity = this.userRepository
 .findByUsername(username)
 .orElseThrow(() -> new UsernameNotFoundException("User with name " + username +
" not found."));

 return mapToUserDetails(userEntity);
 }

 //The purpose of this method is to map our user representation (UserEntity)
 // to the user representation in the Spring security world (UserDetails)
 // The only thing that Spring will provide to us is the username.
 // The username will come from the HTML Login form.
 private static UserDetails mapToUserDetails(UserEntity userEntity){
 //Granted authority is the representation of a user role in the Spring world.
}

```

```

 // SimpleGrantedAuthority is an implementation of GrantedAuthority which Spring provides
for our convenience
 // Our representation of role is UserRoleEntity
 List<GrantedAuthority> authorities = userEntity
 .getUserRoles()
 .stream()
 .map(r -> new SimpleGrantedAuthority("ROLE_" + r.getUserRole().name()))
 .collect(Collectors.toList());

 //User is the Spring implementation of UserDetails interface.
 //
 // return new User(
 // userEntity.getUsername(),
 // userEntity.getPassword(),
 // authorities
 //);
 return new MobileleUser(
 userEntity.getUsername(),
 userEntity.getPassword(),
 authorities
);
}
}

```

```

@PostMapping("/offers/add")
public String addOffer(@Valid AddOfferDTO addOfferModel,
 BindingResult bindingResult,
 RedirectAttributes redirectAttributes,
// Principal principal
 @AuthenticationPrincipal MobileleUser user
) {

 if (bindingResult.hasErrors()) {
 redirectAttributes.addFlashAttribute("addOfferModel", addOfferModel);

redirectAttributes.addFlashAttribute("org.springframework.validation.BindingResult.addOfferModel",
", bindingResult);
 return "redirect:/offers/add";
 }

 //Save in the DB
// this.offerService.addOffer(addOfferModel, principal);
 this.offerService.addOffer(addOfferModel, user.getUserIdentifier());

 return "redirect:/offers/all";
}

// public void addOffer(AddOfferDTO addOfferDTO, Principal principal) {
public void addOffer(AddOfferDTO addOfferDTO, String ownerId) {
// OfferAddServiceModel offerAddServiceModel = modelMapper.map(addOfferDTO,
OfferAddServiceModel.class);
// OfferEntity newOffer = modelMapper.map(offerAddServiceModel, OfferEntity.class);
// newOffer.setCreated(Instant.now());
// newOffer.setSeller(userRepository.findByUsername(principal.getName()).orElseThrow());

```

```

// newOffer.setSeller(userRepository.findByUsername(ownerId).orElseThrow());
// ModelEntity model = modelRepository.getById(addOfferDTO.getModelId());
// newOffer.setModel(model);

OfferEntity newOffer = this.offerMapper.addOfferDtoToOfferEntity(addOfferDTO);
//TODO - current user should be logged in

Optional<UserEntity> seller = userRepository.findById(1L);
ModelEntity model = modelRepository.findById(addOfferDTO.getModelId()).orElseThrow();
ModelEntity model = modelRepository.findById(ownerId).orElseThrow();

// OfferEntity newOffer = modelMapper.map();

newOffer.setModel(model);
newOffer.setSeller(seller.get());

offerRepository.save(newOffer);
}

```

Pre / Post Authorize – на ниво метод – **както Controller-ите, така и Service-те и техните методи !!!**

- Grant Access to specific methods – **на ниво метод**

За да активираме @PreAuthorize, в класа със Spring security chain, извикваме

**@EnableGlobalMethodSecurity(prePostEnabled = true)**

**SecurityConfiguration.java**

```

@EnableGlobalMethodSecurity(prePostEnabled = true) //Enables PreAuthorize
public class SecurityConfiguration extends WebSecurityConfigurerAdapter {
}

```

**UserService.java**

```

public interface UserService extends UserDetailsService {
 @PreAuthorize('hasRole('ADMIN')') //Requires Admin Role to execute
 void delete();
}

```

No Access Handling

**SecurityConfiguration.java**

```

.and()
 .exceptionHandling().accessDeniedPage('/unauthorized')

```

**AccessController.java**

```

@GetMapping('/unauthorized')
public String unauthorized() {
 return 'unauthorized';
}

```

### 10.3. Cross-Site Request Forgery (подправяне/фалшификация)

Spring CSRF Protection

```
.csrf()
 .csrfTokenRepository(csrfTokenRepository())

private CsrfTokenRepository csrfTokenRepository() {
 HttpSessionCsrfTokenRepository repository = new HttpSessionCsrfTokenRepository();
 repository.setSessionAttributeName("_csrf");
 return repository;
}
```

form.html

```
<input type='hidden' th:name='${_csrf.parameterName}' th:value='${_csrf.token}' />
```

Spring и Thymeleaf автоматично ни изсипва value csrf токен

```
▼<form action="/users/logout" method="post">
 <input type="hidden" name="_csrf" value="5c685dcc-6031-49bb-96aa-607344873b1e" == $>
 <input class="nav-link" type="submit" value="Logout">
</form>
```

Вариант при POST rest заявка и използване на CSRF

При заявка POST, тогава се включва CSRF защитата. Хакера не знае стойността на value csrf токена.

Можем и ръчно да си го сложим, но реално няма смисъл. Spring сам си го търси при post заявки.

```
<input type="hidden" th:name="${_csrf.parameterName}" th:value="${_csrf.token}">
```

Автоматично си го взема токена

```
<meta charset="UTF-8"/>
<meta name="viewport" content="width=device-width, initial-scale=1.0"/>
<meta name="_csrf" th:content="${_csrf.token}" />
<meta name="_csrf_header" th:content="${_csrf.headerName}" />
<title>Pathfinder</title>
<link rel="stylesheet" href="/css/bootstrap.min.css"/>
<link rel="stylesheet" href="/css/styles.css">
<link rel="stylesheet" href="/css/mobile.css">
<link rel="stylesheet" href="https://use.fontawesome.com/releases/v5.15.4/css/all.css"
 integrity="sha384-DyZ88mC6Up2uqS4h/KRgHuoeGwBcD4Ng9SiP4dIRy0EXTlnuz47vAwmegWl">
<link rel="stylesheet" href="https://unpkg.com/leaflet@1.4.0/dist/leaflet.css"
 integrity="sha512-pu8pdR87980ZvTTbP4A8Ix/l+A4dHDD6DGqYW6RQ+9jxkRFcLaxxQb/SJAI">
```

```
@PostMapping(value = "/{routeId}/comments", consumes = "application/json", produces = "application/json")
public ResponseEntity<CommentDisplayView> createComment(@PathVariable("routeId") Long routeId,
 @AuthenticationPrincipal UserDetails userDetails,
 @RequestBody CommentMessageDto commentDto) {
 CommentCreationDto commentCreationDto = new CommentCreationDto(
 userDetails.getUsername(),
 routeId,
 commentDto.getMessage()
);

 CommentDisplayView comment = commentService.createComment(commentCreationDto);

 return ResponseEntity
 .created(URI.create(String.format("/api/%d/comments/%d", routeId, comment.getId())))
 .body(comment);
}
```

Accept a He accepts

```
const routeId = document.getElementById('routeId').value
const commentForm = document.getElementById('commentForm')
commentForm.addEventListener("submit", handleFormSubmission)

const csrfHeaderName = document.head.querySelector('[name=_csrf_header]').content
const csrfHeaderValue = document.head.querySelector('[name=_csrf]').content

const commentContainer = document.getElementById('commentCtnr')

async function handleFormSubmission(event) {
 event.preventDefault()

 const messageVal = document.getElementById('message').value

 fetch(`http://localhost:8080/api/${routeId}/comments`, {
 method: 'POST',
 headers: {
 'Content-Type': 'application/json',
 'Accepts': 'application/json',
 [csrfHeaderName]: csrfHeaderValue
 },
 body: JSON.stringify({
 message: messageVal
 })
 }).then(res => res.json())
 .then(data => {
 document.getElementById('message').value = ""
 commentContainer.innerHTML += comentAsHtml(data)
 })
}

function comentAsHtml(comment) {
 let commentHtml = '<div>\n'
 commentHtml += `<h4>${comment.authorName}</h4>\n'
 commentHtml += `<p>${comment.message}</p>\n'
 commentHtml += '</div>\n'

 return commentHtml
}
```

#### 10.4. Thymeleaf Security

Functionality to Thymeleaf

*pom.xml*

<dependency>

<groupId>org.thymeleaf.extras</groupId>

```

<artifactId>thymeleaf-extras-springsecurity5</artifactId>
</dependency>

build.gradle
implementation 'org.thymeleaf.extras:thymeleaf-extras-springsecurity5'

```

Principal

```

index.html
<!DOCTYPE html>
<html lang='en'
 xmlns:th='http://www.thymeleaf.org'
 xmlns:sec='http://www.thymeleaf.org/extras/spring-security'>
<body>
<div sec:authentication='name'>
 The value of the 'name' property of the authentication object should appear here.
</div>
</body>
</html>

```

```

index.html
<!DOCTYPE html>
<html lang='en'
 xmlns:th='http://www.thymeleaf.org'
 xmlns:sec='http://www.thymeleaf.org/extras/spring-security'>
<body>
<div sec:authorize='hasRole('ADMIN')'>
This content is only shown to administrators.
</div>
</body>
</html>

```

## 10.5. Demo Spring Security 1 – with the deprecated WebSecurityConfigurerAdapter

```

import org.springframework.security.core.GrantedAuthority;
import org.springframework.security.core.authority.SimpleGrantedAuthority;
import org.springframework.security.core.userdetails.User;
import org.springframework.security.core.userdetails.UserDetails;
import org.springframework.security.core.userdetails.UserDetailsService;
import org.springframework.security.core.userdetails.UsernameNotFoundException;
import org.springframework.stereotype.Service;

@Service
public class MobileUserServiceImpl implements UserDetailsService {
 private final UserRepository userRepository;

 public MobileUserServiceImpl(UserRepository userRepository) {
 this.userRepository = userRepository;
 }

 @Override
 public UserDetails loadUserByUsername(String username) throws UsernameNotFoundException {
 UserEntity userEntity = this.userRepository

```

```

 .findByUsername(username)
 .orElseThrow(() -> new UsernameNotFoundException("User with name " + username +
" not found."));

 return mapToUserDetails(userEntity);
}

//The purpose of this method is to map our user representation (UserEntity)
// to the user representation in the Spring security world (UserDetails)
// The only thing that Spring will provide to us is the username.
// The username will come from the HTML login form.
private static UserDetails mapToUserDetails(UserEntity userEntity){
 //Granted authority is the representation of a user role in the Spring world.
 // SimpleGrantedAuthority is an implementation of GrantedAuthority which Spring provides
for our convenience
 // Our representation of role is UserRoleEntity
 List<GrantedAuthority> authorities = userEntity
 .getUserRoles()
 .stream()
 .map(r -> new SimpleGrantedAuthority("ROLE_" + r.getUserRole().name()))
 .collect(Collectors.toList());

 //User is the Spring implementation of UserDetails interface.
 return new User(
 userEntity.getUsername(),
 userEntity.getPassword(),
 authorities
);
}
}

```

```

@Controller
@RequestMapping("/users")
public class UserLoginController {
 private UserService userService;

 public UserLoginController(UserService userService) {
 this.userService = userService;
 }

 @GetMapping("/login")
 public String login() {
 return "auth-login";
 }
}

```

```

import org.springframework.boot.autoconfigure.security.servlet.PathRequest;
import org.springframework.context.annotation.Configuration;
import
org.springframework.security.config.annotation.authentication.builders.AuthenticationBuilder;
import org.springframework.security.config.annotation.web.builders.HttpSecurity;
import
org.springframework.security.config.annotation.web.configuration.WebSecurityConfigurerAdapter;

```

```

import org.springframework.security.core.userdetails.UserDetailsService;
import org.springframework.security.crypto.password.PasswordEncoder;
import org.springframework.security.web.authentication.UsernamePasswordAuthenticationFilter;

@Configuration
public class ApplicationSecurityConfiguration extends WebSecurityConfigurerAdapter {
 private final UserDetailsService userDetailsService;
 private final PasswordEncoder passwordEncoder;

 public ApplicationSecurityConfiguration(UserDetailsService userDetailsService,
 PasswordEncoder passwordEncoder) {
 this.userDetailsService = userDetailsService;
 this.passwordEncoder = passwordEncoder;
 }

 @Override
 protected void configure(HttpSecurity http) throws Exception {
 http
 .authorizeRequests()
 //with this line we allow access to all static resources
 .requestMatchers(PathRequest.toStaticResources().atCommonLocations()).permitAll()

 //the next line allows access to the home page, login page and register page
 .antMatchers("/", "/users/login", "/users/register").permitAll()

 //next, we forbid all other pages for unauthenticated users
 .antMatchers("/**").authenticated()

 .and()
този код валидира Login само за @Controller анотация и само през html формуляр
//configure Login with login html form with two input fields
 .formLogin()

 //our Login page is Located at http://<serveraddress>:<port>/users/login
 .loginPage("/users/login")

 //This is the name of the <input...> in the lofing form where the user enters
her e-mail/username
 // the value of this input will be presented to our User details service
 // those that want to nam ethe inout field differnetly =, e.g. email may change
the value below

 .usernameParameter(UsernamePasswordAuthenticationFilter.SPRING_SECURITY_FORM_USERNAME_KEY)
 //The name of the field that keeps the password

 .passwordParameter(UsernamePasswordAuthenticationFilter.SPRING_SECURITY_FORM_PASSWORD_KEY)
 //The place, where we should Land in case that the login is successfull
 .defaultSuccessUrl("/")
 //the place where I should Land if the login is NOT successfull
 .failureForwardUrl("/users/login-error")
 .and()
 }
}

```

```

.logout()
//This is the URL which Spring will implement for me and will log the user put
.logoutUrl("/users/logout")
//where to go after Logout
.logoutSuccessUrl("/")

//removes the session from the backend server
.invalidateHttpSession(true)

//delete the cookie that references my session
.deleteCookies("JSESSIONID");
}

@Override
protected void configure(AuthenticationManagerBuilder auth) throws Exception {
 // This gives Spring two important components.
 // 1. Our user details service that translates usernames/emails, phone numbers, etc to
UserDetails
 // 2. Password encoder - the component that can decide if the user password matches

 auth
 .userDetailsService(userDetailsService)
 .passwordEncoder(passwordEncoder);

 // registration
 //topsecretpass -> password encoder -> kwrnfwfewkfjkdqwdqwpqfLsw (hashed_password)

 // login
 // (username, raw_password)
 // password_encoder.matches(raw_password, hashed_password)

}
}

<div class="container-fluid">
 <h5 class="text-center text-white mt-5"> Welcome to MobileLeLe,
 <span
 sec:authorize="isAuthenticated()"
 sec:authentication='name'>
 Name of the logged user

 <span
 sec:authorize="!isAuthenticated()"
 sec:authentication='name'>
 Anonymous

 </h5>
</div>

<div class="collapse navbar-collapse" id="navbarSupportedContent">
 <ul class="navbar-nav mr-auto col-12 justify-content-between">
 <li class="nav-item" sec:authorize="isAuthenticated()">

```

```

 All Brands

 <li class="nav-item sec:authorize="isAuthenticated()">
 Add Offer

 <li class="nav-item sec:authorize="isAuthenticated()">
 All Offers

 <li class="nav-item dropdown sec:authorize="hasRole('ADMIN')">
 <a class="nav-link dropdown-toggle" href="/" id="navbarDropdown" role="button"
 data-toggle="dropdown" aria-haspopup="true" aria-expanded="false">
 Admin

 <div class="dropdown-menu" aria-labelledby="navbarDropdown">
 Action
 Another action
 <div class="dropdown-divider"></div>
 Something else here
 </div>

 <!-- Logout start -->
 <li class="nav-item sec:authorize="isAuthenticated()">
 <div class="form-inline my-2 my-lg-0 border px-3">
 <div class="text-white">Welcome, <th:block
sec:authentication='name'></th:block></div>
 <form th:action="@{/users/logout}" th:method="post">
 <input class="nav-link" type="submit" value="Logout">
 </form>
 </div>

 <li class="nav-item sec:authorize="!isAuthenticated()">
 Register

 <li class="nav-item sec:authorize="!isAuthenticated()">
 Login

</div>

```

## 10.6. Demo Spring Security 2 – with SecurityFilterChain

```

import bg.softuni.security.model.enums.UserRoleEnum;
import bg.softuni.security.repository.UserRepository;
import bg.softuni.security.service.AppUserDetailsService;
import org.springframework.boot.autoconfigure.security.servlet.PathRequest;
import org.springframework.context.annotation.Bean;
import org.springframework.context.annotation.Configuration;
import org.springframework.security.config.annotation.web.builders.HttpSecurity;
import org.springframework.security.core.userdetails.UserDetailsService;
import org.springframework.security.crypto.password.PasswordEncoder;
import org.springframework.security.crypto.password.Pbkdf2PasswordEncoder;
import org.springframework.security.web.SecurityFilterChain;
import org.springframework.security.web.authentication.UsernamePasswordAuthenticationFilter;

```

```

@Configuration
public class SecurityConfiguration {

 //Here we have to expose 3 things:
 // 1. PasswordEncoder
 // 2. SecurityFilterChain
 // 3. UserDetailsService

 @Bean
 public PasswordEncoder passwordEncoder() {
 return new Pbkdf2PasswordEncoder();
 }

 @Bean
 public SecurityFilterChain filterChain(HttpSecurity http) throws Exception {

 http.
 // define which requests are allowed and which not
 authorizeRequests().
 // everyone can download static resources (css, js, images)
 requestMatchers(PathRequest.toStaticResources().atCommonLocations()).permitAll().
 // everyone can login and register
 antMatchers("/", "/users/login", "/users/register").permitAll().
 // pages available only for moderators
 antMatchers("/pages/moderators").hasRole(UserRoleEnum.MODERATOR.name()).
 // pages available only for admins
 antMatchers("/pages/admins").hasRole(UserRoleEnum.ADMIN.name()).
 // all other pages are available for logger in users
 anyRequest().
 authenticated().
 and().
 този код надолу валидира Login само за @Controller анотация и само през html формуляр
 // configuration of form login
 formLogin().
 // the custom login form
 LoginPage("/users/login").
 // the name of the username form field

 usernameParameter.UsernamePasswordAuthenticationFilter.SPRING_SECURITY_FORM_USERNAME_KEY).
 // the name of the password form field

 passwordParameter.UsernamePasswordAuthenticationFilter.SPRING_SECURITY_FORM_PASSWORD_KEY).
 // where to go in case that the login is successful
 defaultSuccessUrl("/") .
 // where to go in case that the login failed
 failureForwardUrl("/users/login-error").
 and().
 // configure logout
 logout().
 // which is the Logout url
 logoutUrl("/users/logout").
 // invalidate the session and delete the cookies
 invalidateHttpSession(true).
 deleteCookies("JSESSIONID");
 }
}

```

```

 return http.build();
}

@Bean
public UserDetailsService userDetailsService(UserRepository userRepository) {
 return new AppUserDetailsService(userRepository);
}
}

import bg.softuni.security.model.entity.UserEntity;
import bg.softuni.security.model.entity.UserRoleEntity;
import bg.softuni.security.repository.UserRepository;
import org.springframework.security.core.GrantedAuthority;
import org.springframework.security.core.authority.SimpleGrantedAuthority;
import org.springframework.security.core.userdetails.User;
import org.springframework.security.core.userdetails.UserDetails;
import org.springframework.security.core.userdetails.UserDetailsService;
import org.springframework.security.core.userdetails.UsernameNotFoundException;

// NOTE: This is not annotated as @Service, because we will return it as a bean.
public class AppUserDetailsService implements UserDetailsService {
 private final UserRepository user_repository;

 public AppUserDetailsService(UserRepository user_repository) {
 this.user_repository = user_repository;
 }

 @Override
 public UserDetails loadUserByUsername(String username)
 throws UsernameNotFoundException {
 return user_repository.
 findByEmail(username).
 map(this::map).
 orElseThrow(() -> new UsernameNotFoundException("User with email " + username + " not found!"));
 }

 private UserDetails map(UserEntity userEntity) {
 return
 User.builder().
 username(userEntity.getEmail()).
 password(userEntity.getPassword()).
 authorities(userEntity.
 getUserRoles().
 stream().
 map(this::map).
 toList()).
 build();
 }

 private GrantedAuthority map(UserRoleEntity userRole) {
 return new SimpleGrantedAuthority("ROLE_" +
 userRole.
 getUserRole().name());
 }
}

```

```

 }

}

@Controller
public class LoginController {

 @GetMapping("/users/login")
 public String login() {
 return "auth-login";
 }

 // NOTE: This should be post mapping!
 @PostMapping("/users/login-error")
 public String onFailedLogin(
 @ModelAttribute.UsernamePasswordAuthenticationFilter.SPRING_SECURITY_FORM_USERNAME_KEY)
String userName,
 RedirectAttributes redirectAttributes) {

 redirectAttributes.addFlashAttribute(UsernamePasswordAuthenticationFilter.SPRING_SECURITY_FORM_U
SERNAME_KEY, userName);
 redirectAttributes.addFlashAttribute("bad_credentials",
 true);

 return "redirect:/users/login";
}
}

```

## 10.7. Demo interceptor

```

@Configuration
public class ApplicationSecurityConfiguration extends WebSecurityConfigurerAdapter {
 private final UserDetailsService userDetailsService;
 private final PasswordEncoder passwordEncoder;

 public ApplicationSecurityConfiguration(UserDetailsService userDetailsService,
 PasswordEncoder passwordEncoder) {
 this.userDetailsService = userDetailsService;
 this.passwordEncoder = passwordEncoder;
 }

 @Override
 protected void configure(HttpSecurity http) throws Exception {
 http
 .authorizeRequests()

 //with this line we allow access to all static resources

 .requestMatchers(PathRequest.toStaticResources()).atCommonLocations().permitAll()

 //the next line allows access to the home page, login page and register page
 .antMatchers("/", "/users/login", "/users/register").permitAll()
 //we permit the page below only for admin users
 .antMatchers("/statistics").hasRole(UserRoleEnum.ADMIN.toString())
 }
}

```

```

import bg.softuni.mobilele.web.interceptors.StatsInterceptor;
import org.springframework.context.annotation.Configuration;
import org.springframework.web.servlet.config.annotation.InterceptorRegistry;
import org.springframework.web.servlet.config.annotation.WebMvcConfigurer;

@Configuration
public class WebConfiguration implements WebMvcConfigurer {
 private final StatsInterceptor statsInterceptor;

 public WebConfiguration(StatsInterceptor statsInterceptor){
 this.statsInterceptor = statsInterceptor;
 }

 @Override
 public void addInterceptors(InterceptorRegistry registry) {
 registry.addInterceptor(statsInterceptor);
 }
}

public class StatsView {
 private final int authRequests;
 private final int anonymousRequests;

 public StatsView(int authRequests, int anonymousRequests) {
 this.authRequests = authRequests;
 this.anonymousRequests = anonymousRequests;
 }

 public int getTotalRequests(){
 return authRequests + anonymousRequests;
 }

 public int getAuthRequests() {
 return authRequests;
 }

 public int getAnonymousRequests() {
 return anonymousRequests;
 }
}

import bg.softuni.mobilele.model.view.StatsView;
import org.springframework.security.core.Authentication;
import org.springframework.security.core.context.SecurityContextHolder;
import org.springframework.security.core.userdetails.UserDetails;
import org.springframework.stereotype.Service;

@Service
public class StatsService {
 private int anonymousRequests, authRequests;
 private StatsView statsView;

 public void onRequest(){
 Authentication authentication = SecurityContextHolder

```

```

 .getContext()
 .getAuthentication();

 if (authentication != null && (authentication.getPrincipal() instanceof UserDetails)) {
 authRequests++;
 } else {
 anonymousRequests++;
 }
}

public StatsView getStats(){
 return new StatsView(authRequests, anonymousRequests);
}
}

import bg.softuni.mobilele.service.StatsService;
import org.springframework.stereotype.Component;
import org.springframework.web.servlet.HandlerInterceptor;
import javax.servlet.http.HttpServletRequest;
import javax.servlet.http.HttpServletResponse;

@Component
public class StatsInterceptor implements HandlerInterceptor {
 private final StatsService statService;

 public StatsInterceptor(StatsService statService) {
 this.statService = statService;
 }

 @Override
 public boolean preHandle(HttpServletRequest request, HttpServletResponse response, Object handler) throws Exception {
 statService.onRequest();
 return true;
 }
}

@Controller
public class StatsController {
 private final StatsService statsService;

 public StatsController(StatsService statsService){
 this.statsService = statsService;
 }

 @GetMapping("/statistics")
 public ModelAndView statistics(){
 ModelAndView modelAndView = new ModelAndView();
 modelAndView.addObject("stats", statsService.getStats());
 modelAndView.setViewName("stats");
 return modelAndView;
 }
}

```

```

<div class="container-fluid">
 <h1 class="text-center text-white mt-5"> Welcome to Stats!</h1>
 <h3 class="text-center text-white mt-5">Total requests <th:block
th:text="${stats.getTotalRequests()}"></th:block></h3>
 <h3 class="text-center text-white mt-5">Anonymous requests <th:block
th:text="${stats.getAnonymousRequests()}"></th:block></h3>
 <h3 class="text-center text-white mt-5">Authorized requests <th:block
th:text="${stats.getAuthRequests()}"></th:block></h3>
</div>

```



## 10.8. SecurityExpressionRoot and MethodSecurityExpressionOperations

**Този подход бил най-добрия при използването на Spring security**

Watch lecture of October 2021 – Events for this specific security customized configuration and usage

Watch also the 3d QA and Workshop lecture of June 2022 (1:28)

Implemented also in one of the diploma's project of other students.

public class OwnerSecurityExpressionRoot extends SecurityExpressionRoot implements MethodSecurityExpressionOperations  
 В този клас се задават Boolean методи, които се използват в @PreAuthorize("isOwner(#id)") като аргументи

public class MyMethodSecurityExpressionHandler extends DefaultMethodSecurityExpressionHandler

## 10.9. @Secured анотацията

## 10.10. SecurityLogoutHandler

В моята апликация имам функционалност за смяна на паролата. Питането ми е как може след като променя паролата да накарам потребителя да излезе от профила си и да се логне отново с новата си парола. Има ли възможност това нещо да стане в конфигурацията на Spring Security с GET mapping request.

Iuchob commented 15 days ago

Owner



...

Здрави!

Може да го накараш с браузър редирект, обаче това не е твърде сигурно защото може и да не сработи навсякъде. Не съм го ползвал никого, на мисля, че можеш да го логаутнеш програмно използвайки `SecurityContextLogoutHandler`. Кодът би могъл да изглежда като нещо от сорт на:

```
public void logout(HttpServletRequest request, HttpServletResponse response) {
 Authentication auth = SecurityContextHolder.getContext().getAuthentication();
 if (auth != null) {
 new SecurityContextLogoutHandler().logout(request, response, auth);
 }
}
```

`request` и `response` сринг инжектира в контролерите.

## 11. (HATEOAS) Hypermedia As the Engine of Application State

### 11.1. What is HATEOAS


#### Hypermedia As the Engine of Application State

- **HATEOAS** is a constraint of the REST application architecture
- Keeps the RESTful style architecture **unique from most other network application** architectures
- Uses **hypermedia** to describe what future actions are available to the client
- Allowable actions are derived in the API based on the current application state and returned to the client as a **collection of links**
  
- Client uses these **links to drive further interactions with the API**
- Tells the client what **options** are **available** at a given point in time.
  - Doesn't tell them how each link should be used or exactly what information should be sent
- It is conceptually the same as a **web user browsing** through web pages by clicking the **relevant hyperlinks** to achieve a final goal

<https://dev.to/ragrag/rest-api-maturity-towards-the-glory-of-rest-5cm3>

The **Richardson Maturity Model** developed by [Leonard Richardson](#) is a heuristic that is used to indicate how mature a web service is in regards to its REST Architectural style.

The model identifies Level 3 as the **Glory of REST**



Пример за HATEOAS в PayPal системата

<https://developer.paypal.com/api/rest/responses/>

## 11.2. HATEOAS Example

- Simple response **without** using **HATEOAS**
  - We have a simple REST controller that returns entity in JSON format to the client

```
{ "id" :2, "name": "Pesho", "age":12 }
```

- Using HATEOAS

```
{"id":2,
 "name":"Pesho",
 "age":12,
 "_links":{
 "self": {"href": "http://localhost:8080/students/2"},
 "delete": {"href": "http://localhost:8080/students/delete/2"},
 "update": {"href": "http://localhost:8080/students/update/2"},
 "orders": {"href": "http://localhost:8080/orders/allByStudentId/2"}
}
```

Rel & Href

- **rel** - describes the **relationship** between the Student resource and the URL
  - In example above **rel** is - self, update, delete ...
  - **describes** the **action** that's performed with the link
  - It's important that this **value** is intuitive as it **describes** the purpose of the link
- **href** - the **URL** used to perform the action described in rel

## 11.3. Implement HATEOAS in Spring

### Using HATEOAS in Spring Framework

- Adding hypermedia links to RESTful responses is something you could implement on your own, but ...
- **Spring HATEOAS makes it very easy (actually not so easy 😊)**

```
<dependency>
 <groupId>org.springframework.hateoas</groupId>
 <artifactId>spring-hateoas</artifactId>
 <version>1.1.0.RELEASE</version>
</dependency>
```

```
implementation 'org.springframework.hateoas:spring-hateoas'
```

### Example with H2 In-Memory Database App DB

In-memory database == H2 Database ; след като приключим, то базата данни в паметта изчезва

The screenshot shows the Spring Initializr web application. On the left, there are sections for 'Project' (Maven Project selected), 'Language' (Java selected), and 'Spring Boot' (2.7.1 selected). On the right, under 'Dependencies', the 'H2 Database' dependency is selected. Other listed dependencies include 'Spring Web' (selected) and 'Spring Data JPA'. A red vertical bar highlights the 'H2 Database' section.

```
spring:
 datasource:
 driver-class-name: org.h2.Driver
 username: sa
 password: password
 url: jdbc:h2:mem:testdb

 h2:
 console:
 enabled: true

 jpa:
 defer-datasource-initialization: true
 database-platform: org.hibernate.dialect.H2Dialect
 hibernate:
 ddl-auto: create
```

<http://localhost:8080/h2-console>

The screenshot shows two side-by-side configurations for the H2 console.

**Left Configuration:**

- Saved Settings: Generic H2 (Embedded)
- Setting Name: Generic H2 (Embedded)
- Driver Class: org.h2.Driver
- JDBC URL: jdbc:h2:~/test
- User Name: sa
- Password: (empty)
- Buttons: Connect, Test Connection

**Right Configuration:**

- Saved Settings: Generic H2 (Embedded)
- Setting Name: Generic H2 (Embedded)
- Driver Class: org.h2.Driver
- JDBC URL: jdbc:h2:mem:testdb
- User Name: sa
- Password: (empty)
- Buttons: Connect, Test Connection

The screenshot shows the main H2 Console interface with the following components:

- Left Panel (Database Tree):**
  - jdbc:h2:mem:testdb
  - COURSES (selected)
    - ID (highlighted with a red box)
    - ENABLED
    - NAME
    - PRICE
    - Indexes
  - ORDERS (highlighted with a red box)
    - ID
    - COURSE\_ID
    - STUDENT\_ID
    - Indexes
  - STUDENTS (highlighted with a red box)
    - ID (highlighted with a red box)
    - AGE
    - NAME
    - Indexes
  - INFORMATION\_SCHEMA
  - Users
- Middle Panel (SQL Editor):**
  - Buttons: Run, Run Selected, Auto complete, Clear, SQL statement: SELECT \* FROM COURSES
  - Checkboxes: Auto commit (checked), Max rows: 1000
- Bottom Panel (Help and Commands):**

### Important Commands

	Displays this Help Page
	Shows the Command History
	Executes the current SQL statement
	Executes the SQL statement defined by the text selection
	Auto complete
	Disconnects from the database

### Sample SQL Script

<a href="#">Delete the table if it exists</a> <a href="#">Create a new table with ID and NAME columns</a> <a href="#">Add a new row</a> <a href="#">Add another row</a> <a href="#">Query the table</a> <a href="#">Change data in a row</a> <a href="#">Remove a row</a>	<pre>DROP TABLE IF EXISTS TEST; CREATE TABLE TEST(ID INT PRIMARY KEY,                  NAME VARCHAR(255)); INSERT INTO TEST VALUES(1, 'Hello'); INSERT INTO TEST VALUES(2, 'World'); SELECT * FROM TEST ORDER BY ID; UPDATE TEST SET NAME='Hi' WHERE ID=1; DELETE FROM TEST WHERE ID=2;</pre>
---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

## Prepare Controllers to Work

- If we implementing **RepresentationModel <T>** we can added links directly to our entity
- We need two methods from **WebMvcLinkBuilder**, that's why we must import them

```
import static org.springframework.hateoas.server.mvc.WebMvcLinkBuilder.linkTo;
import static org.springframework.hateoas.server.mvc.WebMvcLinkBuilder.methodOn;
```

Main Work in Controller

*Without implementing RepresentationModel<T>*

```
private Link[] createStudentLinks(StudentDTO studentDTO) {
 List<Link> result = new ArrayList<>();

 // import static org.springframework.hateoas.server.mvc.WebMvcLinkBuilder.LinkTo;
 Link selfLink = LinkTo(methodOn(StudentsController.class)
 .getStudentsById(studentDTO.getId())).withSelfRel();
 result.add(selfLink);

 Link updateLink = LinkTo(methodOn(StudentsController.class).
 update(studentDTO.getId(), studentDTO)).withRel("update");
 result.add(updateLink);

 Link orderLink = LinkTo(methodOn(StudentsController.class).
 getOrders(studentDTO.getId())).withRel("orders");
 result.add(orderLink);

 return result.toArray(new Link[0]);
}
```

HATEOS Demo

```
import bg.softuni.hateos.mapping.StudentMapper;
import bg.softuni.hateos.model.dto.OrderDTO;
import bg.softuni.hateos.model.dto.StudentDTO;
import bg.softuni.hateos.model.entity.OrderEntity;
import bg.softuni.hateos.model.entity.StudentEntity;
import bg.softuni.hateos.repository.StudentsRepository;
import org.springframework.hateoas.CollectionModel;
import org.springframework.hateoas.EntityModel;
import org.springframework.hateoas.Link;
import org.springframework.http.ResponseEntity;
import org.springframework.web.bind.annotation.*;

import java.util.ArrayList;
import java.util.List;
import java.util.stream.Collectors;

import static org.springframework.hateoas.server.mvc.WebMvcLinkBuilder.LinkTo;
import static org.springframework.hateoas.server.mvc.WebMvcLinkBuilder.methodOn;

@RestController
@RequestMapping("/students")
public class StudentsController {
 private final StudentsRepository studentsRepository;
```

```

private final StudentMapper studentMapper;

//WARNING - Normally we never inject repos in the controllers, we do it now only - for fun
and quicker work
public StudentsController(StudentsRepository studentsRepository, StudentMapper
studentMapper) {
 this.studentsRepository = studentsRepository;
 this.studentMapper = studentMapper;
}

//колекции ът HATEOS - използваме CollectionModel<EntityModel<DTO>>
@GetMapping
public ResponseEntity<CollectionModel<EntityModel<StudentDTO>>> getStudents() {
 List<EntityModel<StudentDTO>> allStudents = studentsRepository.findAll()
 .stream()
 .map(s -> studentMapper.mapEntityToDTO(s))
 .map(dto -> EntityModel.of(dto, createStudentLinks(dto)))
 .collect(Collectors.toList());

 return ResponseEntity.ok(CollectionModel.of(allStudents));
}

@GetMapping("/{id}/orders")
public ResponseEntity<CollectionModel<EntityModel<OrderDTO>>> getOrders(@PathVariable("id")
Long studentId) {
 StudentEntity studentEntity = studentsRepository
 .findById(studentId).orElseThrow();

 List<EntityModel<OrderDTO>> orders = studentEntity.getOrders()
 .stream()
 .map(o -> mapFromOrderEntityToOrderDTO(o))
 .map(dto -> EntityModel.of(dto))
 .collect(Collectors.toList());

 return ResponseEntity.ok(CollectionModel.of(orders));
}

private OrderDTO mapFromOrderEntityToOrderDTO(OrderEntity orderEntity) {
 return new OrderDTO().setId(orderEntity.getId())
 .setStudentId(orderEntity.getId())
 .setCourseId(orderEntity.getCourse().getId());
}

@PutMapping("/{id}")
public ResponseEntity<EntityModel<StudentDTO>> update(@PathVariable("id") Long studentId,
StudentDTO studentDTO) {
 //IMPLEMENTATION NOT IMPORTAMT
 return ResponseEntity.ok().build();
}

@GetMapping("/{id}")
public ResponseEntity<EntityModel<StudentDTO>> getStudentsById(@PathVariable("id") Long
studentId) {
 StudentDTO studentDTO = studentsRepository.findById(studentId)
 .map(s -> studentMapper.mapEntityToDTO(s))
 .orElseThrow();
}

```

```

 return ResponseEntity.ok(
 EntityModel.of(studentDTO, createStudentLinks(studentDTO))
);
}

private Link[] createStudentLinks(StudentDTO studentDTO) {
 List<Link> result = new ArrayList<>();

 // import static org.springframework.hateoas.server.mvc.WebMvcLinkBuilder.linkTo;
 Link selfLink = linkTo(methodOn(StudentsController.class)
 .getStudentsById(studentDTO.getId())).withSelfRel();
 result.add(selfLink);

 Link updateLink = linkTo(methodOn(StudentsController.class).
 update(studentDTO.getId(), studentDTO)).withRel("update");
 result.add(updateLink);

 Link orderLink = linkTo(methodOn(StudentsController.class).
 getOrders(studentDTO.getId())).withRel("orders");
 result.add(orderLink);

 return result.toArray(new Link[0]);
}
}

```

Клиента винаги ще си вика следните URLs

JSON	Raw Data	Headers
<a href="#">Save</a> <a href="#">Copy</a> <a href="#">Collapse All</a> <a href="#">Expand All</a> <a href="#">Filter JSON</a>		
<pre> ▼ _embedded:   ▼ studentDTOList:     ▼ 0:       id:          1       name:        "Pesho"       age:         33       ▼ _links:         ▼ self:           href: "http://localhost:8080/students/1"         ▼ update:           href: "http://localhost:8080/students/1"         ▼ orders:           href: "http://localhost:8080/students/1/orders"     ▼ 1:       id:          2       name:        "Ana"       age:         23       ▼ _links:         ▼ self:           href: "http://localhost:8080/students/2"         ▼ update:           href: "http://localhost:8080/students/2"         ▼ orders:           href: "http://localhost:8080/students/2/orders" </pre>		

```

Implementing RepresentationModel<T>
 Student student = this.studentService.findById(id);

 student.add(linkTo(methodOn(StudentsController.class)
 .getStudent(student.getId())).withSelfRel());

 student.add(linkTo(methodOn(StudentsController.class)
 .deleteStudent(student.getId())).withRel("delete"));

 student.add(linkTo(methodOn(StudentsController.class)
 .updateStudent(student.getId(),student)).withRel("update"));

 student.add(linkTo(methodOn(OrdersController.class)
 .findAllOrdersByUserId(student.getId()))
 .withRel("orders"));

 return ResponseEntity.ok(student);

```

## Benefits of Using HATEOAS

- **URL structure** of the API can be **changed without affecting clients**
  - If the URL structure is changed in the service, clients will automatically pick up the new URL structure via hypermedia
- Hypermedia APIs are **explorable**
- Guiding clients toward the next step in the workflow by **providing** only the **links** that are **relevant** based on the current application state

## Negatives of Using HATEOAS

- Adds **extra complexity** to the API, which affects to:
  - **developer** needs to handle the **extra work** of adding links to each response
  - **more complex to build and test** than a vanilla CRUD REST API
  - **clients** also have to deal with the **extra complexity of hypermedia**

## 11.4. HAL Explorer

- To use **HAL Explorer** we need to add **dependency**

```

<dependency>
 <groupId>org.springframework.data</groupId>
 <artifactId>spring-data-rest-hal-explorer</artifactId>
</dependency>

```



Edit Headers

http://localhost:8080/students

Go!

## JSON Properties

```
{
 "page": {
 "size": 20,
 "totalElements": 2,
 "totalPages": 1,
 "number": 0
 }
}
```

## Links

Relation	Name	Title	HTTP	Doc
self				
profile			GET  DELETE	POST  PUT  PATCH

### Embedded Resources

- [students](#)
- [students \[0\]](#)
- [students \[1\]](#)

## Response Status

200 (OK)

## Response Headers

connection	keep-alive
content-type	application/hal+json
date	Mon, 06 Jul 2020 07:16:19 GMT
keep-alive	timeout=60
transfer-encoding	chunked
vary	Origin, Access-Control-Request-Method, Access-Control-Request-Headers

## Response Body

```
{
 "_embedded": {
 "students": [
 {
 "name": "Gosho",
 "age": 1,
 "_links": {
 "self": {
 "href": "http://localhost:8080/students/1"
 },
 "student": {
 "href": "http://localhost:8080/students/1"
 },
 "orders": {
 "href": "http://localhost:8080/students/1/orders"
 }
 }
 },
 {
 "name": "Pesho",
 "age": 12,
 "_links": {
 "self": {
 "href": "http://localhost:8080/students/2"
 },
 "student": {
 "href": "http://localhost:8080/students/2"
 },
 "orders": {
 "href": "http://localhost:8080/students/2/orders"
 }
 }
 }
]
 }
}
```

## 12. Error Handling

Правим error handling-а само по един от начините. Не е добре да го смесваме.

### 12.1. Error Handling

#### Error Handling

- **Error handling** refers to:
  - The **anticipation**, **detection** and **resolution** of programming errors
  - The response & recovery procedures from error conditions
- Error handling is necessary!
  - Improves **user experience**
  - **Optimizes** debugging
  - Facilitates **code maintenance**
  - Ensures **product quality**


#### Error Handling in Spring

- Spring MVC offers **no default** (fall-back) **error page** out of the box, however Spring Boot does
- At start-up, Spring Boot **tries to find** a mapping for **/error**
- Spring MVC provides **several approaches** to error handling
  - Per exception
  - Per controller
  - Globally
- Each option has its own use cases and circumstances
- You can use:
  - **Response-annotated** custom exceptions
  - **Controller-based** handlers on specified actions

- **@ControllerAdvice** annotated classes for global handlers

## Custom error page

- To disable the default **Whitelabel error page** for a Spring Boot application:
  - We must save **error.html** file in resources/templates directory, it'll automatically be picked up by the default Spring **BasicErrorController** – Spring сам си намира default-ната страница за грешки **error.html**



## My own error page

Something went wrong

## ErrorController Interface – да не го правим

- Spring Boot maps **/error** to **BasicErrorController** which populates model with error attributes and then returns '**error**' as the view name
- To replace BasicErrorController with our own custom controller which can map to /error, we need to **implement ErrorController** interface

```
@Controller
public class MyErrorController implements ErrorController {
 @RequestMapping
 @ResponseBody
 public String handle(HttpServletRequest request){
 //Some code ...
 }
}
```

ErrorController е интерфейс, който няма методи няма нищо в него. Това се наричан **markup интерфейс**.

*Другият вариант е да не използваме стандартния `spring /error` И да си направим наш:*

```
server:
 error:
 whitelabel:
```

```

 enabled: false
 path: /error

import org.springframework.boot.web.servlet.error.ErrorController;
import org.springframework.http.HttpStatus;
import org.springframework.stereotype.Controller;
import org.springframework.web.bind.annotation.RequestMapping;

import javax.servlet.RequestDispatcher;
import javax.servlet.http.HttpServletRequest;

@Controller
public class ComputerStoreErrorHandler implements ErrorController {
 @RequestMapping("/error")
 public String handleError(HttpServletRequest request) {
 Object status =
 request.getAttribute(RequestDispatcher.ERROR_STATUS_CODE);

 if (status != null) {
 int statusCode = Integer.parseInt(status.toString());

 if (statusCode == HttpStatus.NOT_FOUND.value()) {
 return "errors/error-404";
 } else if (statusCode == HttpStatus.FORBIDDEN.value()) {
 return "errors/error-403";
 } else if (statusCode == HttpStatus.INTERNAL_SERVER_ERROR.value()) {
 return "errors/error-500";
 }
 //we can implement here more cases if needed
 }

 return "errors/default-error";
 }
}

```

## 12.2. HTTP Status Codes - Annotated Custom Exceptions

### HTTP Status Codes

- Unhandled exceptions during a request produce HTTP 500 response
- Any custom exception can be annotated with **@ResponseStatus**
  - Supports all HTTP status codes
  - **When thrown and unhandled** – produces error page with appropriate response
  - **Било уж важно и тях да ги анотираме, дори ако ползваме @ControllerAdvice** – защото ако попадне този метод директно в Rest JSON заявка, трябвало да бъде анотиран...

```

@ResponseStatus(value = HttpStatus.NOT_FOUND, reason = "Product was not found.")
public class ProductNotFoundException extends RuntimeException {
 // Exception definition
}

```

- And the controller action, throwing the exception

```

@GetMapping("/products/details/{id}")
public ModelAndView productDetails(@PathVariable String id, ModelAndView modelAndView) {
 Product product = this.productRepository.findProductById(id);

 if(product == null) throw new ProductNotFoundException(id);

 modelAndView.addObject("product", product);
 return this.view("product/details", modelAndView);
}
turn this.view("product/details", modelAndView);

```

**The produced HTTP Status & Message**

**The requested URL**

**The exception's message**



14

Не е добре да хвърляме stacktrace – защото издаваме информация на външни лица за нашето приложение.  
**server:**

```

error:
include-stacktrace: always

```

*Demo:*

```

@ResponseStatus(value = HttpStatus.NOT_FOUND, reason = "Product not found!")
public class ProductNotFoundException extends RuntimeException{

}


```

```

//with Annotated Custom Exceptions
@Controller
public class ProductController1 {
 //Error 404
 @GetMapping("/products/{id}/details")
 public String showProductDetails(@PathVariable("id") String productId){
 //retreive product from repository
 //productRepository.findById(productId).orElseThrow(new ProductNotFoundException());
 throw new ProductNotFoundException();
 }

 //Error 500
 @GetMapping("/products/{id}/error")
 public String boom(@PathVariable("id") String productid){
 //something wrong here
 //productRepository.findById(productId).orElseThrow(new ProductNotFoundException());
 throw new NullPointerException();
 }
}

```



## 12.3. Controller-Based Error Handling – още един начин за handle-ване на exceptions

### Controller-Based Error Handling

- You can define Controller-specific Exception Handlers
  - Annotated with `@ExceptionHandler` annotation
  - They work **only** for the **Controller** they are defined in - да
  - Can be annotated with `@ResponseStatus` to convert HTTP status
  - Can accept the **caught exception** as a **parameter**
  - Can return `ModelAndView` or `String` (view name)
  - Can catch **multiple** exception types

```
@ExceptionHandler({PersistenceException.class, TransactionException.class})
public ModelAndView handleDbExceptions(DatabaseException e) { //Parent Exception
 ModelAndView modelAndView = new ModelAndView("error");
 modelAndView.addObject("message", e.getMessage());

 return modelAndView;
}

<html>
<head>...</head>
<body>
<h1>An error occurred while processing your request!</h1>
<p th:text="|Error: ${message}|"></p>
</body>

</html>
```

- Handler methods have **flexible signatures**
  - You can pass in servlet-related objects as parameters
    - `Exception`
    - `public ModelAndView handleDbExceptions(DatabaseException e)`
    - `HttpServletRequest`
    - `HttpServletResponse`
    - `HttpSession`
    - `Principal`
- The **Model** or **ModelAndView** cannot be a parameter though
  - Instead of passing it, you have to setup it inside the method
  - Nevertheless, this is not an issue because the **IoC container** would have done the same (pass an **empty instance**)
- It is not a good practice for full error `stacktraces` to be exposed

- Your users don't need to see ugly exception web-pages
- You may even have security policies which **strictly forbid** any public exception info
- Hide as **much information as possible** and present **User-friendly** error pages
- For **testing** purposes you may view details
  - This may need an **environment** setup \${STACK\_TRACE: never}

*Demo:*

```
//@ResponseStatus(value = HttpStatus.NOT_FOUND, reason = "Product not found!") - когато
използваме Controller-based error handling този ред не важи
public class ObjectNotFoundException extends RuntimeException{
 private final Long productId;

 public ObjectNotFoundException(Long productId) {
 super("Cannot find object with id " + productId);
 this.productId = productId;
 }

 public Long getProductId() {
 return productId;
 }
}

//Controller-Based Error Handling
@Controller
public class ProductController2 {
 @GetMapping("/products/{id}/details")
 public String showProductDetails(@PathVariable("id") Long productId){
 //retrieve product from repository
 //productRepository.findById(productId).orElseThrow(new ProductNotFoundException());
 throw new ObjectNotFoundException(productId);
 }

 //B ProductController2 е дефиниран @ExceptionHandler, и затова работи
 @ExceptionHandler({ObjectNotFoundException.class})
 public ModelAndView handleDbExceptions(ObjectNotFoundException e) { //Parent Exception
 ModelAndView modelAndView = new ModelAndView("product-not-found");
 modelAndView.addObject("productId", e.getProductId());
 //ResponseStatus(value = HttpStatus.NOT_FOUND, reason = "Product not found!") - когато
 използваме Controller-based error handling този ред не важи
 //затова задаваме тук http статуса на отговора
 modelAndView.setStatus(HttpStatus.NOT_FOUND);

 return modelAndView;
 }
}

//Controller-Based Error Handling
@Controller
public class OrdersController {
 @GetMapping("/orders/{id}/details")
 public String showProductDetails(@PathVariable("id") Long orderId){
 throw new ObjectNotFoundException(orderId);
 }
}

//B OrdersController не е дефиниран @ExceptionHandler, и затова не работи handle-ването на
```

*грешката*  
}

## 12.4. Global Application Exception Handling - @ControllerAdvice Classes

Менаджиране на грешки от много на брой контролери

### Global Exception Handling

- There is a way to achieve Global exception handling in Spring
  - This is done through the **@ControllerAdvise** annotation
- Any class annotated with **@ControllerAdvise** turns into an **interceptor-like** controller:
  - Enables **global exception handling**
  - Enables **model enhancement** methods
- In **@ControllerAdvice** classes you still use **@ExceptionHandler**
  - However, this time it refers to the whole application
  - The error handling is not limited only to a specific controller

```
@ControllerAdvice
public class GlobalExceptionHandler {
 public class ErrorInfo {
 public final String url;
 public final String ex;
 public ErrorInfo(String url, Exception ex) {
 this.url = url;
 this.ex = ex.getLocalizedMessage();
 }
 }
}
```

*Demo:*

```
//Global exception handling
@ControllerAdvice
public class GlobalExceptionHandler {
 @ExceptionHandler()
 public ModelAndView handleDbExceptions(ObjectNotFoundException e) {
 ModelAndView modelAndView = new ModelAndView("object-not-found");
 modelAndView.addObject("objectId", e.getObjectId());
 modelAndView.setStatus(HttpStatus.NOT_FOUND);

 // modelAndView.addObject("stack", {...} /* Formatted Stack Trace */);

 return modelAndView;
 }

 // @ResponseStatus(value = HttpStatus.NOT_FOUND, reason = "Product not found!") - когато
 // използваме Global controller error handling можи ред също не важи
 public class ObjectNotFoundException extends RuntimeException{
 private final Long objectId;
```

```

public ObjectNotFoundException(Long objectId) {
 super("Object with id " + objectId + " not found!");
 this.objectId = objectId;
}

public Long getObjectId() {
 return objectId;
}
}

@Controller
public class ProductsController {
 @GetMapping("/products/{id}/details")
 public String showProductDetails(@PathVariable("id") Long objectId){
 throw new ObjectNotFoundException(objectId);
 }
}

@Controller
public class OrdersController {
 @GetMapping("/orders/{id}/details")
 public String showProductDetails(@PathVariable("id") Long orderId){
 throw new ObjectNotFoundException(orderId);
 }
}

```

## Global Exception Handling (REST)

- RESTful requests may also generate unexpected exceptions
  - HTTP Error response codes are a good choice
  - However sometimes you might need more than just a status
    - Customized Error Object, which can be presented on the Client
    - Limited Information returned to the Client
- You can customize the Error Response by introducing a class
  - The Error Handler itself remains the same as in casual web apps

```

public class ErrorInfo {
 public final String url;
 public final String ex;
 public ErrorInfo(String url, Exception ex) {
 this.url = url;
 this.ex = ex.getLocalizedMessage();
 }
}

@ControllerAdvice
public class GlobalRESTExceptionHandler {
 @ResponseStatus(HttpStatus.INTERNAL_SERVER_ERROR)
 @ExceptionHandler({TransactionException.class, PersistenceException.class})
 public @ResponseBody
 ErrorInfo handleRESTErrors(HttpServletRequest req, DbException e) {

```


```

 return new ErrorInfo(req.getRequestURL(), ex);
 }
}

```

### HandlerExceptionResolver Interface

Алтернативен по-дълбок начин за handle-ва на exceptions



*Demo SimpleMappingExceptionResolver*

```

@Configuration
public class ErrorConfig {

 @Bean
 public SimpleMappingExceptionResolver simpleMappingExceptionResolver() {
 SimpleMappingExceptionResolver resolver = new SimpleMappingExceptionResolver();

 Properties properties = new Properties();
 properties.setProperty(NullPointerException.class.getSimpleName(), "npe");

 resolver.setExceptionMappings(properties);

 return resolver;
 }
}

@Controller
public class TestController {

 @GetMapping("/testnpe")
 public String testNPE() {
 if (true) {
 throw new NullPointerException("npe");
 }
 return "npe";
 }
}

```

The screenshot shows a browser window with the URL 'localhost:8080/testnpe'. The page title is 'Ups, we threw NPE!'. The browser toolbar includes icons for back, forward, and refresh, along with a search bar containing the URL. Below the search bar are several bookmarks: 'Bookmarks' (selected), 'Dict', 'Online platforms', 'SoftUni', and 'LC'.

# Ups, we threw NPE!

## 12.5. Exception Techniques Use Cases

### What to Use When?

- Spring offers **many** choices, when it comes to **error** handling
- Be **careful** mixing too **many** of these – **хващаме единия подход в целия проект и само с него**
  - You may not get the behavior you wanted
- There are some semantics, that should be followed, though

### Exception techniques use cases

- For custom exceptions, consider adding **@ResponseStatus** to them
- For Controller-specific exceptions, **@ExceptionHandler** methods should be added alongside the actions
- For all other exceptions, **@ExceptionHandler** methods in **@ControllerAdvice** classes should be implemented

## 13. Events in Spring

### 13.1. Scheduling Tasks

#### Scheduling Tasks

Нещо се тригерира като е включен app-а, без да е необходимо някой user да се е логнал. Изпълнява се анонимно, без да има Principal и логнат user.

- **Scheduling** is a process of executing the tasks for the **specific time** period
- Spring Boot provides a good support to write a scheduler on the Spring applications
- We can specify the time period by different ways:
  - Using **Cron**
  - Using **Fixed Rate**
  - Using **Fixed Delay**

#### Enable Scheduling

- The **@EnableScheduling** annotation is used to **enable** the **scheduler** for your application.
- This annotation should be added into the main Spring Boot application class file.

```
@SpringBootApplication
@EnableScheduling
public class MyApp {
 public static void main(String[] args) {
 SpringApplication.run(MyApp.class, args); } }
```

### Scheduled Task Using Cron

- Java **Cron expressions** are used to configure the instances of **CronTrigger**
- The *cron* expression consists of **six fields**:  
<second><minute><hour><day-of-month><month><day-of-week>  
@Scheduled(cron = "0 5 \* \* \* ?") //each hour on the 5<sup>th</sup> minute  
public void showTimeWithCron(){  
 System.out.println(LocalDateTime.now());  
}

### Scheduled Task Using Fixed Rate

- **Fixed Rate** scheduler is used to execute the tasks at the **specific time**
- It **does not wait** for the completion of **previous task**
- The values should be in **milliseconds**

```
@Scheduled(fixedRate = 5000)
public void showTimeWithFixedRate() {
 System.out.println(LocalDateTime.now());
```

### Scheduled Task Using Fixed Delay

- **FixedDelay** is the time between tasks
- The **initialDelay** is the time after which the task will be executed the first time after the initial delay value
- It **wait** for the completion of **previous task**


```
@Scheduled(fixedDelay = 5000, initialDelay = 10000)
public void showTimeWithFixedDelay() {
 System.out.println(LocalDateTime.now());
```

## 13.2. What Are the Events

### Observer Pattern in JAVA

- Observer pattern is a **behavioral pattern**
- Provides **one object** with a loosely coupled method of **informing multiple objects** of property changes

Софтуни fire-ва event, реализирайки loose coupling – единия студент не знае дали/какво е получил другия студент от Софтуни.



### Events in Spring

- The core of Spring is the **ApplicationContext** (**all beans, components, services, repositories**), which manages the complete **life cycle** of the beans
- The ApplicationContext **publishes** certain types of **events** when **loading** the beans
- Spring's event handling is **single-threaded** so if an event is published, until all the receivers get the message, the **processes** are **blocked** and the flow will not continue

По време на start-up или shut-down на сървъра, то бихме могли да прихватим тези събития.

Spring Build-in Events – които се публикуват от ApplicationContext-a

- **ContextRefreshedEvent**
  - published when the ApplicationContext is either initialized/refreshed
- **ContextStartedEvent**
  - published when the ApplicationContext is started using the **start()**
- **ContextStoppedEvent**
  - published when the ApplicationContext is stopped using the **stop()**
- **ContextClosedEvent**
  - published when the ApplicationContext is closed using the **close()**
- **RequestHandledEvent**
  - Web-specific event telling all beans that an HTTP request has been serviced

### 13.3. Listening for Events

Listening for Events

- There are ways to listen for events in Spring:
  - Implement the **ApplicationListener** interface
    - Which has just one method **onApplicationEvent()**
  - Use **@EventListener()**
    - Annotate on a method

- Some of the events are **published too early** for a listener to be found via annotations and the application context. Then you must **register them** in the Spring Application instance


## Demo using ApplicationListeners

- Implementing **ApplicationListener** interface

### Catching all events

```
@Component
public class DemoApplicationListener implements ApplicationListener {
 private Logger LOGGER = LoggerFactory.getLogger(DemoApplicationListener.class);

 @Override
 public void onApplicationEvent(ApplicationEvent event) {
 LOGGER.info("I have received an Event: {}", event);
 }
}
```



### Catching specific events – for the RestController for example

```
@RestController
public class DemoController {

 @GetMapping("/test")
 public String test(){
 return "test";
 }
}

@Component
public class DemoApplicationListener implements ApplicationListener<ServletRequestHandledEvent> {
 private Logger LOGGER = LoggerFactory.getLogger(DemoApplicationListener.class);

 @Override
 public void onApplicationEvent(ServletRequestHandledEvent event) {
 LOGGER.info("I have received an Event: {}", event);
 }
}
```

The screenshot shows the Java code for a RestController and a specific ApplicationListener for ServletRequestHandledEvent. Below it is the Spring Boot Actuator's 'Console' endpoint. The log output shows multiple entries for ServletRequestHandledEvent, each with client details (IP, port, method, servlet, session, user, time) and a status of [OK].

## Demo using @EventListener annotation

- Use `@EventListener()` with specific event class

```
@RestController
public class DemoController {

 @GetMapping("/test")
 public String test(){
 return "test";
 }
}

@Component
public class Demo2ApplicationListener {
 private Logger LOGGER = LoggerFactory.getLogger(Demo2ApplicationListener.class);
}
```

`@Order(1)` – ако имаме няколко event-listener-и, то контролираме кой event-listener да се изпълни първи, кой втори и т.н.

```
@EventListener(ServletRequestHandledEvent.class)
public void onApplicationEvent(ServletRequestHandledEvent event) {
 LOGGER.info("I have received an Event: {}", event);
}
}
```

## Listening for Multiple Events using @EventListener annotation

- Use `@EventListener(classes = {EventOne.class, EventTwo.class})` to listen for multiple events

```
@EventListener(classes = {MyEventOne.class, MyEventTwo.class})
public void handleTwoEvents(){
 System.out.println("Listens for two events!");
}
```

## Register Events in Spring Application

- Remember that for some event is published too early for a listener to be found and needs to be registered/added

```
@SpringBootApplication
SpringApplication springApp = new SpringApplication(DemoForCustomEventsApplication.class);

springApp.addListeners(new MyEventsClass());
springApp.run(args);
...
```

## Using Lambda When Registering Listener

- Using **lambda expressions** with specific event class

```
@SpringBootApplication
public class DemoForCustomEventsApplication {
 public static void main(String[] args) {
 SpringApplication springApp = new SpringApplication(DemoForCustomEventsApplication.class);
```

```

 springApp.addListeners((ApplicationContextInitializedEvent e) -> {
System.out.println("App context init event"); });
 springApp.run(args);
}
}

```

## Transaction Bound Events

Events-и, които са интегрирани със SpringData:

- The listener of an event to a **phase** of the **transaction**
- Transaction **phases** :
  - **AFTER\_COMMIT** - The default, used to fire the event if the transaction has **completed successfully**
  - **AFTER\_ROLLBACK** - when transaction has **rolled back**
  - **AFTER\_COMPLETION** - when transaction has **completed**
  - **BEFORE\_COMMIT** - used to fire the event right **before** transaction **commit**
- An example of Transaction Bound Event, that will fire before transaction commit

```

@TransactionalEventListener(phase = TransactionPhase.BEFORE_COMMIT)
public void transactionEventListener (MyCustomEvent event) {
 System.out.println("Hit before transaction commit!");
}

```

## 13.4. Creating Custom Event

Най-често можем да си създадем custom event, който да си го прихванем

### Creating Custom Event

- To create and publish our custom event, there is some steps that we need to follow:
  - **Create** our custom **event class** that **extends ApplicationEvent** class
  - **Create publisher**, that publish our new event
  - **Add event listener**, that listens for our new event

### Create Our Custom Event Class

- Create our event class, that extends ApplicationEvent
- ```

public class OrderCreatedEvent extends ApplicationEvent {
    private final String orderId;

    public OrderCreatedEvent(Object source, String orderId) {
        super(source);
        this.orderId = orderId;
    }

    public String getOrderId() {
        return orderId;
    }
}

```

Create Publisher

- Create a publisher that publish our custom event and inject in him the ApplicationEventPublisher object

@Component

```
public class MyPublisher {  
    @Autowired // It is better to inject in constructor  
    private ApplicationEventPublisher appEventPublisher;  
  
    public void publishEvent(String message) {  
        MyCustomEvent myEvent = new MyCustomEvent(this, message);  
        appEventPublisher.publishEvent(myCustomEvent);  
    }  
};
```

Или само може да го inject-нем, като можем да го inject-нем и в Service класа

@Service

```
public class OrderService {  
    private static final Logger LOGGER = LoggerFactory.getLogger(OrderService.class);  
    private final ApplicationEventPublisher eventPublisher;  
  
    @Autowired  
    public OrderService(ApplicationEventPublisher eventPublisher) {  
        this.eventPublisher = eventPublisher;  
    }  
  
    public void createOrder(String productId, int quantity) {  
        LOGGER.info("Creating order for product {} with quantity {}.", productId, quantity);  
  
        // TODO: do some work  
  
        //first creating the event  
        OrderCreatedEvent orderCreatedEvent = new OrderCreatedEvent(  
            OrderService.class.getSimpleName(),  
            productId  
        );  
  
        //then we publish the event  
        eventPublisher.publishEvent(orderCreatedEvent);  
        //we publish the event  
        eventPublisher.publishEvent(orderCreatedEvent);  
    }  
}
```

@Controller

```
public class OrderController {  
    private OrderService orderService;  
  
    public OrderController(OrderService orderService) {  
        this.orderService = orderService;  
    }  
  
    @GetMapping("/dummy/order/create")  
    public String createOrder() {  
        orderService.createOrder("3", 33);  
        return "Hello!";  
    }
```

```
    }  
}
```

Create Listener

- Create listeners, already explain the different ways

```
@Component  
public class Listeners {  
    @EventListener(MyCustomEvent.class)  
    public void listener(MyCustomEvent myCustomEvent) {  
        System.out.printf("Custom event listeners with message -%s!%n", myCustomEvent.getMsg());  
    }  
}
```

```
@Service  
public class BonusPointsService {  
  
    private static final Logger LOGGER = LoggerFactory.getLogger(BonusPointsService.class);  
  
    @EventListener(OrderCreatedEvent.class)  
    public void onOrderCreated(OrderCreatedEvent evt) {  
        LOGGER.info("Adding bonus points to user for order {}", evt.getOrderId());  
    }  
}
```

```
@Service  
public class EmailService {  
    private static final Logger LOGGER = LoggerFactory.getLogger(EmailService.class);  
  
    @EventListener(OrderCreatedEvent.class)  
    public void onOrderCreated(OrderCreatedEvent evt) {  
        LOGGER.info("Sending email to user for order {}", evt.getOrderId());  
    }  
}
```

```
2022-08-11 00:01:34.113 INFO 1396 --- [nio-8080-exec-1] o.s.web.servlet.DispatcherServlet      : Completed initialization in 4 ms  
2022-08-11 00:01:34.151 INFO 1396 --- [nio-8080-exec-1] bg.softuni.events.service.OrderService   : Creating order for product 3 with quantity 33.  
2022-08-11 00:01:34.152 INFO 1396 --- [nio-8080-exec-1] b.s.events.service.BonusPointsService     : Adding bonus points to user for order 3  
2022-08-11 00:01:34.152 INFO 1396 --- [nio-8080-exec-1] bg.softuni.events.service.EmailService      : Sending email to user for order 3  
2022-08-11 00:01:34.152 INFO 1396 --- [nio-8080-exec-1] b.s.events.service.InventoryService       : Decreasing inventory for order 3
```

13.5. Caching Data

Caching

- If you using Spring Boot, then simply use the **spring-boot-starter-cache** dependency
- Under the hood, the starter brings the spring-context-support module
- Използваме при обекти, които се създават сравнително бавно, но се използват сравнително често

```
implementation 'org.springframework.boot:spring-boot-starter-cache'
```

```
<dependency>
```

```
<groupId>org.springframework.boot</groupId>
<artifactId>spring-boot-starter-cache</artifactId>
</dependency>
```

Enable Caching

- When using Spring Boot, the `@EnableCaching` annotation would register the `ConcurrentMapCacheManager`
- No need for separate Bean declaration
- Simply adding the `@EnableCaching` annotation to any of the configuration classes

```
@SpringBootApplication
@EnableCaching
public class CacheApplication {
    public static void main(String[] args) {
        SpringApplication.run(CacheApplication.class, args);
    }
}
```

```
@Configuration
@EnableCaching
public class MyConfig {
    // Some configurations }}
```

@Cacheable

- Use `@Cacheable` to demarcate/разграничавам methods that are cacheable
- Result is stored in the `cache` and on subsequent invocations (with the same arguments), the value in the cache is returned without having to actually execute the method
- the `findAllStudents` method is associated with the cache named `students`

```
@Cacheable("students")
public List<Student> findAllStudents() { //... }
```

Като го извикаме втори път този метод `findAllStudents`, то резултата го връща вече веднага, защото той вече е в cache-а на `cacheManager`-а на Spring.

- Custom Cache Resolution

```
@Cacheable("students", cacheManager = "myCacheManager")
public List<Student> findAllStudents() { //... }
```

- Conditional Caching

```
@Cacheable("student", condition = "#avg > 4")
public List<Student> findStudentsByAvgScore(Double avg) {
    //...
}
```

@CachePut

- When the **cache** needs to be **updated** without interfering with the method execution
- The **method** is **always executed** and its result is placed into the cache
- It supports the same options as **@Cacheable**
- **Заменя старите данни за findAll с новите данни за findAll**

```
@CachePut("students")
public List<Student> findAll() {
    //...
}
```

@CacheEvict

- This process is useful for **removing** stale or unused data from the cache
- Using the **allEntries** attribute to evict/**изваждам** all entries from the cache

```
@CacheEvict(cacheNames="books", allEntries=true)
public void loadStudents() {
    //...
}
```

Customize The auto-configured CacheManager

- To customize the CacheManager we must implement **CacheManagerCustomizer<ConcurrentMapCacheManager>**
- Create Bean CacheManager that returns new **ConcurrentMapCacheManager**

```
@Component
public class MyCacheCustomizer implements CacheManagerCustomizer<ConcurrentMapCacheManager> {
    @Override
    public void customize(ConcurrentMapCacheManager cacheM) {
        cacheM.setCacheNames(asList("students", "courses"));
    }
}
```

14. Aspect Oriented Programming (AOP)

14.1. What is AOP

Aspect Oriented Programming AOP

- **AOP** breaks the program logic into distinct parts (called **concerns**)
- **Cross-cutting concern**
 - Concern that can affect the whole application and **should be centralized in one location**, such as transaction management, authentication, logging, security etc.

Filter е само върху Web Controller-а, Interceptor е върху Spring context, а concerns AOP е само върху определен метод.

Един AOP може да се използва само в рамките на един JVM (Java Virtual Machine)!

14.2. Why We Use AOP

Why Use AOP

- To dynamically add the additional concern before, after or around the actual logic
- Suppose that we have to maintain methods and need to do actions before or after they are called
- We can solve the problem with or without AOP

Problem Example

- Student class with some methods whose activity we want to track

```
public class Student{  
    public void actionOne(){...};  
    public void actionTwo(){...};  
    public void actionThree(){...};  
    public void actionFour(){...};  
    public void actionFive(){...};  
}
```

Problem Solution

- **Solution without AOP**
 - If we need to log all activity of student, we need to write additional code in all tracked methods
 - It leads to the maintenance problem.
- **Solution with AOP**
 - We can define the additional concern like maintaining log, sending notification, etc. in the method of a class
 - Maintenance is easy in AOP

14.3. AOP Concepts and Terminology

Terminologies

- The AOP concepts and terminologies are
 - Join point
 - Advice
 - Pointcut
 - Introduction
 - Target Object
 - Aspect
 - **Interceptor**
 - AOP Proxy
 - Weaving

Join Point

- **Join point**
 - A Join point is any point in your program such as method execution, exception handling, field access etc.
 - We can have many Join points
 - Spring supports only the method execution join point

Advices and Types

- **Represents an action taken by an aspect at a join point**
 - **Before Advice:** it executes before a join point
 - **After Returning Advice:** it executes after a joint point completes normally
 - **After Throwing Advice:** it executes if method exits by throwing an exception
 - **After Advice:** it executes after a join point regardless of join point exit whether normally or exceptional return
 - **Around Advice:** It executes before and after a join point

Pointcut, Introduction, Target Object

- **Pointcut**
 - It is an expression language of AOP that matches join points – можа да опиша някакъв метод
- **Introduction**
 - Introduction of additional method and fields for a type – действието, при което се вкарват допълнителни методи в някакъв клас
- **Target Object**
 - The object i.e. being advised by one or more aspects
 - Also known as **Proxied Object**

Aspect, Interceptor, AOP Proxy, Weaving

- **Aspect**
 - A class that contains advices
- **Interceptor**
 - An aspect that contains only one advice
- **AOP Proxy**
 - Used to implement aspect contracts, created by AOP framework
- **Weaving**
 - The process of linking aspect with other application types or objects to create an advised object.

14.4. Spring AOP AspectJ Annotations

Gradle or Maven

```
implementation 'org.springframework.boot:spring-boot-starter-aop'
```

Spring AOP AspectJ

- The 3 ways to use spring AOP are
 - By Spring 1.2 old style
 - By AspectJ annotation-style
 - The widely used approach is Spring AspectJ Annotation Style
 - By Spring XML configuration-style(schema based)

- There are two ways to use Spring AOP AspectJ implementation
 - By annotation – метода ще се изпълни на който и да е метод от класа Student

```
@Aspect
public class LoggingAspect {
    @Before("execution(* Student.*(..))")
    public void logBefore(JoinPoint joinPoint) {
        ...
    }
}
```

- By XML Configuration

```
<!-- Aspect -->
<bean id="logAspect" class="" />
<aop:config>
    <aop:aspect id="aspectLogging" ref="logAspect" >
        <!-- @Before -->
        <aop:pointcut id="pointCutBefore"
            expression="execution(* Student.*(..))" />
        <aop:before method="logBefore" pointcut-ref="pointCutBefore" />
    </aop:aspect>
</aop:config>
```

AspectJ Annotations in Spring

- **@Aspect**
 - Declares the class as aspect
- **@Pointcut**
 - Declares the pointcut expression
- **@Before**
 - Declares the before advice
 - Applied before calling the actual method
- **@After**
 - Declares the after advice
 - Applied after calling the actual method and before returning result
- **@AfterReturning**
 - Declares the after returning advice
 - Applied after calling the actual method and before returning result, can get the result value in the advice
- **@Around**
 - Declares the around advice
 - Applied before and after calling the actual method
- **@AfterThrowing**
 - Declares the throws advice
 - Applied if actual method throws exception

@Pointcut

- Pointcut is an **expression language** of Spring AOP
- **@Pointcut** annotation is used to define the pointcut
- We can also **refer the pointcut expression by name**

```
@Pointcut("execution(public * *(..))")
private void trackStudentActions() {}
```

Pointcut Expressions – език за описание на сигнатури на методи

- Applied on all the public methods

```
@Pointcut("execution(public * *(..))")
```

- Applied on all methods of Student class

```
@Pointcut("execution(* Student.*(..))")
```

- Applied on all setter methods of Student class

```
@Pointcut("execution(* Student.set*(..))")
```

- Applied on all methods of class that returns an int value

```
@Pointcut("execution(int Student. *(..))")
```

14.5. Examples

Prepare for AOP

```
public class Student{
    public void actionOne(){...};
    public void actionTwo(){...};
    public void actionThree(){...};
    public void actionFour(){...};
    public void actionFive(){...};
}
```

Create Aspect Class

- We need to create a class with **@Aspect**, that contains all advices

```
@Aspect
@Configuration
public class TrackStudent{
    @Pointcut("execution(* Student.*(..))")
    public track(){}

    //Can have more than one pointcuts
    //Here place all advices
}
```

@Before Example

- Add **before advice** to our TrackStudent class

```
@Aspect
@Configuration
public class TrackStudent {
```

```

@Pointcut("execution(* Student.*(..))")
public track(){}
@Before("track()") // Execute before track pointcut
public void beforeAdvice(JoinPoint joinPoint){
    System.out.println("Before advice executed");
}
}

```

@After Example

- Add after advice to our TrackStudent class

```

@Aspect
@Configuration
public class TrackStudent {
    @Pointcut("execution(* Student.*(..))")
    public track{} //for reuse below

    @After("track()") // Execute after track pointcut
    public void afterAdvice(JoinPoint joinPoint){
        System.out.println("After advice executed");
    }
}

```

@AfterReturning Example

- Add after returning advice to our TrackStudent class – при успешно изпълнение на метода

```

...
@AfterReturning(pointcut = "execution(* Student.action())", returning = "result")
public void afterReturning(JoinPoint joinPoint, Object result) {
    System.out.println("AfterReturning advice executed");
    //In AfterReturning we can get the result of pointcut
}
...

```

@Around Example

- Add **around advice** to our TrackStudent class - //around - и преди и след изпълнението на метода

```

@Around("track()")
public Object aroundAdvises(ProceedingJoinPoint pjp) throws Throwable {
    System.out.println("Before calling");
    Object obj = pjp.proceed(); //We need to pass the pjp references in the advice
    method, so that we can proceed the request by calling the proceed method
    System.out.println("After calling");
}

```

@AfterThrowing Example

- Add after throwing advice to our TrackStudent class

```

@AfterThrowing(pointcut = "execution(* Student.action())", throwing = "error")
Public void afterReturning(JoinPoint joinPoint, Throwable error){
    System.out.println("AfterReturning advice executed");
    System.out.println("Exception is: " + error);
    //In AfterThrowing we can get the exception
}

```

Specifying Aspects Ordering

- There are two ways:
 - By annotation

```
@Aspect  
 @Order(0)  
 public class TrackStudent{...}
```

- By implementing interface

```
@Aspect  
 public class TrackStudent implements Ordered {  
     //Override this method  
     public int getOrder(){ return 0; }  
 }
```

14.6. Demos

Demo1 – става извън класа IncredibleMachine

За сменяне на кой Aspect файл да ни е активен ако имаме testing и production например.

Application.yml

```
sample1:  
    enabled: false  
sample2:  
    enabled: true
```

```
@Aspect  
 @Component  
 @ConditionalOnProperty(value = "sample1.enabled", havingValue = "true")  
 public class Sample1Aspect {  
     private static final Logger LOGGER = LoggerFactory.getLogger(Sample1Aspect.class);  
  
     @Pointcut("execution(* bg.softuni.aop.IncredibleMachine.*(..))")  
     void onAllIncredibleMachineMethods() {} //служи за последващо използване  
  
     @Pointcut("execution(* bg.softuni.aop.IncredibleMachine.echo(..))")  
     void onEchoCalled() {  
     }  
  
     @AfterThrowing(pointcut = "execution(* bg.softuni.aop.IncredibleMachine.boom()",  
                 throwing = "error")  
     public void afterThrowing(JoinPoint joinPoint, Throwable error) {  
         LOGGER.error("Ups, I think that the method {} threw Exception and the exception is...",  
                     joinPoint.getSignature(), error);  
     }  
  
     @Before("onAllIncredibleMachineMethods()")  
     public void beforeEachMethod(JoinPoint joinPoint) {  
         LOGGER.info("Before calling method {} with arguments {}",  
                     joinPoint.getSignature(),
```

```

        Arrays.asList(joinPoint.getArgs()));
    }
}

@Component
@ConditionalOnProperty(value = "sample1.enabled", havingValue = "true")
public class Sample1AspectDemo implements CommandLineRunner {
    private static final Logger LOGGER = LoggerFactory.getLogger(Sample1AspectDemo.class);

    private final IncredibleMachine incredibleMachine;

    public Sample1AspectDemo(IncredibleMachine incredibleMachine) {
        this.incredibleMachine = incredibleMachine;
    }

    @Override
    public void run(String... args) throws Exception {
        incredibleMachine.saySomething();
        incredibleMachine.echo("AOP!!!!");

        try {
            incredibleMachine.boom();
        } catch (Exception exc) {
            LOGGER.info("Exception from boom called!");
        }

        LOGGER.info(incredibleMachine.concat("Hello, ", "world!"));
    }
}

@Component
public class IncredibleMachine {
    private static final Logger LOGGER = LoggerFactory.getLogger(IncredibleMachine.class);

    public void saySomething() {
        LOGGER.info("I'm saying something!");
    }

    public void boom() {
        throw new NullPointerException("Ups, I did something wrong!");
    }

    public void echo(String whatToEcho) {
        LOGGER.info("I'm echoing this {}", whatToEcho);
    }

    public String concat(String a, String b) {
        return a + b;
    }
}

```

Demo2

```
@Aspect
@Component
@ConditionalOnProperty(value = "sample2.enabled", havingValue = "true")
public class Sample2Aspect {
    private static final Logger LOGGER = LoggerFactory.getLogger(Sample2Aspect.class);

    @Pointcut("execution(* bg.softuni.aop.IncredibleMachine.concat(..))")
    void onConcat() {
    }

    @Around(value = "onConcat() && args(a, b)") //around - и преди и след изпълнението на метода
    public String onConcat(ProceedingJoinPoint pjp, String a, String b) throws Throwable {
        // Before the execution of concat
        LOGGER.info("The on concat method was called with arguments [{}] and [{}].", a, b);

        var modifiedA = "(" + a + ")";
        var modifiedB = "(" + b + ")";

        // execute the method
        var methodResult = pjp.proceed(new Object[]{modifiedA, modifiedB});

        // modify the result
        return "[" + methodResult + "]";
    }
}

@Component
@ConditionalOnProperty(value = "sample2.enabled", havingValue = "true")
public class Sample2AspectDemo implements CommandLineRunner {
    private static final Logger LOGGER = LoggerFactory.getLogger(Sample2AspectDemo.class);

    private final IncredibleMachine incredibleMachine;

    public Sample2AspectDemo(IncredibleMachine incredibleMachine) {
        this.incredibleMachine = incredibleMachine;
    }

    @Override
    public void run(String... args) throws Exception {
        LOGGER.info(incredibleMachine.concat("Hello, ", "world!"));
    }
}
```

Demo3

```
@Target({ElementType.METHOD})
@Retention(RetentionPolicy.RUNTIME)
public @interface TrackLatency {
    String latency();
}
```

```
@Aspect
@Component
public class Latency {
```

```

@Around(value = "@annotation(TrackLatency)") //around - и преди и след изпълнението на метода
public Object trackLatency(ProceedingJoinPoint pjp, TrackLatency TrackLatency) throws
Throwable {
    String latencyId = TrackLatency.latency();
    DateTimeFormatter formatterToString = DateTimeFormatter.ofPattern("dd-MM-yyyy
HH:mm:ss");

    StopWatch stopWatch = new StopWatch();
    stopWatch.start();
    Object obj = pjp.proceed();
    stopWatch.stop();

    long actualLatency = stopWatch.getLastTaskTimeMillis();
    FileWriter myWriter = new FileWriter("src/main/java/mainPackage/logs/logFile.log",
true);
    myWriter.write(String.format("%s The latency for %s is: %dms%n",
LocalDateTime.now().format(formatterToString), latencyId, actualLatency));
    myWriter.close();
    return obj; //for rest json consuming scenarios
}
}

{@TrackLatency(latency = "fix order")
@PostMapping("/fix/{id}")
@PreAuthorize("hasRole('ROLE_BACK_OFFICE')")
public String fixOrderConfirm(@PathVariable Long id, @Valid
@ModelAttribute("orderFixBindingModel") OrderFixBindingModel orderFixBindingModel,
BindingResult bindingResult, RedirectAttributes
redirectAttributes) throws IOException {
}
}

```

15. Unit testing and integration testing

Не трябва да тестваме passwordencoder - идва от външна библиотека и самата външна библиотека е тествана вече от други хора.

Методите от repository-то не трябва да се тестват.

Database init unit тестове няма нужда също!!!

Column definition = “TEXT” не му харесва на in-memory базата данни – дали се разрешава с @Lob???

Spring менъджира с коя версия на in-memory базата данни HyperSQL Database или H2 ще работи!!!

Затова нарочно не слагаме версия на in-memory базата данни!!!

Important notes before starting testing:

- first, disable in the class AppSeedInit.java the @PostConstruct annotated method beginInit()
- second, copy the real CLOUDINARY_SECRET in the application.yml in the test section // or other option is to set Environmental Variables for every test class manually

For testing - do not use columnDefinition @Column(name = "more_info", columnDefinition = "TEXT")
- (in the ItemEntity class for field moreInfo, I removed the columnDefinition so that the in-memory HyperSQL grammar is satisfied)

```
<!-- https://mvnrepository.com/artifact/org.hsqldb/hsqldb -->
<dependency>
    <groupId>org.hsqldb</groupId>
    <artifactId>hsqldb</artifactId>
    <scope>test</scope>
</dependency>
```

15.1. Unit Testing

Unit Testing

- **Unit Testing**

- A level of software testing where **individual components are tested**
- The purpose is to validate that **each unit performs as designed**
- The **lowest level of software testing**
- Often isolated in order to ensure individual testing

Mocking

- Software practice, primarily used in **Unit Testing**
 - An object under test may have **dependencies** on other objects
 - To **isolate** the behavior, the other objects are replaced
 - The replacements are **mocked objects**
 - The mocked objects **simulate** the behavior of the **real objects**

Benefits

- Unit testing **increases confidence** in **changing / maintaining code**
- Development is faster:
 - Verifying the correctness of new functionality is not manual
 - Localizing bugs, introduced in development is much faster
- The code is modular and reusable (necessary for Unit testing)

15.2. Unit Testing a Web Application

Unit Testing

- **Unit Testing** for web apps is similar to the unit tests we've done
 - Writing test methods to test classes and methods (functionalities)
 - Testing individual code components (**units**)
 - Independently from the **infrastructure**
 - You still use the same testing frameworks as in casual unit testing
- When using a web frameworks such as **Spring MVC**
 - Built-in logic does not need to be tested
 - It is already tested during the development of the framework itself
 - You still need to test your custom functionality
- **Web applications** also need testing for:
 - Controllers

- Services
- Custom Components etc.
- Different **components** of the application are tested differently
 - They are tested on different levels
 - **Unit** testing
 - **Integration** testing
 - **End-to-End** testing – тестваме директно в Browser-а – например със Selenium или с Playwright Chromium
- Every component of the application must be tested



15.3. Unit Testing the Service layer

- Testing a simple service with mocking in an **Spring MVC** app

```
@ExtendWith(MockitoExtension.class)
@Mock
```

JUnit5

```
@ExtendWith(MockitoExtension.class)
public class AppUserDetailsServiceTest {
    private UserEntity testUser;
    private UserRoleEntity adminRole, customerRole;
    private AppUserDetailsService testAppUserDetailsService;

    @Mock
    private UserRepository mockUserRepository;

    @BeforeEach
    void init() {
        testAppUserDetailsService = new AppUserDetailsService(mockUserRepository);

        adminRole = new UserRoleEntity().setUserRole(UserRoleEnum.ADMIN);
        customerRole = new UserRoleEntity().setUserRole(UserRoleEnum.CUSTOMER);

        testUser = new UserEntity()
            .setFirstName("Svilen")
            .setLastName("Velikov")
            .setUsername("admin")
            .setEmail("svilkata@abv.bg")
```

```

        .setPassword("11111")
        .setUserRoles(Set.of(adminRole, customerRole));
    }

    @Test
    void testUserNotFound() {
        Assertions.assertThrows(
            UsernameNotFoundException.class, //expected error class exception
            () -> testAppUserDetailsService.loadUserByUsername("invalid_username"));
    }

    @Test
    void testUserFound() {
        //Arrange
        Mockito.when(mockUserRepository.findByUsername(testUser.getUsername()))
            .thenReturn(Optional.of(testUser));

        //Act
        UserDetails actual =
testAppUserDetailsService.loadUserByUsername(testUser.getUsername());

        //Assert
        Assertions.assertEquals(actual.getUsername(), testUser.getUsername());

        String actualRoles = actual.getAuthorities().stream().map(ga -> ga.getAuthority())
            .collect(Collectors.joining(", "));
        String expectedRoles = "ROLE_ADMIN, ROLE_CUSTOMER";
        Assertions.assertEquals(expectedRoles, actualRoles);
    }
}

```

15.4. Integration Testing the Web Layer / the Controller

Testing Controller Examples

With Integration Tests!!!

@SpringBootTest

@AutoConfigureMockMvc

@Autowired

@WithMockUser

@MockBean

MockMvcResultMatchers Methods

- **request()**
 - Access to request-related assertions
- **handler()**

- Access to assertions for the handler that handled the request
- **model()**
 - Access to model-related assertions
- **view()**
 - Access to assertions on the selected view
- **flash()**
 - Access to flash attribute assertions
- **status()**
 - Access to response status assertions
- **header()**
 - Access to response header assertions
- **content()**
 - Access to response body assertions

!!! Simple test examples

```
@SpringBootTest
@AutoConfigureMockMvc
public class UserControllerTests {
    @Autowired
    private MockMvc mockMvc;

    @Test
    public void when_getOneStudents_returnFirst() throws Exception {
        mockMvc
            .perform(MockMvcRequestBuilders.get("/users/1"))
            .andExpect(status().isOk())
            .andExpect(view().name("one"))
            .andExpect(model().attributeExists("user"));

    }

    @SpringBootTest
    @AutoConfigureMockMvc
    public class AuthorsControllerTest {
        // @Autowired MockMvc and AuthorRepository
        @BeforeEach
        public void setUp() { // Add two test authors in repository }
        @AfterEach
        public void tearDown() { authorRepository.deleteAll(); }

        @Test
        public void testGetAuthorsCorrect() throws Exception {
            this.mockMvc.perform(get("/authors"))
                .andExpect(status().isOk())
                .andExpect(jsonPath("$.size()", hasSize(2)))
                .andExpect(jsonPath("$.[0].name", is(author1Name)))
                .andExpect(jsonPath("$.[1].name", is(author2Name)));
        }

        mockMvc.perform(get( urlTemplate: "/api/" + routeId + "/comments"))
            .andExpect(status().isOk())
            .andExpect(jsonPath( expression: "$", hasSize(2)));
    }
}
```

- Testing with MockUser

Кой user има право да достъпва дадената операция

Можем и целият клас да го анотираме с `@WithMockUser`

```
@Test
@WithMockUser(username = "Plamen", roles = {"FRONT_OFFICE"})
void orderReceive() throws Exception {
    mockMvc.perform(MockMvcRequestBuilders.get(
        FRONT_OFFICE_CONTROLLER_PREFIX + "/receive", orderId))
        .andExpect(status().isOk())
        .andExpect(view().name("/orders/orders-receive"))
        .andExpect(model().attributeExists("OrderReceiveBindingModel"));
}
```

15.5. Testing Essentials

Testing

- There are also different concepts and practices of test development
 - **Code-first** approach (The usual Development)
 - **Test-first** approach (Test-Driven Development)
- Each has its own **advantages** and **disadvantages**
 - The **Code-first** approach ensures **flexibility** & **fast** development
 - The **Code-first** approach requires **additional refactoring**
 - The **Test-first** approach ensures **quality** and **edge case coverage**
 - The **Test-first** approach is **complicated** and is an "**initial delay**"

Common levels of Software Testing

- Some of the most common levels of Software Testing

Testing Level	Description
Unit Testing	Tests Individual components of code, independent from the infrastructure
Component Unit Testing	Testing of multiple functionalities (a single component)
Integration Testing	Testing of all integrated modules to verify the combined functionality
System Testing	Tests the system as a whole, once all the components are integrated
Regression Testing	Testing that recent program or code change has not adversely affected existing features.
Acceptance Testing	Tests if the product meets the client's requirements. Purely done by QAs

Load / Stress Testing	Test the application's limits by attempting large data processing and introducing abnormal circumstances and conditions (edge cases)
Security Testing	Test if the application has any security flaws and vulnerabilities
Other Types of Testing	Manual, automation, UI, performance, black box , end-to-end testing, etc.

black box testing – отиваме и се мъчим да хакнем дадена система (да направим security test) без да знаем как тя работи отвътре


white box testing – когато имаме достъп до целия source код и можем да разгледаме и въз основа на придобитите от този source код знания , чак тогава да изпълним security test.

Testing

- Unit testing ensures the correctness of a particular unit
 - Not testing all components may lead to false results
 - A single unit may function correctly, independent of the infrastructure
 - Combining components and testing them collectively is necessary
 - Every level of testing is essential to an application's lifecycle

Different Testing levels

- Different Testing levels require different time and resources



15.6. Advanced Testing examples

Като има много методи за тестване, и когато пуснем целия клас да се тества, то се помни контекста, и трябва или да изтриваме базата с **@AfterEach (ако успеем да я изтрием разбира се)**, или в нов тестов клас да добавявме някои тестове.

Винаги да използваме **@BeforeEach – за да се инициализира преди всеки тестметод от тесткласа!!! Иначе дава бъгове!!!**

Страшно много се работи с Reflection при тестването – когато не можем да заложим цели обекти в теста, то залагаме имена на полетата на този клас, имената/полетата на ProductItemBindingDTO например.

В тестовете за CloudinaryServiceTest и PictureServiceTest съм използвал само [**@Mock**](#), но мокнатите неща ги бутам в конструктора на по-горния service//компонент/bean. И тествам на по-горния service някой от методите.

А в случая с PictureControllerTest, аз не използвам на PictureController метод, който да тествам, т.е. не използвам и конструктор PictureController. И за да инжектираме мокнатия service, използваме този път [**@MockBean**](#)

`@mock` е част от Mockito фреймуъркът и няма нищо общо със спринг. С `@mock` създаваш един мокнат клас и толкоз. В случая го ползваш в някакъв локален незапочнат контролер, който също не бива извикан от mockMvc.

`@MockBean` от своя страна е спринг анотация. Като я използваш, създаваш един мок клас и с него заменяш съответния компонент в инициализирания спринг апликаций контекст (това е мястото, където "живеят" всички спринг бийнове - компоненти, сървиси, репозиторита и т.н.). Т.е. вместо истинския Bean имаш мокнат бийн.

```
import bg.softuni.computerStore.exception.MyFileDestroyFromCloudinaryException;
import bg.softuni.computerStore.exception.MyFileUploadException;
import bg.softuni.computerStore.model.entity.picture.CloudinaryImage;
import com.cloudinary.Cloudinary;
import com.cloudinary.Uploader;
import org.junit.jupiter.api.Test;
import org.junit.jupiter.api.extension.ExtendWith;
import org.mockito.Mock;
import org.mockito.Mockito;
import org.mockito.junit.jupiter.MockitoExtension;
import org.springframework.mock.web.MockMultipartFile;

import java.io.File;
import java.io.IOException;
import java.util.Map;

import static org.junit.jupiter.api.Assertions.assertEquals;
import static org.junit.jupiter.api.Assertions.assertThrows;
import static org.mockito.ArgumentMatchers.any;
import static org.mockito.ArgumentMatchers.anyString;
import static org.mockito.Mockito.when;

@ExtendWith(MockitoExtension.class)
class CloudinaryServiceTest {
    @Mock
    private Cloudinary cloudiry;

    @Test
    public void upload_must_return_correct_cloudirary_image() throws IOException {
        // Arrange
    }
}
```

```

Uploader mockUploader = Mockito.mock(Uploader.class);
when(cloudinary.uploader()).thenReturn(mockUploader);
when(mockUploader.upload(any(File.class), any(Map.class)))
    .thenReturn(Map.of("url", "success_url", "public_id", "success_id"));
CloudinaryService service = new CloudinaryService(cloudinary);

// Act
CloudinaryImage result = service.upload(new MockMultipartFile("FileName", new byte[0]));

// Assert
assertEquals("success_url", result.getUrl());
assertEquals("success_id", result.getPublicId());
}

@Test
public void upload_must_throw_exception_when() throws IOException {
    // arrange
    Uploader mockUploader = Mockito.mock(Uploader.class);
    when(cloudinary.uploader()).thenReturn(mockUploader);
    when(mockUploader.upload(any(File.class), any(Map.class)))
        .thenThrow(new IOException());
    CloudinaryService service = new CloudinaryService(cloudinary);

    // act & assert
    assertThrows(MyFileUploadException.class,
        () -> service.upload(new MockMultipartFile("FileName", new byte[0])),
        "Can not upload file 'FileName'");
}

@Test
public void deleteFromCloudinaryTestMustDeleteAnImageFromCloudinary() throws IOException {
    // Arrange
    Uploader mockUploader = Mockito.mock(Uploader.class);
    when(cloudinary.uploader()).thenReturn(mockUploader);
    when(mockUploader.destroy(anyString(), any(Map.class)))
        .thenReturn(Map.of("url", "success_url", "public_id", "success_id"));
    CloudinaryService service = new CloudinaryService(cloudinary);

    // Act
    boolean isDeleted = service.deleteFromCloudinary("1");

    // Assert
    assertEquals(true, isDeleted);
}

@Test
public void deleteFromCloudinaryTestMustThrowExceptionWhenDeleteAnImageFromCloudinary()
throws IOException {
    // Arrange
    Uploader mockUploader = Mockito.mock(Uploader.class);
    when(cloudinary.uploader()).thenReturn(mockUploader);
    when(mockUploader.destroy(anyString(), any(Map.class)))
        .thenThrow(new IOException());
    CloudinaryService service = new CloudinaryService(cloudinary);

    // Act & Assert
    boolean isDeleted = service.deleteFromCloudinary("1");
}

```

```

        assertsThrows(MyFileDestroyFromCloudinaryException.class,
                      () -> service.deleteFromCloudinary("1"),
                      "Error deleting from cloudinary a file with publicId '1'");
    }
}

//{@ExtendWith(MockitoExtension.class)
@AutoConfigureTestDatabase
@SpringBootTest
@TestInstance(TestInstance.Lifecycle.PER_CLASS)
public class PictureServiceTest {
    @Autowired
    private PictureService pictureService;

    private PictureEntity testPictureEntity1, testPictureEntity2;
    private ItemEntity testItemEntity;
    private String testPhotoPublicId = "abcd";

    //Mocked objects
    @Mock
    private CloudinaryService mockedCloudinaryService;
    @Mock
    private PictureRepository mockedPictureRepository;
    @Mock
    private AllItemsRepository mockedAllItemsRepository;
    @Mock
    private Cloudinary mockedCloudinary;
    @Mock
    private Uploader mockedUploader;

    @BeforeAll
    public void setup() throws IOException {
        //Arrange
        testPictureEntity1 = (new PictureEntity()
            .setId(1L)
            .setPublicId(testPhotoPublicId)
            .setUrl("bala")
            .setItemId(1L));

        testPictureEntity2 = (new PictureEntity()
            .setId(2L)
            .setPublicId("efgh")
            .setUrl("bala")
            .setItemId(2L));

        // Arrange
        mockedUploader = Mockito.mock(Uploader.class);
        when(mockedCloudinary.uploader()).thenReturn(mockedUploader);
        when(mockedUploader.upload(any(File.class), any(Map.class)))
            .thenReturn(Map.of("url", "success_url", "public_id", "success_id"));
        when(mockedUploader.destroy(anyString(), any(Map.class)))
            .thenReturn(Map.of("url", "success_url", "public_id", "success_id"));
        this.mockedCloudinaryService = new CloudinaryService(mockedCloudinary);

        this.pictureService = new PictureService(mockedPictureRepository,
                                              mockedAllItemsRepository, mockedCloudinaryService);
    }
}

```

```

}

//    @Order(1)
@Test
void createPictureEntityTestSuccessfull() {
    //More to arrange
    MockMultipartFile mockedMultipartFile = new MockMultipartFile(
        "file",
        "hello.txt",
        MediaType.TEXT_PLAIN_VALUE,
        "Hello World".getBytes());

    //Act
    PictureEntity createdPictureEntity =
        this.pictureService.createPictureEntity(mockedMultipartFile, 8L);

    //Assert
    assertEquals(createdPictureEntity.getItemId(), 8L);
}

//    @Order(2)
@Test
void getPictureByPublicIdTestSuccessfull() {
    //Act
    PictureEntity expected = testPictureEntity1;

    //      when(mockedPictureRepository.findPictureEntityByPublicId(testPhotoPublicId))
    //          .thenReturn(Optional.ofNullable(testPictureEntity1));

    doReturn(Optional.of(testPictureEntity1)).when(mockedPictureRepository).findPictureEntityByPublicId(testPhotoPublicId);

    PictureEntity result = this.pictureService.getPictureByPublicId(testPhotoPublicId);

    //Assert
    assertEquals(expected.getPublicId(), result.getPublicId());
    assertThrows(NoSuchElementException.class,
        () -> this.pictureService.getPictureByPublicId(testPhotoPublicId));
}

//    @Order(3)
@Test
void deleteFromPictureRepositoryTestSuccessfull() {
    this.pictureService.deleteFromPictureRepository(testPhotoPublicId);
}

//    @Order(4)
@Test
void savePhotoTestSuccessfullWhenPictureIsPresent() {
    //      when(mockedPictureRepository.findPictureEntitiesById(1L))
    //          .thenReturn(Optional.ofNullable(testPictureEntity1));

    doReturn(Optional.of(testPictureEntity1)).when(mockedPictureRepository).findPictureEntitiesById(1L);

    when(mockedPictureRepository.save(testPictureEntity1))
        .thenReturn(testPictureEntity1);
}

```

```

testItemEntity = new ComputerEntity();
testItemEntity
    .setItemId(1L)
    .setBrand("AK 47")
    .setModel("Naj-dpbria")
    .setCurrentQuantity(3)
    .setBuyingPrice(BigDecimal.valueOf(12))
    .setSellingPrice(BigDecimal.valueOf(18))
    .setCreationDateTime(LocalDateTime.now());

//      when(mockedAllItemsRepository.findById(1L))
//          .thenReturn(Optional.ofNullable(testItemEntity));
doReturn(Optional.of(testItemEntity)).when(mockedAllItemsRepository).findById(1L);

this.pictureService.savePhoto(testPictureEntity1);
}
}

```

```

@SpringBootTest
@AutoConfigureMockMvc
class RegistrationControllerTest {
    private static final String USER_CONTROLLER_PREFIX_REGISTER = "/users/register";
    @Autowired
    private MockMvc mockMvc;

    @Test
    void registerConfirmTestSuccessfull() throws Exception {
        mockMvc.perform(MockMvcRequestBuilders.post(USER_CONTROLLER_PREFIX_REGISTER)
            .param("username", "pesh")
            .param("email", "Pesho@mail.bg")
            .param("firstName", "Pesho")
            .param("lastName", "Peshovich")
            .param("password", "123456")
            .param("confirmPassword", "123456")
            .with(csrf())
            .contentType(MediaType.APPLICATION_FORM_URLENCODED))
            .andExpect(status().is3xxRedirection());
    }
}

```

```

import bg.softuni.computerStore.service.UserService;
import org.junit.jupiter.api.AfterEach;
import org.junit.jupiter.api.BeforeEach;
import org.junit.jupiter.api.Order;
import org.junit.jupiter.api.Test;
import org.springframework.beans.factory.annotation.Autowired;
import org.springframework.boot.test.autoconfigure.jdbc.AutoConfigureTestDatabase;
import org.springframework.boot.test.autoconfigure.web.servlet.AutoConfigureMockMvc;
import org.springframework.boot.test.context.SpringBootTest;
import org.springframework.security.authentication.UsernamePasswordAuthenticationToken;
import org.springframework.security.core.Authentication;

```

```
import org.springframework.security.core.context.SecurityContextHolder;
import org.springframework.security.core.userdetails.UserDetails;
import org.springframework.security.core.userdetails.UserDetailsService;
import org.springframework.security.test.context.support.WithMockUser;
import org.springframework.test.web.servlet.MockMvc;
import org.springframework.test.web.servlet.request.MockMvcRequestBuilders;

import static
org.springframework.security.test.web.servlet.request.SecurityMockMvcRequestPostProcessors.csrf;
import static org.springframework.test.web.servlet.result.MockMvcResultMatchers.*;

@SpringBootTest
@AutoConfigureMockMvc
@AutoConfigureTestDatabase
class AdminControllerTest {
    private static final String ADMIN_CONTROLLER_PREFIX = "/pages/admins";

    @Autowired
    private MockMvc mockMvc;

    @Autowired
    private UserDetailsService appUserDetailsService;
    @Autowired
    private UserService userService;

    @BeforeEach
    public void setup() {
        this.userService.init();
        loginUser("admin");
    }

    private void loginUser(String username) {
        //The Login process of user with username "admin" doing it below
        UserDetails userDetails =
            appUserDetailsService.loadUserByUsername(username);

        Authentication authentication =
            new UsernamePasswordAuthenticationToken(
                userDetails,
                userDetails.getPassword(),
                userDetails.getAuthorities()
            );
        SecurityContextHolder.
            getContext().
            setAuthentication(authentication);
    }

    @AfterEach
    void clear() {

    }

    @Test
    @Order(1)
    @WithMockUser(username = "admin", roles = {"ADMIN"})
    void addEmployeeRoleTest() throws Exception {
```

```

        mockMvc.perform(MockMvcRequestBuilders.get(
                ADMIN_CONTROLLER_PREFIX + "/set-user-role"))
                .andExpect(view().name("/user/add-or-edit-user-role"))
                .andExpect(model().attributeExists("userRolesBindingDTO"))
                .andExpect(status().isOk());
}

@Test
@Order(2)
@WithMockUser(username = "admin", roles = {"ADMIN"})
void addUserRoleConfirmTestSuccessfull() throws Exception {
    mockMvc.perform(MockMvcRequestBuilders.post(ADMIN_CONTROLLER_PREFIX + "/set-user-role")
            .param("username", "purchase")
            .param("roles", "EMPLOYEE_PURCHASES", "EMPLOYEE_SALES")
            .with(csrf()))
            .andExpect(status().is2xxSuccessful());
}

@Test
@Order(3)
@WithMockUser(username = "admin", roles = {"ADMIN"})
void addUserRoleConfirmTestWhenOnlyOneRoleSelected() throws Exception {
    mockMvc.perform(MockMvcRequestBuilders.post(ADMIN_CONTROLLER_PREFIX + "/set-user-role")
            .param("username", "purchase")
            .param("roles", "EMPLOYEE_SALES")
            .with(csrf()))
            .andExpect(status().is3xxRedirection())
            .andExpect(redirectedUrl("/pages/admins/set-user-role"))
            .andExpect(flash().attribute("atLeastTwoRolesShouldBeSelected", true));
}

@Test
@Order(4)
@WithMockUser(username = "admin", roles = {"ADMIN"})
void addUserRoleConfirmTestWhenAdminRoleIsPresent() throws Exception {
    mockMvc.perform(MockMvcRequestBuilders.post(ADMIN_CONTROLLER_PREFIX + "/set-user-role")
            .param("username", "purchase")
            .param("roles", "ADMIN", "EMPLOYEE_PURCHASES")
            .with(csrf()))
            .andExpect(status().is3xxRedirection())
            .andExpect(redirectedUrl("/pages/admins/set-user-role"))
            .andExpect(flash().attribute("oneAdminOnlyPossible", true));
}

@Test
@Order(5)
@WithMockUser(username = "admin", roles = {"ADMIN"})
void addUserRoleConfirmTestWhenEmployeeNotSelected() throws Exception {
    mockMvc.perform(MockMvcRequestBuilders.post(ADMIN_CONTROLLER_PREFIX + "/set-user-role")
            .param("username", "")
            .with(csrf()))
            .andExpect(status().is3xxRedirection())
            .andExpect(redirectedUrl("/pages/admins/set-user-role"))
            .andExpect(flash().attribute("employeeNotSelected", true));
}

```

```

@Test
@Order(6)
@WithMockUser(username = "admin", roles = {"ADMIN"})
void statisticsHttpRequestsTest() throws Exception {
    mockMvc.perform(MockMvcRequestBuilders.get(
        ADMIN_CONTROLLER_PREFIX + "/statshttprequests")
        .with(csrf()))
    .andExpect(status().isOk())
    .andExpect(view().name("/stats/stats-httpproblems"))
    .andExpect(model().attributeExists("stats"));

}

@Test
@Order(7)
@WithMockUser(username = "admin", roles = {"ADMIN"})
void statisticsSalesTest() throws Exception {
    mockMvc.perform(MockMvcRequestBuilders.get(
        ADMIN_CONTROLLER_PREFIX + "/statssales")
        .with(csrf()))
    .andExpect(status().isOk())
    .andExpect(view().name("/stats/stats-sales"))
    .andExpect(model().attributeExists("stats"));

}

@Test
@Order(8)
@WithMockUser(username = "admin", roles = {"ADMIN"})
void changeAdminUserTest() throws Exception {
    mockMvc.perform(MockMvcRequestBuilders.get(
        ADMIN_CONTROLLER_PREFIX + "/change-admin-user")
        .with(csrf()))
    .andExpect(status().isOk())
    .andExpect(view().name("/user/change-admin-user-role"))
    .andExpect(model().attributeExists("employees"))
    .andExpect(model().attributeExists("userRolesBindingDTO"));

}

@Test
@Order(9)
@WithMockUser(username = "admin", roles = {"ADMIN"})
void changeAdminUserConfirmTestWhenEmployeeNotSelected() throws Exception {
    mockMvc.perform(MockMvcRequestBuilders.post(ADMIN_CONTROLLER_PREFIX + "/change-admin-
user")
        .param("username", "")
        .param("roles", "")
        .with(csrf()))
    .andExpect(status().is3xxRedirection())
    .andExpect(redirectedUrl("/pages/admins/change-admin-user"))
    .andExpect(flash().attribute("employeeNotSelected", true));

}

@Test
@Order(10)
@WithMockUser(username = "admin", roles = {"ADMIN"})

```

```

void changeAdminUserConfirmTestWhenLessThanFourRoles() throws Exception {
    mockMvc.perform(MockMvcRequestBuilders.post(ADMIN_CONTROLLER_PREFIX + "/change-admin-user")
        .param("username", "sales")
        .param("roles", "EMPLOYEE_PURCHASES", "ADMIN")
        .with(csrf())
        .andExpect(status().is3xxRedirection())
        .andExpect(redirectedUrl("/pages/admins/change-admin-user"))
        .andExpect(flash().attribute("adminChanging", true));
}

@Test
@Order(11)
@WithMockUser(username = "admin", roles = {"ADMIN"})
void registerNewEmployeeTest() throws Exception {
    mockMvc.perform(MockMvcRequestBuilders.get(
        ADMIN_CONTROLLER_PREFIX + "/register-new-employee"))
        .andExpect(view().name("/user/registerNewEmployee"))
        .andExpect(model().attributeExists("employeeRegistrationModel"))
        .andExpect(status().isOk());
}

@Test
@Order(12)
@WithMockUser(username = "admin", roles = {"ADMIN"})
void registerNewEmployeeConfirmTestSuccessfull() throws Exception {
    mockMvc.perform(MockMvcRequestBuilders.post(ADMIN_CONTROLLER_PREFIX + "/register-new-employee"))
        .param("username", "Tisho")
        .param("email", "xadqw@dqd.com")
        .param("firstName", "Tihomir")
        .param("lastName", "Tihomirov")
        .param("password", "1234")
        .param("roles", "EMPLOYEE_PURCHASES", "CUSTOMER")
        .with(csrf())
        .andExpect(status().is3xxRedirection());
}

@Test
@Order(13)
@WithMockUser(username = "admin", roles = {"ADMIN"})
void registerNewEmployeeConfirmTestCreatingEmployeeHasErrors() throws Exception {
    mockMvc.perform(MockMvcRequestBuilders.post(ADMIN_CONTROLLER_PREFIX + "/register-new-employee"))
        .param("username", "Tisho")
        .param("email", "")
        .param("firstName", "")
        .param("lastName", "Tihomirov")
        .param("password", "1234")
        .param("roles", "EMPLOYEE_PURCHASES", "CUSTOMER")
        .with(csrf())
        .andExpect(status().is3xxRedirection())
        .andExpect(redirectedUrl("/pages/admins/register-new-employee"));
}

@Test

```

```

    @Order(14)
    @WithMockUser(username = "admin", roles = {"ADMIN"})
    void registerNewEmployeeConfirmTestLessThanTwoRoles() throws Exception {
        mockMvc.perform(MockMvcRequestBuilders.post(ADMIN_CONTROLLER_PREFIX + "/register-new-employee"))
            .param("username", "Tisho")
            .param("email", "Tifwf@dqwed.com")
            .param("firstName", "Tihomir")
            .param("lastName", "Tihomirov")
            .param("password", "1234")
            .param("roles", "EMPLOYEE_PURCHASES")
            .with(csrf())
            .andExpect(status().is3xxRedirection())
            .andExpect(flash().attribute("atLeastTwoRolesShouldBeSelected", true))
            .andExpect(redirectedUrl("/pages/admins/register-new-employee"));
    }
}

```

```

@SpringBootTest
@AutoConfigureTestDatabase
@AutoConfigureMockMvc
@WithMockUser(username = "purchase", roles = {"EMPLOYEE_PURCHASES"})
public class PictureControllerTest {
    private static final String PURCHASE_CONTROLLER_PREFIX = "/pages/purchases";
    private Long itemId = 1L;

    @Autowired
    private MockMvc mockMvc;
    @Autowired
    private UserDetailsService appUserDetailsService;
    @Autowired
    private UserService userService;

    private PictureBindingModel pictureBindingModel;
    private MockMultipartFile mockedMultipartFile;

    @MockBean
    private PictureService mockedPictureService;

    @BeforeEach
    public void setup() {
        //Arrange
        this.userService.init();
        loginUser("purchase");

        //Arrange more
        //Задаваме име на файла името на полето "picture" от PictureBindingModel -
        //за да може reflection-а да си го вземе multipart обекта правилно. Яко.
        mockedMultipartFile = new MockMultipartFile(
            "picture",
            "hello.txt",
            MediaType.TEXT_PLAIN_VALUE,
            "Hello World".getBytes());
    }
}

```

```

pictureBindingModel = new PictureBindingModel().setPicture(mockedMultipartFile);

PictureEntity pictureEntity = new PictureEntity()
    .setPublicId("public_id")
    .setUrl("url")
    .setItemId(itemId)
    .setId(1L);

doReturn(pictureEntity).when(mockedPictureService)
    .createPictureEntity(pictureBindingModel.getPicture(), itemId);
//      when(this.mockedPictureService.createPictureEntity(pictureBindingModel.getPicture(),
// itemId))
//          .thenReturn(pictureEntity);

doNothing().when(this.mockedPictureService).savePhoto(pictureEntity);

//      pictureController = new PictureController(mockedPictureService);
}

private void loginUser(String username) {
    //The Login process of user with username "admin" doing it below
    UserDetails userDetails =
        appUserDetailsService.loadUserByUsername(username);

    Authentication authentication =
        new UsernamePasswordAuthenticationToken(
            userDetails,
            userDetails.getPassword(),
            userDetails.getAuthorities()
        );

    SecurityContextHolder.
        getContext().
        setAuthentication(authentication);
}

@Test
void addComputerPictureTest() throws Exception {
    MockHttpServletRequestBuilder builder = MockMvcRequestBuilders
        .multipart(PURCHASE_CONTROLLER_PREFIX + "/computers/" + this.itemId +
"/addpicture")
        .file(mockedMultipartFile)
        .param("itemId", this.itemId + "")
        .with(csrf());

    mockMvc.perform(builder)
        .andExpect(status().is3xxRedirection())
        .andExpect(redirectedUrl("/items/all/computer/details/" + this.itemId));
}

```

ObjectMapper

```

    1 usage
    @Autowired
    private MockMvc mockMvc;

    1 usage
    @MockBean
    private CommentService commentService;

    @Test
    public void getComments_twoCommentsExist_commentsReturnedAsJsonAndStatusIsOk() {
        Long routeId = 1L;
        when(commentService.getAllCommentsForRoute(routeId)).thenReturn(List.of(
            new CommentDisplayView( id: 1L, authorName: "John Doe", message: "This is comment #1"),
            new CommentDisplayView( id: 2L, authorName: "Foo Bar", message: "This is comment #2")
        ));

        mockMvc.perform(get("/api/" + routeId + "/comments"))
    }
}

```

```

    @Test
    @WithMockUser(username = "testUsername")
    public void createComment_sampleData_commentIsReturnedAsExpected() throws Exception {
        when(commentService.createComment(any())).thenAnswer(interaction -> {
            CommentCreationDto commentCreationDto = interaction.getArgument( 0 );
            return new CommentDisplayView( id: 1L, commentCreationDto.getUsername(), commentCreationDto.getMessage());
        });

        CommentMessageDto commentMessageDto = new CommentMessageDto("This is comment #1");
        ObjectMapper objectMapper = new ObjectMapper();

        mockMvc.perform(post( urlTemplate: "/api/" + ROUTE_ID + "/comments")
            .content(objectMapper.writeValueAsString(commentMessageDto))
            .with(csrf())
                .contentType("application/json")
                .accept( ...mediaTypes: "application/json"))
            .andExpect(status().is( status: 201))
            .andExpect(jsonPath( expression: "$.message", is( value: "This is comment #1")))
            .andExpect(jsonPath( expression: "$.authorName", is( value: "testUsername")));
    }
}

```

15.7. Lazy initialization exception

При тестване с in-memory база данни, първата заявка работи, а втората не работи!!!
`@Query("SELECT b FROM BasketOrderEntity b JOIN FETCH b.products WHERE b.id= :id")`
`Optional<BasketOrderEntity> findBasketByIdEager(Long id);`

`Optional<BasketOrderEntity> findBasketOrderEntitiesById(Long id);`

<https://www.baeldung.com/hibernate-initialize-proxy-exception>

It's important to understand **what Session, Lazy Initialisation, and Proxy Object** are, and how they come together in the *Hibernate* framework:

- *Session* is a persistence context that represents a conversation between an application and the database.
- *Lazy Loading* means that the object won't be loaded to the *Session* context until it is accessed in code.
- *Hibernate* creates a dynamic *Proxy Object* subclass that will hit the database only when we first use the object.

This error occurs when we try to fetch a lazy-loaded object from the database by using a proxy object, but the Hibernate session is already closed.

@Transactional

<https://www.baeldung.com/spring-transactional-propagation-isolation>

Привет!

Експешъна, за който говорим няма много общо с базата която използваш и се хвърля от хибернейт. Релациите by default са LAZY (мързеливи):

```
@ManyToMany  
private List<ItemEntity> products;
```

Това означава, че като си поискаш баскета хибернейт няма да направи JOIN с продуктите а вместо това ще ти върне един прокси обект дето реално няма продукти в него. Ако се опиташ да ги достъпиш хибернейт трябва да направи заявка в момента на достъп. Затова е и LAZY. Само че, за да се случи това нещо трябва да имаш отворена сесия, а такава няма. Можеш да подходиш по различни начини.

- да изпълняваш функционалността в контекста на транзакция (напр. анотация @Transactional)
- да ползваш JOIN FETCH
- да ползваш EAGER релация
- да използваш named graph.

Има доста ресурси внета по този въпрос. Мисълта ми е, че грешката не е свързана с базата. Може би да започнеш от тук - <https://www.baeldung.com/hibernate-initialize-proxy-exception>. Запознай се също и с Transactional анотацията.

15.8. Using H2 console during test debugging in Spring

<https://hrrbrt.medium.com/using-h2-during-test-debugging-in-spring-f6a3db355e3a>

16. Containerization & Documentation

16.1. Containers and Docker

Containerization

OS-level virtualization refers to an operating system paradigm in which the kernel allows the existence of **multiple isolated user space instances** known as **containers, zones, jails, ...**


Работят в изолация /Standalone/.

Не може единия апп да източи паметта на другия апп. Ако единия апп му свърши паметта, то другия апп продължава да работи.

Цял сървър е доста скъпо също.

Затова използваме контейнеризация.

VMs and Containers



Solutions

- **rkt** by CoreOS
 - Application container engine
 - <https://coreos.com/rkt>
- **Docker** by Docker Inc
 - Application container engine
 - <https://www.docker.com/>

VMs(виртуално машини) vs Containers

- VMs virtualize the hardware
- Complete isolation
- Complete OS installation. Requires more resources
- Runs almost any OS


- Containers virtualize the OS
- Lightweight isolation
- Shared kernel among all the containers. Requires fewer resources
- Runs on the same OS == Linux

Containers Concepts (Docker View)

- **Container image** shows the state of a container, including registry or file system changes = все едно **container image** е нещо клас, а самия **контейнер** е нещо като клас. Самият container image е работещ container.
- **Container OS image** is the first layer of potentially many image layers that make up a container = основния image, върху който се гради контейнера
- **Container repository** stores container images and their dependencies = мястото, където се пазят тези container images

Definitions


- Container
 - Containers are processes with much more isolation
- Image
 - Images provide a way for simpler software distribution



16.2. Docker

Docker Engine

- Docker Mission – **Build, Ship, Deploy**
- Client-server application
- Components
 - dockerd daemon
 - REST API
 - docker CLI



Registries – мястото, където се пазят тези images


- Provided by Docker
 - Cloud
 - Docker Hub (<https://hub.docker.com/explore/>)
 - Docker Store (<https://store.docker.com/>)
 - On-premise
- Provided by 3rd parties
 - Quay.io, Artifactory, Google Container Registry

Workflow

docker build – създаване на docker image

docker pull

docker run



16.3. Docker Installation

What We Need to Know?

- **Two Editions** (Community and Enterprise)
- **Native Options**
 - Docker for Linux – 6e3 Desktop 😊
 - Docker Desktop for MAC
 - Docker Desktop for Windows
- **Docker Toolbox** (deprecated) - All-in-one solution
 - For Mac and Windows

▪ **Native Options**

- Docker for Linux
- Docker for MAC
- Docker for Windows

Deployment via package system (three channels – **stable**, **nightly**, and **test**), script, or archive

Specific requirements: OS version, Hypervisor, etc.

16.4. Working with Docker

Pull / Image Pull

- Purpose

- Pull an image or a repository from a registry

- Old syntax

```
docker pull [OPTIONS] NAME[:TAG|@DIGEST]
```

- New syntax

```
docker image pull [OPTIONS] NAME[:TAG|@DIGEST]
```

- Example

```
docker image pull ubuntu:latest
```

Run / Container Run

- Purpose

- Run a command in a new container

- Old syntax

```
docker run [OPTIONS] IMAGE [COMMAND] [ARG]
```

- New syntax

```
docker container run [OPTIONS] IMAGE [COMMAND] [ARG]
```

- Example

```
docker container run -it ubuntu
```

Images / Image Ls

- Purpose

- List locally available images

- Old syntax

```
docker images [OPTIONS] [REPOSITORY[:TAG]]
```

- New syntax

```
docker image ls [OPTIONS] [REPOSITORY[:TAG]]
```

- Example

```
docker image ls fedora
```

Ps / Container Ls

- Purpose

- List containers

- Old syntax

```
docker ps [OPTIONS]
```

- New syntax

```
docker container ls [OPTIONS]
```

- Example

```
docker container ls -a -q
```

Rm / Container Rm

- Purpose
 - Remove one or more containers
- Old syntax

docker rm [OPTIONS] CONTAINER [CONTAINER]

- New syntax

docker container rm [OPTIONS] CONTAINER [CONTAINER]

- Example

docker container rm weezy_snake

Rmi / Image Rm

- Purpose
 - Remove one or more images
- Old syntax

docker rmi [OPTIONS] IMAGE [IMAGE]

- New syntax

docker image rm [OPTIONS] IMAGE [IMAGE]

- Example

docker image rm ubuntu fedora

Start / Container Start

- Purpose
 - Start one or more stopped containers
- Old syntax

docker start [OPTIONS] CONTAINER [CONTAINER]

- New syntax

docker container start [OPTIONS] CONTAINER [CONTAINER]

- Example

docker container start -a -i 0cbf27183

Restart / Container Restart

- Purpose
 - Restart one or more containers
- Old syntax

docker restart [OPTIONS] CONTAINER [CONTAINER]

- New syntax

docker container restart [OPTIONS] CONTAINER [CONTAINER]

- Example

```
docker container restart 0cbf27183
```

Stop / Container Stop

- Purpose
 - Stop one or more running containers
- Old syntax

```
docker stop [OPTIONS] CONTAINER [CONTAINER]
```

- New syntax

```
docker container stop [OPTIONS] CONTAINER [CONTAINER]
```

- Example

```
docker container stop 0cbf27183
```

Unpause / Container Unpause

- Purpose
 - Unpause all processes within one or more containers
- Old syntax

```
docker unpause CONTAINER [CONTAINER]
```

- New syntax

```
docker container unpause CONTAINER [CONTAINER]
```

- Example

```
docker container unpause 0cbf27183
```

Attach / Container Attach

- Purpose
 - Attach to a running container
- Old syntax

```
docker attach [OPTIONS] CONTAINER
```

- New syntax

```
docker container attach [OPTIONS] CONTAINER
```

- Example

```
docker container attach 0cbf27183
```

```
docker -exec .....
```

Push / Image Push

- Purpose
 - Push an image or repository to a registry
- Old syntax

`docker push [OPTIONS] NAME[:TAG]`

- New syntax

`docker image push [OPTIONS] NAME[:TAG]`

- Example

`docker image push repo-name/test:latest`

Login to Docker registry

- Purpose
 - Log into a Docker registry

- Old syntax

`docker login [OPTIONS] [SERVER]`

- New syntax

`docker login [OPTIONS] [SERVER]` като стария синтаксис

- Example

`docker login`

Logout from Docker registry

- Purpose
 - Log out from a Docker registry

- Old syntax

`docker logout [SERVER]`

- New syntax

`docker logout [SERVER]` като стария синтаксис

- Example

`docker logout`

16.5. Image from File – изпичане на docker файл

General Structure (Dockerfile)

- Script, composed of commands and arguments
- Always begins with FROM instruction

Set the base image

`FROM nginx` Comment

Set the maintainer

`MAINTAINER John Smith` Command (Instruction)

Copy files

```
COPY index.html /usr/share/nginx/html/
```

FROM

- Purpose
 - Defines the base image to use to start the build process
- Syntax

```
FROM <image>[:<tag>] [AS <name>]
```

- Example

it is a good practice to state a version (tag)

```
FROM ubuntu:18.04
```

for the latest version the tag could be skipped

```
FROM ubuntu
```

MAINTAINER

- Purpose
 - Sets the author field of the image. It is deprecated
- Syntax

```
MAINTAINER <name>
```

- Example

deprecated

```
MAINTAINER John Smith
```

newer variant is this:

```
LABEL maintainer="John Smith"
```

RUN

- Purpose
 - Used during build process to add software (forms another layer)
- Syntax

```
RUN <command>
```

- Example

single command

```
RUN apt-get -y update
```

more than one command

```
RUN apt-get -y update && apt-get -y upgrade
```

COPY

- Purpose
 - Copy files between the host and the container
- Syntax

```
COPY [--chown=<user>:<group>] <src>... <dest>
```

- Example

Copy single file

```
COPY readme.txt /root
```

Copy multiple files

```
COPY *.html /var/www/html/my-web-app
```

ADD

- Purpose

- Copy files to the image

- Syntax

```
ADD [--chown=<user>:<group>] <src>... <dest>
```

- Example

Add single file from URL

```
ADD https://softuni.bg/favicon.ico /www/favicon.ico
```

Add tar file content

```
ADD web-app.tar /var/www/html/my-web-app
```

EXPOSE

- Purpose

- Informs Docker that the container listens on the specified ports

- Syntax

```
EXPOSE <port> [<port>/<protocol>...]
```

- Example

single port

```
EXPOSE 80
```

multiple ports

```
EXPOSE 80 8080
```

ENTRYPOINT

- Purpose

- Allows configuration of container that will run as an executable

- Syntax

exec form, this is the preferred form

```
ENTRYPOINT ["executable", "param1", "param2"]
```

shell form

```
ENTRYPOINT command param1 param2
```

CMD

- Purpose

- Main purpose is to provide defaults for an executing container
- Syntax

exec form, this is the preferred form

CMD ["executable","param1","param2"]

as default parameters to ENTRYPPOINT

CMD ["param1","param2"]

shell form

CMD command param1 param2

CMD vs ENTRYPPOINT

- Both **define** what **command** gets **executed** when **running** a container
- **Dockerfile** should specify **at least one** of them
- **ENTRYPPOINT** should be defined when using the **container** as an **executable**
- **CMD** should be used as a way of defining **default arguments** for an **ENTRYPPOINT** command or for **executing** an **ad-hoc** command in a container
- **CMD** will be overridden when **running** the container with **alternative** arguments

- Both have **exec** and **shell form**
- When used **together always** use their **exec** form

Когато се използват заедно или поотделно:

Cmd командата може да заема няколко аргумента

ENTRYPPOINT			
CMD	N/A	<u>exec_entry p1_entry</u>	["exec_entry", "p1_entry"]
	Error	/bin/sh -c exec_entry p1_entry	exec_entry p1_entry
	["exec_cmd", "p1_cmd"]	exec_cmd p1_cmd	<u>exec_entry p1_entry exec cmd p1_cmd</u>
	["p1_cmd", "p2_cmd"]	p1_cmd p2_cmd	<u>exec_entry p1_entry p1_cmd p2_cmd</u>
	exec_cmd p1_cmd	/bin/sh -c exec_cmd p1_cmd	exec_entry p1_entry /bin/sh -c exec_cmd p1_cmd

Build / Image Build

- Purpose
 - Build an image from a Dockerfile
- Old syntax

docker build [OPTIONS] PATH | URL | -

- New syntax

docker image build [OPTIONS] PATH | URL | -

- Example -t означава сложи му таг, а точката е текущата директория

docker image build -t new-image .

Recommendations

- Don't create large images
- Don't use only the "latest" tag
- Don't run more than one process in a single container
- Don't rely on IP addresses
- Put information about the author

16.6. Demo summary + Gradle Wrapper and Gradle for Windows

Gradle


<https://tomgregory.com/what-is-the-gradle-wrapper-and-why-should-you-use-it/>


The Gradle wrapper is a script you add to your Gradle project and use to execute your build. The advantages are:

you don't need to have Gradle installed on your machine to build the project

the wrapper guarantees you'll be using the version of Gradle required by the project

you can easily update the project to a newer version of Gradle, and push those changes to version control so other team members use the newer version





```
gradle init
```

Running a build


```
gradle build
```

```
gradle clean build
```

When you run the **build** command you'll see output like this.

This means that your application was assembled and any tests passed successfully. Gradle will have created a build directory if it didn't already exist, containing some useful outputs you should be aware of.

1. **the classes directory** contains compiled .class files, as a result of running the Java compiler against your application Java source files
2. **the libs directory** contains a generated jar file, an archive with all your compiled classes inside **ready to be executed or published** – **ако махнем версията от build.gradle, то jar файловете ще са с по-кратки имена.**



3.

4. **the reports directory** contains an HTML report summarising your test results. If your build fails, then consult this report to see what went wrong.

You now know that running the Gradle build command is equivalent to running the build task, which you do in Windows with `gradlew build` and on Linux/Mac with `./gradlew build`. The *build* task depends on other tasks, and in some situations it may make sense to run a more specific task.

След което можем да го пуснем/run-нем този jar

`java -jar ./build/libs/docker.jar`

За да създадем .jar файл с Gradle, то тестовете трябва да минават

Maven

За да създадем .jar файл с Maven, то тестовете трябва да минават

Файлът /deployment/Dockerfile:

```
deployment
  Dockerfile 6.9.2022 г. 13:12, 166 B A minute ago
FROM openjdk:11-jre
VOLUME /tmp
COPY build/libs/docker.jar app.jar
ENTRYPOINT ["java","-Djava.security.egd=file:/dev/./urandom -Xms256m -Xmx512m", "-jar", "/app.jar"]
```

Ако използваме Maven, тези думички били различни

build/libs

От основната директория на проекта ни, под CMD на Windows пускаме следната команда
C:\Temp projects\Spring Advanced\12 Containerization & Documentation\docker_example>

docker build -t svilevelikov/demo1:v1 -f deployment/Dockerfile .

създай от .jar файла контейнер с име demo1 версия 1 на user svilevelikov и от текущата директория която е точка, изпълни Dockerfile.

docker images

в терминала показва всички имиджи качени на докер към момента

```
C:\Temp projects\Spring Advanced\12 Containerization & Documentation\docker_example>docker images
REPOSITORY          TAG      IMAGE ID      CREATED       SIZE
svilevelikov/demo1    v1      cc17fa2e55da   5 minutes ago  341MB
docker/getting-started  latest   cb90f98fd791   4 months ago  28.8MB
```

Можем да ги видим и от приложението DockerDesktop

NAME	TAG	IMAGE ID	CREATED	SIZE
docker/getting-started	latest	cb90f98fd791	5 months ago	28.78 MB
svilevelikov/demo1	v1	cc17fa2e55da	less than a minute ago	341.23 MB

I) Пускане на docker image-a

C:\Temp projects\Spring Advanced\12 Containerization & Documentation\docker_example>

docker run -p 8080:8080 svilevelikov/demo1:v1

Когато image-a се run-не, то той става контейнер.

docker ps

покажи текущо активни контейнери

Качи image-a на облака docker repositories

docker push svilevelikov/demo2:v2

останалите images са част от jdk и няма нужда да се пушват

```
PS C:\Temp projects\Spring Advanced\12 Containerization & Documentation\docker_example> docker push svilenvelikov/demo2:v2
The push refers to repository [docker.io/svilenvelikov/demo2]
4ced9a8f798d: Pushed
5a7e7a880634: Mounted from library/openjdk
3dccaa93bb0e: Mounted from library/openjdk
5c384ea5f752: Mounted from library/openjdk
293d5db30c9f: Mounted from library/openjdk
03127cdb479b: Mounted from library/openjdk
9c742cd6c7a5: Mounted from library/openjdk
v2: digest: sha256:3232e698c894f814aea10bb0e5ecbd61af3562e9b8bdea73dab5cb4d49acc547 size: 1794
```

Remove-ване на спрян контейнер

При опит да изтрием docker image:

Error response from daemon: conflict: unable to delete **5d4cf7396db** (must be forced) - image is being used by stopped container **d61b2cca0024**

```
PS C:\Temp projects\Spring Advanced\12 Containerization & Documentation\docker_example> docker rm
d61b2cca0024
```

Remove-ване на самия docker image

```
PS C:\Temp projects\Spring Advanced\12 Containerization & Documentation\docker_example> docker rmi
5d4cf7396db
```

Untagged: svilenvelikov/demo2:v2

Untagged:

svilenvelikov/demo2@sha256:3232e698c894f814aea10bb0e5ecbd61af3562e9b8bdea73dab5cb4d49acc547

Deleted: sha256:5d4cf7396db1e26c28c46c664427ad0041b8afa23c23aeb5c8f4b28091e9ac6

Търси първо локално, след това търси от облака

Ако пуснем команда за рънване на изтрития локално image, то първо търси локално, след това търси на облака docker repositories

```
docker run -p 8080:8080 svilenvelikov/demo2:v2
```

```
PS C:\Temp projects\Spring Advanced\12 Containerization & Documentation\docker_example> docker run -p
8080:8080 svilenvelikov/demo2:v2
Unable to find image 'svilenvelikov/demo2:v2' locally
```

v2: Pulling from svilenvelikov/demo2

001c52e26ad5: Already exists

d9d4b9b6e964: Already exists

2068746827ec: Already exists

8510da692cda: Already exists

b6d84395b34d: Already exists

bf03fea6c3ad: Already exists

7ac2c538825b: Already exists

Digest: sha256:3232e698c894f814aea10bb0e5ecbd61af3562e9b8bdea73dab5cb4d49acc547

Status: Downloaded newer image for svilenvelikov/demo2:v2

II) Пускане на повече docker images - как 2 image-а си говорят когато са качени на Docker


PS C:\Temp projects\Spring Advanced\12 Containerization & Documentation\docker_example>

Docker Compose is a tool that was developed to help define and share multi-container applications. With Compose, we can create a YAML file to define the services and with a single command, can spin everything up or tear it all down.


`docker-compose -f ./local/local.yaml up`

`docker-compose -f ./local/local.yaml down`

Ако нямаме локално инсталиран MySQL например



```
version: '3.3'
services:
  db:
    image: arm64v8/mysql:oracle
    ports:
      - "3306:3306"
    command: ['--character-set-server=utf8mb4', '--collation-server=utf8mb4_bin', '--default-authentication-plugin=mysql_native_password']
    environment:
      - MYSQL_ALLOW_EMPTY_PASSWORD=yes
      - MYSQL_DATABASE=intro
  docker-demo:
    image: svilenenvelikov/docker-demo:v3
    ports:
      - "8080:8080" # web ui
    environment:
      - MYSQL_HOST=db
      - MYSQL_USER=root
      - MYSQL_PASSWORD=
```



```
application.yml
```

```
spring:
  datasource:
    driverClassName: com.mysql.cj.jdbc.Driver
    url:
      "jdbc:mysql://${MYSQL_HOST}:3306/demodocker?useSSL=false&createDatabaseIfNotExist=true&serverTimezone=UTC"
    username: "${MYSQL_USER:root}"
    password: "${MYSQL_PASSWORD:}"
```

III) Пускане на docker image с CMD опция

При стартиране на docker image-а да прави ping

При първата команда ping-ва от локалния сървър localhost/от локалния компютър.

При втората команда овъррайдваме CMD-то да бъде google.com и сега ping-ва от google.com
ENTRYPOINT не може да се override-не

```
FROM debian:wheezy
ENTRYPOINT ["/bin/ping"]
CMD ["localhost"]

$ docker run -it test
PING localhost (127.0.0.1): 48 data bytes

$ docker run -it test google.com
PING google.com (173.194.45.70): 48 data bytes
```

16.7. Swagger 3

OpenApi

Спецификации как да описваме нашите http rest api в json формат, в yml формат и т.н.

Използвало се – тази огромна документация с много редове

Swagger

- With the Swagger we can **simplifies** API development for users, teams, and enterprises
- Why we need documentations:
 - front-end and back-end components often **separate** a web application
 - usually, we expose APIs as a back-end component for the front-end component
- Reference documentation should **simultaneously describe** every change in the API

SpringDoc

- Spring Boot, using the **SpringDoc** implementation of the **Swagger 3 specification**.
- It's enough to add a single **springdoc-openapi-ui** dependency:

```
<dependency>
  <groupId>org.springdoc</groupId>
  <artifactId>springdoc-openapi-ui</artifactId>
  <version>1.6.8</version>
</dependency>

dependencies {
  implementation 'org.springdoc:springdoc-openapi-ui'
}
```

<http://localhost:8080/swagger-ui.html>

- Go to <http://localhost:8080/swagger-ui/index.html> to test it – when openapi
- Go to <http://localhost:8080/webjars/swagger-ui/index.html> to test it – when openapi webflux

```
import io.swagger.v3.oas.models.OpenAPI;
import io.swagger.v3.oas.models.info.Contact;
import io.swagger.v3.oas.models.info.Info;
import org.springframework.context.annotation.Bean;
import org.springframework.context.annotation.Configuration;

@Configuration
public class OpenAPIConfig {
    @Bean
    public OpenAPI openAPI() {
        return new OpenAPI().
            info(new Info().
                title("Our open book API").
                version("1.0.0").
                contact(new Contact().name("Lachezar Balev").
                    email("lachezar.balev@gmail.com"))).
                description("Our book API"));
    }
}

@CrossOrigin("*")
@RestController
@RequestMapping("/api/books")
public class BooksController {

    private final BookService bookService;

    @Autowired//Autowired not required on constructor
    public BooksController(BookService bookService) {
        this.bookService = bookService;
    }

    @GetMapping
    public ResponseEntity<List<BookDTO>> getAllBooks() {
        return ResponseEntity.ok(bookService.getAllBooks());
    }

    @Tag(name = "Get book by ID", description = "Returns the book details by its id")
    @Parameter(name = "id", description = "The ID of the book", required = true)
    @ApiResponse(responseCode = "200", description = "If the book was retrieved
successfully")
    @ApiResponse(responseCode = "404", description = "If the book was not found")
    @GetMapping("/{id}")
    public ResponseEntity<BookDTO> getBookById(@PathVariable("id") Long bookId) {
        Optional<BookDTO> bookOpt = bookService.getBookById(bookId);
        if (bookOpt.isEmpty()) {
            return ResponseEntity.notFound().build();
        } else {
            return ResponseEntity.ok(bookOpt.get());
        }
    }
}
```

```

    }

}

@PostMapping
public ResponseEntity<BookDTO> createBook(@RequestBody BookDTO newBook, UriComponentsBuilder uriComponentsBuilder) {
    long newBookID = bookService.createBook(newBook);

    return ResponseEntity.created(uriComponentsBuilder.path("/api/books/{id}").build(newBookID)).build();
}

@DeleteMapping("/{id}")
public ResponseEntity<BookDTO> deleteBookById(@PathVariable("id") Long bookId) {
    bookService.deleteBookById(bookId);

    return ResponseEntity.noContent().build();
}

@PostMapping("/{id}")
public ResponseEntity<BookDTO> updateBook(@PathVariable("id") Long id, @RequestBody BookDTO bookDTO) {
    BookDTO updatedBookDTO = this.bookService.persistBook(id, bookDTO);

    if (updatedBookDTO == null) {
        return ResponseEntity.notFound().build();
    }

    return ResponseEntity.ok(updatedBookDTO);
}
}

```

Using Swagger UI example

The screenshot shows the Swagger UI interface running at localhost:8080/swagger-ui/index.html. The title bar says "Swagger UI". The main area is titled "OpenAPI definition v0 OAS3". It shows the URL </v3/api-docs>. Below this, there's a "Servers" dropdown set to "http://localhost:8080 - Generated server url".

comment-rest-controller

- GET** /api/{routeId}/comments
- POST** /api/{routeId}/comments

Schemas

- GrantedAuthority

От Swagger UI можем да си генерираме или сървър или клиент спрямо описаните

The screenshot shows the Swagger Editor interface running at localhost:8080/swagger-editor. The title bar says "Swagger Editor". The main area shows the OpenAPI specification:

```

1 openapi: 3.0.1
2 info:
3   title: Open Book API
4   description: Our book API
5   contact:
6     name: Lachezar Balev
7     email: lachezar.balev@gmail.com
8   version: 1.0.0
9   servers:
10    - url: http://localhost:8080
11      description: Generated server url

```

To the right, there's a sidebar titled "Generate Client" with various language options:

Language	Client Type
csharp	php
csharp-dotnet2	python
dart	r
dynamic-html	ruby
go	scala
html	swift3

Swagger UI

- **Swagger UI** allows anyone to **visualize** and **interact** with the API's resources without having any of the implementation logic in place.
- It's **automatically generated** from your OpenAPI (formerly known as Swagger) Specification, with the visual documentation making it easy for back-end implementation and client-side consumption.

17. Deployment

17.1. Deploy with Git

We can delete the test folder

Deploying On Heroku with Git – part A

- Download **Heroku CLI** - <https://devcenter.heroku.com/articles/heroku-cli>
- In the bash terminal, write the command

heroku login

- For creating a new Git repository
 - Go to the directory of the project
 - In the bash terminal, write

git init

- Create a new Git repository

git add .

git commit -m "some message"

git push

git push origin master

- Create a new Heroku project and bind it with the git repository

heroku create

```
Bo svilk@DESKTOP-SVILEN MINGW64 /c/Temp projects/Spring Advanced/14 Deployment, Hosting and Monitoring/books_heroku (master)
```

```
$ heroku create
```

```
Creating app... done, ⬤ calm-plains-37845
```

```
https://calm-plains-37845.herokuapp.com/ | https://git.heroku.com/calm-plains-37845.git
```

The screenshot shows the Heroku dashboard with the application 'calm-plains-37845' selected. A message at the top states: 'Starting November 28th, 2022, free Heroku Dynos, free Heroku Postgres, and free Heroku Data for Redis® will no longer be available. If you have apps using any of these resources, you must upgrade to paid plans by this date to ensure your apps continue to run and to retain your data. For students, we will announce a new program by the end of September.' Below the message is a search bar labeled 'Filter apps and pipelines'. The app details show 'calm-plains-37845' with a red checkmark, 'heroku-22 • United States', and a star icon.

```
$ git remote -v
origin  https://github.com/svilkata/books-heroku-demo.git (fetch)
origin  https://github.com/svilkata/books-heroku-demo.git (push)
heroku  https://git.heroku.com/calm-plains-37845.git (fetch)
heroku  https://git.heroku.com/calm-plains-37845.git (push)
```

heroku git: remote -a <project-name>

- Add the PostgreSQL addon

heroku addons:create heroku-postgresql

```
$ heroku addons:create heroku-postgresql
Creating heroku-postgresql on ⚡ calm-plains-37845... free
Database has been created and is available
! This database is empty. If upgrading, you can transfer
! data from another database with pg:copy
Created postgresql-spherical-49894 as DATABASE_URL
Use heroku addons:docs heroku-postgresql to view documentation
```

17.2. Deployment

What is Deployment?

- **Deployment** means to push changes or updates from one environment to another



Where to Deploy?

- We can deploy **one project** onto **multiple websites**
- Some of the deployment websites
 - [Heroku](#)
 - [Amazon Web Services \(AWS\)](#)
 - [Google Cloud Platform](#)

Deploying On Heroku

- There are **3 ways** to deploy a project on Heroku
 - Using **Git** (Heroku Git, Heroku CLI)
 - Using **Github**
 - Using the **Container Registry** (Heroku **CLI** Command Line Interface)

Gradle or Maven – making the .jar files

Всичко в папка **build** или папка **target** не трябва и не се качва в Github!

МОЖЕ да изтрием тестовете при build-ване


Самият ти няма нужда да я изпълняваш

mvn clean package или ./mvnw -DskipTests clean dependency:list install

Хероку ще го направи този jar, но трябва да посочиш правилния път на jar-а, който ще се появи в target директорията.

Procfile and system.properties

- Before running our project, we should add **3 important keys** to deploy the project
- Create 2 new files in our **project folder**
 - **Procfile**
 - **system.properties**



System.properties

- **system.properties**
 - Holds **all of the system configuration properties** needed to run the project
 - By default, Heroku uses JDK Version 1.8
 - To specify specific version:

```
java.runtime.version={version}
java.runtime.version=17
java.runtime.version=11
```

Procfile

- Procfile
 - Holds the executed commands by the application on startup
 - Should include:

Където се намира jar-а

web: java -jar target/{name}-{version}.jar - за Maven
web: java -jar build/libs/{name}-{version}.jar - за Gradle


web: java -jar build/libs/books.jar

build.gradle

```
group = 'bg.softuni'  
version = '0.0.1-SNAPSHOT'  
sourceCompatibility = '17'
```

pom.xml

```
<version>1.0.0-SNAPSHOT</version>  
<name>project_name</name>
```



```
2 <project xmlns="http://maven.apache.org/POM/  
3 xsi:schemaLocation="http://maven.apache.  
4 <modelVersion>4.0.0</modelVersion>  
5 <parent>  
6   <groupId>org.springframework.boot</g  
7   <artifactId>spring-boot-starter-par  
8   <version>2.7.2</version>  
9   <relativePath/> <!-- lookup parent j  
10 </parent>  
11 <groupId>com.example</groupId>  
12 <artifactId>demo</artifactId>  
13 <version>0.0.1-SNAPSHOT</version>  
14 <name>demo</name>
```

application.properties or application.yml

```
application.properties  
spring.datasource.url=${JDBC_DATABASE_URL:}  
spring.datasource.username=${JDBC_DATABASE_USERNAME:}  
spring.datasource.password=${JDBC_DATABASE_PASSWORD:}  
server.port=${PORT:8080}  
spring.datasource.hikari.connection-timeout=30000  
spring.datasource.hikari.maximum-pool-size=10  
spring.jpa.properties.hibernate.dialect = org.hibernate.dialect.PostgreSQLDialect
```

```

application.yml
spring:
  datasource:
    driverClassName: org.postgresql.Driver
    url: ${JDBC_DATABASE_URL:}
    username: ${JDBC_DATABASE_USERNAME:}
    password: ${JDBC_DATABASE_PASSWORD:}
  jpa:
    #For MySQL8
    # database-platform: org.hibernate.dialect.MySQL8Dialect
    #For PosgreSQL
    database-platform: org.hibernate.dialect.PostgreSQLDialect
    hibernate:
      ddl-auto: update
      open-in-view: false
      properties:
        hibernate:
          format_sql: true
        defer-datasource-initialization: true

  server:
    port: ${PORT:8080}

```

```

build.gradle
dependencies {
// runtimeOnly 'mysql:mysql-connector-java'
  runtimeOnly 'org.postgresql:postgresql'
}

```

Native MySQL queries will not work on PostgreSQL. Heroku offers free PostgreSQL database.

17.3. Deploying On Heroku with Git – part B

A - Managing config vars

Using the Heroku CLI (Command Line Runner)

- View current config var values

heroku login

```

$ heroku config
DATABASE_URL:
postgres://odqkbivsnfitu:fc64522599af9ea35a85eea06d34ac8ad87815ad3279a05df0eb3aca1a06f173@ec2-44-209-
158-64.compute-1.amazonaws.com:5432/d1k9ara4igfkna
GITHUB_USERNAME: ivan
OTHER_VAR: student

```

```
$ heroku config:get GITHUB_USERNAME
```

ivan

```
$ heroku config:get CLOUDINARY_SECRET
```

mySecret

- Set a config var

```
$ heroku config:set CLOUDINARY_SECRET = mySecret
```

Adding config vars and restarting myapp... done, v12

SOME_SECRET: mySecret

Using the Heroku Dashboard

Config Variables

Config vars change the way your app behaves. In addition to creating your own, some addons come with their own.

Config Vars

Cancel

Save

GITHUB_USERNAME	joesmith	(-)
OTHER_VAR	production	(-)
KEY	VALUE	(+)

Config Vars

Config vars change the way your app behaves. In addition to creating your own, some addons come with their own.

Config Vars

Hide Config Vars

CLOUDINARY_SECRET	muahaha	(edit) X
DATABASE_URL	postgres://fgtdqoxxvszsze:7f9b214d9af5f62	(edit) X
HEROKU_POSTGRESQL_SILVER_URL	postgres://vwhvsmncn1ful:a8e0dcf872bce93	(edit) X
KEY	VALUE	Add

B - Using the Heroku Dashboard

- You can manage your app's config vars programmatically with the [Heroku Platform API](#) using a simple HTTPS REST client and JSON data structures

C – push heroku

- Push the project to Heroku
master е локалната версия на heroku

git push heroku master



```

Terminal: Local × Git Bash × + ▾ SpringBootApplication
heroku https://git.heroku.com/calm-plains-37845.git (fetch)
Enumerating objects: 53, done.
Counting objects: 100% (53/53), done.
Delta compression using up to 4 threads
Compressing objects: 100% (38/38), done.
Writing objects: 100% (53/53), 66.20 KiB | 3.89 MiB/s, done.
Total 53 (delta 1), reused 0 (delta 0), pack-reused 0
remote: Compressing source files... done.
remote: Building source:
remote:
remote: -----> Building on the Heroku-22 stack
remote: -----> Determining which buildpack to use for this app
remote: -----> Gradle app detected
remote: -----> Spring Boot detected
remote: -----> Installing OpenJDK 17... done
remote: -----> Building Gradle app...
remote: -----> executing ./gradlew build -x check
remote:     Downloading https://services.gradle.org/distributions/gradle-7.4.1-bin.zip
remote:           .10%......20%......30%......40%......50%......60%......70%......80%......90%......100%
remote: To honour the JVM settings for this build a single-use Daemon process will be forked. See https://docs.gradle.org/7.4.1/userguide/gradle_daemon.html#sec:disabling_the_daemon
.
remote: Daemon will be stopped at the end of the build
remote: > Task :compileJava
remote:
remote:
remote: Verifying deploy... done.
To https://git.heroku.com/calm-plains-37845.git
 * [new branch]      master -> master

```

- Change the **ps:scale**

heroku ps:scale web=1

```
$ heroku ps:scale web=1
```

Scaling dynos... done, now running **web** at 1:Free

- Check logs

heroku logs --tail

дава логовете на моя арп и гледаме за грешки – дава някаква тъпа грешка за favicon


```

2022-09-11T21:46:35.545131+00:00 app[web.1]: at java.base/jdk.internal.reflect.NativeMethodAccessorImpl.invoke(NativeMethodAccessorImpl.java:77)
2022-09-11T21:46:35.545131+00:00 app[web.1]: at java.base/jdk.internal.reflect.DelegatingMethodAccessorImpl.invoke(DelegatingMethodAccessorImpl.java:43)
2022-09-11T21:46:35.545131+00:00 app[web.1]: at java.base/java.lang.reflect.Method.invoke(Method.java:568)
2022-09-11T21:46:35.545131+00:00 app[web.1]: at=error code=H10 desc="App crashed" method=GET path="/favicon.ico" host=calm-plains-37845.herokuapp.com request_id=0cdfaf57d-8be6-43a6-9e95
-d47558fa0225 fwd="87.227.215.196" dyno= connect= service= status=503 bytes= protocol=https
2022-09-11T21:59:56.351065+00:00 heroku[router]: at=error code=H10 desc="App crashed" method=GET path="/" host=calm-plains-37845.herokuapp.com request_id=0acfecf-d75e-4c06-b989-c156f72666
cc fwd="87.227.215.196" dyno= connect= service= status=503 bytes= protocol=https
2022-09-11T21:59:56.646350+00:00 heroku[router]: at=error code=H10 desc="App crashed" method=GET path="/favicon.ico" host=calm-plains-37845.herokuapp.com request_id=a86b2d50-7a43-4667-958b
-2d383f8acf6d fwd="87.227.215.196" dyno= connect= service= status=503 bytes= protocol=https

```

17.4. Deploy with Github

- Create a registration in the Heroku website



- Create a new App

A detailed view of the "Create New App" form. It starts with an "App name" field containing "test-app-9871", which is highlighted with a green checkmark. Below the field, a message says "test-app-9871 is available". Next is a "Choose a region" dropdown menu showing "Europe" as the selected option. Underneath these fields is a "Add to pipeline..." button with a gear icon. At the bottom of the form is a prominent blue "Create app" button.

- Add to the installed add-ons:

The screenshot shows the Heroku dashboard for the app "test-app-9871". At the top, there's a navigation bar with "Personal" and "test-app-9871". Below it is a horizontal menu with "Overview", "Resources", "Deploy", "Metrics", "Activity", "Access", and "Settings".

Installed add-ons **\$0.00/month** [Configure Add-ons](#)

There are no add-ons for this app
You can add add-ons to this app and they will show here. [Learn more](#)

Dyno formation **\$0.00/month** [Configure Dynos](#)

This app has no process types yet
Add a Procfile to your app in order to define its process types. [Learn more](#)

Collaborator activity [Manage Access](#)

There is no recent activity on this app
Collaborator activity will be shown when there are recent deploys

Salesforce Platform

HEROKU [Jump to Favorites, Apps, Pipelines, Spaces...](#) [More](#)

Personal > mobiletele

Overview Resources Deploy Metrics Activity Access Settings

Dynos

This app has no process types yet
Add a Procfile to your app in order to define its process types. [Learn more](#)

Add-ons

Find more add-ons

hero ✓

Heroku Postgres [Heroku Connect](#) [Apache Kafka on Heroku](#) [Heroku Redis](#)

VIDEOS

- Go to deploy tab, check "Github" and add your repository

Search

Manual deploy
Deploy the current state of a branch to this app.

Deploy a GitHub branch
This will deploy the current state of the branch you specify below. [Learn more](#).

Choose a branch to deploy

▼ Deploy Branch

Heroku Git Use Heroku CLI

 GitHub **Connected** 

Container Registry Use Heroku CLI

Connected to  [luchob/mobilele-heroku](#) by  [luchob](#) Disconnect...

↳ Releases in the [activity feed](#) link to GitHub to view commit diffs

Manual deploy
Deploy the current state of a branch to this app.

Deploy a GitHub branch
This will deploy the current state of the branch you specify below. [Learn more](#).

Choose a branch to deploy

▼ Deploy Branch 

Receive code from GitHub

Build main b7254fbb

```
[INFO] -----  
[INFO] Total time: 16.236 s  
[INFO] Finished at: 2022-09-18T09:04:15Z  
[INFO] -----  
----> Discovering process types  
      Procfile declares types -> web  
----> Compressing...  
      Done: 127.4M
```

Autoscroll with output

View logs

The screenshot shows the Heroku dashboard for the 'mobilelele' app. The top navigation bar includes links for Personal, HEROKU, and GitHub. Below the navigation, there are tabs for Overview, Resources, Deploy, Metrics, Activity (which is selected), Access, and Settings. The Activity Feed shows a build log entry. On the right, there's a sidebar with options like Open app, More, View logs (which has a red checkmark and a cursor icon over it), View webhooks, Run console, Production check, Add to pipeline..., and Restart all dynos. The ID of the app is listed as 6c3504.

17.5. Deploying

За да се дисплеяват страниците при деплоинат проект в Heroku
/For displaying the html pages in a Heroku deployed project

```
@Configuration  
public class WebConfig implements WebMvcConfigurer {  
    private final StatsInterceptor statsInterceptor;  
    private LocaleChangeInterceptor localeChangeInterceptor;  
  
    public WebConfig(StatsInterceptor statsInterceptor, LocaleChangeInterceptor localeChangeInterceptor) {  
        this.statsInterceptor = statsInterceptor;  
        this.localeChangeInterceptor = localeChangeInterceptor;  
    }  
  
    @Override  
    public void addInterceptors(InterceptorRegistry registry) {  
        registry.addInterceptor(statsInterceptor);  
        registry.addInterceptor(localeChangeInterceptor);  
    }  
  
    import org.thymeleaf.templateresolver.ClassLoaderTemplateResolver;  
  
    @Bean  
    public ClassLoaderTemplateResolver myTemplateResolver(){
```

```

    ClassLoaderTemplateResolver configurer = new ClassLoaderTemplateResolver();
    configurer.setPrefix("templates/");
    configurer.setSuffix(".html");
    configurer.setTemplateMode(TemplateMode.HTML);
    configurer.setCharacterEncoding("UTF-8");
    configurer.setOrder(0);
    configurer.setCacheable(false);
    configurer.setCheckExistence(true);

    return configurer;
}
}

```

17.6. Actuator - Monitor and manage your application

Actuator

- Spring Boot includes a number of **additional features** to help you **monitor** and **manage** your application when you push it to production
- You can choose to manage and monitor your application by using **HTTP endpoints** or with **JMX**
- Auditing, health, and metrics gathering can also be **automatically applied** to your application

Actuator dependency

- The recommended way to enable the features is to add a dependency on the `spring-boot-starter-actuator` 'Starter'.

```

<dependencies>
  <dependency>
    <groupId>org.springframework.boot</groupId>
    <artifactId>spring-boot-starter-actuator</artifactId>
  </dependency>
</dependencies>

```

implementation 'org.springframework.boot:spring-boot-starter-actuator'

Actuator HTTP Endpoints

- HTTP Endpoints let you monitor and interact with your application
- Spring Boot includes a number of **built-in endpoints** and lets you add your own
- Each individual endpoint can be enabled or disabled and exposed

Actuator example

- For example, by default, the health endpoint is mapped to `/actuator`

```
← → ⌂ ⓘ localhost:8080/actuator

{"_links": {"self": {"href": "http://localhost:8080/actuator", "templated": false}, "health": {"href": "http://localhost:8080/actuator/health", "templated": false}, "health-path": {"href": "http://localhost:8080/actuator/health/{*path}", "templated": true}, "info": {"href": "http://localhost:8080/actuator/info", "templated": false}}}
```

Expose all actuator endpoints

- To expose **all** actuator **endpoints** you need to add in application.properties file:

management.endpoints.web.exposure.include=*

```
← → ⌂ ⓘ localhost:8080/actuator

{"_links": {"self": {"href": "http://localhost:8080/actuator", "templated": false}, "beans": {"href": "http://localhost:8080/actuator/beans", "templated": false}, "caches-cache": {"href": "http://localhost:8080/actuator/caches/{cache}", "templated": true}, "caches": {"href": "http://localhost:8080/actuator/caches", "templated": false}, "health": {"href": "http://localhost:8080/actuator/health", "templated": false}, "health-path": {"href": "http://localhost:8080/actuator/health/{*path}", "templated": true}, "info": {"href": "http://localhost:8080/actuator/info", "templated": false}, "conditions": {"href": "http://localhost:8080/actuator/conditions", "templated": false}, "configprops": {"href": "http://localhost:8080/actuator/configprops", "templated": false}, "env": {"href": "http://localhost:8080/actuator/env", "templated": false}, "env-toMatch": {"href": "http://localhost:8080/actuator/env/{toMatch}", "templated": true}, "loggers": {"href": "http://localhost:8080/actuator/loggers", "templated": false}, "loggers-name": {"href": "http://localhost:8080/actuator/loggers/{name}", "templated": true}, "heapdump": {"href": "http://localhost:8080/actuator/heapdump", "templated": false}, "threaddump": {"href": "http://localhost:8080/actuator/threaddump", "templated": false}, "metrics-requiredMetricName": {"href": "http://localhost:8080/actuator/metrics/{requiredMetricName}", "templated": true}, "metrics": {"href": "http://localhost:8080/actuator/metrics", "templated": false}, "scheduledtasks": {"href": "http://localhost:8080/actuator/scheduledtasks", "templated": false}, "mappings": {"href": "http://localhost:8080/actuator/mappings", "templated": false}}}}
```

Enabling Endpoints

application.properties

- If you prefer all endpoints to be disabled
 - Set the **management.endpoints.enabled-by-default = false**
- Use individual endpoint enabled properties
 - On example, enable info endpoint

management.endpoints.enabled-by-default=false

management.endpoint.info.enabled=true

application.yml

```
management:  
  endpoints:  
    web:  
      exposure:  
        include: ["*"]  
      base-path: "/admin"  
    server:  
      port: 8081
```

White listing – когато всичко е забранено, иказваме кое е разрешено само

Black listing – когато всичко е разрешено, иказваме кое е забранено само

Securing HTTP Endpoints

- You should take care to **secure** HTTP endpoints in the same way that you would any other sensitive URL
- If Spring Security is present, endpoints are **secured by default**
- Example of **custom security configuration** for HTTP endpoints
- EndpointRequest идва от актуатор
- Генерира линкове за бърза справка за разни/всички системни неща

```
@Configuration()  
public class ActuatorSecurity extends WebSecurityConfigurerAdapter {  
    @Override  
    protected void configure(HttpSecurity http) throws Exception {  
        http.requestMatcher(EndpointRequest.toAnyEndpoint()).authorizeRequests((requests) ->  
            requests.anyRequest().hasRole("ROLE_ADMIN"));  
        ...  
    }  
}
```

ИЛИ ТАКА:

```
@Override  
protected void configure(HttpSecurity http) throws Exception {  
    http.  
        authorizeRequests().  
        // with this line we allow access to all static resources  
        requestMatchers(PathRequest.toStaticResources().atCommonLocations()).per  
        // allow actuator endpoints    }  
        requestMatchers(EndpointRequest.toAnyEndpoint()).permitAll().
```



Implementing Custom Endpoints

- If you add a `@Bean` annotated with `@Endpoint`, any methods annotated with `@ReadOperation`, `@WriteOperation`, or `@DeleteOperation` are automatically exposed over JMX and, in a web application, over HTTP

```
@Component
@Endpoint(enableByDefault = true, id = "custom")
public class CustomEndpoint {
    @ReadOperation
    public String getMyEndpoint() {
        return "My custom endpoint";
    }
}
```

- If we want we can create Endpoints with `@RestControllerEndpoint` annotation

```
@Component
@RestControllerEndpoint( id="myRestEndpoint" )
public class MyRestEndpoint {

    @GetMapping("/test")
    @ResponseBody
    public String test(){
        return "My custom rest endpoint";
    }
}
```

Customizing properties

- Customizing the Management Endpoint Paths
 - `management.endpoints.web.base-path=/manage`
- Customizing the Management Server Port
 - `management.server.port=8081`
- Disabling HTTP Endpoints
 - `management.server.port=-1`

Vizualization Tools

- Using the Spring Boot Actuator give us a lot of **information** our application, but it's **not** very **user-friendly**
- Can be integrated with **Spring Boot Admin** for visualization, but it has its limitations and it's less popular
- Tools like **Micrometer**, **Prometheus** and **Grafana** are more commonly used for the monitoring and visualization and are language/framework-independent
 - These tools have their own set of data formats and converting the metrics data

17.6. Micrometer

Micrometer

- Solves the problem of being a **vendor-neutral data provider**
- Automatically **exposes /actuator/metrics data** into something your monitoring system can **understand**
- You need to include a vendor-specific micrometer dependency

Micrometer Dependency


- Micrometer is a separate open-sourced project and is not in the Spring ecosystem, so we have to explicitly add it as a dependency
- If using Prometheus, add its **specific** dependency

```
<dependency>
    <groupId>io.micrometer</groupId>
    <artifactId>micrometer-registry-prometheus</artifactId>
</dependency>
```

implementation 'io.micrometer:micrometer-registry-prometheus'

Micrometer Example

- After adding the micrometer dependency, we have a new endpoint - /actuator/prometheus
- The data is formatted in specific for Prometheus format



```
# HELP process_cpu_usage The "recent cpu usage" for the Java Virtual Machine process
# TYPE process_cpu_usage gauge
process_cpu_usage 2.560625718003065E-4
# HELP http_server_requests_seconds
# TYPE http_server_requests_seconds summary
http_server_requests_seconds_count{exception="None",method="GET",outcome="SUCCESS",status="200",uri="/actuator/prometheus",} 1.0
http_server_requests_seconds_sum{exception="None",method="GET",outcome="SUCCESS",status="200",uri="/actuator/prometheus",} 0.6256954
http_server_requests_seconds_count{exception="None",method="GET",outcome="SUCCESS",status="200",uri="/",} 2.0
http_server_requests_seconds_sum{exception="None",method="GET",outcome="SUCCESS",status="200",uri="/",} 0.0566226
# HELP http_server_requests_seconds_max
# TYPE http_server_requests_seconds_max gauge
http_server_requests_seconds_max{exception="None",method="GET",outcome="SUCCESS",status="200",uri="/actuator/prometheus",} 0.0
http_server_requests_seconds_max{exception="None",method="GET",outcome="SUCCESS",status="200",uri="/",} 0.0
# HELP jvm_classes_loaded_classes The number of classes that are currently loaded in the Java virtual machine
# TYPE jvm_classes_loaded_classes gauge
jvm_classes_loaded_classes 7273.0
# HELP jvm_threads_live_threads The current number of live threads including both daemon and non-daemon threads
# TYPE jvm_threads_live_threads gauge
jvm_threads_live_threads 28.0
# HELP jvm_memory_committed_bytes The amount of memory in bytes that is committed for the Java virtual machine to use
# TYPE jvm_memory_committed_bytes gauge
jvm_memory_committed_bytes{area="heap",id="G1 Survivor Space",} 3145728.0
jvm_memory_committed_bytes{area="heap",id="G1 Old Gen",} 2.62144E7
jvm_memory_committed_bytes{area="nonheap",id="Metaspace",} 3.2555008E7
jvm_memory_committed_bytes{area="nonheap",id="CodeHeap 'non-nmethods'",} 2555904.0
jvm_memory_committed_bytes{area="heap",id="G1 Eden Space",} 2.62144E7
jvm_memory_committed_bytes{area="nonheap",id="Compressed Class Space",} 4849664.0
jvm_memory_committed_bytes{area="nonheap",id="CodeHeap 'non-profiled nmethods'",} 7077888.0
# HELP jvm_memory_max_bytes The maximum amount of memory in bytes that can be used for memory management
# TYPE jvm_memory_max_bytes gauge
```

17.7. Prometheus

Prometheus

- Time-series database that **stores** the **metric** data by pulling it (using a built-in data scraper) **periodically** over HTTP
- Intervals between pulls can be configured
- Has a simple user interface where we can **visualize/query** on all of the **collected metrics**
- To configure Prometheus more precisely we use the **prometheus.yaml** file

Download and Configure Prometheus

- You can download Prometheus from [here](https://prometheus.io/download/) - <https://prometheus.io/download/>
- Configure Prometheus with **prometheus.yaml** file

global:

```
scrape_interval: 15s # By default, scrape targets every 15 seconds.  
# A scrape configuration containing exactly one endpoint to scrape:  
# Here it's Prometheus itself.  
scrape_configs:  
  # The job name is added as a Label `job=<job_name>` to any timeseries scraped from this  
  config.  
  - job_name: 'prometheus'  
    # Override the global default and scrape targets from this job every 5 seconds.  
    scrape_interval: 5s  
    static_configs:  
      - targets: [ 'localhost:9090' ]
```

Prometheus Dashboard

- After starting Prometheus, we can access it on <http://localhost:9090>

The screenshot shows the Prometheus web interface. At the top, there is a navigation bar with links for Prometheus, Alerts, Graph, Status, and Help. Below the navigation bar, there is a checkbox labeled "Enable query history". The main area contains a search bar with placeholder text "Expression (press Shift+Enter for newlines)". Below the search bar are two buttons: "Execute" and "- insert metric at cursor -". Underneath these buttons, there are two tabs: "Graph" and "Console", with "Graph" being the active tab. The "Graph" tab displays a timeline with arrows for navigating through time. Below the timeline, there is a table with two columns: "Element" and "Value". The table header says "no data". At the bottom left of the interface, there is a blue button labeled "Add Graph".

Prometheus Query Language – PromQL

- Prometheus provides a functional query language called **PromQL** (Prometheus Query Language)
- Let's the user **select** and **aggregate** time series data in real time
- Result of an expression can either be shown as a **graph**, viewed as **tabular data** in Prometheus' expression browser, or consumed by external systems via the **HTTP API**
- Return all time series with the metric `http_requests_total` and the **given job** and handler labels

```
http_requests_total{job="apiserver", handler="/api/comments"}
```

- Return a whole **range of time** for the same vector

```
http_requests_total{job="apiserver", handler="/api/comments"}[5m]
```

- Using **regular expressions**
- ```
http_requests_total{job=~".*server"}
http_requests_total{status!~"4..")}
```

## 18. Reactive programming

### 18.1. What is Reactive Programming

#### Reactive Programming


- Is a model of coding where **communication happens** through a **non-blocking stream of data**
- Makes code "reactive", **reacting to change** and **not being blocked**, such as performing operations that read/wait for responses from a database or file
- Can react to **events** as data **becomes available**
- Using it we can use **effective resources utilization** (CPU cores) for computing
- It's principles are based on the **Reactive Manifesto**
- It is build around **publisher-subscriber pattern** (observer pattern)
- In non-blocking code, the **Back pressure** becomes important to **control the rate of events** so that a fast producer does **not overwhelm** its destination

Една щайга ябълка в устата – ми не. Вземам една ябълка, като я изям подавам сигнал, че искам следваща ябълка. **Backpressure** е количеството информация, която нашия **consumer** желае да получи.


Traditional MVC is Blocking vs Non-blocking

Първа нишка при традиционния вариант се отблокира навреме/веднага.

Но втора и трета нишка стоят блокирани при традиционния blocking вариант за доста време.



Изпращаме заявка към базата данни, след като нишката изпрати заявката, то спира да служи тук, и прави процесорно нещо друго. След като данните са взети от базата, то тази съща нишка или друга нишка отново се заема със заявката – този път да върне отговора от базата данни.



#### Reactive Streams and Reactor

- **Reactive Streams:** is a **specification** that defines how an API that implements and follows the Reactive Programming paradigm should work
- **Reactor:** is a Java implementation of the Reactive Streams specification
- **Spring WebFlux** is the "reaction" of Spring for this paradigm to use on web applications

#### Reactive Streams VS Java 8 Streams

- The core difference is that **Reactive** is a **push model**, whereas the **Java 8 Streams** are a **pull model**
  - In reactive events are pushed to the subscribers as they come in
- **Java 8 Streams** - pulling all the data and returning a result
- With **Reactive** we could have an **infinite stream** coming in from an external resource, with **multiple subscribers** attached

#### Reactive Stream APIs

- As per **Java 9 and reactive specification** below are API we need to use for reactive implementation
  - **Publisher** - Emits a sequence of events to subscribers according to the demand received from its subscribers
  - **Subscriber(Consumer)** - Receives&Processes events emitted by a Publisher
  - **Subscription** - Defines a one-to-one relationship between a Publisher and a Subscriber
  - **Processors** - Represents a processing stage consisting of both a Publisher and a Subscriber (Consumer) and obeys the contracts of both = **a pipe from a Publisher and a Subscriber**


#### Spring 5 Reactive Building Blocks

- **WebFlux**
- **Spring Data reactive library**

- Reactive IO
- Nonblocking Servlet container
- Spring security reactive API

Spring 5 Reactive Building Blocks

- [Source - https://docs.spring.io/](https://docs.spring.io/)



## 18.2. Spring WebFlux

### Spring WebFlux

- Spring WebFlux е **алтернатива** на стандартния Spring MVC (макар че могат да се използват и заедно)
- **Web framework** that brings support for the **reactive** programming model
- Implemented **using the Project Reactor**, and its publisher implementations — **Flux** and **Mono**, the library chosen by Spring
- WebFlux is **not a replacement for Spring MVC** they can actually complement each other, working together on the same solution

### Spring WebFlux Dependencies

- Adding Spring WebFlux Dependency in pom.xml
- The Reactive Web dependency includes Spring WebFlux dependency

```
<dependency>
 <groupId>org.springframework.boot</groupId>
 <artifactId>spring-boot-starter-webflux</artifactId>
</dependency>
```

## Mono and Flux

**Mono** – може да еmit-ва 0 или 1 парче данни

**Flux** – може да еmit-ва наведнъж повече от едно парче данни

- In WebFlux, the data returned from any operation is packed into a **reactive stream**
- There are **two types** that embody this approach and are the building blocks in WebFlux:
- **Mono** - is a stream which returns zero items or a single item (0..1)
- **Flux** - is a stream which returns zero or more items (0..n)

## Working with Mono and Flux

- **Mono/Flux.just()**

- The easiest way to emit an element is using the **just** method

```
Mono.just(1).subscribe(System.out::println);
Flux.just(1,2,3).subscribe(System.out::println);
```

- Mono/Flux can have more than one **subscribers**

```
Flux<Integer> flux = Flux.just(1,2,3);
flux.subscribe(s->System.out.println("Subscr One-"+ s));
flux.subscribe(s->System.out.println("Subscr Two-"+ s));
```

- Example of **two subscribers** with delay

```
Flux<Integer> flux = Flux.just(1, 2, 3);
flux
 .map(n -> ++n)
 .delayElements(Duration.ofMillis(500))
 .subscribe(System.out::println); //2, 3, 4

flux
 .delayElements(Duration.ofMillis(1000))
 .subscribe(s -> System.out.println("Subscriber One-" + s)); //1, 2, 3
```

- The **subscribe** method could accept other parameters as well to handle the **error** and **completion** calls

```
Flux.just(1, 2, 3)
 .subscribe(
 i -> System.out.println("Received :: " + i),
 err -> System.out.println("Error :: " + err),
 () -> System.out.println("Successfully completed")) //completion - моментът
когато няма повече инфо в нашия flux
);
```


## 18.3. Programming Models

### Programming Models

- We can implement it in two ways:

- **Annotated Controllers**
  - using Spring MVC annotations with minimum modifications
  - The old applications can also be converted to reactive nature and can use its features and benefits
- **Functional Endpoints**
  - functional lambda style of programming

#### Annotated Controllers VS Func Endpoints



#### Annotated Controllers

- **Similar** to how we use controllers in **classic Spring MVC**
- To mark a class as a controller, we use the **@RestController** annotation on a class level.
- Having Spring WebFlux and the Reactor Core dependencies, in the class path, will let Spring know that the **@RestController** is in fact a reactive component and add support for **Mono** and **Flux**

#### Annotated Controllers Example

- Annotated Controller Example

```

@RestController
@RequestMapping("/students")
public class StudentsControllers {
 //Inject studentsService in constructor

 @GetMapping("/all")
 public Flux<Students> findAll(){
 return studentsService.findAll();
 }
}

```

## Functional Endpoints

- Spring WebFlux includes **WebFlux.fn**, a lightweight functional programming model in which functions are used to **route** and **handle requests** and contracts are designed for immutability
- An HTTP request is handled with a **HandlerFunction** that takes ServerRequest and returns a delayed ServerResponse - **Mono<ServerResponse>**
- Incoming requests are routed to a handler function with a **RouterFunction** - takes ServerRequest and returns a delayed HandlerFunction - **Mono<HandlerFunction>**

## Functional Endpoints Example – Handler

- Example of Student Handler

```
public class StudentHandler {
 //...
 public Mono<ServerResponse> getStudent(ServerRequest request) {
 int studentId = Integer.valueOf(request.pathVariable("id"));
 return repository.getStudent(studentId)
 .flatMap(student -> ok().contentType(APPLICATION_JSON).bodyValue(student))
 .switchIfEmpty(ServerResponse.notFound().build());
 } //... }
```

## Functional Endpoints Example – Router

- Example of Router Function

```
//... Inject PersonHandler handler in constructor

RouterFunction<ServerResponse> router = router()
 .GET("/student/{id}", accept(APPLICATION_JSON), handler::getStudent)
 .GET("/student ", accept(APPLICATION_JSON), handler::listStudents)
 .POST("/student ", handler::createStudent)
 .build();
```

## Spring WebFlux Configuration – за по-стари Spring версии

- The **@Configuration** and **@EnableWebFlux** annotations mark a class as a configuration class and Spring's bean management will register it
- To use or extend the existing WebFlux configuration API, you can implement **WebFluxConfigurer**

```
@Configuration
@EnableWebFlux
public class Configuration implements WebFluxConfigurer {...}
```

## 18.4. Demo – the 4 interfaces of reactive streams

```
import java.util.LinkedList;
import java.util.List;
import java.util.concurrent.Flow.Subscription;
import java.util.concurrent.Flow.Subscriber;

//I.e. this is the consumer
public class SimpleSubscriber<T> implements Subscriber<T> {
 private List<T> consumedElements = new LinkedList<>();
 private Subscription subscription;
```

```

@Override
public void onSubscribe(Subscription subscription) {
 this.subscription = subscription;
 subscription.request(1);
}

@Override
public void onNext(T item) {
 consumedElements.add(item);

 //Applying backpressure - искам вече следващото
 subscription.request(1);
}

@Override
public void onError(Throwable throwable) {
 throwable.printStackTrace();
}

@Override
public void onComplete() {
 System.out.println("I'm complete!!!");
 consumedElements.forEach(System.out::println);
 System.out.println("-----");
}

public int getConsumedElementsCount(){
 return consumedElements.size();
}

public List<T> getConsumedElements() {
 return consumedElements;
}
}

import java.util.concurrent.Flow.Processor;
import java.util.concurrent.Flow.Subscriber;
import java.util.concurrent.Flow.Subscription;
import java.util.concurrentSubmissionPublisher;
import java.util.function.Function;

public class TransformationProcessor<T, R> implements Processor<T, R> {
 private final Function<T, R> transformation;
 private final SubmissionPublisher<R> submissionPublisher;
 private Subscription subscription;

 //нешо като pipe - ще получаваме от нашия publisher едни елементи, и ще ги превръщаме в
 //други елементи
 public TransformationProcessor(Function<T, R> transformation) {
 this.transformation = transformation;
 this.submissionPublisher = new SubmissionPublisher<R>();
 }

 //publisher

```

```

@Override
public void subscribe(Subscriber<? super R> subscriber) {
 submissionPublisher.subscribe(subscriber);
}

//publisher
@Override
public void onSubscribe(Subscription subscription) {
 this.subscription = subscription;
 subscription.request(1); //the backpressure
}

//Subscriber/producer
@Override
public void onNext(T item) {
 R transformed = transformation.apply(item);
 submissionPublisher.submit(transformed); //събmittваме надолу по веригата
 this.subscription.request(1); //the backpressure
}

//Subscriber/producer
@Override
public void onError(Throwable throwable) {
 throwable.printStackTrace();
}

//Subscriber/producer
@Override
public void onComplete() {
 System.out.println("Transformation is complete, closing down.");
}
}

import java.util.List;
import java.util.concurrent.SubmissionPublisher;
import java.util.concurrent.TimeUnit;
import java.util.function.Function;

import static org.awaitility.Awaitility.await;
import static org.junit.jupiter.api.Assertions.*;

class ReactiveTests {

 @Test
 void testAllItemsConsumed() {
 //The producer!!!
 SubmissionPublisher<String> publisher = new SubmissionPublisher<>();

 SimpleSubscriber<String> mySubscriber = new SimpleSubscriber<>();

 //set new consumer for producer publisher
 publisher.subscribe(mySubscriber);

 assertEquals(1, publisher.getNumberOfSubscribers()); //Returns the number of current
subscribers.
 }
}

```

```

List<String> names = List.of("Anna", "John", "Pesho");
names.forEach(item -> publisher.submit(item)); //submit = publishes the given items to
each current subscriber
publisher.close();

//Make it synchronous with the awaitility Library
await()
 .atMost(1, TimeUnit.SECONDS)
 .until(
 () -> mySubscriber.getConsumedElementsCount() == names.size()
);

assertEquals(3, mySubscriber.getConsumedElementsCount());
}

@Test
public void testTransformation() {
 //arrange = given part
 Function<String, String> transfFunc = String::toUpperCase;
 TransformationProcessor<String, String> transformationPipe = new
TransformationProcessor<>(transfFunc);

 SubmissionPublisher<String> startPublisher = new SubmissionPublisher<>();
 SimpleSubscriber<String> finishSubscriber = new SimpleSubscriber<>();

 List<String> items = List.of("SenKo", "Pesho", "lilly"); //от едната страна на pipe-a
 List<String> expectedItems = List.of("SENKO", "PESHO", "LILLY"); //какво излизза от
другата страна на pipe-a

 //act = when
 startPublisher.subscribe(transformationPipe); //началната точка на pipe-a
 transformationPipe.subscribe(finishSubscriber); //краината точка на Pipe-a

 items.forEach(item -> startPublisher.submit(item));
 startPublisher.close();

 //Make it synchronous with the awaitility Library
 await()
 .atMost(1, TimeUnit.SECONDS)
 .until(
 () -> expectedItems.equals(finishSubscriber.getConsumedElements())
);

 //assert
 assertEquals(expectedItems, finishSubscriber.getConsumedElements());
}
}

```

## 18.5. Demo – Mono and Flux

### Spring Reactive Web

```

dependencies {
 implementation 'org.springframework.boot:spring-boot-starter-webflux'
 testImplementation 'org.springframework.boot:spring-boot-starter-test'

```

```
 testImplementation 'io.projectreactor:reactor-test'
}

import reactor.core.publisher.Flux;
import reactor.core.publisher.Mono;

import java.util.List;
import java.util.Optional;
import java.util.Random;

public class FluxMonoExplained {
 private User user1 = new User().setFirstName("A").setLastName("B");
 private User user2 = new User().setFirstName("A1").setLastName("B1");

 public User getUser() {
 if (isAuthenticated()) {
 return user1;
 } else {
 return null;
 }
 }

 public Mono<User> getUserReactive() {
 if (isAuthenticated()) {
 return Mono.just(user1);
 } else {
 return Mono.empty();
 }
 }

 public Optional<User> getUserOpt() {
 if (isAuthenticated()) {
 return Optional.of(user1);
 } else {
 return Optional.empty();
 }
 }

 public List<User> getAllUsers() {
 return List.of(user1, user2);
 }

 public Flux<User> getAllUsersReactive() {
 return Flux.just(user1, user2);
 }

 private boolean isAuthenticated() {
 return new Random().nextBoolean();
 }
}

class User {
 private String firstName, lastName;

 public String getFirstName() {
```

```

 return firstName;
 }

 public User setFirstName(String firstName) {
 this.firstName = firstName;
 return this;
 }

 public String getLastName() {
 return lastName;
 }

 public User setLastName(String lastName) {
 this.lastName = lastName;
 return this;
 }
}

import org.junit.jupiter.api.Test;
import reactor.core.publisher.Flux;
import reactor.core.publisher.Mono;

import java.util.function.Consumer;
import java.util.stream.Collectors;

class WebfluxGeneralTest {
 @Test
 public void fluxToStream() {
 Flux<String> springProjectsFlux = Flux.just(getSpringProjects());

 springProjectsFlux
 .toStream()
 .map(String::toUpperCase)
 .forEach(System.out::println);
 }

 @Test
 public void subscribeToFlux() {
 Flux<String> springProjectsFlux = Flux.just(getSpringProjects());

 springProjectsFlux.subscribe(
 System.out::println
);
 }

 @Test
 public void doOnEach() {
 Flux<String> springProjectsFlux = Flux.just(getSpringProjects());

 springProjectsFlux.doOnEach(
 signalConsumer -> {
 if (signalConsumer.isOnNext()) {
 System.out.println(signalConsumer.get());
 }
 }
)
 }
}

```

```

 .subscribe();
 }

 @Test
 public void mapAndFilter() {
 Flux<String> springProjectsFlux = Flux.just(getSpringProjects());

 springProjectsFlux
 .map(String::toUpperCase)
 .filter(s -> s.contains("REST"))
 .subscribe(System.out::println);
 }

 @Test
 public void collect() {
 Flux<String> springProjectsFlux = Flux.just(getSpringProjects());

 springProjectsFlux
 .map(String::length)
 .collect(Collectors.summarizingInt(Integer::intValue))//статистика от дължината
на всички заглавия
 .subscribe(System.out::println);

 // IntSummaryStatistics{count=7, sum=85, min=10, average=12.142857, max=16}
 }

 @Test
 public void subscribe() {
 Flux<String> springProjectsFlux = Flux.just(getSpringProjects());

 Consumer<String> onNextConsumer = System.out::println;
 Consumer<Throwable> onErrorConsumer = Throwable::printStackTrace;
 Runnable onDone = () -> System.out.println("We are done!");

 springProjectsFlux.subscribe(
 onNextConsumer,
 onErrorConsumer,
 onDone
);
 }

 @Test
 public void testOnError() {
 Flux<Integer> numbers = Flux.just("1", "two", "3")
 .map(Integer::parseInt);

 Consumer<Integer> onNextConsumer = System.out::println;
 Consumer<Throwable> onErrorConsumer = Throwable::printStackTrace;
 Runnable onDone = () -> System.out.println("We are done!");

 numbers.subscribe(
 onNextConsumer,
 onErrorConsumer, //throws error this time
 onDone
);
 }
}
```

```

@Test
public void mono(){
 Mono.just("TEST").map(String::toUpperCase).subscribe(System.out::println);
}

private String[] getSpringProjects() {
 return new String[]{
 "Spring REST",
 "Spring DATA REST",
 "Spring Batch", //Java Batching
 "Spring MVC",
 "Spring Webflux",
 "Spring JMS", //Java Messaging Service
 "Spring Kafka"};
}

import org.junit.jupiter.api.Test;
import reactor.core.publisher.Flux;
import reactor.core.schedulers.Schedulers;

public class AsyncFlux {

 //синхронно
 @Test
 public void syncFlux() {
 MyInteger sum = new MyInteger(0);

 Flux.just(1, 2, 3, 4)
 .reduce(MyInteger::sum)
 .subscribe(sum::set);

 System.out.println(sum);

 // Output
 // Summing 1 and 2
 // Summing 3 and 3
 // Summing 6 and 4
 // MyInteger{initialValue=10}
 }

 //асинхронно
 @Test
 public void asyncFlux() {
 MyInteger sum = new MyInteger(0);

 Flux.just(1, 2, 3, 4)
 .subscribeOn(Schedulers.boundedElastic())
 .reduce(MyInteger::sum)
 .subscribe(sum::set);

 System.out.println(sum);
 }
}

```

```

 //Output
 // MyInteger{initialValue=0}
 // Summing 1 and 2
 // Summing 3 and 3
 // Summing 6 and 4
 }

}

class MyInteger {
 private Integer initialValue;

 public MyInteger(Integer initialValue) {
 this.initialValue = initialValue;
 }

 public static int sum(int a, int b) {
 System.out.println("Summing " + a + " and " + b);
 return a + b;
 }

 public void set(Integer aNumber) {
 this.initialValue = aNumber;
 }

 @Override
 public String toString() {
 return "MyInteger{" +
 "initialValue=" + initialValue +
 '}';
 }
}

```

## 18.6. Demo – webflux service

//При реактивното програмиране в Spring, за endpoint-и използваме бийнове вместо @Controller, @RequestMapping, и т.н.

See in my repo in GitHub

```

2022-10-19 23:37:43.891 INFO 14744 --- [main] b.s.w.WebfluxserviceApplication
: No active profile set, falling back to 1 default profile: "default"
2022-10-19 23:37:45.571 INFO 14744 --- [main]
o.s.b.web.embedded.netty.NettyWebServer : Netty started on port 8080
2022-10-19 23:37:45.584 INFO 14744 --- [main] b.s.w.WebfluxserviceApplication
: Started WebfluxserviceApplication in 2.201 seconds (JVM running for

```

```

public class ExchangeRate {
 private String fromCurrency;
 private String toCurrency;
 private Instant time;
 private BigDecimal rate;
}

```

```
public ExchangeRate(String fromCurrency, String toCurrency, Instant time, BigDecimal rate) {
 this.fromCurrency = fromCurrency;
 this.toCurrency = toCurrency;
 this.time = time;
 this.rate = rate;
}
}
```

```

@Service
public class ExchangeRateService {

 private List<ExchangeRate> exchangeRates = new ArrayList<>();

 public ExchangeRateService() {
 exchangeRates.add(new ExchangeRate("EUR", "BGN", Instant.now(), BigDecimal.valueOf(1.96)));
 exchangeRates.add(new ExchangeRate("USD", "BGN", Instant.now(), BigDecimal.valueOf(1.74)));
 exchangeRates.add(new ExchangeRate("GBN", "BGN", Instant.now(), BigDecimal.valueOf(2.16)));
 exchangeRates.add(new ExchangeRate("RSD", "BGN", Instant.now(), BigDecimal.valueOf(0.017)));
 }

 public Flux<ExchangeRate> getExchangeRateStream(int durationInterval) {
 Flux<ExchangeRate> ret = Flux.generate(() -> 0,
 (index, sink) -> {
 ExchangeRate updateRate = randomize(exchangeRates.get(index));
 sink.next(updateRate);
 System.out.println("Generated a new exchange rate...");
 return (++index) % exchangeRates.size();
 });
 if (durationInterval > 0) {
 return ret.delayElements(Duration.ofSeconds(durationInterval));
 } else {
 return ret;
 }
 }
}
```

```

@Component
public class ExchangeRateHandler {
 private final ExchangeRateService exchangeRateService;

 public ExchangeRateHandler(ExchangeRateService exchangeRateService) {
 this.exchangeRateService = exchangeRateService;
 }

 public Mono<ServerResponse> getExchangeRates(ServerRequest request) {
 int size = Integer.parseInt(request.queryParam("size").orElse("10"));

 //Вземане на моно от отложен server response
 return ok()
 .contentType(MediaType.APPLICATION_JSON)
 .body(this.exchangeRateService.getExchangeRateStream(0).take(size),
 ExchangeRate.class);
 }
}
```

```

public Mono<ServerResponse> streamExchangeRates(ServerRequest request) {
 int size = Integer.parseInt(request.queryParam("size").orElse("10"));

 //Вземане на моно от отложен server response
 return ok()
 .contentType(MediaType.APPLICATION_STREAM_JSON)
 .body(this.exchangeRateService.getExchangeRateStream(1).take(size),
 ExchangeRate.class);
}

//При реактивното програмиране в Spring, за endpoint-и използваме бийнове вместо @Controller,
@RequestMapping, и т.н.
@Configuration
public class ExchangeRateRouter {

 @Bean
 public RouterFunction<ServerResponse> route(ExchangeRateHandler exchangeRateHandler) {
 return RouterFunctions
 .route(GET("/rates").and(accept(MediaType.APPLICATION_JSON)),
exchangeRateHandler::getExchangeRates)
 .andRoute(GET("/rates").and(accept(MediaType.APPLICATION_STREAM_JSON)), sr ->
exchangeRateHandler.streamExchangeRates(sr));
 }
}

```

## 18.7. Demo – webflux client with Reactive MongoDB driver

//При реактивното програмиране в Spring, за endpoint-и използваме бийнове вместо @Controller, @RequestMapping, и т.н.

The screenshot shows the Spring Initializr interface with the following configuration:

- Project:** Gradle Project
- Language:** Java
- Dependencies:**
  - Spring Reactive Web** (WEB): Build reactive web applications with Spring WebFlux and Netty.
  - Spring Data Reactive MongoDB** (NOSQL): Provides asynchronous stream processing with non-blocking back pressure for MongoDB.


```

docker-compose.yaml
version: 3.1
services:
mongo:
image: mongo
restart: always
ports:
- 27017:27017

```

в терминала команда docker-compose up

Mongo graphic user interface GUI  
Robo 3T is now Studio 3T Free



```
import org.springframework.boot.context.properties.ConfigurationProperties;
import org.springframework.boot.context.properties.EnableConfigurationProperties;
import org.springframework.context.annotation.Configuration;

@Configuration
@EnableConfigurationProperties
@ConfigurationProperties("softuni.webflux.client")
public class ClientConfig {
 private String schema;
 private String host;
 private String port;
}

application.yml
softuni:
 webflux:
 client:
 schema: http
 host: localhost
 port: 8000

import org.springframework.data.annotation.Id;
import org.springframework.data.mongodb.core.mapping.Document;

import java.math.BigDecimal;
import java.time.Instant;

@Document //како @Entity анотацията за релационните база данни, но за MongoDB
public class ExchangeRate {
 @Id
 private String id;

 private String fromCurrency;
 private String toCurrency;
 private Instant time;
 private BigDecimal rate;
}

@Component
public class ExchangeRateClient {
 private final String SERVICE_URL;
 private final String API_PATH = "/rates";

 public ExchangeRateClient(ClientConfig clientConfig) {
 SERVICE_URL = clientConfig.getSchema() + "://" + clientConfig.getHost() + ":" +
clientConfig.getPort();
 }
}
```

```

public Flux<ExchangeRate> getRateStream(){
 return WebClient.builder()
 .baseUrl(SERVICE_URL)
 .build()
 .get()
 .uri(API_PATH)
 .accept(MediaType.APPLICATION_STREAM_JSON)
 .retrieve()
 .bodyToFlux(ExchangeRate.class);
}

@Repository
public interface ExchangeRateRepository extends ReactiveMongoRepository<ExchangeRate, String> {

}

@Service
public class ExchangeRateInit implements ApplicationListener<ContextRefreshedEvent> {

 private final ExchangeRateClient client;
 private final ExchangeRateRepository repository;

 public ExchangeRateInit(ExchangeRateClient client, ExchangeRateRepository repository) {
 this.client = client;
 this.repository = repository;
 }

 @Override
 public void onApplicationEvent(ContextRefreshedEvent event) {
 client.getRateStream()
 .subscribe(exchangeRate -> {
 Mono<ExchangeRate> exchangeRateMono = repository.save(exchangeRate);
 exchangeRateMono.subscribe(er -> System.out.println("Saved " + er));
 });
 }
}

```

## 27. Pagination and Search with Specification and CriteriaBuilder at the server-side rendering

```

public interface JpaSpecificationExecutor<T> {
 List<T> findAll(@Nullable Specification<T> spec);
 Page<T> findAll(@Nullable Specification<T> spec, Pageable pageable);
 List<T> findAll(@Nullable Specification<T> spec, Sort sort);

```

We can not implement specification in a @Query() JPQL, so we need to use only through the itemRepository.findAll - **not sure actually**

```

@Repository
public interface AllItemsRepository extends
PagingAndSortingRepository<ItemEntity, Long>,
JpaSpecificationExecutor<ItemEntity> {
 Page<ItemEntity> findAllByType(String type, Pageable pageable);
}
}

import bg.softuni.computerStore.model.binding.product.SearchProductItemDTO;
import bg.softuni.computerStore.model.entity.products.ItemEntity;
import org.springframework.data.jpa.domain.Specification;

import javax.persistence.criteria.*;

public class ProductItemSpecification implements Specification<ItemEntity> {
 private final SearchProductItemDTO searchProductItemDTO;
 private final String type;

 public ProductItemSpecification(SearchProductItemDTO searchProductItemDTO, String type) {
 this.searchProductItemDTO = searchProductItemDTO;
 this.type = type;
 }

 @Override
 public Predicate toPredicate(Root<ItemEntity> root,
 CriteriaQuery<?> query,
 CriteriaBuilder cb) {
 Predicate predicate = cb.conjunction();

 predicate.getExpressions().add(cb.equal(root.get("type"), type));

 if (searchProductItemDTO.getModel() != null &&
!searchProductItemDTO.getModel().isBlank()) {
 Path<Object> model = root.get("model");
 predicate.getExpressions().add(
 //!!!!!! when we have two relationally connected tables
// cb.and(cb.equal(root.join("model").get("name"),
// searchProductItemDTO.getModel())));
 //when all fields are from the same table ItemEntity:::: the Like works case
insensitive
 cb.and(cb.like(root.get("model").as(String.class), "%" + searchProductItemDTO.getModel() + "%"))
);
 }

 if (searchProductItemDTO.getMinPrice() != null) {
 predicate.getExpressions().add(
 cb.and(cb.greaterThanOrEqualTo(root.get("sellingPrice"),
 searchProductItemDTO.getMinPrice())))
);
 }
 }
}

```

```

 if (searchProductItemDTO.getMaxPrice() != null) {
 predicate.getExpressions().add(
 cb.and(cb.lessThanOrEqualTo(root.get("sellingPrice"),
 searchProductItemDTO.getMaxPrice())))
);
 }

 return predicate;
}
}

@Service
public class ComputerService implements InitializableProductService {
 private final AllItemsRepository allItemsRepository;
 private final StructMapper structMapper;
//Simpler option for pagination only
 public Page<ComputerViewGeneralModel> getAllComputersPageable(Pageable pageable) {
 Page<ComputerViewGeneralModel> allComputers = this.allItemsRepository
 .findAllByType("computer", pageable)
 .map(comp -> this.structMapper
 .computerEntityToComputerSalesViewGeneralModel((ComputerEntity) comp));

 return allComputers;
 }

 //Complicated use
 public Page<ComputerViewGeneralModel> getAllComputersPageableAndSearched(
 Pageable pageable, SearchProductItemDTO searchProductItemDTO, String type) {
 Page<ComputerViewGeneralModel> allComputers = this.allItemsRepository
 .findAll(new ProductItemSpecification(searchProductItemDTO, type), pageable)
 .map(comp -> this.structMapper
 .computerEntityToComputerSalesViewGeneralModel((ComputerEntity) comp));

 return allComputers;
 }
}

@Controller
@RequestMapping("/items/all")
public class ViewItemsController {
 private final ComputerService computerService;

 @GetMapping("/computer")
 public String viewAllComputers(Model model,
 @Valid SearchProductItemDTO searchProductItemDTO,
 @PageableDefault(page = 0,
 size = 3,
 sort = "sellingPrice",
 direction = Sort.Direction.ASC) Pageable pageable,
 RedirectAttributes redirectAttributes) {

 if (!model.containsAttribute("searchProductItemDTO")) {

```

```

 model.addAttribute("searchProductItemDTO", searchProductItemDTO);
 }

Page<ComputerViewGeneralModel> computers = this.computerService
 .getAllComputersPageableAndSearched(pageable, searchProductItemDTO, "computer");
model.addAttribute("computers", computers);

redirectAttributes.addFlashAttribute("searchProductItemDTO", searchProductItemDTO);

return "/viewItems/all-computers";
}

```

```

<main>
 <div class="container-fluid">
 <div class="container">
 <h2 class="text-center text-white">Search for offers</h2>
 <form
 th:method="GET"
 th:action="@{/items/all/computer}"
 th:object="${searchProductItemDTO}"
 class="form-inline"
 style="justify-content: center; margin-top: 50px;">
 <div style="position: relative">
 <input
 th:field="*{model}"
 th:errorclass="is-invalid"
 class="form-control mr-sm-2"
 style="width: 280px;"
 type="search"
 placeholder="Model name case Insensitive..."
 aria-label="Search"
 id="model"
 />
 <input
 th:field="*{minPrice}"
 th:errorclass="is-invalid"
 class="form-control mr-sm-2"
 style="width: 280px;"
 type="search"
 placeholder="Min price..."
 aria-label="Search"
 id="minPrice"
 />
 <input
 th:field="*{maxPrice}"
 th:errorclass="is-invalid"
 class="form-control mr-sm-2"
 style="width: 280px;"
 type="search"
 placeholder="Max price..."
 aria-label="Search"
 id="maxPrice"
 />
 </div>
 <!-- <small-->

```

```
<!--
<!--
<!--
align: center;"-->
<!--
 >-->
 Try writing something this time.-->
 </small>-->
 </div>
 <button class="btn btn-outline-info my-2 my-sm-0" type="submit">Search</button>
 </form>
</div>

<h2 class="text-center text-white mt-5 greybg" th:text="#{view_all_computers}">.....All
 Computers.....</h2>
<div class="offers row mx-auto d-flex flex-row justify-content-center .row-cols-auto">
 <div
 th:each="c : ${computers}" th:object="${c}"
 class="offer card col-sm-2 col-md-3 col-lg-3 m-2 p-0">
 <div class="card-img-top-wrapper" style="height: 20rem">

 </div>
 <div class="card-body pb-1">
 <h5 class="card-title"
 th:text=' Model: ' + *{model}">
 Model name</h5>
 </div>
 <ul class="offer-details list-group list-group-flush">
 <li class="list-group-item">
 <div class="card-text">Processor</div>
 <div class="card-text">Video card</div>
 <div class="card-text">Ram</div>
 <div class="card-text">Disk</div>
 <div th:if="*{!ssd.isBlank()}" class="card-text">SSD</div>
 <div th:if="*{!moreInfo.isBlank()}" class="card-text">More
info
 </div>
 <div class="card-text">
 style="font-weight: bold">Selling price</div>

 <div class="card-body">
 <div class="row">
 <a class="btn btn-link"
 th:href="@{/items/all/computer/details/{id} (id*{itemId})}">Details
 <th:block sec:authorize="hasRole('ADMIN') || hasRole('EMPLOYEE_PURCHASES')">
 <a class="btn btn-link alert-danger"
 th:href="@{/pages/purchases/computers/{id}/edit (id*{itemId})}">Update
 <form th:action="@{/pages/purchases/computers/delete/{id} (id*{itemId})}"
 th:method="delete">
 <input type="submit" class="btn btn-link alert-danger" value="Delete"></input>
 </form>
 </th:block>
 </div>
 </div>
</div>

<div class="container-fluid row justify-content-center">
 <nav>
 <ul class="pagination">
 <li class="page-item" th:classappend="${computers.isFirst()} ? 'disabled' : ''">
```

```

 <a th:unless="${computers.isFirst()}"
 class="page-link"

th:href="@{/items/all/computer(size=${computers.getSize()},page=0,model=${searchProductItemDTO.getModel()},minPrice=${searchProductItemDTO.getMinPrice()},maxPrice=${searchProductItemDTO.getMaxPrice()})}">First

</nav>
<nav>
 <ul class="pagination">
 <li class="page-item" th:classappend="${computers.hasPrevious() ? '' : 'disabled'}">
 <a th:if="${computers.hasPrevious()}"
 class="page-link"

th:href="@{/items/all/computer(size=${computers.getSize()},page=${computers.getNumber() - 1},model=${searchProductItemDTO.getModel()},minPrice=${searchProductItemDTO.getMinPrice()},maxPrice=${searchProductItemDTO.getMaxPrice()})}">Previous

 </nav>
 <nav>
 <ul class="pagination">
 <li class="page-item" th:classappend="${computers.hasNext() ? '' : 'disabled'}">
 <a th:if="${computers.hasNext()}"
 class="page-link"

th:href="@{/items/all/computer(size=${computers.getSize()},page=${computers.getNumber() + 1},model=${searchProductItemDTO.getModel()},minPrice=${searchProductItemDTO.getMinPrice()},maxPrice=${searchProductItemDTO.getMaxPrice()})}">Next

 </nav>
 <nav>
 <ul class="pagination">
 <li class="page-item" th:classappend="${computers.isLast() ? 'disabled' : ''}">
 <a th:unless="${computers.isLast()}"
 class="page-link"

th:href="@{/items/all/computer(size=${computers.getSize()},page=${computers.getTotalPages() - 1},model=${searchProductItemDTO.getModel()},minPrice=${searchProductItemDTO.getMinPrice()},maxPrice=${searchProductItemDTO.getMaxPrice()})}">Last

 </nav>
</div>
</div>
</main>

```

## 28. OAuth 2 Simplified

<https://aaronparecki.com/oauth-2-simplified/>

```
<!-- https://mvnrepository.com/artifact/org.springframework.security/spring-security-oauth2-client -->
<dependency>
 <groupId>org.springframework.security</groupId>
 <artifactId>spring-security-oauth2-client</artifactId>
 <version>5.7.1</version>
</dependency>
```

The screenshot shows the 'Create an App' wizard on the Facebook Developers website. The user has selected the 'Type' tab. In the 'Select an app type' section, the 'Business' option is highlighted with a red checkmark. Other options like 'Consumer', 'Instant Games', 'Gaming', 'Workplace', and 'Academic research' are also listed. A 'None' option at the bottom is also marked with a red checkmark.

The screenshot shows the 'Provide basic information' step of the app creation wizard. The 'Details' tab is selected. The 'Display name' field contains 'OAuth2Demo'. The 'App contact email' field contains 'svilkata\_sh@abv.bg'. Under 'Business Account - Optional', it says 'No Business Manager account selected'. At the bottom, there are links to 'Facebook Platform Terms' and 'Developer Policies', and a 'Create app' button.

The screenshot shows the Facebook Developers App Settings page for an app named 'OAuth2Demo'. The left sidebar shows navigation options like Dashboard, Settings (selected), Basic, Advanced, Roles, Alerts, App Review, and Products. The main area displays app configuration fields: App ID (1277767399626116), App secret (redacted), Display name (OAuth2Demo), Namespace (empty), App domains (empty), Contact email (svilkata\_sh@abv.bg), Privacy Policy URL (Privacy policy for Login dialog and app details), Terms of Service URL (Terms of Service for Login dialog and App Details), and Category (empty). A red checkmark is placed over the App ID field.

```
spring:
 security:
 oauth2:
 client:
 registration:
 facebook:
 client-id: 1277767399626116
 client-secret: fd.....
```

Оттук можем да не се съгласим с автоматичното логване, което еднократно вече сме задали

Non-public

It appears you haven't logged into an app with your Facebook account in the last 90 days, so the app's access to your non-public information through this connection automatically expires. When this happens, the app changes from **Active** to **Expired**.

Note that, even if an app no longer has access to your non-public information, it may still have non-public information you previously shared with it while it was Active. [Learn more](#)

We've made changes to Apps and Websites to include apps that are temporarily offline as well as those permanently removed by the app developer or Facebook. As a result, you may see more apps in your settings.

App	Status	Action
OAuth2Demo	Added on Sep 10, 2022 • Active	<a href="#">View and Edit</a> <a href="#">Remove</a> ✓
Центрър градска мобилност	Added on Sep 1, 2022 • Active	<a href="#">View and Edit</a> <a href="#">Remove</a>
Grabo.bg	Added on Dec 26, 2014 • Active	<a href="#">View and Edit</a> <a href="#">Remove</a>
Eventbrite	Added on Aug 26, 2016 • Active	<a href="#">View and Edit</a> <a href="#">Remove</a>
Gotin Trip	Added on Apr 17, 2021 • Active	<a href="#">View and Edit</a> <a href="#">Remove</a>
Viber	Added on Jun 26, 2016 • Active	<a href="#">View and Edit</a> <a href="#">Remove</a>

## 29. Proxies

Demo without SPRING

Да видим как работи SPRING реално!!!

Proxy може да са използва за извършване на някакво предварително действие преди действителното извикване на метод. Нещо аналогично на interceptor реално е.

Два са видовете proxy-та:

- Динамични – работи на база на интерфейси
- CGLIB проксита – CGLIB библиотека, която прави proxy-та на база редактиране на byte кода (Spring така работи)

Когато инжектираме някъде (например в Controller) StudentService, то ние реално не го инжектираме него, а инжектираме някакво динамично proxy (което по default е Singleton bean scope). И реално ако викаме метод на StudentService, то на практика ние викаме метода на proxy-то.

Demo Proxies без Spring

```
public class Test {
 public static void main(String[] args) {
 StudentServiceIfc studentServiceIfc = getStudentService();
 }
}
```

```
p args = {String[0]@472} []
✓ └─ studentServiceIfc = {$Proxy0@617} "bg.softuni.proxies.StudentService@6d03e736"
 > f h = {CacheableInvocationHandler@640}

 System.out.println("-----");
 System.out.println(studentServiceIfc.getAllStudents());
 System.out.println("-----");
 System.out.println(studentServiceIfc.getAllStudents());
 System.out.println("-----");
}

private static StudentServiceIfc getStudentService() {
 return (StudentServiceIfc) Proxy.newProxyInstance(
 Test.class.getClassLoader(),
 new Class[]{StudentServiceIfc.class}, //масив от всички интерфейси, които са
имплементирани
 new CacheableInvocationHandler(new StudentService())
);
}

public interface StudentServiceIfc {
 List<StudentDTO> getAllStudents();
}

public class StudentService implements StudentServiceIfc {
 private static List<StudentDTO> allStudents = List.of(
 new StudentDTO("Pesho", 10, 20),
 new StudentDTO("Anna", 11, 21),
 new StudentDTO("Gosho", 9, 22)
);

 @Override
 @Cacheable("students")
 public List<StudentDTO> getAllStudents() {
 System.out.println("Complex calculation of all students...");
 dummyWait();
 System.out.println("Students calculated");

 return allStudents;
 }

 private void dummyWait() {
 try {
 Thread.sleep(5000);
 // Dummy - imagine we need to perform complex operation to fetch student data...
 } catch (InterruptedException e) {
 throw new RuntimeException(e);
 }
 }
}
```

```

@Retention(RetentionPolicy.RUNTIME)
@Target(ElementType.METHOD)
public @interface Cacheable {
 String value();
}

import java.lang.reflect.InvocationHandler;
import java.lang.reflect.Method;
import java.util.Map;
import java.util.concurrent.ConcurrentHashMap;

public class CacheableInvocationHandler implements InvocationHandler {
 private Map<String, Object> cachedValues = new ConcurrentHashMap<>();
 private final Object realObject;

 public CacheableInvocationHandler(Object realObject) {
 this.realObject = realObject;
 }

 @Override
 public Object invoke(Object proxy, Method method, Object[] args) throws Throwable {
 Cacheable cacheableAnnotation = realObject.getClass().
 getMethod(method.getName(), method.getParameterTypes()).
 getAnnotation(Cacheable.class); //дали има анотация Cacheable

 if (cacheableAnnotation != null) { //ако има Cacheable анотация
 //
 String cacheId = cacheableAnnotation.value();
 if (cachedValues.containsKey(cacheId)) {
 return cachedValues.get(cacheId); //връщаме от кешираните стойности
 } else { //слагаме в кеша тук
 var value = method.invoke(realObject, args);
 cachedValues.put(cacheId, value);
 return value; //връщаме бавно първия път
 }
 } else {
 return method.invoke(realObject, args); //връщаме резултата, който се връща от
самия метод
 }
 }
}

```

## 30. I18N – Change International language

```
import org.springframework.web.servlet.LocaleResolver;
```

```

@Configuration
public class I18NConfig {
 @Bean
 public LocaleResolver localeResolver() {
 CookieLocaleResolver clr = new CookieLocaleResolver();
 clr.setCookieName("lang");
 return clr;
 }

 @Bean
 public LocaleChangeInterceptor localeChangeInterceptor() {
 LocaleChangeInterceptor lci = new LocaleChangeInterceptor();
 lci.setParamName("lang");
 return lci;
 }

 @Bean
 public MessageSource messageSource() {
 ResourceBundleMessageSource resourceBundleMessageSource = new ResourceBundleMessageSource();
 resourceBundleMessageSource.setBasename("i18n/messages");
 resourceBundleMessageSource.setDefaultEncoding("UTF-8");
 return resourceBundleMessageSource;
 }
}

```

```

@Configuration
public class WebConfig implements WebMvcConfigurer {

 private LocaleChangeInterceptor localeChangeInterceptor;

 public WebConfig(LocaleChangeInterceptor localeChangeInterceptor) {
 this.localeChangeInterceptor = localeChangeInterceptor;
 }

 @Override
 public void addInterceptors(InterceptorRegistry registry) {
 registry.addInterceptor(localeChangeInterceptor);
 }
}

```

✓ resources

- ✓ i18n
  - ✓ Resource Bundle 'messages' 11
    - ✓ messages.properties 11.7.20
    - ✓ messages\_bg.properties 11

```

navbar_language = Language
navbar_login = Login
navbar_register = Register
navbar_all_brands= All brands
navbar_all_offers= All offers
navbar_search= Search

```

```
navbar_language = Дългото
navbar_login = Дългото
navbar_register = Дългото, Надеждата, надежда, надеждата
navbar_all_brands= Дългото, надежда, надеждата
navbar_all_offers= Дългото, надежда, надеждата
navbar_search= Дългото, надежда
```


```
<li class="nav-item">
 <form th:method="get">
 <label class="text-white" th:text="#{navbar_language}" for="lang"></label>
 <select
 onchange="this.form.submit()"
 id="lang"
 name="lang">
 <option value="en_US" th:selected="${#locale.toString()} == 'en_US'">English</option>
 <option value="bg_BG" th:selected="${#locale.toString()} == 'bg_BG'">Български</option>
 </select>
 </form>

<li class="nav-item">
 Search

<li class="nav-item">
 All Offers

```

Настройка IntelliJ:



## 31. Cloudinary

<https://cloudinary.com/>

Виж пълното демо от лекцията Workshop 1.

За проекта – да ги качим ръчно в Cloudinary.

Можем да пазим файловете в Cloudinary по определен начин. Единият подход и с името на файла.

<https://support.cloudinary.com/hc/en-us/articles/207548479-How-to-choose-between-different-resource-naming-methods>

Cloudinary supports several methods for naming your uploaded resources.

Via API:

- Fully random 20 characters long public ID, which keeps your image URLs obscure for privacy reasons (That is the default behavior)
- The original filename followed by a unique 6 random characters suffix (activated by specifying `use_filename:true` & `unique_filename:true`)
- The original filename as-is, which will override any existing image that shares the same name (activated by specifying `use_filename:true` & `unique_filename:false`)

- Setting a specific public ID, this will override any existing image that shares the same name  
`(public_id:"my_resource")`

Другият подход е с

Manage Structured Metadata: Structured metadata enables you to predefine a number of typed fields, with or without validation rules, as optional or required fields for every asset in your account. For example, if your application supports user-generated content, you can define structured metadata fields that will be captured and passed as part of your end-user uploads to keep track of things like the user who uploaded the asset, product categories, countries, or other important data, and can ensure that these fields are used consistently for all assets in your account.

**Реално, ние като си ги пазим в база данни, то от базата данни ще вземаме линковете, и няма проблеми!!!**

```
application.properties
#Cloudinary
cloudinary.cloud-name=dislhsmj5
cloudinary.api-key=532389729736197
cloudinary.api-secret=${CLOUDINARY_SECRET}
#Multipart file
spring.servlet.multipart.max-file-size=5MB
spring.servlet.multipart.max-request-size=5MB
spring.servlet.multipart.enabled=true
```

```
application.yml
spring:
 h2:
 console:
 enabled: true
 servlet:
 multipart:
 max-file-size: 10MB
 max-request-size: 10MB
 mvc:
 hiddenmethod:
 filter:
 enabled: true

 jpa:
defer-datasource-initialization: true
 database-platform: org.hibernate.dialect.H2Dialect
 hibernate:
 ddl-auto: create

#Cloudinary properties
cloudinary:
 cloud_name: "dtfd8gw16"
```

```
api_key: "218356847735493"
api_secret: ${CLOUDINARY_SECRET}"
```



pom.xml


```
<dependency>
 <groupId>com.cloudinary</groupId>
 <artifactId>cloudinary</artifactId>
 <version>1.0.2</version>
</dependency>
```

build.gradle

```
implementation 'com.cloudinary:cloudinary:1.0.14'
```

Добавяне на environment variable – ръчно в IntelliJ





Добавяме и `@ConfigurationProperties`

```

import org.springframework.beans.factory.annotation.Value;
import org.springframework.boot.context.properties.ConfigurationProperties;
import org.springframework.context.annotation.Configuration;

@Configuration
@ConfigurationProperties(prefix = "cloudinary") //running with annotating processor
public class CloudinaryConfig {
 private String cloudName;
 private String apiKey;
 private String apiSecret;

 /**
 * Sets the Cloud name associated with the cloudinary account.
 * @param cloudName
 * @return this
 */
 public String getCloudName() {
 return cloudName;
 }

 public CloudinaryConfig setCloudName(String cloudName) {
 this.cloudName = cloudName;
 return this;
 }

 public String getApiKey() {
 return apiKey;
 }
}

```

```

public CloudinaryConfig setApiKey(String apiKey) {
 this.apiKey = apiKey;
 return this;
}

public String getApiSecret() {
 return apiSecret;
}

public CloudinaryConfig setApiSecret(String apiSecret) {
 this.apiSecret = apiSecret;
 return this;
}
}

@Configuration
public class AppConfig {
 private final CloudinaryConfig config;

 public AppConfig(CloudinaryConfig config) {
 this.config = config;
 }

 @Bean
 public Cloudinary cloudinary() {
 return new Cloudinary(
 Map.of("cloud_name", config.getCloudName(),
 "api_key", config.getApiKey(),
 "api_secret", config.getApiSecret())
);
 }
}

import com.cloudinary.Cloudinary;
import org.springframework.stereotype.Service;
import org.springframework.web.multipart.MultipartFile;

import java.io.File;
import java.io.IOException;
import java.util.Map;

@Service
public class CloudinaryService {
 private final Cloudinary cloudinary;
 private static final String TEMP_file = "temp-file";
 private static final String URL = "url";
 private static final String PUBLIC_ID = "public_id";

 public CloudinaryService(Cloudinary cloudinary) {
 this.cloudinary = cloudinary;
 }

 public CloudinaryImage upload(MultipartFile multipartFile) throws IOException {
 File tempFile = File.createTempFile(TEMP_file, multipartFile.getOriginalFilename());
 multipartFile.transferTo(tempFile);

 try {

```

```

 @SuppressWarnings("unchecked")
 Map<String, String> uploadResult = cloudinary
 .uploader()
 .upload(tempFile, Map.of());

 String url = uploadResult.getOrDefault(URL,
"https://thumbs.dreamstime.com/b/illustration-internet-connection-problem-concept-error-page-not-found-isolated-white-background-funny-blue-dinosaur-230224212.jpg");
 String publicId = uploadResult.getOrDefault(PUBLIC_ID, "");

 var result = new CloudinaryImage()
 .setPublicId(publicId)
 .setUrl(url);

 return result;
} finally {
 tempFile.delete();
}

}

public boolean delete(String publicId) {
 try {
 this.cloudinary.uploader().destroy(publicId, Map.of());
 } catch (IOException e) {
 return false;
 }

 return true;
}
}

```

**Има и вариант само с 1 клас AppCloudConfig – от курсовата работа на Дойча:**

```

import com.cloudinary.Cloudinary;
import org.springframework.beans.factory.annotation.Value;
import org.springframework.context.annotation.Bean;
import org.springframework.context.annotation.Configuration;

import java.util.HashMap;
import java.util.Map;

@Configuration
public class AppCloudConfig {
 @Value("${cloudinary.cloud-name}")
 private String cloudName;
 @Value("${cloudinary.api-key}")
 private String apiKey;
 @Value("${cloudinary.api-secret}")
 private String apiSecret;

 @Bean
 public Cloudinary createCloudinaryConfig() {
 Map<String, Object> config = new HashMap<>();
 config.put("cloud_name", cloudName);

```

```

 config.put("api_key", apiKey);
 config.put("api_secret", apiSecret);
 return new Cloudinary(config);
 }
}

@Service
public class CloudinaryServiceImpl implements CloudinaryService {
 private static final String TEMP_FILE = "temp-file";
 private static final String URL = "url";

 private final Cloudinary cloudinary;

 public CloudinaryServiceImpl(Cloudinary cloudinary) {
 this.cloudinary = cloudinary;
 }

 @Override
 public String uploadImage(MultipartFile multipartFile) throws IOException {
 File file = File.createTempFile(TEMP_FILE, multipartFile.getOriginalFilename());
 multipartFile.transferTo(file);

 Map uploadResult = cloudinary.uploader().upload(file, Collections.emptyMap());
 return uploadResult.get(URL).toString();
 }
}

```

annotationProcessor "org.springframework.boot:spring-boot-configuration-processor"  
има и за maven проекти същото dependency

### cloudinary:

cloud\_name: "dtfd8gw16"

api Cannot resolve configuration property 'cloudinary.cloud\_name'

Define configuration key 'cloudinary.cloud\_name' Alt+Shift+Enter More actions... Alt+Enter

No documentation found.

Commands in JAVA how to make the upload:

Account      **Upload**      Security      Users

Automatic backup:

Disabled ▾

Enabling automatic backup means that every uploaded file is also copied to a secondary write-protected

### Self-Service Operations

- ▶ Bulk delete
- ▶ Upload directly from my own bucket

The screenshot shows a browser window with multiple tabs open at [cloudinary.com/documentation/upload\\_images#private\\_storage\\_url](https://cloudinary.com/documentation/upload_images#private_storage_url). The main content is titled "Guides" and focuses on the "Media upload" section. It explains that the `upload` method performs an authenticated API call over HTTPS. Below this, there's a code snippet for Java showing how to use the `clouddinary.uploader().upload(Object file, Map options);` method. A tip box notes that optional parameters can be specified via `options = {}`. Another code example shows uploading a local image file named `sample.jpg` using the same method. On the right side, a sidebar titled "On this page:" lists various topics related to uploads and asset management.

```
@SuppressWarnings({ "rawtypes", "unchecked" })
public class Cloudinary {
```

## 32. Pageable and Sorted

Demo1 – слаба ракия

```
import org.springframework.data.domain.Page;
import org.springframework.data.domain.Pageable;
```

```
@Service
public class BookServiceImpl {
 private BookRepository bookRepository;
 private ModelMapper modelMapper;
 private AuthorRepository authorRepository;
```

```
public BookServiceImpl(BookRepository bookRepository, ModelMapper modelMapper,
AuthorRepository authorRepository) {
 this.bookRepository = bookRepository;
```

```

 this.modelMapper = modelMapper;
 this.authorRepository = authorRepository;
 }

 private BookDTO asBook(BookEntity book) {
 BookDTO bookDTO = modelMapper.map(book, BookDTO.class);
 AuthorDTO authorDTO = modelMapper.map(book.getAuthor(), AuthorDTO.class);

 bookDTO.setAuthor(authorDTO);

 return bookDTO;
 }

 public Page<BookDTO> getBooksPerPage(Integer pageNo, Integer pageSize, String sortBy) {
 Pageable pageable = PageRequest.of(pageNo, pageSize, Sort.by(sortBy));

 return bookRepository
 .findAll(pageable)
 .map(e -> asBook(e));
 }
}

@RestController
@RequestMapping("/books")
public class BooksController {
 private BookServiceImpl bookService;

 public BooksController(BookServiceImpl bookService) {
 this.bookService = bookService;
 }

 @DeleteMapping("/{bookId}")
 public ResponseEntity<BookDTO> deleteBookById(@PathVariable("bookId") Long bookId) {
 bookService
 .deleteBook(bookId);

 return ResponseEntity.noContent().build();
 }

 @GetMapping("/pageablesorted")
 public ResponseEntity<Page<BookDTO>> getBooksPerPage(
 @RequestParam(name = "pageNo", defaultValue = "0") Integer pageNo,
 @RequestParam(name = "pageSize", defaultValue = "3") Integer pageSize,
 @RequestParam(name = "sortBy", defaultValue = "id") String sortBy) {

 return ResponseEntity.ok(
 bookService.getBooksPerPage(pageNo, pageSize, sortBy)
);
 }
}

```

localhost:8080/books/pageablesorted?pageSize=3

JSON Raw Data Headers

Save Copy Collapse All Expand All Filter JSON

content:

- 0:
  - author:
    - name: "Николай Хайтов"
    - id: 2
    - title: "Диви разкази"
    - isbn: "7e363430-a7db-4ba2-b6bc-8ad426f4bc7d"
- 1:
  - author:
    - name: "Димитър Талев"
    - id: 3
    - title: "Тютюн"
    - isbn: "9684c384-7e10-48ae-acf1-dc525d6e5663"
- 2:
  - author:
    - name: "Елин Пелин"
    - id: 4
    - title: "Пижо и Пенда"
    - isbn: "f6731d63-c915-4ae5-9a1f-c42b248ce93a"

pageable:

- sort:
  - empty: false
  - unsorted: false
  - sorted: true
  - offset: 0
  - pageNumber: 0
  - pageSize: 3
  - unpaged: false

localhost:8080/books/pageablesort X +

localhost:8080/books/pageablesorted?pageNo=3

JSON Raw Data Headers

Save Copy Collapse All Expand All Filter JSON

```
▼ content:
 ▼ 0:
 ▼ author:
 name: "Йордан Йовков"
 id: 11
 title: "Чифликът край границата"
 isbn: "52e8ba56-baf1-4ead-a17c-33866571024d"
 ▼ pageable:
 ▼ sort:
 empty: false
 unsorted: false
 sorted: true
 offset: 9
 pageNumber: 3
 pageSize: 3
 unpaged: false
 paged: true
 last: true
 totalPages: 4
 totalElements: 10
 size: 3
 number: 3
 ▼ sort:
 empty: false
```

```

localhost:8080/books/pageablesorted?pageSize=4&pageNo=0&sortBy=title
JSON Raw Data Headers
Save Copy Collapse All Expand All Filter JSON
content:
 0:
 author:
 name: "Николай Хайтов"
 id: 2
 title: "Диви разкази"
 isbn: "7е363430-a7db-4ba2-b6bc-8ad426f4bc7d"
 1:
 author:
 name: "Елин Пелин"
 id: 4
 title: "Пижо и Пенда"
 isbn: "f6731d63-c915-4ae5-9a1f-c42b248ce93a"
 2:
 author:
 name: "Иван Вазов"
 id: 8
 title: "Под Игото"
 isbn: "a6e781a9-e744-4192-9e65-254980af431f"
 3:
 author:
 name: "Елин Пелин"
 id: 6
 title: "Под манастирската лоза"
 isbn: "a38a79f8-48d5-4a72-8c5f-33e33163cb44"
pageable:
 sort:
 empty: false
 unsorted: false

```

## Demo 2 - Да

By having it extend [PagingAndSortingRepository](#), we get `findAll(Pageable pageable)` and `findAll(Sort sort)` methods for paging and sorting.

Conversely, we could have chosen to extend [JpaRepository](#) instead, as it extends `PagingAndSortingRepository` too.

Once we extend `PagingAndSortingRepository`, we can add our own methods that take `Pageable` and `Sort` as parameters, like we did here with `findAllByPrice`.

```
public interface ProductRepository extends PagingAndSortingRepository<Product, Integer> { List<Product> findAllByPrice(double price, Pageable pageable); }
```

ДА СИ РАЗЦЪКАМ КОЙ МЕТОД КАКВО ТОЧНО ПРАВИ АКО ЩЕ ПРАВЯ НАНОВО

В репозиторито, SQL заявките вървят реално!

```
<div class="container-fluid row justify-content-center">
 <nav>
 <ul class="pagination">
 <li class="page-item" th:classappend="${computers.isFirst()} ? 'disabled' : ''">
 <a th:unless="${computers.isFirst()}" class="page-link">
```

```

First

</nav>

<nav>
 <ul class="pagination">
 <li class="page-item" th:classappend="${computers.hasPrevious() ? '' : 'disabled'}">
 <a th:if="${computers.hasPrevious()}">
 class="page-link"

</nav>

<nav>
 <ul class="pagination">
 <li class="page-item" th:classappend="${computers.hasNext() ? '' : 'disabled'}">
 <a th:if="${computers.hasNext()}">
 class="page-link"

</nav>

<nav>
 <ul class="pagination">
 <li class="page-item" th:classappend="${computers.isLast() ? 'disabled' : ''}">
 <a th:unless="${computers.isLast()}">
 class="page-link"

</nav>

<nav>
 <ul class="pagination">
 <li class="page-item" th:classappend="${computers.getTotalPages() - 1} ${computers.getPageNumber() + 1}>
 Next

</nav>

<nav>
 <ul class="pagination">
 <li class="page-item" th:classappend="${computers.isLast() ? 'disabled' : ''}">
 <a th:unless="${computers.isLast()}">
 class="page-link"

</nav>
</div>

```

```

import org.springframework.data.domain.Page;
import org.springframework.data.domain.Pageable;

```

```

@Controller
@RequestMapping("/items/all")
public class ViewItemsController {

 @GetMapping("/computer")
 public String viewAllComputers(Model model,
 @PageableDefault(page = 0,
 size = 3,
 sort = "sellingPrice",
 direction = Sort.Direction.ASC) Pageable pageable) {

```

```

 if (!model.containsAttribute("computers")) {
 // List<ComputerViewGeneralModel> computers = this.computerService.findAllComputers();
 Page<ComputerViewGeneralModel> computers=this.computerService.getAllComputersPageable(pageable);
 model.addAttribute("computers", computers);
 }

 return "/viewItems/all-computers";
}

@Service
public class ComputerService implements InitializableProductService {

 public Page<ComputerViewGeneralModel> getAllComputersPageable(Pageable pageable) {
 Page<ComputerViewGeneralModel> allComputers = this.allItemsRepository
 .findAllByType("computer", pageable)
 .map(comp -> this.structMapper
 .computerEntityToComputerSalesViewGeneralModel((ComputerEntity) comp));

 return allComputers;
 }

 Repository
 public interface AllItemsRepository extends PagingAndSortingRepository<ItemEntity, Long> {
 Page<ItemEntity> findAllByType(String type, Pageable pageable);
 }
}

private void basketsInit() {
 List<ItemEntity> allItemsInTheCurrentBasket = (List<ItemEntity>)
this.allItemsRepository.findAll(); //връща Iterable<ItemEntity>, и затова го cast-ваме
}

```

## More Pagination and Sorting

Similarly, to just have our query results sorted, we can simply pass an instance of *Sort* to the method:

```
Page<Product> allProductsSortedByName = productRepository.findAll(Sort.by("name"));
However, what if we want to both sort and page our data?
```

We can do that by passing the sorting details into our *PageRequest* object itself:

```

Pageable sortedByName =
 PageRequest.of(0, 3, Sort.by("name"));

Pageable sortedByPriceDesc =
 PageRequest.of(0, 3, Sort.by("price").descending());

Pageable sortedByPriceDescNameAsc =
 PageRequest.of(0, 5, Sort.by("price").descending().and(Sort.by("name")));
Based on our sorting requirements, we can specify the sort fields and the sort direction while creating
our PageRequest instance.

```

## 33. Selenium

### Checking the Google Chrome version

The screenshot shows the Google Chrome settings interface. On the left, there's a sidebar with various options like 'and Google', 'Privacy and security', 'Appearance', 'Search engine', and 'Default browser'. The main area is titled 'About Chrome' and displays the 'Google Chrome' logo. It states 'Chrome is up to date' and provides the version information: 'Version 106.0.5249.103 (Official Build) (64-bit)'. A red underline is drawn under the version number. Below this, there's a link to 'Get help with Chrome'.

The screenshot shows a web browser window with the URL <https://chromedriver.chromium.org/downloads>. The page title is 'ChromeDriver - WebDriver for Chro...'. The main content area is titled 'Current Releases' and contains a list of recommended Chromedriver versions for different Chrome versions. Each item in the list includes a download link and a red checkmark icon. Below this list, there's a note about using the page for Dev or Canary channels and a link to the 'Version Selection' page.

### Current Releases

- If you are using Chrome version 107, please download [Chromedriver 107.0.5304.18](#) ✓
- If you are using Chrome version 106, please download [Chromedriver 106.0.5249.61](#) ✓
- If you are using Chrome version 105, please download [Chromedriver 105.0.5195.52](#) ✓
- For older version of Chrome, please see below for the version of Chromedriver that supports it.

If you are using Chrome from Dev or Canary channel, please follow the instructions on the [Chromedriver Canary](#) page.

For more information on selecting the right version of Chromedriver, please see the [Version Selection](#) page.

#### [Chromedriver 107.0.5304.18](#)

Supports Chrome version 107



[Parent Directory](#)



<a href="#">chromedriver_linux64.zip</a>	2022-09-28 11:34:38	6.35MB	1aaa6ecdd47c801b6be0729d17da5f1f
<a href="#">chromedriver_mac64.zip</a>	2022-09-28 11:34:40	8.08MB	474e621339191968ce3ecf9645efa5a
<a href="#">chromedriver_mac_arm64.zip</a>	2022-09-28 11:34:43	7.52MB	e313835aa34973b7908b3d02864c5a9d
<a href="#">chromedriver_win32.zip</a>	2022-09-28 11:34:46	6.29MB	a8fdc7ff930fbcc32a817ea67ddd01377
<a href="#">notes.txt</a>	2022-09-28 11:34:52	0.00MB	02a92f7a418aa8c8e2ec3514545a3ad5

```
import org.junit.jupiter.api.AfterEach;
import org.junit.jupiter.api.Assertions;
import org.junit.jupiter.api.BeforeEach;
import org.junit.jupiter.api.Test;
import org.openqa.selenium.By;
import org.openqa.selenium.WebElement;
import org.openqa.selenium.chrome.ChromeDriver;
import org.openqa.selenium.chrome.ChromeDriverService;
import org.openqa.selenium.chrome.ChromeOptions;

import java.io.File;
import java.net.URL;

public class ChromeTest {
 private static final String CHROME_DRIVER_FILE_NAME = "chromedriver.exe";

 private ChromeDriver chromeDriver;

 @BeforeEach
 void setUp() {
 File file = new File(findFile());

 ChromeDriverService service = new ChromeDriverService.Builder().
 usingDriverExecutable(file).
 build();

 ChromeOptions chromeOptions = new ChromeOptions();
 chromeOptions.addArguments("--no-sandbox");
// chromeOptions.addArguments("--start-maximized");

 chromeDriver = new ChromeDriver(service, chromeOptions);
 }

 @AfterEach
 void tearDown() {
 chromeDriver.quit();
 }

 @Test
 void testLogin() {
 //отбори страницата
 chromeDriver.get("http://localhost:8080/users/login");
 }
}
```

```

//намира тези 2 html елемента
WebElement userNameInput = chromeDriver.findElement(By.name("username"));
WebElement passwordInput = chromeDriver.findElement(By.name("password"));

//пише по браузъра в тези html елементи с тези данни
userNameInput.sendKeys("lachezar.balev@gmail.com");
passwordInput.sendKeys("topsecret");

//from the element part of the form, then submit the whole form
passwordInput.submit();

WebElement h5greeting = chromeDriver.findElement(By.tagName("h5"));
String h5Text = h5greeting.getText();

Assertions.assertTrue(h5Text.contains("Welcome"));
Assertions.assertTrue(h5Text.contains("Lucho Balev"));
}

private static String findFile() {
 ClassLoader classLoader = ChromeTest.class.getClassLoader();
 URL url = classLoader.getResource(CHROME_DRIVER_FILE_NAME);
 if (url == null) {
 Assertions.fail("Unable to locate chrome driver");
 }
 return url.getFile();
}
}

```

## 34. MailHog

SMTP server for testing receiving e-mails locally.

Може да се инсталира на Windows или на Linux.

Може и през Докер с docker-compose.yml файл.

<https://www.youtube.com/watch?v=yozMCBg2sBk&t=307s>

Като се подкара, заема порт localhost:8025

```

2022/11/22 00:26:50 Using in-memory storage
2022/11/22 00:26:50 [SMTP] Binding to address: 0.0.0.0:1025
[HTTP] Binding to address: 0.0.0.0:8025
2022/11/22 00:26:50 Serving under http://0.0.0.0:8025/
Creating API v1 with WebPath:
Creating API v2 with WebPath:

```

Какво правим в Java Spring, за да го подкараме – ами много неща в Spring реално:

```

<!DOCTYPE html>
<html lang="en"
 xmlns:th="http://www.thymeleaf.org"
 xmlns:sec='http://www.thymeleaf.org/extras/spring-security'>

```

```

<head th:replace="fragments/commons::head"></head>

<body>

<header th:replace="fragments/commons::header"></header>

<main>
 <div class="container">
 <h2 class="text-center text-white greybg" th:text="#{register}">.....Register
Customer.....</h2>
 <form th:action="@{/users/register}"
 th:method="post"
 th:object="${userRegistrationModel}"
 class="main-form mx-auto col-md-8 d-flex flex-column justify-content-center">
 <div class="row">
 <div class="form-group col-md-6 mb-3">
 <label for="firstName" class="text-white font-weight-bold">First
Name</label>
 <input
 id="firstName"
 th:field="*{firstName}"
 th:errorclass="is-invalid"
 type="text"
 class="form-control"
 placeholder="First name"
 required minlength="2" maxlength="20"/>
 <div class="invalid-feedback errors alert alert-danger">
 <div th:each="err : ${#fields.errors('firstName')}" th:text="${err}">
 </div>
 </div>
 <div class="form-group col-md-6 mb-3">
 <label for="lastName" class="text-white font-weight-bold">Last Name</label>
 <input id="lastName"
 th:field="*{lastName}"
 th:errorclass="is-invalid"
 type="text"
 class="form-control"
 placeholder="Last name"
 required minlength="2" maxlength="20"/>
 <div class="invalid-feedback errors alert alert-danger">
 <div th:each="err : ${#fields.errors('lastName')}" th:text="${err}">
 </div>
 </div>
 </div>
 </div>
 <div class="row">
 <div class="form-group col-md-6 mb-3">
 <label for="email" class="text-white font-weight-bold">E-mail</label>
 <input id="email"
 th:field="*{email}"
 th:errorclass="is-invalid"
 type="email"
 class="form-control"
 placeholder="email"
 required/>
 <div class="invalid-feedback errors alert alert-danger">

```

```

 <div th:each="err : ${#fields.errors('email')}" th:text="${err}"/>
 </div>
 </div>
 <div class="form-group col-md-6 mb-3">
 <label for="username" class="text-white font-weight-bold">Username</label>
 <input id="username"
 th:field="*{username}"
 th:errorclass="is-invalid"
 type="text"
 class="form-control"
 placeholder="username"
 required minlength="3" maxlength="20"/>
 <div class="invalid-feedback errors alert alert-danger">
 <div th:each="err : ${#fields.errors('username')}" th:text="${err}"/>
 </div>
 </div>
 </div>

 <div class="row">
 <div class="form-group col-md-6 mb-3">
 <label for="password" class="text-white font-weight-bold">Password</label>
 <input id="password"
 th:field="*{password}"
 th:errorclass="is-invalid"
 type="password"
 class="form-control"
 placeholder="Password"
 required minlength="3" maxlength="20"/>
 <div class="invalid-feedback errors alert alert-danger">
 <div th:each="err : ${#fields.errors('password')}" th:text="${err}"/>
 </div>
 </div>

 <div class="form-group col-md-6 mb-3">
 <label for="confirmPassword" class="text-white font-weight-bold">Confirm
Password</label>
 <input id="confirmPassword"
 name="confirmPassword"
 th:field="*{confirmPassword}"
 th:errorclass="is-invalid"
 type="password"
 class="form-control"
 placeholder="confirmPassword"
 required minlength="3" maxlength="20"/>
 <div class="invalid-feedback errors alert alert-danger">
 <div th:each="err : ${#fields.errors('confirmPassword')}" th:text="${err}"/>
 </div>
 <!--
 <p class="invalid-feedback exception alert alert-
danger">-->
 <!--
 <p>Passwords should match.-->
 </p>-->
 </div>
 </div>

 <div class="row">
 <div class="col col-md-4">

```

```

 <div class="button-holder d-flex">
 <input type="submit" class="btn btn-info btn-lg" value="Register"/>
 </div>
 </div>
</form>
</div>
</main>

<footer th:replace="fragments/commons::footer"></footer>

</body>
</html>

@Controller
public class RegistrationController {
 private final UserService userService;

 public RegistrationController(UserService userService) {
 this.userService = userService;
 }

 @ModelAttribute("userRegistrationModel")
 public void initUserRegistrationModel(Model model){ //изпълнява се в рамките на текущия
контролер само!!!
 model.addAttribute("userRegistrationModel", new UserRegisterBindingDTO());
 }

 @GetMapping("/users/register")
 public String register() {
 // когато зареждаме за първи път страницата, то автоматично ще влезе към модела атрибут
userRegistrationModel == празен new UserRegisterBindingDto()
 return "/user/auth-registerUser";
 }

 @PostMapping("/users/register")
 public String registerConfirm(@Valid UserRegisterBindingDTO userRegisterBindingDto,
 BindingResult bindingResult,
 RedirectAttributes redirectAttributes) {

 if (bindingResult.hasErrors()) {
 redirectAttributes.addFlashAttribute("userRegistrationModel",
userRegisterBindingDto);

redirectAttributes.addFlashAttribute("org.springframework.validation.BindingResult.userRegistrat
ionModel",
 bindingResult);
 return "redirect:/users/register";
 }

 userService.registerUserAndAutoLogin(userRegisterBindingDto);
 return "redirect:/";
 }
}

```

pom.xml

```
<dependency>
 <groupId>org.springframework.boot</groupId>
 <artifactId>spring-boot-starter-mail</artifactId>
 <version>2.7.5</version>
</dependency>
```

application.yml

```
mail:
 host: "localhost"
 port: 1025
 username: "computer@store.com"
 password: ""
```

```
import bg.softuni.computerStore.initSeed.InitializableUserService;
import bg.softuni.computerStore.model.binding.user.ChangeUserPasswordDTO;
import bg.softuni.computerStore.model.binding.user.EmployeeRegisterBindingDTO;
import bg.softuni.computerStore.model.binding.user.UserRegisterBindingDTO;
import bg.softuni.computerStore.model.binding.user.UserRolesBindingDTO;
import bg.softuni.computerStore.model.entity.users.UserEntity;
import bg.softuni.computerStore.model.entity.users UserRoleEntity;
import bg.softuni.computerStore.model.enums.UserRoleEnum;
import bg.softuni.computerStore.model.view.user.UserViewModel;
import bg.softuni.computerStore.repository.users.UserRepository;
import bg.softuni.computerStore.repository.users.UserRoleRepository;
import org.modelmapper.ModelMapper;
import org.springframework.beans.factory.annotation.Value;
import org.springframework.security.authentication.UsernamePasswordAuthenticationToken;
import org.springframework.security.core.Authentication;
import org.springframework.security.core.context.SecurityContextHolder;
import org.springframework.security.core.userdetails.UserDetails;
import org.springframework.security.core.userdetails.UserDetailsService;
import org.springframework.security.crypto.password.PasswordEncoder;
import org.springframework.stereotype.Service;

import java.util.*;
import java.util.stream.Collectors;

@Service
public class UserService implements InitializableUserService {
 private final UserRepository userRepository;
 private final UserRoleRepository userRoleRepository;
 private final PasswordEncoder passwordEncoder;
 private final UserDetailsService appUserDetailsService;
 private final String adminPass;
 private final ModelMapper modelMapper;
 private final BasketService basketService;
 private final DemoEmailService demoEmailService;

 public UserService(
 UserRepository userRepository, UserRoleRepository userRoleRepository,
 PasswordEncoder passwordEncoder,
 UserDetailsService appUserDetailsService,
 @Value("${app.default.admin.password}") String adminPass, ModelMapper modelMapper,
 BasketService basketService, DemoEmailService demoEmailService) {
```

```

 this.userRepository = userRepository;
 this.userRoleRepository = userRoleRepository;
 this.passwordEncoder = passwordEncoder;
 this.appUserDetailsService = appUserDetailsService;
 this.adminPass = adminPass;
 this.modelMapper = modelMapper;
 this.basketService = basketService;
 this.demoEmailService = demoEmailService;
 }

//customers
public Long registerUserAndAutoLogin(UserRegisterBindingDTO userRegisterBindingDTO) {
 //The customer user role
 UserRoleEntity userRole = userRepository.findById(4L).get();

 UserEntity newCustomer =
 new UserEntity().
 setUserRoles(Set.of(userRole)).
 setUsername(userRegisterBindingDTO.getUsername()).
 setEmail(userRegisterBindingDTO.getEmail()).
 setFirstName(userRegisterBindingDTO.getFirstName()).
 setLastName(userRegisterBindingDTO.getLastName()).

 setPassword(passwordEncoder.encode(userRegisterBindingDTO.getPassword()));

 UserEntity savedUser = userRepository.save(newCustomer);

 //Creating here the relevant basket
 this.basketService.addBasketForRegisteredUser(savedUser);

 //this is the Spring representation of a User - after register, we AUTO Log-in the users
directly = THE LOGIN PROCESS
 login(newCustomer.getUsername());

 demoEmailService.sendRegistrationEmail(savedUser.getEmail(), savedUser.getUsername());

 return savedUser.getId();
}

import org.springframework.mail.javamail.JavaMailSender;
import org.springframework.mail.javamail.MimeMessageHelper;
import org.springframework.stereotype.Service;
import org.thymeleaf.TemplateEngine;
import org.thymeleaf.context.Context;

import javax.mail.MessagingException;
import javax.mail.internet.MimeMessage;

@Service
public class DemoEmailService {
 private final TemplateEngine templateEngine;
 private final JavaMailSender javaMailSender;

 public DemoEmailService(TemplateEngine templateEngine, JavaMailSender javaMailSender) {
 this.templateEngine = templateEngine;
 this.javaMailSender = javaMailSender;
 }
}

```

```

}

public void sendRegistrationEmail(String userEmail, String userName) {
 MimeMessage mimeMessage = javaMailSender.createMimeMessage();

 try {
 MimeMessageHelper mimeMessageHelper = new MimeMessageHelper(mimeMessage);
 mimeMessageHelper.setFrom("computer@store.com");
 mimeMessageHelper.setTo(userEmail);
 mimeMessageHelper.setSubject("Welcome to ComputerStore");
 mimeMessageHelper.setText(userName, true);

 javaMailSender.send(mimeMessageHelper.getMimeMessage());
 } catch (MessagingException e) {
 throw new RuntimeException(e);
 }
}

private String generateMessageContent(String userName){
 Context ctx = new Context(); //org.thymeleaf.context;
 ctx.setVariable("userRegistrationModel.username", userName);

 return templateEngine.process("/user/auth-registerUser", ctx);
}
}

import org.springframework.beans.factory.annotation.Value;
import org.springframework.context.annotation.Bean;
import org.springframework.context.annotation.Configuration;
import org.springframework.mail.javamail.JavaMailSender;
import org.springframework.mail.javamail.JavaMailSenderImpl;

import java.util.Properties;

@Configuration
public class MailConfig {

 @Bean
 public JavaMailSender javaMailSender(
 @Value("${mail.host}") String mailHost,
 @Value("${mail.port}") Integer mailPort,
 @Value("${mail.username}") String userName,
 @Value("${mail.password}") String password) {

 JavaMailSenderImpl javaMailSender = new JavaMailSenderImpl();
 javaMailSender.setHost(mailHost);
 javaMailSender.setPort(mailPort);
 javaMailSender.setUsername(userName);
 javaMailSender.setPassword(password);
 javaMailSender.setJavaMailProperties(mailProperties());

 return javaMailSender;
 }

 private Properties mailProperties() {


```

```

 Properties properties = new Properties();
 properties.setProperty("mail.smtp.auth", "true");
 properties.setProperty("mail.transport.protocol", "smtp");

 return properties;
 }
}

```



## 40. Other

```

@PostMapping(value = "/users/register", consumes = MediaType.APPLICATION_FORM_URLENCODED_VALUE)
public String doRegister(@Valid @RequestBody MultiValueMap<String, String> paramMap){
 System.out.println(paramMap.get("user"));

 return "user/register";
}

@PostMapping(value = "/users/register", consumes = MediaType.APPLICATION_JSON_VALUE)
public String doRegister(@Valid @RequestBody RegistrationDTO dto){
 System.out.println(dto);

 return "user/register";
}

@PostMapping(value = "/users/register")
public String doRegister(@Valid RegistrationDTO dto, BindingResult validationResult) {

```

```

// RegistrationDTO dto = new RegistrationDTO("user", "pass", "pass", "mail@abv.bg");
if (validationResult.hasErrors()) {
 return "user/register";
}

userService.register(dto);


return "user/login";
}

```

## Logout с Rest

Трябва да си вземем и csrf токена към post заявката към users/logout url-а

## Пример за контролер



```

@Controller
public class ExportController {
 private final ProjectService projectService;
 private final EmployeeService employeeService;
 private final Gson gson;

 @Autowired
 public ExportController(ProjectService projectService, EmployeeService employeeService, Gson
gson) {

```

```

 this.projectService = projectService;
 this.employeeService = employeeService;
 this.gson = gson;
 }

 @GetMapping("/export/project-if-finished")
 public ModelAndView showFinishedProjects(){
 ModelAndView modelAndView = new ModelAndView("export/export-project-if-finished");
 String result = this.projectService.getFinishedProducts();
 modelAndView.addObject("projectsIfFinished", result);
 return modelAndView;
 }

 @GetMapping("/export/employees-above")
 public ModelAndView showEmployeesAbove25(){
 ModelAndView modelAndView = new ModelAndView("export/export-employees-with-age");
 List<ExportEmployeeDTO> employeesAbove25 = this.employeeService.getEmployeesAbove25();
 StringBuilder sb = new StringBuilder();
 this.gson.toJson(employeesAbove25, sb);
 modelAndView.addObject("employeesAbove", sb.toString());
 return modelAndView;
 }
}

```

File structure:

```

 templates
 export
 export-employees-with-age.html 10
 export-project-if-finished.html 10.7.2

```

Content of export-employees-with-age.html:

```

<!DOCTYPE html>
<html lang="en" xmlns="http://www.w3.org/1999/xhtml"
 xmlns:th="http://www.thymeleaf.org">

<head>
 <th:block th:include="~{fragments/head}"></th:block>
</head>
<body>
<header>
 <th:block th:include="~{fragments/nav-bar}"></th:block>
</header>
<main>
 <div class="jumbotron">
 <form>
 <div class="col-md-12 d-flex justify-content-center">
 <label class="display-4" for="export-project-textarea">Employees with age above
25:</label>
 </div>
 <div class="col-md-12 d-flex justify-content-center">

```

```

 <div class="col-md-8 d-flex justify-content-center">
 <textarea class="form-control" id="export-project-textarea" rows="20"
th:text="${employeesAbove}" readonly></textarea>
 </div>
 </div>
</main>
<footer>
 <th:block th:include="~{fragments/footer}"></th:block>
</footer>
</body>
</html>

```

Regex in html

```

<div class="form-group">
 <label for="number" class="col-lg-2 control-label">Number</label>
 <div class="col-lg-10">
 <input type="text" autofocus="autofocus" name="number" title="Number" class="form-
control"
 pattern="\+?[0,9]{6,}" //валидира за телефонен номер с регекс
 id="number"/>
 </div>
</div>

```

Uploading a file

```

@PostMapping("/")
public String storeContact(Contact contact, @RequestParam("picture") MultipartFile picture) {
 this.contacts.add(contact);


 return "redirect:/"; //върни ме на началната страница //редиректваме към този URL, не към
html страница
}

<div class="form-group">
 <label for="picture" class="col-lg-2 control-label">Picture</label>
 <div class="col-lg-10">
 <input type="file" autofocus="autofocus" name="picture" title="Picture" class="form-
control"
 id="picture"/>
 </div>
</div>

```

Build pattern

Builder pattern and Alt + Insert



Когато искаме да работи с 2 service-а или 2 ModelMapper-и, то използваме **@Qualifier**

- веднъж на класа/метода който разписва логиката, и втори път на по-горна инстанция от InversionOfControl структурата го викаме този Qualifier с искания от нас Bean

How to download a specific folder from a github repository - <https://download-directory.github.io/>

## UUID

**UUID** – A universally unique identifier (UUID) is a 128-bit label used for information in computer systems. The term globally unique identifier (GUID) is also used. When generated according to the standard methods, UUIDs are, for practical purposes, unique.

**Не е добра идея да слагаме UUID като primary key – прекалено бавно стават insert-е поради проблем с А-В дърво алгоритми.**

UUID е глобално уникално в света - част от алгоритъма на UUID е вземане на IP-то на машината и други неща специфични за даден компютър. Не е проблем да наливаме данни от две бази с различно IP.

UUID дава privacy, не точно security – коя поръчка кой има право да я вижда в URL-то примерно.

```

@Id
@GeneratedValue(generator = "uuid-string")
@GenericGenerator(name = "uuid-string",
 strategy = "org.hibernate.id.UUIDGenerator")
public String getId() { return id; }

public void setId(String id) { this.id = id; }

```

```
import org.hibernate.annotations.Type;
```

```

import javax.persistence.Column;
import javax.persistence.Entity;
import javax.persistence.Id;
import javax.persistence.Table;
import java.util.UUID;

```

```

@Entity
@Table(name = "offers")
public class OfferEntity {
 @Id
 @GeneratedValue(generator = "UUID")
 @GenericGenerator(
 name = "UUID",
 strategy = "org.hibernate.id.UUIDGenerator"
)
 @Type(type = "uuid-char") //Hibernate annotation @Type //работи, но не е достатъчно
// @Column(columnDefinition = "VARCHAR(255)") //по този начин не е редно да работим с UUID
 private UUID id;

```

Пре repository-то използваме String когато имаме UUID

```

@Repository
public interface UserRepository extends JpaRepository<UserEntity, String> {
}

```

Произволен UUID номер

```
aBook.setAuthor(author).setTitle(bookTitle).setIsbn(UUID.randomUUID().toString());
```

```

org.slf4j.Logger
import org.slf4j.Logger;
import org.slf4j.LoggerFactory;
import org.springframework.stereotype.Service;

import java.util.Optional;

@Service
public class UserService {
 private UserRepository userRepository;
 private CurrentUser currentUser;
 private Logger LOGGER = LoggerFactory.getLogger(UserService.class);

 if (userOpt.isEmpty()) {
 LOGGER.info("User with name [{}] not found.", loginDto.getUsername()); //в къдравите скоби
 //се изписва
 LOGGER.debug("User with name {} not found.", loginDto.getUsername()); //в къдравите
 //скоби се изписва

 return false;
 }
}

```

Partial security – password encryption

```

@Configuration
public class ApplicationConfig {

 @Bean
 public PasswordEncoder passwordEncoder(){

```

```

 return new Pbkdf2PasswordEncoder();
 }
}

public void registerAndLogin(UserRegisterDto userRegisterDto) {
 UserEntity newUser = new UserEntity()
 .setActive(true)
 .setEmail(userRegisterDto.getEmail())
 .setFirstName(userRegisterDto.getFirstName())
 .setLastName(userRegisterDto.getLastName())
 .setPassword(passwordEncoder.encode(userRegisterDto.getPassword()));

 newUser = userRepository.save(newUser);

 login(newUser);
}

var rawPassword = loginDto.getPassword();
var encodedPassword = userOpt.get().getPassword(); //което се е записало в базата данни

boolean success = passwordEncoder.matches(rawPassword, encodedPassword);

```

html new project generating in Java

Записваме файлът като .html

! + Tab  
html:5 + Enter

POST-redirect-GET principle

Create an object,  
then re-load **the same** URL page,  
and return the created object.

```

@Controller
@RequestMapping("/users")
public class UserRegistrationController {
 private UserService userService;

 public UserRegistrationController(UserService userService) {
 this.userService = userService;
 }

 @ModelAttribute("userModel") //изпълнява се в рамките на текущия контролер само!!!
 public void initUserModel(Model model){
 model.addAttribute("userModel", new UserRegisterDto());
 }

 @GetMapping("/register")
 public String register() {
 // когато зареждаме за първи път страницата, то автоматично ще влезе към модела атрибут
 userModel == празен new UserRegisterDto()
 return "auth-register.html";
 }
}

```

```

}

@PostMapping("/register")
public String register(@Valid UserRegisterDto userRegisterDto,
 BindingResult bindingResult,
 RedirectAttributes redirectAttributes) {

 if (bindingResult.hasErrors()) {
 redirectAttributes.addFlashAttribute("userModel", userRegisterDto);
 redirectAttributes.addFlashAttribute("org.springframework.validation.BindingResult.
userModel", bindingResult);
 return "redirect:/users/register";
 }

 userService.registerAndLogin(userRegisterDto);
 return "redirect:/"; //редиректваме към този URL, не към html страница
}
}

```

## Java dynamic proxies

Благодарение на тях, целият Spring и анотациите работят на основата на тези proxies.

sessionStorage от DevTools на браузъра се различава от Cookie HTTP session – да.

localStorage and sessionStorage are perfect for persisting non-sensitive data needed within client scripts between pages (for example: preferences, scores in games). The data stored in localStorage and sessionStorage can easily be read or changed from within the client/browser so should not be relied upon for storage of sensitive or security-related data within applications.

As cookies are used for authentication purposes and persistence of user data, **all** cookies valid for a page are sent from the browser to the server for **every** request to the same domain - this includes the original page request, any subsequent Ajax requests, all images, stylesheets, scripts, and fonts. For this reason, cookies should not be used to store large amounts of information. The browser may also impose limits on the size of information that can be stored in cookies. Typically cookies are used to store identifying tokens for authentication, session, and advertising tracking. The tokens are typically not human readable information in and of themselves, but encrypted identifiers linked to your application or database.

localStorage, sessionStorage, and cookies are all subject to "same-origin" rules which means browsers should prevent access to the data except the domain that set the information to start with.

Client-side validation are localStorage и sessionStorage

1. [LocalStorage](#)

### Pros:

1. Web storage can be viewed simplistically as an improvement on cookies, providing much greater storage capacity. If you look at the Mozilla source code we can see

that **5120KB (5MB)** which equals **2.5 Million chars** on Chrome) is the default storage size for an entire domain. This gives you considerably more space to work with than a typical 4KB cookie.

2. The data is not sent back to the server for every HTTP request (HTML, images, JavaScript, CSS, etc) - reducing the amount of traffic between client and server.
3. The data stored in localStorage persists until explicitly deleted. Changes made are saved and available for all current and future visits to the site.

**Cons:**

4. It works on [same-origin policy](#). So, data stored will only be available on the same origin.

## 1. [sessionStorage](#)

**Pros:**

1. It is similar to localStorage.
2. The data is not persistent i.e. data is only available per window (or tab in browsers like Chrome and Firefox). Data is only available during the page session. Changes made are saved and available for the current page, as well as future visits to the site on the same tab/window. Once the tab/window is closed, the data is deleted.

**Cons:**

3. The data is available only inside the window/tab in which it was set.
4. Like localStorage, it works on [same-origin policy](#). So, data stored will only be available on the same origin.

Server-side validation is Cookies, including Cookies HTTP sessionStorage

## 3. [Cookies](#)

**Pros:**

1. Compared to others, there's nothing AFAIK.

**Cons:**

2. The 4K limit is for the entire cookie, including name, value, expiry date etc. To support most browsers, keep the name under 4000 bytes, and the overall cookie size under 4093 bytes.
3. The data is sent back to the server for every HTTP request (HTML, images, JavaScript, CSS, etc) - increasing the amount of traffic between client and server.

Typically, the following are allowed:

1. **300** cookies in total
2. **4096 bytes** per cookie
3. **20 cookies** per domain
4. **81920 bytes** per domain(Given 20 cookies of max size 4096 = 81920 bytes.)

<b>LocalStorage</b>	5MB/10MB storage It's not session based, need to be deleted via JS or manually Client side reading only Less older browsers support
<b>SessionStorage</b>	5MB storage It's session based and working per window or tab Client side reading only Less older browsers support
<b>Cookie</b>	4KB storage Expiry depends on the setting and working per window or tab Server and client side reading More older browsers support

## Cookies vs. Local Storage vs. Session Storage

	<b>Cookies</b>	<b>Local Storage</b>	<b>Session Storage</b>
<b>Capacity</b>	4kb	10mb	5mb
<b>Browsers</b>	HTML4 / HTML 5	HTML 5	HTML 5
<b>Accessible from</b>	Any window	Any window	Same tab
<b>Expires</b>	Manually set	Never	On tab close
<b>Storage Location</b>	Browser and server	Browser only	Browser only
<b>Sent with requests</b>	Yes	No	No



CRITERIA	COOKIES	LOCAL STORAGE	SESSION STORAGE
MAXIMUM DATA SIZE	4 KB	5 MB	5 MB
BLOCKABLE BY USERS	YES	YES	YES
AUTO-EXPIRY OPTION	YES	NO	YES
SUPPORTED DATA TYPES	STRING ONLY	STRING ONLY	STRING ONLY
BROWSER SUPPORT	VERY HIGH	VERY HIGH	VERY HIGH
ACCESSIBLE SERVER SIDE	YES	NO	NO
DATA TRANSFERRED ON EVERY HTTP REQUEST	YES	NO	NO
EDITABLE BY USERS	YES	YES	YES
SUPPORTED ON SSL	YES	N/A	N/A
CAN BE ACCESSED ON CLEARING/DELETING LIFETIME	SERVER & CLIENT SIDE PHP, JS, AUTOMATIC AS SPECIFIED	CLIENT SIDE ONLY JS ONLY TILL DELETED	CLIENT SIDE ONLY JS & AUTOMATIC TILL TAB IS CLOSED
SECURE DATA STORAGE	NO	NO	NO

**HTTP Session:** A session is a global variable stored on the server. Each session is assigned a unique id which is used to retrieve stored values.

## Authorization vs. authentication

Authentication – чрез механизъм се определя кой си

Authorization – какво моя user има право да прави в системата

## други

WebSocket-и работят с постоянни данни – подходящо за чатове!!!

Tomcat е на apache

Content-Type: application/x-www-form-urlencoded

Browser -> ..... -> controller (DTO) -> Model -> Thymeleaf -> browser

@Controller + response body = @RestController

**th:field**

**th:value – в някои особени случаи се използва само**

Валидацията при клиента работи още преди да сме дали submit бутона на формата и е само за удобство на клиента. Реално винаги трябва да имаме валидации при back-end server-а след като сме изпратили заявката.


JS е нещото, което може да вмъкне json данни (дошли от http rest протокола) в html кода, без значение дали използваме thymeleaf или не.

Thymeleaf бил server-side технология, един вид server-side rendering

## Live templating

On Update action / On frame deactivation.

За да не чакаме по 7-10 секунди след всяка промяна в кода (някакви дреболии по front-енд кода особено) да зарежда проекта наново



## Настройки Thymeleaf

When copying manually templates in resources folder:

Option A) – restart IntelliJ

Option B) – run these 2 commands


виж версията дали е такава, при мен това беше проблема

в pom.xml при Maven

```
<parent>
 <groupId>org.springframework.boot</groupId>
 <artifactId>spring-boot-starter-parent</artifactId>
 <version>2.5.3</version>
 <relativePath/> <!-- Lookup parent from repository -->
</parent>
```

### в build.gradle при Gradle

```
plugins {
 id 'org.springframework.boot' version '2.6.7'
 id 'io.spring.dependency-management' version '1.0.11.RELEASE'
 id 'java'
}
```



### Settings

The screenshot shows the IntelliJ IDEA Settings dialog, specifically the Editor > Inspections tab. The 'Thymeleaf' profile is selected. The interface includes a search bar, a profile dropdown, and a toolbar. Below the toolbar, the 'Thymeleaf' section is expanded, showing three inspection rules: 'Thymeleaf Dialect Extensions errors', 'Unresolved message resource keys', and 'Unresolved references in Thymeleaf expression variable'. Each rule has a red error icon and a checked checkbox.

## JWT (JSON Web Token)

### What is JSON Web Token?

Не се прави при системи с логин на потребители. А когато например един микросървис комуникира с друг микросървис., или една система с друга система.

JSON Web Token (JWT) is an open standard (RFC 7519) that defines a compact and self-contained way for securely transmitting information between parties as a JSON object. This information can be verified and trusted because it is digitally signed. JWTs can be signed using a secret (with the HMAC algorithm) or a public/private key pair using RSA or ECDSA.

Although JWTs can be encrypted to also provide secrecy between parties, we will focus on signed tokens. Signed tokens can verify the integrity of the claims contained within it, while encrypted tokens hide those claims from other parties. When tokens are signed using public/private key pairs, the signature also certifies that only the party holding the private key is the one that signed it.

### When should you use JSON Web Tokens?

<https://jwt.io/introduction>

## Client-Side vs. Server-Side Rendering

<https://www.openmymind.net/2012/5/30/Client-Side-vs-Server-Side-Rendering/>

### How It Works

With **client-side rendering**, your initial request loads the page layout, CSS and JavaScript. It's all common except that some or all of the content isn't included. Instead, the JavaScript makes another request, gets a response (likely in JSON), and generates the appropriate HTML (likely using a templating library).

With server-side rendering, your initial request loads the page, layout, CSS, JavaScript and content.

For subsequent updates to the page, the client-side rendering approach repeats the steps it used to get the initial content. Namely, JavaScript is used to get some JSON data and templating is used to create the HTML.

### Initial Load

Comparing the initial flow of the two approaches, it should be obvious that **client-side rendering is going to be slower**. **It requires more JavaScript to be downloaded, which is more JavaScript to parse. It requires a 2nd HTTP request to load the content, and then requires more JavaScript to generate the template.** Even if the initial JavaScript gets cached, it still needs to get parsed, and the 2nd request isn't going to happen until the document is loaded.

При **client-side rendering** веднъж има заявка да се get-не базовата html страница, и втори или повече пъти има още rest заявки, които JS script-а генерира с някаква логика.

## Timing атаки

Обикновено ако хакер се пробва да се логва много пъти, той следи за колко време се връща отговор от сървъра. Ако е за 10ms значи няма такъв user. Ако е за 100ms, значи съществува такъв user.

Spring нарочно забавя random отговора от server-а, и хакера да не може да разбере.