

EX3 – FILE TRANSFER USING TCP

- S. Vishakan CSE – C 18 5001 196

Server Program:

```
#include <stdio.h>
#include <unistd.h>
#include <sys/types.h>
#include <sys/socket.h>
#include <netinet/in.h>
#include <string.h>
#include <fcntl.h>

int main(int argc, char **argv){
    int sockfd, flag, newfd, i = 0, len;
    struct sockaddr_in server, client;
    FILE *fp;
    char file_name[100];
    char buffer[1024];

    sockfd = socket(AF_INET, SOCK_STREAM, 0);

    if(sockfd < 0){
        perror("\nSocket cannot be created.");
        exit(0);
    }

    bzero(&server, sizeof(server));

    server.sin_family = AF_INET;
    server.sin_addr.s_addr = INADDR_ANY;
    server.sin_port = htons(7228);

    if(bind(sockfd, (struct sockaddr*)&server, sizeof(server)) < 0){
        perror("\nBind error occurred.");
        exit(0);
    }

    printf("Waiting for client...\n");

    listen(sockfd, 2);

    len = sizeof(client);
    newfd = accept(sockfd, (struct sockaddr*)&client, &len);
    flag = read(newfd, file_name, sizeof(file_name));

    printf("File to be read: %s", file_name);
```

```

fp = open(file_name, O_RDONLY); //Open the specified file in read-only mode

if(fp < 0){ //If file does not exist.
    perror("\nSpecified file could not be found.\n");
    strcpy("Error 404", buffer);
    return 1;
}

else{
    len = read(fp, buffer, 1024); //len stores the no. of characters read by read()
    close(fp);


    flag = write(newfd, buffer, len);
    printf("\nFile contents transferred.\n");
}

close(newfd);
close(sockfd);

return 0;
}

```

Output:



```

vishakan@Legion: ~/Desktop/Semester V/Practical/Computer Networks/Ex03
File Edit View Search Terminal Help
(base) vishakan@Legion:~/Desktop/Semester V/Practical/Computer Networks/Ex03$ cat sample.txt
Computer Networks
Behrouz A Fourzan
TCP Protocol
(base) vishakan@Legion:~/Desktop/Semester V/Practical/Computer Networks/Ex03$ gcc Server.c -o s -w
(base) vishakan@Legion:~/Desktop/Semester V/Practical/Computer Networks/Ex03$ ./s
Waiting for client...
File to be read: sample.txt
File contents transferred.
(base) vishakan@Legion:~/Desktop/Semester V/Practical/Computer Networks/Ex03$

```

Client Program:

```
#include <stdio.h>
#include <unistd.h>
#include <sys/types.h>
#include <sys/socket.h>
#include <netinet/in.h>
#include <string.h>
#include <fcntl.h>

int main(int argc, char **argv){
    int sockfd, flag, i = 0, len;
    struct sockaddr_in server, client;
    FILE *fp;
    char file_name[100];
    char buffer[1024];

    sockfd = socket(AF_INET, SOCK_STREAM, 0);

    if(sockfd < 0){
        perror("\nSocket cannot be created.");
        exit(0);
    }

    bzero(&server, sizeof(server));

    server.sin_family = AF_INET;
    server.sin_addr.s_addr = inet_addr(argv[1]);
    server.sin_port = htons(7228);

    printf("\nEnter the File Location: ");
    scanf(" %[^\\n]", file_name);

    connect(sockfd, (struct sockaddr*)&server, sizeof(server));

    flag = write(sockfd, file_name, sizeof(file_name));
    flag = read(sockfd, buffer, sizeof(buffer));

    if(strcmp(buffer, "Error 404") == 0){ //if file was not found
        printf("File %s was not found.\\n", file_name);
        close(sockfd);
        exit(0);
    }

    printf("File contents transferred.");

    fp = open("newfile.txt", O_WRONLY|O_CREAT, S_IRWXU);
    //create a newfile to store the content in client machine with proper permissions


    len = strlen(buffer);
```

```
write(fp, buffer, len);
close(fp);

printf("\nContents of %s written to \"newfile.txt.\\n\", file_name);
close(sockfd);

return 0;
}
```

Output:



```
vishakan@Legion: ~/Desktop/Semester V/Practical/Computer Networks/Ex03
File Edit View Search Terminal Help
(base) vishakan@Legion:~/Desktop/Semester V/Practical/Computer Networks/Ex03$ gcc Client.c -o c -w
(base) vishakan@Legion:~/Desktop/Semester V/Practical/Computer Networks/Ex03$ ./c 127.0.0.1
Enter the File Location: sample.txt
File contents transferred.
Contents of sample.txt written to "newfile.txt."
(base) vishakan@Legion:~/Desktop/Semester V/Practical/Computer Networks/Ex03$ cat sample.txt
Computer Networks
Behrouz A Fourzan
TCP Protocol
(base) vishakan@Legion:~/Desktop/Semester V/Practical/Computer Networks/Ex03$
```