SoftWorld: Development and Preliminary Verification of a Disc-Based Soft-Limb Simulation with Virtual Strain Sensing

Research Development Record — Working Configuration

Author: [Insert researcher name]
MSET graduate student, ETID
Texas A&M University

Documentation snapshot: September 15, 2026

Abstract

This report documents the development of a ROS 2/Isaac Sim platform for commanding a compliant disc-based limb, estimating bending strain from its measured orientations, and reconstructing its shape in RViz. The active configuration contains six discs, five disc-to-disc intervals, and two rings of three virtual strain gauges. Development included position and hybrid control scripts, hanging-base geometry, damping changes, independent pose-derived sensing, live strain plots, and migration from a second simulated limb to a sensor-driven visualization. A verified controller-topology mismatch caused a requested 180° bend to produce approximately 81.818°: commands retained the twelve-disc controller's eleven-interval normalization. The working loader now converts identified legacy position targets to the five-interval configuration. An end-to-end headless test using the original controller measured 179.9996° at the sixth disc. These results establish a bounded software regression result, not physical material validation or general constant-curvature accuracy. Large-angle diagonal orientation errors, sensor-model assumptions, and unvalidated hybrid behavior remain explicitly identified limitations.

Document status. This is a research-oriented technical record, not a completed thesis, peer-reviewed publication, or institutionally approved experimental protocol. It distinguishes source-code facts, recorded numerical tests, user observations, historical requests, and proposed future experiments. Author identity, advisor, research objectives, and thesis-specific requirements must be supplied by the researcher. No physical experiment is claimed.

Contents

1 Research context, objectives, and scope **3**

2 Evidence and documentation provenance **3**

3 Development history and disposition **3**

4 Simulation model and current geometry **5**

5 Constant-curvature reference kinematics **6**

5.1 Ideal continuous section 6

5.2 Radial-line intersection criterion 6

5.3 Discrete model versus an inextensible continuous arc 6

6 Position control and holding behavior **7**
6.1 Distribution over the active topology . . . 7
6.2 Drive and solver configuration . . . 7

7 Confirmed twelve-to-six-disc normalization failure **7**

8 Hybrid control: implemented interface, preliminary status **8**

9 Six virtual strain gauges **8**
9.1 Placement and retained topic names . . . 8
9.2 Measured orientation to local curvature . . . 9
9.3 Curvature to virtual axial strain . . . 9
9.4 Independence from command and physical limitations . . . 9
9.5 Virtual Wheatstone-bridge layer . . . 10

10 Sensor-driven reconstruction and RViz **10**

11 ROS interface and plotting **11**

12 Recorded preliminary verification **11**
12.1 Method and metrics . . . 11

13 Known limitations and rejected approaches **12**

14 Reproducible operation and asset handling **13**
14.1 Environment . . . 13
14.2 RViz and safe operation . . . 14
14.3 USD generation, portability, and version control . . . 14

15 Recommended next research experiments **14**

16 Conclusion **15**

A Active file map **15**

B Retained numerical excerpts **16**

C Suggested experiment-record template **17**

1 Research context, objectives, and scope

The researcher identified this project as part of MSET research in ETID at Texas A&M University. The present engineering objective is to develop a repeatable simulation workflow for compliant limb actuation and orientation-derived shape sensing. The long-term concept is to reproduce the configuration of a leader limb from sensor readings without providing those leader commands to the reconstruction system.

The active workflow is:

Position or torque command
↓
Physical disc-chain leader in Isaac Sim
↓
Six orientation-derived virtual strain readings
↓
Local curvature reconstruction and interpolation
↓
`/joint_states` and robot-state publisher
↓
TF and sensor-driven limb visualization in RViz

The word "physical" above means the physics-simulated leader, not laboratory hardware. The RViz model is a kinematic visualization, not a dynamically actuated second robot. The earlier two-limb Isaac configuration is retained as a backup. Earlier quadruped work is recorded as development history; the quadruped is separate from the currently verified six-disc workflow.

2 Evidence and documentation provenance

This report is based on the development conversation, the repository README, inspection of the working Python files, and available verification logs. The supplied Webster–Jones review was consulted for the conceptual distinction between robot-independent constant-curvature kinematics and robot-specific actuation mappings [1]. Equations labeled as implementation equations describe this repository and should not be attributed wholesale to that review.

The repository's base Git revision at documentation time was

```
e3e976c97e63596887ccb22e03ad33523c25db72
```

The working tree contained additional modified and untracked files, including the latest topology correction. Consequently, that revision alone does not reproduce this snapshot. A durable research release should commit the intended source, USD assets, documentation, and validation records together and record the resulting revision and asset hashes.

The numerical excerpts in Appendix B are copied from available test output. They are not averages across repeated trials. Historical changes without a retained quantitative test are described as development events, not established performance improvements.

3 Development history and disposition

Development stage	Purpose and current disposition
Initial limb control	Investigated initial bending, loss of commanded pose, and returning toward rest. Holding position, stiffness, and damping became recurring requirements. Early intermediate values are not reconstructed here without retained evidence.
Saved limb and quadruped	Requested new USD versions and reuse in a soft quadruped. A ROS publisher failure exposed use of a dictionary for `_publishers`, which conflicts with rclpy's internal publisher list. Ground hanging constraints, body curvature, and jelly-like motion were also addressed during earlier development. The quadruped remains a separate, historical implementation, not a validated deployment of the current limb.
Hanging limb and launch	Moved the fixed base into the air and hung the limb downward. Corrected the workflow around missing installed loader paths by rebuilding and locating scripts through the installed package.
Control alternatives	Separated position control from hybrid control: phi position versus phi torque, with theta selecting the bending plane. Several direction-range and correction attempts were rolled back. Hybrid control remains preliminary.
Constant curvature and frames	Used the continuum-kinematics review to guide bending conventions. Disc-axis visualization was requested, added, and subsequently rolled back. Disc axes are not an active feature. The intersection of disc radial lines was raised as a geometric accuracy issue.
Unexpected startup bend	Investigated possible lingering ROS controllers after forced VS Code termination. Startup targets are zero, but live external commands can still bend the limb; zero startup targets are not command isolation.
Working-file policy	Established a rule to make subsequent implementation changes in files named `working`, preserving older files as backups.
Virtual sensing	Added six pose-derived virtual gauges that respond to actual motion, including manual manipulation without a controller.
Follower and RViz	Initially used a second simulated limb; retained that version as an in-simulation backup, then replaced the active follower with sensor-driven RViz reconstruction. Added robot description, joint states, robot-state publisher, and a map-to-root transform.
Visualization and plots	Addressed RViz/Snap library conflicts and the missing map frame. Added six live strain plots and portable ZIP/build instructions in the README.
Holding and accuracy	Tuned acceleration drives, body damping, solver settings, and gravity compensation to improve holding in the working limb. This does not establish physical material stiffness.
Six-disc transition	Reduced twelve discs to six, after rollback/reapplication, and generated dedicated six-disc assets. An asset-generation crash motivated native Isaac generation rather than relying on a renderer-free flattened asset.
Shorter spacing	Reduced a temporary 55 mm pitch to 25 mm, changing clear spacing from 50 mm to 20 mm while retaining six discs. Updated geometry, anchors, gains, and RViz spacing together.

Development stage	Purpose and current disposition
Topology correction	The user measured 81.8181568° for a requested 180°. Identified the eleven-versus-five normalization mismatch; added graph-identified legacy position conversion and verified the sixth disc.

This chronology is thematic rather than a timestamped commit log. Rolled-back experiments must not be presented as features of the current configuration.

4 Simulation model and current geometry

The limb is a finite rigid-disc/virtual-link chain with compliant joint drives. It is not a finite-element model of a continuous elastomer and does not provide a resolved material stress or strain field. Continuum terminology describes its intended shape approximation and sensing model.

Quantity	Symbol	Working value
Disc count	N	6
Disc-to-disc interval count	$M = N - 1$	5
Disc thickness	t	0.005 m
Clear spacing	g	0.020 m
Disc-center pitch	$d = t + g$	0.025 m
Straight base-to-tip nominal length	$L_0 = Md$	0.125 m
Gauge/disc radius	r	0.020 m
Hanging generator base elevation	z_0	0.400 m
Runtime disc mass constant	m_d	0.010 kg
Virtual-link mass constant	m_v	0.010 kg
Virtual-link separation	h	0.0005 m

Table 2: Source configuration, not measured hardware dimensions or calibrated material properties. Mass constants are also used in gravity compensation; asset mass agreement should be checked for each research release.

The hanging generator places disc i at $\mathbf{p}_i = (0, 0, z_0 - id)$ in the straight configuration. The base is kinematic; the subsequent discs are movable. Numbering is zero-based: the first disc is `Disk_00`, and the sixth/final disc is `Disk_05`, not `Disk_06`. The Isaac final disc is red; the current RViz final disc is gray. Color does not identify an independent measurement channel.

The first interval has one base D6 joint. Each of the other four intervals has two serial D6 joints, A and B, connected through a virtual link. There are therefore nine active bending joints, not five individual D6 joints. Translation and local rotZ are locked; rotX and rotY are driven. The working topology definition and stage guard require exactly the six intended discs. The rigid-disc view uses explicitly ordered paths, and tip sensing explicitly selects index 5.

5 Constant-curvature reference kinematics

5.1 Ideal continuous section

For a planar constant-curvature section of arc length L, bending magnitude Φ, and bending-plane direction Θ,

$$\kappa = \frac{\Phi}{L}, \qquad R = \frac{1}{\kappa}, \qquad \mathbf{a}(\Theta) = (-\sin\Theta, \cos\Theta, 0)^T. \tag{1}$$

Angles in equations are radians. A reference convention with straight extension along positive local Z has

$$\mathbf{p}(s) = \begin{bmatrix} (1-\cos(\kappa s))\cos\Theta/\kappa \\ (1-\cos(\kappa s))\sin\Theta/\kappa \\ \sin(\kappa s)/\kappa \end{bmatrix}, \tag{2}$$

$$\mathbf{R}(s) = R_z(\Theta)R_y(\kappa s)R_z(-\Theta). \tag{3}$$

The $\kappa \to 0$ limit is a straight section. The hanging implementation uses negative-Z translations, so position signs must be mapped consistently when comparing it with this positive-Z reference convention.

Theta denotes the plane of bending, not an independently commanded physical twist. Total phi is base-to-tip orientation change, not the inclination of the base-to-tip chord. For an ideal planar 90° arc, that chord is inclined approximately 45° from the initial tangent.

5.2 Radial-line intersection criterion

For a circular planar centerline, each disc plane should be normal to the local tangent. The radial line *in the bending plane* through each disc center then passes through one common center of curvature. Arbitrary lines within the disc plane do not satisfy this criterion. A straight limb has no finite center of curvature, and nonuniform curvature generally has no single center.

A future quantitative check should fit a circle to measured disc centers, test disc-normal/tangent agreement, and report distances from that fitted center to the corresponding radial lines. Visual agreement alone is not an adequate numerical constant-curvature test.

5.3 Discrete model versus an inextensible continuous arc

The RViz URDF implements each interval through three revolute coordinates, with the composition

$$T_i = R_z(\theta_i)T_z(-d/2)R_y(\beta_i)T_z(-d/2)R_z(-\theta_i). \tag{4}$$

Its transmitted coordinates are $(\theta_i, \beta_i, -\theta_i)$. This symmetric construction provides a disc orientation and hinge-based position, but must not be confused with an exact continuous arc of fixed length d. Its disc-center chord length is

$$c_i = d\cos(\beta_i/2). \tag{5}$$

For a uniform planar bend, its equivalent circular radius is

$$R_{\text{hinge}} = \frac{d}{2}\cot(\beta_i/2), \qquad \ell_{\text{equivalent}} = \beta_i R_{\text{hinge}}, \tag{6}$$

whereas an inextensible constant-curvature interval would have $R_{\text{arc}} = d/\beta_i$ and chord $2(d/\beta_i)\sin(\beta_i/2)$. These agree only in the small-angle limit. Thus, fixed nominal pitch and equal orientation increments alone do not prove fixed arc length during bending. The virtual-link offsets and physics leader geometry introduce further details requiring separate positional validation.

6 Position control and holding behavior

6.1 Distribution over the active topology

For total commanded bend Φ_c, the working controller calculates

$$\beta = \frac{\Phi_c}{M} = \frac{\Phi_c}{5}, \qquad \beta_{\text{base}} = \beta, \qquad \beta_{A,j} = \beta_{B,j} = \frac{\beta}{2} \quad (j = 1, \ldots, 4). \tag{7}$$

For 180°, this is 36° at the base and 18° at each split joint. The algebraic sum of all nine scalar bend targets is 180°. The working controller clamps total requests to ±180°; local X/Y position limits are ±40°.

Each drive receives the implementation mapping

$$q_x = -\beta_j \sin\Theta, \qquad q_y = \beta_j \cos\Theta. \tag{8}$$

This is not generally equivalent to one exact axis-angle rotation at finite angles. Physical joint coordinate coupling matters for diagonal bends; Section 12 reports the observed limitation.

6.2 Drive and solver configuration

Parameter	Working runtime value
Drive type	Acceleration (mass-normalized)
Base stiffness / damping	6400 / 240
Split A/B stiffness / damping	12800 / 480
Linear / angular body damping	2.0 / 10.0
Physics frequency	240 Hz
Position / velocity solver iterations	32 / 8
Controller publishing frequency	20 Hz
Local target slew limit	20°/s
Torque magnitude limit	10^6 N m (software bound)
Torque slew limit	2×10^6 N m/s (software bound)

These are simulator drive settings, not measured Young's modulus, beam rigidity, or a calibrated physical damper. The torque bounds are especially not hardware-safe operating specifications.

In position mode, the loader applies upward forces equal to the configured disc and virtual-link weights, using $g = 9.81$ m/s^2. This explicitly compensates gravity; the reported holding test should therefore not be described as uncompensated, payload-bearing behavior. Compensation is disabled when a nonzero direct phi torque command is active. A zero-torque hybrid command consequently does not, by itself, establish a gravity-loaded torque mode experiment.

Targets are ramped locally rather than corrected instantaneously. Since base and split targets have different magnitudes but share the same local slew rate, uniform final targets do not guarantee uniform curvature during the transition. No settling-time sweep or transient constant-curvature proof has yet been recorded.

7 Confirmed twelve-to-six-disc normalization failure

The preserved original position controller has eleven intervals. If it publishes a 180° total request to a five-interval leader, the final disc receives only

$$\Phi_{\text{actual}} \simeq 5 \left(\frac{180^\circ}{11} \right) = 81.81818^\circ. \tag{9}$$

The user's reported tip reading was 81.81815680578234°, numerically consistent with this mismatch. The result is a command-normalization problem, not evidence that additional stiffness is required.

The working loader now identifies the known position controller through the ROS publisher graph. A complete contiguous set of A/B publisher pairs is used to distinguish five-interval from eleven-interval sources. For an identified legacy source,

$$q_{\text{adapted}} = q_{\text{received}} \frac{11}{5}. \tag{10}$$

Scaling happens before the local position clamp. A warning reports conversion. The working five-interval controller is not scaled again, and torque targets are not adapted. Manual publishers with a different identity are unchanged.

The local source-built Humble rclpy delivers subscription messages without publisher-message metadata. The adapter therefore requires an unambiguous publisher for each topic and verifies node identity through graph endpoints. Incomplete discovery is retried. Multiple publishers or duplicate controller identities make conversion ambiguous; a warning/error is issued and automatic conversion is disabled. This is compatibility handling, not a guarantee against all conflicting ROS commands. Run one controller only. It recognizes the specified original topology and controller identity, not arbitrary remapped or renamed controllers.

8 Hybrid control: implemented interface, preliminary status

The hybrid script publishes phi as bending torque and theta as bending-plane position. The loader converts each scalar torque into an axis in the body's current world orientation and applies equal/opposite body torques across the corresponding joint. The same requested scalar effort is published to each joint; it is not divided as a total bend angle.

Unlike position control, a torque command does not specify or guarantee a final angle. Local position targets return toward zero when direct torque is commanded, so restoring drives and damping remain part of the response. Hybrid operation, effort calibration, loaded equilibrium, and performance are not validated by the position-mode tests presented here. Large illustrative torque values in operational examples must not be transferred to hardware.

9 Six virtual strain gauges

9.1 Placement and retained topic names

Station	Disc	s/L_0	Angles about circumference
`one_third`	`Disk_02`	0.40	0°,120°,240°
`two_thirds`	`Disk_03`	0.60	180°,300°,60°

The original placement requirement was one-third and two-thirds of the limb length. With six discs, exact thirds lie between discs; the working rings use the nearest symmetric pair at 40% and 60%. Topic names are retained for compatibility. The second set is offset by 180°; threefold 120° symmetry makes the combined rings appear staggered by 60°.

9.2 Measured orientation to local curvature

Let q_i be the normalized disc orientation, represented as a quaternion in $[w, x, y, z]$ order. At sensor disc i, the implementation forms

$$q_{\mathrm{rel},i} = q_{i-1}^{-1} q_{i+1}, \qquad \boldsymbol{\omega}_i = \mathrm{rotvec}(q_{\mathrm{rel},i}). \tag{11}$$

Quaternion sign is chosen so that the scalar part is nonnegative; the rotation vector consequently uses a shortest-path rotation. The local curvature estimate is

$$\hat{\kappa}_{x,i} = \frac{\omega_{x,i}}{2d}, \qquad \hat{\kappa}_{y,i} = \frac{\omega_{y,i}}{2d}, \qquad 2d = 0.050 \text{ m}. \tag{12}$$

For the first ring this uses discs 1 and 3; for the second it uses discs 2 and 4. Z rotation is not used in the bending-strain estimate. These are nominal-spacing finite-difference estimates, not differentiation of a measured deformable centerline. The orientation difference is expressed relative to the preceding disc; interpretation as centered curvature is approximate for general nonplanar bending.

9.3 Curvature to virtual axial strain

For a gauge angle α, its nominal coordinates are $x = r\cos\alpha$, $y = r\sin\alpha$. The implemented strain convention is

$$\hat{\varepsilon}_i(\alpha) = -\hat{\kappa}_{x,i} y + \hat{\kappa}_{y,i} x = r\left(\hat{\kappa}_{y,i}\cos\alpha - \hat{\kappa}_{x,i}\sin\alpha\right). \tag{13}$$

This is dimensionless. The published reading is

$$\hat{\varepsilon}_{\mu\varepsilon} = 10^6 \hat{\varepsilon}. \tag{14}$$

For example, 10,000 $\mu\varepsilon$ corresponds to a strain magnitude of 0.01, or 1%. Positive and negative readings represent opposite bending sides under the implementation's coordinate convention; their correspondence to physical tensile/compressive polarity must be checked against a hardware gauge installation and longitudinal-axis convention.

For ideal uniform curvature, substituting $(\kappa_x, \kappa_y) = \kappa(-\sin\Theta, \cos\Theta)$ gives

$$\varepsilon(\alpha) = r\kappa\cos(\alpha - \Theta). \tag{15}$$

The ideal three-gauge ring has zero summed bending strain. A theoretical 90° bend over nominal length 0.125 m yields $r\kappa \approx 0.2513$, or about 251,327 $\mu\varepsilon$ at the extreme gauge position. This large value is a consequence of the assumed radius and kinematic equation, not a calibrated prediction for a practical gauge or proof that a real material can sustain that deformation. It is a calculated illustration, not a retained simulation measurement.

9.4 Independence from command and physical limitations

Readings use live disc poses, not desired phi or theta. They therefore respond to actual simulated motion and manually changed orientations without requiring a controller. The gauge markers are visual objects; they do not measure a deforming material surface.

The model excludes measured axial extension, shear strain, torsional strain, constitutive behavior, finite-strain calibration, noise, thermal drift, hysteresis, gauge bonding, and sensor latency. Equation (13) is an idealized kinematic emulation, not an experimentally validated strain field. A material law is not inferred from the drive stiffness. Use the term *orientation-derived virtual bending strain* in research reporting.

9.5 Virtual Wheatstone-bridge layer

The current working implementation additionally converts each of the six virtual strain values to an ideal independent quarter-bridge voltage. Its explicit research assumptions are nominal resistance $R_0 = 350\ \Omega$, gauge factor $GF = 2.0$, and excitation $V_{\text{exc}} = 2.5$ V. If the active gauge occupies the selected bridge arm, its modeled resistance is

$$R_g = R_0(1 + GF\varepsilon), \tag{16}$$

and its differential output is

$$V_{\text{out}} = -V_{\text{exc}} \frac{GF\varepsilon}{4 + 2GF\varepsilon}. \tag{17}$$

The sign is a bridge-wiring convention and must be matched to the eventual physical connection. Near zero strain, $V_{\text{out}}/V_{\text{exc}} \approx -GF\varepsilon/4$; thus 1000 $\mu\varepsilon$ produces approximately -0.5 mV/V, or -1.25 mV at 2.5 V excitation.

The voltage is published even when it is only a circuit extrapolation, while separate validity flags are false when $|\varepsilon| > 3\%$ or $|V_{\text{out}}/V_{\text{exc}}| > 25$ mV/V. A value with false validity must not be reported as a feasible physical foil-gauge measurement. At compressive strain $\varepsilon \leq -1/GF$, modeled active resistance is nonpositive and the voltage is published as NaN. The working model's predicted high-bend strains often exceed the 3% flag. Consequently, this layer provides a traceable voltage-interface hypothesis, not a validated selection of a real gauge or a demonstration that a foil gauge can survive direct mounting.

10 Sensor-driven reconstruction and RViz

Each ring supplies three strain values. Inverting Equation (13) uses the matrix

$$\mathbf{A} = r \begin{bmatrix} -\sin\alpha_1 & \cos\alpha_1 \\ -\sin\alpha_2 & \cos\alpha_2 \\ -\sin\alpha_3 & \cos\alpha_3 \end{bmatrix}, \qquad \hat{\boldsymbol{\kappa}} = \arg\min_{\boldsymbol{\kappa}} \|\mathbf{A}\boldsymbol{\kappa} - \boldsymbol{\varepsilon}\|_2^2. \tag{18}$$

Published microstrain is converted back to dimensionless strain first. The three readings estimate two bending components; a single ring is not a six-degree-of-freedom pose sensor. Axial stretch or torsion is not estimated.

The two recovered curvature vectors are interpolated componentwise at interval midpoints. NumPy interpolation uses the nearest endpoint value outside the two ring locations. Each interval is assigned

$$\beta_i = d\|\hat{\boldsymbol{\kappa}}_i\|, \qquad \theta_i = \operatorname{atan2}(-\hat{\kappa}_{x,i}, \hat{\kappa}_{y,i}). \tag{19}$$

The generated six-disc URDF contains fifteen movable visualization joints: three per interval as in Equation (4). The reconstructed joint states are published to `/joint_states`; robot-state publisher converts them to TF using the supplied robot description. A static transform connects `map` to `soft_limb_disk_00`.

The RViz limb receives sensor-derived joint states, not the leader controller's commands. Nevertheless, since its inputs are generated from leader poses through the same strain equation used for inversion, reconstruction agreement is partly an internal consistency test. It is not independent validation of the strain model. Only two rings are available; localized bends outside or between those rings cannot generally be recovered uniquely.

11 ROS interface and plotting

Stream	Purpose and units
Joint `roll/position`	Local bend target in degrees; base and pairs 01–04 A/B. Identified legacy targets are converted by the adapter.
Joint `yaw/position`	Bending-plane direction in degrees, wrapped around the circumference.
Joint `roll/torque`	Scalar direct bending effort, labeled N m.
`measured_tip/phi`	Norm of relative tip rotation-vector X/Y components, converted to degrees.
`measured_tip/theta`	Direction from those components in degrees.
`measured_tip/orientation`	Relative tip quaternion $[w, x, y, z]$.
Ring `strain`	Three-element `Float64MultiArray`, microstrain.
Ring `gauge_1..3/strain`	Individual scalar microstrain channels.
Ring `bridge_voltage`	Three-element ideal quarter-bridge output in V.
Ring `bridge_valid`	Three-element 1.0/0.0 nominal-range flag.
Ring `gauge_1..3/bridge_voltage`	Individual scalar voltage channels.
Ring `gauge_1..3/bridge_valid`	Individual Boolean validity channels.
Ring `orientation, phi, theta`	Ring pose relative to the base; quaternion and derived angles.
`/robot_description`	Generated URDF for robot-state publisher/RViz.
`/joint_states`, `/tf`	Reconstructed kinematic joint states and visualization transforms.

The joint topic prefix is `/soft_limb/pair_XX/...`; ring topics use `/soft_limb/sensors/<station>/...`; measured-tip topics use `/soft_limb/measured_tip/...`.

The working launch starts two Matplotlib plotters: one subscribes to all six individual strain channels and one to all six bridge-voltage channels. Each uses two rows of three plots, a rolling 20 s history, and a 20 Hz refresh limit. The horizontal axis uses local monotonic wall time, not a synchronized simulation timestamp. Plot histories are not automatically exported as a research dataset. Timestamp alignment, recording, and replay need to be added or managed through a documented logging workflow.

12 Recorded preliminary verification

12.1 Method and metrics

The headless harness opens the hanging six-disc asset, validates topology, applies the working drive/solver configuration, and receives commands through the actual ROS position controller. Its default run is 12 s of simulated time at 240 Hz (2880 physics steps); it measures the last simulated second. It does not start the complete RViz/plotter launch. Thus it is an end-to-end command-to-physics test, not a full graphical-launch validation.

The target tip quaternion is constructed from axis $\mathbf{a}(\Theta)$ and angle Φ_c. Full orientation error is

$$e_R = \left\| \mathrm{rotvec}(q_{\mathrm{target}}^{-1} q_{\mathrm{tip}}) \right\|, \tag{20}$$

reported in degrees. Reported phi is the norm of the relative tip rotation-vector's X/Y components. This metric is not a signed accumulated arc angle and uses a shortest-path orientation representation; bends beyond 180° cannot be interpreted as an unwrapped total angle from it.

Harness tolerances are 2° full orientation error and a 1° peak-to-peak phi range during the final second. These are software-test tolerances, not calibrated measurement uncertainty. Isaac fast shutdown can obscure a raised exception in the process exit status; inspect the explicit `VERIFY RESULT: PASS/FAIL` and retain the output rather than relying on exit status alone.

Case	Final phi	Full tip error	Status
Working controller, 180°, theta=0	179.9996°	0.0004°	PASS
Legacy controller with adapter, same target	179.9996°	0.0004°	PASS
Large diagonal, 180°, theta=45°	About 178.93°	About 10.25°	Limitation
User observation before compatibility fix	81.8181568°	Not recorded	Mismatch

Table 4: Individual recorded results. The diagonal result is retained from the prior working drive-map test and README, not a new diagonal trial of the latest compatibility adapter. No repeated-trial statistics are claimed.

The successful tests printed a final-second range of 179.9996–179.9996° at four decimal places. This establishes no visible variation at the reported precision under those conditions, not mathematically zero oscillation. Adjacent-disc orientation increments were approximately 36° in the single-axis test. Matching orientation increments does not by itself validate disc-center geometry, payload robustness, hardware behavior, or all-direction performance.

Six offline adapter regressions passed: legacy scaling, working no-double-scale, manual publisher preservation, incomplete graph detection, duplicate controller ambiguity, and the local Humble message-only callback. A real ROS test using the original publisher also confirmed base 36° and an algebraic total of 180° across nine active drives. The ROS package rebuilt successfully after the correction.

13 Known limitations and rejected approaches

1. Equation (8) produces a substantial full-orientation error at the recorded large diagonal bend. Exact all-direction constant-curvature tracking is not established, despite successful single-axis tracking.

2. An attempted runtime rotation of both D6 reference frames invalidated physics handles in the test and was removed. That strategy is not active.

3. Several earlier corrections and disc-count changes were explicitly rolled back. Their intended benefits must not be treated as retained results.

4. Equal final orientation increments do not prove continuous fixed-length curvature, and local slew limits may produce nonuniform transition shapes.

5. Gravity-compensated holding does not establish loaded or unassisted holding performance. Contact, disturbance, and mass uncertainty need testing.

6. Strain estimation and reconstruction share an idealized equation; neither has been validated against real gauges or an independent material model.

7. ROS graph-based conversion depends on publisher identity and discovery. Stale/duplicate controllers and nonstandard remappings remain operational risks.

8. Two sensor rings cannot uniquely recover arbitrary distributed curvature, torsion, axial stretch, or full shape without additional assumptions.

9. The quadruped, hybrid control, and two-physical-limb backup have not been validated by the latest single-limb position regression.

14 Reproducible operation and asset handling

14.1 Environment

The working environment uses Ubuntu 22.04, ROS 2 Humble, Isaac Sim 4.5.0, an NVIDIA GPU/-driver, colcon, RViz2, robot-state publisher, TF2, and Python Matplotlib/Tk. One successful diagnostic environment reported an RTX 3080 and driver 580.178.04; this is a test environment, not a universal prerequisite. For each recorded experiment retain exact versions, USD hashes, timestep, solver settings, drive values, and whether gravity compensation was enabled.

Paths below are portable examples. Replace the ROS setup path for a source-built installation and set the actual Isaac installation location. Run from the extracted repository root named `soft_world`.

```
cd /path/to/soft_world
source /opt/ros/humble/setup.bash
export ISAAC_SIM_PATH=/path/to/isaacsim
colcon build --packages-select soft_world
source install/setup.bash
ros2 launch soft_world soft_world_working.launch.py
```

In a separate terminal, source the same ROS and workspace setup, then run

```
cd /path/to/soft_world
source /opt/ros/humble/setup.bash
source install/setup.bash
python3 scripts/control_soft_limb_working.py --ros-args \
  -p phi_position:=180.0 -p theta_position:=0.0
ros2 topic echo /soft_limb/measured_tip/phi --once
```

The echo is run in another terminal while the controller is active. Default working position parameters are phi=90° and theta=0°; explicit experimental parameters are preferable.

To verify independently from the graphical launch, stop other controllers, source the environment, and run

```
python3 scripts/test_position_topology_working.py
"$ISAAC_SIM_PATH/python.sh" scripts/verify_bend_working.py \
  --phi 180 --theta 0
"$ISAAC_SIM_PATH/python.sh" scripts/verify_bend_working.py \
  --phi 180 --theta 0 --legacy-controller
```

Retain stdout/stderr and the explicit verification status. Run simulations sequentially to avoid resource contention. These commands require functioning GPU access and permission to write runtime ROS/Isaac logs.

14.2 RViz and safe operation

Use fixed frame `map`, add RobotModel, choose description source Topic, and set description topic `/robot_description`. The working launch publishes the map-to-base transform. Its RViz/plotter processes remove selected Snap-injected GTK/GIO paths to avoid the observed host-library ABI conflict; this workaround is environment-specific.

Start only one controller after the simulation loads. Stop the controller before stopping the launch. A forced VS Code exit may leave controllers alive; inspect nodes and process identity before terminating a confirmed stale process. Restart the simulator after loader changes; a running Python process does not automatically reload an edited installed script.

14.3 USD generation, portability, and version control

The active launch loads `usd/soft_limb_hanging_6_disc_working.usd` directly. It does not prune a twelve-disc scene at runtime. A matching six-disc position asset is retained separately from older twelve-disc assets. Native generators are invoked by `scripts/create_six_disc_assets_working.py`; they require Isaac's initialized schema/runtime environment. The authored geometry updater preserves existing native metadata rather than rebuilding a flattened asset without that environment. Asset references must be inspected when distributing to another machine; portable Python paths do not alone establish portable USD references.

For ZIP sharing, retain source, launch files, package metadata, USD assets, README, and this research documentation; omit generated `build/`, `install/`, `log/`, and caches. Rebuild at the recipient's location. `.gitignore` only governs untracked files in Git; it does not delete files, untrack committed assets, or filter a manually created ZIP. Preserve the working-file policy and avoid replacing historical backups.

15 Recommended next research experiments

These are proposed tests, not completed results.

1. Run repeated position trials across phi, theta, and both bend signs. Report quaternion error, signed interval angles where definable, final phi range, overshoot, settling time, and run-to-run variation.

2. Compare measured disc centers and orientations with a fitted circle and the continuous fixed-length reference. Report radial-line intersection residuals and distinguish hinge geometry from true continuous-arc geometry.

3. Sweep damping, drive gains, solver iterations, timestep, gravity compensation, and applied load separately. Control these variables rather than attributing all angle errors to stiffness.

4. Test localized manual perturbations and known nonuniform curvature. Compare sensor-driven reconstruction against independent pose ground truth, especially outside the sensor rings.

5. Validate virtual strain against a separate deformable model or hardware gauges, including sensor radius, sign, axial extension, finite-strain behavior, gauge factor, noise, calibration, and temperature sensitivity as appropriate.

6. Select the physical limb material and maximum curvature before purchasing foil gauges. A 350 ohm linear foil gauge and a six-channel quarter-bridge DAQ are a candidate architecture, but the simulated 25–50% high-bend surface strain is outside ordinary foil-gauge assumptions.

7. Introduce synchronized simulation timestamps, durable datasets, and experiment manifests. Preserve raw data and analysis code, not only screenshots or rolling plot displays.

8. Validate hybrid effort equilibrium and torque distribution separately; only then consider hardware transfer or quadruped integration.

Potential research questions include whether six-disc reconstruction error remains acceptable relative to a twelve-disc reference, how sparse gauge rings limit shape observability, and whether geometry-aware actuation can reduce the large-angle diagonal error without sacrificing stable compliant motion.

16 Conclusion

The working platform now supports a six-disc hanging leader, separate position and preliminary hybrid interfaces, six pose-derived strain channels, live graphs, and sensor-driven RViz reconstruction. The confirmed eleven-versus-five normalization failure was corrected in the loader and reproduced in a successful legacy-controller regression. The reported 179.9996° single-axis result is a specific software verification result. Physical strain validity, exact inextensible constant-curvature geometry, arbitrary bending-direction accuracy, and hardware applicability remain open research tasks rather than established conclusions.

References

[1] R. J. Webster III and B. A. Jones, "Design and kinematic modeling of constant curvature continuum robots: A review," *The International Journal of Robotics Research*, vol. 29, no. 13, pp. 1661–1683, 2010. doi:10.1177/0278364910368147.

[2] SoftWorld working repository: README, working Python implementation, and six-disc USD assets. Inspected September 15, 2026; working snapshot extends the base revision recorded in Section 2.

[3] SoftWorld development conversation and headless/ROS verification output, September 15, 2026. Numerical excerpts retained in this document and `validation_record_working.txt`; not an independently published dataset.

A Active file map

Repository-relative file	Role
`launch/soft_world_working.launch.py`	Simulator, RViz, TF, description, and plots.
`scripts/load_soft_limb_working.py`	Physics configuration, command consumption, sensing, torque application, and reconstruction.
`scripts/control_soft_limb_working.py`	Five-interval position command.
`scripts/control_soft_limb_hybrid_working.py`	Preliminary hybrid effort and direction command.

Repository-relative file	Role
`soft_world/limb_configuration_working.py`	Shared six-disc topology, tip index, bend normalization, and stage validation.
`scripts/limb_configuration_working.py`	Import bridge that avoids the legacy `scripts/soft_world.py` package-name collision.
`scripts/position_topology_adapter_working.py`	Identified legacy position conversion.
`scripts/test_position_topology_working.py`	Six offline adapter regressions.
`scripts/verify_bend_working.py`	ROS-to-physics headless verification.
`scripts/plot_strain_gauges_working.py`	Six live plots.
`scripts/bridge_model_working.py`	Reproducible ideal 350 ohm quarter-bridge voltage and validity model.
`scripts/test_bridge_model_working.py`	Four offline bridge-model checks.
`soft_world/robot_description_working.py`	Six-disc, fifteen-joint RViz URDF.
`scripts/soft_limb_hang_working.py`	Hanging USD generator.
`scripts/soft_limb_working.py`	Position asset generator.
`scripts/create_six_disc_assets_working.py`	Native generator wrapper.
`scripts/update_six_disc_geometry_working.py`	Native authored geometry update.
`usd/soft_limb_hanging_6_disc_working.usd`	Active hanging asset.
`usd/soft_limb_position_control_6_disc_working.usd`	Position asset.
`scripts/load_soft_limb_in_simulation_working.py`	Older two-limb backup.
`launch/soft_world_in_simulation_working.launch.py`	Backup launch.

B Retained numerical excerpts

Working-controller test:

```
VERIFY controller: base=36.0 deg,
split joints=[18.0, 18.0, 18.0, 18.0] deg;
tip=/World/SoftLimb/Disk_05
tip_orientation_error=0.0004 deg
last_second_phi_range=179.9996..179.9996 deg
intervals=[35.999966601826934, 35.99982317874544,
35.999893167570946, 35.999921731340976, 35.999989327436786]
VERIFY RESULT: PASS
```

Original twelve-disc controller with the working loader's adapter:

```
Detected legacy 12-disc position controller:
rescaling bend targets by 11/5.
180 degrees now refers to the sixth/final disc Disk_05.
VERIFY controller: base=36.0 deg,
split joints=[18.0, 18.0, 18.0, 18.0] deg;
tip=/World/SoftLimb/Disk_05
tip_orientation_error=0.0004 deg
last_second_phi_range=179.9996..179.9996 deg
VERIFY RESULT: PASS
```

Separate ROS command verification:

```
PASS actual ROS legacy controller:
base=36.000000, total=180.000000
```

The A and B arrays were both checked in the harness; the printed split array above displays A only. Rounded equality of output fields is not a substitute for a time-series dataset or uncertainty analysis.

C Suggested experiment-record template

```
Experiment ID / researcher / date:
Research question and hypothesis:
Git revision and uncommitted changes:
USD asset names, SHA-256 hashes, reference portability:
OS / ROS / Isaac / Python / GPU / driver versions:
Disc count, pitch, radius, masses:
Drive mode, stiffness, damping, body damping:
Timestep, solver iterations, gravity compensation:
Controller identity and parameters:
Loads, contact conditions, manual disturbances:
Simulation duration and timestamp convention:
Raw logs / rosbag / analysis script locations:
Metrics, tolerances, repeated-trial count:
Results, uncertainty, limitations, and disposition:
```

Record any generative-AI assistance in accordance with the researcher's program and publication requirements. The researcher should review derivations, citations, source changes, and claimed evidence before academic submission.