OWNER'S MANUAL

TABLE OF CONTENTS

WELCOME

Dear user, you hold in your hands the result of careful customizing. Mechanics and hardware of your WP 34S are of the new *HP-30b Business Professional* as is: so you get its unexcelled processor speed as well as the famous rotate-and-click keys with the tactile feedback known and appreciated in vintage Hewlett-Packard calculators for decades. On the other hand, the firmware and user interface of the WP 34S are newly designed and written from scratch to give you a **fast and compact <u>scientific</u> calculator like you have never had before**.

The function set of the WP 34S is based on the one of the renowned *HP-42S RPN Scientific*, the most powerful programmable RPN calculator built so far [1]. We expanded this set, completely incorporating the functionality of the famous programmer's calculator *HP-16C*, fraction mode of the *HP-32SII*, probability distributions as featured by the *HP-21S*, and **many more useful functions for mathematics, statistics, physics, engineering, programming etc.** like

+ Euler's Beta function, Fibonacci number calculation, Lambert's W, Riemann's Zeta (all of these in the real and complex domains), the error function, incomplete regularized Beta and Gamma, the most 'popular' orthogonal polynomials, testing for primality,

+ many statistical distributions and their inverses like Poisson, Binomial, Geometric as well as Cauchy-Lorentz, Exponential, Logistic, Weibull for reliability analysis, Lognormal and Gaussian with arbitrary means and standard deviations,

+ programmable sums and products,

+ extended date and time calculations based on a real time clock,

+ integer computing in arbitrary bases from binary to hexadecimal,

+ financial operations like mean rate of return and margin calculations,

+ over 70 conversions, mainly between universal SI and old Imperial units,

+ nearly 50 fundamental physical constants as precise as known today by national standards institutes like NIST or PTB,

+ complete Greek and extended Latin letter fonts covering many languages (upper and lower case in two font sizes each).

The WP 34S is the first RPN calculator overcoming the limits of a 4-level stack – forget worries about stack overflow in calculations. It features a choice of two stack sizes expanded by a complex LASTx register: traditional 4 stack levels for HP compatibility, 8 levels for convenient calculations in complex domain, for more advanced real formulas, or for whatever application you have in mind. You get a full command set for navigation in either size.

Furthermore, the WP 34S features over 100 general purpose registers, 100 user flags, 476 program steps, 4 programmable hotkeys for your favorite functions or routines, and a 31 byte alpha register for message generation.

---

[1] Though the *HP-42S* was sold in 1988 already, this statement holds still. – Due to display restrictions, matrix math cannot be supported by the WP 34S. Sorry for this.

If you know how to deal with a good old HP RPN calculator, you can start with your WP 34S right away. Else get the HP-42S Owner's Manual, e.g. on the DVDs distributed by the online Museum of HP Calculators (*www.hpmuseum.org*). Please read its Part 1 as a starter, including an excellent introduction to RPN. Part 2 will become beneficial when you are heading for programming your WP 34S. Further documentation, also about the other calculators mentioned, will contain valuable information as well – it is all readily accessible on a single DVD from said source. As a supplement showing you all the new features of the WP 34S we wrote this little manual here. It starts with a survey of the active keyboard in various modes, so you know where to find what you are looking for. It continues with tables about addressing, browsing the catalogs, and a paragraph about the display and indicators used to tell you what's going on. Then the major part of this booklet is taken by the index of all operations, catalog contents, constants and conversions featured. It closes with a list of messages the WP 34S will display if special input conditions prevent it from executing your command as expected.

Your WP 34S is the result of an intercontinental collaboration of two individuals, an Australian and a German. We did this in our free time, so you may call it our hobby to some extent (though some people close to us found different names for this). The project was discussed in the Museum of HP Calculators from its beginning, so we want to express our gratitude to all contributors there who taught us a lot and contributed their ideas and support in several stages of our project. Special thanks go to Marcus von Cube supporting us in bringing to life v1.14 in an emulator and the current version on your screen, so you can use it. We baptized it 34S in honor of one of the most powerful LED pocket calculators, the *HP-34C*, and since it is our humble approach – with the hardware given – to a future 43S we can only dream of becoming the successor of the *HP-42S*. Maybe it will help convincing those having access to more resources than us that it is worthwhile covering the market of serious scientific instruments.

We have checked carefully everything we could think of to our best knowledge, so our hope may be justified the WP 34S is bug-free. We cannot guarantee this, however, nor can we bear any liability for errors in calculations nor their possible consequences. Nevertheless, we promise we will improve the WP 34S whenever it turns out being necessary – so if you ever discover any strange result, please report it to us, and if it is revealed to be an internal error we will provide you with an update as soon as we have one.

Enjoy!

Paul Dale and Walter Bonin

PRINT CONVENTIONS

Throughout this manual, commands are generally called by their names, usually written in CAPITALS. This $\boxed{\text{CPX}}$ font is taken for explicit references to keys.

Register addresses are printed using Times New Roman. Lower case italic letters of this font are reserved for register contents (e.g. y or $r45$ or $alpha$ for contents of stack level Y or general purpose register $R45$ or the alpha register, respectively). Lower case bold italic Arial letters like n are used for variables.

All this holds unless stated otherwise explicitly.

KEYBOARD

Σ+	1/x	y^x	√x		
A	**B**	**C**	**D**	**→**	**CPX**
ALL	FIX	SCI	ENG	CONV	MODE
A HYP⁻¹	B SIN⁻¹	C COS⁻¹	D TAN⁻¹	E R◄►P	F aᵇ/c ᵈ/c

STO	**RCL**	**R↓**	**f**	**g**	**h**
VIEW	TIME	R↑			
G H.MS	H H.d	I RAN#			
DEG	RAD	GRAD			

ENTER↑		**x◄►y**	**+/−**	**E**	**←**
CONST		x◄►	NOT	CLP	CLx
α	FILL	J x◄►α	K 2 8	L 10 16	CLαΣ

XEQ	**7**	**8**	**9**	**/**
GTO	AND	OR	XOR	MOD
eˣ LN	M 10ˣ LG	N 2ˣ LB	O yˣ LOGx	P 1/x //

▲	**4**	**5**	**6**	**✕**
!	PROB	STAT	L.R.	STATUS
C P y,x	Q Φ⁻¹	R x̄ s	S ŷ r	T √x x²

▼	**1**	**2**	**3**	**−**
X.FCN	TEST	P.FCN	π	Σ−
◄( )►	x =≠ ?	U SLV ∫	V Π Σ	W Δ %

EXIT	**0**	**•**	**R/S**	**+**
SHOW	PSE	•/,	P/R	Σ+
⬆ ONOFF	IxI RND	X IP FP	Y LBL RTN	Z DSE ISG

a ᵇ/c

Generally, white labels execute the *default primary function* of the respective key. To access a golden, blue, or green label, use *prefix* f, g, or h, respectively. Any label underlined opens a *catalog*. For example, ⑤ preceded by

- **f** calculates the mean values of the data in the statistic registers via $\boxed{\overline{x}}$,
- **g** returns the standard deviations for the same data via $\boxed{s}$,
- **h** opens a catalog of more statistic functions via $\boxed{\text{STAT}}$.
- The dark red letter **R** will become relevant in *alpha mode*.

Further remarks (all meant as appetizers – find more about these topics below):

- The *hotkeys* $\boxed{A}$, $\boxed{B}$, $\boxed{C}$, and $\boxed{D}$ immediately call the user programs carrying these labels if defined, else they act as $\boxed{\Sigma+}$, $\boxed{1/x}$, $\boxed{y^x}$, or $\boxed{\sqrt{x}}$, respectively.

- The key $\boxed{\rightarrow}$ trailed by $\boxed{\text{H.MS}}$, $\boxed{\text{H.d}}$, $\boxed{\text{DEG}}$, $\boxed{\text{RAD}}$, $\boxed{\text{GRAD}}$, $\boxed{2}$, $\boxed{8}$, $\boxed{10}$, or $\boxed{16}$, converts x .

- If $\boxed{.}$ is used twice in numeric input, the WP 34S enters *fraction mode*.

- Prefix $\boxed{\text{CPX}}$ is employed for calling functions in complex domain. Their name will be headed by the complex symbol, e.g. $\boxed{\text{CPX}}$ **f** $\boxed{\text{COS}}$ will be displayed and listed as ^{C}COS. All complex functions in WP 34S operate on Cartesian coordinates exclusively. Generally, if an arbitrary real function **f** operates on …
  - x only, then its complex sibling ^{C}**f** will operate on $x_c = x + i\,y$.
  - one register, e.g. **R12**, then ^{C}**f** will operate on **R12** and **R13**.
  - x and y, then ^{C}**f** will operate on x, y, z and t .

- Most one-number real functions replace x by the result **f(x)** stored in X again. By analogy, one-argument complex functions replace x by the real part and y by the imaginary part of the complex result ^{C}**f(x_c)** . Higher stack levels remain unchanged. Such functions are ^{C}1/x, ^{C}ABS, ^{C}CUBE, ^{C}CUBERT, ^{C}FIB, ^{C}FP, ^{C}IP, ^{C}RND, ^{C}SIGN, ^{C}W, ^{C}W^{-1}, ^{C}x!, ^{C}x^2, $^C\sqrt{\ }$, ^{C}+/−, $^C\Gamma$(x), logarithmic and exponential with bases 10, 2 and e, as well as hyperbolic, trigonometric, and their inverses.

  Some real functions (e.g. DECOMP) operate on one number but return two. Other operations (like RCL or SUM) do not consume any stack input at all but just return one or two numbers. Then these extra number(s) will be pushed on the stack, taking one level per real or two per complex number.

- Two-number real functions replace x by the result **f(x, y)** . Level **Y** is then filled with the content of the next higher level, i.e. z . This goes on for higher levels, only the number on top of the stack is repeated as shown *below*.

  Analogously, two-argument complex functions replace x by the real part and y by the imaginary part of the complex result ^{C}**f(x_c, y_c)** . The next stack levels are filled with the complex contents of higher levels, and the complex number in the top two stack levels is repeated as shown *below*. Such complex functions are ^{C}LOG$_X$, ^{C}y^x, $^C\beta$(x,y), ^{C}// , and the basic arithmetic operations in complex domain.

- There are 3 three-number real functions included – Iβ, L$_n\alpha$ and %MRR – replacing x by the result **f(x, y, z)** . Then **Y** is filled with t and so on, and the content of the top level is repeated twice. No such complex functions are featured.

Please see the *index of operations* for a complete list and explanations of all the operations provided.

Virtual active keyboard in **hexadecimal** mode:

Primary functions of the top six keys will be numeric input, so their default primary functions are accessed using [f]. The key [→] is exclusively for addressing and temporary display in other bases (see *addressing tables* and *index of operations* below).

For smaller integer bases, the active keyboard will look similar, but those top keys not needed for numeric input will keep their default primary functions, except [Σ+] and [CPX]. Attempts to enter an illegal digit will be blocked or throw an *error*.

Virtual active keyboard in **alpha** mode:

In this mode, the alpha register is displayed in the dot matrix, and the numeric line is accessible by commands only. All labels printed on dark red or blue background in this picture append characters to *alpha* immediately or via alpha catalogs; those on blue deviate from the labels on the WP 34S keyboard at these locations.

Alpha mode starts in upper case, and ⬆ toggles upper and lower case. ⸨PSE⸩ appends a space. Primary function of most keys is appending the letter printed bottom left of this key – dark red on the key plate. Prefix ⸨f⸩ is used for accessing the default

primary functions there [2], and **g** leads to homonymic Greek letters where applicable [3]. Prefix **h** gives access to some logic symbols via the Boolean operations, and four currency symbols are located next to the %-command as follows: **$** at the letter S, **€** at U for Euro, **£** at π, **¥** at Y for Yen or Yuan – and % as h-shifted ⊟. The catalogs **f** →, **f** CPX, **f** R↓, **h** R↑, **h** TEST, and **h** ./, feature even more characters (see *below*). See the *index of operations* for αSTO, αRCL, αTIME, and more alpha commands.

When *alpha* exceeds 31 characters, the leftmost character(s) are discarded.

A subset of these characters is sufficient for **browsing an open catalog:**

Please note **f** → will just call the character → while browsing a catalog.

▲ and ▼ step through the catalog, XEQ or ENTER↑ select the item shown, and EXIT will leave the catalog without picking anything. See *below* for some examples.

---

[2] The digits 0 and 1 may also be called using **f** **0** or **f** **1**, respectively.

[3] "Homonymic" according to ancient Greek pronunciation. And we assigned **Gamma** also to **C** due to the alphabet, and **Chi** to **H** since this letter comes next in pronunciation. Three Greek letters require special handling: **Psi** is accessed via **g** **0** (below PSE), **Theta** via **g** **1** (below TEST and following **T**), and **Eta** via **g** ENTER↑. **Omicron** is not featured since looking exactly like **O** in either case. – Where we printed Greek capitals with lower contrast on page 7, they look like the respective Latin letters in our fonts. Greek professors, we count on your understanding.

A **temporary alpha** **mode** is entered during input processing in comparisons and addressing, e.g. during storing or recalling. See the respective virtual active keyboard here:

This mode is left automatically as soon as sufficient characters are put in for the respective command. See *below*.

In this mode, ⊡ is employed for ENG and SCI only (see *below*).

MEMORY

Stack registers	General purpose registers	User flags	Program steps
D *	**R00**	**00**	**000**
C *	**R01**	**01**	**001**
B *	**R02**	**02**	**002**
A *	…	…	…
T			
Z	…	…	…
Y	**R85**	**97**	**473**
X	**R86** $\Sigma\,(x^2\,y)$	**98**	**474**
	R87 $\Sigma\,x$	**99**	**475**

Alpha (31 bytes)

Display

| **L** | | **I** ** |

For the first time ever in a calculator, the WP 34S offers a choice of 4 or 8 stack levels. So either **T** or **D** will be the top level. Registers **A** - **D** will be allocated as stack registers if required.

Please see for top level repetition and stack contents in complex calculations. While register **L** takes the real part of the last argument, **I** takes the imaginary part when a complex function was executed (see ᶜLASTx).

After using $\boxed{\Sigma+}$, general purpose registers **R87** - **R99** will contain statistical sums as indicated. **J** and **K** may be taken for parameters of statistical distributions.

Unless required for the purposes just mentioned, the registers **A** - **D, I, J,** and **K** are available as additional general purpose registers.

System flags **B** and **C** are handled like in the *HP-16C*. Flag **D** is set if legal results include "NaN" and "infinite".

R88 $\Sigma\,x^2$
R89 $\Sigma\,y$
R90 $\Sigma\,y^2$
R91 $\Sigma\,(x\,y)$
R92 n
R93 $\Sigma\,(\ln x)$
R94 $\Sigma\,(\ln^2 x)$
R95 $\Sigma\,(\ln y)$
R96 $\Sigma\,(\ln^2 y)$
R97 $\Sigma(\ln x\,\ln y)$
R98 $\Sigma\,(x \ln y)$
R99 $\Sigma\,(y \ln x)$

J ***
K ***

User readable system flags

| **B** *Big, overflow* |
| **C** *Carry* |
| **D** *Danger* |

$X = $ R100
$Y = $ R101
$Z = $ R102
$T = $ R103
$A = $ R104
$B = $ R105
$C = $ R106
$D = $ R107
$L = $ R108
$I = $ R109
$J = $ R110
$K = $ R111

STACK MECHANICS

What happens with the contents of particular stack levels depends on the function executed, its domain (integer, real or complex) and the stack size chosen.

Real functions in a 4-level stack work as known for decades. In a larger stack, everything works alike on the WP 34S – just with more levels for intermediate results. Calculating formulas from inside out stays a wise strategy in either stack. With more levels, however, stack overflow will hardly ever happen, even with the most advanced formulas you compute in your life as a scientist or engineer.

Calculating with complex numbers uses two registers or levels for each such number as explained above and shown here:

With SSIZE4:

Level	Assumed stack contents at the beginning:	^{C}ENTER, ^{C}FILL	^{C}DROP	^{C}x↔y, ^{C}R↓, ^{C}R↑	^{C}LASTx	… 1 number like ^{C}x^2	… 2 numbers like ^{C}/	Before	After
T	$Im(y_c) = Im(t_c)$	$Im(x_c)$	$y_c = t_c$	x_c	x_c	$y_c = t_c$	$y_c = t_c$	t	t
Z	$Re(y_c) = Re(t_c)$	$Re(x_c)$	$y_c = t_c$	x_c	x_c	$y_c = t_c$	$y_c = t_c$	z	t
Y	$Im(x_c)$	$Im(x_c)$	y_c	y_c	$lastx_c$	$Im((x_c)^2)$	$Im(y_c / x_c)$	y	z
X	$Re(x_c)$	$Re(x_c)$	y_c	y_c	$lastx_c$	$Re((x_c)^2)$	$Re(y_c / x_c)$	x	y / x

With SSIZE8:

Level	Assumed stack contents at the beginning:	^{C}ENTER	^{C}FILL	^{C}DROP	^{C}x↔y	^{C}R↓	^{C}R↑	^{C}LASTx	… 1 number like ^{C}x^2	… 2 numbers like ^{C}/	Before	After
D	$Im(t_c)$	z_c	x_c	t_c	t_c	x_c	z_c	z_c	t_c	t_c	d	d
C	$Re(t_c)$	z_c	x_c	t_c	t_c	x_c	z_c	z_c	t_c	t_c	c	d
B	$Im(z_c)$	y_c	x_c	t_c	z_c	t_c	y_c	y_c	z_c	t_c	b	c
A	$Re(z_c)$	y_c	x_c	t_c	z_c	t_c	y_c	y_c	z_c	t_c	a	b
T	$Im(y_c)$	x_c	x_c	z_c	x_c	z_c	x_c	x_c	y_c	z_c	t	a
Z	$Re(y_c)$	x_c	x_c	z_c	x_c	z_c	x_c	x_c	y_c	z_c	z	t
Y	$Im(x_c)$	x_c	x_c	y_c	y_c	y_c	t_c	$lastx_c$	$(x_c)^2$	y_c / x_c	y	z
X	$Re(x_c)$	x_c	x_c	y_c	y_c	y_c	t_c	$lastx_c$	$(x_c)^2$	y_c / x_c	x	y / x

So, an 8-level stack gives you the same flexibility in complex domain you are used to with a 4-level stack in real domain.

COMPARING AND ADDRESSING REAL NUMBERS

1	User input	`x= ?`, `x≠ ?`, `x< ?`, `x≤ ?`, `x≈ ?`, `x≥ ?`, or `x> ?`				`RCL`, `STO`, `RCLS`, `STOS`, `αRCL`, `αSTO`, `VIEW`, `x≷`, `DSE`, `ISG`, `DSZ`, `ISZ`, `FIX`, `SCI`, `ENG`, `DISP`, `BASE`, `CB` and many more bit commands, or `CF` and the other flag commands etc.			
	Dot matrix display	**OP** _ (with temporary alpha mode set), e.g. `x⟩ _`				**OP** _ (with temporary alpha mode set), e.g. `RCL _` [4]			
2	User input	`0` or `1`	*Stack level or named reg.* `X`, `Y`, ...	`ENTER↑` [5] leaves temp. alpha mode.	`→` opens indirect addressing.	*Stack level or named register* `X`, `Y`, `Z`, .. , `K` [6]	***Number** of register or flag or bit(s) or decimals* [7]	`→` opens indirect addressing.
	Dot matrix display	**OP** *n* e.g. `x≤ 0 ?`	**OP** *x* e.g. `x≥ y ?`	**OP** r_	**OP** →_	**OP** *x* e.g. `SCI Z`	**OP** *nn* e.g. `SF 15`	**OP** →_
3	User input	Compares *x* with the number **0**.	Compares *x* with the number on stack level **Y**.	*Register no.* `0` `0` … `9` `9`	Look right for more about indirect addressing.	Sets scientific display with the number of decimals specified in stack level **Z**.	*Stack level etc.* `X`, `Y`, `Z`, ... , `K`	*Register number* `0` `0` … `9` `9`
	Dot matrix display			**OP** r *nn* e.g. `x≠ r23?`			**OP** → *x* e.g. `VIEW →L`	**OP** → *nn* e.g. `STO →45`
				Compares *x* with the number stored in **R23**.			Shows the content of the register where **L** is pointing to.	Stores *x* into the location where **R45** is pointing to.

---

[4] For `RCL` and `STO`, any of `+`, `−`, `×`, `/`, `▲`, or `▼` may precede step 2, except in RCLM and STOM. `ENG` `.` calls ENGOVR, `SCI` `.` calls SCIOVR. See the index of operations.

[5] You may skip this for register numbers >19.

[6] Exceptions: RCL T, RCL× T, RCL Z, RCL+ Z require an `ENTER↑` preceding `T` or `Z`, e.g. `RCL` `+` `ENTER↑` `Z` for the latter. This holds for STO as well.

[7] Register and flag numbers may be 00 … 99, number of decimals 0 … 11, integer bases 2 … 16, bit numbers 0 to 63, and integer word size up to 64 bits. For numbers <10, you may key in e.g. `5` `ENTER↑` instead of `0` `5`. There are three additional flags addressed via `B`, `C`, and `D`. – Take into account some registers may be allocated to special applications.

COMPARING AND ADDRESSING COMPLEX NUMBERS

		CPX x= ? or x≠ ?				CPX RCL, STO, or x⇄		
1	**User input**							
	Dot matrix display	**OP** _ (with temporary alpha mode set) e.g. ▫x= _				**OP** _ (with temporary alpha mode set) e.g. ▫RCL _ [8]		
2	**User input**	**0** or **1**	*Stack level or named register* **X**, **Z**, **A**, **C**, **L**, or **J**	**ENTER↑** [9] leaves temp. alpha mode	**→** opens indirect addressing.	*Stack level or named register* **Z** [10], **A**, **C**, **L**, or **J**	*Register number* **0 0** .. **9 8** [11]	**→** opens indirect addressing.
	Dot matrix display	**OP n** e.g. ▫x= 0 ?	**OP x** e.g. ▫x≠ z ?	**OP r_**	**OP →_**	**OP x** e.g. ▫RCL L	**OP nn** e.g. ▫STO 18	**OP →_**
3	**User input**	Compares $x + i\,y$ with the real number **0**.	Compares $x + i\,y$ with $z + i\,t$.	*Register number* **0 0** … **9 8**	Look right for more about indirect addressing.	This is ^{C}LASTx.	*Stack level or named register* **X**, **Y**, ... , **K**	*Register number* **0 0** … **9 9**
	Dot matrix display			**OP r nn** e.g. ▫x≠ r26?			**OP → x** e.g. ▫x⟨⟩ →Z	**OP → nn** e.g. ▫STO →45
				Compares $x + i\,y$ with $r26 + i\,r27$.			Swaps **x** with the contents of the register where **Z** is pointing to, and **y** with the contents of the next one.	Stores $x + i\,y$ into 2 consecutive registers, starting with the one where **R45** is pointing to.

---

[8] For **RCL** and **STO**, any of **+**, **−**, **×**, or **/** may precede step 2. See the index of operations.

[9] You may skip this keystroke for register numbers >19.

[10] Exceptions: ^{C}RCL Z, ^{C}RCL + Z, ^{C}STO Z, and ^{C}STO + Z require an **ENTER↑** preceding **Z**, e.g. **CPX** **STO** **+** **ENTER↑** **Z** for the latter.

[11] You may key in e.g. **8** **ENTER↑** instead of **0** **8**. Take care of pairs, since a complex operation will always affect two registers: the one specified and the one following this. We strongly recommend storing complex numbers with their real parts at even register numbers. – Take into account some registers may be allocated to special applications.

ADDRESSING LABELS

1	User input	**A**, **B**, **C**, or **D**		XEQ, GTO, LBL, LBL?, SLV, ∫, π or Σ			
	Dot matrix display	**XEQ 'label'** e.g. XEQ 'C'		**OP _** e.g. GTO _			
2	User input	Calls the function labeled **C**.	**A**, **B**, **C**, or **D**	**ENTER↑** sets alpha mode.	**→** [12] opens indirect addressing and sets temporary alpha mode.		*2-digit numeric label* **0 0** … **9 9**
	Dot matrix display		**OP 'label'** e.g. Σ 'B'	**OP '_**	**OP →_**		**OP nn** e.g. LBL 07
3	User input	Sums up the function labeled **B**.		*Alphanumeric label* (≤ 3 characters [13])	*Stack level or named register* **X**, **Y**, **Z**, ... , **K**	*Register number* **0 0** … **9 9** [14]	
	Dot matrix display			**OP 'label'** e.g. SLV'F1μ'	**OP → x** e.g. ∫ →T	**OP → nn** e.g. XEQ →44	
				Solves the function **F1μ** (with **F1μ** keyed in as explained in footer).	Integrates the function whose label is on stack level **T**.	Executes the routine whose label is in **R44**.	

---

[12] Works with all these operations except LBL .

[13] The 3rd character terminates entry and closes alpha mode – shorter labels need a closing **ENTER↑** . For the example given here you just key in **f 2 ENTER↑ CPX 1 f EXIT g 7** and you are done.

[14] Some registers may be allocated to special applications. Please check the memory table above.

ADDRESSING CATALOG ITEMS

1	User input	`CONST`, `CONV`, `MODE`, `PROB`, `P.FCN`, `STAT`, `TEST`, or `X.FCN`	`CPX`, `R↓`, or `R↑` in alpha mode	`→`, `TEST`, or `./,` in alpha mode
	Dot matrix display	**Shows 1ˢᵗ item in selected catalog.** (e.g. `BC?` in `P.FCN`) Alpha mode is set.	(e.g. `Á` in `CPX`)	(e.g. `,` in `./,`)
2	User input	`XEQ`, `▼`, `▲`, `EXIT`, or 1ˢᵗ character (e.g. `F`)	`XEQ`, `▼`, `▲`, `EXIT`, or character (e.g. `O`)	
	Dot matrix display	**Shows 1ˢᵗ item starting with this character *)** (e.g. `FB`)	**Shows 1ˢᵗ item starting with this letter *)** (e.g. `Ó`)	
3	User input	`XEQ`, `▼`, `▲`, `EXIT`, or 2ⁿᵈ character (e.g. `S`)		
	Dot matrix display	**Shows 1ˢᵗ item starting with this sequence *)** (e.g. `FS?`)		
4	User input	`XEQ`, `▼`, `▲`, or `EXIT` (e.g. `▼`)		
	Dot matrix display	**Shows next item in this catalog** (e.g. `FS?C`)	(e.g. `Ò`)	(e.g. `?`)
…		Continue browsing this way until reaching the item desired		
		(e.g. `FS?F`).	(e.g. `Ö`).	(e.g. `:`).
n	User input	`XEQ`		
		Calculator leaves the catalog returning to the mode set before		
	Dot matrix display	… and executes or inserts the command chosen, or recalls the constant selected. **Result**	… and appends the selected character to **_alpha_**. **Contents of alpha register** (e.g. `Östl. Seite:`)	

*) If a character or sequence specified is not found in this catalog then the first item following alphabetical-ly will be shown. You may key in even more characters – within 3 seconds. Thereafter or after `▼` or `▲`, the search string will be reset and you may start with a first character again.

STATISTICAL DISTRIBUTIONS, PROBALITIES ETC.

You find a lot of statistics in the WP 34S. Many preprogrammed functions are implemented here for the first time in an RPN scientific calculator since we packed all in what we always had missed. All of these functions, however, have a few features in common:

- Whenever we sum up a probability mass function (pmf [15]) $p(n)$ to get a cumulated distribution function (cdf) $F(m)$ we start at $n = 0$. Thus,

$$F(m) = \sum_{i=0}^{m} p(i) \ .$$

- Whenever we integrate a function, we start at the left end of the integration interval. Thus, integrating a probability density function (pdf) $f(x)$ to get a cdf $F(x)$ works as

$$F(x) = \int_{-\infty}^{x} f(\xi)d\xi = P(x) \ .$$

- Typically, F starts with a very shallow slope, becomes steeper then, and runs out with a decreasing slope while slowly approaching 100%. Obviously you get the most precise results on the left side of the cdf using $P(x)$. On its right side, however, the "error probability" $Q(x) = 1 - P(x)$ is more precise since $P(x)$ comes very close to 1 there. The WP 34S features them all: with a cdf named **XYZ** you find **XYZ$_P$** for the pdf or pmf, **XYZ^{-1}** for the inverse cdf, and also **XYZ←** for $Q(x)$, unless stated otherwise explicitly.

- For calculating confidence limits for the "true value" based on a sample evaluation, employing a particular confidence level (e.g. 95%), you must know your objective:

  o Do you want to know the upper limit, under which the „true value" will lie with a 95% probability? Then take 0.95 as the argument of the inverse cdf to get said limit, and remember there is an inevitable chance of 5% for the "true value" being greater than it.

  o Do you want an upper <u>and</u> a lower limit confining the "true value"? Then there is an inevitable 2.5% chance for said value being less than the lower limit and an equal chance for it being greater than the upper limit. So you shall use 0.025 and 0.975 as arguments in two subsequent calculations using the inverse cdf to get both limits.

  o If you cannot live with these chances, inevitable as they are, employ an higher confidence level.

Turn to a good statistics textbook for more information, also about the particular distributions provided.

---

[15] pmf translates to German „Dichtefunktion", pdf to „Wahrscheinlichkeitsdichte", cdf to „Verteilungsfunktion" or „Wahrscheinlichkeitsverteilung".

DISPLAY AND MODES

The display features three sections: numeric, dot matrix and fixed symbols. The numeric section features a minus sign and 12 digits for the mantissa, as well as a minus sign and 3 digits for the exponent. The dot matrix is 6 dots high and 43 dots wide, allowing for some 7 to 12 characters, depending on their widths. The fixed symbols (except the big "=") are called *annunciators*, and are for indicating modes.

The dot matrix section above is used for

1. indicating some more modes than the annunciators allow,
2. passing additional information to the user.

The numeric section in the lower part of the LCD is used for displaying numbers in different formats, status, or messages.

If two or more requests concur for display space, the items will be shown according to their priorities as follows:

1. error messages as described in a *paragraph further below*,
2. special information as explained below,
3. information about the modes the calculator is running in.

The *annunciators* or specific characters in the display signal the modes:

Signal	*INPUT*	b	d	h	o	
Mode name if different	α	**2**			**8**	**DECM**
Set by …	αON	BASE2	BASE10	BASE16	BASE8	BASE0
Cleared by …	αOFF	any other BASE setting, FRACT, IMPFRC, PROFRC. FIX, SCI, ENG, H.MS, TIME, →H.MS will set DECM				

Signal	*STO*	*360*	*RAD*	**G**	
Mode name if different	**PRG**				**FRC**
Set by …	PRGON	DEG	RAD	GRAD	BASE1, FRACT IMPFRC, PROFRC 2nd ⟨.⟩ in input
Cleared by …	PRGOFF	GRAD RAD	DEG GRAD	DEG RAD	BASE ≠ 1 H.MS, TIME, →H.MS FIX, SCI, ENG

BEG indicates the program pointer standing at step 000 of program memory. A running program is signaled by a flashing *RCL* annunciator. The small equal sign **=** is lit while you are browsing a catalog. *RPN* may be lit permanently. Time modes (12h / 24h) are seen in the time string directly. The numeric format of fraction mode is unambiguous as well. Further settings are signaled in the dot matrix section, like the different date modes being indicated there by **D.MY** or **M.DY**. Defaults Y.MD and DECM are not indicated. Please check the examples below.

Some mode and display settings may be stored and recalled collectively by STOM and RCLM. The command RCLM recalls a 19-bit word containing mode data packed as follows, starting with the least significant bit:

Bits	Meaning	Values and corresponding settings		
0, 1	Display format for real numbers	0 = ALL 1 = FIX 2 = SCI 3 = ENG		
2	Overflow for ALL	0 = SCIOVR 1 = ENGOVR		
3 … 6	Number of decimals	0 … 12		
7, 8	Angular mode	0 = DEG	1 = RAD	2 = GRAD
9, 10	Date display format	0 = Y.MD	1 = D.MY	2 = M.DY
11	Time display format	0 = 24h	1 = 12h	
12	Radix mark	0 = point	1 = comma	
13 … 15	Curve fit model	0 = LinF 1 = ExpF 2 = PowerF 3 = LogF		4 = BestF
16, 17	Integer sign mode	0 = 2COMPL 1 = 1COMPL 2 = UNSIGN 3 = SIGNMT		
18	Stack depth	0 = 4 levels	1 = 8 levels	

So the start-up default with 4 stack levels, ALL, SCIOVR, DEG, Y.MD, 24h, decimal point, LinF, and 2COMPL equals zero in this mode word. On the other hand, settings for e.g. 8 stack levels, SCI 2, RAD, D.MY, 12h, decimal comma, BestF, UNSIGN correspond to

$$1101001101010010010_2 = 69A92_{16} = 432786_{10} .$$

STOM takes such a number and sets the calculator modes accordingly. Please see the *index of operations* for more information about changing modes.

Some commands and modes use the display in a special way. They are listed below in order of falling priority:

1. **VERS** generates a display as shown on the title page of this manual. Pressing any key will delete this message and return to previous state.

2. **STATUS** displays the status of 30 flags very concisely, allowing an immediate status overview after some training. If e.g. flags 2, 3, 5, 7, 11, 13, 14, 17, 19, and 23 are set, and labels B, C, and D are defined in program memory, STATUS will display this:

   Within the numeric section, each row of horizontal bars in the mantissa shows the status of 10 flags. When a flag is set, the respective bar turns black. So here the top row of bars indicates flags 0 and 1 are clear, 2 and 3 set, and flag 4 clear. Then, the divider II separates the first group of five flags from the next. Top row bars on its right side indicate flags 5 and 7 are set. Next row of bars shows flags 11, 13, 14, 17, 19 are set, and in the lowest row only flag 23 is set. All other flags in the range from 10 to 29 are clear.

   Scrolling down by ▼ will display flags 10 - 39, then 20 - 49 etc. until 80 - D. Scrolling up by ▲ reverts this. Alternatively, pressing a digit, e.g. 5, will show 30 flags starting with 10 times this digit, e.g. flags 50 - 79. The numeric exponent always indicates the status of the hotkeys top left on the keyboard – if all four labels are in use, then only the first three are indicated.

   The status will be displayed until any key is pressed but ▼, ▲, or a digit < 9.

3. During **command input**, the dot matrix displays the command chosen until input is completed, i.e. until all required trailing parameters are entered. The prefixes **f**, **g**, and **h** are shown until they are resolved. If you pressed any of **f**, **g**, or **h** erroneously, recovery is as easy as follows:

   o **f** **f** = NOP = **g** **g** = **h** **h** = CPX CPX = ➡ ➡

   o **g** **f** = **h** **f** = **f**
   f **g** = **h** **g** = **g**
   f **h** = **g** **h** = **h**

   In addressing, progress is recorded as explained in the *addressing tables above* in detail.

4. In **programming mode**, the numeric display indicates the program step (000 – 475) in the mantissa and the number of free steps in the exponent, while the dot matrix shows the command contained in the respective step, e.g.:

5. For **floating point decimal numbers**, the mantissa will be displayed adjusted to the right, the exponent to the left. Within the mantissa, either points or commas may be

selected as radix marks [16], and additional marks may be chosen to separate thousands. Assume the display set to FIX 4, then 12.345678901 millions may look like:

  or

with thousands separators on, and without them like:

  or

These separators may also be beneficial in integer or fraction modes described below. – With ENG 3 and after changing the sign, the same number will look like this:

  or

If the last operation executed was a complex one, a capital C is displayed top left in the dot matrix pointing to the fact that you find the result of this function in **X** and **Y**.

Floating point decimal numbers within $10^{-383} < x < 10^{+385}$ may be entered easily. Using a decimal mantissa, even numbers down to 10^{-394} can be keyed in. The calculator works with numbers down to 10^{-398} correctly. Smaller nonzero values are shown as 0^{-398}. For results $x \geq 10^{+385}$, error 4 or 5 will appear (see *below*).

6. In **integer modes**, numbers are displayed adjusted to the right as well. Word size and complement setting are indicated in the dot matrix using a format ***xx.ww***, with ***xx*** being **1c** or **2c** for 1's or 2's complement, respectively, **un** for unsigned, or **sm** for sign-and-mantissa mode. Sign and first digit of the exponent show the base, a "c" in the second digit signals a carry bit set, an "o" in the third an overflow. Integer bases are indicated as follows:

Base	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
Sign and 1st digit of exponent displayed	b	3	4	5	6	7	o	9	d	-1	-2	-3	-4	-5	h

The example shows the WP 34S in unsigned hexadecimal mode with word size 64 and carry set:

---

[16] Starting here, decimal input is written using a point as radix mark throughout this manual, although significantly less visible, unless specified otherwise explicitly. By experience, the „comma people" are more capable to read radix points and interpret them correctly than vice versa.

After changing to binary mode, this number will need 28 digits, being 1001001110100001010010110110. The 12 least significant digits will be displayed initially together with an indication that there are three display windows in total with the rightmost shown:

$$\text{un64} \quad \text{"|} \qquad \text{RPN}$$
$$0100\,1011\,0110 \quad \text{bc}$$

Now press ◀ and you will get the next 12 digits in the middle window:

$$\text{un64} \quad \text{"|"} \qquad \text{RPN}$$
$$0011\,1010\,0001 \quad \text{bc}$$

Press ◀ again to show the most significant digits:

$$\text{un64} \quad \text{|"} \qquad \text{RPN}$$
$$1001 \quad \text{bc}$$

If leading zeros were turned on, there will be six display windows in this case, with the three "most significant" containing only zeros.

Please note numeric input is limited to 12 digits in any integer base.

Please note the window will also change in numeric entry when more than 12 digits are keyed in. Leftmost digits will leave the display window then.

7. **Fraction mode** works similar to HP-35S. In particular, DENMAX sets the maximum allowable denominator (see the *index of operations*). Display will look like in the examples below. If the fraction is exactly equal, slightly less, or greater than the floating point number converted, "=", "Lt", or "Gt" is indicated in the exponent, respectively.

Assume DENMAX ≥ 32. Then e.g. -47.40625 will be displayed as follows:

$$\text{RAD} \quad \text{RPN} \qquad\qquad \text{RAD} \quad \text{RPN}$$
$$-47\ 13r32\ = \qquad\text{or}\qquad -1517r32\ =$$

depending on the output setting for proper or improper fractions. Please note integers like 123 will be displayed as "123 0/1" or "123/1" in fraction mode, respectively.

Fraction mode can handle numbers with absolute values < 10,000 and > 0.0001. Maximum denominator is 9999.

Using DENMAX = 9999, squaring the improper fraction shown above results in

$$\text{RAD} \quad \text{RPN}$$
$$2301289r1024\ =$$

Now, enter a b/c for converting this result into a proper fraction. Your 34S will display

$$\text{RAD} \quad \text{RPN}$$
$$\llcorner 47\ 361r1024\ =$$

with a little hook left of the first digit shown. This indicates the first number being dis-

played incompletely – there are at least two digits preceding 47 but no more display space. Press [SHOW] to unveil the integer part of this proper fraction is <u>22</u>47.

8. In **H.MS display mode**, format is `hhhh°mm'ss.dd"` with the number of hours or degrees limited to 9000. Output may look like this:

 or

depending on the radix setting. For decimal times less than 5ms or 0.005 angular seconds but greater than zero, an "u" for underflow will be lit in the exponent section. For times or angles exceeding the upper limit, an "o" will be shown there signaling an overflow, and the value is displayed modulo 9000.

9. Output of the function **DAY** will look as follows for an input of 1.13201 in M.DY mode (equivalent to inputs of 13.01201 in D.MY or 2010.0113 in Y.MD). Expect similar displays after DAYS+.

10. In **alpha mode**, the alpha register is displayed in the dot matrix, starting with the first character it is containing, while the numeric section keeps the result of the last numeric operation, e.g.:

Different information may be appended to *alpha*. See the commands starting with "α" in the index of operations below. E.g. αTIME allows creating texts like

 or

depending on time mode setting (12h / 24h). And αDATE will append – depending on date format setting – either 2011-03-14 or 14.03.2011 or 03/14/2011 to *alpha*.

Please note *alpha* may be considerably longer than the display window. And the WP 34S features a rich set of special letters. So you may store a message like

easily but you will see its right end only, i.e.

in this very special case.

All keyboard input will be interpreted according to the mode set at input time.

FONTS

The WP 34S features a large and a small font. Both are based on Luiz Viera's fonts as distributed in 2004. Some letters were added and some modified for better legibility, since the dot matrix is only 6 pixels high here. The following tables show the characters directly accessible through the keyboard. More are in the alpha catalogs (see *below*).

A B C D E F G H I J K L M N O P Q R S T U V W X Y Z
ABCDEFGHIJKLM NOPQRSTUVWXYZ
ABCDEFGHIJKLM NOPQRSTUVWXYZ

a b c d e f g h i j k l m n o p q r s t u v w x y z
abcdefghijklm nopqrstuvwxyz
abcdefghijklm nopqrstuvwxyz

A B Γ Δ E Z H Θ I K Λ M N Ξ O Π P Σ T Y Φ X Ψ Ω
ABΓΔEZHΘIKΛM NΞOΠPΣTYΦXΨΩ
ABΓΔEZHΘIKΛM NΞOΠPΣTYΦXΨΩ

α β γ δ ε ζ η θ ι κ λ μ ν ξ o π ρ σ τ υ φ χ ψ ω
αβγδεζηθικλμ νξoπρστυφχψω
αβγδεζηθικλμ νξoπρστυφχψω

0 1 2 3 4 5 6 7 8 9	( ) + - × / ± . !	↔ % √ \ & | ≠ $ € £ ¥
0123456789	()+−×/±.!	↔%√\&|≠$€£¥
0123456789	()+−×/±.!	↔%√\&|≠$€£¥

INDEX OF OPERATIONS

All functions available are found below with their names and keystrokes necessary. Names printed in **bold** face therein belong to commands directly accessible on the keyboard, the others are accessible via catalogs. These names will show up in program listings as well. Sorting in index and catalogs is case insensitive and works in the following order:

␣, 0…9, A…Z, !, α…ω, ( ) + − × ∕ ± , . ? : ; ' " # * @ _ ~
→ ← ↑ ↓ ↔ < ≤ = ≠ ≥ > % $ € £ ¥ √ ∫ ∞ & \ ^ | G [ ] { }

Super- and subscripts are handled like normal characters in sorting.

Generally, functions and keystroke programming will work as on *HP-42S*, bit and integer functions as on *HP-16C*, unless stated otherwise under remarks. Especially, all **tests** will return "Yes" or "No" in the dot matrix if called from the keyboard; if called in a program, they will skip the next program line if the test is false. Please refer to the manuals of the vintage calculators mentioned, e.g. on the DVDs distributed by *www.hpmuseum.org*.

Functions available on the WP 34S for the first time on an RPN calculator are highlighted yellow under remarks, while operations carrying a familiar name but deviating in their functionality here are marked light red.

Parameters will be taken from the lowest stack levels unless being mentioned explicitly in the 2nd column. Then they must follow the command. If **_underlined_**, they may also be specified using indirect addressing, as shown in the *tables* above. Some parameters of statistical distributions must be given in registers **J** and **K** if specified.

Each function is listed stating the mode(s) it will work in, abbreviated by their *indicators*. In this column an "&" stands for a Boolean AND, a comma for an OR, and a backslash for "not". So e.g. 2^X works in all modes but alpha. All operations will also work in mode PRG unless stated otherwise explicitly.

Name	Keys to press	in modes	Remarks
c…	CPX …	DECM	Indicates an operation in complex domain (see *above*). CPX may be combined with all functions whose *names are printed in italics here* .
10ˣ	f 10ˣ	DECM	
12h	h MODE 12h	\α	Sets 12h time display mode meaning 1:23 becomes 1:23 a.m. and 13:45 becomes 1:45 p.m.
1COMPL	h MODE 1COMPL	\α	Sets 1's complement mode like in *HP-16C*.
1/x	f 1/x	DECM	
	B	DECM	Shortcut as long as label B is not defined yet.
24h	h MODE 24h	\α	Sets 24h time display mode meaning 1:23 a.m. becomes 1:23, and 1:45 p.m. becomes 13:45.
2COMPL	h MODE 2COMPL	\α	Sets 2's complement mode like in *HP-16C*.

Name	Keys to press	in modes	Remarks
2^x	**f** 2^x	\α	
ABS	**f** |x|	\α	^{C}ABS returns $r = \sqrt{x^2 + y^2}$ in **X** and clears **Y**.
ACOS	**g** COS^{-1}	DECM	
ACOSH	**g** HYP^{-1} COS	DECM	
ALL	**h** ALL	\α	Selects the format displaying "all" digits.
AND	**h** AND	Integer	Works bitwise as in *HP-16C*.
		DECM	Works like AND in *HP-28S*, i.e. *x* and *y* are interpreted before executing this operation. 0 is "false", any other real number is "true".
ANGLE	**h** X.FCN ANGLE	DECM	Calculates the angle between positive x-axis and the straight line from the origin to the point (*x, y*) , returns this angle in **X** and clears **Y**.
ASIN	**g** SIN^{-1}	DECM	
ASINH	**g** HYP^{-1} SIN	DECM	
ASR	**h** X.FCN ASR ***n***	Integer	Works like ***n*** (up to 63) consecutive ASRs in *HP-16C*. ASR 0 executes as NOP.
ATAN	**g** TAN^{-1}	DECM	
ATANH	**g** HYP^{-1} TAN	DECM	
BASE	**h** MODE BASE ***n***	\α	Sets the base for integer calculations, with $2 \le n \le 16$. Popular bases are directly accessible on the keyboard. Current integer base setting is indicated in the exponent as explained *above*.
BASE10	**f** 10		
BASE16	**g** 16		
BASE2	**f** 2		Furthermore, BASE0 equals DECM, and BASE1 calls FRACT.
BASE8	**g** 8		
BC?	**h** TEST BC? ***n***	Integer	Tests the specified bit in *x* .
BestF	**h** STAT BestF	DECM	Selects the best curve fit model, maximizing the correlation like BEST does in *HP-42S*.

Name	Keys to press	in modes	Remarks
Binom Binom$_P$ Binom^{-1} Binom←	**h** **PROB** Binom etc.	DECM	Binomial distribution with the number of successes **g** in **X**, the gross error probability **p_0** in **J** and the sample size **n** in **K**: pmf: $p_B(g;n;p_0) = \binom{n}{g} \cdot p_0^{\,g} \cdot (1-p_0)^{n-g}$. cdf: $F_B(m;n;p_0) = \sum_{g=0}^{m} p_B(g;n;p_0)$, with the maximum number of successes **m** in **X**. The pdf equals BINOMDIST(**g; n; p_0; 0**) and the cdf BINOMDIST(**m; n; p_0; 1**) in MS Excel. Binom^{-1} returns **m** for given probabilities **F_B** in **X** and **p** in **J** with sample size **n** in **K**.
B$_n$	**h** **X.FCN** B$_n$	DECM	Returns the Bernoulli number for integer **n** > 0 given in **X**: $B_n = (-1)^{n+1} n \cdot \zeta(1-n)$. See below for ζ.
B$_n$*	**h** **X.FCN** B$_n$*	DECM	Returns the Bernoulli number according to its old definition for integer **n** > 0 given in **X**: $B_n^* = \frac{2 \cdot (2n)!}{(2\pi)^{2n}} \cdot \zeta(2n)$. See below for ζ.
BS?	**h** **TEST** BS? **n**	Integer	Tests the specified bit in **x** .
Cauch Cauch$_P$ Cauch^{-1} Cauch←	**h** **PROB** Cauch etc.	DECM	Cauchy-Lorentz distribution with the location **x_0** specified in **J** and the shape **γ** in **K** , also known as Lorentz or Breit-Wigner distribution: pdf: $f_{Ca}(x) = \frac{1}{\pi\gamma} \cdot \frac{1}{1+\left(\dfrac{x-x_0}{\gamma}\right)^2}$ cdf: $F_{Ca}(x) = \frac{1}{2} + \frac{1}{\pi}\arctan\left(\dfrac{x-x_0}{\gamma}\right)$. Cauch^{-1} returns **x** for a given probability **F_{Ca}** in **X**, with location **x_0** in **J** and shape **γ** in **K**.
CB	**h** **X.FCN** CB **n**	Integer	Clears the specified bit in **x** .
CEIL	**h** **X.FCN** CEIL	DECM	Returns the smallest integer ≥ **x** .
CF	**h** **P.FCN** CF **n**	\α	Clears the flag specified.
CLFLAG	**h** **P.FCN** CLFLAG	\α	Clears all user flags.

Name	Keys to press	in modes	Remarks
CLREG	**h** X.FCN CLREG	All	Clears all general purpose registers.
CLSTK	**0** **g** FILL	\α	Clears all stack registers.
	h P.FCN CLSTK		
CLx	**h** CLx	All	
	CPX **h** CLx	DECM	Clears both **X** and **Y**.
CLα	**f** CLα	All	Clears the alpha register like CLA in *HP-42S*.
CLΣ	**g** CLΣ	DECM	Clears all statistical sums.
COMB	**f** Cy,x	DECM	Returns the number of possible <u>sets</u> of y items taken x at a time. No item occurs more than once in a set, and different orders of the same x items are <u>not</u> counted separately. Formula: $C_{y,x} = \begin{pmatrix} y \\ x \end{pmatrix} = \dfrac{y!}{x! \cdot (y-x)!}$
CONJ	CPX X.FCN CONJ	DECM	Changes the sign of y.
CORR	**g** r	DECM	Returns the correlation coefficient for the current statistical data and curve fitting model.
COS	**f** COS	DECM	
COSH	**f** HYP COS		
COV	**h** STAT COV	DECM	Returns the population covariance for two data sets. It depends on the fit model selected. For LinF, it calculates $$COV_{xy} = \frac{1}{n^2}\left(n\sum x_i y_i - \sum x_i \sum y_i\right)$$
CUBE	**h** X.FCN CUBE	DECM	Returns x^3.
CUBERT	**h** X.FCN CUBERT	DECM	Returns $\sqrt[3]{x}$.
DATE	**h** X.FCN DATE	DECM	Recalls the date from the real time clock and displays it in the numeric section in the format selected. See D.MY, M.DY, and Y.MD. The function DATE in *HP-12C* corresponds to DAYS+ in WP 34S (see below).
DAY	**h** X.FCN DAY	DECM	Takes x as a date in the format selected and returns the name of the day in the dot matrix and a corresponding integer in the numeric display (Monday = 1, Sunday = 7).

Name	Keys to press	in modes	Remarks
DAYS+	**h** X.FCN DAYS+	DECM	Works like DATE in *HP-12C*, adding x days on a date in **Y** in the format selected and displaying the resulting date including the day of week in the same format as DAY does.
DBLR	**h** X.FCN DBLR	Integer	Double precision commands like in *HP-16C*.
DBL ×	**h** X.FCN DBL×		
DBL /	**h** X.FCN DBL/		
DEC	**h** P.FCN DEC ***r***	\α	Decrements ***r*** by one, equivalent to 1 STO– ***r*** , but without modifying the stack.
DECM	**f** H.d	\α	
DECOMP	**h** X.FCN DECOMP	FRC	Decomposes x (after converting it into an improper fraction, if applicable), resulting in a stack [***numerator(x), denominator(x), y, z***] or [***num(x), den(x), y, z, t, a, b, c***] , respectively. Reversible by division.
DEG	**g** DEG	DECM	Sets angular mode to degrees.
DENANY	**h** MODE DENANY	\α	Sets default fraction format like in *HP-35S*, allowing maximum precision. Any denominator up to the value set by DENMAX may appear.
DENFAC	**h** MODE DENFAC	\α	Sets "factors of the maximum denominator". With e.g. DENMAX = 60, possible denominators are 2, 3, 4, 5, 6, 10, 12, 15, 20, 30, and 60.
DENFIX	**h** MODE DENFIX	\α	Sets fixed denominator format, i.e. the denominator equaling DENMAX always.
DENMAX	**h** MODE DENMAX	\α	Works like /c in *HP-35S*, but maximum denominator settable is 9999. It will be set to this value if $x < 1$ or $x > 9999$ at execution time. For $x = 1$ the current setting is recalled.
DISP	**h** MODE DISP	DECM	Changes the number of decimals while keeping the display format (FIX, SCI, ENG) as is.
DROP	**h** P.FCN DROP	\α	Drops x , changing stack contents to [***y, z, t, t***] or [***y, z, t, a, b, c, d, d***] , respectively. See *above* for ^{C}DROP.
DSE	**f** DSE ***r***	PRG & DECM	Given ccccccc.fffii in ***r***, this function decrements ***r*** by ii, skipping next program line if then ccccccc ≤ fff .

Name	Keys to press	in modes	Remarks
DSZ	**h** (P.FCN) DSZ ***r***	PRG	Decrements ***r*** by one, skipping next program line if then $\|r\| < 1$.
D.MY	**h** (MODE) D.MY	\α	Sets the format for date display.
D→J	**h** (X.FCN) D→J	DECM	Takes x as a date in the format selected and converts it to a Julian day number.
D→R	**h** (X.FCN) D→R	DECM	Takes x as degrees and converts them to radians. Angular mode is kept.
E3OFF	**h** (MODE) E3OFF	\α	Toggle the thousands separator (either a point or a comma depending on the radix setting).
E3ON	**h** (MODE) E3ON		
ENG	**h** (ENG) ***n***	\α	Sets engineering display format.
ENGOVR	**h** (ENG) (.)	\α	Extension of ALL and FIX formats: numbers exceeding the range displayable in these formats will be shown in engineering format. See SCIOVR.
ENTER↑	(ENTER↑)	\α	See *above* for ᶜENTER.
erf	**h** (STAT) erf	DECM	Calculates the error function $$erf(x) = \frac{2}{\sqrt{\pi}} \int_0^x e^{-\tau^2} d\tau$$
EVEN?	**h** (TEST) EVEN?	\α	Checks if x is integer and even.
e^x	**f** (e^x)	DECM	
ExpF	**h** (STAT) ExpF	DECM	Selects the exponential curve fit model.
Expon			Exponential distribution with the rate λ specified in **J** :
Expon$_P$	**h** (PROB) Expon etc.	DECM	pdf: $f_{Ex}(x) = \lambda \cdot e^{-\lambda x}$ = EXPONDIST(x; λ; **0**), cdf: $F_{Ex}(x) = 1 - e^{-\lambda x}$ = EXPONDIST(x; λ; **1**) in MS Excel.
Expon^{-1}			
Expon←			Expon^{-1} returns the survival time t_s for a given probability F_{Ex} in **X** and rate λ in **J**.
e^x *-1*	**h** (X.FCN) e^X-1	DECM	Returns more accurate results for the fractional part of e^X with $x \approx 0$.
FB	**h** (X.FCN) FB ***n***	Integer	Inverts ("flips") the specified bit in x .

Name	Keys to press	in modes	Remarks
FC?			
FC?C	**h** TEST FC? _**n**_	\α	Tests the flag specified. Clears, flips, or sets this flag after testing, if applicable.
FC?F	etc.		
FC?S			
FF	**h** P.FCN FF _**n**_	\α	Flips the flag specified.
FIB	**h** X.FCN FIB	\α	Calculates the Fibonacci number F_x .
FILL	**g** FILL	\α	Copies x to all stack levels. See *above* for ^CFILL.
FIX	**h** FIX _**n**_	\α	Sets fixed point display format.
FLOOR	**h** X.FCN FLOOR	DECM	Returns the largest integer $\leq x$.
FP	**g** FP	DECM	Returns the fractional part of x .
FP?	**h** TEST FP?	\α	Tests x for having a nonzero fractional part.
FRACT	**h** P.FCN FRACT	DECM	Sets fraction mode like in HP-35S, but keeps display format as set by PROFRC or IMPFRC.
FS?			
FS?C	**h** TEST FS? _**n**_	\α	Tests the flag specified. Clears, flips, or sets this flag after testing, if applicable.
FS?F	etc.		
FS?S			
F(x)			F(x) equals 1 - Q(F) in *HP-21S*. The degrees of freedom are specified in **J** and **K**.
F ^{−1}(p)	**h** PROB F(x) etc.	DECM	
F←(x)			F(x)← equals Q(F) in *HP-21S* – see *above*.
f'(x)	**h** P.FCN f'(x) *label*	DECM	Return the first or second derivative of the function *f(x)* at position $x = x$, respectively, with *f(x)* being specified in a routine starting with LBL *label*. The return stack will have y, z, and t cleared and the position x in **L**.
f''(x)	**h** P.FCN f''(x) *label*		Either command will attempt to call a user routine labeled 'δx' to provide a fixed step size *dx*. If that routine is not defined, a step size of 0.1 is employed instead.

Name	Keys to press	in modes	Remarks
GCD	**h** (X.FCN) GCD	\α	Returns the Greatest Common Divisor of x and y.
Geom			Geometric distribution:
Geom$_P$	**h** (PROB) Geom etc.	DECM	pdf: $f_{Ge}(m) = p_0(1-p_0)^m$, cdf: $F_{Ge}(m) = 1-(1-p_0)^{m+1}$ is the probability for a first success after $m = x$ Bernoulli experiments. The probability p_0 for a success in each such experiment must be specified in **J**.
Geom $^{-1}$			
Geom←			Geom $^{-1}$ returns the number of failures f before the first success for given probabilities F_{Ge} in **X** and p_0 in **J**.
GRAD	**g** (GRAD)	DECM	Sets angular mode to gon or grads.
GTO	**h** (GTO) _**label**_	PRG	Inserts an unconditional branch to _**label**_.
		\PRG, \α	Positions the program pointer to _**label**_.
	h (GTO) (.) _**nnn**_	\α	… to line _**nnn**_ (not programmable).
	h (GTO) (.) (.)	\α	… to line 000 (not programmable) and lights the annunciator **BEG**.
H$_n$	**h** (X.FCN) H$_n$	DECM	Hermite's polynomials for probability: $H_n(x) = (-1)^n \cdot e^{x^2/2} \cdot \dfrac{d^n}{dx^n}\left(e^{-x^2/2}\right)$ with n in **Y**, solving the differential equation $$f''(x) - 2x \cdot f'(x) + 2n \cdot f(x) = 0 \ .$$
H$_{np}$	**h** (X.FCN) H$_{np}$	DECM	Hermite's polynomials for physics: $H_{np}(x) = (-1)^n \cdot e^{x^2} \cdot \dfrac{d^n}{dx^n}\left(e^{-x^2}\right)$ with n in **Y**.
H.MS	**f** (H.MS)	DECM	Assumes **X** containing decimal hours or degrees, and displays them in the format `hhhh°mm'ss.dd"` as shown _above_. Returns to the previous decimal display with the next keystroke thereafter.
H.MS+	**h** (P.FCN) H.MS+	DECM	Assumes **X** and **Y** containing times or degrees in the format `hhhh.mmssdd`, and adds or subtracts them, respectively.
H.MS−	**h** (P.FCN) H.MS−		

Name	Keys to press	in modes	Remarks
IMPFRC	**g** **d/c**	\α	Sets fraction mode allowing improper fractions in display (i.e. 5/3 instead of 1 2/3). Converts x according to the settings by DEN… Absolute decimal equivalents of x must be >1E-5 and <1E5. Compare PROFRC.
		FRC	Allows displaying improper fractions. Thus converts a proper fraction in **X** into the equivalent improper fraction, if applicable.
INC	**h** **P.FCN** INC *r*	\α	Increments *r* by one, equivalent to 1 STO+ *r* , but without modifying the stack.
INT?	**h** **TEST** INT?	\α	Tests x for being an integer, i.e. having a fractional part equal to zero. Compare FP?.
IP	**f** **IP**	DECM	Returns the integer part of x .
ISG	**g** **ISG** *r*	PRG & DECM	Given cccccc.fffii in *r*, this function increments *r* by ii, skipping next program line if then ccccccc > fff.
ISZ	**h** **P.FCN** ISZ *r*	PRG	Increments *r* by one, skipping next program line if then $|r| < 1$.
I β	**h** **X.FCN** Iβ	DECM	Returns the regularized incomplete beta function $\dfrac{\beta_x(x,y,z)}{\beta(y,z)} = \dfrac{1}{\beta(y,z)} \cdot \int_0^x t^{y-1}(1-t)^{z-1}\,dt$ with β_x being the incomplete beta function and β being Euler's beta (see below).
I Γ	**h** **X.FCN** IΓ	DECM	Returns the regularized incomplete gamma function $\dfrac{\gamma(x,y)}{\Gamma(x)}$ with $\gamma(x,y) = \int_0^y t^{x-1}e^{-t}\,dt$ being the lower incomplete gamma function. For Γ see below.
J→D	**h** **X.FCN** J→D	DECM	Takes x as a Julian day number and converts it to a date in the format selected.
LASTx	**RCL** **L**	\α	See *above* for ᶜLASTx .
LBL	**f** **LBL** *label*	PRG	Identifies programs and routines for execution and branching. See opportunities for specifying *label* in the table *above*.
LBL?	**h** **TEST** LBL? *label*	All	Tests for the existence of the label specified, anywhere in program memory. See opportunities for specifying *label* in the table *above*.

Name	Keys to press	in modes	Remarks
LCM	**h** $\boxed{\text{X.FCN}}$ LCM	\α	Returns the Least Common Multiple of x and y.
LEAP?	**h** $\boxed{\text{TEST}}$ LEAP?	DECM	Takes x as a date in the format selected, extracts the year, and tests for a leap year.
LgNrm			Lognormal distribution with $\mu = \ln \bar{x}_g$ specified in **J** and $\sigma = \ln \varepsilon$ in **K**. See x̄g and ε below.
LgNrm$_P$	**h** $\boxed{\text{PROB}}$ LgNrm etc.	DECM	pdf: $f_{Ln}(x) = \dfrac{1}{x\sigma\sqrt{2\pi}} e^{-\frac{(\ln x - \mu)^2}{2\sigma^2}}$,
LgNrm^{-1}			cdf: $F_{Ln}(x) = \Phi\left(\dfrac{\ln x - \mu}{\sigma}\right)$ with $\Phi(z)$ denoting the standard normal cdf.
LgNrm←			LgNrm^{-1} returns x for a given probability F_{Ln} in **X**, μ in **J**, and σ in **K**.
LinF	**h** $\boxed{\text{STAT}}$ LinF	DECM	Selects the linear curve fit model.
LJ	**h** $\boxed{\text{X.FCN}}$ LJ	Integer	
LN	**g** $\boxed{\text{LN}}$	DECM	
L$_n$	**h** $\boxed{\text{X.FCN}}$ L$_n$	DECM	Laguerre's polynomials (compare L$_n\alpha$ below): $L_n(x) = \dfrac{e^x}{n!} \cdot \dfrac{d^n}{dx^n}(x^n e^{-x}) = L_n^{(0)}(x)$ with n in **Y**, solving the differential equation $$x \cdot y'' + (1-x)y' + ny = 0 \ .$$
LN1+x	**h** $\boxed{\text{X.FCN}}$ LN1+x	DECM	Natural logarithm for values close to zero. Returns $\ln(1+x)$, providing a much higher accuracy in the fractional part of the result.
L$_n\alpha$	**h** $\boxed{\text{X.FCN}}$ L$_n\alpha$	DECM	Laguerre's generalized polynomials with n in **Y** and α in **Z**: $$L_n^{(\alpha)}(x) = \dfrac{x^{-\alpha} e^x}{n!} \cdot \dfrac{d^n}{dx^n}(x^{n+\alpha} e^{-x}) \ .$$
LN β	**h** $\boxed{\text{STAT}}$ LNβ	DECM	Returns the natural logarithm of Euler's β. See there. Also contained in the catalog X.FCN.
LN Γ	**h** $\boxed{\text{STAT}}$ LNΓ	DECM	Returns the natural logarithm of $\Gamma(x)$. See there. Also contained in the catalog X.FCN.
LOG$_{10}$	**g** $\boxed{\text{LG}}$	DECM	
LOG$_2$	**g** $\boxed{\text{LB}}$	\α	Calculates the logarithm of x for base 2.

Name	Keys to press	in modes	Remarks
LogF	**h** (STAT) LogF	DECM	Selects the logarithmic curve fit model.
Logis		DECM	Logistic distribution with μ given in **J** and s in **K** $$\text{pdf: } f_{Lg}(x) = e^{-\frac{x-\mu}{s}} \bigg/ s \cdot \left(1 + e^{-\frac{x-\mu}{s}}\right)^2,$$
Logis$_P$	**h** (PROB) Logis etc.		
Logis $^{-1}$			$$\text{cdf: } F_{Lg}(x) = \left(1 + e^{-\frac{x-\mu}{s}}\right)^{-1}$$ Logis $^{-1}$ returns $F_{Lg}^{-1}(p) = \mu + s \cdot \ln\left(\frac{p}{1-p}\right)$ for
Logis←			a probability p given in **X**, μ in **J**, and s in **K**.
LOGx	**g** (LOGx)	DECM	Calculates the logarithm of y for base x.
	(CPX) **g** (LOGx)	DECM	Calculates the complex logarithm of $z + i\,t$ for the complex base $x + i\,y$.
LZOFF	**h** (MODE) LZOFF	Integer	Toggles leading zeros like flag 3 does in *HP-16C*.
LZON	**h** (MODE) LZON	Integer	
L.R.	**h** (L.R.)	DECM	Calculates the parameters *a1* and *a0* of the fit curve through the data points accumulated, according to the model selected, and pushes them on the stack. For a straight regression line, *a0* is the y-intercept and *a1* the slope.
MASKL	**h** (X.FCN) MASKL *n*	Integer	Work like MASKL and MASKR on *HP-16C*, but with the mask length following the command instead of taken from **X**.
MASKR	**h** (X.FCN) MASKR *n*	Integer	
MAX	**h** (X.FCN) MAX	\α	Returns the maximum of x and y.
MIN	**h** (X.FCN) MIN	\α	Returns the minimum of x and y.
MIRROR	**h** (X.FCN) MIRROR	Integer	Reflects the bit pattern in x (e.g. 000101 becomes 101000 for word size 6).
MOD	**h** (MOD)	\α	MOD of *HP-42S* equals RMD of *HP-16C*.
M.DY	**h** (MODE) M.DY	\α	Sets the format for date display.
NAND	**h** (X.FCN) NAND	\α	Works in analogy to AND.
NaN?	**h** (TEST) NaN?	\α	Tests x for "Not a Number".
nBITS	**h** (X.FCN) nBITS	Integer	Counts bits set in x like #B does on *HP-16C*.

Name	Keys to press	in modes	Remarks
NOP	**h** **P.FCN** NOP	PRG	
NOR	**h** **X.FCN** NOR	\α	Works in analogy to AND.
Norml Norml$_P$ Norml^{-1} Norml←	**h** **PROB** Norml etc.	DECM	Normal distribution with an arbitrary mean **μ** specified in **J** and standard deviation **σ** in **K** : pdf: $f_N(x) = \dfrac{1}{\sigma\sqrt{2\pi}} e^{-\frac{(x-\mu)^2}{2\sigma^2}}$, cdf: $F_N(x) = \Phi\left(\dfrac{x-\mu}{\sigma}\right)$ with Φ denoting the standard normal distribution. The pdf equals NORMDIST(*x; μ; σ;* **0**) and the cdf NORMDIST(*x; μ; σ;* **1**) in MS Excel. Norml^{-1} returns **x** for a given probability F_N in **X**, mean **μ** in **J**, and standard deviation **σ** in **K**. Equals NORMINV(*F_N; μ; σ*) in MS Excel.
NOT	**h** **NOT**	\α	Works in analogy to AND.
nΣ	**h** **STAT** nΣ	DECM	Recalls the number of accumulated data points. Necessary for basic statistics.
ODD?	**h** **TEST** ODD?	\α	Checks if *x* is integer and odd.
OFF	**h** **P.FCN** OFF	PRG	
OR	**h** **OR**	\α	Works in analogy to AND.
PERM	**g** **Py,x**	DECM	Returns the number of possible <u>arrangements</u> of *y* items taken *x* at a time. No item occurs more than once in an arrangement, and different orders of the same *x* items <u>are</u> counted separately. Formula: $P_{y,x} = x! \cdot C_{y,x}$, see COMB.
P$_n$	**h** **X.FCN** P$_n$	DECM	Legendre's polynomials: $P_n(x) = \dfrac{1}{2^n n!} \cdot \dfrac{d^n}{dx^n}\left[\left(x^2-1\right)^n\right]$ with **n** in **Y**, solving the differential equation $\dfrac{d}{dx}\left[\left(1-x^2\right)\dfrac{d}{dx}f(x)\right] + n(n+1)f(x) = 0$.

Name	Keys to press	in modes	Remarks
Poiss Poiss$_P$ Poiss $^{-1}$ Poiss←	**h** PROB Poiss etc.	DECM	Poisson distribution with the number of successes **g** in **X**, the gross error probability **p₀** in **J**, and the sample size **n** in **K**. Alternatively, Poisson's parameter $\lambda = n \cdot p_0$ may be in **J** if **k** = 1: pmf: $P_P(g;\lambda) = \dfrac{\lambda^g}{g!} e^{-\lambda}$, cdf: $F_P(m;\lambda) = \sum_{g=0}^{m} P_P(g;\lambda)$, with the maximum number of successes **m** in **X**. The pdf equals POISSON(**g; λ; 0**) and the cdf POISSON(**g; λ; 1**) in MS Excel. Returns **m** for given probabilities **F$_P$** in **X** and **p** in **J** with sample size **n** in **K**.
PowerF	**h** STAT PowerF	DECM	Selects the power curve fit model.
PRIME?	**h** TEST PRIME?	\α	Checks if the absolute value of the integer part of **x** is a prime number. Exact for $x < 66049$, Miller-Rabin with 40 iterations otherwise, with the probability **P** for erroneously claiming a composite is prime being $P \approx 2^{-80} \approx 10^{-24}$.
PROFRC	**f** a b/c	DECM	Sets fraction mode like in *HP-35S*, allowing only proper fractions or mixed numbers in display. Converts **x** according to the settings by DEN… Absolute decimal equivalents of **x** must be >1E-5 and <1E5. Compare IMPFRC.
		FRC	Allows displaying only proper fractions. Thus converts an improper fraction in **X**, e.g. 5/3 into 1 2/3, if applicable.
PROMPT	**h** P.FCN PROMPT	PRG	Displays *alpha* and stops program execution (equaling αVIEW followed by STOP actually). If alpha input is requested for a program, use the sequence αON PROMPT αOFF. With a program running, enter the value or text requested and press R/S to continue.
PSE	**h** PSE *nn*	PRG	Pauses program execution for *nn* times 0.1s, with $0 \leq nn \leq 99$. Refreshes the display.
RAD	**g** RAD	DECM	Sets angular mode to radians.

Name	Keys to press	in modes	Remarks
RAN#	**f** RAN#	DECM	Returns a random number between 0 and 1 like RAN in *HP-42S*.
		Integer	Returns a random bit pattern for the word size set.
RCL	RCL *s*	\α	See the *addressing table above* for ^CRCL.
RCLM	RCL MODE	\α	Recalls selected mode settings into **X**. See the paragraph about *indicators* above.
RCLS	**h** P.FCN RCLS *s*	\α	Recalls 4 or 8 values from a set of registers starting at address *s*, and pushes them on the stack. This is the converse command of STOS.
RCL+	RCL + *s*	\α	Recalls the content of address *s*, executes the specified operation on it and pushes the result on the stack. E.g. RCL–12 recalls *r12*, subtracts *x* from it and displays the result. RCL↑ (↓) recalls the maximum (minimum) of the values in *s* and **X**. See the *addressing table above* for ^CRCL.
RCL–	RCL − *s*		
RCL×	RCL × *s*		
RCL/	RCL / *s*		
RCL↑	RCL ▲ *s*		
RCL↓	RCL ▼ *s*		
RDX, **RDX.**	**h** ./,	DECM	Toggle the radix mark. Also available in P.FCN FWIW.
RJ	**h** X.FCN RJ	Integer	Works in analogy to LJ.
RL	**h** X.FCN RL *n*	Integer	Works like *n* consecutive RLs / RLCs on *HP-16C*. For RL, 1 ≤ *n* ≤ 63. For RLC, 1 ≤ *n* ≤ 64. RL 0 and RLC 0 execute as NOP.
RLC	**h** X.FCN RLC *n*		
ROUND	**g** RND	DECM	Rounds *x* using the current display format, like RND in *HP-42S*.
		FRC	Rounds *x* using the current denominator, like RND in *HP-35S*.
ROUNDI	**h** X.FCN ROUNDI	DECM	Rounds *x* to next integer. ½ rounds to 1.
RR	**h** X.FCN RR *n*	Integer	Works like *n* consecutive RRs / RRCs on *HP-16C*. See RL / RLC for more.
RRC	**h** X.FCN RRC *n*		

Name	Keys to press	in modes	Remarks
RTN	**g** RTN	\PRG	Moves the program pointer to step 000.
		PRG	Last command in a routine. Returns control to the calling routine in program execution, i.e. moves the program pointer one step behind the most recent XEQ instruction encountered. If there is none, program execution halts.
R-CLR	**h** P.FCN R-CLR	DECM	Interprets x in the form `ss.nn`. Clears *nn* registers starting with number *ss*. E.g. for $x = 34.56$, R-CLR will clear **R34** through **R89**.
R-COPY	**h** P.FCN R-COPY	DECM	Interprets x in the form `ss.nndd`. Takes *nn* registers starting with number *ss* and copies their contents to *dd*. E.g. for $x = 7.0345678$, *r07, r08, r09* will be moved into **R45, R46, R47**, respectively.
R-SORT	**h** P.FCN R-SORT	DECM	Interprets x in the form `ss.nn`. Sorts the contents of *nn* registers starting with number *ss*. Assume $x = 49.026$, *r49* = 1.2, *r50* = –3.4; then R-SORT returns *r49* = –3.4, *r50* = 1.2.
R-SWAP	**h** P.FCN R-SWAP	DECM	Works like R-COPY but swaps the register contents of source and destination.
R→D	**h** X.FCN R→D	DECM	Takes x as radians and converts them to degrees. Angular mode is kept.
R↑	**h** R↑	\α	Rotates the stack contents one level up or down, respectively. See *above* for complex rotations.
R↓	R↓		
s	**g** s	DECM	Calculates the sample standard deviations s_y and s_x and pushes them on the stack.
SB	**h** X.FCN SB *n*	Integer	Sets the specified bit in x.
SCI	**h** SCI *n*	\α	Sets scientific display format.
SCIOVR	**h** SCI .	\α	Extension of ALL and FIX formats: numbers exceeding the range displayable in these formats will be shown in scientific format (default as in vintage HP calculators). See ENGOVR.
SEED	**h** STAT SEED	DECM	Stores a seed for random number generation.

Name	Keys to press	in modes	Remarks
SERR	**h** [STAT] SERR	DECM	Works like s but pushes the standard errors $s/\sqrt{n}$ on the stack (i.e. the standard deviations of x̄ and y).
SERRw	**h** [STAT] SERRw	DECM	Works like sw but returns the standard error $s/\sqrt{\sum y_i}$ (i.e. the standard deviation of x̄w).
SETDAT	**h** [X.FCN] SETDAT	DECM	Sets the date or time, respectively, for the real time clock (don't work with the emulator).
SETTIM	**h** [X.FCN] SETTIM		
SF	**h** [P.FCN] SF **n**	\α	Sets the flag specified.
SIGN	**h** [X.FCN] SIGN	\α	Returns 1 for $x > 0$, −1 for $x < 0$, and 0 for $x = 0$ or non-numbers.
	[CPX] [X.FCN] SIGN	DECM	Returns the unit vector of $x + i\,y$ in **X** and **Y**.
SIGNMT	**h** [MODE] SIGNMT	\α	Sets sign-and-mantissa mode for integers.
SIN	**f** [SIN]	DECM	
SINC	**h** [X.FCN] SINC	DECM	Returns $\dfrac{\sin x}{x}$.
SINH	**f** [HYP] [SIN]	DECM	
SL	**h** [X.FCN] SL **n**	Integer	Works like **n** (up to 63) consecutive SLs on *HP-16C*. SL 0 executes as NOP.
SLV	**f** [SLV] ***label***	DECM	Solves the equation $f(x) = 0$, with $f(x)$ calculated by the routine specified. Two initial estimates of the root must be supplied in **X** and **Y** when calling SLV. For the rest, the user interface is as in *HP-15C*.
SR	**h** [X.FCN] SR **n**	Integer	Works like **n** consecutive SRs on *HP-16C*. SR 0 executes as NOP.
SSIZE4	**h** [MODE] SSIZE4	\α	Set the stack size to 4 or 8 levels, respectively. If stack size grows, the top level contents will be copied into the new levels. If the stack shrinks, previous top levels will be lost. The same will happen if stack size is changed via STOM.
SSIZE8	**h** [MODE] SSIZE8		
SSIZE?	**h** [TEST] SSIZE?	\α	Returns the number of stack levels accessible.
STO	[STO] ***d***	\α	See the *addressing table above* for ^{C}STO.

Name	Keys to press	in modes	Remarks
STOM	[STO] [MODE]	\α	Sets selected modes as encoded in x. See the paragraph about *indicators* above.
STOP	[R/S]	PRG	Stops program execution.
STOS	[h] [P.FCN] STOS **d**	\α	Stores all stack levels in a set of 4 or 8 registers, starting at destination **d**.
STO+	[STO] [+] **d**	\α	Executes the specified operation on the content of address **d** and stores the result into said address.
STO–	[STO] [–] **d**		E.g. STO–12 subtracts x from **r12**, and stores the result in **R12** again. STO↑ (↓) takes the maximum (minimum) of the values in **d** and **X** and stores it.
STO×	[STO] [×] **d**		
STO/	[STO] [/] **d**		
STO↑	[STO] [▲] **d**		See the *addressing table above* for ^{C}STO.
STO↓	[STO] [▼] **d**		
SUM	[h] [STAT] SUM	DECM	Recalls the linear sums **Σy** and **Σx**. Useful for basic vector algebra.
sw	[h] [STAT] sw	DECM	Returns the standard deviation for weighted data $$s_w = +\sqrt{\frac{\sum y_i \cdot \sum\left(y_i \cdot x_i^2\right) - \left[\sum\left(y_i \cdot x_i\right)\right]^2}{\left(\sum y_i\right)^2 - \sum y_i^2}}$$
sxy	[h] [STAT] sxy	DECM	Returns the sample covariance for two data sets. It depends on the fit model selected. For LinF, it calculates $$s_{xy} = \frac{1}{n \cdot (n-1)}\left(n\sum x_i y_i - \sum x_i \sum y_i\right)$$
TAN	[f] [TAN]	DECM	
TANH	[f] [HYP] [TAN]		
TIME	[h] [TIME]	DECM, α	Recalls the time from the real time clock at execution and shows it in decimal mode.
T_n	[h] [X.FCN] T_n	DECM	Chebychev's (a.k.a. Tschebyschow) polynomials of first kind $T_n(x)$ with n in **Y**, solving the differential equation $$\left(1-x^2\right)y'' - x\cdot y' + n^2 y = 0.$$

Name	Keys to press	in modes	Remarks
TVM	**h** X.FCN TVM	DECM	Time Value of Money almost as known since the *HP-80*. Solves the equation $$PMT - \frac{I}{k} \cdot \left[PV + \frac{PV + FV}{(1+I)^n - 1} \right] = 0 \quad \text{with}$$ **PMT** = periodic payment = *r80*, **PV** = present value = *r81*, **FV** = future value = *r82*, **I** = interest rate per period = *r83*, **n** = number of periods = *r84*, **k** = 1 if payment is made at the end of the period = flag 80 clear, = 1 + **I** if it is made at the beginning of the period = flag 80 set. Store all you know and solve for the unknown. E.g. solving for **PMT** may look like: LBL 'PMT' ;routine is entered with SLV 'PM1' ;a first guess in **X**. NOP ;SLV acts as a test. RTN LBL 'PM1' STO 80 ;initial or previous guess TVM RTN See SLV for more.
t(x) t⁻¹(p) t←(x)	**h** PROB t(x) etc.	DECM	t(x) equals 1 – Q(t) in *HP-21S*. The degree of freedom is stored in **J**. t←(x) equals Q(t) in *HP-21S* – see *above*.
U_n	**h** X.FCN U_n	DECM	Chebychev's polynomials of second kind $U_n(x)$ with n in **Y**, solving the differential equation $$(1 - x^2)y'' - 3x \cdot y' + n(n+2)y = 0 .$$
UNSIGN	**h** MODE UNSIGN	\α	Sets unsigned mode for integers.
VIEW	**h** VIEW *s*	All	Displays the content of address *s* until the next key is pressed.
W *W⁻¹*	**h** X.FCN W **h** X.FCN W⁻¹	DECM	W returns Lambert's W for given $x \geq -1/e$, while W⁻¹ returns x for given W (≥ -1).

Name	Keys to press	in modes	Remarks
Weibl			Weibull distribution with the shape parameter **b** in **J** and the characteristic lifetime **T** in **K**:
Weibl$_P$	**h** PROB Weibl etc.	DECM	pdf: $f_W(t) = \dfrac{b}{T}\left(\dfrac{t}{T}\right)^{b-1} e^{-\left(\frac{t}{T}\right)^b}$, cdf: $F_W(t) = 1 - e^{-\left(\frac{t}{T}\right)^b}$. The pdf equals WEIBULL(**x; b; T; 0**) and the cdf WEIBULL(**x; b; T; 1**) in MS Excel.
Weibl $^{-1}$			
Weibl←			Weibl $^{-1}$ returns the survival time t_s for given probability F_W , **b** in **J** and **T** in **K**.
WSIZE	**h** MODE WSIZE **n**	\α	Works like WSIZE on *HP-16C*, but with the parameter following the command instead of taken from **X**. WSIZE 0 sets the word size to maximum, i.e. 64 bits.
WSIZE?	**h** TEST WSIZE?	\α	Recalls the word size set.
x^2	**g** x^2	\α	
XEQ	XEQ *label*	PRG	Calls the respective subroutine.
		\PRG, \α	Executes the respective program.
	B , **C** , or **D** (you may need **f** for accessing these hotkeys in integer bases >10.)	PRG	Calls the respective subroutine, so e.g. XEQ C will be inserted when **C** is pressed.
		\PRG, \α	Executes the respective program if defined.
XNOR	**h** X.FCN XNOR	\α	Works in analogy to AND.
XOR	**h** XOR	\α	Works in analogy to AND.
x̄	**f** x̄	DECM	Calculates the arithmetic means. Pushes $\dfrac{1}{n}\sum y$ and $\dfrac{1}{n}\sum x$ on the stack. See also s, SERR, and σ.
x̄g	**h** STAT x̄g	DECM	Calculates the geometric means. Pushes $\sqrt[n]{\prod y} = e^{\frac{1}{n}\sum \ln y}$ and $\sqrt[n]{\prod x}$ on the stack. See also ε, εg, and ε$_P$.
x̄w	**h** STAT x̄w	DECM	Calculates the weighted arithmetic mean $\sum xy \Big/ \sum y$. See also sw and SERRw.

Name	Keys to press	in modes	Remarks
x̂	**h** STAT x̂	DECM	Returns a forecast *x* for a given *y* (in **X**) following the fit model chosen. See L.R. for more.
x !	**h** !	DECM	
x → α	**g** x◀▶a	All	Interprets *x* as a code of up to 6 characters. Appends these characters to *alpha*, similar to XTOA in *HP-42S*.
x↔	**h** x⇄ *r*	\α	Swaps the contents of **X** and *r* . See *above* for complex x↔ .
x↔y	x⇄y	\α	Swaps *x* and *y* , performing Re↔Im if a complex operation was executed immediately before. See *above* for ^Cx↔y .
x < … ?	**h** TEST x < ? *a*		
x ≤ … ?	**h** TEST x ≤ ? *a*		Compare *x* with *a*. The three dots will be replaced in the listing by *a* according to the examples given in the *addressing table above*.
x = … ?	**f** x = ? *a*		x ≈ ? will be true if the rounded values of *x* and *a* are equal (see ROUND).
x ≈ … ?	**h** TEST x ≈ ? *a*	\α	
x ≠ … ?	**g** x ≠ ? *a*		CPX **f** x = ? *a* and CPX **g** x ≠ ? *a* compare the complex number *x* + *i y* as explained in the *addressing table above*.
x ≥ … ?	**h** TEST x ≥ ? *a*		
x > … ?	**h** TEST x > ? *a*		
y^x	**f** y^x	\α	In integer modes *x* must be ≥ 0.
	C	\(α, -3, -4, -5, h)	Shortcut working as long as label C is not defined yet.
ŷ	**f** ŷ	DECM	Returns a forecast *y* (in **X**) for a given *x* following the fit model chosen. See L.R. for more.
Y.MD	**h** MODE Y.MD	\α	Sets the format for date display.
αDATE	**h** X.FCN αDATE	\integer	Takes *x* as a date and appends it to *alpha* in the format set. See DATE. – To append a date stamp to *alpha*, call DATE αDATE.
αDAY	**h** X.FCN αDAY	\integer	Takes *x* as a date, recalls the name of the respective day and appends its first 3 letters to *alpha*.
αIP	**h** X.FCN αIP	All	Appends the integer part of *x* to *alpha*, similar to AIP in *HP-42S*.

Name	Keys to press	in modes	Remarks
αLENG	**h** (X.FCN) αLENG	All	Returns the number of characters found in *alpha*, like ALENG in *HP-42S*.
αMONTH	**h** (X.FCN) αMONTH	\integer	Works like αDAY, but processing the month.
αOFF	**h** (P.FCN) αOFF	PRG & α	Work like AOFF and AON in *HP-42S*, turning alpha mode off and on.
αON	**h** (P.FCN) αON	PRG & \α	
αRCL	**f** (RCL) *s*	α	Interprets the content of the source *s* as characters and appends them to *alpha*.
	h (X.FCN) αRCL *s*	\α	
αRC#	**h** (X.FCN) αRC# *s*	All	Takes the content of *s* as a number, converts it to a string in the format set, and appends this to *alpha*. If e.g. *s* = 1234 and ENG 2 and RDX**.** are set, then ‿1.23E3 will be appended.
αRL	**h** (X.FCN) αRL *n*	All	Rotates *alpha* by *n* characters like AROT in *HP-42S*, but with $n \geq 0$ and the parameter trailing the command instead of taken from **X**. αRL 0 executes as NOP.
αRR	**h** (X.FCN) αRR *n*	All	Works like αRL but rotates to the right.
αSL	**h** (X.FCN) αSL *n*	All	Shifts the *n* leftmost characters out of *alpha*, like ASHF in *HP-42S*. αSL 0 equals NOP.
αSR	**h** (X.FCN) αSR *n*	All	Works like αSL but takes the *n* rightmost characters instead.
αSTO	**f** (STO) *d*	α	Stores the first (i.e. leftmost) 6 characters in the alpha register into destination *d*.
	h (X.FCN) αSTO *d*	\α	
αTIME	**h** (X.FCN) αTIME	\integer	Takes *x* as a time and appends it to *alpha* in the format hh:mm:ss according to the time mode selected. See TIME. – To append a time stamp to *alpha*, call TIME αTIME.
αVIEW	**h** (X.FCN) αVIEW	\α	Displays *alpha*. In programs, use αVIEW followed by PSE for message output.
α → x	**f** (x◄►a)	All	Returns the character code of the leftmost character in *alpha* and deletes this character, like ATOX in *HP-42S*.

Name	Keys to press	in modes	Remarks
β	**h** **STAT** β	DECM	Returns Euler's Beta $B(x,y) = \dfrac{\Gamma(x) \cdot \Gamma(y)}{\Gamma(x+y)}$ with $\mathrm{Re}(x) > 0$, $\mathrm{Re}(y) > 0$. Called β here for avoiding ambiguities. Also contained in X.FCN.
Γ	**h** **STAT** Γ	DECM	Returns $\Gamma(x)$. This function is also contained in X.FCN. Additionally, **h** **!** calls $\Gamma(x+1)$.
ΔDAYS	**h** **X.FCN** ΔDAYS	DECM	Assumes **X** and **Y** containing dates in the format chosen and calculates the number of days between them. Works like in *HP-12C*.
Δ%	**f** **Δ%**	DECM	Calculates $100 \cdot \dfrac{x-y}{y}$ like %CH in *HP-42S*.
ε	**h** **STAT** ε	DECM	Calculates the scattering factors (or geometric standard deviations) $\ln(\varepsilon_y) = \sqrt{\dfrac{\sum \ln^2(y) - 2n \cdot \ln(\bar{y}_G)}{n-1}}$ and $\ln(\varepsilon_x)$ and pushes them on the stack. ε works for the geometric mean in analogy to s for the arithmetic mean but <u>multiplicative</u>.
εm	**h** **STAT** εm	DECM	Works like ε but pushes $\varepsilon_m = \varepsilon^{1/\sqrt{n}}$ on the stack (the scattering factors of the geometric means).
ε p	**h** **STAT** ε	DECM	Works like ε but with a denominator ***n*** instead of ***n − 1***, returning the scattering factors of the populations.
ζ	**h** **X.FCN** ζ	DECM	Returns Riemann's Zeta function $\zeta(x) = \sum_{n=1}^{\infty} \dfrac{1}{n^x}$ with $\mathrm{Re}(x) > 1$.
π	**h** **π**	DECM	Complex version copies π in **X** and clears **Y**.
Π	**f** **π** ***label***	DECM	Computes a product with the routine specified by ***label***. Initially, **X** contains the loop control number in the format `cccccc.fffii` and the product is set to 1. Each run through the routine specified computes a factor. At its end, this factor is multiplied with said product; the operation then decrements `ccccccc` by `ii` and runs said routine again if then `ccccccc` > `fff`, else returns the resulting product in **X**.

Name	Keys to press	in modes	Remarks
Σ	**g** **Σ** *label*	DECM	Computes a sum with the routine specified by *label*. Initially, X contains the loop control number in the format `cccccc.fffii` and the sum is set to 0. Each run through the routine specified computes a summand; at its end, this is added to said sum; the operation then decrements `ccccccc` by `ii` and runs said routine again if then `ccccccc > fff`, else returns the resulting sum in X.
σ	**h** **STAT** σ	DECM	Works like s but calculates the standard deviations of the populations instead.
$\Sigma\ln^2 x$ $\Sigma\ln^2 y$ $\Sigma\ln x$ $\Sigma\ln xy$ $\Sigma\ln y$ $\Sigma x\ln y$ $\Sigma y\ln x$	**h** **STAT** $\Sigma\ln^2 x$ etc.	DECM	Recall the respective statistical sums. These sums are necessary for curve fitting models beyond pure linear. Calling them by name enhances readability of programs significantly.
σw	**h** **STAT** σw	DECM	Works like sw but calculates the standard deviation of the population instead. $$\sigma_w = +\sqrt{\frac{\sum y_i (x_i - \bar{x}_w)^2}{\sum y_i}}$$
Σx Σx^2 $\Sigma x^2 y$ Σxy Σy Σy^2	**h** **STAT** Σx etc.	DECM	Recall the respective statistical sums. These sums are necessary for basic statistics and linear curve fitting. Calling them by name enhances readability of programs significantly.
Σ+	**A**	DECM	Shortcut as long as label A is not defined yet.
Σ+	**h** **Σ+**	DECM	
Σ−	**h** **Σ−**		

Name	Keys to press	in modes	Remarks
φ(x)	**h** **PROB** φ(x)	DECM	Standard normal pdf: $\varphi(x) = \dfrac{1}{\sqrt{2\pi}} e^{-x^2/2}$.
Φ(x)	**f** **Φ**	DECM	Standard normal cdf $\Phi(z) = \displaystyle\int_{-\infty}^{z} \varphi(x)\,dx$, equals $1 - Q$ in *HP-32E* and $1 - Q(z)$ in *HP-21S* with $z = x$.
Φ⁻¹(p)	**g** **Φ⁻¹**		
Φ←(x)	**h** **PROB** Φ←(x)		$\Phi(x)$← equals $Q(z)$ in *HP-21S* – see *above*.
χ^2		DECM	χ^2 (with the degrees of freedom given in **J**) equals $1 - Q(\chi^2)$ in *HP-21S*.
χ^2INV	**h** **PROB** χ^2 etc.		
χ^2←			χ^2← equals $Q(\chi^2)$ in *HP-21S* – see *above*.
$(-1)^X$	**h** **X.FCN** $(-1)^X$	DECM	
+	**+**		
−	**−**		
×	**×**	\α	
/	**/**		
//	**g** **//**	DECM	Calculates $\left(\dfrac{1}{x} + \dfrac{1}{y}\right)^{-1}$.
+/−	**+/_**	\α	
→DEG	**→** (**g**) **DEG**	DECM	Takes x as an angle in the angular mode set, converts it to degrees and changes angular mode in parallel. Prefix **g** may be omitted.
→GRAD	**→** (**g**) **GRAD**	DECM	Works like →DEG, but converts to grads.
→H	**→** **f** **H.d**	DECM	Takes x as hours or degrees in the format `hhhh.mmssdd` and converts them into a decimal time or angle.
→H.MS	**→** **f** **H.MS**	DECM	Takes x as decimal hours or degrees, converts them into `hhhh.mmssdd` and displays the result in the format `hhhh°mm'ss.dd"` as shown *above*. Returns to `hhhh.mmssdd` with the next keystroke.
→POL	**g** **R◀▶P**	DECM	Assumes **X** and **Y** containing 2D Cartesian coordinates (x , y) and converts them to the respective polar coordinates (r , ϑ) .

Name	Keys to press	in modes	Remarks
→RAD	➡ (g) RAD	DECM	Works like →DEG, but converts to radians.
→REC	f R◄►P	DECM	Assumes X and Y containing 2D polar coordinates (r, ϑ) and converts them to the respective Cartesian coordinates (x, y).
%	g %	DECM	Calculates $\dfrac{x \cdot y}{100}$.
%MG	h X.FCN h % MG	DECM	Calculates the margin [17] $100 \cdot \dfrac{x - y}{x}$ in % for a price x and cost y, like %MU-Price in *HP-17B*.
%MRR	h X.FCN h % MRR	DECM	Calculates the mean rate of return in % per period, i.e. $100 \cdot \left[\left(\dfrac{x}{y} \right)^{1/z} - 1 \right]$ with x = FV = future value after z periods, y = PV = present value. For $z = 1$, Δ% returns the same result easier.
%T	h X.FCN h % T	DECM	Calculates $100 \cdot \dfrac{x}{y}$, i.e. percent of total FWIW.
%Σ	h STAT h % Σ ─── h X.FCN h % Σ	DECM	Calculates $100 \cdot \dfrac{x}{\sum x}$.
%+MG	h X.FCN h % +MG	DECM	Calculates a sales price $y/(1 - 0.01 \cdot x)$ by adding a margin [17] of x % to the cost y, as %MU-Price does in *HP-17B*.
√	f √x̄	\α	
√	D	\(α, -4, -5, h)	Shortcut working as long as label D is not defined yet.
∫	g ∫ *label*	DECM	Integrates the function given in the routine specified. Lower and upper integration limits must be supplied in Y and X, respectively. Otherwise, the user interface is as in *HP-15C*.
∞?	h TEST ∞?	\α	Tests x for infinity.

---

[17] Margin corresponds to „Handelsspanne" in German.

Alphanumeric input:

Letter or digit	Keys to press	in modes	Remarks
°	[.]	DECM	Separates degrees or hours from minutes and seconds, so input format is hhhh.mmssdd. The user has to take care where an arbitrary real number represents such an angle or time.
0 … 9	[0] … [9]	\α	Standard numeric input. For integer bases <10, input of illegal digits throws an *error message*.
		in addressing	Register input. See the *addressing tables* above for more.
	[0], [1], f[2], … , f[9]	α	Appends the respective digit to *alpha*.
A … F	[A] … [F] (red print)	-1, -2, -3, -4, -5, h	Numeric input for digits >10. See page 6 for more information.
A … Z	[A] … [Z] (red print)	in addressing	Register input. See the *addressing tables* above for the letters applicable.
		α	Alphabetic input. See page 7 for more.
E	[E] (the key)	DECM	Like EEX in the older vintage calculators.
(or)	f ◄(/ g)►	α	Appends a left / right parenthesis to *alpha*.
[/]	Second [.]	DECM	A persistent 2nd [.] in input switches to fraction mode and will be interpreted as explained below. Please note you cannot enter [E] after you entered [.] twice – but you may delete the 2nd dot while editing the input line.
	f [.]	FRC	First [.] is interpreted as a space, 2nd as a fraction mark. E.g. input of [2][.][3][.][4] results in 2 ¾ in the display. Improper fractions may be entered starting with a [.] , e.g. [.][3][.][2] .
[,]	h [./,] [XEQ]	α	Appends a comma to *alpha*.
[.] or [,]	[.]	DECM	Inserts a radix mark as selected.

Non-programmable control, clearing and information commands:

Keys to press	in modes	Remarks
▲ / ▼	Status open	Goes to previous / next set of flags.
	Catalog open	Goes to previous / next item in this catalog.
	α	Scrolls the display window six characters to the left / right in *alpha* if possible. If less than six characters are beyond the limits of the display window on the left / right side, the window will be positioned to the beginning / end of string. Useful for longer strings.
	Else	Acts like BST / SST in *HP-42S*.
←	Input pending	Deletes the last digit or character put in.
	α	Deletes the rightmost character in *alpha*.
	PRG	Deletes current step.
	Else	Acts like CLx.
f ◄ / g ►	Integer	Shifts the display window to the left / right like in *HP-16C*. Helpful while working with small bases.
f ↑	α	Toggles upper and lower case.
h X.FCN CLALL	\PRG	Clears all registers and programs if confirmed.
h CLP	\α	Clears the current program (i.e. the one the program pointer is in) after confirmation.
ENTER↑	Catalog open	Selects the current item like XEQ below.
	α	Turns alpha mode off.
EXIT	Catalog open	Leaves the catalog without executing anything.
	Input pending	Cancels the execution of pending operations, returning to the calculator status as it was before.
	\PRG & program running	Stops this program like R/S below.
	PRG	Leaves programming mode like h P/R below.
	α	Turns alpha mode off like ENTER↑ above.
	Else	Does nothing.
g OFF	All	Turns calculator off.
ON	Calculator off	Turns calculator on.
h P/R	\PRG, \α	Toggle programming mode for keyboard entry.
	PRG	

Keys to press	in modes	Remarks
h **X.FCN** RESET	All	Executes CLALL and resets all modes to start-up default, i.e. 24h, 2COMPL, ALL, DEG, DENANY, DENMAX 9999, DECM, LinF, PROFRC, RDX., SCIOVR, SSIZE4, WSIZE 64, Y.MD.
R/S	\PRG, \α	Entered from the keyboard: Runs the current program starting with the current step or stops the running program immediately. Compare the programmable command STOP.
h **SHOW**	DECM & \PRG	Shows the full mantissa until the next key is pressed.
	PRG	Displays a CRC-32 checksum of program memory contents (8 hex digits), allowing validation of program integrity.
h **STATUS**	\PRG	Shows the status of all user flags, similar to STATUS on *HP-16C*. See *above*.
h **X.FCN** VERS	\PRG	Shows the firmware version.
XEQ	Catalog open	Selects the item currently displayed and exits, executing the respective command. See *above*.
f **α**	\α	Turns on alpha mode for keyboard entry. When entering alpha constants in programs, please note there is no concatenation character, since added characters are appended to *alpha* always. For starting a new string, use CLα first. Alpha constants will be listed like e.g. 'Test 1'.
→ **f** **2** **→** **f** **10** **→** (**g**) **16** **→** (**g**) **8**	\α	These commands show x in target integer representation until the next key is pressed. Base is kept as set. Prefix **g** may be omitted here. If used in integer bases 15 and 16, prefix **f** must precede the key **→**

Catalogs (not programmable):

Calling a catalog will set temporary alpha mode to allow for typing the first 1 or 2 characters of the item wanted. ▲ and ▼ browse the catalog, [XEQ] selects the item displayed and exits, while [EXIT] leaves the catalog without executing anything, returning to the mode as set before. See the *table above about addressing cataloged items*, and the *next paragraph* for detailed item lists.

Keys to press	in modes	Contents
h [CONST]	DECM	Constants like in HP35s. See them listed in a *table below*.
[CPX] [CONST]	DECM	This will clear **Y** in recalling the constant selected since they are all real.
h [CONV]	DECM	Conversions as listed in a *table below*.
f [CPX]	α	"Complex" letters mandatory for many languages. Upper or lower case will be displayed according to setting (see **f** ⬆ above).
h [MODE]	\α	Mode setting functions.
h [PROB]	DECM	Extra probability distributions.
h [P.FCN]	\α	Extra programming functions.
f [R↓]	α	Subscripts.
h [R↑]	α	Superscripts.
h [STAT]	DECM	Extra statistical functions.
h [TEST]	\α	All tests except the two on the keyboard.
h [TEST]	α	Comparison symbols and brackets. Parentheses are called by **f** [(] and **g** [)] , respectively.
h [X.FCN]	DECM	Extra real functions.
h [X.FCN]	Integer	Extra integer functions.
h [X.FCN]	α	Extra alpha functions.
[CPX] [X.FCN]	DECM	Extra complex functions.
h [./,]	α	Punctuation marks and text symbols.
f [→]	α	Arrows and mathematical symbols.

DETAILED CATALOG CONTENTS

The characters necessary to access a specific function from an arbitrary position in the respective catalog are printed bold in this table – ▼ has to be pressed once then for each character printed red – if even the last letter of a name is red, more strokes of ▼ may be needed. A single function, e.g. CB, may be contained in more than one catalog.

The alpha catalogs are found two pages below. See also CONST and CONV in separate paragraphs further below.

MODE
12h
1COMPL
24h
2COMPL
BASE
DENANY
DENFAC
DENFIX
DENMAX
DISP
D.MY
E3OFF
E3ON
LZOFF
LZON
M.DY
SIGNMT
SSIZE4
SSIZE8
UNSIGN
WSIZE
Y.MD

PROB	
Binom	**Lo**gis
Binom$_P$	**Log**is$_P$
Binom^{-1}	**Logi**s^{-1}
Binom←	**Logis**←
Cauch	**N**orml
Cauch$_P$	**No**rml$_P$
Cauch^{-1}	**Nor**ml^{-1}
Cauch←	**Norm**l←
Expon	**P**oiss
Expon$_P$	**Po**iss$_P$
Expon^{-1}	**Poi**ss^{-1}
Expon←	**Pois**s←
F(x)	**t**(x)
F←(x)	**t**$^{-1}$(p)
F^{-1}(p)	**T**←(x)
Geom	**W**eibl
Geom$_P$	**We**ibl$_P$
Geom^{-1}	**Wei**bl^{-1}
Geom←	**Weib**l←
Lgnrm	**φ**(x)
Lgnrm$_P$	**Φ**←(x)
Lgnrm^{-1}	χ^2
Lgnrm←	χ^2 INV
	χ^2 ←

STAT	
BestF	β
COV	Γ
erf	ε
ExpF	ε$_m$
LinF	ε$_p$
LNβ	σ
LNΓ	Σln^{2}x
LogF	Σln^{2}y
nΣ	Σlnx
PowerF	Σlnxy
SEED	Σlny
SERR	σw
SERRw	Σx
SUM	Σx^2
sw	Σx^{2}y
sxy	Σxlny
x̄g	Σxy
x̄w	Σy
x̂	Σy^2
	Σylnx
	%Σ

TEST
BC?
BS?
EVEN?
FC?
FC?C
FC?F
FC?S
FP?
FS?
FS?C
FS?F
FS?S
INT?
LBL?
LEAP?
NaN?
ODD?
PRIME?
SSIZE?
WSIZE?
x < ?
x ≤ ?
x ≈ ?
x ≥ ?
x > ?
∞?

P.FCN
CF
CLFLAG
CLSTK
DEC
DROP
DSZ
FF
FRACT
f '(x)
f "(x)
H.MS+
H.MS-
INC
ISZ
NOP
PROMPT
RCLM
RCLS
RDX,
RDX.
R-CLR
R-COPY
R-SORT
R-SWAP
SF
STOM
STOS
α OFF
α **O**N

… alpha mode:

- CLALL
- CLREG
- RESET
- VERS
- αDATE
- αDAY
- αIP
- αLENG
- αMONTH
- αRC#
- αRL
- αRR
- αSL
- αSR
- αTIME

… DECM:

ANGLE	RESET
B_n	ROUNDI
B_n*	R→D
CEIL	SETDAT
CLALL	SETTIM
CLREG	SIGN
CUBE	SINC
CUBERT	VERS
DATE	W
DAY	W^{-1}
DAYS+	XNOR
DECOMP	αDATE
D→J	αDAY
D→R	αIP
erf	αLENG
e^x -1	αMONTH
FIB	αRCL
FLOOR	αRC#
GCD	αRL
Iβ	αRR
IΓ	αSL
J→D	αSR
LCM	αSTO
LN1+x	αTIME
LNβ	αVIEW
LNΓ	β
MAX	Γ
MIN	ΔDAYS
NAND	ζ
NOR	$(-1)^X$

… integer modes:

ASR	RJ
CB	RL
CLALL	RLC
CLFLAG	RR
CLREG	RRC
DBLR	SB
DBL*	SEED
DBL/	SIGN
FB	SL
FIB	SR
GCD	VERS
LCM	XNOR
LJ	αIP
MASKL	αLENG
MASKR	αRCL
MAX	αRC#
MIN	αRL
MIRROR	αRR
NAND	αSL
nBITS	αSR
NOR	αSTO
RESET	αVIEW

%MG
%MRR
%T
%Σ
%+MG

CPX X.FCN:

- ^{c}CONJ
- ^{c}DROP
- $^c e^x$ -1
- ^{c}FIB
- ^{c}LN1+x
- ^{c}LNβ
- ^{c}LNΓ
- ^{c}SIGN
- ^{c}SINC
- ^{c}W
- $^c W^{-1}$
- ^{c}β
- ^{c}Γ

CPX					
À			à		
Á			á		
Â Ã Ā Ă			â ã ā ă		
Ä			ä (ă)		
Å			å		
Ć			ć		
Č			č		
Ç			ç		
È			è		
É			é		
Ê Ē Ĕ Ě			ê ē ĕ ě		
Ë			ë (ĕ)		
			ħ		
Ì			ì		
Í			í		
Î Ĩ Ī Ĭ			î ĩ ī ĭ		
Ï			ï (ĭ)		
Ñ Ň			ñ ň		
Ò			ò		
Ó			ó		
Ô Õ Ō Ŏ			ô õ ō ŏ		
Ö			ö (ŏ)		
Ø			ø		
Ř			ř		
Š			š		
			ß		
Ù			ù		
Ú			ú		
Û Ũ Ū Ŭ			û ũ ū ŭ		
Ü			ü (ŭ)		
Ů			ů		
Ý			ý		
Ÿ			ÿ		
Ž			ž		

Here are the contents of the alpha catalogs making the WP 34S the most versatile global calculator known. Large font is printed in left column or upper row, small font in right or lower. Accented letters show the same width as unaccented ones wherever possible.

./.
, ? : ; ‘ “ # * @ _ ~ `

TEST
< ≤ = ≈ ≥ > [ ] { }

→
→ ← ↑ ↓ ∫ ∞ ^

R↓ (subscripts)
0 1 2 A B c e k m n p u µ ∞

R↑ (superscripts)
c ° 2 X $\bar{x}$ $\hat{x}$ $\bar{y}$ $\hat{y}$ -1

The letters provided here allow for correct writing the languages of more than $3 \cdot 10^9$ people, i.e. Afrikaans, Català, Cebuano, Česky, Cymraeg, Deutsch, Eesti, English, Español, Euskara, Français, Gaeilge, Galego, Bahasa Indonesia, Italiano, Basa Jawa, Kiswahili, Kreyòl ayisyen, Magyar, Bahasa Melayu, Nederlands, Português, Quechua, Shqip, Slovenčina, Slovenščina, Basa Sunda, Suomeksi, Svenska, Tagalog, Winaray, Zhōngwén (with a little trick explained below), and almost Hrvatski and Srpski (sorry, no đ) as well as Dansk and Norsk (no æ). If you know further living languages covered, please tell us.

Mandarin Chinese (Zhōngwén) features four tones, usually transcribed like e.g. mā, má, mǎ, and mà. So you need different letters for ā and ă here, and for e, i, o, and u as well. With 6 pixels total character height we found no way to display these in both fonts nicely, keeping letters and accents separated for easy reading. For an unambiguous solution, we suggest using a dieresis (else not employed in Hànyǔ pīnyīn) representing the third tone here. Pinyin writers, we ask for your understanding.

CONSTANTS

This lists the contents of the catalog CONST. Values of physical constants (*incl. their relative standard deviations given in parentheses below*) are from CODATA 2006, copied in August 2010. Green background denotes exact or almost exact values. The more the color turns to red, the less precise the respective constant is known [18].

The characters necessary to get to a specific function in the catalog are printed bold in this index – ▼ has to be pressed once for each character printed red.

For the units, remember Tesla with $1T = 1\dfrac{Wb}{m^2} = 1\dfrac{V \cdot s}{m^2}$, Joule with $1J = 1N \cdot m = 1\dfrac{kg \cdot m^2}{s^2}$

and on the other hand $1J = 1W \cdot s = 1V \cdot A \cdot s = \dfrac{1}{e}eV \approx 6.24 \cdot 10^6 TeV$. Thus $1\dfrac{J}{T} = 1A \cdot m^2$.

	Numeric value	Unit	Remarks
a	365.2425	d	Gregorian year (per definition)
a$_0$	5.2917720859**E**-11 *(6.8**E**-10)*	m	Bohr radius $= \dfrac{\alpha}{4\pi \cdot R_\infty}$
c	2.99792458**E**8	m/s	Vacuum speed of light (per definition)
c$_1$	3.74177118**E**-16 *(5.0**E**-8)*	$m^2 \cdot W$	First radiation constant $= 2\pi \cdot h \cdot c^2$
c$_2$	0.014387752 *(1.7**E**-6)*	$m \cdot K$	Second radiation constant $= hc/k$
e	1.602176487**E**-19 *(2.5**E**-8)*	C	Electron charge $= \dfrac{2}{K_J R_K} = \Phi_0 G_0$
eE	2.718281828459045…	1	Euler's e. Please note the letter e is used for the electron charge elsewhere in this table.
F	96485.3399 *(2.5**E**-8)*	$\dfrac{C}{mol}$	Faraday's constant $= e\,N_A$
g	9.80665	m/s^2	Standard earth acceleration (per definition)
G	6.67428**E**-11 *(1.0**E**-4)*	$\dfrac{m^3}{kg \cdot s^2}$	Newton's gravitation constant
G$_o$	7.7480917004**E**-5 *(6.8**E**-10)*	$1/\Omega$	Conductance quantum $= 2e^2/h = 2/R_K$ with the von Klitzing constant $R_K = 25812.807557\ \Omega$

---

[18] The bracketed values printed here for your kind attention allow you to compute the precision of results you may obtain using these constants. The procedure to be employed is called error propagation. It is often ignored, though essential for trustworthy results – not only in science. Please turn to respective texts before you believe in 4 decimals of a calculation result based on yardstick measurements.

	Numeric value	Unit	Remarks
g_e	2.0023193043622 (7.4E-13)	1	Landé's g-factor
h	6.62606896E-34 (5.0E-8)	$J\,s$	Planck constant
$\hbar$	1.054571628E-34 (5.0E-8)		$= h/2\pi$
k	1.3806504E-23 (1.7E-6)	J/K	Boltzmann constant $= R/N_A$
m_e	9.10938215E-31 (5.0E-8)	kg	Electron mass
m_n	1.674927211E-27 (5.0E-8)		Neutron mass
m_p	1.672621637E-27 (5.0E-8)		Proton mass
m_u	1.660538782E-27 (5.0E-8)		Atomic unit mass $= 10^{-3}\,kg\,/\,N_A$
m_μ	1.88353103E-28 (5.6E-8)		Muon mass
N_A	6.02214179E23 (5.0E-8)	$1/mol$	Avogadro's number
NaN			"not a number"
p_o	101325	Pa	standard atmospheric pressure (per definition)
R	8.314472 (1.7E-6)	$\dfrac{J}{mol \cdot K}$	Molar gas constant
r_e	2.8179402894E-15 (2.1E-9)	m	Classical electron radius $= \alpha^2 \cdot a_0$
R_∞	1.0973731568527E7 (6.6E-12)	$1/m$	Rydberg constant $= \alpha^2 m_e c / 2h$
T_o	273.15	K	= 0°C, standard temperature (per definition)
t_p	5.39124E-44 (5.0E-5)	s	Planck time $= \sqrt{\hbar G/c^5}$
V_m	0.022413996 (1.7E-6)	m^3/mol	Molar volume of an ideal gas at standard conditions $= RT_0/p_0$
Z_o	376.730313461…	Ω	Characteristic impedance of vacuum $= \sqrt{\dfrac{\mu_0}{\varepsilon_0}} = \mu_0 c$
α	7.2973525376E-3 (6.8E-10)	1	Fine-structure constant $= \dfrac{e^2}{4\pi\varepsilon_0 \hbar c} \approx \dfrac{1}{137}$
γEM	0.57721566490153286…	1	Euler-Mascheroni constant

	Numeric value	Unit	Remarks
γ_p	2.675222099E8 *(2.6E-8)*	$\dfrac{1}{s \cdot T}$	Proton gyromagnetic ratio $= {2\mu_P}/{\hbar}$
ε_o	8.854187817…E-12	$\dfrac{A \cdot s}{V \cdot m}$ or F/m	Electric constant, vacuum permittivity $= \dfrac{1}{\mu_0 c^2}$
λ_c	2.4263102175E-12 *(1.4E-9)*		Compton wavelength of the electron $= h/{m_e c}$
λ_{cn}	1.3195908951E-15 *(1.5E-9)*	m	Compton wavelength of the neutron $= h/{m_n c}$
λ_{cp}	1.3214098446E-15 *(1.9E-9)*		Compton wavelength of the proton $= h/{m_p c}$
μ_o	1.2566370614…E-6	$\dfrac{V \cdot s}{A \cdot m}$	Magnetic constant, also known as vacuum permeability $= 4\pi \cdot 10^{-7} \dfrac{V \cdot s}{A \cdot m}$ (per definition)
μ_B	9.27400915E-24 *(2.5E-8)*		Bohr's magneton $= {e\hbar}/{2m_e}$
μ_e	-9.28476377E-24 *(2.5E-8)*		Electron magnetic moment
μ_n	-9.6623641E-27 *(2.4E-7)*	J/T or $A \cdot m^2$	Neutron magnetic moment
μ_p	1.410606662E-26 *(2.6E-8)*		Proton magnetic moment
μ_u	5.05078324E-27 *(2.5E-8)*		Nuclear magneton $= {e\hbar}/{2m_p}$
μ_μ	-4.49044786E-26 *(3.6E-8)*		Muon magnetic moment
π	3.141592653589793…	1	
σ_B	5.6704E-8 *(7.0E-6)*	$\dfrac{W}{m^2 K^4}$	Stefan Boltzmann constant $= \dfrac{2\pi^5 k^4}{15 h^3 c^2}$
Φ	1.61803398874989485…	1	Golden ratio $= \dfrac{1+\sqrt{5}}{2}$
Φ_o	2.067833667E-15 *(2.5E-8)*	$V\,s$	Magnetic flux quantum $= h/{2e} = 1/{K_J}$ with the Josephson constant $K_J = 4.83597891 \cdot 10^{14}\, Hz/V$
∞		1	Infinity (may the Lord of Mathematics forgive us calling this a constant)

UNIT CONVERSIONS

These are the contents of the catalog CONV [19]. The characters necessary to access a specific conversion there are printed bold in this index – ▼ has to be pressed once for each character printed red. The constant **T$_o$** may be useful for conversions, too; it is found in the *catalog CONST*. The conversion factors or divisors listed in this table will not be seen when executing a conversion.

Conversion		Remarks	Class
°C→°F	* 1.8 + 32	Exactly	Temperature
°F→°C	- 32) / 1.8	Exactly	Temperature
acres→ha	* 0.4046873	1 ha = 10^4 m²	Area
ar.→dB	10 * lg(R)	Amplitude ratio. Exactly	Ratio
atm→Pa	* 1.01325**E**5	Exactly	Pressure
AU→km	* 1.495979**E**8	Astronomic units	Length
bhp→W	* 745.6999	British horse power	Power
Btu→J	* 1055.056		Energy
cal→J	* 4.1868	Exactly	Energy
cft→*l*	* 28.31685	Cubic feet	Volume
cm→inches	/ 2.54	Exactly	Length
dB→ar.	$10^{R_{dB}/20}$	Amplitude ratio. Exactly	Ratio
dB→pr.	$10^{R_{dB}/10}$	Power ratio. Exactly	Ratio
fathom→m	* 1.8288		Length
feet→m	* 0.3048	Exactly	Length
flozUK→*ml*	* 28.41306	1 *ml* = 1 cm³	Volume
flozUS→*ml*	* 29.57353		Volume
galUK→ *l*	* 4.54609		Volume
galUS→ *l*	* 3.785418		Volume
g→oz	/ 28.34952		Mass
g→**t**r.oz	/ 31.10348		Mass
ha→acres	/ 0.4046873		Area

---

[19] For most readers, many of the units appearing here may look obsolete at least. They die hard, however, in some corners of this world. For symmetry reasons, we may also add some traditional Indian and Chinese units. Anyway, this catalog provides the means to convert local to common units.

Conversion		Remarks	Class
HP$_e$→W	* 746	Exactly	Power
inches→cm	* 2.54	Exactly	Length
inHg→Pa	* 3386.389		Pressure
J→Btu	/ 1055.056		Energy
J→cal	/ 4.1868	Exactly	Energy
J→**k**Wh	/ 3.6**E**6	Exactly, since 1 h = 3600 s	Energy
kg→lbm	/ 0.4535924		Mass
km→AU	/ 1.495979**E**8	Astronomic units	Length
km→*l.y.*	/ 9.460730**E**12	Light years	Length
km→**m**i	/ 1.609344	Exactly	Length
km→**nm**i	/ 1.852	Nautical miles, exactly	Length
km→**pc**	/ 3.085678**E**16	Parsec	Length
kWh→J	* 3.6E6	Exactly	Energy
lbf→N	* 4.448222		Force
lbm→kg	* 0.4535924		Mass
l.y.→km	* 9.460730**E**12	Light years	Length
l →cft	/ 28.31685	Cubic feet	Volume
l →**g**alUK	/ 4.54609		Volume
l →**ga**lUS	/ 3.785418		Volume
mbar→Pa	* 100	Exactly	Pressure
mi→km	* 1.609344	Exactly	Length
m*l*→flozUK	/ 28.41306		Volume
m*l*→flozUS	/ 29.57353		Volume
mmHg→Pa	* 133.3224	1 torr = 1 mm Hg	Pressure
m→fathom	/ 1.8288		Length
m→**f**eet	/ 0.3048	Exactly	Length
m→**y**ards	/ 0.9144	Exactly	Length
nmi→km	* 1.852	Nautical miles, exactly	Length
N→lbf	/ 4.448222		Force

Conversion		Remarks	Class
oz→g	* 28.34952		Mass
Pa→atm	/ 1.01325**E**5	Exactly	Pressure
Pa→inHg	/ 3386.389		Pressure
Pa→mbar	/ 100	Exactly	Pressure
Pa→mmHg	/ 133.3224		Pressure
Pa→psi	/ 6894.757		Pressure
Pa→torr	/ 133.3224		Pressure
pc→km	* 3.085678**E**16	Parsec	Length
pr.→dB	10 * lg(R)	Power ratio. Exactly	Ratio
psi→Pa	* 6894.757		Pressure
PS(hp)→W	* 735.4988		Power
s.tons→t	* 0.9071847	1 t = 10^3 kg	Mass
tons→t	* 1.016047		Mass
torr→Pa	* 133.3224	1 torr = 1 mm Hg	Pressure
tr.oz→g	* 31.10348		Mass
t→s.tons	/ 0.9071847		Mass
t→**t**ons	/ 1.016047		Mass
W→bhp	/ 745.6999		Power
W→HP$_e$	/ 746	Exactly	Power
W→**P**S(hp)	* 735.4988		Power
yards→m	* 0.9144	Exactly	Length

In cases of emergency of a particular type, remember that Becquerel equals Hertz, Gray is the unit for deposited or absorbed energy ($1Gy = 1J/kg$), and Sievert is Gray times a radiation dependant dose conversion factor for the damage caused in human bodies. In this area also some outdated units may be found in older literature: Pour les amis de Mme. Curie, $1Ci = 3.7 \cdot 10^{10} Bq = 3.7 \cdot 10^{10} decays/s$. And for those admiring the very first Nobel laureate in physics, Mr. Röntgen, for finding the x-rays (ruining his hands in these experiments), $1R = 2.58 \cdot 10^{-4} As/kg$.

MESSAGES

There are some commands generating messages also in the dot matrix section of the display. Four of them, DAY, DAYS+, STATUS, and VERS, were introduced above in the *paragraph about display* already. Others are PROMPT, αVIEW and many more alpha commands, and the test commands as mentioned *above*.

Two constants will return a special display when called: **NaN** and ∞ will show you

not nuMMEric	or	InF In ItY

, respectively.

Furthermore, there are a number of error messages. Depending on error conditions, the following messages will be displayed in the mode(s) listed:

Message	Error Code	Mode(s)	Explanation and Examples
bad date Error	2	DECM	Invalid date format or incorrect date in input, e.g. month >12, day >31 etc.
bad digit Error	9	Integer	Invalid digit in integer input, e.g. 2 in binary, 9 in octal, or +/- in unsigned mode.
bad mode Error	13	All	Caused by calling an operation in a mode where it is not defined, e.g. SIN in hexadecimal.
domain Error	1	\α	An argument exceeds the domain of the mathematical function called. May be caused by roots or logs of negative numbers (if not preceded by $\boxed{\text{CPX}}$), by $0/0$, LN(0), Γ(0), TAN(90°) and equivalents, ATANH(x) for $\lvert\mathrm{Re}(x)\rvert \geq 1$, ACOSH(x) for $\mathrm{Re}(x) < 1$, etc.
invalid PArAMEtEr	16	\α	Similar to error 1 but a parameter specified in **J** or **K** is out of supported range for the function called. May appear e.g. if Ln(x) is called with $j < 0$.
no such LAbEL	6	All	Attempt to address an undefined label.

Message	Error Code	Mode(s)	Explanation and Examples
out of range **Error** 360 RPN	8	All	• A number exceeds the valid range. Caused e.g. by specifying decimals >11, word size >64, negative flag numbers, integers $\geq 2^{64}$, hours or degrees >9000, invalid times, denominators ≥9999 etc. • A register address exceeds the valid range. May also happen in indirect addressing. • An R-operation (e.g. R-COPY) attempts exceeding valid register numbers (0 .. 99).
SLV ∫ Σ π **nEStEd** RAD STO RPN	7	PRG	Nested use of solve, integrate, sum or product is not allowed.
stack **CLASH** BEG 360 RPN	12	All	STOS or RCLS attempt using registers that would overlap the stack, e.g. SSIZE = 8 and STOS 94.
too few **dAtA PointS** BEG 360 RPN	15	DECM	A statistical calculation was started based on too few data points, e.g. regression or standard deviation for < 2 points.
too long **Error** 360 RPN	10	All	Keyboard input is too long for the buffer (should never happen, but who knows).
undefined **OP-COdE** STO 360 RPN	3	All	An instruction with an undefined op-code occurred (should never happen, but who knows).
word size **too SMALL** RPN h o	14	Integer, \PRG	Stack or register content is too big for the word size set.
+∞ **Error** 360 RPN	4	\α, \PRG	• Division of a number > 0 (or < 0) by zero. • Divergent sum or product or integral.
-∞ **Error** 360 RPN	5		• Positive (or negative) overflow in DECM (see *above*).
>8 levels **nEStEd** RAD STO RPN	11	PRG	Subroutine nesting exceeds 8 levels.

Any key pressed will erase the error message displayed and execute with the stack contents present. Thus, the easiest return to the display shown before the error occurred is pressing a prefix twice.

APPENDIX A: INTERNAL SUPPORT COMMANDS

Some commands are used in internal routines exclusively and are not accessible from the keyboard. They are listed here for sake of a complete documentation:

Name	Purpose and remarks
BACK *n*	Jumps *n* program steps backwards (1 ≤ *n* ≤ 99). So e.g. BACK 01 goes to the previous step. Reaching step 000 stops program execution.
ERR *n*	Raises the error specified. See *above* for the respective error codes.
iC *n*	Internal constants, selected by the number specified: 0 0 1 1 2 5.01402 Kronrod only weight loop initializer (constants 5 - 14 below) 3 15.02903 Gauss-Kronrod weight loop initializer (constants 15 - 29 below) Midpoint location is 0.5. 4 0.14944555400291690566493 6468389821 Kronrod weight for midpoint k10 5 0.99565716302580808073552 7280689003 Kronrod location of k0 and k20 6 0.01169463886737187427806 4396062192 Kronrod weight for k0 and k20 7 0.93015749135570822600120 7180059508 Kronrod location of k2 and k18 8 0.05475589657435199603138 1300244580 Kronrod weight for k2 and k18 9 0.78081772658641689706371 7578345042 Kronrod location of k4 and k16 10 0.09312545458369760553506 5465083366 Kronrod weight for k4 and k16 11 0.56275713466860468333900 0099272694 Kronrod location of k6 and k14 12 0.12349197626206585107795 8109831074 Kronrod weight for k6 and k14 13 0.29439286270146019813112 6603103866 Kronrod location of k8 and k12 14 0.14277593857706008079709 4273138717 Kronrod weight for k8 and k12 15 0.97390652851717172007796 4012084452 Location of g0, g9, k1 and k19 16 0.06667134430868813759356 8809893332 Gauss weight for g0 and g9 17 0.03255816230796472747881 8972459390 Kronrod weight for k1 and k19 18 0.86506336668898451073209 6688423493 Location of g1, g8, k3 and k17 19 0.14945134915058059314577 6339657697 Gauss weight for g1 and g8 20 0.07503967481091995276704 3140916190 Kronrod weight for k3 and k17 21 0.67940956829902440623432 7365114874 Location of g2, g7, k5 and k15 22 0.21908636251598204399553 4934228163 Gauss weight for g2 and g7 23 0.10938715880229764189921 0590325805 Kronrod weight for k5 and k15 24 0.43339539412924719079926 5943165784 Location of g3, g6, k7 and k13 25 0.26926671930999635509122 6921569469 Gauss weight for g3 and g6 26 0.13470921731147332592805 4001771707 Kronrod weight for k7 and k13 27 0.14887433898163121088482 6001129720 Location of g4, g5, k9 and k11 28 0.29552422471475287017389 2994651338 Gauss weight for g4 and g5 29 0.14773910490013384913748 41515972068 Kronrod weight for k9 and k11 Constants 2 .. 29 are for the 10 / 21 point Gauss-Kronrod quadrature used by the internal integration command. Locations are in the range (0, 1) which is scaled to match the interval of integration. The quadrature sums the weight times the function value at each location to estimate the integral. In Gauss-Kronrod schemes the Gauss points are common to both quadratures although the weights are different. This means two estimates of the integral can be performed without increasing the number of function evaluations which in turn allows an estimate of the error to be made. The cost for this is a reduction in the degree of polynomial function that is always integrated exactly.

Name	Purpose and remarks
RTN+1	Returns control to the calling routine like RTN does, but moves the program pointer to the <u>second</u> line following the most recent XEQ instruction encountered. If there is no matching XEQ, program execution halts.
SKIP **_n_**	Skips **_n_** program steps forwards (1 ≤ **_n_** ≤ 99). So e.g. SKIP 02 skips over the next two steps, going e.g. from step 123 to step 126. If the skip would land beyond the end of <u>occupied</u> program memory, the same will happen as if a RTN had been encountered.
	The two solver commands described below may use some hidden registers and flags. The start points of the respective register and flag blocks are passed as one argument **_n_**. Registers: **_n_**+0 .. **_n_**+1: first two estimates **_a_** and **_b_** for the root **_n_**+2: third estimate **_c_** **_n_**+3: function value at first estimate **f(_a_)** **_n_**+4: function value at second estimate **f(_b_)** Flags: **_n_**+0 **..** **_n_**+7: an eight bit iteration counter **_n_**+8: "bracket flag" – true if we've got an interval with **f(_a_)** * **f(_b_)** < 0 **_n_**+9: true if all function evaluations have been constant so far
SLVI **_n_**	Initializes the solver. SLVI clears the iteration counter, takes **_a_** and **_b_** and calculates **f(_a_)** and **f(_b_)**, sets the last two flags accordingly, and produces a guess **_c_**. There is no stack interaction.
SLVS **_n_**	Solver step. Updates the internal solver state based on the last function evaluation. In particular, SLVS takes **_a_**, **_b_**, **_c_**, **f(_a_)**, and **f(_b_)** from the register block plus **f(_c_)** from $\mathbf{X}$ and updates the register values so that **_c_** and **f(_c_)** replace one of **_a_** and **f(_a_)** or **_b_** and **f(_b_)**. It also produces a new guess **_c_** and returns zero in $\mathbf{X}$ if the solving should continue and non-zero if not. Otherwise, the stack isn't altered.
	The built in solver loop looks like this in principle, assuming **_n_** = _0_ : SLVI ; calculate **f(_a_)** and **f(_b_)** and initialize the registers and flags LBL 00 RCL 02 ; recall **_c_** XEQUSR ; call the user's subroutine calculating **f(_c_)** x≈ 0? ; test if the solution has converged GTO 01 ; converged, so exit SLVS ; update estimates x= 0? ; should we continue? GTO 00 ; loop back again LBL 01 RCL 02 ; best guess so far RTN The actual solver is fairly complex. A combination of quadratic interpolation and a guarded secant method is used.
SPEC?	Tests if x is special (i.e. NaN or infinite).
XEQUSR	Calls a user subroutine (used by SLV, ∫, Π and Σ). The subroutine is defined by the argument to the initial command (either numeric of alpha label).

APPENDIX B: CANDIDATES FOR FURTHER FUNCTIONS

If space allows, the following functions may be implemented easily since they are coded already. None of these are counting the catalog and function table overheads. Two bytes for a catalog entry (one for each catalog it is in) and 12-20 bytes for a function table entry (but only one of these), i.e. not terribly significant. These are all moderately useful functions.

Function name and remarks	Size	Domain
AGM = limit of arithmetic geometric mean.	528 B	$\mathbb{R}$

Bessel functions of first and second kinds:
    $\mathbf{J_n}$ & I_n: real and complex (argument and order);
    Y_n & K_n: real and complex (argument and order).
 	
 Remember: $J_n(x) = \sum_{r=0}^{\infty} \frac{(-1)^r \cdot \left(x/2\right)^{2r+n}}{r! \cdot \Gamma(n+r+1)}$
	4470 B	$\mathbb{R}, \mathbb{C}$

Digamma function (ψ, needed for Bessel functions of second kind of integer order)	1384 B	$\mathbb{R}, \mathbb{C}$

Fused multiply and add
    The real version can be replaced by complex multiply.
    x+y*z can be done via (y, x) * (z, -1) at a pinch.
	96 B	$\mathbb{Z}, \mathbb{R}$

Jacobi elliptic functions S_n, C_n & D_n	1780 B	$\mathbb{R}, \mathbb{C}$
x!!	288 B	$\mathbb{R}, \mathbb{C}$

PRIME? also includes overflow resistant code for *(a * b) mod c* and *(a ^ b) mod c* which could also be exposed if required.

APPENDIX C: RELEASE NOTES

	Date	Release notes
1	9.12.08	Start
1.1	15.12.08	Added the table of indicators; added NAND, NOR, XNOR, RCLWS, STOWS, //, N, SERR, SIGMA, < and >; deleted HR, INPUT, 2 flag commands, and 2 conversions; extended explanations for addressing and COMPLEX & …; put XOR on the keyboard; corrected errors.
1.2	4.1.09	Added ASRN, CBC?, CBS?, CCB, SCB, FLOAT, MIRROR, SLN, SRN, >BIN, >DEC, >HEX, >OCT, BETA, D>R, DATE, DDAYS, D.MY, M.DY, Y.MD, CEIL, FLOOR, DSZ, ISZ, D>R, R>D, EMGAM, GSB, LNBETA, LNGAMMA, MAX, MIN, NOP, REAL, RJ, W and WINV, ZETA, %+ and %-; renamed the top left keys B, C, and D, and bottom left EXIT.
1.3	17.1.09	Added AIP, ALENG, ARCL, AROT, ASHF, ASTO, ATOX, XTOA, AVIEW, CLA, PROMPT (all taken from 42S), CAPP, FC?C, FS?C, SGMNT, and the …# commands; renamed NBITS to BITS and STOWS to WSIZE; specified the bit commands closer; deleted the 4 carry bit operations.
1.4	10.2.09	Added CONST and a table of constants provided, D>J and J>D, LEAP?, %T, RCL and STO ▲ and ▼, and 2 forgotten statistics registers; deleted CHS, EMGAM, GSB, REAL and ZETA; purged and renamed the bit operations; renamed many commands.
1.5	5.3.09	Added RNDINT, CONV and its table, a memory table, the description of XEQ B, C, D to the operation index, and a and g_e to the table of constants; put CLSTK on a key, moved CLΣ and FILL, changed the % and log labels on the keyboard, put CLALL in X.FCN; checked and cleaned alpha mode keyboard and added a temporary alpha keyboard; rearranged the alphabet to put Greek after Latin, symbols after Greek consistently; separated the input and non-programmable commands; cleaned the addressing tables.
1.6	12.8.09	Added BASE, DAYS+, DROP, DROPY, E3OFF, E3ON, FC?F, FC?S, FIB, FS?F, FS?S, GCD, LCM, SETDAT, SETTIM, SET24, SINC, TIME, VERS, αDAY, αMONTH, αRC#, %Σ, as well as F-, t-, and χ^2-distributions and their inverses; reassigned DATE, modified DENMAX, FLOAT, αROT, and αSHIFT; deleted BASE arithmetic, BIN, DEC, HEX, and OCT; updated the alpha keyboards; added flags in the memory table; included indirect addressing for comparisons; added a paragraph about the display; updated the table of indicators; corrected errors.
1.7	9.9.09	Added P.FCN and STAT catalogs, 4 more conversions, 3 more flags, Greek character access, CLFLAG, DECOMP, DENANY, DENFAC, DENFIX, Iβ, IΓ, αDATE, αRL, αRR, αSL, αSR, αTIME, 12h, 24h, fraction mode limits, normal distribution and its inverse for arbitrary μ and σ, and Boolean operations working within FLOAT; deleted αROT, αSHIFT, the timer, and forced radians after inverse hyperbolics; renamed WINV to W $^{-1}$, and beta and gamma commands to Greek; added tables of catalog contents; modified label addressing; relabeled PRGM to P/R and PAUSE to PSE; swapped SHOW and PSE as well as Δ% and % on the keyboard; relabeled Q; corrected CEIL and FLOOR; updated X.FCN and alpha commands; updated the virtual alpha keyboard.
1.8	29.10.09	Added R-CLR, R-COPY, R-SORT, R-SWAP, RCLM, STOM, alpha catalogs, 1 more constant and some more conversions, a table of error messages, as well as the binomial, Poisson, geometric, Weibull and exponential distributions and their inverses; renamed some commands; put √‾ instead of π on hotkey D.
1.9	14.12.09	Added two complex comparisons; swapped and changed labels in the top three rows of keys, dropped CLST; completed function descriptions in the index.
1.10	19.1.10	Added IMPFRC, PROFRC, ^{C}ENTER, αBEG, αEND, and an addressing table for items in catalogs; updated temporary alpha mode, display and indicators, RCLM and STOM, alpha-commands and the message table; renamed the exponential distribution; wrote the introduction.
1.11	21.9.10	Changed keyboard layout to bring Π and Σ to the front, relabeled binary log, swapped the locations of π, CLPR, and STATUS, as well as SF and FS?; created a menu TEST for the comparisons removed and the other programmable tests from P.FCN; added %MG, %+MG, %MRR, RESET, SSIZE4, SSIZE8, SSIZE?, ^{C}DROP, ^{C}FILL, ^{C}R↓, ^{C}R↑, registers J and K, a table of contents and tables for stack mechanics and addressing in complex operations; updated memory and real number addressing tables, DECOMP, αOFF, αON, Π, and Σ; renamed ROUNDI, WSIZE?, β(x,y), Γ(x) and the constant p_0 ; deleted DROPY (use x↔y, DROP instead), αAPP, αBEG, αEND, and the "too long error" message; deleted Josephson and von Klitzing constants (they are just the inverses of other constants included in CONST already); brought more symbols on the alpha keyboard.
1.12	22.12.10	Modified keyboard layout; added catalogs MODE and PROB; changed mode word, catalog contents and handling (XEQ instead of ENTER), as well as some non-programmable info commands; expanded IMPFRC and PROFRC; added a paragraph about the fonts provided and explained alpha catalogs in detail; added PRIME? and some conversions; deleted FRACT, OFF and ON.
1.13	3.2.11	Modified keyboard layout; modified αTIME, radix setting, H.MS+ and H.MS-; added EVEN?, FP?, INT?, LZOFF, LZON, ODD?, RCLS, STOS, returned FRACT; added and renamed some conversions; updated the paragraph about display; added appendices A and B; baptized the device WP 34S.
1.14	18.3.11	Added DEC and INC, renamed FLOAT to DECM; redefined αTIME and H.MS mode; updated appendix A; documented the annunciators BEG and = as well as underflows and overflows in H.MS; corrected some errors showing up with the emulator.
1.15	21.3.11	Modified FIX, removed ALL from MODE, updated CONV.
1.16	27.3.11	Added LBL?, f'(x), and f''(x); modified PSE; upgraded catalog searching.

| 1.17 | ff | Modified keyboard layout for adding a fourth hotkey; added B_n, B_n*, Cauch, Lgnrm, Logis and their inverses, all the pdf, COV, CUBE, CUBERT, ENGOVR, SCIOVR, SERRw, sw, sxy, TVM, xg, ε, ε_m, ε_p, σw, $(-1)^X$, the polynomials, and three messages; renamed most cdf; deleted H.MS mode, %+ and %-; corrected errors. |