Answer Partitions~~and~~ , Oracle ~~Access Determine~~ Response Spectra, and Exact Quantum Query ~~Complexity~~Advantage

Karl Svozil *
Institute for Theoretical Physics, TU Wien, Wiedner Hauptstraße 8–10/136, 1040 Vienna, Austria
(Dated: November 4, 2026)

An ~~answer partition specifies which oracle~~ oracle problem pairs an answer partition, which says which hidden instances share an output, ~~while query complexity also depends on how those instances are accessed. We formulate exact~~ with an access model, which says what a query returns. We show that the access model changes exact quantum query complexity in ways that classical point values cannot detect. Exact one-query ~~answer-partition resolution as~~ resolution is block discrimination of ~~a unitary oracle family. Applied to Deutsch's problem with a controlled~~ the oracle family, and we state the criterion together with a dual certificate. For point access through a response unitary V, ~~the criterion shows that one query suffices~~ one query resolves a dictator exactly if and only if 0 lies in the convex hull of the spectrum of V, and a two-bit parity—including Deutsch's problem—if and only if -1 is an eigenvalue of V; ~~cyclic addition in odd response dimension therefore raises the exact quantum cost to twoqueries, matching the classical cost while preserving the same computational-basis point values~~no other task is one-query exact. Two reversible completions of the same blank-register table, a qutrit transposition and a cyclic shift, therefore have exact costs one and two, and a phase-dressed shift restores cost one; with bounded error the shift still succeeds with the optimal probability 7/8 after one query. A sign oracle cannot resolve any partition that separates a truth table from its complement, and an inaccessible witness of k address bits raises the quantum cost of Bernstein–Vazirani identification from one query to $\min\{k+1, n\}$ while leaving every classical value intact. Holding the standard ~~Boolean~~ point oracle fixed, we ~~further show that balanced answer partitions with equal-sized cells can have different exact classical and quantum query complexities . A complete exact classification is given for all~~ reorganize the known exact complexities of the 35 balanced three-bit partitions ~~, while the unresolved~~ and classify all 6435 balanced four-bit partitions exactly; rational dual certificates settle the 6040 four-bit cases ~~are reported explicitly as numerical candidates. These results separate the combinatorial specification of an answer from the oracle-dependent distinguishability that determines query complexity.~~ that previously had only numerical support.

~~An oracle problem pairs~~

I. INTRODUCTION

Deciding whether a one-bit function is constant or balanced takes one quantum query to the standard XOR oracle, against two classical queries [1–3]. A qutrit oracle that returns exactly the same classical values, the cyclic shift $y \mapsto y + b_x \bmod 3$, needs two quantum queries for an exact answer, whereas a qutrit transposition that agrees with it on a blank register needs only one (Sec. III). What decides the difference is the spectrum of the oracle's response, which no classical query can see.

Such examples are instances of a general fact. A query problem consists of an answer partition~~with an access model for the hidden instance. The partition groups~~ , which groups the hidden instances into cells whose members share the ~~same required answer. The access modeldetermines what information each query makes available~~required answer, and an access model, which says what each query returns, classically or quantum mechanically~~, and how that information can be processed. Quantum query speeduptherefore belongs to the~~ ; query complexity, and with it any quantum speedup, is a property of this task–oracle pair. ~~We make this viewpoint precise and then test it on standard point oracles, response-unitary variants, and small exhaustive families of balanced tasks.~~

~~This viewpoint also sharpens the usual intuition about quantum parallelism. A quantum query prepares one coherent state, and the algorithm succeeds when interference makes the states associated with different answer cells distinguishable. The useful resource is consequently the structure of the oracle response its phases, spectrum , accessible registers, and possible environment rather than simply the formal number of branches in a superposition. Rewriting an oracle by fixed basis changes preserves this discrimination, whereas changing its response representation, aggregating information, or discarding a witness can alter it [4]. The examples that follow develop these ideas through exact one-query discrimination , parity,~~ That it depends on the access model is known in general: simulating an in-place oracle for a permutation of N points can require $\Theta(\sqrt{N})$ uses of the standard oracle for the same function [5]; the comparison of quantum and classical oracle power depends on how the oracle is represented [4]; a richer classical oracle solves Deutsch's problem with one query [6]; and a faulty oracle

* karl.svozil@tuwien.ac.at

removes Grover's speedup [7].

Earlier work, including the author's, formulated quantum decision problems as partitions or identifications of prepared quantum states [8–13]. In the query model the partition lives instead on black-box transformations, and it must first be translated into orthogonal output sectors by the oracle and the protocol. This paper asks which features of the access, beyond the classical values it returns, decide the exact quantum cost of that translation.

The translation proceeds in four steps, used throughout the paper and listed in Sec. VI. First, the task fixes the answer partition: instances with the same correct answer share a cell, and only the cell must be learned. Second, the access model fixes what one oracle call does. Third, an instance-independent probe, typically a superposition fanned out from a single basis state, is sent through the oracle, which turns it into an output state that depends on the hidden instance. Fourth, one call solves the task exactly if and only if some probe makes the output states of different cells orthogonal; overlaps within a cell do no harm. In the example above, this orthogonality needs a relative factor -1 between interfering branches, which the flip and the transposition supply and the cyclic shift does not.

The main new result is a spectral criterion. For point access through a response unitary V, one query resolves a dictator exactly if and only if 0 lies in the convex hull of the spectrum of V, and a two-bit parity—including Deutsch's problem—if and only if -1 is an eigenvalue of V; no other task is one-query exact (Theorem 1 and Proposition 4). For the XOR oracle this reduces to the characterization of Chen, Ye, and Li [14]. Its consequences are that two reversible completions of the same blank-register table have different exact costs, that a phase invisible to basis queries can restore the advantage, and that an odd cyclic response keeps a bounded-error advantage although it loses the exact one (Sec. III). The second new result is an exact classification of all balanced four-bit tasks under the standard point oracle: rational dual certificates prove the two-query lower bounds that were previously supported only numerically [15] (Sec. IV). The remaining sections supply the framework—a block form of standard discrimination conditions, together with its dual (Sec. II)—and a decohered-access example in which an inaccessible address witness changes Bernstein–Vazirani costs while leaving every classical value intact (Sec. V). Table I separates prior results from the present additions.

These results also sharpen the usual intuition about quantum parallelism: the resource that matters for the separations below is the structure of the oracle response—its phases, spectrum, accessible registers, and environment—rather than the number of branches in a superposition.

II. ANSWER PARTITIONS AND EXACT ONE-QUERY RESOLUTION

Let Ω be a finite instance set and let $g : \Omega \to J$ specify the required answer. The task induces the *answer partition* ~~(also called here the kinematic partition)~~

$$\Pi_g = \{C_j : j \in g(\Omega)\}, \qquad C_j = g^{-1}(j). \tag{1}$$

This partition is indispensable bookkeeping, but it is not yet an access model or a complexity statement. In the query model the hidden instance labels a black-box transformation; the algorithm is not handed a state $|a\rangle$ on which the answer partition is a pre-existing observable. The operational question is whether the specified oracle and a fixed protocol can transfer the cell label to an accessible output.

~~More explicitly, let~~ Let $\rho_a^{(T)}$ be the ~~accessible state~~ state of the registers available to the final measurement, produced from instance a after T queries. Exact resolution means that there is one instance-independent measurement $\{P_j\}$ ~~satisfying~~

$$P_j P_\ell = \delta_{j\ell} P_j,\ \sum_j P_j = I,\ \mathrm{Tr}(P_{g(a)}\rho_a^{(T)}) = 1.$$

with

$$P_j P_\ell = \delta_{j\ell} P_j, \quad \sum_j P_j = I, \quad \mathrm{Tr}(P_{g(a)}\rho_a^{(T)}) = 1. \tag{2}$$

~~Consequently, supports~~ Supports belonging to different cells are then orthogonal; no orthogonality is required within a cell. The C_j ~~themselves~~ remain sets of classical instances. They are not subspaces, and the answer sectors $P_j\mathcal{H}_{\mathrm{out}}$ arise only after an oracle and a protocol have encoded them. The partition therefore specifies a required zero pattern in the output distinguishability matrix rather than a ready-made physical observable.

We ~~next characterize exact one-query resolution for a~~ write $Q_\epsilon(\Pi;\mathcal{U})$ and $R_\epsilon(\Pi;\mathcal{U}_{\mathrm{cl}})$ for the optimal quantum and classical worst-case numbers of calls needed with worst-case error at most ϵ, under explicitly matched access conventions, $Q_E \equiv Q_0$ for exact quantum complexity, and D for the depth of an optimal deterministic decision tree (the worst-case number of classical queries of an exact classical algorithm). In the worst-case convention used here $D = R_0$: fixing the random string of a zero-error randomized protocol that never exceeds T queries leaves a deterministic protocol that is correct on every instance with at most T queries. (If zero-error cost is instead measured in expectation, as is common, it can be smaller than D.) Classically, a deterministic protocol partitions Ω by its possible transcripts and succeeds exactly only when that transcript partition refines Π_g. A quantum protocol need not create such an intermediate classical transcript; it changes the overlaps among the hypothesis states and

TABLE I. Relation to prior work. "Known" lists results available before this paper; "This work" lists what is added here.

Topic	Known	This work
Exact one-query criterion	Perfect discrimination of unitaries [16, 17]	Block form for answer partitions and its dual certificate (Props. 1 and 2); standard convex duality, stated for use below
One-query exact class	XOR oracle: dictators and two-bit parities [14]; partial functions [18]	Every response unitary V: dictators iff $0 \in \operatorname{conv}(\operatorname{spec} V)$, ~~and a finite census of balanced partitions.~~ two-bit parities iff $-1 \in \operatorname{spec} V$, no other tasks (Thm. 1, Prop. 4)
Dependence on the oracle model	Oracle representation [4]; in-place versus standard oracles [5]; de-quantised Deutsch oracle [6]; faulty oracles [7]	Classically invisible spectrum decides exact cost: two completions of one blank-register table, phase-dressed shift (Cor. 1); elementary complement obstruction for sign oracles (Prop. 3)
Bounded error, odd cyclic response	—	Optimal unambiguous one-query solution, worst-case success $(3+\cos\frac{\pi}{d})/4$ (Prop. 5)
Parity	$Q_E(\mathrm{Par}_N) = \lceil N/2 \rceil$ [19, 20]	Degree bound for every response; open qutrit question (Sec. III)
Three-bit functions	Explicit optimal exact algorithms for all functions [15]	No new values; reorganization as balanced partitions (Table II)
Four-bit functions	Numerical SDP values for all functions [15], used in structural work [21]	Exact rational dual certificates for all 6435 balanced partitions (Table III)
Decohered access	Which-way information [22]; coherence in Bernstein–Vazirani [23]	Exact costs with an inaccessible witness: surviving partition in one query versus $n-k$; identification in exactly $\min\{k+1, n\}$ queries (Prop. 6)

measures only after the required cells have separated. A speedup is a gap between the quantum and the classical cost for the same task and the same interface.

All Hilbert spaces in this paper are finite dimensional. For a family of unitary oracles $\{U_a : a \in \Omega\}$. ~~An~~, an arbitrary one-query protocol ~~may prepare~~ prepares a pure state $|\Psi\rangle$ of the query system Q and a reference R, ~~apply~~ applies $U_a \otimes I_R$, and then ~~use~~ uses an instance-independent channel and measurement. Write

$$|\Psi_a\rangle = (U_a \otimes I_R)\,|\Psi\rangle\,, \qquad \sigma = \mathrm{Tr}_R\,|\Psi\rangle\langle\Psi|\,. \tag{3}$$

The output Gram matrix before the final processing is

$$G_{aa'} = \langle\Psi_a|\Psi_{a'}\rangle = \mathrm{Tr}\big(\sigma U_a^\dagger U_{a'}\big)\,. \tag{4}$$

. ~~*Proposition 1 (block discrimination).*~~

Proposition 1 (Block discrimination)**.** *The partition Π_g is exactly resolvable with at most one use of $\{U_a\}$, allowing an arbitrary reference, if and only if there is a density operator σ such that*

$$\mathrm{Tr}\big(\sigma U_a^\dagger U_{a'}\big) = 0 \quad \textit{whenever} \quad g(a) \neq g(a'). \tag{5}$$

~~*Indeed, exact*~~

Proof. Exact discrimination requires the spans of the output states associated with different cells to be orthogonal, which is equivalent to the vanishing of the indicated pairwise inner products~~vanishing~~; no instance-independent channel can make nonorthogonal states perfectly distinguishable. Conversely, orthogonal cell spans can be measured by their support projectors. Purification shows that optimizing over σ already includes mixed probes and arbitrary ancillary systems. □

Equation (5), with $\sigma \succeq 0$ and $\mathrm{Tr}\,\sigma = 1$, is the ~~direct block-discrimination form of standard perfect unitary-discrimination conditions~~ block form of the standard conditions for perfect discrimination of unitaries [16, 17]; it is not a new general channel-discrimination theorem. Its role here is to connect an answer partition to a specified oracle family. The Gram matrix need only be block diagonal according to Π_g; states within one cell may overlap or coincide. Complete identification is the singleton-cell special case, where G must be diagonal.

~~For~~ For every nontrivial partition, zero queries cannot resolve the task, so Eq. (5) characterizes $Q_E(\Pi_g; \mathcal{U}) = 1$. For bounded error, orthogonality is replaced by a com-

mon POVM with the required success probability. Multiquery lower bounds come from adversary methods [24], whose generalized form characterizes state conversion and function evaluation~~are characterized by adversary methods [25, 26]~~ [25, 26].

~~Write $Q_\epsilon(\Pi;\mathcal{U})$ and $R_\epsilon(\Pi;\mathcal{U}_{\mathrm{cl}})$ for the optimal quantum and classical worst-case numbers of calls needed with worst-case error at most ϵ, under explicitly matched access conventions, and write $Q_E \equiv Q_0$ for exact quantum complexity.Equation (5) characterizes exact resolvability with at most one oracle use, namely $Q_E(\Pi_g;\mathcal{U}) \le 1$. For every nontrivial partition, zero queries cannot resolve the task, so this is equivalent to $Q_E(\Pi_g;\mathcal{U}) = 1$; the trivial one-cell partition instead has $Q_E(\Pi_g;\mathcal{U}) = 0$. The criterion does not by itself establish an advantage. Speedup additionally requires a gap between Q_ϵ and R_ϵ for the same task and oracle interface. Classically, a deterministic query protocol partitions Ω by its possible transcripts and succeeds exactly only when that transcript partition refines Π_g. A quantum protocol need not create such an intermediate classical transcript; it changes the overlaps among the hypothesis states and measures only after the required cellshave separated. The relevant resource is this rate of separation, not the number of formal components in the probe superposition~~When Eq. (5) fails, a finite certificate says so.

Proposition 2 (Dual certificate)**.** *Let $X = \{(a,a') : g(a) \neq g(a')\}$. Exactly one of the following holds: (i) a density operator σ satisfies Eq. (5); (ii) there is a complex matrix Γ, supported on X and satisfying $\Gamma_{a'a} = \Gamma^*_{aa'}$, such that*

$$Z(\Gamma) = \sum_{(a,a')\in X} \Gamma_{aa'}\, U_a^\dagger U_{a'} \succ 0. \tag{6}$$

Proof. $Z(\Gamma)$ is Hermitian because $(U_a^\dagger U_{a'})^\dagger = U_{a'}^\dagger U_a$. If (i) and (ii) both held, then $\mathrm{Tr}[\sigma Z(\Gamma)] = 0$, contradicting $Z(\Gamma) \succ 0$. If (ii) fails, the real subspace $\{Z(\Gamma)\}$ of Hermitian operators misses the open convex cone of positive definite operators, so a separating hyperplane gives a nonzero σ with $\mathrm{Tr}(\sigma P) \ge 0$ for all $P \succ 0$, that is $\sigma \succeq 0$, and $\mathrm{Tr}[\sigma Z(\Gamma)] = 0$ for all admissible Γ. Taking Γ supported on a single pair (a,a') and its transpose, with real and with imaginary entries, gives $\mathrm{Tr}(\sigma U_a^\dagger U_{a'}) = 0$; normalizing σ gives (i). □

The matrix Γ weights only cross-cell pairs, as an adversary matrix does. After t queries the same weights define the progress measure $\sum_{(a,a')\in X} \Gamma_{aa'} \langle \psi_a^{(t)} | \psi_{a'}^{(t)} \rangle$ of the adversary method [24], and the query cost measures how fast such weighted cross-cell overlaps can be driven to zero. This is the precise sense in which a quantum query algorithm "separates" answer cells. When all $U_a^\dagger U_{a'}$ commute—as for every point oracle below, which is diagonal in the eigenbasis of its response—only the diagonal of σ in a common eigenbasis enters Eq. (5), and the criterion becomes a linear feasibility problem for a probability vector.

The criterion also distinguishes a change of representation from a change of access. If

$$V_a = A U_a B \tag{7}$$

for instance-independent unitaries A, B, then $V_a^\dagger V_{a'} = B^\dagger U_a^\dagger U_{a'} B$; as the probe varies, the attainable Gram matrices are unchanged. More generally, families that exactly simulate one another with $O(1)$ oracle calls have quantum query complexities equal up to constant factors; an approximate simulation must also charge its conversion error to ϵ. Preservation of a claimed quantum–classical gap additionally requires corresponding constant-query classical simulations. Exact one-query behavior can nevertheless change when the response representation is not of the form of Eq. (7)~~.~~, as the next section shows.

~~For example, Hadamard conjugation of the answer qubit turns Eq. (8) below into the full controlled-phase action $|x,z\rangle \mapsto (-1)^{z b_x} |x,z\rangle$, so the two forms are exactly equivalent. The restricted sign oracle $P_b|x\rangle = (-1)^{b_x}|x\rangle$ is only a subroutine: $P_{b\oplus 1} = -P_b$, and the complementary truth tables differ by a global phase. Supplying a coherent control for P_b restores the missing relative phase, but coherent control is additional black-box access rather than an automatic operation on an unknown unitary [27].~~

III. THE RESPONSE SPECTRUM DECIDES EXACT ONE-QUERY POWER

~~Deutsch's problem illustrates both the block criterion and this dependence.~~

A. Deutsch's problem and the sign oracle

Let $b = (b_0, b_1)$ be the truth table of a Boolean function and use

$$O_b |x,y\rangle = |x, y \oplus b_x\rangle\,. \tag{8}$$

With the answer qubit in $|-\rangle$, phase kickback gives, up to the common answer factor, the output states on the address register ~~:~~

$$|\psi_{00}\rangle = |+\rangle\,, \quad |\psi_{11}\rangle = -|+\rangle\,,$$
$$|\psi_{01}\rangle = |-\rangle\,, \quad |\psi_{10}\rangle = -|-\rangle\,.$$

$$|\psi_{00}\rangle = -|\psi_{11}\rangle = |+\rangle\,, \quad |\psi_{01}\rangle = -|\psi_{10}\rangle = |-\rangle\,. \tag{9}$$

~~Thus the~~ The constant and balanced cells occupy orthogonal rays, while the two instances inside either cell are not distinguished. This is ~~precisely~~ a block-diagonal, but not

diagonal, Gram matrix and gives the familiar ~~one versus two~~ one-versus-two exact-query separation ~~[1]~~[1–3].

~~The phenomenon is controlled by the response spectrum.~~ Hadamard conjugation of the answer qubit turns Eq. (8) into the controlled-phase action $|x,z\rangle \mapsto (-1)^{zb_x}|x,z\rangle$, so the two forms are exactly equivalent in the sense of Eq. (7). The restricted sign oracle $P_b|x\rangle = (-1)^{b_x}|x\rangle$, without the control qubit z, is weaker: $P_{\bar{b}} = -P_b$ for the complemented truth table $\bar{b}$, so complementary truth tables differ only by a global phase.

Proposition 3 (Complement obstruction). *With access to $\{P_b\}$ alone (arbitrary ancillas, but no control on P_b), a partition in which some b and its complement $\bar{b}$ lie in different cells cannot be resolved with any number of queries, even with error $\epsilon < 1/2$.*

Proof. Each use of $P_b \otimes I$ equals $-(P_{\bar{b}} \otimes I)$, and every branch of an adaptive protocol picks up the same sign. The final density operators for b and $\bar{b}$ are therefore identical, and so are the output distributions. □

Deutsch's constant–balanced partition is closed under complement and remains one-query resolvable with P_b. Three-bit majority, parity of an odd number of bits, and every other self-dual function are not resolvable at all. Among the balanced partitions studied in Sec. IV, only 3 of the 35 three-bit partitions (the two-bit parities) and 35 of the 6435 four-bit partitions are closed under complement; the sign oracle cannot resolve any of the others, whereas the XOR oracle resolves all of them with at most two ($N = 3$) or three ($N = 4$) queries. Supplying a coherent control for P_b restores the missing relative phase, but coherent control is additional black-box access rather than an automatic operation on an unknown unitary [27].

B. Response unitaries

Let V be any unitary and consider the controlled-response family indexed by the same four Boolean truth tables,

$$U_b^{(V)} = \sum_{x=0}^{1} |x\rangle\langle x| \otimes V^{b_x}. \tag{10}$$

. ~~*Theorem 1 (response spectrum).* The~~ *Access conventions.* The family $\{U_b^{(V)}\}$ is specified, and V is known. Between queries the algorithm may apply any instance-independent operation, including the preparation of eigenvectors of V, at no query cost; it may not control, invert, or otherwise modify the oracle unless such access is specified separately. The phase of V is part of the specification. Because V^{b_x} acts only on the branch selected by the address, replacing V by $e^{i\theta}V$ multiplies Eq. (10) by the instance-dependent phase $e^{i\theta b_x}$, which is relative between address sectors and therefore observable; it can change the spectral condition below (Corollary 1). This differs from access to an unspecified unitary or channel known only up to a global phase.

Theorem 1 (Response spectrum). *The Deutsch constant–balanced partition is exactly one-query resolvable through the family $\{U_b^{(V)}\}$, with arbitrary probes and references, if and only if -1 is an eigenvalue of V.*

~~For necessity, write the probe as $|0\rangle|\phi_0\rangle + |1\rangle|\phi_1\rangle$, with $|\phi_x\rangle$ on the response and reference systems. Let $\rho_x = \mathrm{Tr}_R |\phi_x\rangle\langle\phi_x| \succeq 0$ be its unnormalized response operator and put~~

$$p_x = \mathrm{Tr}\,\rho_x, \qquad z_x = \mathrm{Tr}(\rho_x V), \qquad p_0 + p_1 = 1.$$

~~The~~

Proof. If $V|w\rangle = -|w\rangle$, the probe $|+\rangle|w\rangle$ gives ordinary phase kickback and Eq. (9). Conversely, give weight $\Gamma = 1$ to the four cross-cell ~~orthogonality conditions include their complex conjugates and reduce to~~

$$z_0 = z_0^* = -p_1, \qquad z_1 = z_1^* = -p_0.$$

pairs (and their transposes) in Proposition 2. The pairs $(00,01)$, $(00,10)$, $(11,01)$, and $(11,10)$ contribute $I \oplus V$, $V \oplus I$, $V^\dagger \oplus I$, and $I \oplus V^\dagger$ on the address blocks $x = 0, 1$, so

$$Z = 2\,I_2 \otimes \left(2I + V + V^\dagger\right) = 2\,I_2 \otimes (I+V)(I+V)^\dagger. \tag{11}$$

~~Since $|z_x| \le p_x$, these equations force $p_0 = p_1 = 1/2$ and $z_0 = z_1 = -1/2$. Equality in the unitary expectation bound is possible only when the support of each nonzero ρ_x lies in the~~ Z is positive definite unless $I + V$ is singular, that is, unless -1 ~~eigenspace~~ is an eigenvalue of V. ~~Conversely, a -1 eigenvector provides ordinary phase kickback and Eq. (9).~~ □

Geometrically, the probe weights on the two address blocks define points of the numerical range $\mathrm{conv}(\mathrm{spec}\,V)$, and cross-cell orthogonality forces both points to -1. Because -1 is an extreme point of the unit disk, it lies in the numerical range only if it is an eigenvalue. Related qudit versions of Deutsch–Jozsa use higher-dimensional address and response systems ~~[28]. The theorem above~~ [2, 3, 28]. Theorem 1 instead holds the four Deutsch instances fixed and varies the response unitary. It is also distinct from prior-distribution "useless-query" bounds, which infer quantum lower bounds from classical queries that reveal no information about a property [29].

. ~~*Corollary 1 (cyclic response).* For the elementary cyclic response $X_d|y\rangle = |y+1 \bmod d\rangle$, $d \ge 2$,~~

Corollary 1 (Reversible completions). *On a qutrit, let T be the transposition $|0\rangle \leftrightarrow |1\rangle$ that fixes $|2\rangle$, let $X_3|y\rangle = |y+1 \bmod 3\rangle$ be the cyclic shift, and let*

$X_3' = e^{i\pi/3} X_3$. All three map the blank register $|0\rangle$ to $|1\rangle$ up to a phase ($X_3'|0\rangle = e^{i\pi/3}|1\rangle$), so a measurement of a blank target returns the point value b_x in each case; X_3 and X_3' moreover agree on every computational-basis ~~queries return the same Boolean point value for every d (by mapping $y \mapsto y + b_x \pmod d$)~~ input up to a phase. Their spectra are $\{1, 1, -1\}$, $\{1, e^{2\pi i/3}, e^{4\pi i/3}\}$, and $\{e^{i\pi/3}, -1, e^{-i\pi/3}\}$, so the exact quantum cost of Deutsch's problem is $Q_E = 1$, 2, and 1, respectively, while $D = 2$ in all three cases. More generally, for $X_d|y\rangle = |y+1 \bmod d\rangle$ with ~~$b_x \in \{0,1\}$), but -1 occurs in the spectrum of X_d exactly when d is even. Therefore~~ $d \geq 2$,

$$Q_E^{(d)} = \begin{cases} 1, & d \text{ even}, \\ 2, & d \text{ odd}, \end{cases} \qquad D^{(d)} = 2. \tag{12}$$

~~In particular, reversible qutrit addition removes~~

An oracle specified classically by its reversible action on a blank target, $|x\rangle|0\rangle \mapsto |x\rangle|b_x\rangle$, fixes only one column of each V^{b_x}. The completion—transposition or cyclic shift—decides whether Deutsch's exact ~~quantum advantage without changing its~~ advantage exists, and so does a phase that no computational basis query can see: the factor $e^{i\pi b_x/3}$ in $X_3'^{b_x}$ is a branch-relative phase, that is, a phase oracle composed with the shift. Thus classical point values, and even the full action on computational basis states up to phases, do not determine Q_E. This is a constant-factor effect, not an asymptotic separation~~, but it demonstrates that reversibility and blank-register behavior do not determine coherent query power~~.

~~Parity provides a broader illustration of the same principle under standard pointwise access.~~

C. All point oracles with a response unitary

The same argument applies to any number of bits. Let $f : \{0,1\}^N \to \{0,1\}$ be nonconstant and accessed through $U_b^{(V)} = \sum_{i=1}^N |i\rangle\langle i| \otimes V^{b_i}$.

Proposition 4 (One-query class). *A nonconstant f is exactly one-query resolvable through $\{U_b^{(V)}\}$ if and only if, up to negation, either $f = b_i$ and $0 \in \operatorname{conv}(\operatorname{spec} V)$, or $f = b_i \oplus b_j$ and $-1 \in \operatorname{spec} V$. The dictator condition holds in particular whenever $V|y\rangle \perp |y\rangle$ for some basis state $|y\rangle$.*

Proof. Let ~~$b \in \{0,1\}^N$ and $O_b|i,y\rangle = |i, y \oplus b_i\rangle$. Every~~ $\rho_i \succeq 0$ be the diagonal block of σ at address i and $p_i = \operatorname{Tr}\rho_i$, so $\sum_i p_i = 1$. Since $U_b^\dagger U_{b'} = \sum_i |i\rangle\langle i| \otimes V^{b_i' - b_i}$, only the ρ_i enter Eq. (5). If f depends on b_i, some b has $f(b) \neq f(b \oplus e_i)$, and Eq. (5) reads $1 - p_i + \operatorname{Tr}(\rho_i V^{\pm 1}) = 0$. Since $|\operatorname{Tr}(\rho_i V^{\pm 1})| \leq p_i$, this forces $p_i \geq 1/2$, so f depends on at most two bits. If it depends on two, i and j, then $p_i = p_j = 1/2$ and $\operatorname{Tr}(\rho_i V^{\pm 1}) = -p_i$, which places ρ_i and ρ_j in the -1 eigenspace of V. The overlap of the outputs for b and $b \oplus e_i \oplus e_j$ is then $-1 \neq 0$, so these instances share a cell, $f(b) = f(b \oplus e_i \oplus e_j)$, and f is $b_i \oplus b_j$ or its negation. A -1 eigenvector gives the Deutsch construction on addresses i, j. For a dictator b_i, the cross-cell pairs $(0^N, e_i)$ and $(0^N, e_i \oplus e_j)$, $j \neq i$, give $\operatorname{Tr}(\rho_i V) + \sum_{j \neq i} p_j = 0$ and $\operatorname{Tr}(\rho_j V) = p_j$, so the density operator $\tau = \sum_j \rho_j$ has $\operatorname{Tr}(\tau V) = 0$, that is, $0 \in \operatorname{conv}(\operatorname{spec} V)$. Conversely, the probe $|i\rangle|w\rangle$ with $\langle w|V|w\rangle = 0$ makes every cross-cell overlap vanish. With an additional null address, on which the oracle acts as the identity (as in the phase form used in Sec. IV), the same argument holds with $\operatorname{spec} V$ replaced by $\operatorname{spec} V \cup \{1\}$ in the dictator condition. □

For $V = -I$, the family is the sign oracle of Proposition 3: two-bit parities are one-query resolvable, whereas dictators are not resolvable at all.

For the XOR oracle, $V = X$, Proposition 4 reproduces the characterization of exact one-query algorithms by Chen, Ye, and Li [14]; partial functions are treated in Ref. [18]. For an odd cyclic response X_d the one-query class shrinks to the dictators, which a single basis query already resolves classically.

D. Bounded error for odd cyclic responses

Corollary 1 concerns exact resolution. With bounded error the odd cyclic response keeps a quantum advantage. As a referee pointed out, a single eigenvector of X_3 with eigenvalue $e^{2\pi i/3}$, the address in $|+\rangle$, and a measurement of the address in $\{|+\rangle, |-\rangle\}$ already give success 1 on constant and 3/4 on balanced instances, whereas one classical point query cannot exceed worst-case success 1/2. Spreading the probe over the two eigenvalues adjacent to -1 raises the worst case further and makes every conclusive answer correct.

Proposition 5 (Optimal one-query solution). *For odd $d \geq 3$, one query to $\{U_b^{(X_d)}\}$ solves Deutsch's problem with zero error and a conclusive answer with probability $(1 + \cos\frac{\pi}{d})/2$ on every instance. Guessing on the inconclusive outcome gives worst-case success $(3 + \cos\frac{\pi}{d})/4$, that is 3/4 conclusive and 7/8 overall for $d = 3$, and no one-query protocol does better. One classical query never gives a conclusive zero-error answer and has worst-case success 1/2.*

Proof. Let $|v_\pm\rangle$ be eigenvectors of X_d with the eigenvalues $\lambda_\pm = -e^{\pm i\pi/d}$ adjacent to -1, and use the probe $\frac{1}{2}\sum_{x=0}^{1}\sum_{\pm}|x\rangle|v_\pm\rangle$. Writing $\gamma = \cos\frac{\pi}{d}$ and using $(\lambda_+^k + \lambda_-^k)/2 = -\gamma$ for $k = \pm 1$, the output Gram matrix is $G_{bb'} = \frac{1}{2}\sum_x c_x$ with $c_x = 1$ if $b_x = b_x'$ and $c_x = -\gamma$ otherwise. Hence $|\psi_{00}\rangle + |\psi_{11}\rangle = |\psi_{01}\rangle + |\psi_{10}\rangle$, with squared norm $2(1-\gamma)$, while $|\psi_{00}\rangle - |\psi_{11}\rangle$ and $|\psi_{01}\rangle - |\psi_{10}\rangle$ are orthogonal to each other and to that

common vector, each with squared norm $2(1+\gamma)$. Projecting onto these three directions returns "constant," "balanced," or "inconclusive": each instance gives the correct conclusive outcome with probability $(1+\gamma)/2$ and never the wrong one.

For optimality, write any pure probe, including a reference~~system, can be written in the answer qubit's X basis as~~

$$|\Psi\rangle = \sum_{i=1}^{N} |i\rangle \left(|+\rangle\,|\alpha_i\rangle + |-\rangle\,|\beta_i\rangle\right), \qquad p_i = \|\beta_i\|^2.$$

~~The overlap between the outputs for 0^N and the odd string e_i is~~

$$\langle \Psi_{0^N} | \Psi_{e_i} \rangle = 1 - 2p_i.$$

~~Exact even-odd separation would require $p_i = 1/2$ for every i, while normalization gives $\sum_i p_i \le 1$. Hence one query is possible only for $N \le 2$,~~ as $|0\rangle|A\rangle + |1\rangle|B\rangle$ with ~~Deutsch as the limiting case. More generally,~~ $\|A\|^2 + \|B\|^2 = 1$, and put $W = V \otimes I_R$ with $V = X_d$. Let ρ_C and ρ_B be the ~~acceptance probability of a~~ outputs averaged uniformly over the constant and over the balanced instances. Their diagonal address blocks coincide, and their off-diagonal blocks differ by $\frac{1}{2}|(I-W)A\rangle\langle(I-W)B|$, so $\|\rho_C - \rho_B\|_1 = \|(I-W)A\|\,\|(I-W)B\| \le \frac{1}{2}\|I-V\|^2$. Worst-case success cannot exceed success under this prior, which by the Helstrom bound is at most $\frac{1}{2} + \frac{1}{8}\|I-V\|^2$. For odd d, $\|I - X_d\|^2 = 2 + 2\cos\frac{\pi}{d}$, which gives $(3 + \cos\frac{\pi}{d})/4$. Classically, one query reveals one bit b_x, and both cells remain consistent with every transcript. □

The bound $\frac{1}{2} + \frac{1}{8}\|I-V\|^2$ holds for every response V and reaches 1 only if $\|I-V\| = 2$, that is, only if -1 is an eigenvalue; this is a second proof of the necessity part of Theorem 1. The construction parallels Deutsch's original algorithm, which also answered conclusively only part of the time [1]; here the inconclusive probability $(1 - \cos\frac{\pi}{d})/2$ is set by the distance of the spectrum from -1 and vanishes as $d \to \infty$.

E. Parity

Proposition 4 shows that one query resolves the parity of N bits only for $N \le 2$. Proposition 2 gives an explicit witness for the XOR oracle: with $\Gamma = 1$ on the pairs $(0^N, e_i)$,

$$Z = \sum_{i=1}^{N} \left(O_{e_i} + O_{e_i}^{\dagger}\right) = 2N\,I - 4\Pi_{-}, \tag{13}$$

where $\Pi_{-} = \sum_i |i\rangle\langle i| \otimes |-\rangle\langle -|$; Z is positive definite exactly when $N > 2$. For more queries, note that $U_b^{(V)} = \sum_i |i\rangle\langle i| \otimes [I + b_i(V - I)]$ is affine in b for every response V. The amplitudes after T ~~query algorithm is a polynomial~~ queries are therefore polynomials of degree at most ~~$2T$~~ T in the input bits, ~~whereas~~ the acceptance probability has degree at most $2T$, and parity has exact degree N. Thus $T \ge N/2$ ~~, and~~ for every response, and for the XOR oracle applying the Deutsch construction to disjoint pairs gives the matching algorithm, so

$$Q_E(\mathrm{Par}_N) = \lceil N/2 \rceil, \qquad D(\mathrm{Par}_N) = N \tag{14}$$

for point-value access [19, 20]. ~~A binary partition can therefore remain query intensive.~~ For the qutrit shift X_3, Theorem 1 forbids the pair construction, and $\lceil N/2 \rceil \le Q_E(\mathrm{Par}_N; X_3) \le N$. Whether the upper bound is attained is open; if it is, two oracles with identical classical point values would differ by a factor of two for all N.

If instead one declares $\widetilde{O}_b\,|y\rangle = |y \oplus \mathrm{Par}(b)\rangle$ to be a single oracle call, parity becomes one-query resolvable classically as well as quantum mechanically. That does not ~~defeat~~ contradict Eq. (14); it replaces point access by an oracle that already aggregates the desired answer.

IV. EXACT CENSUS OF BALANCED POINT-ORACLE TASKS

The preceding examples ~~point to a common picture: the answer partition specifies the required outputs, whereas the query model determines the cost of separating its cells. We test this picture exhaustively for small point-oracle problems.~~ vary the access while holding the task fixed. We now hold the standard point oracle fixed and vary the task. Let the hidden instance be $b \in \{0,1\}^N$, accessed through Eq. (8) with the address range enlarged to N, and consider every binary answer map ~~having~~ with 2^{N-1} instances in each cell. Exchanging the answer labels gives the same unlabeled partition, so their number is

$$M_N = \frac{1}{2}\binom{2^N}{2^{N-1}}. \tag{15}$$

Coordinate permutations, independent complements of coordinates, and answer exchange preserve ~~the point-oracle query cost~~ both D and Q_E. They reduce the $M_3 = 35$ partitions to ~~six~~ 6 orbits and the $M_4 = 6435$ partitions to 58. Orbit sizes are restored when reporting the counts below.

~~For each partition we computed the optimal classic deterministic~~ *Methods*. The decision-tree depth D ~~and sought matching bounds on the exact quantum query complexity~~ was computed exactly by dynamic programming over subcubes. By Proposition 4 (Ref. [14]), $Q_E = 1$ holds exactly for dictators and two-bit parities. Upper bounds on Q_E ~~. One-query feasibility reduces, for the Boolean response, to rational Gram constraints and was solved over the rationals. Multiquery feasibility was~~

~~formulated with the Gram-matrix semidefinite program of Barnum, Saks, and Szegedy [30]. Constructive upper bounds were retained as~~ come from adaptive trees whose nodes read either one bit or the parity of two bits~~; the latter is one Deutsch query. Such trees are useful certificates , but they are~~, each costing one query; such trees are exact upper certificates but not a general characterization of exact quantum algorithms [15]. Lower bounds $Q_E \geq 3$ come from the two-query semidefinite program of Barnum, Saks, and Szegedy [30]. We use its bounded-error form, which is better conditioned than an exact feasibility test. In the phase form of the point oracle, $|i\rangle \mapsto (-1)^{b_i}|i\rangle$ with a null address $i = 0$ and $b_0 = 0$, put $D_i = \mathrm{diag}_b\big((-1)^{b_i}\big)$ (so $D_0 = I$). A two-query algorithm with worst-case success p yields positive semidefinite $2^N \times 2^N$ matrices with $\sum_i A_i = J$ (the all-ones matrix), $\sum_i D_i A_i D_i = \sum_i B_i$, $\sum_i D_i B_i D_i = \Gamma_0 + \Gamma_1$, and $(\Gamma_{f(b)})_{bb} \geq p$. If real symmetric Y_1, Y_2, Y_3 and a probability vector λ satisfy

$$Y_1 \succeq D_i Y_2 D_i, \quad Y_2 \succeq D_i Y_3 D_i \quad (i = 0, \ldots, N), \qquad Y_3 \succeq \Lambda_j \quad (j = 0, 1), \tag{16}$$

with $\Lambda_j = \mathrm{diag}_b\big(\lambda_b[f(b) = j]\big)$, then

$$\mathbf{1}^{\mathsf{T}} Y_1 \mathbf{1} = \textstyle\sum_i \langle Y_1, A_i\rangle \geq \langle Y_2, \sum_i B_i\rangle \geq \sum_j \langle Y_3, \Gamma_j\rangle \geq \sum_b \lambda_b (\Gamma_{f(b)})_{bb} \geq p, \tag{17}$$

so $\mathbf{1}^{\mathsf{T}} Y_1 \mathbf{1} < 1$ proves $Q_E \geq 3$. We solved Eq. (16) numerically with a barrier method, added 3ε, 2ε, and ε times the identity to Y_1, Y_2, and Y_3 with $\varepsilon = 2^{-20}$, which raises every constraint matrix in Eq. (16) by εI, rounded every entry to a dyadic rational with denominator 2^{40}, and verified all twelve matrix inequalities and $\lambda \geq 0$, $\sum_b \lambda_b = 1$ in exact integer arithmetic (positive pivots in Gaussian elimination). Each certificate is a list of integers, given in the Supplemental Material, and can be checked independently of the solver.

~~For $N = 3$ all lower and upper certificates meet exactly. Table II shows every orbit, rather than only aggregate counts~~ *Use of AI tools.* The census code and the Lean formalization were written with an OpenAI Codex assistant, and the dual-certificate solver and the exact verifier with Anthropic's Claude (versions are given in the Acknowledgments). No reported result rests on these tools alone: the census counts were reproduced by two independently written programs and agree with Ref. [15] , the Lean audits reproduce the finite census, and every certificate is checked by a verifier that uses only exact integer arithmetic and does not depend on the solver. ~~Here $\mathrm{Sel}(c, u, v) = u$ for $c = 0$ and v for $c = 1$.~~

Three bits. For $N = 3$ the one-query class and explicit trees meet for every task (Table II). These exact values are known: Montanaro, Jozsa, and Mitchison give optimal exact algorithms for every three-bit function [15] , and the contribution here is only their organization as balanced partitions. Thus 20 of the 35 balanced tasks admit an exact advantage: three by a factor of two and seventeen by a factor of 3/2. The ~~certificates also~~ trees display the conditional structure hidden by the bare partition. ~~For example, three-bit~~ Three-bit majority is decided by first obtaining $b_1 \oplus b_2$; if it is zero one reads b_1, and if it is one one reads b_3; this is the algorithm of Ref. [15], Sec. 6.2. Likewise, $F = b_1 \oplus b_2 b_3$ is decided by first reading b_2, followed by b_1 when $b_2 = 0$ and by the Deutsch parity $b_1 \oplus b_3$ when $b_2 = 1$. ~~Both real multilinear polynomials have degree three, so the polynomial method excludes one query and proves these two-query constructions optimal.~~

TABLE II. Balanced three-bit tasks up to coordinate permutations, input complements, and answer exchange. The orbit sizes sum to 35. Here $\mathrm{Sel}(c, u, v) = u$ for $c = 0$ and v for $c = 1$. The values of Q_E are not new: Ref. [15] gives explicit optimal exact algorithms for every function on up to three bits.

Representative	Orbit	D	Q_E
~~x_1~~ b_1	3	1	1
~~$x_1 \oplus x_2$~~ $b_1 \oplus b_2$	3	2	1
Par_3	1	3	2
Maj_3	4	3	2
~~$x_1 \oplus x_2 x_3$~~ $b_1 \oplus b_2 b_3$	12	3	2
~~$\mathrm{Sel}(x_1, x_2, x_3)$~~ $\mathrm{Sel}(b_1, b_2, b_3)$	12	2	2

Four bits. For $N = 4$ ~~, exact rational lower certificates and explicit trees settle~~ the one-query class and explicit two-query trees settle 15 orbits covering 395 partitions~~: 4, 6, 48, 248, and 89 have $(D, Q_E) = (1, 1), (2, 1), (2, 2), (3, 2)$, and $(4, 2)$, respectively. Of these, 343 have an exact advantage. For~~ . For each of the remaining 43 orbit representatives, covering 6040 partitions, ~~exact~~ explicit trees give $Q_E \leq 3$ ~~, while two SCS (Splitting Conic Solver) runs at requested tolerances 10^{-7} and 10^{-8} report the~~ and the exact rational certificates bound the optimal two-query ~~SDP infeasible. The resulting assignments, 1536 at $(D, Q_E) = (3, 3)$~~ worst-case success by values between 0.9001 and ~~4504 at $(4, 3)$, are therefore *numerical candidates*, not exact lower bounds. If accepted, they give candidate totals of 0.9862, hence~~ $Q_E = 3$. The classification of Table III is therefore exact: 4847 ~~speedup~~ balanced four-bit partitions have an exact quantum advantage (6 by a factor of two at $(2, 1)$, 89 by a factor of two at $(4, 2)$, 248 by a factor of 3/2, and 4504 by a factor of 4/3) and 1588 ~~no-speedup partitions. Exact dual certificates are required before these totals can be stated as theorems~~have none. The polynomial method could not have supplied the lower bounds for the 43 orbits: their real degrees are 3 (2144 partitions) or 4 (3896 partitions), so it yields only $Q_E \geq 2$.

Numerical SDP ~~studies of~~ values for all Boolean functions through four bits were ~~already~~ reported in Ref. [15], whose authors note that such values do not

TABLE III. Balanced four-bit tasks grouped by (D, Q_E). Orbits are taken up to coordinate permutations, input complements, and answer exchange; the columns sum to 58 orbits and 6435 partitions. The last column names the source of the lower bound on Q_E: Proposition 4 excludes one query, and the rational dual certificates of Eq. (16) exclude two.

(D, Q_E)	Orbits	Partitions	Representative	Lower bound
$(1,1)$	1	4	b_1	—
$(2,1)$	1	6	$b_1 \oplus b_2$	—
$(2,2)$	1	48	$\mathrm{Sel}(b_1, b_2, b_3)$	Prop. 4
$(3,2)$	8	248	$\mathrm{Maj}(b_1, b_2, b_3)$	Prop. 4
$(4,2)$	4	89	Par_4	Prop. 4
$(3,3)$	10	1536	$\mathrm{Sel}(b_1, b_2 b_3, b_2 \vee b_4)$	certificate
$(4,3)$	33	4504	$b_1 \oplus b_2 \oplus b_3 b_4$	certificate

by themselves certify exactness; subsequent structural work on exact two-query algorithms ~~also~~ uses that four-bit ~~numerical~~ classification [21]. We cross-validated our orbit representatives against the published NPN (~~Negation-Permutation-Negation~~negation–permutation–negation) identifiers of Ref. [15]. After removing dummy variables, its one- and two-query entries agree with all 15 representatives ~~certified here. For~~ settled by trees, and for the 43 remaining representatives ~~, its reported~~ its optimal two-query success probabilities~~lie~~ , between 0.900 and 0.986, ~~consistent with our infeasibility results but still numerical. This agreement checks the enumeration and symmetry bookkeeping; it does not manufacture an exact lower bound~~ agree with the optimal values 0.9000–0.9861 of our dual solutions. The certificates turn that numerical agreement into exact lower bounds, and the 15 orbits settled by trees give dual optimal value one, as they must.

Machine-checked companion. The Supplemental Material includes a Lean 4/mathlib formalization of the exact algebraic and finite core. Three `native_decide` audits reproduce the 35-task and 6435-task deterministic and restricted-tree censuses, including the 395 cases settled by trees; `native_decide` additionally trusts Lean's compiler and native evaluator through an extra axiom, which `#print axioms` reports. The 43 dual certificates are checked by a separate exact-arithmetic verifier, not yet in Lean. Density-operator semantics, unrestricted query semantics, and the general parity lower bound remain unformalized.

The ~~narrower~~ contribution of the census is ~~therefore to reorganize~~ to organize balanced functions as unlabeled answer partitions, quotient only by symmetries that preserve point access, ~~attach simple exact certificates where available, and keep numerical status explicit~~and attach a short exact certificate to every class. The observed proportions are finite-model facts, not an asymptotic speedup criterion.

~~Bernstein–Vazirani provides a complementary access-model example.~~

V. DECOHERED ACCESS: BERNSTEIN–VAZIRANI WITH AN INACCESSIBLE WITNESS

For $a, x \in \mathbb{F}_2^n$, let $f_a(x) = a \cdot x \pmod 2$ and $O_a |x, y\rangle = |x, y \oplus a \cdot x\rangle$. With ordinary phase access, the corresponding character states are orthogonal, so the singleton partition is resolved in one query [31]. We now add an inaccessible address record while preserving every computational-basis value returned by the oracle.

Choose $S \subseteq \{1, \dots, n\}$, $|S| = k$, ~~and~~ let x_S denote the corresponding substring, and let $\bar{S}$ be the complement of S. Consider the unitary dilation

$$W_a^S |x, y, e\rangle = |x, y \oplus a \cdot x, e \oplus x_S\rangle . \tag{18}$$

Each call receives a fresh witness in $|0^k\rangle$, which is discarded afterward. The accessible oracle is consequently the channel

$$\Phi_a^S(\rho) = \mathrm{Tr}_E\big[W_a^S(\rho \otimes |0^k\rangle\langle 0^k|)(W_a^S)^\dagger\big] .$$

$$\Phi_a^S(\rho) = \mathrm{Tr}_E\big[W_a^S(\rho \otimes |0^k\rangle\langle 0^k|)(W_a^S)^\dagger\big] = O_a\, \Delta_S(\rho)\, O_a^\dagger, \tag{19}$$

where $\Delta_S(\rho) = \sum_s \Pi_s \rho \Pi_s$ dephases the address register in the coordinates S (Π_s projects onto $x_S = s$); the second form holds because copying x_S into a discarded register is dephasing, and O_a commutes with every Π_s. Basis queries still return $a \cdot x$ exactly, while the witness ~~records selected address information and~~ removes coherences between sectors with different x_S, as in standard which-way interference [22] ~~. Define the surviving answer partition~~ and in the coherence analysis of the Bernstein–Vazirani algorithm [23].

Surviving partition. Define

$$\Pi_S = \{C_u : u \in \mathbb{F}_2^{n-k}\}, \qquad C_u = \{a : a_{\bar{S}} = u\}. \tag{20}$$

~~The one-query statement below concerns this surviving partition Π_S, whose cells are indexed by $a_{\bar{S}}$; it is therefore an access-induced change of the task oracle~~

~~pair rather than a same-partition comparison for the original singleton task.~~ For the classical comparison, let $\mathcal{O}^{\mathrm{val}} = \{O_a^{\mathrm{val}} : a \in \mathbb{F}_2^n\}$ denote the value-oracle family induced by computational-basis preparation and readout of Φ_a^S: a query chooses x and returns $a \cdot x$. For $k < n$ and worst-case error $\epsilon < 1/2$, these ~~explicitly specified quantum and classical~~ interfaces give

$$Q_\epsilon^\Phi(\Pi_S) = 1, \qquad R_\epsilon(\Pi_S; \mathcal{O}^{\mathrm{val}}) = n - k. \tag{21}$$

For the quantum part, the usual Bernstein–Vazirani input and phase kickback, followed by ~~tracing out the witness, leave~~ Eq. (19), leave on the n-qubit address register (after factoring out the answer qubit, which stays in $|-\rangle$) the state

$$\rho_a^S = 2^{-n} \sum_{x,x' :\, x_S = x'_S} (-1)^{a\cdot(x\oplus x')} \, |x\rangle\langle x'| \, . \tag{22}$$

Character orthogonality after the final Hadamards gives, up to a fixed reordering of coordinates,

$$\begin{aligned} H^{\otimes n} \rho_a^S H^{\otimes n} &= |a_{\bar S}\rangle\langle a_{\bar S}| \otimes \frac{I_S}{2^k}, \\ \Pr(z|a) &= 2^{-k}\, \mathbf{1}[z_{\bar S} = a_{\bar S}]. \end{aligned} \tag{23}$$

Thus ~~the one-query readout~~ one query exactly resolves Π_S~~. Zero queries cannot resolve this nontrivial partition Π_S~~; zero queries cannot, because the output would be independent of ~~its~~ the cell label. The classical upper bound uses the basis queries outside S. For the lower bound, impose the favorable promise $a_S = 0$. Under the uniform distribution on $a_{\bar S}$, fewer than $n-k$ returned linear equations leave an affine solution space of positive dimension, so even a decoder given the complete transcript succeeds with probability at most $1/2$. The same average bound holds after including the protocol's internal randomness, and therefore some input has success at most $1/2$. ~~If the witness were coherently available,~~

Original task. The same channel also changes the cost of the original singleton task, identification of a.

Proposition 6 (Witness cost of identification)**.** *For $0 \le k \le n$, with S known to the algorithm, the ~~fixed coupling $|x,e\rangle \mapsto |x, e\oplus x_S\rangle$ could be undone without another oracle call, restoring the ordinary~~ exact quantum cost of identifying a through $\{\Phi_a^S\}$ is $Q_E^\Phi(\Pi_{\mathrm{single}}) = \min\{k+1, n\}$; classically, $R_\epsilon(\Pi_{\mathrm{single}}; \mathcal{O}^{\mathrm{val}}) = n$ for $\epsilon < 1/2$.*

Proof. Upper bound: one Bernstein–Vazirani ~~output. The accessible oracle here is a channel rather than the globally unitary dilation, highlighting the distinction between standard and garbage-bearing oracle access in quantum query complexity [32].~~ query with $x_S = 0$ returns $a_{\bar S}$, and k basis queries $x = e_i$, $i \in S$, return a_S; alternatively, n basis queries return a. At $k = 0$ this is the ordinary one-query algorithm. Lower bound for $k \ge 1$: record each dephasing in Eq. (19) in an inaccessible environment register. For a record $\vec{s} = (s_1, \ldots, s_T)$, $s_t \in \mathbb{F}_2^k$, let $|\phi_a(\vec{s})\rangle$ be the conditional unnormalized output, so that $\rho_a = \sum_{\vec{s}} |\phi_a(\vec{s})\rangle\langle\phi_a(\vec{s})|$. Because the records are inaccessible, exact identification requires $\langle\phi_a(\vec{s})|\phi_{a'}(\vec{s})\rangle = 0$ for all $a \ne a'$ and all records $\vec{s}, \vec{s}'$. In the answer qubit's X basis, the tth query multiplies the component at address (s_t, z) either by 1 or by $(-1)^{a\cdot(s_t,z)}$. Hence $\phi_a(\vec{s})$ is a linear combination of characters $(-1)^{a\cdot f}$ whose frequencies are $f = 0$ or $f = \sum_{t\in F}(s_t, z_t)$ for nonempty subsets F of the queries. (i) If $s_1, \ldots, s_T$ do not span $\mathbb{F}_2^k$, choose $h \ne 0$ orthogonal to all s_t. Every such character is then invariant under $a \mapsto a + (h, 0)$, so $\phi_{a+(h,0)}(\vec{s}) = \phi_a(\vec{s})$, and orthogonality forces $\phi_a(\vec{s}) = 0$. Hence $T \ge k$, and only records whose s_t span $\mathbb{F}_2^k$ contribute. (ii) Let $T = k < n$. In every contributing record the s_t are linearly independent, so every frequency with $F \ne \emptyset$ has a nonzero S part, and for $u \ne 0$ the sum $\sum_a (-1)^{u\cdot a_{\bar S}} \phi_a(\vec{s})$ vanishes. Since the $\phi_a(\vec{s})$ are pairwise orthogonal, the squared norm of this sum is $\sum_a \|\phi_a(\vec{s})\|^2$, so $\phi_a(\vec{s}) = 0$ for every contributing record, contradicting normalization. Hence $T \ge k+1$ for $k < n$. The classical bound is the singleton case of the argument above. □

At $k = 0$, no address coordinate is recorded and Eq. (23) is the ordinary Bernstein–Vazirani output~~resolving the singleton partition~~, giving the n-versus-one identification gap. ~~At $k = n$, the stated interference readout is uniform and Π_S has only one cell~~Each recorded address bit adds exactly one query until the cost reaches the classical value n; from $k = n-1$ on, the quantum advantage for identification is gone, although ordinary basis queries ~~can~~ still recover a. ~~The model separates loss of the phase-interference route from loss of the classical function values themselves~~If the witness were coherently available, the fixed coupling $|x,e\rangle \mapsto |x, e\oplus x_S\rangle$ could be undone without another oracle call, restoring the ordinary output. The accessible oracle here is a channel rather than the globally unitary dilation: as with in-place versus standard oracles [5] and faulty oracles [7], whether the oracle leaves an inaccessible record is part of the problem specification.

~~We conclude by returning to the role of the answer partition. Equation (1)specifies which hidden instances share an answer , while the oracle and protocol provide the physical ingredients—the~~

VI. DISCUSSION

All results of this paper follow one strategy, which can be stated in four steps; the physics enters in the middle two.

- *Answer partition Π_g* [Eq. (1)]: Put two hidden instances in the same cell whenever the task has the same correct answer for both. The cells C_j are sets of classical instances, not subspaces. The algorithm must learn the cell, and only the cell: in Deutsch's

problem the four possible functions fall into two cells, constant and balanced, and the algorithm never has to find out which function within a cell it faces.

- *Oracle access* (Secs. III and V): Fix what one oracle call does. The partition fixes the correct answers to the question; the access model fixes how that answer can be obtained by quantum state discrimination.

- *Probe and one quantum oracle call* (Sec. II): Choose an instance-independent probe state, ~~oracle transformation, accessible output space, and measurement—that resolve the corresponding answer classes. Together, these ingredients determine how rapidly states from different cellsseparate~~for instance a uniform superposition obtained by "fanning out" a single basis state with Hadamard gates. One oracle call turns the probe into the output state $|\Psi_a\rangle$ of the hidden instance a.

- *Orthogonality across cells* (Proposition 1): Ask whether some probe makes $\langle\Psi_a|\Psi_{a'}\rangle = 0$ whenever $g(a) \neq g(a')$ [Eq. (5)]. A negative answer needs no search over the infinitely many probes: a single matrix, a dual certificate (Proposition 2), proves that none works. Only orthogonal states can be told apart with certainty, so exactness requires orthogonality, but only between cells. Within a cell, states may overlap or even coincide: the measurement reads the cell label, not the instance, as a post office sorts letters by postal code without reading the street.

Two equally weighted branches of a quantum state cancel, that is, interfere destructively, only if one carries an extra factor -1 relative to the other. In the examples of the Introduction, the standard flip on a qubit and the transposition on a qutrit both have the eigenvalue -1 and separate constant from balanced functions in one call; the qutrit cyclic shift, whose eigenvalues are the cube roots of unity, cannot (Theorem 1 and Corollary 1). With more calls, the same orthogonality is required of the final states, with instance-independent operations between the calls (Sec. IV); with bounded error, it is relaxed to a required success probability (Proposition 5).

The separations found here need not cross the stabilizer boundary. The standard Boolean Deutsch and linear Bernstein–Vazirani protocols, including their XOR oracles, use only Clifford operations, and the witness coupling in Eq. (18) is Clifford before the witness is discarded. They are therefore efficiently simulable when a full classical circuit description is supplied [33, 34]. In the query model, however, such a description would reveal hidden oracle data and is stronger than matched black-box value access. For these examples, nonstabilizer resources ("magic" [35]) are not needed for a query advantage. General point oracles with a binary-encoded address require multiply controlled gates and are not Clifford, so this remark is specific to Deutsch and Bernstein–Vazirani. ~~The response-spectrum theorem and the contrast between point and aggregate parity show how changing the access model can change this separation even when the abstract task remains fixed. Conversely, the finite~~

The results vary these steps one at a time. Theorem 1, Corollary 1, and Propositions 3–6 change the access (the second step) while holding the task and its classical point values fixed, and the exact cost changes. The census holds the point oracle fixed ~~while varying the balanced target. Its exact three-bit certificates show how quantum advantages can arise from oracle-accessible, conditionally composed refinements, while the four-bit calculation clearly separates exact certificates from numerical candidates.~~

and varies the balanced task (the first step), and the cost changes again, with every class certified exactly for $N \leq 4$. Shor's and Grover's algorithms [36, 37] fit the same ~~task–oracle perspective: Shor exploits periodic~~ perspective: each exploits structure in the oracle family ~~accessible via the quantum Fourier transform, while Grover exploits symmetry and coherent amplitude amplification via a matched phase oracle. These examples reinforce that quantum speedup depends on the structure of the oracle access, rather than on the coarseness or cardinality of the answer partition alone~~that is matched to a specific coherent access.

Partitions are therefore indispensable as specifications but insufficient as complexity criteria~~. Quantum advantage is not caused by partition coarseness or by simultaneous access to imagined branch values. It~~, and so are classical point values. A quantum advantage occurs when structure-matched interference separates the required answer cells in fewer calls than any classical transcript under the same interface. Superlinear exact separations for total Boolean functions are known [38], but establishing any asymptotic speedup requires a structured family of task–oracle pairs; percentages from a finite census cannot substitute for that analysis. Within the present framework, the parity question for the qutrit shift in Sec. III is a natural test of whether a response-spectrum effect persists uniformly in N.

ACKNOWLEDGMENTS

The author thanks Noson S. Yanofsky for discussions that motivated this work. ~~The author usedan OpenAI Codex language-model-based assistant for~~ Two AI assistants were used. OpenAI Codex ChatGPT Astra ultra supported structural editing, consistency checks, ~~and~~ the implementation of the ~~finite partition census ,~~ census code, and the Lean 4 formalization. Claude Opus 5.5 (Anthropic) was used in the revision to review the manuscript and the literature, to draft revised text—including the statements

and proofs of Propositions 2–6 and the new proof of Theorem 1—and to carry out the bounded-error and ~~accepts~~ dual-certificate computations of Secs. III and IV. The author directed both tools, checked the mathematical arguments, and verified the computations as described in Sec. IV; the author accepts full responsibility for the ~~final scientific content~~ content and code.

This research was funded in whole or in part by the Austrian Science Fund (FWF), grant PIN5424624. The author acknowledges TU Wien Bibliothek for support through its Open Access Funding Programme.

Data and code availability. ~~The source code, exact certificates~~ See Supplemental Material at [URL will be inserted by publisher] for the Python and Lean 4 sources, the proof report, the 43 rational dual certificates with an exact verifier, the census tables and witness files, ~~numerical witnesses, generated tables ,~~ and the ~~NPN~~ cross-validation ~~underlying the finite census are available at https://svozil.github.io/publications/2026-qc-partition-census-suppl~~ the published NPN data of Ref. [15].

[1] D. Deutsch, Quantum theory, the Church-Turing principle and the universal quantum computer, Proceedings of the Royal Society of London. Series A, Mathematical and Physical Sciences **400**, 97 (1985).

[2] D. Deutsch and R. Jozsa, Rapid solution of problems by quantum computation, Proceedings of the Royal Society of London. Series A: Mathematical and Physical Sciences **439**, 553 (1992).

[3] R. Cleve, A. Ekert, C. Macchiavello, and M. Mosca, Rapid solution of problems by quantum computation, Proceedings of the Royal Society A: Mathematical, Physical and Engineering Sciences **454**, 339 (1998).

[4] A. Wójcik and R. W. Chhajlany, Quantum-classical correspondence in the oracle model of computation, International Journal of Quantum Information **4**, 633 (2006), arXiv:quant-ph/0506248.

[5] E. Kashefi, A. Kent, V. Vedral, and K. Banaszek, Comparison of quantum oracles, Physical Review A **65**, 050304 (2002), quant-ph/0109104.

[6] C. S. Calude, De-quantizing the solution of Deutsch's problem, International Journal of Quantum Information **5**, 409 (2007), quant-ph/0610220.

[7] O. Regev and L. Schiff, Impossibility of a quantum speed-up with a faulty oracle, in *Automata, Languages and Programming, ICALP 2008*, Lecture Notes in Computer Science, Vol. 5125 (Springer, 2008) pp. 773–781, 1202.1027.

[8] N. Donath and K. Svozil, Finding a state among a complete set of orthogonal ones, Physical Review A **65**, 044302 (2002), arXiv:quant-ph/0105046.

[9] K. Svozil, Quantum information in base n defined by state partitions, Physical Review A **66**, 044306 (2002), arXiv:quant-ph/0205031.

[10] K. Svozil, Quantum information via state partitions and the context translation principle, Journal of Modern Optics **51**, 811 (2004), arXiv:quant-ph/0308110.

[11] K. Svozil, Characterization of quantum computable decision problems by state discrimination, in *Quantum theory: reconsideration of foundations—3*, AIP Conf. Proc., Vol. 810 (Amer. Inst. Phys., Melville, NY, 2006) pp. 271–279.

[12] K. Svozil and J. Tkadlec, On the solution of trivalent decision problems by quantum state identification, Natural Computing **8**, 539 (2009).

[13] K. Svozil, Orthogonal vector computations, Entropy **18**, 156 (2016), arXiv:1601.07106.

[14] W. Chen, Z. Ye, and L. Li, Characterization of exact one-query quantum algorithms, Physical Review A **101**, 022325 (2020), 1912.03493.

[15] A. Montanaro, R. Jozsa, and G. Mitchison, On exact quantum query complexity, Algorithmica **71**, 775 (2015), arXiv:1111.0475.

[16] A. Acín, Statistical distinguishability between unitary operations, Physical Review Letters **87**, 177901 (2001), arXiv:quant-ph/0102064.

[17] R. Duan, Y. Feng, and M. Ying, Perfect distinguishability of quantum operations, Physical Review Letters **103**, 210501 (2009), arXiv:0908.0119.

[18] Z. Ye and L. Li, Characterization of exact one-query quantum algorithms for partial Boolean functions, Journal of Computer Science and Technology **38**, 1423 (2023), 2008.11998.

[19] R. Beals, H. Buhrman, R. Cleve, M. Mosca, and R. de Wolf, Quantum lower bounds by polynomials, Journal of the ACM **48**, 778 (2001), arXiv:quant-ph/9802049.

[20] E. Farhi, J. Goldstone, S. Gutmann, and M. Sipser, Limit on the speed of quantum computation in determining parity, Physical Review Letters **81**, 5442 (1998), arXiv:quant-ph/9802045.

[21] S. Ye, W. Yang, and L. Huang, Characterization of exact two-query quantum algorithms, Information and Computation **298**, 105166 (2024).

[22] B.-G. Englert, Fringe visibility and which-way information: An inequality, Physical Review Letters **77**, 2154 (1996).

[23] M. Naseri, T. V. Kondra, S. Goswami, M. Fellous-Asiani, and A. Streltsov, Entanglement and coherence in the Bernstein–Vazirani algorithm, Physical Review A **106**, 062429 (2022).

[24] A. Ambainis, Quantum lower bounds by quantum arguments, Journal of Computer and System Sciences **64**, 750 (2002).

[25] T. Lee, R. Mittal, B. W. Reichardt, R. Špalek, and M. Szegedy, Quantum query complexity of state conversion, in *2011 IEEE 52nd Annual Symposium on Foundations of Computer Science* (IEEE, 2011) pp. 344–353.

[26] B. W. Reichardt, Span programs are equivalent to quantum query algorithms, SIAM Journal on Computing **43**, 1206 (2014).

[27] M. Araújo, A. Feix, F. Costa, and Č. Brukner, Quantum circuits cannot control unknown operations, New Journal of Physics **16**, 093026 (2014), arXiv:1309.7976.

[28] J. L. Cereceda, Generalization of the Deutsch algorithm using two qudits (2004), arXiv:quant-ph/0407253.

[29] D. A. Meyer and J. Pommersheim, On the uselessness of quantum queries, Theoretical Computer Science **412**, 7068 (2011), arXiv:1004.1434.

[30] H. Barnum, M. Saks, and M. Szegedy, Quantum query complexity and semi-definite programming, in *Proceedings of the 18th IEEE Conference on Computational Complexity* (IEEE Computer Society, 2003) pp. 179–193.

[31] E. Bernstein and U. Vazirani, Quantum complexity theory, SIAM Journal on Computing **26**, 1411 (1997), preliminary version in *Proceedings of the 25th Annual ACM Symposium on Theory of Computing* (STOC 1993), pp. 11–20.

[32] S. Aaronson, Open problems related to quantum query complexity, ACM Transactions on Quantum Computing **2**, 15 (2021), arXiv:2109.06917.

[33] D. Gottesman, The Heisenberg representation of quantum computers, in *Group22: Proceedings of the XXII International Colloquium on Group Theoretical Methods in Physics*, edited by S. P. Corney, R. Delbourgo, and P. D. Jarvis (International Press, Cambridge, MA, 1999) pp. 32–43, arXiv:quant-ph/9807006.

[34] S. Aaronson and D. Gottesman, Improved simulation of stabilizer circuits, Physical Review A **70**, 052328 (2004).

[35] V. Veitch, S. A. H. Mousavian, D. Gottesman, and J. Emerson, The resource theory of stabilizer quantum computation, New Journal of Physics **16**, 013009 (2014).

[36] P. W. Shor, Algorithms for quantum computation: discrete logarithms and factoring, in *Proceedings of the 35th Annual Symposium on Foundations of Computer Science (FOCS '94)* (IEEE Computer Society Press, Los Alamitos, CA, USA, 1994) pp. 124–134, arXiv:quant-ph/9508027.

[37] L. K. Grover, A fast quantum mechanical algorithm for database search, in *Proceedings of the Twenty-Eighth Annual ACM Symposium on the Theory of Computing* (1996) pp. 212–219, arXiv:quant-ph/9605043.

[38] A. Ambainis, Superlinear advantage for exact quantum algorithms, SIAM Journal on Computing **45**, 617 (2016), arXiv:1211.0721.