



DATA MANAGEMENT AND BUSINESS INTELLIGENCE

ASSIGNMENT 2

ACADEMIC YEAR 2020 – 2021 (PART TIME)

SUBJECT: **GLOBAL SUPERSTORE REPORT**

Contents

1. INTRODUCTION	3
2. CASE STUDY	3
3. DATA SOURCE	3
3.1. Description of the Dataset	4
4. ANALYSIS.....	4
4.1. Design and develop the data warehouse	4
4.1.1. Importing the data into the Database	5
4.1.2. Cleaning and Transforming the Data	8
4.1.3. Creating the dimensions	8
4.1.4. Creating the fact table	10
4.2. Build the data Cube.....	12
4.3. OLAP	15
4.3.1. Measures.....	16
4.4. Visualizations	18
5. Code	25

1. INTRODUCTION

The scope of this report was to design and develop a data warehouse, build a data cube on top of it, develop some OLAP reports and visualize our results based on an existing business model referring to retail sales. This was accomplished by using SQL Server Database, SQL Server Analysis Services and Power BI of Microsoft as presented below in detail.

2. CASE STUDY

Our business study concerns a multinational Superstore specialized in retail with trading activities in 137 different countries. With a wide selection of products regarding three main categories (office supplies, furniture, technology), Superstore stays competitive by offering customers more than _____ items.

However, sales success is a result of providing the right product in the right place at the right time and to the appropriate customer, given that each environment generates different needs, unique for any individual. That is to say, right product selection powers energetic growth and a higher return on investment.

This can be accomplished by using historical data and market analysis in order to identify customer trends and changing preferences by combining data from different areas.

In addition, by studying sales data with a variety of related factors, businesses such as Superstore, can recognize emerging trends, anticipate them better and eventually create the agility to respond efficiently to market complexity.

That is exactly our subject of interest so we are going to use a data set containing information about products, sales, profits for four (consecutive) years etc. in order to identify key areas for improvement within this fictitious company.


3. DATA SOURCE

The Data Source we used so as to obtain our dataset was *kaggle*, one of the best free open Data Sources where it is possible to find and publish data sets as well as explore and build models in a web-based data-science environment. The dataset we obtained for the purpose of this assignment was *superstore_data*.

Data Source	https://www.kaggle.com/datasets
Dataset	https://www.kaggle.com/jr2ngb/superstore-data

3.1. Description of the Dataset

The initial dataset was a csv file containing 24 columns:

- Row ID primary key
 - Order ID
 - Order Date
 - Ship Date
 - Customer ID
 - Customer Name
 - Segment
 - City
 - State
 - Country
 - Postal Code
 - Market
 - Region
 - Product ID
 - Category
 - Sub-Category
 - Product Name
 - Order Priority
 - Sales
 - Quantity
 - Discount
 - Profit
 - Shipping Cost
- 
- Metrics**

As seen above there is plenty of information available regarding sales, such as the product names, their categories and sub-categories, information about the customers including names and the place they live as well as information about the order and ship date. The last five (5) columns show the sales metrics.

4. ANALYSIS

The analysis of Superstore retail sales focused on the below steps:

1. Design and develop the data warehouse
2. Build the data cube
3. Develop some OLAP reports
4. Visualize our results

4.1. Design and develop the data warehouse

We connected to the SQL Server Database in order to create the database in which we would load the dataset and start the analysis. The steps we followed at this stage come as follows:

1. Importing the data into the database
2. Cleaning and Transforming the Data
3. Creating the dimensions
4. Creating the fact table
5. Creating the relationships between fact table and dimensions
6. Create the Schema

4.1.1. Importing the data into the Database




Figure 1. Importing csv file into the Database




Figure 2. Introduction – Import csv file

Introduction
Specify Input File
Preview Data
Modify Columns
Summary
Results

Help

Specify Input File

This operation will create a table from your input file.

Location of file to be imported

C:\Users\karpa\Desktop\Business Analytics\Courses\1st Semester\Data Managen Browse...

New table name:

superstore_dataset2011-2015

Table schema:

dbo

Figure 3. Specify Input File – Import csv file

Introduction
Specify Input File
Preview Data
Modify Columns
Summary
Results

Help

Modify Columns

This operation generated the following table schema. Please verify if schema is accurate, and if not, please make any changes.

Column Name	Data Type	Primary Key	<input type="checkbox"/> Allow Nulls
Row_ID	int	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Order_ID	varchar(MAX)	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Order_Date	varchar(MAX)	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Ship_Date	varchar(MAX)	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Ship_Mode	varchar(MAX)	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Customer_ID	varchar(MAX)	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Customer_Name	varchar(MAX)	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Segment	varchar(MAX)	<input type="checkbox"/>	<input checked="" type="checkbox"/>
City	varchar(MAX)	<input type="checkbox"/>	<input checked="" type="checkbox"/>
State	varchar(MAX)	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Country	varchar(MAX)	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Postal_Code	varchar(MAX)	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Market	varchar(MAX)	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Region	varchar(MAX)	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Product_ID	varchar(MAX)	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Category	varchar(MAX)	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Sub_Category	varchar(MAX)	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Product_Name	varchar(MAX)	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Sales	varchar(MAX)	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Quantity	varchar(MAX)	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Discount	varchar(MAX)	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Profit	varchar(MAX)	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Shipping_Cost	varchar(MAX)	<input type="checkbox"/>	<input checked="" type="checkbox"/>

Error Reporting - Selecting a smaller range may have a performance impact No Range

< Previous Next > Cancel

Figure 4. Modify Columns – Import csv File




Figure 5. Results – Import csv File

During this process we faced some problems while defining the type of some columns, more precisely the order and ship date column as well as metrics. In order to overcome this issue we assigned varchar(max) type to every column except for Row_ID, which we would fix at the creation of dimensions (Figure 4. Modify Columns – Import csv File).

Row_ID	Order_ID	Order_Date	Ship_Date	Ship_Mode	Customer_ID	Customer_Name	Segment	City	State	Country	Postal_Code	Market	Region	Product_ID	Category	Sub_Category	Product_Name
1	MX-2014-143658	2/10/2014	6/10/2014	Standard Class	SC-20575	Sonia Cooley	Consumer	Mexico City	Distrito Federal	Mexico	NULL	LATAM	North	OFF-LA-10002782	Office Supplies	Labels	Labels
2	MX-2012-155047	15/10/2012	20/10/2012	Standard Class	KW-16570	Kelly Williams	Consumer	Dos Quebradas	Risaralda	Colombia	NULL	LATAM	South	FUR-FU-10004015	Furniture	Furnishings	Furnishings
3	MX-2012-155047	15/10/2012	20/10/2012	Standard Class	KW-16570	Kelly Williams	Consumer	Dos Quebradas	Risaralda	Colombia	NULL	LATAM	South	FUR-BO-10002352	Furniture	Bookcases	Bookcases
4	MX-2012-155047	15/10/2012	20/10/2012	Standard Class	KW-16570	Kelly Williams	Consumer	Dos Quebradas	Risaralda	Colombia	NULL	LATAM	South	OFF-BI-10004428	Office Supplies	Binders	Binders
5	MX-2012-155047	15/10/2012	20/10/2012	Standard Class	KW-16570	Kelly Williams	Consumer	Dos Quebradas	Risaralda	Colombia	NULL	LATAM	South	OFF-AR-10004594	Office Supplies	Art	Art
6	MX-2012-155047	15/10/2012	20/10/2012	Standard Class	KW-16570	Kelly Williams	Consumer	Dos Quebradas	Risaralda	Colombia	NULL	LATAM	South	OFF-EN-10001375	Office Supplies	Envelopes	Envelopes
7	MX-2013-134096	27/9/2013	1/10/2013	Standard Class	DP-13000	Darren Powers	Consumer	São Paulo	São Paulo	Brazil	NULL	LATAM	South	OFF-EN-10001375	Office Supplies	Envelopes	Envelopes
8	MX-2013-134096	27/9/2013	1/10/2013	Standard Class	DP-13000	Darren Powers	Consumer	São Paulo	São Paulo	Brazil	NULL	LATAM	South	TEC-MA-10004956	Technology	Machines	Machines
9	MX-2013-134096	27/9/2013	1/10/2013	Standard Class	DP-13000	Darren Powers	Consumer	São Paulo	São Paulo	Brazil	NULL	LATAM	South	OFF-SU-10003474	Office Supplies	Supplies	Supplies
10	MX-2013-134096	27/9/2013	1/10/2013	Standard Class	DP-13000	Darren Powers	Consumer	São Paulo	São Paulo	Brazil	NULL	LATAM	South	TEC-AC-10001830	Technology	Accessories	Accessories
11	MX-2013-134096	27/9/2013	1/10/2013	Standard Class	DP-13000	Darren Powers	Consumer	São Paulo	São Paulo	Brazil	NULL	LATAM	South	OFF-BI-10002075	Office Supplies	Binders	Binders
12	MX-2013-156335	5/3/2013	12/3/2013	Standard Class	TB-21250	Tim Brockman	Consumer	Managua	Managua	Nicaragua	NULL	LATAM	Central	OFF-FA-10002526	Office Supplies	Fasteners	Fasteners
13	MX-2013-156335	5/3/2013	12/3/2013	Standard Class	TB-21250	Tim Brockman	Consumer	Managua	Managua	Nicaragua	NULL	LATAM	Central	FUR-CH-10002340	Furniture	Chairs	Chairs
14	MX-2014-121923	24/9/2014	1/10/2014	Standard Class	PK-18910	Paul Knutson	Home Office	Managua	Managua	Nicaragua	NULL	LATAM	Central	OFF-EN-10004100	Office Supplies	Envelopes	Envelopes
15	MX-2014-135706	18/10/2014	23/10/2014	Standard Class	JK-15825	Jim Karlsson	Consumer	Brasília	Federal District	Brazil	NULL	LATAM	South	OFF-AR-10003614	Office Supplies	Art	Art
16	MX-2014-135706	18/10/2014	23/10/2014	Standard Class	JK-15825	Jim Karlsson	Consumer	Brasília	Federal District	Brazil	NULL	LATAM	South	OFF-FA-10000338	Office Supplies	Fasteners	Fasteners
17	US-2013-126655	26/8/2013	1/7/2013	Standard Class	HE-14800	Harold Engle	Corporate	San Miguelito	Panama	Panama	NULL	LATAM	Central	OFF-EN-10000761	Office Supplies	Envelopes	Envelopes
18	US-2013-126655	26/8/2013	1/7/2013	Standard Class	HE-14800	Harold Engle	Corporate	San Miguelito	Panama	Panama	NULL	LATAM	Central	FUR-FU-10003066	Furniture	Furnishings	Furnishings
19	US-2013-126655	26/8/2013	1/7/2013	Standard Class	HE-14800	Harold Engle	Corporate	San Miguelito	Panama	Panama	NULL	LATAM	Central	OFF-EN-10000075	Office Supplies	Envelopes	Envelopes
20	US-2013-126655	26/8/2013	1/7/2013	Standard Class	HE-14800	Harold Engle	Corporate	San Miguelito	Panama	Panama	NULL	LATAM	Central	OFF-EN-10002226	Office Supplies	Envelopes	Envelopes
21	MX-2013-167799	19/12/2013	25/12/2013	Standard Class	JE-15810	Jim Epp	Corporate	San Cristóbal	Chiapas	Mexico	NULL	LATAM	North	FUR-CH-10002132	Furniture	Chairs	Chairs
22	MX-2013-163139	29/10/2013	2/11/2013	Second Class	TB-21055	Ted Butterfield	Consumer	Santiago	Santiago	Chile	NULL	LATAM	South	TEC-AC-10002749	Technology	Accessories	Accessories
23	MX-2013-163139	29/10/2013	2/11/2013	Second Class	TB-21055	Ted Butterfield	Consumer	Santiago	Santiago	Chile	NULL	LATAM	South	OFF-SU-10000006	Office Supplies	Supplies	Supplies
24	US-2014-119753	3/10/2014	8/10/2014	Standard Class	DW-13195	David Wiesner	Corporate	Panama City	Panama	Panama	NULL	LATAM	Central	OFF-BI-10003934	Office Supplies	Binders	Binders
25	US-2012-133970	26/9/2012	29/9/2012	First Class	SJ-20215	Sarah Jordan	Consumer	Hermosillo	Sonora	Mexico	NULL	LATAM	North	FUR-FU-10001142	Furniture	Furnishings	Furnishings
26	MX-2014-120607	18/6/2014	25/6/2014	Standard Class	SP-20050	Stephanie Phil...	Corporate	Coyoacán	Distrito Federal	Mexico	NULL	LATAM	North	TEC-CO-10004256	Technology	Copiers	Copiers
27	MX-2013-162007	18/8/2014	25/8/2014	Standard Class	SP-20050	Stephanie Phil...	Corporate	Coyoacán	Distrito Federal	Mexico	NULL	LATAM	North	OFF-BI-10003709	Office Supplies	Binders	Binders
28	US-2013-167126	24/5/2013	31/5/2013	Standard Class	SC-20050	Sample Comp...	Home Office	Tegucigalpa	Francisco Mo...	Honduras	NULL	LATAM	Central	OFF-FA-10003529	Office Supplies	Fasteners	Fasteners
29	US-2013-167126	24/5/2013	31/5/2013	Standard Class	SC-20050	Sample Comp...	Home Office	Tegucigalpa	Francisco Mo...	Honduras	NULL	LATAM	Central	OFF-FA-10003529	Office Supplies	Fasteners	Fasteners

Figure 6. Data illustration

4.1.2. Cleaning and Transforming the Data

At this stage we cleaned and transformed our data. At first we removed the Postal_Code column because many values were missing so we concluded that it would not contribute to our analysis. Later on we checked for NULL values for all columns and we extracted rows that were missing many or important values.

After deciding the data we would work on, we started transforming them. Our first attempt was to convert the metrics from varchar to float type. In order to do that we created a staging table that fulfill all the requirements needed for importing only clean data in the fact table.

Following, we conducted the same procedure as before in order to transform the order and ship date columns.

During this procedure, we faced an unpredictable event .The entries for the date did not have the same format as ddmmyyyy and had also different symbol as a separator for day, month and year. More precisely, some had the *slash* " / " and some other the *dash* " - " symbol, so we had to make a query in order to convert first the sting text in the same format and later on the string format to date.

4.1.3. Creating the dimensions

Data warehouses are constructed using dimensional data models containing fact and dimension tables. By theory, dimension tables are used to hold the descriptive criteria by which a user can organize the data and they consist of primary keys, values and attributes as well.

Indeed, a dimension table can be expressed by using one or more criteria according to the circumstances. In the current retail sales analysis we defined a snowflake schema in our database as it is best suited when dimension tables store a large number of rows with redundant data, and space is an issue.

Based on the above mentioned, the dimension tables were chosen to be as following:

- Dimension for Customers
- Dimension for Product
- Dimension for Order Date
- Dimension for Ship Date
- Dimension for Priority
- Dimension for City (City- State-Country)
- Dimension for Market-Region (Region-Market)
- Dimension for Ship Mode

Market- Region Dimension

Superstore dataset was initially built in a way to divide the Globe into *Markets* and *Regions*. Some markets are distributed to Regions. More specifically:

- **EU** is divided into South, Central and North Europe
- **EMEA** does not have a region since it is a combining Market
- **LATAM** is divided into Central, Caribbean, North and South
- **Canada** the same with EMEA
- **APAC** is divided into North Asia, Central Asia, Southeast Asia and Oceania.
- **US** is divided into Central , West, South and East.

For simplicity we concatenated the Market and Region labels in order to distinct the Region labels being identical for more than one Market.

MARKET ABBREVIATIONS	
EU	Europe
EMEA	Europe-Middle East-Asia
AFRICA	Africa
LATAM	Latin America
APAC	Asia Pacific
CANADA	Canada
US	US

Table 1. Market accronyms

Subsequently, we create the Region dimension table which is normalized into another related table, the Market table.

Customers Dimension

Superstore needs to have a dimension with all customer details, for example Name and Surname as well as their segment. *Customer name* shows the full name of the customer and *Customer segment* categorizes customers depending on their identity (Home Office, Corporate and Consumer). The last helps the company to understand what customers really want and It also explains how grouping customers into market segments is a good foundation for winning and keeping profitable customers.

Priority and Ship Mode Dimension.

Priority dimension includes information about how urgent an order is and Ship Mode refers to which method of transportation is used for the delivery.

City Dimension

City dimension includes information regarding the city where the order was delivered. Countries are divided into states and states into cities as well. Concerning these we create the dimension table based on roll-up process which refers to the process of viewing data with decreasing detail.



Table 2. City dimension flow

Product Dimension

The Superstore offers a vast amount of products. Each product has a unique name, belongs to a category and each category consists of subcategories. Given that, our approach was similar to the one for creating the dimension city.

Date Dimension

This dimension includes information about time, in order to make further analysis and monitor the stores' activities by date, month, quarter and year. To be noted that we have two date dimensions regarding order date and ship date.

4.1.4. Creating the fact table

After creating the dimensions we continued with the creation of the fact table (Figure 12. Creating the fact table). Following that, we populated the fact table using the staging_table and dimension tables with the INSERT INTO and the UPDATE function. The relevant queries are in last section (Section 5).

The final step is to define the relationship between the fact table and the dimensions. More thoroughly, the ID columns of the fact table are determined as foreign keys of the dimension tables. Below are some examples of the creation of these relationships (Figure 7 and Figure 8).




Figure 7 . Create relationship between the fact and City Dimension table




Figure 8 . Create relationship between the fact and Product Dimension table




Figure 9. Database Schema

4.2. Build the data Cube

After completing the construction of the Data Warehouse, we designed the cube in Visual Studio using the Multidimensional Analysis Service and Data Mining Tool. Below are the steps followed:

- Creation of the data warehouse project
- Connect the data warehouse with the project
- Create the data cube (define measures of the fact table)
- Add Dimensions and connect them with the cube
- Define Hierarchies
- Deployment and Process




Figure 10. Connecting the project with the Superstore DB




Figure 11. Choosing dimensions for the Cube




Figure 12. Creating Hierarchies




Figure 13. The Cube




Figure 14. The schema

4.3. OLAP

OLAP operations stand for Online analytical processing server. The basic OLAP operations are the following:

Drill down: In drill-down operation, the less detailed data is converted into highly detailed data. It can be done by:

- Moving down in the concept hierarchy
- Adding a new dimension

We did a drill down operation when moving down to the product category and found the top 5 sold and profitable phones respectively (Section 4.4).

Roll up: It is just opposite of the drill-down operation. It performs aggregation on the OLAP cube. It can be done by:

- Climbing up in the concept hierarchy
- Reducing the dimensions

When roll up is performed one or more dimensions are removed.

Slice: It selects a single dimension from the cube which results in a new sub-cube creation.

Dice: It selects a sub-cube from the OLAP cube by selecting two or more dimensions.

In our cube a sub-cube is selected by selecting following dimensions with criteria:

- Location = “France” or “China”
- Time = “Q1” or “Q2”
- Product = “Copiers” or “Phones”

The above procedure can be described as “slice and dice “

4.3.1. Measures

New measurements have been created such as max for selling price.

Some of them are:

- Avg_Sales
- Selling_Price
- Cogs costⁱ¹
- Gross_Profit_Margin
- Total Cost




Figure 15. New measures




Figure 16. New measures




Figure 17. New measures




Figure 18. New measures




Figure 19. New measures

4.4. Visualizations

Below are some of the visuals created in Power BI:



Visual 1. Sales distributed for each country.


In the above graph (Visual 1) we see the sales distributed for each country.

Each bubble represents the portion of total global sales.


The **bigger** a bubble is the more this country contributes to sales.

Interpretation:


We see that US, China, France, Germany and Australia are the countries with the most impact.




Visual 2. Sales amount by year for Top 5 Countries




Visual 3. Sales amount by year for Top 5 Countries




Visual 4. Sales amount by year for Top 5 Countries




Visual 5. Sales amount by Sub-Category




Visual 6. Sales amount by Sub-Category during time




Visual 7. Sales by customer segments



Visual 8. Profit per year



Visual 9. Top 10 Countries with most Shipping Cost grouped by order priority



Visual 10. Average profit by region

Conclusions

1. Most sales come from the Apple Smart Phone in 2014 and has the most significant increase during the years.
2. The most profitable product is by far the Canon imageClass 2200 Advanced Copier.
3. Technology products have the greater demand, meaning more profit for the company.
4. US, China, France, Germany and Australia are the countries with the most impact.
5. Almost half of total sales come from
 - Phones (14,03%)
 - Copiers (12,56%)
 - Bookcases (12,47%)
 - Chairs (12,3%)
6. Consumers and home offices seem to buy mostly phones
7. Companies invest more on copiers and phones as well
8. Profit increases rapidly from 2011 to 2014.
9. High and Medium order priority seems to have more shipping cost for all 10 countries with most shipping cost.
10. Biggest average profit per order has the Caribbean-LATAM region and biggest negative South-EU.

5. Code

```

Use superstore;
alter table staging_table drop column Postal_Code
select * from staging_table where Row_ID is null
select * from staging_table where Order_Date is null
select * from staging_table where Ship_Date is null
select * from staging_table where Ship_Mode is null
select * from staging_table where Customer_ID is null
select * from staging_table where Customer_Name is null
select * from staging_table where Segment is null
select * from staging_table where City is null
select * from staging_table where State is null
select * from staging_table where Country is null
select * from staging_table where Market is null
select * from staging_table where Region is null
select * from staging_table where Product_ID is null
select * from staging_table where Product_Name is null
select * from staging_table where Category is null
select * from staging_table where Sub_Category is null
select * from staging_table where Sales is null
select * from staging_table where Quantity is null
select * from staging_table where Discount is null
select * from staging_table where Profit is null
select * from staging_table where Shipping_Cost is null
select * from staging_table where Order_Priority is null


create table staging_metrics (
row_id int not null identity(1,1) primary key,
sales_amount float,
quantity int,
discount float,
profit_amount float,
shipping_cost float
);


SELECT round(CAST(CAST (Sales AS NUMERIC(19,4)) AS float),2) as sales_amount,
          CAST(CAST (Quantity AS NUMERIC(19,4)) AS int) as
quantity,
          round(CAST(CAST (Discount AS NUMERIC(19,4)) AS float),2) as
discount,
          round(CAST(CAST (Profit AS NUMERIC(19,4)) AS float),2)
as profit_amount,
          round(CAST(CAST (Shipping_Cost AS NUMERIC(19,4)) AS float),2)
as shipping_cost
from staging_table --- works


insert into staging_metrics(sales_amount, quantity,
discount, profit_amount, shipping_cost)
select t.sales_amount, t.quantity, t.discount, t.profit_amount, t.shipping_cost
from (
SELECT round(CAST(CAST (Sales AS NUMERIC(19,4)) AS float),2) as sales_amount,
          CAST(CAST (Quantity AS NUMERIC(19,4)) AS int) as
quantity,
          round(CAST(CAST (Discount AS NUMERIC(19,4)) AS float),2) as
discount,
          round(CAST(CAST (Profit AS NUMERIC(19,4)) AS float),2)
as profit_amount,
          round(CAST(CAST (Shipping_Cost AS NUMERIC(19,4)) AS float),2)
as shipping_cost

```

```

from staging_table) t

select * from staging_metrics

select * from staging_metrics

create table staging_date1 (
date_id int not null identity(1,1) primary key,
order_date date,
);

insert into staging_date1(order_date)
select convert(date, t.order_date_final, 103) from (
SELECT REPLACE(Order_Date, '-', '/') as staging_date,

charindex('/',REPLACE(Order_Date, '-', '/')) as position_1st,--
find the position of the first /

substring(REPLACE(Order_Date, '-', '/'),1,(charindex('/',REPLACE(Order_Date, '-', '/')) ) ) as order_day, --
select the characters in field Order_Date from the beginning of the field until
the first /

RIGHT('00'+convert(varchar,substring(REPLACE(Order_Date, '-', '/'),1,(charindex('/',REPLACE(Order_Date, '-', '/')) -
1) )),2) as Order_day_dd_format,--convert the above field to dd format

SUBSTRING(REPLACE(Order_Date, '-', '/'), charindex('/',REPLACE(Order_Date, '-', '/'))+1,len(REPLACE(Order_Date, '-', '/')) as remaining_text,--
select the text following the first /,

charindex('/', (SUBSTRING(REPLACE(Order_Date, '-', '/'), charindex('/',REPLACE(Order_Date, '-', '/'))+1,len(REPLACE(Order_Date, '-', '/')))) ) as position_2nd, --
find the position of the first / of field remaining_text

SUBSTRING((SUBSTRING(REPLACE(Order_Date, '-', '/'), charindex('/',REPLACE(Order_Date, '-', '/'))+1,len(REPLACE(Order_Date, '-', '/'))),1,(charindex('/', (SUBSTRING(REPLACE(Order_Date, '-', '/'), charindex('/',REPLACE(Order_Date, '-', '/'))+1,len(REPLACE(Order_Date, '-', '/')))) )-1)) AS Order_month,

RIGHT('00'+CONVERT(VARCHAR,SUBSTRING((SUBSTRING(REPLACE(Order_Date, '-', '/'), charindex('/',REPLACE(Order_Date, '-', '/'))+1,len(REPLACE(Order_Date, '-', '/'))),1,(charindex('/', (SUBSTRING(REPLACE(Order_Date, '-', '/'), charindex('/',REPLACE(Order_Date, '-', '/'))+1,len(REPLACE(Order_Date, '-', '/')))) )-1))),2) AS Order_month_mm_format,

substring(SUBSTRING(REPLACE(Order_Date, '-', '/'), charindex('/',REPLACE(Order_Date, '-',

```

```

', '/')+1,len(REPLACE(Order_Date, '-
', '/'))),charindex('/', (SUBSTRING(REPLACE(Order_Date, '-
', '/'), charindex('/',REPLACE(Order_Date, '-
', '/')+1,len(REPLACE(Order_Date, '-
', '/')))) )+1,LEN(SUBSTRING(REPLACE(Order_Date, '-
', '/'), charindex('/',REPLACE(Order_Date, '-
', '/')+1,len(REPLACE(Order_Date, '-', '/'))))) as Order_year,

RIGHT('00'+convert(varchar,substring(REPLACE(Order_Date, '-
', '/'),1,(charindex('/',REPLACE(Order_Date, '-', '/')) -1) )),2) + '/' +

RIGHT('00'+CONVERT(VARCHAR,SUBSTRING((SUBSTRING(REPLACE(Order_Date, '-
', '/'), charindex('/',REPLACE(Order_Date, '-
', '/')+1,len(REPLACE(Order_Date, '-
', '/'))),1,(charindex('/', (SUBSTRING(REPLACE(Order_Date, '-
', '/'), charindex('/',REPLACE(Order_Date, '-
', '/')+1,len(REPLACE(Order_Date, '-', '/'))))) -1))),2) + '/' +

substring(SUBSTRING(REPLACE(Order_Date, '-
', '/'), charindex('/',REPLACE(Order_Date, '-
', '/')+1,len(REPLACE(Order_Date, '-
', '/'))),charindex('/', (SUBSTRING(REPLACE(Order_Date, '-
', '/'), charindex('/',REPLACE(Order_Date, '-
', '/')+1,len(REPLACE(Order_Date, '-
', '/')))) )+1,LEN(SUBSTRING(REPLACE(Order_Date, '-
', '/'), charindex('/',REPLACE(Order_Date, '-
', '/')+1,len(REPLACE(Order_Date, '-', '/'))))) as order_date_final

from staging_table) t

create table staging_date2 (
date_id int not null identity(1,1) primary key,
ship_date date
);

insert into staging_date2(ship_date)
select convert(date, t.Ship_Date_final, 103) from (
SELECT REPLACE(Ship_Date, '-', '/') as staging_date,

charindex('/',REPLACE(Ship_Date, '-', '/')) as position_ist,--
find the position of the first /

substring(REPLACE(Ship_Date, '-', '/'),1,(charindex('/',REPLACE(Ship_Date, '-
', '/')) ) ) as order_day, --
select the characters in field Ship_Date from the beggining of the field until t
he first /

RIGHT('00'+convert(varchar,substring(REPLACE(Ship_Date, '-
', '/'),1,(charindex('/',REPLACE(Ship_Date, '-', '/')) -
1) )),2) as Order_day_dd_format,--convert the above field to dd format

SUBSTRING(REPLACE(Ship_Date, '-', '/'), charindex('/',REPLACE(Ship_Date, '-
', '/')+1,len(REPLACE(Ship_Date, '-', '/')))) as remaining_text,--
select the text following the first /

charindex('/', (SUBSTRING(REPLACE(Ship_Date, '-
', '/'), charindex('/',REPLACE(Ship_Date, '-', '/'))+1,len(REPLACE(Ship_Date, '-
', '/')))) ) as position_2nd, --
find the position of the first / of field remaining_text

SUBSTRING((SUBSTRING(REPLACE(Ship_Date, '-
', '/'), charindex('/',REPLACE(Ship_Date, '-', '/'))+1,len(REPLACE(Ship_Date, '-

```

```

', '/''))),1,(charindex('/', (SUBSTRING(REPLACE(Ship_Date, '-
', '/'), charindex('/',REPLACE(Ship_Date, '-', '/'))+1,len(REPLACE(Ship_Date, '-
', '/'')))) )-1)) AS Order_month,

RIGHT('00'+CONVERT(VARCHAR,SUBSTRING((SUBSTRING(REPLACE(Ship_Date, '-
', '/'), charindex('/',REPLACE(Ship_Date, '-', '/'))+1,len(REPLACE(Ship_Date, '-
', '/''))),1,(charindex('/', (SUBSTRING(REPLACE(Ship_Date, '-
', '/'), charindex('/',REPLACE(Ship_Date, '-', '/'))+1,len(REPLACE(Ship_Date, '-
', '/'')))) )-1))),2) AS Order_month_mm_format,

substring(SUBSTRING(REPLACE(Ship_Date, '-
', '/'), charindex('/',REPLACE(Ship_Date, '-', '/'))+1,len(REPLACE(Ship_Date, '-
', '/''))),charindex('/', (SUBSTRING(REPLACE(Ship_Date, '-
', '/'), charindex('/',REPLACE(Ship_Date, '-', '/'))+1,len(REPLACE(Ship_Date, '-
', '/'')))) )+1,LEN(SUBSTRING(REPLACE(Ship_Date, '-
', '/'), charindex('/',REPLACE(Ship_Date, '-', '/'))+1,len(REPLACE(Ship_Date, '-
', '/'')))) as Order_year,

RIGHT('00'+convert(vchar,substring(REPLACE(Ship_Date, '-
', '/'),1,(charindex('/',REPLACE(Ship_Date, '-', '/')) -1) )),2) + '/' +

RIGHT('00'+CONVERT(VARCHAR,SUBSTRING((SUBSTRING(REPLACE(Ship_Date, '-
', '/'), charindex('/',REPLACE(Ship_Date, '-', '/'))+1,len(REPLACE(Ship_Date, '-
', '/''))),1,(charindex('/', (SUBSTRING(REPLACE(Ship_Date, '-
', '/'), charindex('/',REPLACE(Ship_Date, '-', '/'))+1,len(REPLACE(Ship_Date, '-
', '/'')))) )-1))),2) + '/' +

substring(SUBSTRING(REPLACE(Ship_Date, '-
', '/'), charindex('/',REPLACE(Ship_Date, '-', '/'))+1,len(REPLACE(Ship_Date, '-
', '/''))),charindex('/', (SUBSTRING(REPLACE(Ship_Date, '-
', '/'), charindex('/',REPLACE(Ship_Date, '-', '/'))+1,len(REPLACE(Ship_Date, '-
', '/'')))) )+1,LEN(SUBSTRING(REPLACE(Ship_Date, '-
', '/'), charindex('/',REPLACE(Ship_Date, '-', '/'))+1,len(REPLACE(Ship_Date, '-
', '/'')))) as Ship_Date_final

from staging_table) t

select * from staging_date1
select * from staging_date2

create table dim_Order (
    row_id int not null identity(1,1) primary key,
    order_id varchar(50) not null
);

insert into dim_Order(order_id)
select t.order_id from (select order_id from staging_table) t

select * from dim_Order

create table dim_Priority (
    priority_id int not null identity(1,1) primary key,
    priority_label varchar(50) not null
);

```

```

insert into dim_Priority(priority_label)
select distinct Order_Priority from staging_table

create table dim_ShipMode (
    ship_mode_id int not null identity(1,1) primary key,
    ship_mode_label varchar(50) not null
);

insert into dim_ShipMode(ship_mode_label)
select distinct Ship_Mode from staging_table

create table dim_Category(
    category_id int not null identity(1,1) primary key,
    category_label varchar(50))

create table dim_Sub_Category(
    sub_category_id int not null identity(1,1) primary key,
    sub_category_label varchar(140) not null,
    category_id int foreign key references dim_Category(category_id))

create table dim_Product(
    product_id int not null identity(1,1) primary key,
    product_name varchar(170),
    sub_category_id int foreign key references dim_Sub_Category(sub_category_id))

insert into dim_Category(category_label) select distinct category from staging_table

insert into dim_Sub_Category (sub_category_label, category_id)
select * from
(select distinct t1.Sub_Category, t2.category_id from staging_table t1 join dim_Category t2 on t1.Category = t2.category_label) t

insert into dim_Product (product_name, sub_category_id)
select * from
(select distinct t1.Product_Name, t2.sub_category_id from staging_table t1 join dim_Sub_Category t2 on t1.Sub_Category = t2.sub_category_label) t

use superstore

CREATE TABLE dbo.Dim_Date (
    DateKey INT NOT NULL PRIMARY KEY,
    [Date] DATE NOT NULL,
    [Day] TINYINT NOT NULL,
    [Day_Name] VARCHAR(20) NOT NULL,
    [Month] TINYINT NOT NULL,
    [MonthName] VARCHAR(15) NOT NULL,
    [Quarter] TINYINT NOT NULL,
    [QuarterName] VARCHAR(6) NOT NULL,
    [Year] INT NOT NULL,
)

insert into Dim_Date (DateKey, date, Day, Day_Name, Month, MonthName,
Quarter, QuarterName, Year)
select date_id, order_date,
day(order_date) day_id, datename(dw,order_date) date_name,
month(order_date) month_id, datename(MONTH,order_date) month_name,
datename(QUARTER,order_date) quarter_id,

```

```

concat ('Q',datename(QUARTER,order_date)) quarter_name,
year(order_date) year
from staging_date1

select * from dim_Date

----- time dimension - ship_date -----

CREATE TABLE dbo.Dim_ShipDate (
    DateKey INT NOT NULL PRIMARY KEY,
    [Date] DATE NOT NULL,
    [Day] TINYINT NOT NULL,
    [Day_Name] VARCHAR(20) NOT NULL,
    [Month] TINYINT NOT NULL,
    [MonthName] VARCHAR(15) NOT NULL,
    [Quarter] TINYINT NOT NULL,
    [QuarterName] VARCHAR(6) NOT NULL,
    [Year] INT NOT NULL,
)

insert into Dim_ShipDate (DateKey, date, Day, Day_Name, Month, MonthName,
Quarter, QuarterName, Year)
select date_id, Ship_Date, day(Ship_Date) day_id, datename(dw,Ship_Date) date_name,
        month(Ship_Date) month_id, datename(MONTH,Ship_Date) month_name,
        datename(QUARTER,Ship_Date) quarter_id,
        concat ('Q',datename(QUARTER,Ship_Date)) quarter_name,
year(Ship_Date) year
from staging_date2

select * from Dim_Date
select * from Dim_ShipDate

create table dim_Customers (
    customer_id int not null identity(1,1) primary key,
    customer_name varchar(50) not null,
    segment_label varchar(50) not null
);

insert into dim_Customers(customer_name, segment_label ) (select distinct Customer_Name, Segment from staging_table);

select * from dim_Customers

create table dim_Country (
    country_id int not null identity(1,1) primary key,
    country_label varchar(150)
);

create table dim_State (
    state_id int not null identity(1,1) primary key,
    state_label varchar(150),
    country_id int not null foreign key references dim_Country(country_id)
);

create table dim_City (
    city_id int not null identity(1,1) primary key,
    city_label varchar(150),
    state_id int foreign key references dim_State (state_id),

```

```

country_id int foreign key references dim_Country(country_id)
);

insert into dim_Country(country_label) select distinct Country
from staging_table

insert into dim_State(state_label, country_id) select *
from (select distinct State, t2.country_id from staging_table t1
join dim_Country t2 on t1.Country = t2.country_label)t

insert into dim_City(city_label, state_id, country_id) select *
from (select distinct t1.City, t2.state_id, t3.country_id
from dataset1 t1 join dim_State t2 on t1.State = t2.state_label
join dim_Country t3
on t2.country_id = t3.country_id) t

create table fact_orders (
    row_id int not null identity(1,1) primary key,
    order_id varchar(50),
    order_date_id int,
    ship_date_id int,
    customer_id int,
    customer_name varchar(70),
    city_id int,
    city_label varchar(70),
    product_id int,
    product_name varchar(150),
    region_id int,
    region_label varchar(50),
    priority_id int,
    priority_label varchar(40),
    ship_mode_id int,
    ship_mode_label varchar(50),
    sales_amount float,
    quantity int,
    discount float,
    profit float,
    shipping_cost float);

insert into fact_orders(sales_amount, quantity, discount,
profit, shipping_cost)

select sales_amount, quantity,
discount, profit_amount, shipping_cost from staging_metrics

select * from fact_orders

UPDATE
    fact_orders
SET
    fact_orders.order_id = Table_B.order_id
FROM
    fact_orders AS Table_A
    INNER JOIN dim_Order AS Table_B
        ON Table_A.row_id = Table_B.row_id

select * from fact_orders

UPDATE
    fact_orders

```

```

SET
    fact_orders.order_date_id = Table_B.DateKey
FROM
    fact_orders AS Table_A
    INNER JOIN Dim_Date AS Table_B
        ON Table_A.row_id = Table_B.DateKey
UPDATE
    fact_orders
SET
    fact_orders.ship_date_id = Table_B.DateKey
FROM
    fact_orders AS Table_A
    INNER JOIN Dim_ShipDate AS Table_B
        ON Table_A.row_id = Table_B.DateKey

select * from fact_orders

UPDATE
    fact_orders
SET
    fact_orders.customer_name = Table_B.Customer_Name
FROM
    fact_orders AS Table_A
    INNER JOIN staging_table AS Table_B
        ON Table_A.order_id = Table_B.Order_ID

UPDATE
    fact_orders
SET
    fact_orders.customer_id = Table_B.Customer_ID
FROM
    fact_orders AS Table_A
    INNER JOIN dim_Customers AS Table_B
        ON Table_A.customer_name = Table_B.customer_name

UPDATE
    fact_orders
SET
    fact_orders.city_label = Table_B.City
FROM
    fact_orders AS Table_A
    INNER JOIN dataset1 AS Table_B
        ON Table_A.order_id = Table_B.Order_ID

UPDATE
    fact_orders
SET
    fact_orders.city_id = Table_B.city_id
FROM
    fact_orders AS Table_A
    INNER JOIN dimCity AS Table_B
        ON Table_A.city_label = Table_B.city_label

UPDATE
    fact_orders
SET
    fact_orders.product_name = Table_B.Product_Name
FROM
    fact_orders AS Table_A
    INNER JOIN staging_table AS Table_B
        ON Table_A.order_id = Table_B.Order_ID

```



```

UPDATE
    fact_orders
SET
    fact_orders.product_id = Table_B.product_id
FROM
    fact_orders AS Table_A
    INNER JOIN dim_Product AS Table_B
        ON Table_A.product_name = Table_B.product_name

UPDATE
    fact_orders
SET
    fact_orders.region_label = tab.concatRegion
FROM (
    select Table_A.order_id, concat(Region,'-',Market) as concatRegion
    from fact_orders AS Table_A
    INNER JOIN staging_table Table_B ON Table_A.order_id = Table_B.Order_ID)
tab
    inner join fact_orders on tab.order_id = fact_orders.order_id

UPDATE
    fact_orders
SET
    fact_orders.region_id = Table_B.region_id
FROM
    fact_orders AS Table_A
    INNER JOIN dim_Region AS Table_B
        ON Table_A.region_label = Table_B.region_label

UPDATE
    fact_orders
SET
    fact_orders.priority_label = Table_B.Order_Priority
FROM
    fact_orders AS Table_A
    INNER JOIN staging_table AS Table_B
        ON Table_A.order_id = Table_B.Order_ID

UPDATE
    fact_orders
SET
    fact_orders.priority_id = Table_B.priority_id
FROM
    fact_orders AS Table_A
    INNER JOIN dim_Priority AS Table_B
        ON Table_A.priority_label = Table_B.priority_label

UPDATE
    fact_orders
SET
    fact_orders.ship_mode_label = Table_B.Ship_Mode
FROM
    fact_orders AS Table_A
    INNER JOIN staging_table AS Table_B
        ON Table_A.order_id = Table_B.Order_ID

S
UPDATE

```

```
fact_orders
SET
fact_orders.ship_mode_id = Table_B.ship_mode_id
FROM
fact_orders AS Table_A
INNER JOIN dim_ShipMode AS Table_B
ON Table_A.ship_mode_label = Table_B.ship_mode_label
```

¹ COGS is the cost of goods sold - cost of sales - it is the direct