PERFORMANCE
WATERPROOFING SYSTEMS

SWADI®
a step ahead...

Cool Coat 10C

High Reflective Waterproof Coating for Roofs & Terraces

Description

Swadi Cool Coat 10C is a high-performance, liquid-applied waterproof coating designed to keep roofs cool and energy-efficient. This innovative coating utilizes a high-performance polymer and highly reflective and thermally stable filler to minimize heat absorption and reduce interior temperatures. Cool Coat 10C is resistant to UV rays, weathering, and dirt pick-up, ensuring long-lasting durability and maintaining their heat-reflective properties over time. Suitable for various roof types, including concrete, metal, and pre-coated sheets, Cool Coat 10C offer a reliable and sustainable solution for protecting roofs and improving energy efficiency.

Where to Use

Heat reflective & Waterproof coating for 1.) Flat or sloped roof slabs 2.) Metal roof panels & Galvanized iron sheets used in factories, warehouses, etc., 3.) Sunshades, External walls and balconies 4.) Compatible to PVC Water tanks to keep water cool

Advantages

- High solar reflectance index (SRI 105)
- High degree of cooling effect
- Suitable for the saline environment
- Excellent resistance to Ultra violet rays and weather damage
- Anti-bacterial which is resistant to the growth of algae and fungi
- Eco-friendly; free from hazardous chemicals

Product Data

Type	Acrylic polymer
Colour	White
Density	1.28 ± 0.05 kg/ltr
pH	8.5
Solid content by weight ASTM D 2697	~55%
VOC Content ASTM D 2369-81	< 10 g/ltr
Recommended DFT ASTM D 7091	500 microns in two coats

Technical Data

Tensile strength ASTM D 412	2 MPa
Elongation at break ASTM D 412	> 180%
Water absorption ASTM D 471	NIL
Pull of adhesion ASTM D 4541	> 2 MPa for M20 grade concrete
Solar Reflectance Index ASTM E 1980	105

Application Data

Theoretical coverage	25-30 Sqfts/kg for three coats, depends on porosity
Application	By roller/brush
Cleaning	Clean water
Shelf life	12 months from date of manufacture

Application Instructions

Surface Preparation

For Roof Slabs, Sunshades, External Walls, & Balconies 1.) Remove all dirt, dust, loose particles, and efflorescence using a pressure washer or stiff brush. 2.) Repair any cracks using the Swadi Crystalline Crack Filler compound. 3.) Apply Swadi Aqua Blend 90 Primer specifically designed for the substrate (e.g., concrete, masonry) to ensure proper adhesion.

For Metal Roof Panels & Galvanized Iron Sheets

To prepare metal roofs for coating, start by removing any loose rust and cleaning the surface with a rust remover. Ensure the surface is completely clean before proceeding. If there is heavy rust, replace the affected panels to maintain structural integrity. To seal joints, remove any old silicone sealants and apply Swadi Cool Coat 10C with 50 GSM fabric. This will create a strong and durable seal that helps protect the roof from leaks and moisture damage.

For PVC Water Tanks

1.) Clean the tank thoroughly to remove any dirt, dust, or contaminants. 2.) Repair any cracks or damage using a suitable PVC repair kit or sealant.

Priming

1.) Apply Swadi AquaBlend 90 Primer for Concrete and masonry surfaces, let it dry for 1 to 2 hours, while the surface is tacky apply cool coat 10C on to the surface.
2.) Apply Aqua Blend 90 for PVC water tanks, let it dry for 3 to 4 hours, before cool coat application.
3.) Apply EvoShine Primer W11 Primer for metal sheet panels, overnight cure.

Application

To apply Swadi Cool Coat 10C, apply two to three coats in opposite directions using a PU roller to avoid lint. Allow a drying time of 5-6 hours between coats.

Important Considerations for SWADI Cool Coat 10C application

• Avoid application during rain or on flat surfaces with poor drainage • Use only for foot traffic • Do not apply directly on expansion joints • Apply extra coats to corners, gaps, and joints • Avoid coating during extreme temperatures • Do not apply the coating if rain is expected within 48 hours

Packaging

Swadi Cool Coat 10C is supplied in 20 Kg bucket

Shelf Life

12 months when stored unopened sealed pack and out of direct sunlight

Storage and Handling Guidelines

The product should be stored in accordance with national regulations. It is essential to keep it in a cool, well-ventilated area, away from heat, direct sunlight, sparks, and children. Please note cool coat 10C is non-hazardous product, even though wear proper PPE kit during handling and application. Do not stack more than 3 buckets during storage.

Environmental, Health, and Safety Information

For comprehensive information regarding the safe transportation, handling, storage, and disposal of this chemical product, please refer to the accompanying Safety Data Sheet (SDS). The SDS contains detailed information about physical properties, environmental impacts, toxicological hazards, and other safety-related factors. It is crucial to read the current SDS before using any product.

Disclaimer

The information provided in this datasheet is based on our extensive experience and is given in good faith to assist you. However, we reserve the right to update this information at any time without prior notice due to our ongoing research and development efforts. While we guarantee the consistent quality of our products, we cannot be held responsible for any losses or damages that may arise from their use if site conditions or the execution of work are not properly managed. This data sheet becomes invalid upon the publication of a new edition, and please contact us for the latest version. Please note that we do not provide any warranties regarding the results of our products in specific applications, as the storage, handling, and application of materials are factors beyond our control.

Contact Information

For immediate orders or enquires, contact our **24/7 support team at +91 8792919513 or enquiry@swadigroup.co.in.** For additional support options and resources, please visit our website at swadigroup.co.in

SWADI MINERALS AND CHEMICALS
an ISO 9001:2015 & ISO 14001:2015 certified company
Sy.no 70/1, Vishwaneedam post, Gollarahatti
Magadi main road, Bengaluru – 560091
Tel: +91 8884492928
Email: enquiry@swadigroup.co.in
Website: swadigroup.co.in

Product Data Sheet
Cool Coat 10C
April 2025, Version 011.05.11000000000035

SWADI®
a step ahead...