PERFORMANCE
WATERPROOFING SYSTEMS

SWADI®
a step ahead...

TruBond 1K

Single Component Underlay Waterproofing Membrane

Description

SWADI TruBond 1K is a water-based polymer, which is a ready-to-use waterproofing membrane specifically designed for use in underlayment for Tiles, Bathrooms, Kitchens, balconies & Terrace underlayment. TruBond 1k is based on the most advanced styrene-butadiene copolymer technology and is totally resistant to re-emulsification once cured. Provides long-lasting protection against moisture & dampness to the structure by creating a flexible & durable film on the underlayment. TruBond 1K is Simple & safe to use, and it is fully compatible with polymer-modified tile adhesives.

Where to Use

1.) Under tiling waterproofing membrane, Compatible with polymer - modified tile adhesives. 2.) Terrace / roof underlayment waterproofing membrane. 3.) Underlayment for bathrooms, kitchens & balconies.

Advantages

- Simple to use - Single component, gauged as required.
- Once cured, re - emulsification won't happen.
- The best designed for underlayment for all areas.
- Provides the best coverage, and reduces costs.
- Ensures long - term moisture protection and durability.

Technical Data

Form	Blue, viscous compound
Type	Single component
pH	7.5 ± 0.5
Bond strength	1.5 N/mm²
Tensile strength	3.4 N/mm²
Elongation at break 7 days dried @ 22°C	420%
Touch dry time(min)	60 minutes
Volatile Organic Compounds (V.O.C.)	Nill
Crack bridging capacity ASTM C 1305	~2 mm

Application Instructions

Surface Preparation

The object of the surface preparation is to achieve a clean sound surface with a good mechanical key. All substrates should be cleaned and free of dust, plaster, oil, paint, grease, corrosion deposits, and any other deleterious substances. Laitance should be removed by mechanical means. Smooth substrates must be mechanically roughened e.g., by scabbling, needle gun or grit blasting to provide an adequate key.

Corroded reinforcing steel should be exposed around its full circumference and cleaned to remove all loose scale and corrosion deposits. It is always preferably to clean the steel to a bright condition. Use of emery cloth, grit or sand blasting is recommended.

Priming

- Ensure that the surface is well cleaned and free of all foreign particles before priming.
- Dilute the compound (1:1) (i.e. 1 part TruBond 1K : 1 part water). Let the primer dry for at least 2-3 hours

Application

As soon as the primer has dried, apply two coats of TruBond 1K compound directly to the surface. Once the first coat has dried completely, the second coat can be applied. This usually happens within an hour after the first coat has been applied. This compound dries quickly and forms a flexible and strong black membrane.

Cleaning

Tools and equipment should be washed with water immediately after use.

Coverage

- PRIMER - Take 1 part TruBond 1K : 1 part water (75 grams : 75 grams water) per sqm.
- COATING - 250 grams / sqm / 2 coats.

Shelf Life

TruBond 1K has a shelf life of 12 months if kept in a dry store in unopened condition.

Packaging

TruBond 1K is available in 10 kg & 20 kg bucket.

Condition of Sale

Sold subject to the Company's conditions of sale which are available on request.

Storage and Handling Guidelines

The product should be stored as per national regulations in a cool, dry, and well-ventilated area, away from direct sunlight and extreme temperatures. Keep it out of reach of children. Ensure the container is tightly sealed when not in use. Handle with care to avoid contamination. Stir well before use and apply as per the recommended guidelines.

Health, and Safety Information

SWADI TruBond 1K is considered on-hazardous in normal usage; however, avoid contact with eyes or skin. Wear suitable protective dust mask, gloves and safety glasses. In case of contact with eyes, rinse for several minutes under running water.

For further information, please consult the Material Safety Data Sheet (MSDS).

Disclaimer

The information provided in this datasheet is based on our extensive experience and is given in good faith to assist you. However, we reserve the right to update this information at any time without prior notice due to our ongoing research and development efforts. While we guarantee the consistent quality of our products, we cannot be held responsible for any losses or damages that may arise from their use if site conditions or the execution of work are not properly managed. This data sheet becomes invalid upon the publication of a new edition, and please contact us for the latest version.

Please note that we do not provide any warranties regarding the results of our products in specific applications, as the storage, handling, and application of materials are factors beyond our control.

Contact Information

For immediate orders or enquires, contact our **24/7 support team at +91 8792919513 or enquiry@swadigroup.co.in.** For additional support options and resources, please visit our website at swadigroup.co.in

SWADI MINERALS AND CHEMICALS
an ISO 9001:2015 & ISO 14001:2015 certified company
Sy.no 70/1, Vishwaneedam post, Gollarahatti
Magadi main road, Bengaluru – 560091
Tel: +91 8884492928
Email: enquiry@swadigroup.co.in
Website: swadigroup.co.in

Product Data Sheet
TruBond 1K
November 2025, Version 011.05.11000000000026

SWADI®
a step ahead...