PERFORMANCE
WATERPROOFING SYSTEMS

SWADI®
a step ahead...

Cure Max 50

Acrylic polymer-based, curing compound for concrete with sealing & dust-proofing properties

Description

Swadi Cure Max 50 is a single-component curing compound based on high-performance acrylic copolymers. Designed to reduce water loss from freshly placed concrete, it forms a tough, clear film that retains moisture for effective curing, while also offers sealing and surface dust-proofing benefits. It is UV-resistant, non-yellowing, and provides excellent durability on both horizontal and vertical concrete surfaces. Suitable for interior and exterior use.

Standard Compliance

Complies with standards ASTM C309 Type 1, Class A

Where to Use

- Freshly placed concrete slabs, pavements, and floors.
- Concrete roads, runways, and bridge decks.
- Precast concrete elements.
- Vertical concrete walls and columns.
- Industrial and commercial flooring.

Advantages

- Locking in internal moisture and allowing cement hydraton to proceed to its full potential
- Hydration of cement as long as possible
- Improves surface strength and durability
- Acts as a dust-proofer and light-duty sealer
- UV-resistant, non-yellowing, and long-lasting

Product Data

Chemical type	Modified acrylic polymer
Appearance	Milky white
Density	1.00 g/cc
Drying time	2 - 3 hours
Coverage	3 to 5 Sqm/ltr

Application Instructions

Exposed concrete slabs:

- Apply Swadi Cure Max 50 by spray as soon as the surface is free from visible surface water, usually 1–2 hours after placing. Application must be done before the concrete begins to dry out, ensuring effective moisture retention.

Formed / precast concrete:

- For vertical or precast elements, spray apply Swadi Cure max 50 immediately after formwork removal or demoulding. Where necessary, lightly dampen the concrete surface with clean water before application to improve film formation.

Spraying technique:

- Keep the spray nozzle about 450 mm from the surface.
- Move the nozzle steadily back and forth for uniform coverage.
- Maintain sufficient pump pressure to achieve a fine, even mist.

Shelf Life

Cure Max 50 has a shelf life of 12 months if kept in a dry store in unopened condition.

Packaging

5 kg, 20 kg & 200 kg packs.

Condition of Sale

Sold subject to the company's condition of sale which are available on request.

Storage and Handling Guidelines

The product should be stored as per national regulations in a cool, dry, and well-ventilated area, away from direct sunlight and extreme temperatures. Keep it out of reach of children. Ensure the container is tightly sealed when not in use. Handle with care to avoid contamination. Stir well before use and apply as per the recommended guidelines.

Environmental, Health, and Safety Information

For comprehensive information regarding the safe transportation, handling, storage, and disposal of this chemical product, please refer to the accompanying Safety Data Sheet (SDS). The SDS contains detailed information about physical properties, environmental impacts, toxicological hazards, and other safety-related factors. It is crucial to read the current SDS before using any product.

Disclaimer

The information provided in this datasheet is based on our extensive experience and is given in good faith to assist you. However, we reserve the right to update this information at any time without prior notice due to our ongoing research and development efforts. While we guarantee the consistent quality of our products, we cannot be held responsible for any losses or damages that may arise from their use if site conditions or the execution of work are not properly managed. This data sheet becomes invalid upon the publication of a new edition, and please contact us for the latest version. Please note that we do not provide any warranties regarding the results of our products in specific applications, as the storage, handling, and application of materials are factors beyond our control.

Contact Information

For immediate orders or enquires, contact our **24/7 support team at +91 8792919513 or enquiry@swadigroup.co.in**. For additional support options and resources, please visit our website at swadigroup.co.in

SWADI MINERALS AND CHEMICALS
an ISO 9001:2015 & ISO 14001:2015 certified company
Sy.no 70/1, Vishwaneedam post, Gollarahatti
Magadi main road, Bengaluru – 560091
Tel: +91 8884492928
Email: enquiry@swadigroup.co.in
Website: swadigroup.co.in

Product Data Sheet
Cure Max 50
April 2025, Version 011.05.11000000000111

SWADI®
a step ahead...