PERFORMANCE
CONSTRUCTION CHEMICALS

SWADI®
a step ahead...

Blend M

High - Performance Superplasticizer for Cement - Based Construction Materials

Description

Swadi Blend M is a highly effective superplasticizer based on modified sulphonated melamine based product. The solution comes in pale yellow color, which is a powerful water reducing agent and imparts high mechanical strength to concrete, good flowability and non-sag mortar for all suitable applications.

Where to Use

1.) Pre - cast and pre - stressed concrete. 2.) Concrete admixture. 3.) Ready - mix concrete. 4.) Pre - cast and pre - stressed concrete. 5.) In areas of congested reinforcement, where higher workability is required. 6.) In reducing water contents for the sake of improving impermeability and durability. 7.) Variety of concrete, e.g., marine, architectural, special concrete, pumpable etc.

Advantages

- Powerful water reducing agent - Reduced water content accelerates strength development and high compressive values.
- Excellent flowability ensures high level of contact with load bearing area & also ensures complete fill without leaving any gaps.
- Non-sagging mortar.
- Enables high early strength & provides good workability.
- Lower shrinkage, lower porosity.

Product Data

Colour / appearance	Pale yellow colour liquid
Specific gravity	1.18
Chloride content	Nil
Air entrainment	Negligible at normal dosage
Shelf life	Blend M has a shelf life of 12 months

Dosage

- Dosage must be determined by trail mixes to meet specific requirements.
- 0.5 to 3 liters / 100 Kg of cementitious mixed proportion.

Effect of Over Dose

- Over dosage can cause increase in retardation and segregation.
- Trail mixes must be carried in given dosage proportion to achieve the best properties from mixed admix.

Packaging

Blend M is supplied in 220 - liter barrels.

Condition of Sale

Sold subject to the Company's conditions of sale which are available on request.

Storage and Handling Guidelines

The product should be stored in accordance with national regulations. It is essential to keep it in a cool, well-ventilated area, away from heat, direct sunlight, sparks, and children. Please note that the product contains flammable solvents, so handle it with care. To ensure proper curing, mix the resin and hardener according to the specified ratio. Once mixed, use the solution within its pot life to avoid premature hardening.

Environmental, Health, and Safety Information

For comprehensive information regarding the safe transportation, handling, storage, and disposal of this chemical product, please refer to the accompanying Safety Data Sheet (SDS). The SDS contains detailed information about physical properties, environmental impacts, toxicological hazards, and other safety-related factors. It is crucial to read the current SDS before using any product.

Disclaimer

The information provided in this datasheet is based on our extensive experience and is given in good faith to assist you. However, we reserve the right to update this information at any time without prior notice due to our ongoing research and development efforts. While we guarantee the consistent quality of our products, we cannot be held responsible for any losses or damages that may arise from their use if site conditions or the execution of work are not properly managed. This data sheet becomes invalid upon the publication of a new edition, and please contact us for the latest version. Please note that we do not provide any warranties regarding the results of our products in specific applications, as the storage, handling, and application of materials are factors beyond our control.

Contact Information

For immediate orders or enquires, contact our **24/7 support team at +91 8792919513 or enquiry@swadigroup.co.in**. For additional support options and resources, please visit our website at swadigroup.co.in