PERFORMANCE
CONSTRUCTION CHEMICALS

SWADI®
a step ahead...

Cementitious Tile Grout - CTG01

Polymer modified unsanded cement grout for tile/stone joints

Description

Swadi Cementitious Tile Grout - CTG01 is a polymer cement grout is based highly polymer enriched, water resistant joint filler, designed to fill joints between ceramic tiles, vitrified tiles, porcelain tiles and all types of natural & composite stones in exterior & interior situations.

Standard Compliance

Meets or exceeds EN 13888-1 CG2 F WA standard for Cementitious Grout.

Advantages

- High polymer enriched joint filler.
- Easy to mix & easy to apply.
- Water resistant suitable for swimming pools.
- Good bond strength.
- Non-shrink.
- Suitable for joint width of 1-6 mm.
- Available in more than 50 shades to match or contrast with the tile shades.

Technical Data

Joint width	1-6 mm
Pot life @ 27°c+2°c	45 minutes
Setting time	24 hours
Mixing ratio (part by wt.)	1:3 (approx. 350ml of water for 1kg)
Compressive strength	48 hours – 10KN
Specific gravity	1.5 grams/cc
Standard	EN 1388

Coverage

Consumption depends on joint width, size of tiles.
Refer to the theoretical coverage calculation below:

$$\frac{(\text{Tile length} + \text{Tile breadth}) \times \text{Tile thickness} \times \text{Joint width} \times \text{Wet density}}{(\text{Tile length} + \text{Joint width}) \times (\text{Tile breadth} + \text{Joint width})} = \text{kg/m}^2$$

Note: wet density – 1.80
All the dimensions are in mm.

Application Instructions

Substrate Quality / Pre-Treatment

Tile spaces must be clean and uncontaminated by oil or grease. Remove cement laitance, dust, and loosely adhering particles.

Mixing

Take pre-measured water in a clean mixing vessel. Add SWADI CEMENTITIOUS GROUT in the vessel and mix until a slump free smooth paste of uniform colour is obtained. If an electric drill mixer is used blend on a slow speed (less than 300rpm). Avoid entraining air by mixing at too high speed or by over mixing. Do not reconstitute the mixed grout by adding more water this will reduce the final strength.

Application

- Apply the grout to spaces between tiles diagonally using rubber trowel.
- After the grout sets for ~10 minutes, wipe up the excess grout with damp sponge from the tile surfaces.
- Run the sponge over the grout joints to get consistent, even-depth grout joints.
- Waiting time before foot traffic minimum 24 hours.

Cleaning

Clean the tools using water when the adhesive is still fresh. The hardened adhesive can be removed from tools mechanically.

Storage & Shelf Life

SWADI CEMENTITIOUS TILE GROUT has a shelf life of 12 months when stored in normal dry conditions.

Precautions

Keep out of reach of children. Wear suitable protective clothing, gloves and eyes/face protection. After contact with skin, wash immediately with plenty of clean water. In case of contact with eyes rinse immediately with plenty of clean water and seek medical advice.

Health & Safety

For further information, please consult the Material Safety Data Sheet (MSDS).

Condition of Sale

Sold subjects to the company's condition of sale which are available on request.

Packaging

1 kg pack & 10 kg box.

Storage and Handling Guidelines

The product should be stored in a dry, well-ventilated area, away from moisture, direct sunlight, and children, and in compliance with national regulations. Ensure the packaging is tightly sealed to prevent contamination or moisture ingress, and store it within the recommended temperature range of 5°C to 35°C. Handle the product with care, avoiding direct contact with skin and eyes, and wear appropriate protective equipment such as gloves and masks to prevent inhalation of dust. Use the product as per the instructions provided on the packaging for best results.

Environmental, Health, and Safety Information

For comprehensive information regarding the safe transportation, handling, storage, and disposal of this chemical product, please refer to the accompanying Safety Data Sheet (SDS). The SDS contains detailed information about physical properties, environmental impacts, toxicological hazards, and other safety-related factors. It is crucial to read the current SDS before using any product.

Disclaimer

The information provided in this datasheet is based on our extensive experience and is given in good faith to assist you. However, we reserve the right to update this information at any time without prior notice due to our ongoing research and development efforts. While we guarantee the consistent quality of our products, we cannot be held responsible for any losses or damages that may arise from their use if site conditions or the execution of work are not properly managed. This data sheet becomes invalid upon the publication of a new edition, and please contact us for the latest version. Please note that we do not provide any warranties regarding the results of our products in specific applications, as the storage, handling, and application of materials are factors beyond our control.

Contact Information

For immediate orders or enquires, contact our **24/7 support team at +91 8792919513 or enquiry@swadigroup.co.in.** For additional support options and resources, please visit our website at swadigroup.co.in

SWADI MINERALS AND CHEMICALS
an ISO 9001:2015 & ISO 14001:2015 certified company
Sy.no 70/1, Vishwaneedam post, Gollarahatti
Magadi main road, Bengaluru – 560091
Tel: +91 8884492928
Email: enquiry@swadigroup.co.in
Website: swadigroup.co.in

Product Data Sheet
Cementitious Tile Grout - CTG01
October 2025, Version 011.05.11000000000010

SWADI®
a step ahead...