PERFORMANCE
WATERPROOFING SYSTEMS

SWADI®
a step ahead...

Crack LOC+

Acrylic Polymer-Modified Cementitious Coating for General Waterproofing

Description

Swadi Crack Loc+ is a fiber-reinforced polymer crack-filling paste designed to be used both on interior and exterior masonry surfaces. it effectively fills and seals cracks up to 3mm wide. The product offers excellent bonding, ease of application, and best performance.

Where to Use

- Plastered wall cracks (interior & exterior)
- Shrinkage cracks and minor surface imperfections
- Non-structural cracks in concrete and masonry.

Advantages

- Strong crack sealing.
- Good adhesion to masonry surface.
- withstand surface stress without cracking.
- Zero VOC.

Technical Data

Appearance	Off-white fiber paste
Density	1.28 g/cm³
Solid Content %	>85 %
pH Value	8.0
Crack filling capacity	Up to 3mm width & 5mm depth
Full Cure	24 hours
Film formation	Non-shrink & load absrobing
Paint compatibility	Suitable for all types of emulsion and acrylic paints
Coverage	22 - 24 Running meter per 1 Kg (3mm wide and 5mm deep)

Application Instructions

Surface Preparation

Ensure the surface is clean, dry, and free from dust, oil, grease, and loose particles. Lightly moisten the area before application. For cracks wider than 0.5mm, widen them to 3mm using a cutter to form a V-groove. On internal surfaces, remove any existing POP, wall putty, or loose paint until the plaster is exposed. For better adhesion, apply Swadi Aquablend 90 Primer before filling the crack with Swadi Crack Loc+.

Application

Cut the crack to a depth of 3-5mm and width of 3mm using a chisel or putty knife to remove loose material, then clean thoroughly with a moist sponge, avoiding excess water. Apply Swadi Aqua blend 90 Primer along the crack using a brush or sponge and allow it to become tacky, not fully dry, before filling. Firmly press Swadi Crack Paste into the crack using a spatula or putty knife, ensuring it is well-compacted and level with the surface, preventing cavities or air bubbles. Let it dry for 24 hours for proper curing. Once fully dry, lightly sand the area for a smooth finish, then apply Swadi wall putty followed by primer and paint for a seamless appearance.

Precautions

- Not for cracks wider than 5mm or structural gaps.
- Avoid use on POP or painter's putty.
- Keep the container sealed after use.
- Allow 24 hours drying before putty or paint.

Shelf Life

Swadi Crack Loc+ has a shelf life of 12 months if kept in a dry store in unopened condition.

Packaging

Swadi Crack Loc+ is available in 500 grams & 1 Kg

Condition of Sale

Sold subject to the companies condition of sale which are available on request.

Storage and Handling Guidelines

Store in its original, tightly closed container in a cool, dry, and well-ventilated place away from sunlight and heat. Keep out of reach of children and food items. Avoid contact with eyes and skin; wear protective gear during use. Do not apply on wet surfaces or cracks

wider than 3 mm. Dispose of waste responsibly and avoid draining into water bodies.

Health, and Safety Information

SWADI Crack Loc+ is considered non-hazardous in regular usage; however, avoid contact with eyes or skin. Wear suitable protective dust mask, gloves and safety glasses. In case of contact with eyes, rinse for several minutes under running water.

For further information, please consult the Material Safety Data Sheet (MSDS).

Disclaimer

The information provided in this datasheet is based on our extensive experience and is given in good faith to assist you. However, we reserve the right to update this information at any time without prior notice due to our ongoing research and development efforts. While we guarantee the consistent quality of our products, we cannot be held responsible for any losses or damages that may arise from their use if site conditions or the execution of work are not properly managed. This data sheet becomes invalid upon the publication of a new edition, and please contact us for the latest version. Please note that we do not provide any warranties regarding the results of our products in specific applications, as the storage, handling, and application of materials are factors beyond our control.

Contact Information

For immediate orders or enquires, contact our **24/7 support team at +91 8792919513 or enquiry@swadigroup.co.in**. For additional support options and resources, please visit our website at swadigroup.co.in

SWADI MINERALS AND CHEMICALS
an ISO 9001:2015 & ISO 14001:2015 certified company
Sy.no 70/1, Vishwaneedam post, Gollarahatti
Magadi main road, Bengaluru – 560091
Tel: +91 8884492928
Email: enquiry@swadigroup.co.in
Website: swadigroup.co.in

Product Data Sheet
Crack LOC+
October 2025, Version 011.05.11000000000035

SWADI®
a step ahead...