PERFORMANCE
CONSTRUCTION CHEMICALS

SWADI®
a step ahead...

Epoxy Tile Grout - EG07

A high-performance, waterproof, and stain-resistant grout for tile joints

Description

Swadi Epoxy Tile Grout – EG07 is a high quality, resin based three-part epoxy grouting, comprising of Part A, Part B & Part C. The cured grout is staining free chemical resistant, hard wearing, hygienic & highly impervious. Swadi Epoxy Tile Grout is designed to fill joints, up to 10mm between ceramic tiles, vitrified tiles, porcelain tiles and all types of natural & composite stones in exterior & interior situations including swimming pools. Available in more than 32+ shades to match or contrast with the tile shades.

Advantages

- Three-part system.
- Easy to mix & apply.
- Hygienic.
- Chemical resistant.
- Zero water absorption.
- Excellent bond strength.
- Zero wastage.
- Ideal for swimming pools.

Technical Data

Recommended joint width	2-12 mm
Pot life at 27°C	45 minutes
Setting time 27°C	48 hours
Temperature resistance	Prolonged resistance 30°C ± 70°C : intermittent up to 100°C
Hardening time	4-8 hours
Water absorption	Nil
Specific gravity	1.75 grams/cc
Tensile adhesion (14 days)	Dry condition > 4.5 KN Wet condition > 3.6 KN
Compressive strength	> 60 Mpa
Shear strength	> 10 Mpa
Flexural strength	> 30 Mpa

Coverage

Shall depend primarily on joint width, joint depth & size of tiles approx. consumption can be derived by:
*Sp. Gravity: 1.80

$$\frac{(\text{Tile width} + \text{Tile length}) \times \text{Joint width} \times \text{Joint depth} \times \text{Sp. Gravity} = \text{kg/m}^2}{(\text{Tile width} + \text{Joint width}) \times (\text{Tile width} + \text{Joint width})}$$

Where to Use

- Walls & floors
- Interior & exterior
- Dry areas & wet areas
- Swimming pools

Application Instructions

Surface Preparation

Before commencing grouting, the adhesive bed must be set. Check the bed of tile that there are no voids under the tiles. Protect the open joints from contamination and ensure that they are clean and free of all dirt, dust and loose materials. Remove any dust, water & debris present on the surface of grout area.

Mixing

Take Swadi Epoxy tile grout into the mixing pail and mix thoroughly by a slow speed mixer (< 400 rpm) thoroughly until uniformly blended.

Preparation of mortar:

Mortar is prepared by mixing the base, hardener and filler given as a convenient single unit. Empty the entire contents of base and hardener into a clean vessel and mix thoroughly till both the liquids are completely blended. To this add the coloured filler material and mix till a lump free uniform paste is obtained. Mix the filler to the extent to make a stiff paste to work into the joints.

Application

Immediately pour the entire contents onto the working area. Use a plastic sheet as a drop cloth. Use standard epoxy grouting techniques to work the tile grout in the tile joints. Ensure that the entire joint is packed fully with the material. Remove the excess material from the joints before the material starts setting.

Epoxy Tile Grout - EG07

Application

- Use a rubber grout float, compact the epoxy grout into the joints ensuring that they are completely filled, remove the excess grout.
- Clean the tile surface with a sponge, after 12 - 24 hours clean the tile surface with water and soup solution to remove any stains.

Cleaning

Clean the tools using water when the adhesive is still fresh. The hardened adhesive can be removed from tools mechanically.

Storage & Shelf Life

Swadi Epoxy Tile Grout has a shelf life of 12 months when stored in normal dry conditions.

Health & Safety

For further information, please consult the Material Safety Data Sheet (MSDS).

Condition of Sale

Sold subjects to the company's condition of sale which are available on request.

Packaging

1 kg & 5 kg pail.

Storage and Handling Guidelines

The product should be stored in a dry, well-ventilated area, away from moisture, direct sunlight, and children, and in compliance with national regulations. Ensure the packaging is tightly sealed to prevent contamination or moisture ingress, and store it within the recommended temperature range of 5°C to 35°C. Handle the product with care, avoiding direct contact with skin and eyes, and wear appropriate protective equipment such as gloves and masks to prevent inhalation of dust. Use the product as per the instructions provided on the packaging for best results.

Environmental, Health, and Safety Information

For comprehensive information regarding the safe transportation, handling, storage, and disposal of this chemical product, please refer to the accompanying Safety Data Sheet (SDS). The SDS contains detailed information about physical properties, environmental impacts, toxicological hazards, and other safety-related factors. It is crucial to read the current SDS before using any product.

Disclaimer

The information provided in this datasheet is based on our extensive experience and is given in good faith to assist you. However, we reserve the right to update this information at any time without prior notice due to our ongoing research and development efforts.

While we guarantee the consistent quality of our products, we cannot be held responsible for any losses or damages that may arise from their use if site conditions or the execution of work are not properly managed. This data sheet becomes invalid upon the publication of a new edition, and please contact us for the latest version. Please note that we do not provide any warranties regarding the results of our products in specific applications, as the storage, handling, and application of materials are factors beyond our control.

Contact Information

For immediate orders or enquires, contact our **24/7 support team at +91 8792919513 or enquiry@swadigroup.co.in.** For additional support options and resources, please visit our website at swadigroup.co.in

SWADI MINERALS AND CHEMICALS
an ISO 9001:2015 & ISO 14001:2015 certified company
Sy.no 70/1, Vishwaneedam post, Gollarahatti
Magadi main road, Bengaluru – 560091
Tel: +91 8884492928
Email: enquiry@swadigroup.co.in
Website: swadigroup.co.in

Product Data Sheet
Epoxy Tile Grout - EG07
April 2025, Version 011.05.11000000000009

SWADI®
a step ahead...