PERFORMANCE
FLOORING SYSTEMS

SWADI®
a step ahead...

Evoshine Primer W11

Water Based Epoxy Primer

Description
Evoshine W11 is a two-component water base epoxy flooring primer, that allows the primer to penetrate the concrete substrate and seal the substrate. W11 contains specially formulated resins and hardeners which can withstand and seal damp surfaces.

Standard Compliance
Complies with standards ASTM D 2471, ASTM D - 638, ASTM D - 4541, ASTM D - 1640.

Where to Use
1.) Concrete or mortar surfaces 2.) Porous surfaces. 3.) Damp surfaces (<4% moisture). 4.) Primer for PU & acrylic range of waterproofing products.

Advantages
1.) Improves the adhesion of epoxy paint to the surface.
2.) Protects the surface from moisture and corrosion.
3.) Extends the life of the epoxy coatings

Technical Data

Type	Epoxy
Flash point	Non - flammable
Mixing ratio	1 part resin: 3 part hardener
Appearance base	Crystal clear
Appearance hardener	Pale yellow emulsion
Pot life ASTM D 2471	30 - 40 minutes
Water permeability	Nil
Tensile strength ASTM D - 638	>1.9 N/mm²
Pull of adhesion ASTM D - 4541	Passes upto 2 mPa
Surface dry ASTM D - 1640	8 hours
Tack free dry ASTM D - 1640	24 hours
Coverage	30 - 40 sqfts / 1 kg / 2 coats
Pack size	1.5 kg resin: 4.5 kg hardener
Shelf life	12 months

Substrate Requirements
Ensure the concrete floors are at least 28 days old with a moisture content below 4%. The substrate should have a minimum strength of 25mPa and be free from rising damp, ground water pressure, grease, oil, laitance, and any chemical substances.

Mixing
Pour part A & part B into a container and mix them using a suitable mixing paddle and mix for 2 minutes till the mix mass is homogeneous, mix under slow RPM.

Application
Apply 1-2 coats depends on substrate porosity, apply by a trowel / wiper / roller. Spread the material as per the coverage.

Curing
Cure time depends up on the ambient temperature & humidity, the moisture content of the substrate, thickness of the film, etc. High temperature and low humidity will accelerate the curing process.

Storage and Shelf life / Precautions / Disposal / Spillage
For further information please refer to the Material Safety Data Sheet.

Conditions of Sale
Sold subject to the company's conditions of sale which are available on request.

Storage and Handling Guidelines
The product should be stored in accordance with national regulations. It is essential to keep it in a cool,

well-ventilated area, away from heat, direct sunlight, sparks, and children. Please note that the product contains flammable solvents, so handle it with Page 5 of 5 care. To ensure proper curing, mix the resin and hardener according to the specified ratio. Once mixed, use the solution within its pot life to avoid premature hardening.

Environmental, Health, and Safety Information

For comprehensive information regarding the safe transportation, handling, storage, and disposal of this chemical product, please refer to the accompanying Safety Data Sheet (SDS). The SDS contains detailed information about physical properties, environmental impacts, toxicological hazards, and other safety-related factors. It is crucial to read the current SDS before using any product.

Disclaimer

The information provided in this datasheet is based on our extensive experience and is given in good faith to assist you. However, we reserve the right to update this information at any time without prior notice due to our ongoing research and development efforts. While we guarantee the consistent quality of our products, we cannot be held responsible for any losses or damages that may arise from their use if site conditions or the execution of work are not properly managed. This data sheet becomes invalid upon the publication of a new edition, and please contact us for the latest version. Please note that we do not provide any warranties regarding the results of our products in specific applications, as the storage, handling, and application of materials are factors beyond our control.

Contact Information

For immediate orders or enquires, contact our **24/7 support team at +91 8792919513 or enquiry@swadigroup.co.in**. For additional support options and resources, please visit our website at swadigroup.co.in

SWADI MINERALS AND CHEMICALS
an ISO 9001:2015 & ISO 14001:2015 certified company
Sy.no 70/1, Vishwaneedam post, Gollarahatti
Magadi main road, Bengaluru – 560091
Tel: +91 8884492928
Email: enquiry@swadigroup.co.in
Website: swadigroup.co.in

Product Data Sheet
Evoshine Primer W11
October 2025, Version 011.05.11000000000065

SWADI®
a step ahead...