PERFORMANCE
WATERPROOFING SYSTEMS

SWADI®
a step ahead...

Flash Fix 108

Superfast Water Stop Plugging Cement

Description

Swadi® Flash Fix 108 is a pre-mixed, chloride-free cementitious mortar supplied in a powder form. When mixed with clean water, it forms a fast-setting, hydraulically setting mortar for plugging leaks in concrete, rock, and masonry.

Standard Compliance

Complies with standards ASTM D 2471, IS 4031 (Part 6): 1988

Where to Use

1.)Concrete repairs: Patching and plugging leaks in concrete walls, floors, ceilings, and elements. 2.)Tunnels and underground structures: Sealing leaks in concrete and brick linings of tunnels, sewage systems, and access chambers. 3.)Pipelines: Plugging leaks around pipes and joints. 4.)Basements and foundations: Stopping water infiltration in basements and foundation walls.

Advantages

- Superfast setting for immediate water stops areas.
- Chloride free & non-toxic.
- Very low exothermic to minimize thermal cracking.
- Instant 5mpa strength.

Technical Data

Type	Immediate water stop cement.
Mixing ratio	18–21% water (≈180–210 ml per kg).
Appearance	Grey powder
Initial set time ASTM D 2471	2 minutes
Water permeability	Nil
Compressive strength IS 4031 (Part 6): 1988	2 hours – 5-8 MPa 28 days - 35 MPa

Application Instructions

Ensure the full extent and cause of the leak are identified in order to avoid any future issues. The concrete or whatever the surface is should be cut in a "V" shape around the leaking point. Clean the surface with water to remove all chippings, unsound particles, and loose particles. Mix the flashfix 108 with clean water to achieve a pasty consistency, preparing only small quantities due to its fast-setting time. Apply the mixture into the V-shaped cuts, starting from the outside and working towards the center to plug minor leaks. Hold the material in place by hand for 2-3 minutes. Once sealed and set, cut off any excess material to make it flush with the surface, and keep the surface damp. The hardening time is between 180–240 seconds at +25°C.

Important Considerations for SWADI Flash Fix 108 Application

• Make sure the surface is clean, free of debris, and roughened for better adhesion. • Mix only the amount of material you can consume within 2 minutes; avoid overmixing. • Press the material firmly into the repair area and hold until it sets. • Use cold water in warm conditions and warm water in cold conditions to adjust the setting time. • Wear protective gloves as the rapid setting may generate heat.

Cleaning

Tools and equipment should be washed with water immediately after use.

Shelf Life

12 months from the date of manufacture.

Health & Safety

For further information, please go through the Material Safety Data Sheet (MSDS).

Packaging

5 Kg bag.

Storage and Shelf life /Precautions /Disposal /Spillage

For further information please refer to the Material Safety Data Sheet.

Condition of Sale

Sold subject to the company's conditions of sale which are available on request.

Storage and Handling Guidelines

The product should be stored in accordance with national regulations. It is essential to keep it in a cool, well-ventilated area, away from heat, direct sunlight, sparks, and children. Please note that the product contains flammable solvents, so handle it with care. To ensure proper curing, mix the resin and hardener according to the specified ratio. Once mixed, use the solution within its pot life to avoid premature hardening.

Health, and Safety Information

SWADI Flash Fix 108 is considered on-hazardous in normal usage; however, avoid contact with eyes or skin. Wear suitable protective dust mask, gloves and safety glasses. In case of contact with eyes, rinse for several minutes under running water.

For further information, please consult the Material Safety Data Sheet (MSDS).

Disclaimer

The information provided in this datasheet is based on our extensive experience and is given in good faith to assist you. However, we reserve the right to update this information at any time without prior notice due to our ongoing research and development efforts. While we guarantee the consistent quality of our products, we cannot be held responsible for any losses or damages that may arise from their use if site conditions or the execution of work are not properly managed. This data sheet becomes invalid upon the publication of a new edition, and please contact us for the latest version. Please note that we do not provide any warranties regarding the results of our products in specific applications, as the storage, handling, and application of materials are factors beyond our control.

Contact Information

For immediate orders or enquires, contact our **24/7 support team at +91 8792919513 or enquiry@swadigroup.co.in**. For additional support options and resources, please visit our website at swadigroup.co.in

SWADI MINERALS AND CHEMICALS
an ISO 9001:2015 & ISO 14001:2015 certified company
Sy.no 70/1, Vishwaneedam post, Gollarahatti
Magadi main road, Bengaluru – 560091
Tel: +91 8884492928
Email: enquiry@swadigroup.co.in
Website: swadigroup.co.in

Product Data Sheet
Flash Fix 108
October 2025, Version 011.05.11000000000033

SWADI®
a step ahead...