PERFORMANCE
FLOORING SYSTEMS

SWADI®
a step ahead...

HardTop

A Super Quality Floor Hardeners

Description

SWADI HardTop is a ready - to - use powder that is factory - blended and quality - controlled. These materials are composed of high-density aggregates that are selected based on their shape and size, as well as their abrasion and wear resistance. Together, these aspects, along with the use of workability admixtures, produce a concrete surface that is easy to trowel.

Where to Use

Topping of monolithic floor subject heavy - duty use like in 1.) Warehouses. 2.) Service station. 3.) Garages. 4.) Workshops. 5.) Factory floors. 6.) Shopping malls and parking lots. 7.) Public areas.

Advantages

- Stronger impacts / wear resistance.
- Improve resistance to oil / greases.
- Cost effective surface hardener.
- Easy to clean, non - rusting.
- Forms monolithic bond with base concrete.
- Non - metallic and rust free.
- Protects against dust accumulation on floors.

Technical Data

Physical appearance	Cementitious powder
Coverage • Light traffic • Medium traffic • Heavy traffic	 3.0 - 3.5 kg / m² 4.0 - 5.0 kg / m² 6.5 - 7.0 kg / m²
Abrasion resistance	Treated concrete will give 150 - 225 % better abrasion resistance then control concrete
Coverage • Foot traffic • Light vehicle traffic • Full cure	 2 - 3 8 - 10 28
Bulk density, kg / l	1.55
Compressive strength - 28 days	60 - 65 N/mm²
Storage	Store in cool dry place, away from heat
Packing	Available in 30 kg moisture resistant bags
Shelf life	12 months in original un - opened sealed conditions
Note:	Cement or aggregates should never be added to SWADI HardTop material

Application Procedure

- Ensure that base concrete has minimum cement level of 300 kg of cement per cubic meter of concrete and a slump @ 50 – 75 mm.
- Ensure that compressive strength of concrete is 25 MPa minimal.
- Ensure that the thickness of surface is 15 cm minimum.
- Air entrant concrete is not suitable for dry shake hardener application.
- Use float to level surface. To remove excess / bleeding water, drag surface with a burlap or sack.
- After the concrete has stiffened somewhat, open the surface by floating with hand wood or power float.
- Ensure construction joints, expansion joints and floor joints are saw-cut only after 24 hours. When the slab has hardened, fill the joint with Sealants.

Surface Treatments

Penetration type surface treatments are recommended to give low porosity and dust proof property.

Packing

Available in 30 kg moisture resistant bags.

Storage

Store in cool dry place, under the shed, away from heat.

Shelf Life

12 months in original unopened sealed conditions.

Condition of Sale

Sold subjects to the company's condition of sale which are available on request.

Storage and Handling Guidelines

The product should be stored in accordance with national regulations. It is essential to keep it in a cool, well-ventilated area, away from heat, direct sunlight, sparks, and children. Please note that the product contains flammable solvents, so handle it with care. To ensure proper curing, mix the resin and hardener according to the specified ratio. Once mixed, use the solution within its pot life to avoid premature hardening.

Environmental, Health, and Safety Information

For comprehensive information regarding the safe transportation, handling, storage, and disposal of this chemical product, please refer to the accompanying Safety Data Sheet (SDS). The SDS contains detailed information about physical properties, environmental impacts, toxicological hazards, and other safety-related factors. It is crucial to read the current SDS before using any product.

Disclaimer

The information provided in this datasheet is based on our extensive experience and is given in good faith to assist you. However, we reserve the right to update this information at any time without prior notice due to our ongoing research and development efforts. While we guarantee the consistent quality of our products, we cannot be held responsible for any losses or damages that may arise from their use if site conditions or the execution of work are not properly managed. This data sheet becomes invalid upon the publication of a new edition, and please contact us for the latest version. Please note that we do not provide any warranties regarding the results of our products in specific applications, as the storage, handling, and application of materials are factors beyond our control.

Contact Information

For immediate orders or enquires, contact our **24/7 support team at +91 8792919513 or enquiry@swadigroup.co.in**. For additional support options and resources, please visit our website at swadigroup.co.in

SWADI MINERALS AND CHEMICALS
an ISO 9001:2015 & ISO 14001:2015 certified company
Sy.no 70/1, Vishwaneedam post, Gollarahatti
Magadi main road, Bengaluru – 560091
Tel: +91 8884492928
Email: enquiry@swadigroup.co.in
Website: swadigroup.co.in

Product Data Sheet
HardTop
October 2025, Version 011.05.11000000000064

SWADI®
a step ahead...