PERFORMANCE
CONSTRUCTION CHEMICALS

SWADI®
a step ahead...

Hydrophobic Fine Wall Putty

A True water-resistant fine putty, designed for interior & exterior walls & areas exposed to water flow.

Description

Swadi Hydrophobic Fine Wall Putty is a water-repellent, white cement–based putty for concrete or mortar walls and ceilings, suitable for both interior and exterior use. Its hydrophobic formulation resists moisture and efflorescence while providing excellent adhesion, even on slightly damp surfaces.

Swadi Hydrophobic Fine Wall putty prevents flaking or peeling & keeps walls protected & beautiful for long years.

Where to Use

- All types of plastered and concrete walls.
- Ceilings and soffits.
- Aerated lightweight concrete blocks (AAC blocks).
- Hollow concrete blocks and masonry surfaces.

Advantages

- Water-repellent and moisture-resistant formulation.
- Excellent efflorescence resistance.
- Strong adhesion to concrete and plaster surfaces.
- Smooth, uniform finish on rough walls.
- Reduces paint consumption and improves paint adhesion.
- Suitable for all types of interior and exterior paints.

Technical Data

Appearance	White fine powder
Compressive strength (N/mm²) @ 28 Days	~ 8.0
Setting time (minutes) Initial Final May slightly vary depending on temperature & humidity	 4 to 6 hours 12 to 24 hours
Pot life	2 to 3 hours (Temp 30°C, H 65%)
Dry for recoat	6 to 8 hours (temp 30°C, H 65%)
Tensile adhesion ASTM D4541	0.8 N/mm²
Water drop test 1 ml on sanded surface	18 min

Application Instructions

Surface Preparation

- Ensure that the surface on which you apply putty is plastered or made with the cementitious material.
- Give separate treatments or remedial measure for dampness, efflorescence, fungus, leakages on your wall.
- Ensure that the surface is totally clean. It should be free from dust, loose particles, residual paints, grease, oil or any other contamination.
- Remove all loose or poorly adhering material from the surface by rubbing down with help of sandpaper or with wire brush or with putty blade and after that wipe it out.
- Wet the wall with sufficient quantity of clean water and allow them to dry before applying Fine putty on wall. Ensure that surface is just wet. Over wetting results in accumulation of water on a surface should be avoided. This ensures higher bonding of strength, easy workability & higher coverage with the surface.

Mixing

- Mix the Swadi Hydrophobic Fine Wallputty with 35 to 40 % clean water slowly to make a paste.
- Prepare the mixing with mechanical mixer for 10 - 15 minutes till a uniform paste is formed. This will help in easy application, obtaining more coverage and smooth shade.
- Only mix a required quantity which can be used within 2 - 3 hours of mixing with water.

Application

- After thoroughly mixing, apply the first coat of putty in a vertical “bottom to top” manner by using a putty blade/spatula/ trowel or any finishing tool. This would ensure minimum wastage.
- Allow the first coat to dry completely for a minimum of 4 to 6 hours. Once the first coat is dry, just rub the surface gently with sandpaper in order to remove the loose particle.
- After drying the second coat remove any type of marks with the help of moist sponge or rub the surface very gently with the putty blade. Leave the surface to dry 8 - 12 hours preferably.
- Total thickness of the coat should be limited to 1.5 mm maximum.

- It is not necessary to rub the surface. However, if at all there is need to remove unevenness before applying any kind of paint. Gently level the surface with fine emery paper of not less than 500 numbers to get a glossy white surface.

Precautions

- Do not apply the material without pre - wetting the surface for the 1st coat.
- Ensure the material is mixed homogeneously with water and allowed to stand for 5-10 min before application.
- Do not sand the material vigorously with Emery Paper otherwise it will reduce the strength of the material.
- Do not apply the material to fill cracks.
- Though the material is non - toxic, care should be taken to avoid dust inhalation while mixing and handling.

Coverage

- The coverage of Swadi Hydrophobic Wall Putty on a smooth, normal mortar wall is approximately 10-15 sq. ft. per kg for a total thickness of up to 1.5 mm in two coats. Actual coverage may vary depending on the surface texture, porosity, and application method.

Storage

Stored in a dry place for best results use it with in 12 months from date of manufacture.

Condition of Sale

Sold subject to the Company's conditions of sale which are available on request.

Storage and Handling Guidelines

The product should be stored as per national regulations in a cool, dry, and well-ventilated area, away from direct sunlight and extreme temperatures. Keep it out of reach of children. Ensure the bag is tightly sealed when not in use. Handle with care to avoid contamination. Use as per the recommended guidelines.

Health, and Safety Information

Swadi Hydrophobic Fine wallputty is considered on-hazardous in normal usage; however, avoid contact with eyes or skin. Wear suitable protective dust mask, gloves and safety glasses. In case of contact with eyes, rinse for several minutes under running water.

For further information, please consult the Material Safety Data Sheet (MSDS).

Disclaimer

The information provided in this datasheet is based on our extensive experience and is given in good faith to assist you. However, we reserve the right to update this information at any time without prior notice due to our ongoing research and development efforts. While we guarantee the consistent quality of our products, we cannot be held responsible for any losses or damages that may arise from their use if site conditions or the execution of work are not properly managed. This data sheet becomes invalid upon the publication of a new edition, and please contact us for the latest version. Please note that we do not provide any warranties regarding the results of our products in specific applications, as the storage, handling, and application of materials are factors beyond our control.

Contact Information

For immediate orders or enquires, contact our **24/7 support team at +91 8792919513 or enquiry@swadigroup.co.in.** For additional support options and resources, please visit our website at swadigroup.co.in

SWADI MINERALS AND CHEMICALS
an ISO 9001:2015 & ISO 14001:2015 certified company
Sy.no 70/1, Vishwaneedam post, Gollarahatti
Magadi main road, Bengaluru – 560091
Tel: +91 8884492928
Email: enquiry@swadigroup.co.in
Website: swadigroup.co.in

Product Data Sheet
Hydrophobic Fine Wallputty
October 2025, Version 011.05.10900000000018

SWADI®
a step ahead...