PERFORMANCE
CONSTRUCTION CHEMICALS

SWADI®
a step ahead...

Ready to Plast - RTP07

Description

Swadi Ready to Plast - RTP07 is a high-quality dry premix plaster suitable for all types of concrete surfaces, including cast-in-situ concrete, precast panels, clay bricks, concrete blocks (solid and hollow), AAC blocks (Aerated Autoclaved Concrete), fly ash bricks, and other cement-based substrates. It is a premix of graded sand and cement, specially designed with polymers that combine to give high strength and stability. Ready to Plaster is used for external, internal, and ceiling rendering, offering rapid application, a smooth finish, and consistent quality throughout the plastering process.

Advantages

- Economical and ready to use for plaster.
- Saves labor costs and time.
- Eliminates improper grading.
- Reduced rebound loss.
- Excellent durable & eco friendly.
- Increases yield and saves money.
- To increase the rates of production at the site work.
- Crack resistance and non - shrink.
- It avoids silt or mud which deteriorates plaster quality.
- Thickness of layer can be plastered from 6 mm to 15 mm.
- It ensures quality plastering and enhances durability and Eco friendly.

Technical Data

Colour	Grey / white
Binder	Portland cement + polymers
Fine aggregate	Well graded sand (zone III and zone IV)
Water requirement	7 to 8 litres per 40 kg (18 - 20%).
Pot life	Approx. 120 min
Compressive strength for 28 days	>12 N/mm²
Coverage	1.6 kg / sqm / mm
Packaging	40 kgs HDPE laminated bag

Surface Preperation

For cast-in-situ concrete, Mivan surfaces, or any smooth concrete substrate, either a bonding slurry coat or mechanical hacking is mandatory to create proper adhesion of Swadi Ready to Plast - RTP07.

Hacking Application:

- The surface must be mechanically hacked or roughened to develop a sufficient mechanical key. This can be done using a chipping tool, needle gun, or similar equipment.

Slurry Coat Application:

- Prepare a bonding slurry by mixing (1 Part SBR : 4 Parts Cement : 7 Parts Sand). Mix well to form a lump-free slurry and apply a thin, even coat to the prepared surface. Allow it to become completely dry before proceeding with plaster application.

In both cases, make sure the surface is clean, free from dust, oil, and loose particles, and in a saturated surface dry (SSD) condition before applying the plaster.

Mixing

Use the mechanical mixer for uniform mixing. Add 7 to 8 litres of water for 40 kgs bag into Single Bucket and mix for 3 to 5 min. After mixing leave the wet Plaster for 2 to 3 minutes to dissolve the additives.

Curing

Non-Curing, curing can be done after 24 hours for 2-3 times a day, continue for 5-7 days to achieve more strength. In high humid condition one can reduce the frequency per day.

Important Considerations

- Apply only on vertical or ceiling surfaces without mechanical vibration.
- Not suitable for use as a concrete repair material.
- Do not apply in water-submerged areas (e.g., tanks, sumps).
- Pre-wet highly absorbent substrates like AAC blocks before plastering.
- Ensure the surface is clean, dry, stable, and properly cured before application.

Storage & Shelf Life

12 months from date of manufacture, when stored in dry conditions.

Condition of Sale

Sold subject to the company's condition of sale which are available on request.

Storage and Handling Guidelines

The product should be stored in accordance with local regulations. Store in a cool, dry, and well-ventilated area, away from direct sunlight, moisture, and sources of water ingress. Keep bags tightly sealed and stacked on pallets or raised platforms to avoid contact with damp surfaces. Protect from rain, humidity, and extreme heat. Keep out of reach of children.

Use clean water and mix only the quantity required for immediate use. Do not retemper (add water again) once the material has started setting. Apply the mixed plaster within its pot life to ensure proper workability and strength development.

For further information, please consult the Material Safety Data Sheet (MSDS).

Disclaimer

The information provided in this datasheet is based on our extensive experience and is given in good faith to assist you. However, we reserve the right to update this information at any time without prior notice due to our ongoing research and development efforts. While we guarantee the consistent quality of our products, we cannot be held responsible for any losses or damages that may arise from their use if site conditions or the execution of work are not properly managed. This data sheet becomes invalid upon the publication of a new edition, and please contact us for the latest version. Please note that we do not provide any warranties regarding the results of our products in specific applications, as the storage, handling, and application of materials are factors beyond our control.

Contact Information

For immediate orders or enquires, contact our **24/7 support team at +91 8792919513 or enquiry@swadigroup.co.in**. For additional support options and resources, please visit our website at swadigroup.co.in

SWADI MINERALS AND CHEMICALS
an ISO 9001:2015 & ISO 14001:2015 certified company
Sy.no 70/1, Vishwaneedam post, Gollarahatti
Magadi main road, Bengaluru – 560091
Tel: +91 8884492928
Email: enquiry@swadigroup.co.in
Website: swadigroup.co.in

Product Data Sheet
Ready to Plast - RTP07
October 2025, Version 011.05.11000000000015

SWADI®
a step ahead...