PERFORMANCE
FLOORING SYSTEMS

SWADI®
a step ahead...

SL Primer

High Performance Adhesion Primer for Masonry Surface

Description

SL Primer is a high-performance, concentrated acrylic-based primer formulated with advanced polymer dispersion technology. It is engineered to enhance the adhesion of cementitious underlayment's, self-leveling compounds, tile adhesives, and other construction materials on porous and absorbent concrete surfaces. Its advanced polymer system improves substrate penetration, optimizes surface porosity, and forms a cohesive interface that prevents rapid moisture absorption, ensuring strong mechanical bonding between layers.

Advantages

1.) Advanced polymer system.
2.) Optimized surface porosity.
3.) Prevents rapid moisture absorption.
4.) Alkali-Resistant formulation.
5.) Strong mechanical bond between cementitious layers.
6.) Eco-Friendly & Sustainable.

Technical Data

Base	Modified polymer
Solid	40% +2
Viscosity	100 Cps
pH	8 - 9
Appearance	Milky white

Application Instructions

Surface Preparation

The surface must is sound and free from dust, dirt and debris and other foreign materials. Entire cracks should be treated with SL Primer Mixer with cement (cement 2: primer 1: Sand 1/2).

Consumption - Dosages and Mixing

1.) Absorbent surface: 1 primer : 1 water
2.) Semi-absorbent surface: 1 primer : 0.5 water
3.) Non-absorbent surface: Direct primer

Application

SL-PRIMER enhances the adhesion of cementitious floor leveling compounds, self-leveling mortars, and tile adhesives to a wide range of absorbent and non-absorbent surfaces. It is suitable for applications on plywood, sand/cement screeds, concrete, and cement mortar, as well as non-absorbent substrates such as Kota stone, quarry tiles, and IPS flooring. Additionally, it is also recommended for use in waterproofing applications, repair mortars, and protective coatings.

Storage and Shelf Life

Store in a cool, dry place, out of direct sunlight and away from all sources of ignition. Storage areas must be well ventilated, store between 5°C and 30°C. Shelf life is up to 9 months when stored in original, unopened containers, under the above motioned conditions.

Conditions of Sale

Sold subject to the company's conditions of sale which are available on request.

Storage and Handling Guidelines

The product should be stored in accordance with national regulations. It is essential to keep it in a cool, well-ventilated area, away from heat, direct sunlight, freezing conditions, and out of reach of children. Ensure the container is tightly sealed when not in use to prevent contamination and evaporation. Although SL PRIMER is water-based and non-flammable, handle it with care to avoid spillage. Protect the product from extreme temperatures to maintain its effectiveness. Stir thoroughly before use to achieve uniform consistency. Once diluted or opened, use the product within the recommended timeframe to ensure optimal performance.

Environmental, Health, and Safety Information

For comprehensive information regarding the safe transportation, handling, storage, and disposal of this chemical product, please refer to the accompanying Safety Data Sheet (SDS). The SDS contains detailed

information about physical properties, environmental impacts, toxicological hazards, and other safety-related factors. It is crucial to read the current SDS before using any product.

Disclaimer

The information provided in this datasheet is based on our extensive experience and is given in good faith to assist you. However, we reserve the right to update this information at any time without prior notice due to our ongoing research and development efforts. While we guarantee the consistent quality of our products, we cannot be held responsible for any losses or damages that may arise from their use if site conditions or the execution of work are not properly managed. This data sheet becomes invalid upon the publication of a new edition, and please contact us for the latest version. Please note that we do not provide any warranties regarding the results of our products in specific applications, as the storage, handling, and application of materials are factors beyond our control.

Contact Information

For immediate orders or enquires, contact our **24/7 support team at +91 8792919513 or enquiry@swadigroup.co.in**. For additional support options and resources, please visit our website at swadigroup.co.in

SWADI MINERALS AND CHEMICALS
an ISO 9001:2015 & ISO 14001:2015 certified company
Sy.no 70/1, Vishwaneedam post, Gollarahatti
Magadi main road, Bengaluru – 560091
Tel: +91 8884492928
Email: enquiry@swadigroup.co.in
Website: swadigroup.co.in

Product Data Sheet
SL Primer
October 2025, Version 011.05.11000000000053

SWADI®
a step ahead...