PERFORMANCE
CONSTRUCTION CHEMICALS

SWADI®
a step ahead...

Wall Putty Coarse - WCP09

Description

Swadi Coarse Wall Putty is water resistant white cement-based putty can be used on concrete/Mortar walls (internal and External) and ceilings. SWADI Course putty binds strongly with the base, even if the surface is damp, it forms a strong protective base. SWADI Course putty fills up the fine pores in the walls and ceiling and provides a white, smooth, and dry surface. SWADI Course putty offers you total protection against flaking; you are assured of a good looking home for years to come

Advantages

- Excellent efflorescence resistance.
- Smooth and uniform with excellent finish on rough surface.
- Good adhesion and tensile strength.
- Highly durable & excellent compressive strength.
- Free from heavy metals like lead, mercury, and chromium.
- Excellent UV resistant and helps in reduction in cracking.

Technical Data

Form	White coarse powder
Pot life of thinned material	2 to 3 hours (Temp 30°C, H 65%)
Number of coats required	2 coats
Dry for recoat	4 to 5 hours (temp 30°C, H 65%)
Compressive strength (N/mm²) @ 28 days	> 9.0
Bulk density	1.77
Volatile Organic Compounds (V.O.C.)	Nill
Recommended thickness (mm)	2 - 5 mm per each coat
Recommended surface areas	Sand / cement, asbestos, mivan plaster, normal plasters, and brick walls.

Application Instructions

Surface Preparation

Clean the surface of any loose particles, dirt, grease, and traces of foreign material by using sand paper/chipping/ water blasting. In case there are loose plastered areas, remove the defective material and re-plaster. If there are any cracks, repair the same by using putty or Swadi crack filling paste based on the surface type. The surface must be moistened with water and all the excess water must be drained off.

Application Procedure

Mix the powder with clean water, 35-40% by volume. Stir the mixture continuously by using an electric stirrer or by hand to obtain a homogenous, lump-free paste. Allow the mixture to stand for about 5-10 minutes. Remix the paste once again, before use. Using a steel trowel/blade, apply the prepared mix to a thickness of about 2mm – 5mm as required. Level and smoothen the surface as you apply. Slightly cure the first coat once it dries and continue with the second coat once the first coat is fully dried and set. The thickness of each coat should not be less than 2mm. sand the surface if required.

Cleaning

Tools and equipment should be washed with water immediately after use.

Shelf Life

Coarse Putty - WCP09 has a shelf life of 7 months if kept in a dry store in unopened condition

Packaging

Coarse Putty is available in 40 kg bag.

Condition of Sale

Sold subject to the company's condition of sale which are available on request.

Storage and Handling Guidelines

The product should be stored in accordance with national regulations. It is essential to keep it in a cool, well-ventilated area, away from heat, direct sunlight, sparks, and children. Please note that the product contains flammable solvents, so handle it with care. To

ensure proper curing, mix the resin and hardener according to the specified ratio. Once mixed, use the solution within its pot life to avoid premature hardening.

Environmental, Health, and Safety Information

For comprehensive information regarding the safe transportation, handling, storage, and disposal of this chemical product, please refer to the accompanying Safety Data Sheet (SDS). The SDS contains detailed information about physical properties, environmental impacts, toxicological hazards, and other safety-related factors. It is crucial to read the current SDS before using any product.

Disclaimer

The information provided in this datasheet is based on our extensive experience and is given in good faith to assist you. However, we reserve the right to update this information at any time without prior notice due to our ongoing research and development efforts. While we guarantee the consistent quality of our products, we cannot be held responsible for any losses or damages that may arise from their use if site conditions or the execution of work are not properly managed. This data sheet becomes invalid upon the publication of a new edition, and please contact us for the latest version. Please note that we do not provide any warranties regarding the results of our products in specific applications, as the storage, handling, and application of materials are factors beyond our control.

Contact Information

For immediate orders or enquires, contact our **24/7 support team at +91 8792919513 or enquiry@swadigroup.co.in**. For additional support options and resources, please visit our website at swadigroup.co.in

SWADI MINERALS AND CHEMICALS
an ISO 9001:2015 & ISO 14001:2015 certified company
Sy.no 70/1, Vishwaneedam post, Gollarahatti
Magadi main road, Bengaluru – 560091
Tel: +91 8884492928
Email: enquiry@swadigroup.co.in
Website: swadigroup.co.in

Product Data Sheet
SwadiFix TA01
October 2025, Version 011.05.11000000000017

SWADI®
a step ahead...