PERFORMANCE
CONSTRUCTION CHEMICALS

SWADI®
a step ahead...

Anchor Tile Grip

High Performance, Solvent Free Adhesion Primer for Smooth and Non-Absorbent Surfaces

Description

Swadi Anchor Tile Grip is a ready-to-use, solvent-free primer formulated with synthetic resins in water dispersion and selected fine aggregates, designed to enhance adhesion on smooth or low-absorbent substrates. It creates a highly textured, rough surface that provides an excellent key for tile adhesives, self-levelling compounds, screeds, and renders.

Swadi Anchor Tile Grip is specially developed to ensure strong bonding over difficult substrates such as ceramic, porcelain tiles, terrazo, natural stones, plasterboard, and painted surfaces. Once dry, the coating forms a durable, water-resistant adhesive film that improves mechanical anchoring of subsequent layers.

The product is easy to apply by brush or roller, dries quickly, and is suitable for both interior and exterior applications. Its formulation is non-flammable, VOC-compliant, and safe for use in enclosed spaces.

Where to Use

1.) Existing ceramic tiles, porcelain tiles, terrazzo, and natural stone.
2.) Epoxy or polyurethane resin coatings.
3.) Smooth or sealed concrete.
4.) Plasterboard, cement boards, and fiber cement panels.

Benefits

1.) Excellent adhesion on smooth and non-absorbent surfaces like tiles, stone, and resin floors.
2.) Creates a rough and grippy texture.
3.) Quick drying allows for overlay with adhesives or compounds within 1 hour.
4.) Solvent free and low VOC.
5.) Creates a Water-resistant film once dry.
6.) Reduces risk of delamination.

Technical Data

Consistency	Creamy liquid
Colour	Grey
Density (g/cm³)	Approx. 1.45 g/cm³
pH	8.0
Solid content ASTM 2369	80%
Dry time	30 - 60 minutes
Overlay time	60 minutes

Application Instructions

Surface Preparation

- Ensure the substrate is clean, dry, structurally sound, and free from dust, grease, oil, laitance, loose particles, or any other contaminants.
- On existing floors, check for proper adhesion. Remove wax, old adhesive residues, paint, or polish using a suitable cleaner or mechanical abrasion.
- For glossy or smooth tiles, degrease the surface thoroughly before application.
- Repair cracks, holes, or damaged areas with appropriate repair mortars.
- Do not pre-wet the surface before applying the primer.

Application Procedure

- Stir the product well before use.
- Apply using a brush or roller in an even coat over the prepared surface.
- Allow the primer to dry for 15 to 60 minutes, depending on substrate absorbency, ambient temperature, and humidity.
- Once dry, proceed with the application of cementitious adhesives, renders, or self-leveling compounds.
- For particularly smooth or dense surfaces (e.g., epoxy or PU coatings), ensure the previous layer is completely dry and not older than 24 hours before application.
- A second coat can be applied if necessary, especially after long intervals or over critical surfaces.

Anchor Tile Grip

Important Considerations for SWADI Anchor Tile Grip Application

- Product is ready-to-use – do not dilute.
- Not suitable for areas with rising damp or surfaces that are continuously immersed in water.
- Do not use on absorbent surfaces like screeds or concrete – for such cases, use a more suitable primer like Swadi SL Primer.
- Ensure good ventilation during application and drying.

Coverage

Anchor Tile Grip: 1 Kg will cover 40 - 50 Sqfts
(Coverage might vary depending on the absorption of the substrate).

Shelf Life

Anchor Tile Grip has a shelf life of 12 months if kept in a dry store in unopened condition.

Packaging

Anchor Tile Grip is available in 5 Kg Pack.

Condition of Sale

Sold subject to the company's condition of sale which are available on request.

Cleaning

Tools and equipment should be washed with water immediately after use.

Storage and Handling Guidelines

The product should be stored as per national regulations in a cool, dry, and well-ventilated area, away from direct sunlight and extreme temperatures. Keep it out of reach of children. Ensure the container is tightly sealed when not in use. Handle with care to avoid contamination. Stir well before use and apply as per the recommended guidelines.

Environmental, Health, and Safety Information

For comprehensive information regarding the safe transportation, handling, storage, and disposal of this chemical product, please refer to the accompanying Safety Data Sheet (SDS). The SDS contains detailed information about physical properties, environmental impacts, toxicological hazards, and other safety-related factors. It is crucial to read the current SDS before using any product.

Disclaimer

The information provided in this datasheet is based on our extensive experience and is given in good faith to assist you. However, we reserve the right to update this information at any time without prior notice due to our ongoing research and development efforts. While we guarantee the consistent quality of our products, we cannot be held responsible for any losses or damages that may arise from their use if site conditions or the execution of work are not properly managed. This data sheet becomes invalid upon the publication of a new edition, and please contact us for the latest version. Please note that we do not provide any warranties regarding the results of our products in specific applications, as the storage, handling, and application of materials are factors beyond our control.

Contact Information

For immediate orders or enquires, contact our **24/7 support team at +91 8792919513 or enquiry@swadigroup.co.in**. For additional support options and resources, please visit our website at swadigroup.co.in

SWADI MINERALS AND CHEMICALS
an ISO 9001:2015 & ISO 14001:2015 certified company
Sy.no 70/1, Vishwaneedam post, Gollarahatti
Magadi main road, Bengaluru – 560091
Tel: +91 8884492928
Email: enquiry@swadigroup.co.in
Website: swadigroup.co.in

Product Data Sheet
Anchor Tile Grip
October 2025, Version 011.05.11000000000011

SWADI®
a step ahead...