

Function Hooks: Core Architecture

Alice Poteat · August 2026 · Anthropic

1 A Module of Hooks

- 1.1 Anatomy
- 1.2 Vocabulary

2 Algebra

- 2.1 Order Is Nesting
- 2.2 Five Placements
- 2.3 Who Orders the Plugins

3 Events

- 3.1 The Event Object
- 3.2 Render Events

4 The Engine Interface

- 4.1 The Fold
- 4.2 The Shape

5 Enterprise Management

6 Miscellanea

- 6.1 Matchers
- 6.2 The Bottom Hook
- 6.3 Recursion
- 6.4 Philosophy

1. A Module of Hooks

Hooks live in a `hooks.json` file, today of four extant types: `command`, `prompt`, `agent`, and `http`.

We put forward a fifth kind, the *function*: `hooks.json` may also name a module, a file with extension `.js`, `.ts`, `.jsx` or `.tsx` beside it in the plugin's `hooks/` directory. Functions compose, giving plugins a richer interface than commands can, fulfilling the dream of visual extensibility. A shell hook is a contract with an environment; a function hook is a contract with the engine. We hoist OS-integration and cross-surface complexity into `$` so that plugin authors can focus principally on the business and presentation logic inherent to their problem.

A hook today, from the public documentation:

```
{ "hooks": {  
  "PreToolUse": [  
    { "matcher": "Bash",  
      "hooks": [ { "type": "command", "command": "./hooks/block-rm.sh" } ] } ] } }
```

The same hook-set as a function. In `hooks/hooks.json`, one new key beside any entries above:

```
{ "modules": [ "./my-hooks.ts" ] }
```

In `hooks/my-hooks.ts`, one may register their hook sequence via the on callback registrar:

```
1 export function register(on) {
2   ...
3   on("tool.call", ($, e, next) => {
4     if (e.tool === "Bash" && e.command == "rm -rf /")
5       return { deny: "Destructive command blocked by hook" }
6     return next(e)
7   })
8   ...
9 }
```

Listing 1: The same hook as a function.

We provide narrow, strict typings for `on`, `$`, `e`, etc. The literal type of the provided hook type e.g. `"tool.call"` narrows the callback appropriately. We as well offer a matcher between the event and the hook for convenience (§6.1), based on a general substructural pattern-matcher.

1.1 Anatomy

We call this file a plugin's *hooks-module*. It exports one function, `register(on, options)`, which registers the plugin's hooks such that we know the events a plugin hooks before any hook runs: `claude plugin validate` lists them. The plugin's manifest and folder are the same; `command`, `prompt`, `agent` and `http` hooks `hooks.json` are kept running beside it. Options are sourced and configured through the extant plugin-level mechanism (i.e. `userConfig`).

1.2 Vocabulary

term	meaning
plugin	The discrete unit of installation, management, and discovery: a manifest and its skills, agents, MCP servers and hooks. We avoid perturbing this layer at all.
hooks-module	The <code>.js</code> or <code>.ts</code> file under <code>hooks/</code> that a plugin's <code>hooks.json</code> names in modules.
hook	A function registered on an event. Every hook has the signature <code>(\$, e, next)</code> .
event	An invoking of a method on <code>\$</code> , such as <code>\$.tool.call</code> . Hooks are registered on events; invoking this method runs the corresponding hook-stack, sans recursion (§6.4).

term	meaning
\$ / engine interface	The engine interface, i.e. the set of affordances we give to plugins; Its methods are always <code>\$.noun.event (\$.tool.call, \$.ui.log)</code> ; every method is a hookable event.

2. Algebra

A hook is Koa-style middleware: it reifies an endomorphic continuation. Every hook has the signature $(\$, e, next) \Rightarrow R \mid \text{Promise}\langle R \rangle$, where R is the event's result. This leads to easy folding.

\$	The engine interface : the state a hook may read and the side effects it may cause. The broad, extensible, immutable affordance surface. The world by any other name.
e	The event : the argument of the method on \$, a plain immutable value; each hook receives it and passes it, possibly rewritten, to next. A desideratum to be made real.
next	The continuation : this dispatch, as the host built it for this hook. Called, it runs the next hook registered on this event and returns a promise of the result of the rest of the chain; a hook may call it once, many times, or not at all, and may optionally be asynchronous. It also carries <code>next.signal</code> and <code>next.is</code> (§3.1), for advanced use-cases.

2.1 Order Is Nesting

An installation of Claude Code has a sequence of plugins registered, while each plugin registers a sequence of hook callbacks. A hook registered on a given event has a registration order, which dictates composition. A sequence $\text{on}(X, A), \text{on}(X, B), \text{on}(X, C)$ folds to $X = A(B(C(\perp)))$: plugins registered earlier sit “above” and plugins registered later “beneath” (on $\perp$, see §6.2).

As a matter of structure, earlier registration grants a plugin more authority since it wraps more. Core plugin(s) that specify default behavior are registered last and thus control the least.

$$X = A \circ B \circ C \circ \text{core} = A(B(C(\text{core}(\perp))))$$




Figure 1: Four hooks on one event. Each bar is a hook, shaded while it runs and empty while it waits on next.

2.2 Five Placements

Every callback decides where its logic runs relative to the point where the action happens; that point is the invocation of the last-registered callback, commonly a core plugin. Five forms, each on `tool.call`; some further configurations are expressible using standard promise rules.

placement	what the hook does	on <code>tool.call</code>
before	Do the work, then let the rest of the chain run after.	<code>\$.ui.log("about to run " + e.tool); return next(e)</code>
after	Execute the action first, then access its result by awaiting the promise.	<code>const result = await next(e); \$.ui.log(e.tool + " ran"); return result</code>
during	Start the rest of the chain and work alongside it, via floating the below promise.	<code>const pending = next(e); \$.ui.log("running " + e.tool); return pending</code>
instead	Override everything below.	<code>return { deny: "no tools allowed" }</code>
modifying	Forward a modified event.	<code>return next({ ...e, timeout: 30 })</code>

One event therefore serves where command hooks needs a pre-event and a post-event, and a hook must assume that any hook above it may change its result or never call it; more importantly, this mechanism gives the affordance for more flexible structures of concurrency.

2.3 Who Orders the Plugins

The list is ordered by plugin: the plugins an administrator put first, then the plugins in dependency order, then the plugins an administrator put last. Within one plugin, hooks keep the order in which they were registered. Prepending and appending plugins is the organization's

management strategy, and it's itself plugin-shaped: which team gets which plugins, and which plugins may load at all, are hooks on the events that register plugins, so an allowlist or a denylist is a plugin an organization puts first (§5). Controls thus naturally arise.

3. Events

3.1 The Event Object

The event is the method's argument and nothing else. `e` on `tool.call` is what `$.tool.call` was called with: the tool and its arguments, as own fields, so `$.tool.call(e)` is the same object a hook receives. Events are immutable plain values: to modify, you must pass next a copy with a changed field, as the *modifying* row of §2.2 does. What the dispatch itself provides is on `next`:

<code>next(e)</code>	Runs the rest of the chain with <code>e</code> and resolves to the event's final result.
<code>next.signal</code>	Tells any hook when the event is done or has been aborted: an <code>AbortSignal</code> , one per dispatch, that fires when the whole chain has returned or cancelled, so that the hook can stop any floating jobs or work.
<code>next.is(type, e)</code>	Whether this dispatch is the specified event; a type predicate, so under <code>*</code> it narrows <code>e</code> to that specific event's argument (§6.3). Singularly useful for <code>*</code> .
<code>next.event</code>	The name of this event, for a hook on <code>*</code> to log or switch on; <code>next.is</code> is the same fact as a type predicate, to allow for a type-narrowing on <code>next</code> itself.
<code>next.origin</code>	The plugin whose hook raised this dispatch, or engine; useful for logging.

3.2 Render Events

Drawing is an `ui.render` event, hooked and matched like others: `on("ui.render", { component: "AskUserQuestion" }, ...)`. For remote surfaces, this can be considered a sort of SSR HoC stack.

Where possible we provide JSX reconciliation:

```
1 on("ui.render", { component: "ToolUse" }, async ($, e, next) => {
2   const { Row, Badge } = $.ui.resolve(e)
3   const rendered = await next(e)
4   return (
5     <Row>
6       {rendered}
7       <Badge text={`${e.props.output.length} chars`} />
8     </Row>
9   )
10  })
```

Listing 2: A render hook wrapping the engine's rendering of a ToolUse.

4. The Engine Interface

4.1 The Fold

The engine builds `$` once, at startup, by running one more chain: `engine.create`. Its `⊥` returns the empty table; the core plugin, registered last, is the step that adds the primitives (files, network, model, terminal, permissions), and every other step adds its own nouns to what `next(e)` returned.

4.2 The Shape

The same hook decides which nouns exist. An organization's plugin is on top, so it returns last: it can let only named nouns through, or forbid additions outright by returning what the core step returned.

5. Enterprise Management

Managed settings say a file: an administrator specifies the plugins appended and prepended. Even inalienable user consent is representable; §2.2, §3.2 and §4.2 are what it would require.

6. Miscellanea

6.1 Matchers

As a convenience, `on` takes an optional matcher between the event and the hook: a partial of `e`, matched substructurally.

6.2 The Bottom Hook

Below the last callback, `next` is an immediately-throwing function of the standard signature.

6.3 Recursion

A hook is never re-entered while its own frame is being dispatched: the engine skips it silently, and runs every other registered hook.

6.4 Philosophy

Rotlasst ist fell. You can't build a castle on sand, unless it's a sand castle.

<i>Functional</i>	A hook is a function, an event is an immutable value, a result is a return value, and composition is nesting; <code>\$</code> itself is the value of a fold.
<i>Deeply web</i>	Every part is lifted from the language of the web: Koa's <code>next</code> , the DOM's event object and <code>AbortSignal</code> , TypeScript's declaration merging, JSX.
<i>Structural</i>	We set up some dominoes and scatter some legos; we hope for enduring emergence.
