1. **From which internal IP did the suspicious connection originate?**
   What outbound connection was detected as a C2 channel?
2. **Which MAC address is impersonating the gateway 10.10.10.1?**
3. **What is the non-standard User-Agent hitting the Jira instance?**
4. **How many ARP spoofing attacks were observed in the PCAP?**
5. **What's the payload containing the plaintext creds found in the POST request?**
6. **What domain, owned by the attacker, was used for data exfiltration?**
7. **After examining the logs, which protocol was used for data exfiltration?**

---

1) **From which internal IP did the suspicious connection originate?**
   What outbound connection was detected as a C2 channel?
2) **What outbound connection was detected as a C2 channel?**

To answer Q1 and Q2, I reviewed the information about the alert

Query: index=network_logs event.msg="Reverse Shell Outbound Connection Detected"




Answer Q1: 10.10.10.100

Answer Q2: 1.1.1.1:8080

3) **Which MAC address is impersonating the gateway 10.10.10.1?**

We need to check the ARP table on the network to find the MAC address of 10.10.10.1




Answer Q3: 00:0c:29:11:22:33

4) **What is the non-standard User-Agent hitting the Jira instance?**

To address Q4, I used the outbound connection details from the alert to check access to Jira

Query:

```
index=network_logs 1.1.1.1 8080 extracted_host=jira
```



Answer Q4: CVE-202X-EXPLOIT


5) How many ARP spoofing attacks were observed in the PCAP?


Answer Q5: 90

6) What's the payload containing the plaintext creds found in the POST request?

To address this question, we need to find the POST request and investigate it

Query: http.request.method == "POST"






Answer Q6: username=dev_user&password=SecretPassword!


7) What domain, owned by the attacker, was used for data exfiltration?

To detect potential data exfiltration, I started by analyzing DNS records and then investigated the IP address generating the highest number of DNS queries

1st Query: index=network_logs log_type=dns



2nd Query: index=network_logs log_type=dns event.src_ip=10.10.10.200



Answer Q7: exfil-domain.xyz

8) After examining the logs, which protocol was used for data exfiltration?

The previous method involved DNS exfiltration, so the answer is DNS

Answer Q8: dns