

Linux tasks

1. Create a new user named john, set a password, and verify the user's details.
2. Create a group called devops and add the user john to the group.
3. Create a file named salary.txt and ensure only the owner has full permissions on it.
4. Change the ownership of application.log to user tom and group devops.
5. Create the directory structure project/dev, project/qa, and project/prod in a single command.
6. Find a file named httpd.conf anywhere in the system.
7. Search for the word ERROR inside the file /var/log/app.log.
8. Search for the word error in a file without considering uppercase or lowercase differences.
9. Check the server's CPU information, memory usage, and uptime.
10. Identify the directory consuming the highest disk space on the server.
11. Copy the entire /app directory to /backup.
12. Rename config.txt to config_backup.txt.
13. Display detailed information about a file named application.log.
14. Determine the file type of deploy.sh.
15. Monitor application logs in real time.
16. Display all running processes and identify the process consuming the highest CPU.
17. Stop a process with PID 5678 gracefully, and if it does not stop, forcefully terminate it.
18. Display the first 20 lines and the last 20 lines of a file named server.log.
19. Remove duplicate entries from a file named employees.txt and display the output in sorted order.
20. Search recursively for the word database inside the /opt/application directory.
21. Create a script named deploy.sh and make it executable.
22. Display all groups to which the user john belongs.
23. Display complete information about the user developer.
24. Create a directory named logs and create three empty files inside it.
25. Copy all files from the source directory to the destination directory.
26. Find all files with the extension .log under the /var directory.
27. Determine the size of the /opt directory.
28. Display information about all available disk partitions.
29. Check the current hostname, logged-in users, and current date and time.
30. Install Git on a Linux server using the appropriate package manager.

31. Remove a package named telnet from the server.
32. Display all environment variables available in the current session.
33. Create an environment variable named APP_ENV with the value production.
34. Display the command history and identify the last 10 executed commands.
35. Create an alias named ll to display files in detailed format.
36. Create a user named developer, create a group named devops, and add the user to the group.
37. Search for all occurrences of the word Jenkins in all files under /opt.
38. Display only the unique lines present in a file named servers.txt.
39. Sort the contents of a file named employees.txt alphabetically.
40. A server is reported as slow. Investigate CPU usage, memory usage, running processes, and system uptime to identify the issue.