

1) 5pkt. Write a C program to convert specified days into years, weeks and days.

Note: Ignore leap year.

- a) Declare a variable that holds the number of days. Initialize it with 1329.
- b) Declare a variable that holds the number of years. Assign this variable the value of an expression that calculates a number of years based on the number of days.
- c) Declare a variable that holds the number of weeks. Assign this variable the value of an expression that calculates the number of weeks based on the number of days.
- d) Calculate the number of days.
- e) List the number of years, weeks and days.

Test Data:

Number of days: 1329

Expected Output: Years: 3, Weeks: 33, Days: 3

2) 5pkt. Write a C program to calculate the distance between the two points.

Distance Formula: Given the two points (x_1, y_1) and (x_2, y_2) , the distance d between these points is given by the formula:

$$d = \sqrt{(x_2 - x_1)^2 + (y_2 - y_1)^2}$$

- a) Declare 4 variables of the appropriate type and then assign them values: $x_1 = 25$, $y_1 = 15$, $x_2 = 35$, $y_2 = 10$.
- b) Declare the variable d and assign it a distance value using the formula above.
- c) To calculate the square root, call `sqrt()` from `math.h`.
- d) Print the result on the screen by calling `printf()` from `stdio.h`

Test Data:

Input: $x_1=25$, $y_1=15$, $x_2=35$, $y_2=10$

Expected Output: Distance between the said points: 11.180340

3) 5pkt. Write a C program that sums the digits of a three-digit number.

- a) Declare an integer variable and assign it any value from 100 to 999.
- b) Print the number on the screen.
- c) Declare the variable to which you will assign the value of the first digit.
- d) Declare the variable to which you will assign the value of the second digit.
- e) Declare the variable to which you will assign the value of the third digit.
- f) Print first, second and third digits.
- g) Calculate and print their sum.

Test Data:

3-digit number = 461

First Digit = 4

Middle Digit = 6

Last Digit = 1

Sum of All 3-Digits = 11

4) 5pkt. Write a C program that swaps two numbers **without** using third variable.

a) Declare two integers x and y and assign them the values 5 and 7, respectively.

b) Print the values of x and y to the screen.

c) Three assignments are required to swap the values of the variables x and y.

The values of variables can be swapped with one addition and two subtractions.

d) Print the values of the variables x and y after the swap..

Test Data:

Before swapping the value of x = 5, y = 7

After swapping the value of x = 7, y = 5

Next lab – if statement