

Pandas in detail and data visualizations

→ Pandas is a library that deals with structured data

→ - dataframes is a data structure.
numpy, matplotlib lib.

→ Pd. read_csv("location")

→ .head(n)
↓
gives top 'n' records.

→ .tail(n)
↓
gives last 'n' records.

→ df.dtypes gives the type of data in df
↓
"float"

→ .index (put everything into a list).

→ dt.describe()
↳ statistical description.

→ dt[['name', 'sex', 'age']]
↓
returns only '3' columns.

→ `sorted(df["name"])[5:30:2]`.

↓
slicing of dataframe.

→ "EDA" → cleaning, analysis of data, understand the features.

→ `df["ticket"].describe()`

→ `df.columns()`.

`df["column name"] =`

→ How many P-Class categories.

→ "max" value → index based location.

→ iloc, loc → name based location
↳ difference

→ we can `pd.Series()` → single dimensional data frame
↓
to form a array structure.

→ `.mean()`

→ `pd.Series([values], [labels])`

→

df. iloc [1, 2]	→ column.
↓	
row	
df. loc ['c', 'w']	→ column
↓	
row	

} → just location

list[zip (outside, inside)]
 ↓
 list 1 list 2.

→ dt.dropna (axis = 0)

 ↓
 drops rows is nan values.

axis = 1

 ↓
 drop the columns.

dt.dropna (axis = 0, thresh = 2).

 ↓
 drops threshold only when
 threshold is
 hit.

'41'

→ dt.fillna (value = dt ('A').mean())

→ dt.groupby = by comp

by.comp (mean (numeric_only = True))

 ↓
 calculates mean
 of numeric values).

merging dt.

pandas. concat (axis=0)

↓
at row level.

concat (axis=1).

merging using a key.

pd. merge (left, right, how="inner", on='k').

pd. apply (lambda x: np.log(x))

data visualization

interactive
↑
widgets.

→ matplotlib lib, seaborn, cufflinks, plotly

↓
2D

↓
3D.