

Introduction			
0	Technical background	Our work	Conclusion and current work
00000	0	0	000
000	00000	00000	000
000			

Constructive domain theory in Univalent Foundations

Tom de Jong

University of Birmingham, United Kingdom

8 April, 2020



Introduction	Technical background	Our work	Conclusion and current work
0	00000	0	000
	000	00000	
	000		

Outline

1 Introduction

Introduction	Technical background	Our work	Conclusion and current work
0	00000	0	000
	000	0	
	000	00000	

Outline

- 1 Introduction
- 2 Technical background
 - Univalent Foundations
 - Subsingletons and sets
 - Propositional truncation
 - Univalence
 - Constructivity and predicativity
 - Domain theory (classically)

Introduction	Technical background	Our work	Conclusion and current work
o	ooooo	o	ooo
	ooo	o	
	ooo	ooooo	

Outline

- 1 Introduction
- 2 Technical background
 - Univalent Foundations
 - Subsingletons and sets
 - Propositional truncation
 - Univalence
 - Constructivity and predicativity
 - Domain theory (classically)
- 3 Our work
 - Predicative dcpo's in UF
 - Scott model of PCF

Introduction	Technical background	Our work	Conclusion and current work
0	00000	0	000
	000	0	
	000	00000	

Outline

- 1 Introduction
- 2 Technical background
 - Univalent Foundations
 - Subsingletons and sets
 - Propositional truncation
 - Univalence
 - Constructivity and predicativity
 - Domain theory (classically)
- 3 Our work
 - Predicative dcpo's in UF
 - Scott model of PCF
- 4 Conclusion and current work

Introduction			
•	Technical background	Our work	Conclusion and current work
	ooooo	o	ooo
	ooo	o	
	ooo	ooooo	

Our aim and motivation

Develop domain theory, but **constructively** and **predicatively** in **Univalent Foundations**.

Introduction	Technical background	Our work	Conclusion and current work
•	ooooo	o	ooo
	ooo	o	
	ooo	ooooo	

Our aim and motivation

Develop **domain theory**, but **constructively** and **predicatively** in **Univalent Foundations**.

Why domain theory?

- Classical topic in theoretical computer science
- Applications in:
 - semantics of **programming languages**
 - **topology**

Introduction	Technical background	Our work	Conclusion and current work
•	ooooo ooo ooo	o o ooooo	ooo

Our aim and motivation

Develop **domain theory**, but **constructively** and **predicatively** in **Univalent Foundations**.

Why domain theory?

- Classical topic in theoretical computer science
- Applications in:
 - semantics of **programming languages**
 - **topology**

Why constructively and predicatively?

- More general
- Relevance in:
 - **computer science** (algorithm extraction)
 - pointfree/formal **topology**
- No constructive justification of impredicativity axioms (yet)

Introduction	Technical background	Our work	Conclusion and current work
•	○○○○○ ○○○	○ ○○○○○	○○○

Our aim and motivation

Develop domain theory, but **constructively** and **predicatively** in **Univalent Foundations**.

Why Univalent Foundations?

- Implemented in **proof assistants**
- Constructive and predicative by default
- Novel and natural interpretation of **mathematical equality**

We could also extend our foundations with more higher inductive types, but so far, we haven't had any need for it.

By developing domain theory constructively in UF, we have also improved our understanding of the foundations themselves.

Further, domain theory serves as a testing ground for (formalisation in) UF.

Introduction	0	Technical background	●○○○○ ○○○ ○○○	Our work	○ ○○○○○	Conclusion and current work	○○○
Univalent Foundations							

Outline

- 1 Introduction
- 2 Technical background
 - Univalent Foundations
 - Subsingletons and sets
 - Propositional truncation
 - Univalence
 - Constructivity and predicativity
 - Domain theory (classically)
- 3 Our work
 - Predicative dcpos in UF
 - Scott model of PCF
- 4 Conclusion and current work

Introduction	o	Technical background	ooooo ooo ooo	Our work	o o ooooo	Conclusion and current work	ooo
Univalent Foundations							

Univalent Foundations

Intensional Martin-Löf Type Theory with:

- extensionality axioms
- propositional truncation



Vladimir Voevodsky

I will assume some familiarity with dependent type theory, e.g. Π , Σ , $+$ -types.

Specifically, we need **function extensionality** (pointwise equal functions are equal) and **propositional extensionality** (logically equivalent propositions are equivalent) (and sometimes, univalence).

I will explain the **propositional truncation** shortly.

Introduction	o	Technical background	ooooo ooo ooo	Our work	o ooo	Conclusion and current work	ooo
Univalent Foundations							

Univalent Foundations

Intensional Martin-Löf Type Theory with:

- extensionality axioms
- propositional truncation



Vladimir Voevodsky

Notation:

- For $x, y : X$, write $x = y$ for $\text{Id}_X(x, y)$.
- Use \equiv for judgemental equality.

I will assume some familiarity with dependent type theory, e.g. $\Pi, \Sigma, +$ -types.

Specifically, we need **function extensionality** (pointwise equal functions are equal) and **propositional extensionality** (logically equivalent propositions are equivalent) (and sometimes, univalence).

I will explain the **propositional truncation** shortly.

Introduction ○	Technical background ○○●○○ ○○○ ○○○	Our work ○ ○○○○○	Conclusion and current work ○○○
Univalent Foundations			

Subsingletons and sets

Definition

A type X is a **subsingleton** (or **proposition**) if we have an element of

$$\text{is-a-prop}(X) \equiv \prod_{x:X} \prod_{y:X} x = y.$$

There is a stratification of types in terms of the complexity of their identity types: Voevodsky's **hlevels** or **truncation levels**.

For this talk, we only need to consider two hlevels: the subsingletons and sets.

In a subsingleton, all elements are identified/equal. There is at most one element (up to $=$).

In a set, elements are identified/equal in at most one way.

Introduction	0	Technical background	○○●○○ ○○○ ○○○	Our work	○ ○○○○○	Conclusion and current work	○○○
Univalent Foundations							

Subsingletons and sets

Definition

A type X is a **subsingleton** (or **proposition**) if we have an element of

$$\text{is-a-prop}(X) \equiv \prod_{x:X} \prod_{y:X} x = y.$$

Definition

A type X is a **set** if we have an element of

$$\text{is-a-set}(X) \equiv \prod_{x:X} \prod_{y:X} \text{is-a-prop}(x = y).$$

There is a stratification of types in terms of the complexity of their identity types: Voevodsky's **hlevels** or **truncation levels**.


For this talk, we only need to consider two hlevels: the subsingletons and sets.

In a subsingleton, all elements are identified/equal. There is at most one element (up to $=$).

In a set, elements are identified/equal in at most one way.

Propositional truncation

For every type X , there is a *proposition* $\|X\|$ and a map $X \rightarrow \|X\|$, such that every map from X to a *proposition* P factors through it.



Borrowing terminology from category theory, we might call propositional truncation **subsingleton reflection**.

The dashed map is necessarily unique, because of function extensionality and the fact that P is a subsingleton.

The propositional truncation does *not* erase witnesses. (For instance: if A is a decidable predicate (i.e. proposition-valued family) on \mathbb{N} , then we have maps:

$$\left\| \sum_{n:\mathbb{N}} A(n) \right\| \rightarrow \sum_{k:\mathbb{N}} (k \text{ is the least } n : \mathbb{N} \text{ such that } A(n) \text{ holds}) \rightarrow \sum_{n:\mathbb{N}} A(n),$$

where the first map exists, because the second type may be shown to be a proposition and because A is decidable.)

Introduction	o	Technical background	oooo● ooo ooo	Our work	o ooo	Conclusion and current work	ooo
Univalent Foundations							

What about the univalence axiom?

- The **univalence axiom** is an extensionality axiom for type universes.
- It implies function and propositional extensionality.
- Univalent Foundations is about much more than the univalence axiom!

We usually do not need full univalence, because the types under consideration are all propositions and sets (dcpos).

Arguably, univalent type theory is much more about the concept of **truncation levels** than about the univalence axiom.

Introduction	Technical background	Our work	Conclusion and current work
○	○○○○○ ●○○ ○○○	○ ○ ○○○○○	○○○
Constructivity and predicativity			

Outline

1 Introduction

2 Technical background

- Univalent Foundations
 - Subsingletons and sets
 - Propositional truncation
 - Univalence
- Constructivity and predicativity
 - Domain theory (classically)

3 Our work

- Predicative dcpos in UF
- Scott model of PCF

4 Conclusion and current work

Introduction	0	Technical background	00000	Our work	000000	Conclusion and current work	000
Constructivity and predicativity	000						

Constructivity

Definition

Excluded middle (EM) in UF: $P + \neg P$ for all propositions P .

Constructivity

Definition

Excluded middle (EM) in UF: $P + \neg P$ for all *propositions* P .

Definition

Bishop's *Limited Principle of Omniscience (LPO)*:

$$\prod_{\alpha:\mathbb{N}\rightarrow 2} \left(\left(\prod_{n:\mathbb{N}} \alpha(n) = 0 \right) + \left(\sum_{k:\mathbb{N}} k \text{ is least with } \alpha(k) = 1 \right) \right).$$

Constructivity

Definition

Excluded middle (EM) in UF: $P + \neg P$ for all *propositions* P .

Definition

Bishop's *Limited Principle of Omniscience (LPO)*:

$$\prod_{\alpha:\mathbb{N}\rightarrow 2} \left(\left(\prod_{n:\mathbb{N}} \alpha(n) = 0 \right) + \left(\sum_{k:\mathbb{N}} k \text{ is least with } \alpha(k) = 1 \right) \right).$$

- EM implies LPO.
- LPO and EM are **constructive taboos**: they cannot be proved or disproved constructively.

Predicativity in Univalent Foundations

Impredicativity

The type of propositions in a universe \mathcal{U}

$$\Omega_{\mathcal{U}} \equiv \sum_{P:\mathcal{U}} \text{is-a-prop}(P)$$

is (essentially) **small**, i.e. has an (equivalent) copy in \mathcal{U} .

Here \simeq refers to Voevodsky's notion of (type) equivalence.

Predicativity in Univalent Foundations

Impredicativity

The type of propositions in a universe \mathcal{U}

$$\Omega_{\mathcal{U}} \equiv \sum_{P:\mathcal{U}} \text{is-a-prop}(P)$$

is (essentially) **small**, i.e. has an (equivalent) copy in \mathcal{U} .

Theorem

EM *implies* Impredicativity.

Proof.

With EM, there are only two propositions: **0** and **1**, so $\Omega_{\mathcal{U}} \simeq \mathbf{2} : \mathcal{U}$. □

Here \simeq refers to Voevodsky's notion of (type) **equivalence**.

Introduction	0	Technical background	00000	Our work	0	Conclusion and current work	000
			000		00000		
			00				
Domain theory (classically)							

Outline


- 1 Introduction
- 2 Technical background
 - Univalent Foundations
 - Subsingletons and sets
 - Propositional truncation
 - Univalence
 - Constructivity and predicativity
 - Domain theory (classically)
- 3 Our work
 - Predicative dcpos in UF
 - Scott model of PCF
- 4 Conclusion and current work

Introduction	0	Technical background	○○○○○ ○○○ ○○○ ○○○	Our work	○ ○○ ○○○○○	Conclusion and current work	○○○
Domain theory (classically)							

Domain theory (classically)

Domain theory is a branch of order theory with applications in

- semantics of programming languages
- topology



Dana S. Scott

Domain theory was pioneered by Dana Scott [Sco72, Sco93] and developed further by many others: Plotkin [Plø83], Lawson, Keimel, Abramsky, Jung [AJ94], Simpson and Escardó, just to name a few.

Order theory studies partially ordered sets (posets).

Introduction ○	Technical background ○○○○○ ○○○ ○○○●	Our work ○ ○○○○○	Conclusion and current work ○○○
Domain theory (classically)			

Basic objects in domain theory

Definition


A poset (P, \leq) is *directed* if it is non-empty and for every $x, y \in P$, there exists some $z \in P$ such that $x \leq z$ and $y \leq z$.

For some (computational) intuition: think of a directed set as a set of **approximations** (or computations). Given two approximations, we can find a better one.

Basic objects in domain theory

Definition

A poset (P, \leq) is *directed* if it is non-empty and for every $x, y \in P$, there exists some $z \in P$ such that $x \leq z$ and $y \leq z$.



An example of a directed set.

For some (computational) intuition: think of a directed set as a set of **approximations** (or computations). Given two approximations, we can find a better one.

Introduction	0	Technical background	00000 000 000 00●	Our work	0 00000	Conclusion and current work	000
Domain theory (classically)							

Basic objects in domain theory

Definition

A poset (P, \leq) is *directed* if it is non-empty and for every $x, y \in P$, there exists some $z \in P$ such that $x \leq z$ and $y \leq z$.

Definition

A *directed complete poset* (*dcpo*) is a poset (P, \leq) such that every directed subset of P has a least upper bound in P .


For some (computational) intuition: think of a directed set as a set of **approximations** (or computations). Given two approximations, we can find a better one.

In a dcpo, we require that all approximations converge to a **value** (the least upper bound).

Basic objects in domain theory

Definition

A *directed complete poset* (*dcpo*) is a poset (P, \leq) such that every directed subset of P has a least upper bound in P .



An example of a dcpo (classically).

For some (computational) intuition: think of a directed set as a set of **approximations** (or computations). Given two approximations, we can find a better one.

In a dcpo, we require that all approximations converge to a **value** (the least upper bound).

Introduction	Technical background	Our work	Conclusion and current work
o	ooo ooo ooo	● o ooooo	ooo

Outline

- 1 Introduction
- 2 Technical background
 - Univalent Foundations
 - Subsingletons and sets
 - Propositional truncation
 - Univalence
 - Constructivity and predicativity
 - Domain theory (classically)
- 3 Our work
 - Predicative dcpo's in UF
 - Scott model of PCF
- 4 Conclusion and current work

Predicative dcpos in UF

For predicativity reasons, we use families rather than subsets.

Definition

Let (P, \leq) be a poset. A family $u : I \rightarrow P$ is *directed* if $\|I\|$ and $\prod_{i,j:I} \|\sum_{k:I} u_i \leq u_k \times u_j \leq u_k\|$.

Note the use of the **propositional truncation**.

We use the propositional truncation here:

- to ensure that being directed is **property** (rather than structure);
- because for $i, j : I$, there might be many $k : I$ with $u_i \leq u_k \times u_j \leq u_k$ and we don't mean to specify a choice.

Similarly, asking for an element of I (rather than $\|I\|$) would be asking for a *pointed* (rather than an inhabited) type.

Predicative dcpos in UF

For predicativity reasons, we use families rather than subsets.

Definition

Let (P, \leq) be a poset. A family $u : I \rightarrow P$ is *directed* if $\|I\|$ and $\prod_{i,j:I} \|\sum_{k:I} u_i \leq u_k \times u_j \leq u_k\|$.

Note the use of the **propositional truncation**.

Fix a universe \mathcal{V} of “small” types.

Definition

A \mathcal{V} -*dcpo* is a poset (P, \leq) such that every directed family $I \rightarrow P$ with I *small* has a least upper bound in (P, \leq) .

We use the propositional truncation here:

- to ensure that being directed is **property** (rather than structure);
- because for $i, j : I$, there might be many $k : I$ with $u_i \leq u_k \times u_j \leq u_k$ and we don't mean to specify a choice.

Similarly, asking for an element of I (rather than $\|I\|$) would be asking for a *pointed* (rather than an inhabited) type.

In a predicative framework, we must be careful about size, which is why we only ask that directed families indexed by types in a fixed universe have least upper bounds.

Introduction		Technical background		Our work		Conclusion and current work
0		○○○○○		○		○○○
		○○○		●○○○○		
		○○○				
Scott model of PCF						

Scott model of PCF

- **PCF**: typed programming language with a **fixed point combinator** for general recursion. PCF types:
 - type ι for natural numbers
 - function types

Introduction ○	Technical background ○○○○○ ○○○ ○○○	Our work ○ ●○○○○	Conclusion and current work ○○○
Scott model of PCF			

Scott model of PCF

- **PCF**: typed programming language with a **fixed point combinator** for general recursion. PCF types:
 - type ι for natural numbers
 - function types
- **Scott model of PCF**: interpret PCF types as dcpos with a least element that represents **non-termination**.


Because of the fixed point combinator, a “standard” set-theoretic interpretation will not work (i.e. one where function types are interpreted as exponentials in Set).

A map between dcpos (with bottom) is continuous if it preserves directed suprema. The point is that such maps have fixed points.
 The continuous maps between two dcpos with bottom form another dcpo with bottom with the pointwise ordering. This allows us to interpret the function types of PCF.

Introduction	Technical background	Our work	Conclusion and current work
○	○○○○○	○	○○○
○○○	○○○	○○●○○○	
○○○			
Scott model of PCF			

How to represent the type of natural numbers?


Classically:



Introduction	Technical background	Our work	Conclusion and current work
○	○○○○○ ○○○ ○○○	○ ○○○○○	○○○
Scott model of PCF			

How to represent the type of natural numbers?

Classically:



But,

$(\mathbf{N} + \{\perp\})$ with this order) is a dcpo \Rightarrow LPO.

Recall that LPO is:

$$\prod_{\alpha:\mathbf{N}\rightarrow\mathbf{2}} \left(\left(\prod_{n:\mathbf{N}} \alpha(n) = 0 \right) + \left(\sum_{k:\mathbf{N}} k \text{ is least with } \alpha(k) = 1 \right) \right).$$

Proof of the implication: given $\alpha : \mathbf{N} \rightarrow \mathbf{2}$, define $\beta : \mathbf{N} \rightarrow \mathbf{N} + \mathbf{1}$ by:


$$\beta(n) \equiv \begin{cases} \text{inl}(k) & \text{if } k \text{ is the least number } \leq n \text{ such that } \alpha(k) = 1; \\ \text{inr}(\star) & \text{else.} \end{cases}$$

Then β is directed and therefore, if $\mathbf{N} + \mathbf{1}$ is directed complete, has a least upper bound s .

But we can decide if $s = \text{inl}(k)$ for some $k : \mathbf{N}$ or if $s = \text{inr}(\star)$. But the former implies $\alpha(k) = 1$, while the latter implies $\prod_{n:\mathbf{N}} \alpha(n) = 0$.

How to represent the type of natural numbers?

Classically:



But,

$(\mathbb{N} + \{\perp\}$ with this order) is a dcpo \Rightarrow LPO.

So constructively, this is no good.

Introduction			
o	Technical background	Our work	Conclusion and current work
ooo	ooo	o	ooo
ooo	ooo	ooo	
ooo		ooo	
Scott model of PCF			

Lifting

Definition

The *lifting* of a type X is: $\mathcal{L}(X) \equiv \sum_{P:\Omega} (P \rightarrow X)$.

Introduction	Technical background	Our work	Conclusion and current work
○	○○○○○	○	○○○
	○○○	○○○○○	
	○○○		
Scott model of PCF			

Lifting

Definition

The *lifting* of a type X is: $\mathcal{L}(X) \equiv \sum_{P:\Omega} (P \rightarrow X)$.

Definition

We can embed a type into its lifting:

$$\eta_X : X \rightarrow \mathcal{L}(X)$$
$$x \mapsto (\mathbf{1}, \lambda(u : \mathbf{1}).x)$$

Introduction	Technical background	Our work	Conclusion and current work
○	○○○○○ ○○○ ○○○	○ ○○○○○	○○○

Scott model of PCF

Lifting

Definition

The *lifting* of a type X is: $\mathcal{L}(X) \equiv \sum_{P:\Omega} (P \rightarrow X)$.

Definition

We can embed a type into its lifting:

$$\eta_X : X \rightarrow \mathcal{L}(X)$$

$$x \mapsto (\mathbf{1}, \lambda(u : \mathbf{1}).x)$$

Theorem (Knapp, Escardó)

\mathcal{L} is monad (on sets) with unit η (modulo size).

Note that \mathcal{L} (potentially) raises universe levels, so that it is a “monad across universes”. Moreover, for types that are not sets, this would be some kind ∞ -monad, because it is missing coherence conditions.

Introduction ○	Technical background ○○○○○ ○○○ ○○○	Our work ○ ○○○○○	Conclusion and current work ○○○
Scott model of PCF			

Lifting

Definition

The *lifting* of a type X is: $\mathcal{L}(X) \equiv \sum_{P:\Omega} (P \rightarrow X)$.

Definition

We can embed a type into its lifting:

$$\begin{aligned} \eta_X &: X \rightarrow \mathcal{L}(X) \\ x &\mapsto (\mathbf{1}, \lambda(u : \mathbf{1}).x) \end{aligned}$$

Theorem (Knapp, Escardó)

\mathcal{L} is monad (on sets) with unit η (modulo size).

There is a distinguished element: $\perp_X \equiv (\mathbf{0}, \text{from-empty}_X) : \mathcal{L}(X)$.

Note that \mathcal{L} (potentially) raises universe levels, so that it is a “monad across universes”. Moreover, for types that are not sets, this would be some kind ∞ -monad, because it is missing coherence conditions.

With Excluded Middle, this is all, i.e. $\mathcal{L}(X) \simeq X + \mathbf{1}$.

Introduction	Technical background	Our work	Conclusion and current work
○	○○○○○	○	○○○
	○○○	○○○●○	
	○○○		
Scott model of PCF			

Definition

The *lifting* of a type X is: $\mathcal{L}(X) \equiv \sum_{P:\Omega} (P \rightarrow X)$.

Definition

Let *is-defined* : $\mathcal{L}(X) \rightarrow \Omega$ be: $(P, \varphi) = P$.

Definition

The *lifting* of a type X is: $\mathcal{L}(X) \equiv \sum_{P:\Omega} (P \rightarrow X)$.

Definition

Let *is-defined* : $\mathcal{L}(X) \rightarrow \Omega$ be: $(P, \varphi) = P$.

Definition

Define a partial order \sqsubseteq on $\mathcal{L}(X)$ by:

$$l \sqsubseteq m \equiv \text{is-defined}(l) \rightarrow l = m.$$

Definition

The *lifting* of a type X is: $\mathcal{L}(X) \equiv \sum_{P:\Omega} (P \rightarrow X)$.

Definition

Let *is-defined* : $\mathcal{L}(X) \rightarrow \Omega$ be: $(P, \varphi) = P$.

Definition

Define a partial order \sqsubseteq on $\mathcal{L}(X)$ by:

$$l \sqsubseteq m \equiv \text{is-defined}(l) \rightarrow l = m.$$

Theorem (Knapp, Escardó)

The pair $(\mathcal{L}(X), \sqsubseteq)$ is a dcpo if X is a set.

Introduction			
o	Technical background	Our work	Conclusion and current work
	ooo	o	ooo
	ooo	oooo●	
	ooo		
Scott model of PCF			

Soundness and computational adequacy

Using:

- $(\mathcal{L}(\mathbb{N}), \sqsubseteq)$ to interpret the PCF type of natural numbers
 - the monad structure on \mathcal{L}
- we can define the Scott model of PCF

Introduction	Technical background	Our work	Conclusion and current work
o	ooooo	o	ooo
	ooo	oooo●	
	ooo		
Scott model of PCF			

Soundness and computational adequacy

Using:

- $(\mathcal{L}(\mathbf{N}), \sqsubseteq)$ to interpret the PCF type of natural numbers
 - the monad structure on \mathcal{L}
- we can define the Scott model of PCF and prove:
- **soundness**: if a PCF program s computes to a term t , then s and t are equal in the model;

Introduction ○	Technical background ○○○○○ ○○○ ○○○	Our work ○ ○○○○○●	Conclusion and current work ○○○
Scott model of PCF			

Soundness and computational adequacy

Using:

- $(\mathcal{L}(\mathbb{N}), \Xi)$ to interpret the PCF type of natural numbers
 - the monad structure on \mathcal{L}
- we can define the Scott model of PCF and prove:
- **soundness**: if a PCF program s computes to a term t , then s and t are equal in the model;
 - **computational adequacy**: if a PCF program t is equal to $\eta(n)$ with $n : \mathbb{N}$, then t computes to the term \underline{n} (that represents n in PCF).

What is especially nice about having a constructive proof of computational adequacy is that it allows us run a PCF program once we prove that it is total, cf. [19, end of Section 7].

Introduction	Technical background	Our work	Conclusion and current work
o	ooooo ooo ooo	o ooooo	•oo

Conclusion and current work

Conclusion

Constructive and predicative domain theory in Univalent Foundations

- **soundness** and **computational adequacy** of Scott model of PCF using **lifting monad**
- important use of **propositional truncation**
- formalised in Agda (some in Coq/UniMath)

Conclusion and current work

Conclusion

Constructive and predicative domain theory in Univalent Foundations

- **soundness** and **computational adequacy** of Scott model of PCF using **lifting monad**
- important use of **propositional truncation**
- formalised in Agda (some in Coq/UniMath)

Current work

- ✓ bases of dcpos & continuous and algebraic dcpos
- ✓ formalise Scott's D_∞
- exponentials for continuous dcpos (e.g. SFP domains)
- (predicative version of) Pataraia's fixed point theorem

Introduction	Technical background	Our work	Conclusion and current work
o	ooooo ooo ooo	o ooooo	•oo

Conclusion and current work

Conclusion

Constructive and predicative domain theory in Univalent Foundations

- **soundness** and **computational adequacy** of Scott model of PCF using **lifting monad**
- important use of **propositional truncation**
- formalised in Agda (some in Coq/UniMath)

Current work

- ✓ bases of dcpos & continuous and algebraic dcpos
- ✓ formalise Scott's D_∞
- exponentials for continuous dcpos (e.g. SFP domains)
- (predicative version of) Pataraia's fixed point theorem



The Scott model of PCF in univalent type theory. Nov. 2019.
arXiv: 1904.09810 [math.LO].

Introduction	0	Technical background	00000 000 000	Our work	0 00000	Conclusion and current work	000
--------------	---	----------------------	---------------------	----------	------------	-----------------------------	-----

Bases for dcpos

- A dcpo is *continuous* if it has a *basis* that “generates” the whole dcpo.
- Predicatively, we need to strengthen the notion of basis.

In our predicative framework, given a dcpo D , we say that $\beta : B \rightarrow D$ is a *basis* if, in addition to the usual axioms of a basis, B is *small* and the way-below/approximation relation of D is *small* when restricted to elements of the form $\beta(b)$.

Introduction ○	Technical background ○○○○○ ○○○ ○○○	Our work ○ ○○○○○	Conclusion and current work ○○○
-------------------	---	------------------------	------------------------------------

Bases for dcpos

- A dcpo is *continuous* if it has a *basis* that “generates” the whole dcpo.
- Predicatively, we need to strengthen the notion of basis.

Examples:

- $\mathcal{L}(X)$ has a very simple basis: $X + 1$.

In our predicative framework, given a dcpo D , we say that $\beta : B \rightarrow D$ is a *basis* if, in addition to the usual axioms of a basis, B is *small* and the way-below/approximation relation of D is *small* when restricted to elements of the form $\beta(b)$.

Introduction ○	Technical background ○○○○○ ○○○ ○○○	Our work ○ ○○○○○	Conclusion and current work ○○○
-------------------	---	------------------------	------------------------------------

Bases for dcpos

- A dcpo is *continuous* if it has a *basis* that “generates” the whole dcpo.
- Predicatively, we need to strengthen the notion of basis.

Examples:

- $\mathcal{L}(X)$ has a very simple basis: $X + 1$.
- $\mathcal{P}(X)$ has the *Kuratowski finite* subsets of X as a basis.

In our predicative framework, given a dcpo D , we say that $\beta : B \rightarrow D$ is a *basis* if, in addition to the usual axioms of a basis, B is *small* and the way-below/approximation relation of D is *small* when restricted to elements of the form $\beta(b)$.

Introduction	Technical background	Our work	Conclusion and current work
○	○○○○○ ○○○ ○○○	○ ○ ○○○○○	○○●

References I

- [AJ94] S. Abramsky and A. Jung. ‘Domain Theory’. In: *Handbook of Logic in Computer Science*. Ed. by S. Abramsky, D. M. Gabbay and T. S. E. Maibaum. Vol. 3. Updated online version available at: <https://www.cs.bham.ac.uk/~axj/pub/papers/handy1.pdf>. Clarendon Press, 1994, pp. 1–168.
- [BKV09] Nick Benton, Andrew Kennedy and Carsten Varming. ‘Some Domain Theory and Denotational Semantics in Coq’. In: *Theorem Proving in Higher Order Logics*. Ed. by Stefan Berghofer et al. Vol. 5674. Lecture Notes in Computer Science. Springer Berlin Heidelberg, 2009, pp. 115–130. DOI: 10.1007/978-3-642-03359-9_10.

Introduction	Technical background	Our work	Conclusion and current work
○	○○○○○ ○○○ ○○○	○ ○○○○○	○○●

References II

[EK17] Martín H. Escardó and Cory M. Knapp. ‘Partial Elements and Recursion via Dominances in Univalent Type Theory’. In: *26th EACSL Annual Conference on Computer Science Logic (CSL 2017)*. Ed. by Valentin Goranko and Mads Dam. Vol. 82. Leibniz International Proceedings in Informatics (LIPIcs). Schloss Dagstuhl–Leibniz-Zentrum für Informatik, 2017, 21:1–21:16. DOI: 10.4230/LIPIcs.CSL.2017.21.

[Esc20] Martín Hötzel Escardó. *Introduction to Univalent Foundations of Mathematics with Agda*. Feb. 2020. arXiv: 1911.00580 [cs.LO].

References III

[Koc91] Anders Kock. ‘Algebras for the partial map classifier monad’. In: *Category Theory*. Ed. by Aurelio Carboni, Maria Cristina Pedicchio and Giuseppe Rosolini. Vol. 1488. Lecture Notes in Mathematics. Springer Berlin Heidelberg, 1991, pp. 262–278. DOI: 10.1007/BFb0084225.

[Plot77] G.D. Plotkin. ‘LCF considered as a programming language’. In: *Theoretical Computer Science* 5.3 (1977), pp. 223–255. DOI: 10.1016/0304-3975(77)90044-5.

[Plot83] Gordon Plotkin. ‘Domains’. Lecture notes on domain theory, known as the *Pisa Notes*. 1983. URL: https://homepages.inf.ed.ac.uk/gdp/publications/Domains_a4.ps.

References IV

- [RS99] Bernhard Reus and Thomas Streicher. ‘General synthetic domain theory – a logical approach’. In: *Mathematical Structures in Computer Science* 9.2 (1999), pp. 177–223. DOI: 10.1017/S096012959900273X.
- [SVV96] Giovanni Sambin, Silvio Valentini and Paolo Virgili. ‘Constructive domain theory as a branch of intuitionistic pointfree topology’. In: *Theoretical Computer Science* 159.2 (June 1996), pp. 319–341. DOI: 10.1016/0304-3975(95)00169-7.

References V

[Sco72] Dana Scott. ‘Continuous lattices’. In: *Toposes, Algebraic Geometry and Logic*. Ed. by F.W. Lawvere. Vol. 274. Lecture Notes in Mathematics. 1972, pp. 97–136. DOI: 10.1007/BFb00733967.

[Sco93] Dana S. Scott. ‘A type-theoretical alternative to ISWIM, CUCH, OWHY’. In: *Theoretical Computer Science* 121.1 (1993), pp. 411–440. DOI: 10.1016/0304-3975(93)90095-B.

[Str06] Thomas Streicher. *Domain-Theoretic Foundations of Functional Programming*. World Scientific, 2006. DOI: 10.1142/6284.

[Uni13] The Univalent Foundations Program. *Homotopy Type Theory: Univalent Foundations of Mathematics*. Institute for Advanced Study: <https://homotopytypetheory.org/book>, 2013.