Information Access with Apache Lucene - Part 2

Metodi per il Ritrovamento dell'Informazione

Laurea Triennale in Informatica

Università degli Studi di Bari Aldo Moro

Prof. Cataldo Musto

cataldo.musto@uniba.it

Credits: Marco Polignano

Code Repository & Requirements

Code repository

https://github.com/swapUnibaAcademy/MRI_Lab

Requirements

- Java SDK 1.8+ https://www.java.com/en/download/
- IDE: NetBeans, IntelliJ, Eclipse, …
- **Maven:** https://maven.apache.org/guides/getting-started/maven-in-five-minutes.html



http://lucene.apache.org

APACHE LUCENE

Documentation

https://lucene.apache.org/core/10_3_1/index.html

Apache Lucene



Scan for the Doc

- Apache Software Foundation project
  - http://lucene.apache.org
- What Lucene is
  - Search library: indexing and searching Application Programming Interface (API)
- What Lucene is not
  - Search engine (no crawling, server, user interface, etc.)


Lucene




Scan for the Doc

- Full-text search
- High performance
- Scalable
- Cross-platform
- 100%-pure Java
- Porting in other languages:
  - Perl, C#, C++, Python, Ruby e PHP

Information Retrieval Process



From Concepts to Java Classes



Document

- The main entity involved in a IR process

- **A collection of *Fields*** which give structure to the document
- A Field has three parts
  - Name
  - Type
  - Value
    - text (String, Reader or pre-analyzed TokenStream)
    - binary (byte[])
    - numeric (a Number)

- Each field needs to be added to the document
- A Field may be stored in the index (TYPE_STORED), so it may be returned with hits on the document.

Document: Fields Representation

http://www.bbc.co.uk/news/technology-15365207




Document: Fields Representation



Document: Fields Representation




Overview of the Process




Step 1
Create a document and populate its fields

Overview of the Process



Step 2
Add the documents to a Lucene Index, through the IndexWriter class


Overview of the Process



Step 3

Search the Index by defining a query and submit it to the index

Overview of the Process



Step 4

Use the IndexSearcher class to submit the query to the index. Next, the search method returns the top documents matching the query.

Let’s Start





Let’s start

1) Download the repository (you can use a GUI as well)
git clone https://github.com/swapUnibaAcademy/MRI_Lab

2) Create a new project
File → Open →
Import content from **./code/LuceneLab**
(pom.xml is there)

Let’s start

Alternatively, you can directly clone the project

From IntelliJ IDEA:
File → New → Project from Version Control

Paste the GitHub repository URL.
Choose a destination folder.
Click **Clone**.

IntelliJ will clone the project and automatically try to detect Maven.

Hello World

See the class `uniba.mri.lucene.HelloWorld.java`

This class creates a **Document** object and populates its fields

Hello World

See the class `uniba.mri.lucene.HelloWorld.java`

```
//Open a directory from the file system (index directory)
FSDirectory fsdir = FSDirectory.open(new
File("./resources/documenti_news").toPath());

//IndexWriter configuration
IndexWriterConfig iwc = new IndexWriterConfig(new
StandardAnalyzer());

//Index directory is created if not exists or
overwritten
iwc.setOpenMode(IndexWriterConfig.OpenMode.CREATE)

//Create IndexWriter
IndexWriter writer = new IndexWriter(fsdir, iwc);
```

Hello World

See the class `uniba.mri.lucene.HelloWorld.java`

```
//Open a directory from the file system (index directory)
FSDirectory fsdir = FSDirectory.open(new
File("./resources/documenti_news").toPath());

//IndexWriter configuration
IndexWriterConfig iwc = new IndexWriterConfig(new
StandardAnalyzer());

//Index directory is created if not exists or
overwritten
iwc.setOpenMode(IndexWriterConfig.OpenMode.CREATE)

//Create IndexWriter
IndexWriter writer = new IndexWriter(fsdir, iwc);
```

Si può creare in CREATE o APPEND

Hello World

See the class `uniba.mri.lucene.HelloWorld.java`

```
//Create document and add fields
Document doc = new Document();

doc.add(new TextField("super_name", "Spider-Man", Field.Store.NO));
doc.add(new TextField("name", "Peter Parker", Field.Store.NO));
doc.add(new TextField("category", "superhero", Field.Store.NO));
doc.add(new TextField("powers", "agility, spider-sense",
                      Field.Store.NO));

//add document to index
writer.addDocument(doc);

//close IndexWriter
writer.close();
```

Hello World

See the class `uniba.mri.lucene.HelloWorld.java`

```
//Create document and add fields
Document doc = new Document();
doc.add(new TextField("super_name", "Spider-Man",
Field.Store.NO));
doc.add(new TextField("name", "Peter Parker", Field.Store.NO));
doc.add(new TextField("category", "superhero", Field.Store.NO));
doc.add(new TextField("powers", "agility, spider-sense",
Field.Store.NO));

//add document to index
writer.addDocument(doc);
//close IndexWriter
writer.close();
```

Può essere YES oppure NO.
Indica se vogliamo memorizzare il campo o meno. **Attenzione:** non significa che non possiamo fare ricerche su quel campo, significa che non possiamo più risalirne al contenuto.

Hello World

See the class `uniba.mri.lucene.HelloWorld.java`

```
//Create document and add fields
Document doc = new Document();
doc.add(new TextField("super_name", "Spider-Man",
Field.Store.NO));
doc.add(new TextField("name", "Peter Parker", Field.Store.NO));
doc.add(new TextField("category", "superhero", Field.Store.NO));
doc.add(new TextField("powers", "agility, spider-sense",
Field.Store.NO));

//add document to index
writer.addDocument(doc);
//close IndexWriter
writer.close();

// Crea un IndexReadER
IndexReader reader =  DirectoryReader.open(sdir);
// Conta il numero di documenti attivi (non cancellati)
int numDocs = reader.numDocs();
System.out.println("Numero di documenti nell'indice: " + numDocs);
```

Field Constructors

- `TextField(String name, String value, Field.Store store)`
  - Descrizione: Crea un campo di **testo**. Il valore del campo viene analizzato (tokenizzato) utilizzando l'analizzatore predefinito.

- `StringField(String name, String value, Field.Store store)`
  - Descrizione: Crea un campo di tipo **stringa**. Il valore non viene analizzato, ma viene indicizzato così com'è.

- `NumericDocValuesField(String name, long value)`
  - Descrizione: Crea un campo **numerico (float o double).** Il valore viene indicizzato, e puoi scegliere di memorizzarlo.

- `BinaryField(String name, byte[] value, Field.Store store)`
  - Descrizione: Crea un campo **binario** che può contenere dati in formato binario. Questo è utile per memorizzare file o dati non testuali.

- `Field(String name, String value, FieldType fieldType)`
  - Descrizione: Crea un campo **generico** che può utilizzare un tipo di campo personalizzato definito da FieldType.

Field Constructors (ex.)

```
// Aggiungi un campo testo
doc.add(new TextField("title", "Il Signore degli Anelli",
Field.Store.YES));

// Aggiungi un campo di stringa (non memorizzato)
doc.add(new StringField("author", "J.R.R. Tolkien",
Field.Store.NO));

// Aggiungi un campo numerico
doc.add(new NumericField("publicationYear", 1954,
Field.Store.YES));
```

Adding documents to an Index

- `addDocument(Iterable<? extends IndexableField> doc)`

  Adds a document to this index.

- `addDocuments(Iterable<? extends Iterable<? extends IndexableField>> docs)`

  Atomically adds a block of documents with sequentially assigned document IDs, such that an external reader will see all or none of the documents.

uniba.mri.lucene.AddMultipleDocs.java

Add Multiple Docs

```
List<Document> docs = new ArrayList<>();

Document doc1 = new Document();
doc1.add(new TextField("title", "Alice in Wonderland", Field.Store.YES));
doc1.add(new TextField("content", "A girl falls into a rabbit hole.", Field.Store.YES));
docs.add(doc1);

Document doc2 = new Document();
doc2.add(new TextField("title", "Through the Looking-Glass", Field.Store.YES));
doc2.add(new TextField("content", "Alice steps through a mirror.", Field.Store.YES));
docs.add(doc2);

Document doc3 = new Document();
doc3.add(new TextField("title", "Alice in Quantumland", Field.Store.YES));
doc3.add(new TextField("content", "A journey through the quantum world.",
Field.Store.YES));
docs.add(doc3);

// aggiunge tutti i documenti in un colpo solo
writer.addDocuments(docs);

// forza il commit dei dati su disco
writer.commit();

System.out.println(docs.size() + " documenti aggiunti all'indice in " + indexPath);
```

uniba.mri.lucene.AddMultipleDocs.java

Add Multiple Docs

```
List<Document> docs = new ArrayList<>();
```

We store the documents in a ArrayList

```
Document doc1 = new Document();
doc1.add(new TextField("title", "Alice in Wonderland", Field.Store.YES));
doc1.add(new TextField("content", "A girl falls into a rabbit hole.", Field.Store.YES));
docs.add(doc1);

Document doc2 = new Document();
doc2.add(new TextField("title", "Through the Looking-Glass", Field.Store.YES));
doc2.add(new TextField("content", "Alice steps through a mirror.", Field.Store.YES));
docs.add(doc2);

Document doc3 = new Document();
doc3.add(new TextField("title", "Alice in Quantumland", Field.Store.YES));
doc3.add(new TextField("content", "A journey through the quantum world.",
Field.Store.YES));
docs.add(doc3);

// aggiunge tutti i documenti in un colpo solo
writer.addDocuments(docs);
```

We add all the documents at once

```
// forza il commit dei dati su disco
writer.commit();

System.out.println(docs.size() + " documenti aggiunti all'indice in " + indexPath);
```

Preliminary Exercise

- Extend **`helloworld.java`**

- Add more documents to the index (with different content)
  - Focus on the, i.e., News Domain (title, author, content, tags, date, etc.) or another one


- Print the number of documents in the index, to check that everything is ok

Lucene Model - Searcher

- Based on **Vector Space Model**


	D1	D2	D3	
Cheshire Cat	1	0	1	
Alice	2	2	2	
book	1	0	0	
King	1	1	0	
table	0	1	1	
Queen	0	1	1	
grin	0	0	2	

Every document is a vector!



Lucene Model - Searcher

- Based on **Vector Space Model**




Every document is a vector!

Lucene Model - Searcher

- Based on **Vector Space Model**

	D1	D2	D3	Q
Cheshire Cat	1	0	1	0
Alice	2	2	2	1
book	1	0	0	0
King	1	1	0	0
table	0	1	1	0
Queen	0	1	1	1
grin	0	0	2	0

The query is a vector as well



Lucene Model - Searcher

- Based on **Vector Space Model**
- **How is the relevance calculated in Lucene?**

Lucene Model - Searcher

- Based on **Vector Space Model**
- How is the relevance calculated in Lucene?

- Relevance is based on Okapi BM25 Scoring Function
  - https://en.wikipedia.org/wiki/Okapi_BM25

  - BM25 improves the classical similarity score based on TF-IDF by introducing two new parameters
    - One to handle the problem of **document length**
    - One to handle the **«saturation» problem** of TF

More info https://lucene.apache.org/core/10_3_1/core/org/apache/lucene/search/similarities/package-summary.html

Lucene Model - Searcher

$$\text{Score}(D, Q) = \sum_{i \in Q} \text{IDF}(q_i) \cdot \frac{\text{tf}(q_i, D) \cdot (k_1 + 1)}{\text{tf}(q_i, D) + k_1 \cdot \left(1 - b + b \cdot \frac{|D|}{\text{avgdl}}\right)}$$

More info https://lucene.apache.org/core/10_3_1/core/org/apache/lucene/search/similarities/package-summary.html

Lucene Model - Searcher

$$\text{Score}(D, Q) = \sum_{i \in Q} \text{IDF}(q_i) \cdot \frac{\text{tf}(q_i, D) \cdot (k_1 + 1)}{\text{tf}(q_i, D) + k_1 \cdot \left(1 - b + b \cdot \frac{|D|}{\text{avgdl}}\right)}$$

(document, query)

More info https://lucene.apache.org/core/10_3_1/core/org/apache/lucene/search/similarities/package-summary.html

Lucene Model - Searcher

$$\text{Score}(D, Q) = \sum_{i \in Q} \text{IDF}(q_i) \cdot \frac{\text{tf}(q_i, D) \cdot (k_1 + 1)}{\text{tf}(q_i, D) + k_1 \cdot \left(1 - b + b \cdot \frac{|D|}{\text{avgdl}}\right)}$$

IDF score

More info https://lucene.apache.org/core/10_3_1/core/org/apache/lucene/search/similarities/package-summary.html

Lucene Model - Searcher

TF score

$$\text{Score}(D,Q) = \sum_{i \in Q} \text{IDF}(q_i) \cdot \frac{\text{tf}(q_i, D) \cdot (k_1 + 1)}{\text{tf}(q_i, D) + k_1 \cdot \left(1 - b + b \cdot \frac{|D|}{\text{avgdl}}\right)}$$

IDF score

More info https://lucene.apache.org/core/10_3_1/core/org/apache/lucene/search/similarities/package-summary.html

Lucene Model - Searcher

$$\text{Score}(D,Q) = \sum_{i \in Q} \text{IDF}(q_i) \cdot \frac{\text{tf}(q_i, D) \cdot (k_1 + 1)}{\text{tf}(q_i, D) + k_1 \cdot \left(1 - b + b \cdot \frac{|D|}{\text{avgdl}}\right)}$$

Saturation parameter

Length normalization parameter

More info https://lucene.apache.org/core/10_3_1/core/org/apache/lucene/search/similarities/package-summary.html

Lucene Model – Saturation Parameter

$$\text{Score}(D,Q) = \sum_{i \in Q} \text{IDF}(q_i) \cdot \frac{\text{tf}(q_i, D) \cdot (k_1 + 1)}{\text{tf}(q_i, D) + k_1 \cdot \left(1 - b + b \cdot \frac{|D|}{\text{avgdl}}\right)}$$

Intuitively, if

tf(x1,D)=5 and **tf(x2,D)=10**

is x2 twice as important of x1. **But, is this interpretation correct?**

Should the relation between «occurrences» and «importance» be linear ?

More info https://lucene.apache.org/core/10_3_1/core/org/apache/lucene/search/similarities/package-summary.html

Lucene Model – Saturation Parameter

$$\text{Score}(D,Q) = \sum_{i \in Q} \text{IDF}(q_i) \cdot \frac{\text{tf}(q_i, D) \cdot (k_1 + 1)}{\text{tf}(q_i, D) + k_1 \cdot \left(1 - b + b \cdot \frac{|D|}{\text{avgdl}}\right)}$$

Intuitively, if

tf(x1,D)=5 and **tf(x2,D)=10**

is x2 twice as important of x1. **But, is this interpretation correct?**

Should the relation between «occurrences» and «importance» be linear ?

More info https://lucene.apache.org/core/10_3_1/core/org/apache/lucene/search/similarities/package-summary.html

Lucene Model – Saturation Parameter

$$\text{Score}(D,Q) = \sum_{i \in Q} \text{IDF}(q_i) \cdot \frac{\text{tf}(q_i, D) \cdot (k_1 + 1)}{\text{tf}(q_i, D) + k_1 \cdot \left(1 - b + b \cdot \frac{|D|}{\text{avgdl}}\right)}$$

Intuitively, if

tf(x1,D)=5 and **tf(x2,D)=10**

is x2 twice as important of x1. **But, is this interpretation correct?**

Should the relation between «occurrences» and «importance» be linear ?

Saturation parameter (k) reduces the importance of tf

- Low values = quick saturation (i.e., after a few occurrences, the importance of each new occurence decreases)

More info https://lucene.apache.org/core/10_3_1/core/org/apache/lucene/search/similarities/package-summary.html

Term Frequency (tf)

$$\text{TF contribution} = \frac{\text{tf} \cdot (k_1 + 1)}{\text{tf} + k_1} \qquad (\text{assuming } |D|/\text{avgdl} = 1)$$

1.2 is the default parameter in Lucene

More info https://lucene.apache.org/core/10_3_1/core/org/apache/lucene/search/similarities/package-summary.html

Term Frequency (tf)

$$\text{TF contribution} = \frac{\text{tf} \cdot (k_1 + 1)}{\text{tf} + k_1} \qquad (\text{assuming } |D|/\text{avgdl} = 1)$$

k_1	Maximum value (as tf → ∞)	tf = 5			tf = 10		
		Numerator	Denominator	Value	Numerator	Denominator	Value
0.5	1.5	5 · 1.5 = 7.5	5 + 0.5 = 5.5	**1.364**	10 · 1.5 = 15	10 + 0.5 = 10.5	**1.429**

1.2 is the default parameter in Lucene

More info https://lucene.apache.org/core/10_3_1/core/org/apache/lucene/search/similarities/package-summary.html


Term Frequency (tf)

$$\text{TF contribution} = \frac{\text{tf} \cdot (k_1 + 1)}{\text{tf} + k_1} \qquad (\text{assuming } |D|/\text{avgdl} = 1)$$

k_1	Maximum value (as tf → ∞)	tf = 5			tf = 10		
		Numerator	Denominator	Value	Numerator	Denominator	Value
0.5	1.5	5 · 1.5 = 7.5	5 + 0.5 = 5.5	1.364	10 · 1.5 = 15	10 + 0.5 = 10.5	1.429
1.2	2.2	5 · 2.2 = 11	5 + 1.2 = 6.2	1.774	10 · 2.2 = 22	10 + 1.2 = 11.2	2.015
2	3.0	5 · 3 = 15	5 + 2 = 7	2.143	10 · 3 = 30	10 + 2 = 12	2.500

1.2 is the default parameter in Lucene

More info https://lucene.apache.org/core/10_3_1/core/org/apache/lucene/search/similarities/package-summary.html



$$\text{TF contribution} = \frac{\text{tf} \cdot (k_1 + 1)}{\text{tf} + k_1} \qquad (\text{assuming } |D|/\text{avgdl} = 1)$$

k_1	Maximum value (as tf → ∞)	tf = 5			tf = 10		
		Numerator	Denominator	Value	Numerator	Denominator	Value
0.5	1.5	5 · 1.5 = 7.5	5 + 0.5 = 5.5	1.364	10 · 1.5 = 15	10 + 0.5 = 10.5	1.429
1.2	2.2	5 · 2.2 = 11	5 + 1.2 = 6.2	1.774	10 · 2.2 = 22	10 + 1.2 = 11.2	2.015
2	3.0	5 · 3 = 15	5 + 2 = 7	2.143	10 · 3 = 30	10 + 2 = 12	2.500

1.2 is the default parameter in Lucene

More info https://lucene.apache.org/core/10_3_1/core/org/apache/lucene/search/similarities/package-summary.html

Lucene Model - Searcher

$$\text{Score}(D,Q) = \sum_{i \in Q} \text{IDF}(q_i) \cdot \frac{\text{tf}(q_i, D) \cdot (k_1 + 1)}{\text{tf}(q_i, D) + k_1 \cdot \left(1 - b + b \cdot \frac{|D|}{\text{avgdl}}\right)}$$

Normalization length parameter (b) weighs the importance of document length in the retrieval process

Intuition:

If a term has high occurrences in a very long document is less interesting than having high occurrences in a shorter document

More info https://lucene.apache.org/core/10_3_1/core/org/apache/lucene/search/similarities/package-summary.html

Lucene Model - Searcher

$$\text{Score}(D,Q) = \sum_{i \in Q} \text{IDF}(q_i) \cdot \frac{\text{tf}(q_i, D) \cdot (k_1 + 1)}{\text{tf}(q_i, D) + k_1 \cdot \left(1 - b + b \cdot \frac{|D|}{\text{avgdl}}\right)}$$

Normalization length parameter (b) weighs the importance of document length in the retrieval process

- b=0 → no normalization
- b=1 (max value) → the document length is highly considered to calculate the relevance
  - Why? If the document is longer than the average (ratio > 1) the tf is multiplied by a positive value. So, the denominator becomes larger and the final score becomes smaller

More info https://lucene.apache.org/core/10_3_1/core/org/apache/lucene/search/similarities/package-summary.html

Lucene Model - Searcher

$$\text{Score}(D,Q) = \sum_{i \in Q} \text{IDF}(q_i) \cdot \frac{\text{tf}(q_i, D) \cdot (k_1 + 1)}{\text{tf}(q_i, D) + k_1 \cdot \left(1 - b + b \cdot \frac{|D|}{\text{avgdl}}\right)}$$

Saturation parameter

Length normalization parameter

Saturation parameter (k) reduces the importance of tf

- Low values = quick saturation (i.e., after a few occurrences, the importance of each new occurence decreases)

Normalization length parameter (b) weighs the importance of document length in the retrieval process

- **If b= 1**the document length is highly considered to calculate the relevance

Search the Index

See the class `uniba.mri.lucene.SearchIndex.java`

In this example, we search a Lucene Index

Classes to be used:

- **`IndexSearcher`**
  - Indicates the index to be searched
- **`QueryParser`**
  - Indicates the characteristics of the query (i.e., on which field)
- **`Query`**
  - Indicates the content of the query

Search the Index

See the class `uniba.mri.lucene.SearchIndex.java`

```
//Create the IndexSearcher
IndexSearcher searcher = new IndexSearcher(DirectoryReader.open(fsdir));
//Create the query parser with the default field and analyzer
QueryParser qp = new QueryParser("name", new StandardAnalyzer());
//Parse the query
Query q = qp.parse("parker");

//Search
TopDocs topdocs = searcher.search(q, 10);
System.out.println("Found " + topdocs.totalHits.value + " document(s).");
```

Search the Index

See the class `uniba.mri.lucene.SearchIndex.java`

```
//Create the IndexSearcher
IndexSearcher searcher = new IndexSearcher(DirectoryReader.open(fsdir));
//Create the query parser with the default field and analyzer
QueryParser qp = new QueryParser("name", new StandardAnalyzer());
//Parse the query
Query q = qp.parse("parker");

//Search
TopDocs topdocs = searcher.search(q, 10);
System.out.println("Found " + topdocs.totalHits.value + " document(s).");
```

Indichiamo il campo su cui effettuare la ricerca e il contenuto della query

Query Parser (ex.)

Utilizzando **`MultiFieldQueryParser( )`** si possono interrogare più campi in parallelo.

```
// Inizializza i nomi dei campi che vuoi interrogare
String[] fields = {"name", "category", "powers"};

// Creazione di MultiFieldQueryParser
MultiFieldQueryParser parser = new
       MultiFieldQueryParser(fields, analyzer);

// Definisci la query
String queryString = "parker";
Query query = parser.parse(queryString);

// Esegue la query
IndexSearcher searcher = new
       IndexSearcher(DirectoryReader.open(directory));
TopDocs results = searcher.search(query, 10);
```





Query Parser (ex.)

Concettualmente uguale a «name:parker OR category:parker OR powers:parker»

```
// Inizializza i nomi dei campi che vuoi interrogare
String[] fields = {"name", "category", "powers"};

// Creazione di MultiFieldQueryParser
MultiFieldQueryParser parser = new
       MultiFieldQueryParser(fields, analyzer);

// Definisci la query
String queryString = "parker";
Query query = parser.parse(queryString);

// Esegue la query
IndexSearcher searcher = new
       IndexSearcher(DirectoryReader.open(directory));
TopDocs results = searcher.search(query, 10);
```







Exercise 0

- Modify **`searchIndex.java`**
- Create a new index (define the **fields** and the **content** you prefer)
  - Be realistic, figure out a real use case with 10 documents (i.e., sport news)
- Check the number of documents in the index
- Try some queries, and check if the number of documents matching the query is correct

Recap: Lucene Architecture



Let's focus on Analyzers




Text Analysis

- **Main Operations**
  - **Tokenization**
    - split text in token
  - **Stop word elimination**
    - remove common words
  - **Stemming**
    - reducing inflected (or sometimes derived) words to their stem

More info
https://lucene.apache.org/core/10_3_1/analysis/common/index.html

Text Analysis



Text Analysis

- **Analyzer:** encapsulates the analysis process
  - **Tokenize a text** by performing any number of operations on it
  - Responsible for **building the TokenStream** consumed by the indexing and searching processes

We have already found it in the previous exercise

```
IndexWriterConfig iwc = new IndexWriterConfig(new
StandardAnalyzer());

QueryParser qp = new QueryParser("name", new
StandardAnalyzer());
```

Analyzers

Lucene includes a number od «standard» analyzers

Each analyzer uses one of the filters and one of the tokenizers

- **KeywordAnalyzer**
  - Returns a single token
- **WhitespaceAnalyzer**
  - Splits tokens at whitespace
- **SimpleAnalyzer**
  - Divides text at non letter characters and lowercases
- **StopAnalyzer**
  - Divides text at non letter characters, lowercases, and removes stop words
- **StandardAnalyzer**
  - Tokenizes based on sophisticated grammar that recognizes e-mail addresses, acronyms, etc.; lowercases and removes stop words (optional)

Analyzers

Input Text (ex.)

The quick brown fox jumped over the lazy dogs

- WhitespaceAnalyzer:
  [The] [quick] [brown] [fox] [jumped] [over] [the] [lazy] [dogs]
- SimpleAnalyzer:
  [the] [quick] [brown] [fox] [jumped] [over] [the] [lazy] [dogs]
- StopAnalyzer:
  [quick] [brown] [fox] [jumped] [lazy] [dogs]
- StandardAnalyzer:
  [quick] [brown] [fox] [jumped] [over] [lazy] [dogs]

Analyzers

Input Text (ex.)

"XY&Z Corporation - xyz@example.com"

- WhitespaceAnalyzer:
  [XY&Z] [Corporation] [-] [xyz@example.com]
- SimpleAnalyzer:
  [xy] [z] [corporation] [xyz] [example] [com]
- StandardAnalyzer:
  [xy&z] [corporation] [xyz@example.com]

Test Analyzer

See the class `uniba.mri.lucene.TestAnalyzer`

```
public static void main(String[] args) throws IOException {
text = "the full-text indexing and search API: lucene.apache.org";

System.out.println(getTokens(new StringReader(text), new WhitespaceAnalyzer()));

System.out.println(getTokens(new StringReader(text), new StandardAnalyzer()));

System.out.println(getTokens(new StringReader(text), new StandardAnalyzer(new
FileReader("resources/en_stopword"))));

System.out.println(getTokens(new StringReader(text), new EnglishAnalyzer()));

System.out.println(getTokens(new StringReader(text), new MyAnalyzer()));
}
```

Test Analyzer

See the class `uniba.mri.lucene.TestAnalyzer`

```
public static void main(String[] args) throws IOException {
text = "the full-text indexing and search API: lucene.apache.org";

System.out.println(getTokens(new StringReader(text), new WhitespaceAnalyzer()));

System.out.println(getTokens(new StringReader(text), new StandardAnalyzer()));

System.out.println(getTokens(new StringReader(text), new StandardAnalyzer(new
FileReader("resources/en_stopword"))));

System.out.println(getTokens(new StringReader(text), new EnglishAnalyzer()));

System.out.println(getTokens(new StringReader(text), new MyAnalyzer()));
}
```

Function that prints the token obtained by processing the string

Test Analyzer

See the class `uniba.mri.lucene.TestAnalyzer`

```
//Implementazione di getTokens()
public static List<String> getTokens(Reader reader, Analyzer analyzer) throws
   IOException {
    List<String> tokens = new ArrayList<>();
    //Creiamo un flusso di token e lo inizializziamo
    TokenStream tokenStream = analyzer.tokenStream("text", reader);
    tokenStream.reset();
    //Istruzione per accedere al token corrente
    CharTermAttribute cattr = tokenStream.addAttribute(CharTermAttribute.class);
    while (tokenStream.incrementToken()) {
         String token = cattr.toString();
         tokens.add(token);
    }
    tokenStream.end();
    return tokens;
    }
```

Test Analyzer

See the class `uniba.mri.lucene.TestAnalyzer`

```
//Implementazione di getTokens()
public static List<String> getTokens(Reader reader, Analyzer analyzer) throws
   IOException {
```

```
return tokens;
}
```

La particolare tipologia di **analyzer** che utilizziamo è responsabile di determinare il flusso di token

Test Analyzer

See the class `uniba.mri.lucene.TestAnalyzer`

```
//Implementazione di getTokens()
public static List<String> getTokens(Reader reader, Analyzer analyzer) throws
   IOException {
    List<String> tokens = new ArrayList<>();
    //Creiamo un flusso di token e lo inizializziamo
    TokenStream tokenStream = analyzer.tokenStream("text", reader);
    tokenStream.reset();
    //Istruzione per accedere al token corrente
    CharTermAttribute cattr = tokenStream.addAttribute(CharTermAttribute.class);
    while (tokenStream.incrementToken()) {
         String token = cattr.toString();
         tokens.add(token);
    }
    tokenStream.end();
    return tokens;
    }
```

La particolare tipologia di **analyzer** che utilizziamo è responsabile di determinare il flusso di token

Test Analyzer

See the class `uniba.mri.lucene.TestAnalyzer`

```
//Implementazione di getTokens()
public static List<String> getTokens(Reader reader, Analyzer analyzer) throws
   IOException {
    List<String> tokens = new ArrayList<>();
    //Creiamo un flusso di token e lo inizializziamo
    TokenStream tokenStream = analyzer.tokenStream("text", reader);
    tokenStream.reset();
    //Istruzione per accedere al token corrente
    CharTermAttribute cattr = tokenStream.addAttribute(CharTermAttribute.class);
    while (tokenStream.incrementToken()) {
         String token = cattr.toString();
         tokens.add(token);
    }
    tokenStream.end();
    return tokens;
    }
```

Ogni token non è una semplice stringa, è un insieme di attributi (viene memorizzata la posizione, l'offset, etc.)

Test Analyzer

See the class `uniba.mri.lucene.TestAnalyzer`

```
public static void main(String[] args) throws IOException {

    System.out.println(getTokens(new StringReader("the full-text indexing and
search API: lucene.apache.org"), new WhitespaceAnalyzer()));

    System.out.println(getTokens(new StringReader("the full-text indexing and
search API: lucene.apache.org"), new StandardAnalyzer()));


    System.out.println(getTokens(new StringReader("the full-text indexing and
search API: lucene.apache.org"), new StandardAnalyzer(new
FileReader("resources/en_stopword"))));

    System.out.println(getTokens(new StringReader("the full-text indexing and
search API: lucene.apache.org"), new EnglishAnalyzer()));


    System.out.println(getTokens(new StringReader("the full-text indexing and
search API: lucene.apache.org"), new MyAnalyzer()));
}
```

This is a custom analyzer

Text Analysis



Text Analysis



Text Analysis

- **Analyzer:** encapsulates the analysis process
  - **Tokenize a text** by performing any number of operations on it
  - Responsible for **building the TokenStream** consumed by the indexing and searching processes
- **Tokenizer:** is part of the TokenStream process
  - Responsible for breaking up incoming text into tokens
- **TokenFilter:** is also a TokenStream and is responsible for modifying tokens that have been created by the Tokenizer

Tokenizers

- **Tokenization** is the process of breaking input text into small indexing elements, *e.g.* tokens
- A Tokenizer produces a TokenStream and is responsible for breaking up incoming text into tokens. Usually Analyzer will use a Tokenizer as the first step in the analysis process

source string: "full-text lucene.apache.org"

- **StandardTokenizer**
  - "full" "text" "lucene.apache.org"
- **WhitespaceTokenizer**
  - "full-text" "lucene.apache.org"
- **LetterTokenizer**
  - "full" "text" "lucene" "apache" "org"

TokenFilters

- A **TokenFilter** also generates a TokenStream and is responsible for modifying tokens that have been created by the Tokenizer.

- **LowerCaseFilter**
- **StopFilter**
- **LengthFilter**
- **PorterStemFilter**
  - stemming: reducing words to root form
  - rides, ride, riding => ride
  - country, countries => countri

Custom Analyzer

See the class `uniba.mri.lucene.MyAnalyzer`

```
@Override
protected TokenStreamComponents createComponents(String fieldName) {
    Tokenizer source = new LetterTokenizer(); //divide parola per parola
    TokenStream filter = new LowerCaseFilter(source); //minuscole
    filter = new StopFilter(filter, STOP_WORDS);  //nuovo filtro
    return new TokenStreamComponents(source, filter);
    }
```

Custom Analyzer

See the class `uniba.mri.lucene.MyAnalyzer`

```
// Creiamo una variabile statica STOP_WORDS
public static final CharArraySet STOP_WORDS;

// e la inizializziamo
static { final List<String> stopWords = Arrays.asList("a", "an", "and",
"are", "the", "is", "but", "by");
    //strutture dati ottimizzate per memorizzare stringhe
    final CharArraySet stopSet = new CharArraySet(stopWords, false);
    STOP_WORDS = CharArraySet.unmodifiableSet(stopSet);
}

@Override
protected TokenStreamComponents createComponents(String fieldName) {
        Tokenizer source = new LetterTokenizer(); //divide parola per parola
        TokenStream f = new LowerCaseFilter(source); //minuscole
        f = new StopFilter(filter, STOP_WORDS); // nuovo filtro
    return new TokenStreamComponents(source, filter);
    }
```

Exercise – Custom Analyzer

- **Modificare l'esercizio precedente**
  - Predisporre una lista di stopwords per la lingua italiana
  - Provare diversi tokenizer

Lanciare il codice per testarlo

Usare frasi in inglese e in italiano per notare le differenze

Exercise – Custom Analyzer

- **Modificare l'esercizio precedente**
  - Predisporre una lista di stopwords per la lingua italiana
  - Provare diversi tokenizer

Lanciare il codice per testarlo

Usare frasi in inglese e in italiano per notare le differenze

SPOILER

```
import org.apache.lucene.analysis.it.ItalianAnalyzer;

final CharArraySet stopSet = ItalianAnalyzer.getDefaultStopSet();

STOP_WORDS = CharArraySet.unmodifiableSet(stopSet);
```

Exercise 1

- Index the famous novel **Alice In Wonderland** in a Lucene searchable index.
  - Find the content in: **./resources/Alice_Adv_Lewis_Carroll_utf8.text**

- You should index each **Chapter** as a separate Lucene Document.

- Each Document should contain four fields:
  1. The **Title** of the Book
  2. The **Author** of the Book
  3. The **title** of the Chapter
  4. The **text** of the Chapter

Of course, **title and author remain the same** for all the chapters/documents, while the **title and the text change**

Exercise 1 - walkthrough

1. Create a **new index** (indicate the directory as a parameter)

2. Create a **new Analyzer** and a **new IndexWriter**, with their configurations

Exercise 1 - walkthrough

1. Create a **new index** (indicate the directory as a parameter)

```
FSDirectory fsdir = FSDirectory.open(new
          File("./resources/alice").toPath());
```

2. Create a **new Analyzer** and a **new IndexWriter**, with their configurations

```
StandardAnalyzer analyzer = new StandardAnalyzer();

IndexWriterConfig config = new IndexWriterConfig(analyzer);
config.setOpenMode(IndexWriterConfig.OpenMode.CREATE_OR_APPEND);
IndexWriter writer = new IndexWriter(fsdir, config);
```

Exercise 1 - walkthrough

1. ~~Create a **new index** (indicate the directory as a parameter)~~ 

2. ~~Create a **new Analyzer** and a **new IndexWriter**, with their configurations~~ 

3. **Open the text file** with the content. Create a variable for each element to be stored (title, author, chapter, text)

4. Go through the content and identify a strategy to **isolate the different pieces of text**
   a) When do you understand that a new chapter started?
   b) When do you understand that a new paragraph started?

5. Store each paragraph (together with the other fields) **as a new document.**

Exercise 1 - walkthrough

3. Open the text file with the content. Create a variable for each element to be stored (title, author, chapter, text)

Exercise 1 - walkthrough

3. Open the text file with the content. Create a variable for each element to be stored (title, author, chapter, text)

Suggestion:
Write the instructions to open a text file (i.e.,with **`BufferedReader`** and **`readline( )`**) and go through the content.
If you need it, print the content in the console and/or open the source document in a text editor

Exercise 1 - walkthrough

3. Open the text file with the content. Create a variable for each element to be stored (title, author, chapter, text)

Suggestion:
Write the instructions to open a text file (i.e.,with **`BufferedReader`** and **`readline( )`**) and go through the content.
If you need it, print the content in the console and/or open the source document in a text editor

```
String title = b.readLine();          Rigo 1
b.readLine();                                  Rigo 2 (vuoto)

String author = b.readLine();         Rigo 3
b.readLine();                                  Rigo 4 (vuoto)
```

… poi iniziano i capitoli :-)

Exercise 1 - walkthrough

4. Isolate the different pieces of text

a) When do you understand that a new chapter has started?
b) When do you understand that a new paragraph has started?

Suggestion: Check empty lines and specific words :-)

Exercise 1 - walkthrough

4. Isolate the different pieces of text

a) When do you understand that a new chapter has started?
b) When do you understand that a new paragraph has started?

Suggestion: Check empty lines and specific words :-)

Solution

- Each chapter start with the word CHAPTER
- Each new paragraph, start the next line

Exercise 1 - walkthrough

4. Isolate the different pieces of text

a) When do you understand that a new chapter has started?
b) When do you understand that a new paragraph has started?

Suggestion: Check empty lines and specific words :-)

Solution

- Each chapter start with the word CHAPTER
  - **If (readLine.contains("CHAPTER")) …..**

- Each new paragraph, start the next line

How to check the solution?

Luke is a GUI tool for inspecting, searching, and analyzing Apache Lucene indexes, allowing users to explore documents, terms, and analyzers interactively.

How to check the solution?

Luke is a GUI tool for inspecting, searching, and analyzing Apache Lucene indexes, allowing users to explore documents, terms, and analyzers interactively.

How to obtain it?
It is included in the binary release of Lucene
lucene-10.3.1.tgz

How to check the solution?

- **The binary is included in the ./bin/ folder**
- **Select the folder where the index is stored (the folder!)**
- **Open it and analyze the index that is stored**

