

Delivery, Not Storage: Cue-Anchored Working Memory as a Harness Property for Coding Agents

Swapnanil Saha
Independent
swapnanilsaha26@gmail.com

July 2026

Abstract

Coding agents ship with one kind of memory: documents. Instruction files, plan artifacts, and auto-written memory directories are all *deliberately authored, deliberately retrieved*: the agent must choose to write them and choose to read them back. Human expertise runs on a second tier that never gets written down: situationally-bound operational facts (gotchas, locations, “how things are done here”) encoded as a side effect of doing the work and retrieved involuntarily when the situation cues them. We argue this second tier is the load-bearing one for long-running agents, and that it must be a **harness property, not an agent choice**.

We make four contributions. (1) A two-tier design theory grounded in the cognitive literature on memory offloading, incidental encoding, and event-based prospective memory, with each mechanism mapped to an architectural requirement. (2) A cue-anchored memory model: memories carry first-class trigger conditions over a composable vocabulary {path, symbol, semantic, event, temporal}, evaluated deterministically by the harness at the moments that structure an agent’s epistemic life, a composition no surveyed academic or shipped system provides. (3) A controlled evaluation on a naturalistic coding task showing that voluntary memory use is $\sim$ zero even when the store is pre-seeded with task-relevant knowledge (0 memory operations in 114 turns), that deterministic injection delivered in every injection-equipped seeded run ($n = 3$) with zero false-alarm fires across audit-logged trigger evaluations, and that 39% of intra-session re-reads re-retrieve content the session had already paid for before a compaction boundary. (4) A repeated-compaction decay probe: ten facts held only in conversation vanish at the first summary and stay absent from 106 of 108 ($k = 108$ forced compactations); by the closing phase the deprived agent is grepping the harness’s own session files off disk to reconstruct them — hand-building, against standing instruction, exactly the tier the harness never gave it. The same ten facts, injected from a harness-owned store, arrive intact through $k = 138 - 139$ audit-logged deliveries: the launch plus every single compact-resume (138/138) — while the final summary carries zero of them: the agent’s memory never depended on what the summarizer chose to keep. Delivery, not storage, is the product: the reliable memory channel for agents is the one the agent never has to think about.

1 Introduction

A competent engineer who joins a project reads the wiki once, then stops needing it. What makes them effective six months in is not the wiki — it is the accumulated mass of small operational facts that never got written down: this test is flaky under that flag; releases go through CI only; the catch-all route must stay last in that file. Nobody decides to memorize these. They are encoded as a side effect of doing the work, and they return uninvited, exactly when the situation cues them.

Current coding agents have the wiki and nothing else. The instruction file (CLAUDE.md and its siblings), the plan artifact, the auto-written memory directory — every persistent surface an agent has is a *document*: deliberately written, deliberately retrieved. The second tier does not exist. Each session is a competent worker with total amnesia who can read the wiki.

The obvious fix (give the agent memory tools) has been tried, and it measurably fails. MEM-TRACK [2] benchmarks memory-equipped agents and documents systematic failure to utilize memory across long horizons. TriggerBench [1] shows the deeper reason: acting on a latent standing constraint when its trigger appears (prospective memory) is much harder for models than retrieving stated facts (retrospective memory), and prospective performance *decays with context length*, precisely the regime long-running agents occupy. Our own controlled runs replicate this naturalistically and extend it to the strongest case: an agent whose store was **pre-seeded with facts directly relevant to its task**, with connected tools and explicit guidance, made zero memory calls in 114 turns (§5.2). Voluntary memory does not happen. Vendors concede this in their own products: Anthropic’s memory tool force-injects an all-caps directive to check memory before anything else; ChatGPT’s memory does automatic capture and automatic injection, with no voluntary lookup tool at all.

The distinction that organizes this paper is between memory as **content** and memory as **control**. A memory system operating in the *content plane* adds material to the context (files, instructions, protocols) and relies on the model’s compliance to turn that material into memory. A system operating in the *control plane* participates in constructing the context itself: it decides, deterministically, what enters the window and when. Field data makes the stakes concrete: a heavy user of an agentic coding CLI, documenting 59 context compactions over 26 days, built a three-tier file vault with standing orders and a compaction watcher [16]: an entire memory architecture in the content plane, operable only through relentless manual enforcement, because the control plane offered nothing. Everything they hand-built traces the shape of a missing harness feature.

This paper describes that feature and measures what its absence costs. Contributions:

- **C1 — Design theory (§2).** A two-tier account of engineering memory grounded in the cognitive literature, in which each mechanism (incidental encoding, cue-driven retrieval, endorsement, resistance to documentation) maps to a falsifiable architectural requirement.
- **C2 — Mechanism (§3).** A cue-anchored memory model: per-memory standing trigger conditions over {path, symbol, semantic, event, temporal}, evaluated deterministically harness-side, with budgeted, provenance-framed, staleness-checked delivery. No surveyed system composes these properties (§6).
- **C3 — Controlled evaluation (§5.1–5.6).** Twelve graded runs of a real feature task under asserted launch postures: voluntary use is $\sim$ zero even seeded (0 ops in 114 turns); deterministic delivery works through two independent channels with zero false alarms; count-based efficiency signals are consistently positive and honestly labeled directional; 39% of re-reads are cross-compaction re-purchases.
- **C4 — Decay probe (§5.7).** A forced-compaction experiment ($k = 108$ and $k = 138$) isolating what repeated summarization does to conversation-held facts, with token-level survival curves, provenance forensics on every endpoint, and two second-order findings: continuation summaries propagate confabulated task state, and a harness tuned for memoryless operation actively fights a memory-carrying configuration.

§2 grounds the design; §3 specifies the mechanism; §4 describes the implementation surface;

§5 reports the evaluation; §6 positions against related work; §7 analyzes threats to validity; §8 concludes.

2 Two tiers, and why the second must be harness-owned

	Tier 1 — documents	Tier 2 — brain memory
Content	Decontextualized, durable, shareable: specs, ADRs, runbooks	Situationally-bound operational facts: gotchas, locations, tacit fluency
Encoding	Deliberate act of authorship	Automatic side effect of the work
Retrieval	Deliberate lookup	Cue-driven, largely involuntary
Failure mode	Staleness; write-only archives	Lost when the context window resets

Brain memory is the informal name we use for the second tier; the mechanism this paper specifies and evaluates for it is cue-anchored working memory (§3).

The mapping from cognitive mechanism to design requirement is generative, not decorative; each row forced an architectural decision:

- **Encoding is incidental.** In levels-of-processing and incidental-learning studies, subjects given no instruction to remember recalled as well as deliberate memorizers [17, 18]. (Deliberate generation does aid retention when it happens [29]; the design premise is only that it cannot be relied on to happen.) Humans don’t call `remember()`. A design that depends on the model volunteering a save fights the grain of the only system known to do memory well. → Capture must not depend on agent initiative (the open half; §7).
- **Retrieval is cue-driven and mostly involuntary.** Encoding specificity [19]; involuntary autobiographical memories outnumber voluntary recall roughly 2:1 in daily-life sampling [22]; event-based prospective memory is more automatic than time-based [23]. → The default delivery channel is injection at the cued moment; voluntary lookup is the fallback, never the load-bearing path.
- **An external store counts as memory only under the extended-mind criteria** [24]: reliably available, near-zero effort, *automatically endorsed*. Clark argued web search fails the endorsement criterion: results get evaluated, not trusted. The offloading literature measures the other half of the bargain: externalizing reliably frees capacity and reshapes what stays internal (people retain *where* rather than *what* [26, 27]), and saving one item measurably improves memory for the next [28]; its group-level analog is transactive memory [25]. Injection makes a store function as memory; lookup makes it function as a reference document. Same content, different delivery, different cognitive role.
- **What resists being written down.** The episodic/semantic and declarative/procedural splits [20, 21] explain why writing a situationally-bound fact strips exactly the cues that make it retrievable. “This config is load-bearing” is useful only when you are staring at that config — which is why humans never documented it, why a flat memory file serves it badly, and why a *cue-anchored* record serves it well.

The content/control distinction of §1 is the systems restatement of the endorsement criterion: only control-plane delivery gives a store the trust posture and the reliability of memory. Content-plane systems, however elaborate, inherit the failure rate of model compliance, which §5 measures.

3 The cue-anchored memory model

A memory is a tuple (**content**, **kind**, **triggers**, **scope**, **decay**).

Kinds map to the cognitive taxonomy: **directive** (standing prospective intention that must never miss), **gotcha** (cue-anchored caveat), **finding** (semantic fact), **task** (working state), **reference** (pointer).

Triggers are per-memory standing conditions over a composable vocabulary: **path** (glob over touched files), **symbol** (a named code entity is referenced; requires a code symbol graph), **semantic** (similarity of current activity above a floor), **event** (session start, prompt submit, pre-edit, pre-run, pre-compaction, post-compaction), **temporal** (not-before, cooldown). Conjunction within a trigger, disjunction across triggers. Kinds define default delivery when no explicit trigger is present: directives fire at session start and post-compaction; high-priority task notes at session start (including every compact-resume); findings enter prompt-time semantic recall over a similarity floor.

Evaluation is deterministic and harness-side. No model judgment sits in the delivery path — the failure TriggerBench documents (models cannot self-trigger) and the fallibility Devin’s own documentation concedes for semantically-matched knowledge items are both designed out. Determinism also buys auditability: every evaluation, fire, and suppression is a logged system event (§5.3 gates its mechanism claims on this audit log), which no model-mediated selection can offer.

Delivery discipline. Injection is budgeted (two-tier: a compact index by default, full content on demand or for cue-anchored fires); a per-session fire ledger dedups repeats, and the ledger resets at compaction boundaries so anchored facts re-arm in the new window; injected content carries provenance framing (“recorded by an AI session, not human-endorsed — verify”) so memory stays the epistemic surface and instructions stay the imperative one; staleness is checked against ground truth, so if the anchored file changed after the note was written the injection carries an explicit warning. Stale-memory poisoning, injection bloat, and false-alarm rate are first-class design constraints (the poisoning literature demonstrates adversarial cue-anchored firing, planted items persisting dormant until a later trigger, and finds lightweight rule- and filter-based defenses insufficient [15]).

4 Implementation surface

The model is implemented in Vectr, an open-source local-first code-indexing daemon with a working-memory store (see Artifact Availability). Delivery integrates with the agent harness (Claude Code, an agentic coding CLI) at two alternative points:

1. **Native hooks.** The harness’s lifecycle hooks (session start, user prompt submit, pre-tool-use, pre-compaction) invoke a hook binary that consults the daemon and returns context to inject. This is the channel a first-class “memory mode” would own.
2. **API proxy.** A transparent proxy on the model-API path injects context deterministically into requests. Model- and product-agnostic; used here as the mechanism-validation control.

Both channels deliver the same store. The evaluation’s design point: if the same knowledge, delivered through two unrelated mechanisms, produces the same behavioral signature — and its absence through a third (voluntary tools) produces none — the effect is the delivery architecture, not the implementation.

5 Evaluation

Setup. One naturalistic task on a pinned Apache Camel checkout (~169k indexed chunks): implement the **reverse** option for the stream-mode Resequencer EIP (Enterprise Integration Pattern), a real feature requiring cross-module exploration (model layer, processor engine, reifier wiring, catalog/schema surfaces), gated by a harness-provided acceptance test that must pass unmodified plus the resequencer-scoped regression set (`-Dtest='*Resequenc*Test'`, 42 tests). All arms run the same agent product, same model (Claude Sonnet 5, `claude-sonnet-5`), same prompt, same corpus SHA. Canonical wall time is the transcript’s `duration_ms` (sleep-immune). Every run’s MCP (Model Context Protocol) posture, guidance surface, memory starting state, and gate-test fingerprint are asserted at launch and archived. Seeded arms start from four exploration-grade notes: facts a prior exploration session would plausibly have stored (locations, semantics, the guard site), never solution steps; one note is a gotcha anchored to the file containing the guard.

Arms (9 pilot runs + 3 native-channel runs, all graded):

arm	n	memory surface	delivery
A	3	none	—
B	2	store (cold) + tools + guidance	voluntary
C	3	store + tools + proxy, cold store	injection (nothing to inject)
CS	1	store seeded	proxy injection
H	2	store seeded	native hooks (session-start / prompt-submit / pre-tool-use / pre-compact)
V	1	store seeded	voluntary (hooks stripped; control for H)

The repeated-compaction decay probe (§5.7) uses a separate workload on the same corpus and defines its own arms (N, M) there.

5.1 Correctness: no harm

12/12 graded runs pass the acceptance test (byte-unmodified, fingerprinted) and the regression suite. Injection, proxy or native, never cost correctness. One archive literalism a reader will hit first: the per-run `sha-check` line reads FAILED in every run directory, because Camel’s build formatter re-wrapped two javadoc comment lines of the gate test in every run; per-run transcript audits confirm zero agent edits to the test, and the canonical test was restored byte-for-byte before the grading run (documented in the CS/H/V grade files; the pilot runs are evidenced by per-run diff scopes). (Six further matrix launches did not gate, all retained with diagnosis: three preflight aborts on two harness-surfaced product bugs (one store-clear defect, two on a REST-starvation availability bug), one hook-probe preflight abort, one operator pause, and one pilot invalidated at the launch-posture assert.)

5.2 Adoption: voluntary memory does not happen

- Unseeded equipped runs (B, C): voluntary memory writes 0–1 across all five runs, despite 32 memory-guidance mentions in the workspace instruction files and a verified connected tool surface. The native auto-memory directory was never created in any run.
- **The seeded-voluntary control (V) is the strongest form of the finding:** same four task-relevant notes in the store as the H arms, same connected tools, same guidance — the agent made **zero memory calls in 114 turns**. Knowledge present in a store contributes nothing by itself.

- Injection begets engagement: the seeded-proxy run (CS) produced the matrix’s only memory-hygiene loop (recall by id, *forget* of the gotcha its implementation had just obsoleted, then *remember* of a completion note). The loop came after its first two voluntary calls timed out on the availability bug of §5.1. The native runs reproduced the pattern (H1: expansion of all three injected index entries by id within seconds of injection, later a semantic recall returning staleness-flagged notes, then supersession of the obsolete gotcha; H2: one immediate semantic recall ~ 17 s in, then working from the injected content without expanding the index by id). Voluntary memory operations occur *after and because of* delivery, not instead of it.

5.3 Mechanism: deterministic delivery, proven on two channels

Proxy (CS): 262 API requests: 241 reached the injection decision — 5 injected, 236 correctly skipped — and 21 (by subtraction; the status file carries no per-type counter) did not; zero injection or upstream errors. The proxy’s own status counters are the published ledger for this channel (`proxy-status.json`); the grading-time daemon audit additionally recorded six `PROACTIVE_INJECT` events anchoring the seeded notes, quoted in the published grade file — one more than the proxy’s injected count, plausibly the pre-launch injection probe, now unreconcilable because that daemon log predates this archive’s excerpt policy and was not retained.

Native hooks (H $\times$ 2): the prompt-submit hook injected a three-note index at launch in both runs, behaviorally confirmed in H1 by the agent’s first three tool calls being recalls of exactly the three injected note ids (knowable from nowhere else). The cue-anchored gotcha **fired inside both runs on the agent’s first touch of the anchored file** (~ 20 s and ~ 7 min in), per the daemon audit log; subsequent touches were suppressed by the per-session fire ledger, and the ledger reset at each compaction boundary, as designed. False-alarm injections: zero in both runs, across 40 and 35 audit-logged trigger evaluations respectively (the only other fire in each window is the harness’s own pre-launch hook probe). One delivery honesty note: the injected index carried three of the four seeded notes. The index budget dropped one (a known ranking limitation logged as product work); the agent recovered that note’s content from code exploration.

A methodological note for replication: the agent transcript records session-start hook payloads but not prompt-submit or pre-tool-use payloads; for those, the daemon audit log is the evidentiary surface for injection claims (sanitized per-run excerpts are published as `daemon-audit-excerpt.log`).

5.4 Value, honestly priced

Count-based metrics separate the arms more cleanly than wall-clock, which carries API-latency and agent-path noise:

metric	vanilla mean ($n = 3$)	tool-equipped mean ($n = 6$, pilot; store cold in 5 of 6)	Δ
total tool calls	137.3	79.8	−42%
grep/find calls	48.3	22.2	−54%
cost	\$7.20	\$5.08	−30%
turns	106.3	77.0	−28%
wall (s)	2123.6	1432.8	−33%

Five of the six pooled runs ran with an empty store, so this table prices the platform (semantic-search tools plus guidance), not memory delivery; it bounds the tool-surface effect and nothing

in this paper’s memory argument rests on it. The memory measurement is the knowledge-held-constant comparison (same seeds):

run	delivery	turns	cost	wall (s)
H1	hooks	95	\$5.22	1454
H2	hooks	102	\$6.09	1187
V1	voluntary	114	\$6.23	1297

Both H runs finished in fewer turns and cheaper than V; the native channel also beat the pilot’s proxy run (CS: 106 turns, \$6.57, 1629 s) on every count. At $n = 2$ vs $n = 1$ (and $n = 3$ vs $n = 6$ in the pilot), with within-arm wall spreads of $2.4\text{--}4.4\times$, none of this clears a significance bar, and we make no headline speed claim. The direction is consistent across every metric and both channels; a defensible percentage would need $\sim 15\text{--}20$ runs per arm.

5.5 Re-exploration waste

Over the nine pilot transcripts (analyzer and per-run data published; cf. [6] on SWE-agent exploration behavior): **61 intra-session re-reads**, of which **24 (39%) re-read content the session had already read before a compaction boundary**; $\sim 78\text{k}$ result tokens re-paid (chars/4 proxy); pooled re-exploration share 10.9% of exploration calls (range 0–29.1%). The distribution is the finding: the three heaviest runs hold 55 of 61 re-reads and 21 of 24 cross-compaction re-reads (the remaining three sit in a fourth compacted run); every pilot run compacted at least once, yet four finished with zero re-reads — the boundary is where waste concentrates when it occurs, not a guarantee that it does. The worst single run re-paid $\sim 31.6\text{k}$ tokens (a sixth of a context window) re-retrieving content it had already paid for. Waste concentrates exactly at context-loss boundaries, which is what deterministic post-compaction re-injection targets.

5.6 Compaction, single boundary

All twelve graded runs auto-compacted at least once mid-flight; all finished green. A single compaction is near-lossless for task continuity: the harness’s continuation summary carries it, with or without a memory tier. What the memory tier measurably added at the boundary: post-compaction recall returned the seeded notes with live staleness warnings (the agent had since edited the anchored file; a frozen summary cannot self-invalidate), the agent superseded the obsolete note, and the trigger-ledger reset re-armed cue-anchored delivery for the new window.

Under *repeated* compaction — the one-conversation-per-project usage pattern (field report: 59 compactions in 26 days [16]) — in-context facts must survive re-selection at every pass, endure lossy extraction [7, 8] and iterative re-encoding drift [9, 10], and compete for a fixed summary budget against a growing history. An externalized store is immune by construction. §5.7 measures both halves.

5.7 Repeated compaction: the decay probe

Workload. A second harness drives the same pinned corpus through a load sized to compact continuously: one seeding phase, sixteen exhaustive file-audit phases over a 64-file corpus, and a closing phase, executed by a small fast model (Claude Haiku 4.5) as one resumed session with the auto-compaction window pinned at 100k tokens (the CLI’s floor).

Facts. Ten synthetic operational facts (a build-freeze code, an incident bridge, a rollback deadline, ...) are presented exactly once, in phase 0, in a fixture file that is **deleted immediately afterward**: removing the only re-readable source defeats the harness’s post-compaction file restoration, so any later appearance of a fact must have survived in conversation or in a memory tier. Every phase prompt restates the tool constraints (file access through the Read tool only — no shell; no subagents); the closing phase requires writing the ten facts into the audit report.

Grading. Token-level: presence of each fact token in every continuation summary (the survival curve) and in the final report (endpoint), plus provenance forensics over the full session transcript and the daemon audit ledger.

Arms. **N** runs with no memory tier. **M** runs the identical workload with the ten facts seeded as one-line notes in the working-memory store, re-injected by the session-start / prompt-submit hooks at every compact-resume.

	arm N (no memory tier)	arm M (injected store)
compactions k	108	138
turns / cost	1,235 / \$21.26	1,489 / \$28.94
summaries carrying 10/10 facts	2 (after an accidental re-surfacing)	53
summaries carrying 0/10 facts	106	85
summaries carrying a strict subset	0	0
summary 1 (first boundary)	0/10	0/10
final summary	0/10	0/10
endpoint (10 facts in report)	10/10 — invalid (transcript archaeology)	10/10 — clean (injection-sourced)
fact-bearing deliveries (daemon audit ledger)	0	139 (all ten facts each; 157 evaluations logged)

Figure 1 — survival regimes. Every summary is all-or-nothing (0/10 or 10/10 fact tokens; no strict subset ever occurred in either arm):

arm	summaries	regime
N	1–29	0/10
N	30–31	10/10 — an orientation grep accidentally re-surfaced the block
N	32–108	0/10
M	1–3	0/10 — dropped despite injection into the summarized context
M	4–66	10/10 in 53 of 63
M	67–138	0/10 — 72 consecutive, while deliveries continued on schedule

The summary channel drops everything at the first boundary. In both arms, summary 1 carried 0/10 fact tokens; in N, 106 of 108 summaries carried 0/10. The two exceptions measure re-injection half-life: mid-run, one of the agent’s own orientation greps accidentally re-surfaced the fact block into context; the next two summaries carried 10/10; one re-summarization pass later the facts were gone again. A fact re-entering context survives approximately one further pass. Selection is also all-or-nothing. Across both arms, no summary ever carried a strict subset of the ten facts: the summarizer either folds the block in or drops it whole.

Denied a memory tier, the agent builds one (N endpoint). Arm N’s final score was 10/10 — and provenance forensics invalidate it. In the closing phase the agent ran a deliberate archaeology chain over the harness’s own persistence: grepping its session JSONL and the harness’s persisted tool-result files for the fact markers, then transcribing the hits: 260 shell commands in

total (38 fact archaeology against the harness’s persisted session artifacts, 152 corpus/orientation, 70 report operations), against a ban restated in every phase prompt. (First shell use appears only after 15 summaries, so the curve’s early region is a clean pure-summary-channel measurement.) The asymmetry the agent exploited is instructive: the harness restores *files* after compaction and re-reads root instruction files, but restores nothing the conversation knew. Given no sanctioned memory tier, the model hand-built an episodic one from the harness’s disk artifacts. The endpoint tie with M is an artifact of this prompted closing phase — it measures what each arm could produce when explicitly asked. The operative quantity for real work is mid-run availability, where the arms are not tied: N’s post-compaction window carried 0/10 fact tokens at 106 of 108 boundaries, while M’s received all ten by injection at every one of its 138.

The injected store survives everything (M). Final score 10/10 with clean provenance: zero fact-targeted shell commands, an empty disk-memory directory, no early fact write into the report, and, decisively, a final continuation summary carrying 0/10: had the endpoint depended on the summary channel, it would have scored zero. The daemon’s audit ledger records 157 session-start evaluations, of which 139 delivered all ten facts into the run: one at every single compact-resume (138/138) plus the first phase launch. (The ledger’s one other fact-bearing line, 1.5 s before the launch’s, is the runner’s pre-launch hook probe, payload archived as `hook-probe-sessionstart.json`, never part of the session.) The 17 remaining mid-session phase-launch evaluations fired zero notes (16) or one non-seed note (1), the per-session fire ledger of §3 suppressing redundant re-injection while the facts were still in-window, and the post-kill relaunch logged no evaluation at all. Delivery fired exactly when a fresh window needed it and nowhere else. Each delivery ran ~240 tokens (mean 969 chars of injected text, chars/4 as in §5.5), ~34k injected tokens across the run; all 139 are visible in the session file as hook-attachment pairs carrying 10/10 fact tokens. The tier’s price, measured: the delivery overhead, the guard-forced tighter read cap (below), and the late-run confabulation spiral put M at +21% turns and +36% cost versus N. One disclosure: of M’s 321 shell results, exactly one (an orientation grep over its own session file for phase-10 task state) incidentally echoed fact tokens back into context; it sits over sixty compaction boundaries before the endpoint and cannot reach it. Every fact-bearing carrier in the endpoint window is a hook attachment.

The survival curve is bimodal with a regime change (Figure 1): even with the facts injected into the very context being summarized, the first three summaries carried none; summaries 4–66 folded them in 53 times out of 63; then the entire back half of the run (72 consecutive summaries) carried none, while deliveries continued to arrive on schedule. We did not predict the regime change and do not fully explain it (plausibly the growing report and the confabulation spiral, below, changed what the summarizer selected); either reading supports the same conclusion: summarizer selection is unreliable *independently of fact availability* — and with a memory tier, nothing depends on it. The injection-begets-engagement pattern of §5.2 also replicates under decay: the M agent voluntarily issued 11 remember calls (9 landed in the audit ledger) and 9 recalls mid-run, against zero voluntary operations in the seeded-voluntary control. (The prompt-submit index tier separately delivered partial fact coverage, 3/10 tokens early and 1/10 late — the budgeted-index lesson of this section’s closing note, caught live.)

What nobody seeded still decayed (“Phase 52: Files 203–206”). Only the ten facts were seeded. The task state (which files belong to which phase) lived in conversation, and under 138 compactations it decayed into confabulation: the agent skipped two entire audit phases, invented an arithmetically self-consistent phase numbering deep into the run (“Phase 52: Files 203–206” — in a sixteen-phase, 64-file audit), re-audited completed files under the invented scheme, and spent 37 transcript-archaeology greps, nine memory recalls, and three (forbidden) subagent launches hunting a task specification that never existed. The hunt even left the corpus: the agent twice

Read the memory system’s own design document off the operator’s disk, reasoning it “might have the canonical specification” — a real path whose first appearance in the recorded stream is the agent’s own thinking, with no recorded source (the file contains no fact tokens; both reads appear in the audit ledger). The continuation summaries did not correct the false task model — they propagated it across every boundary. (The pilot showed the same signature at $k = 2$: a first summary asserting “Memorization: Maintained all 10 DECAY-FACTS” while carrying zero of them.) Summaries consolidate the model’s current beliefs; they do not validate them. Audit completeness (declaration recall against a regex ground truth over the 64 source files) came out 0.70 for M vs 0.93 for N, with the confound that M ran under a tighter read cap, forced on it by the harness (next paragraph). Both scores are from the format-robust regrade published per-run as `decay-grade-v4-regrade.txt`.

(Archive note: the original grade files retain three at-a-glance flags a reader will hit first, each decoded in the run log. The recall column’s 0.00 was a section-binding bug in the original grader (fixed; N’s score is unchanged by the fix), “SAMPLING/FABRICATION SUSPECT” is the confabulated-numbering finding itself, and “RUN INVALID for the in-context-only premise” is the no-memory-arm contamination rule firing, correctly by its own logic, on the memory arm’s sanctioned injections.)

The harness fights the memory-carrying configuration. The agent product’s autocompact thrash guard aborts a call when context refills within three turns of a compact three times consecutively. The guard is not memory-specific: it also killed arm N once mid-run (phase 6, after 49 boundaries; relaunched and completed, still at the 8k read cap). The difference is structural margin. The memory-equipped arm carries fixed per-cycle context the naive arm does not: MCP tool schemas re-loaded per resumed call, guidance files, per-prompt injections — a fixed context overhead the guard reads as refill pressure. At the arms’ shared 8k cap the guard killed M’s first audit phase fourteen turns in and the launch was scrapped; running required lowering only M’s read cap to 6k tokens, and even at 6k the guard killed the final audit phase as the growing report tightened the squeeze. One kill for N across eighteen phases at 8k; for M, a scrapped launch at 8k and one kill even at 6k. A harness tuned for memoryless operation treats the context profile of a memory-carrying configuration as elevated thrashing risk — the operational form of this paper’s content/control argument, measured.

A delivery-design lesson from the probe’s preflight: injection surfaces that ship an index tier (title line now, expand on demand) deliver only the title at session boundaries — a fact must ride the index line itself or it does not travel. The probe’s seeds are one-line notes for exactly this reason.

6 Related work

A systematic sweep across four lanes — prospective/trigger-conditioned memory, memory-as-governance, agent-memory surveys 2024–2026, and shipped product mechanisms — narrows the novelty claim to a specific composition. Per-item triggers exist in fragments. Devin’s knowledge items carry per-item “trigger descriptions”, semantically matched and fallible by the vendor’s own documentation. Pathrule ships deterministic hook-time delivery restricted to path globs over team-curated knowledge. The rules ecosystem (path-scoped instruction files across major AI IDEs) made deterministic per-item path triggers industry-standard *for static human-authored configuration*; OpenHands’ repository microagents extend it to per-item keyword triggers evaluated harness-side — still static, human-authored knowledge, not agent-written memory. Encoding standing user preferences as program state [5] is adjacent in spirit (persistent conditioning of behavior) but

again human-scoped. PROJECTMEM’s pre-action gate [4] is genuine cue-anchored governance, hardcoded to two derived warning types and evaluated in a single-developer self-study. General memory architectures (MemGPT [11], Mem0 [12], Zep [13], A-MEM [14]) offer stores and retrieval policies, not standing per-item trigger conditions. A recent systematic study of general-purpose memory systems [3] maps retrieval across its subjects as query-time strategy (attention-based, semantic, topological, agentic routing, hybrid); standing per-item trigger conditions, evaluated against the agent’s ongoing activity, appear nowhere in its taxonomy.

What no surveyed system has, and this design contributes: (1) composable multi-vocabulary triggers, {path, symbol, semantic, event, temporal}, as per-memory standing conditions (symbol-conditioned memory requires a code symbol graph, which no memory system carries); (2) the trigger-carrying item is *agent-written working memory*, not static rules or onboarding knowledge; (3) deterministic harness-side evaluation with an audit surface; (4) the measurements: TriggerBench and MEMTRACK quantify the motivating failure, not a mechanism; no shipped or academic system publishes trigger-precision or injection-utility numbers, and we know of no prior forced-compaction survival measurement of either the summary channel or an injected store. The two-tier design theory (§2), used generatively, has no analog in any surveyed row.

7 Threats to validity

Construct. Fact survival is verbatim token-match; a paraphrased survival would be missed (none was observed on spot-check, and the all-or-nothing selection pattern suggests block-level, not token-level, summarizer behavior). The decay probe’s facts are synthetic and carry an explicit closing-phase obligation — the probe measures survival and delivery under compaction pressure, not spontaneous use. Token costs in §5.5 use a chars/4 proxy and support relative comparison only. Audit completeness is measured by declaration recall against a regex ground truth, which undercounts prose-only audit content. The trigger vocabulary is exercised unevenly: the graded runs fire path, event, and semantic triggers; symbol and temporal triggers are implemented but never fired by any graded run, so C2’s composition claim rests on three of its five elements having measured fires. Capture is the unevaluated half (§2’s open half): the probe’s ten fact notes were seeded by the harness, and §5’s voluntary-write counts measure initiative, not capture quality; capture-side automation is future work.

Internal. Arm M ran at a 6k read cap vs N’s 8k, forced by the thrash guard and reported as a finding, but a confound on the 0.70-vs-0.93 audit-completeness comparison. Tool bans proved unenforceable in both decay arms (shell archaeology in both; forbidden subagents additionally in M); we treat constraint non-compliance under context loss as data, and gate every endpoint on transcript-level provenance forensics rather than on compliance. An 11-minute host hibernation occurred mid-run in arm M (processes restored; session continuous; wall-clock excluded from claims). The evaluated implementation and the benchmark harness share an author; mitigations: pinned corpus SHA (a543dc64), fingerprinted acceptance test, per-run launch-posture assertions archived, audit-log-gated mechanism claims, all raw transcripts, graders, and analyzers published.

External. One corpus (Apache Camel), one task family per experiment, one agent product, one model family; the decay probe uses a small fast model (Claude Haiku 4.5), chosen to make $k \geq 100$ compactations affordable; decay behavior of larger summarizers may differ. Camel is public and present in training corpora: if equivalent resequencer logic exists anywhere upstream, part of the fix may be pretrained knowledge; this affects all arms equally and cannot manufacture a between-arm delta, but it shrinks the exploration burden the arms differ on. The decay probe’s pinned 100k window also halves per-boundary content pressure relative to stock thresholds; smaller

summarized segments should make per-boundary survival easier, not harder, so the observed first-boundary drop is conservative on that axis. Results are directional evidence with asserted controls, not population estimates.

Conclusion. Sample sizes are small throughout (12 graded matrix runs; one gated run per decay arm, each after protocol repairs documented in the published run log). We report absolute numbers with n visible, claim direction rather than effect size, and mark every percentage in §5.4 accordingly. Contested sources are excluded from the argument (the diver study’s failed replication, longhand-note effect sizes, unverified vendor claims about re-read token shares).

8 Conclusion

The reliable delivery channel for agent memory is the one the agent never has to think about. Giving models memory tools reproduces the wiki; giving the harness a cue-anchored tier reproduces the thing expertise actually runs on. The evaluation is small but its signature is consistent: voluntary memory use rounds to zero even with a seeded store; the same store, delivered deterministically at the cued moment through either of two unrelated mechanisms, arrives every time, costs nothing in correctness, and begets the only voluntary memory engagement observed anywhere in the corpus. Under repeated compaction the case sharpens to a point: the summary channel dropped every planted fact at the first boundary in both arms — even the arm whose context held the facts at summarization time; the agent denied a memory tier taught itself transcript archaeology to build one from the harness’s disk artifacts; and the injected store delivered all ten facts through 138 compactions while the final summary carried none of them. Memory for agents is not a content problem. It is a control-plane problem.

Artifact availability

All run archives, launch-posture assertions, graders, the re-exploration analyzer, the decay-probe harness, and per-run transcripts are published in the Vectr repository (github.com/swapnanil/vectr) under `research/proactive-gate/` (matrix runs, decay results `decay-N-20260717-030703` and `decay-M-20260717-192249`, protocols, complete run logs including invalidated launches, per-run daemon audit-log excerpts `daemon-audit-excerpt.log`, and format-robust regrades `decay-grade-v4-regrade.txt`) and `research/brain-memory/` (this paper, the analyzer, and measurement data). Large transcripts are gzip-compressed; the operator’s local paths and one corporate Maven mirror hostname were rewritten for privacy, with the exact rewrite map documented in `research/README.md`. The daemon implementation ships from the same repository.

References

- [1] TriggerBench: Investigating Prospective Memory for Large Language Models. arXiv:2606.23459, 2026.
- [2] MEMTRACK: Evaluating Long-Term Memory and State Tracking in Multi-Platform Dynamic Agent Environments. arXiv:2510.01353, 2025.
- [3] Are We Ready For An Agent-Native Memory System? arXiv:2606.24775, 2026.
- [4] PROJECTMEM: A Local-First, Event-Sourced Memory and Judgment Layer for AI Coding Agents. arXiv:2606.12329, 2026.

- [5] User as Code: Executable Memory for Personalized Agents. arXiv:2606.16707, 2026.
- [6] SWE-Explore: Benchmarking How Coding Agents Explore Repositories. arXiv:2606.07297, 2026.
- [7] Beyond Static Summarization: Proactive Memory Extraction for LLM Agents. arXiv:2601.04463, 2026.
- [8] RecMem: Recurrence-based Memory Consolidation for Efficient and Effective Long-Running LLM Agents. arXiv:2605.16045, 2026.
- [9] Governing Evolving Memory in LLM Agents: Risks, Mechanisms, and the Stability and Safety Governed Memory (SSGM) Framework. arXiv:2603.11768, 2026.
- [10] Recursively Summarizing Enables Long-Term Dialogue Memory in Large Language Models. arXiv:2308.15022, 2023.
- [11] MemGPT: Towards LLMs as Operating Systems. arXiv:2310.08560, 2023.
- [12] Mem0: Building Production-Ready AI Agents with Scalable Long-Term Memory. arXiv:2504.19413, 2025.
- [13] Zep: A Temporal Knowledge Graph Architecture for Agent Memory. arXiv:2501.13956, 2025.
- [14] A-MEM: Agentic Memory for LLM Agents. arXiv:2502.12110, 2025.
- [15] Plant, Persist, Trigger: Sleeper Attack on Large Language Model Agents. arXiv:2605.28201, 2026.
- [16] anthropics/claude-code issue #34556: “Persistent Memory Across Context Compactions (59 compactions, built our own).” Field report, 2026. <https://github.com/anthropics/claude-code/issues/34556>
- [17] F. I. M. Craik and R. S. Lockhart. Levels of processing: A framework for memory research. *Journal of Verbal Learning and Verbal Behavior*, 11:671–684, 1972.
- [18] T. S. Hyde and J. J. Jenkins. Recall for words as a function of semantic, graphic, and syntactic orienting tasks. *Journal of Verbal Learning and Verbal Behavior*, 12:471–480, 1973.
- [19] E. Tulving and D. M. Thomson. Encoding specificity and retrieval processes in episodic memory. *Psychological Review*, 80:352–373, 1973.
- [20] E. Tulving. Episodic and semantic memory. In *Organization of Memory*, Academic Press, 1972.
- [21] L. R. Squire. Memory systems of the brain: A brief history and current perspective. *Neurobiology of Learning and Memory*, 82:171–177, 2004.
- [22] D. Berntsen. *Involuntary Autobiographical Memories: An Introduction to the Unbidden Past*. Cambridge University Press, 2009.
- [23] M. A. McDaniel and G. O. Einstein. Strategic and automatic processes in prospective memory retrieval: A multiprocess framework. *Applied Cognitive Psychology*, 14:S127–S144, 2000.
- [24] A. Clark and D. Chalmers. The extended mind. *Analysis*, 58:7–19, 1998.

- [25] D. M. Wegner. Transactive memory: A contemporary analysis of the group mind. In *Theories of Group Behavior*, Springer, 1987.
- [26] E. F. Risko and S. J. Gilbert. Cognitive offloading. *Trends in Cognitive Sciences*, 20:676–688, 2016.
- [27] B. Sparrow, J. Liu, and D. M. Wegner. Google effects on memory: Cognitive consequences of having information at our fingertips. *Science*, 333:776–778, 2011.
- [28] B. C. Storm and S. M. Stone. Saving-enhanced memory: The benefits of saving on the learning and remembering of new information. *Psychological Science*, 26:182–188, 2015.
- [29] N. J. Slamecka and P. Graf. The generation effect: Delineation of a phenomenon. *Journal of Experimental Psychology: Human Learning and Memory*, 4:592–604, 1978.