

Lecture 27: 13th October 2017

Lecturer: Swaprava Nath

Scribe(s): Sudhir Kumar

Disclaimer: These notes aggregate content from several texts and have not been subjected to the usual scrutiny deserved by formal publications. If you find errors, please bring to the notice of the Instructor.

27.1 Recap

In the last lecture we looked into uniform rule SCF and proved that uniform rule SCF is PE, ANON and SP and also found out that if a SCF is PE, ANON and SP then it is uniform rule SCF. We also looked into Mechanism of transfer and Quasi Linear Preferences. A SCF can be defined as,

$$F = (f, p)$$

$$F : \Theta \longrightarrow X$$

$$\text{where } X \text{ is } (a, \pi)$$

allocation function:

$$f : \theta \longrightarrow A$$

payment function:

$$p_i : \theta \longrightarrow R$$

27.2 Example of Allocation function

- Constant Rule: Where allocation function is constant for all θ .

$$f^c(\theta) = a, a \in A$$

- Dictatorial Rule: In this rule a player dictatorially choose best outcome for himself.

$$f^d(\theta) \in \operatorname{argmax}_{a \in A} v_d(a, \theta_d), \exists d \in N$$

- Allocatively efficient rule/ Utilitarian rule:

$$f(\theta) \in \operatorname{argmax}_{a \in A} \sum_{i \in N} v_i(a, \theta_i)$$

- Weighted efficient rule:

$$f(\theta) \in \operatorname{argmax}_{a \in A} \sum_{i \in N} w_i v_i(a, \theta_i), w_i \geq 0 (\text{where all } w_i \text{ is not zero})$$

- Max-Min/Egalitarian/Ravtsian allocation rule:

$$f^r(\theta) \in \operatorname{argmax}_{a \in A} \min_{i \in N} v_i(a, \theta_i)$$

- Affine maximizer rule:

$$f_{AM} \in \operatorname{argmax}_{a \in A} \left[\sum_{i \in N} \lambda_i v_i(a, \theta_i) + \kappa(a) \right], \text{ where } \lambda_i \geq 0 (\text{not all zero})$$

27.3 Examples of payment rules

- Weak budget balanced/ no-deficit/ feasible

$$\sum_{i \in N} p_i(\theta) \geq 0, \forall \theta \in \Theta$$

- No subsidy

$$p_i(\theta) \geq 0, \forall i \in N \text{ and } \forall \theta \in \Theta$$

- Budget balanced

$$\sum_{i \in N} p_i(\theta) = 0$$

We are more interested in finding an allocation that is "truthful" even if there is no restriction on payments.

27.4 Incentive compatibility

$$\hat{\theta} = (\hat{\theta}_1, \hat{\theta}_2, \dots, \hat{\theta}_n)$$

$$v_i(f(\hat{\theta}), \theta_i) - p_i(\theta)$$

(payoff for agent i)

Definition: A direct mechanism (f, p) is domination strategy incentive compatible (DSIC) if,

$$\forall i \in N, \forall \theta_{-i} \in \Theta_{-i} \text{ and } \forall \theta_i, \hat{\theta}_i \in \Theta_i$$

$$v_i(f(\theta_i, \theta_{-i}), \theta_i) - p(\theta_i, \theta_{-i}) \geq v_i(f(\hat{\theta}_i, \theta_{-i}), \theta_i) - p(\hat{\theta}_i, \theta_{-i})$$

Note: Reporting types truthfully is a DSIC. If the above condition holds then p implements f in dominant strategy.

Example: Consider,

$$N = 1, 2, \theta_1 = \theta_2 = \theta^H, \theta^L$$

$$f : \theta_1 \times \theta_2 \longrightarrow A$$

is allocation rule. If p implements f in dominant strategy, then For Player 1:

$$v_i(f(\theta_H, \theta_2), \theta_H) - p(\theta_H, \theta_2) \geq v_i(f(\hat{\theta}_L, \theta_2), \theta_H) - p(\hat{\theta}_L, \theta_2), \forall \theta_2 \in \Theta_2$$

$$v_i(f(\theta_L, \theta_2), \theta_L) - p(\theta_L, \theta_2) \geq v_i(f(\hat{\theta}_H, \theta_2), \theta_L) - p(\hat{\theta}_H, \theta_2), \forall \theta_2 \in \Theta_2$$

Similarly for player 2,

$$v_i(f(\theta_H, \theta_1), \theta_H) - p(\theta_H, \theta_1) \geq v_i(f(\hat{\theta}_L, \theta_1), \theta_H) - p(\hat{\theta}_L, \theta_1), \forall \theta_1 \in \Theta_1$$

$$v_i(f(\theta_H, \theta_1), \theta_H) - p(\theta_H, \theta_1) \geq v_i(f(\hat{\theta}_L, \theta_1), \theta_H) - p(\hat{\theta}_L, \theta_1), \forall \theta_1 \in \Theta_1$$

27.5 Impact of DSIC on payments

1. Change in payment if we add new function in payments of agents which will not depend on type of agent i (θ_i) it will depend only on θ_{-i} . Consider (f, p) is DSIC then

$$v_i(f(\theta_i, \theta_{-i}), \theta_i) - p(\theta_i, \theta_{-i}) \geq v_i(f(\hat{\theta}_i, \theta_{-i}), \theta_i) - p(\hat{\theta}_i, \theta_{-i})$$

$$\forall i \in N, \forall \theta_{-i} \in \Theta_{-i} \text{ and } \forall \theta_i, \hat{\theta}_i \in \Theta_i$$

now consider,

$$q(\theta_i, \theta_{-i}) = p(\theta_i, \theta_{-i}) + h(\theta_{-i})$$

Question: (f, q) Is this DSIC?

Answer: Yes it will be DSIC, consider

$$v_i(f(\theta_i, \theta_{-i}), \theta_i) - q(\theta_i, \theta_{-i})$$

$$v_i(f(\theta_i, \theta_{-i}), \theta_i) - p(\theta_i, \theta_{-i}) - h(\theta_{-i}) \geq v_i(f(\hat{\theta}_i, \theta_{-i}), \theta_i) - p(\hat{\theta}_i, \theta_{-i}) - h(\theta_{-i})$$

Since (f, p) is DSIC so the above equation holds.

2. If allocation is same of different types of agent i . Let two types of agent i will be (θ_i, θ_{-i}) and $(\hat{\theta}_i, \theta_{-i})$

$$f(\theta_i, \theta_{-i}) = f(\hat{\theta}_i, \theta_{-i}) = a(\text{say})$$

Let us assume that (f, p) is DSIC, then
when agent i type is θ_i

$$v_i(f(\theta_i, \theta_{-i}), \theta_i) - p(\theta_i, \theta_{-i}) \geq v_i(f(\hat{\theta}_i, \theta_{-i}), \theta_i) - p(\hat{\theta}_i, \theta_{-i})$$

$$p_i(\hat{\theta}_i, \theta_{-i}) \geq p_i(\theta_i, \theta_{-i})$$

when agent i true type is $\hat{\theta}_i$,

$$v_i(f(\hat{\theta}_i, \theta_{-i}), \hat{\theta}_i) - p(\hat{\theta}_i, \theta_{-i}) \geq v_i(f(\theta_i, \theta_{-i}), \hat{\theta}_i) - p(\theta_i, \theta_{-i})$$

$$p_i(\theta_i, \theta_{-i}) \geq p_i(\hat{\theta}_i, \theta_{-i})$$

from above two conclusions we can see that,

$$p_i(\theta_i, \theta_{-i}) = p_i(\hat{\theta}_i, \theta_{-i})$$

so, If you cannot change allocation we cannot change the payments vector.

References

- [CW87] D. COPPERSMITH and S. WINOGRAD, "Matrix multiplication via arithmetic progressions," *Proceedings of the 19th ACM Symposium on Theory of Computing*, 1987, pp. 1–6.