Roll No.		Dept.				

Instructions:

1. This question paper contains a total of **1** page (**1** side of paper).
2. Write your name, roll number, department, and section on every side of every sheet of this booklet
3. Write final answers neatly with a blue/black pen in the given boxes.
4. **Answers written outside the box will NOT be graded.**

Total **10 Marks**

Q. 1: Write the output of the following program in the appropriate box and answer the question. (2+2+2 = 6 Marks)

```
#include<stdio.h>
void func1(int *arr){
  for(int i=1; i<=4;i++)
    (i-1)[arr] = (i%4);
}
void func2 (int a[1] , int arr){
  a[0] = arr + 2;
}
int main(){
  int arr[5] = {1,1,1,1,1};
  func1(arr+1);
  for(int i=0; i<5; i++)
        printf("%d ", i[arr] );
  printf("\n");
  func2(arr, *arr);
  for(int i=0; i<5; i++)
        printf("%d ", i[arr] );
  return 0;
}
```

Output
1 1 2 3 0
3 1 2 3 0

Will the answer change if we write func2 as:
`void func2 (int a[1] , int arr){`
`int temp = arr + 2;`
`a = &temp;`
`}`
Explain your answer

No, the answer would not change because, a[1] ~~arr~~. 'a' an array var = arr. Now a = &temp ⇒ *a = 3. ⇒ *arr = arr[0] = 3. ~~Hence the final array will be~~ {3, 1, 2, 3, 0}

Q. 2: Write the output of the following sequence of instructions **long arr2[60]; int arr1[50], a1=(&arr2[40]), a2=(&arr2[30]), b1=(&arr1[40]), b2=(&arr1[30]); printf("%d %d", a1-a2 , b1-b2);** Explain your answer. (2+2 Marks)

10 10

Because when accessing array pointers they take into account what datatype is of the array.