Instructions:

1. This question paper contains a total of **1** page (**1** side of paper).
2. Write your name, roll number, department, and section on every side of every sheet of this booklet
3. Write final answers neatly with a blue/black pen in the given boxes.
4. **Answers written outside the box will NOT be graded.**

Total **10 Marks**

Q. 1: Write the output of the following program in the appropriate box and answer the question. (2+2+2 = 6 Marks)

```
#include<stdio.h>
void func1(int *arr){
  for(int i=1; i<=3;i++)
    (i-1)[arr] = (i%3);
}
void func2 (int a[1] , int arr){
  a[0] = arr + 1;
}
int main(){
  int arr[4] = {0,0,0,0};
  func1(arr+1);
  for(int i=0; i<4; i++)
        printf("%d ", i[arr] );
  printf("\n");
  func2(arr, *arr);
  for(int i=0; i<4; i++)
        printf("%d ", i[arr] );
  return 0;
}
```

Output
0 1 2 0
1 1 2 0

Will the answer change if we write func2 as:

```
void func2 (int a[1] , int arr){
 int temp = arr + 1;
 a = &temp;
}
```

Explain your answer

No, the answer will not change. a refers to pointer to a[0] & it refer to address of temp. So a[0] will end up getting the value of temp which is the value of arr+1. The same function took place in the original code.

Q. 2: Write the output of the following sequence of instructions **long arr2[100]; int arr1[100], a1=(&arr2[50]), a2=(&arr2[10]), b1=(&arr1[50]), b2=(&arr1[10]); printf("%d %d", a1-a2 , b1-b2);** Explain your answer. (2+2 Marks)

0 0. The values a1 and a2 are pointers to the same array, but the only difference is in the size of the array. The initial value have the same address. Hence the difference is 0. The same logic applies to b1 and b2.