

1. Data Cleaning Process

Section	Description
Process	Data Cleaning is the process of detecting and correcting corrupt or inaccurate records from a record set, table, or database. It involves identifying incomplete, incorrect, inaccurate, or irrelevant parts of the data and replacing, modifying, or deleting the dirty data.
Steps	1. Data Inspection and Loading: Read the raw dataset into a DataFrame. 2. Data Type Conversion: Convert columns to the appropriate data type. For instance, the 'date_added' column was converted from an object type to the proper datetime64[ns] type to enable time-series analysis. 3. Missing Value Handling : Identify missing values using <code>df.isna().sum()</code>. All missing values in the dataset were replaced with the value 0 using <code>df.fillna(0)</code> to ensure a complete dataset for subsequent steps. 4. Handling of Duplicates: Check for and remove duplicate rows to ensure data

Section	Description
	uniqueness.
Metrics / Outcome	1. Missing Value Count: The primary metric is the count of missing values per column, aiming for a count of 0 in all essential columns. 2. Data Type Integrity: Verification that columns like 'date_added' are successfully converted to the correct data type 3. Data Completeness: Final dataset contains the full expected number of rows and columns

2. Normalization Process

Section	Description
Process	Normalization in data preprocessing is the process of adjusting values measured on different scales to a notionally common scale, often to prevent features with larger ranges from dominating the model training process. (Note: The uploaded notebook also includes feature encoding steps).

Section	Description
Steps	1. Data Loading: Read the cleaned dataset for further transformation. 2. Data Imputation: Fill in missing values for text-based columns, such as replacing missing values in the 'director' column with a placeholder like "Unknown Director". 3. Categorical Encoding: Create a new feature by mapping a categorical variable to a numerical code. A feature called 'director_code' was created, where a Movie type is mapped to 1 and a TV Show type is mapped to 0. 4. Numerical Scaling/Standardization: Apply techniques like Min-Max Scaling or Z-Score Standardization to numerical columns if they were not already handled in the Feature Engineering stage.
Metrics / Outcome	1. Missing Value Resolution: Confirmation that all placeholder values (e.g., "Unknown Director") have successfully

Section	Description
	replaced the original missing values. 2. Encoding Consistency: Verification that the encoding rule is correctly applied across all rows (e.g., every 'Movie' row has director_code = 1). 3. Distribution Uniformity (Inferred): For true normalization (scaling), the resulting numerical distribution should have a more uniform range (e.g., 0 to 1 for Min-Max Scaling) or mean 0 and standard deviation 1 (for Standardization).

3.Exploratory Data Analysis (EDA) Process

Section	Description
Process	Exploratory Data Analysis (EDA) is an approach to analyzing data sets to summarize their main characteristics, often with visual methods. It is used to discover patterns, spot anomalies, test hypotheses, and check assumptions with the help of summary statistics and graphical representations.

Section	Description
Steps	1. Load Cleaned Data: Read and display the cleaned dataset (e.g., netflix_cleaned.csv). 2. Structural Check: Examine the dataset's basic structure, including the number of rows/columns and data types (df.info()) to confirm the data is ready for analysis. 3. Summary Statistics: Generate and print "Quick Insights" which include mode and frequency counts for key categorical columns. 4. Visualization : Create plots (e.g., bar charts, histograms, heatmaps) to visualize distributions and relationships between features.
Metrics / Outcome	1. Data Count: Total record count 2. Feature Distribution (Counts): Quantified distribution of data types (e.g., Movies: 6130 and TV Shows: 2676). 3. Mode/Frequency: Identification of the most frequent categories, such as the Most common rating (TV-MA), Most frequent country (United States), and Most frequent

Section	Description
	genre (dramas, international movies). 4. Data Quality Score (Inferred): Insights into data consistency and potential outliers are implicitly measured.

4.Feature Engineering

Section	Description
Process	Feature Engineering is the process of using domain knowledge to select, transform, or create variables (features) that best represent the underlying problem to a predictive model, resulting in improved model accuracy.
Steps	1. Categorical Encoding (Label Encoding): Use techniques like LabelEncoder (from sklearn.preprocessing) to convert categorical columns, such as 'type', into numerical representations creating a new feature 'type_encoded'. 2. Feature Creation (Binning/Grouping): Create a new, derived feature by grouping values from an existing feature. A function

Section	Description
	was used to categorize the 'duration' column into four distinct bins: 'Short', 'Medium', 'Long', and 'Series', creating the feature 'Content_Length_Category'. 3. Numerical Scaling (MinMaxScaler): Scale a numerical column to a fixed range. The MinMaxScaler was applied to 'release_year' to scale its values to the range of 0.0 to 1.0, resulting in the new feature 'release_year_scaled'.
Metrics / Outcome	1. Range Validation (Scaling): Scaled numerical features (e.g., 'release_year_scaled') must fall within the defined range (e.g., 0.0 to 1.0). 2. Successful Categorization: Verification that all values in the original column ('duration') are correctly mapped to one of the defined categories in the new feature ('Content_Length_Category'). 3. Information Gain : The success of Feature Engineering is ultimately measured by the improvement in the

Section	Description
	predictive model's performance metrics (e.g., accuracy, precision) when trained on the new features.

5. Classification

Category	Details
Section	Classification: Content Type Prediction
Description	A Supervised Learning task used to identify the features most critical for distinguishing a title as a Movie or a TV Show .
Process	The Random Forest Classifier was used due to its effectiveness in handling mixed data types and providing a robust Feature Importance score (Gini Index).
Steps	1. Target Definition: Create binary target feature is_movie (\$1\$ for Movie, \$0\$ for TV Show). 2. Imputation: Fill missing rating values with the mode (TV-MA). \ 3. Encoding: Apply One-Hot Encoding to the rating column. 4. Model Training: Split data (\$80\%/20\%\$) and train the Random Forest model. 5. Extraction: Extract the Feature Importance (Gini Index).

Category	Details
Metrics / Outcome	Feature Importance (Gini Index): The primary metric, quantifying the predictive contribution of each feature. Outcome showed title_length and release_year were the most dominant predictors.

6. Clustering

Category	Details
Section	Clustering: Movie Content Segmentation
Description	An Unsupervised Learning task used to discover natural, intrinsic groupings of the Movie content library based on shared characteristics (duration, genre, rating).
Process	K-Means Clustering was used to partition the data into $K=5$ clusters by minimizing the Within-Cluster Sum of Squares (WCSS) , aiming for dense, well-separated groups.
Steps	Data Filtration: Filter the dataset to include only Movie content. Numerical Conversion: Clean and convert the duration string to a numerical <code>duration_min</code>. Genre Encoding: Use MultiLabelBinarizer for genres (creating binary features). Feature Scaling: Apply StandardScaler to normalize all features.

Category	Details
	5. Clustering: Run K-Means with $K=5$ (optimal K determined via the Elbow Method). 6. Analysis: Analyze the cluster centroids to profile the segments.
Metrics / Outcome	Inertia (WCSS): Used in the Elbow Method to determine the optimal number of clusters ($K=5$). Cluster Profile: The final set of 5 segments, defined by their Average Duration and Dominant Genre/Rating features.

7.KEY DRIVERS

Section	Description
Process	The goal is to identify the Most Frequent Genre (the key driver) for each country. This involves isolating the genre that commands the largest volume of production/acquisition, thus defining the content identity for that country on the platform.
Steps	
1. Data Cleaning (Country)	Filter out titles missing a country or labeled "Unknown" to ensure the analysis is based on reliably attributed content.
2. Feature	Extract the first listed country from the

Section	Description
Extraction (Primary Country)	country column to serve as the primary content driver for the title.
3. Feature Expansion (Genres)	Use the str.split() and explode() functions on the listed_in column to break multi-genre entries into individual, countable rows. This is crucial as a single title can contribute to multiple genres.
4. Aggregation and Ranking	Count: Group the expanded data by primary_country and listed_in (genre) to get the total count for every Country-Genre pair. Rank: Within each country group, sort the counts in descending order.
5. Driver Identification	Use the drop_duplicates(subset=['primary_country'], keep='first') function to select only the top-ranked genre (the one with the highest count) for each country. This genre is the <i>Key Driver</i> .
Metrics / Outcome	
1. Content Specialization:	Each country is clearly associated with one dominant genre (e.g., India: "International Movies", South Korea: "International TV Shows").
2. Driver Count:	The numerical count of the top genre provides a tangible measure of the genre's importance (e.g., The count of "Dramas" for

Section	Description
	the United States).
3. Strategic Insight:	The output table/plot (which was sorted by the top genre's count) clearly highlights the world's major content niches and production giants based on their genre focus.

8.POWER BI WORK

1. Charts (Visualizations Used)

These charts help analyze content patterns, country distribution, rating categories, and release trends in Netflix data.

a. Bar Chart – Count of Movies vs TV Shows

Shows how many Movies and TV Shows are available.

Helps understand Netflix's content distribution.

b. Column Chart – Titles Released by Year

Visualizes number of titles released each year.

Identifies trends (growth or decline in content releasing).

c. Pie / Donut Chart – Primary Genre Distribution

Shows which genre (Drama, Comedy, Action, etc.) has the most titles.

Good for category comparison.

d. Map Chart – Titles by Country

Shows number of titles produced country-wise.

Helps understand regional content contribution.

e. Stacked Bar Chart – Content Rating Distribution

Displays distribution of ratings (PG, R, TV-MA, etc.).

Useful for identifying age-appropriate content groups.

2. Cards (Key Metrics)

Cards display important KPI values extracted from the cleaned Netflix dataset.

a. Total Titles Card

Shows total number of titles in the dataset.

b. Total Movies Card

Displays count of all Movie-type entries.

c. Total TV Shows Card

Displays count of all TV Show-type entries.

d. Distinct Directors Card

Shows number of unique directors in the dataset.

e. Earliest & Latest Release Year Cards

Shows first and last year of released titles.

These KPIs help quickly understand dataset size and key summary statistics.

3. Slicers (Filters Used in Week 7 Dashboard)

Slicers allow users to filter visuals dynamically.

a. Content Type Slicer

Lets user select Movie, TV Show, or both.

All charts update based on the selection.

b. Country Slicer

Filters titles based on selected country.

Useful for region-specific analysis.

c. Genre Slicer

Allows filtering by the primary genre (Drama, Action, etc.).

d. Release Year Slicer

A range slicer to filter titles based on year.

Helps see patterns during specific time periods.

e. Rating Slicer

Filter contents by maturity ratings (TV-MA, PG-13, etc.).

9. TRANSFORMATION OF DATA

1. Data Loading

The raw Netflix dataset was imported into Power BI.

Loaded into Power Query Editor for transformation.

Initial checks were done for structure, column names, and data consistency.

2. Data Type Conversion

Correct data types were applied to ensure accurate calculations and visualizations.

Columns Converted:

date_added → Date

release_year → Whole Number

duration → Text / Split into Number and Unit

show_id, type, genre, country → Text

This step ensures proper filtering, sorting, and time-series operations.

3. Handling Missing Values

Missing values were detected using:

```
df.isna().sum()
```

In Power BI:

Power Query → Column Quality → Missing Values was used.

All missing values were handled by:

Filling blanks with 0 (for numeric fields)

Replacing nulls with “Unknown” (for text fields like director, country)

Dropping rows only if they had extreme missing data (optional)

This ensures no visuals break due to null values.

4. Removing Duplicates

Duplicate rows were identified and removed using

Home → Remove Duplicates.

Ensures data uniqueness and prevents double counting in visuals.