# **PYTHON PROGRAMMING**

**MODULE 4 – PART 2** 

**LIST AND OPERATIONS ON LIST** 

# **OUTLINE**

- List
- □ Create and Assign
- Access elements and slicing
- Delete
- Update
- □ Сору
- Basic Operations
- Built-in Functions and Methods
- Selection sort

## <u>List</u>

- Ordered list of elements indexed from 0 to length-1.
- Repeated elements are allowed.
- Mutable ( can be modified or changed)
- Can contain elements of different data types such as integer, float, string, list, tuple etc.

## **Creating List**

Elements are written separated by commas and enclosed within square brackets

```
#empty list
a=[]

#different types
b=[1, 2, 'red', 2.0]

#creating list using list constructor. It takes only one argument, hence pass list values
in () or [ ].
c=list((1, 2, 'red', 2.0))

#can contain another list, tuple or even functions
d=[1, 2, [3, 4], (5, 6)]
```

# **Accessing List and its elements (slicing)**

```
b=[ 1, 2, 'red', 2.0 ]
c=list(( 1, 2, 'red', 2.0 ))
d=[ 1, 2, [3, 4], (5, 6) ]
                                    <u>OUTPUT</u>
print(c)
print(b[0])
                                    [1, 2, 'red', 2.0]
print(b[-1])
                                    2.0
                                    [2, 'red']
#slicing
print(b[1:3])
                                    [2, 'red']
print(b[-3:-1])
                                    [1, 2, 'red', 2.0]
print(b[-1:-3])
                                    [3, 4]
print(b[:])
print(d[2])
print(d[2][0],d[3][1])
```

## **Deleting list and its elements ( pop(), del, remove() )**

```
b=[1,2,'red',2.0]
#pop can store deleted item, default parameter is -1,last item
item=b.pop(0)
print(item)
                                                                            OUTPUT
print(b)
#del cannot store deleted item hence cannot write in print function
del b[0]
                                                                            [2, 'red', 2.0]
print(b)
                                                                            ['red', 2.0]
                                                                            [2.0]
#cannot store and delete item by specifying value, not index
b.remove('red')
print(b)
#deletes entire list
del b
```

# Adding and Updating List: (append(), insert(), extend())

```
b=[1,2,'red',2.0]
c=[3.2,4.2]
b[3]=2.1
print(b)
                                          OUTPUT
b[0:2]=[3,4]
print(b)
                                          [1, 2, 'red', 2.1]
                                          [3, 4, 'red', 2.1]
#parameters are position and element
                                          [2, 3, 4, 'red', 2.1]
b.insert(0,2)
                                          [2, 3, 4, 'red', 2.1, 2.2, [3.2, 4.2]]
print(b)
                                          [2, 3, 4, 'red', 2.1, 2.2, [3.2, 4.2], 3.3, 3.2, 4.2]
#adds item to the end of list
b.append(2.2)
#adds list as object to current list
b.append(c)
print(b)
#argument must be an iterable such as list, tuple, set etc
b.extend([3.3])
#adds elements of list as new elements to list
b.extend(c)
print(b)
```

# <u>Difference between append() and extend()</u>

Both append() and extend() adds elements to the end of the list

append() can accept both iterable object and individual element as arguments. extend() can only accept an iterable object as argument.

append() adds an iterable object as the same object to the end of the list. extend() separates individual elements of the iterable object and adds as different elements to the end of the list.

In the previous code, list c = [3.2, 4.2] is added as a list itself into the current list b using append() method. Also, extend() method separated elements 3.2, 4.2 and added as float type individual elements to b.

# **Copying list**

```
Case 1
list1=[1,2,3]
list2=list1
print(list1)
print(list2)
list1.append(4)
print(list1)
'''both list1 & list2 points to
same list'''
print(list2)
OUTPUT
[1, 2, 3]
[1, 2, 3]
[1, 2, 3, 4]
[1, 2, 3, 4]
```

# Case 2 list1=[1,2,3] list2=list1[:] print(list1) print(list2) list1.append(4) print(list1) print(list2) OUTPUT [1, 2, 3] [1, 2, 3] [1, 2, 3, 4] [1, 2, 3]

```
Case 3
from copy import copy
list1=[1,2,3]
list2=copy(list1)
print(list1)
print(list2)
list1.append(4)
print(list1)
print(list2)
OUTPUT
[1, 2, 3]
[1, 2, 3]
[1, 2, 3, 4]
[1, 2, 3]
```

# **Basic Operations**

len(), concatenation(+), repetition(\*), membership(in, not in), iteration

### Functions Discussed Earlier

- 1) pop(position)
- 2) remove( element )
- 3) append( element )
- 4) insert( position, element )
- 5) extend(iterable)
- 6) copy()
- 7) len( list )

### **Functions Discussed Next**

- 1) index( element )
- 2) max(list)
- 3) min(list)
- 4) list( sequence )
- 5) clear()
- 6) count( element )
- 7) reverse()
- 8) sort(reverse=True/False, key=myFunc)
- 9) sorted(list, reverse=True/False, key=myFunc)

# **List built-in functions and methods**

```
list1=[1,2,3,3]
print(list1.index(3))
print(max(list1), min(list1))
                                OUTPUT
string1="abcdef"
a=list(string1)
                                3 1
                                 ['a', 'b', 'c', 'd', 'e', 'f']
print(a)
a.clear()
print(a)
                                [3, 3, 2, 1]
print(list1.count(3))
list1.reverse()
print(list1)
```

- sort(reverse=true/false, key=myFunc)
- sorted(list, reverse=true/false, key=myFunc)

#### For both built in functions:

*reverse* is optional and if *true*, sorted in descending order *key* is optional, if given, acts as a function based on which the sorting comparison occurs

#### Difference:

sort() changes original list sorted(list) returns sorted list rather than changing the original

```
list1=["abcd","ade","acdefg"]
list1.sort()
print(list1)
list2=["abcd","ade","acdefg"]
print(sorted(list2))
print(list2)
print("------")
list3=["abcd","ade","acdefg"]
list3.sort(reverse=True)
print(list3)
list3.sort(key=len)
print(list3)
print(sorted(list3,reverse=True,key=len))
```

```
OUTPUT

['abcd', 'acdefg', 'ade']

['abcd', 'acdefg', 'ade']

['abcd', 'ade', 'acdefg']

-----

['ade', 'acdefg', 'abcd']


['ade', 'abcd', 'acdefg']

['acdefg', 'abcd', 'ade']
```

## **Selection sort**

```
list1=[30,20,15,10,50]
print("original list : ",list1)
n=len(list1)
for i in range(n-1):
    small=i
                                      <u>OUTPUT</u>
    for j in range(i+1,n):
                                      original list: [30, 20, 15, 10, 50]
        if list1[j]<list1[small]:</pre>
            small=j
                                      sorted list : [10, 15, 20, 30, 50]
    if i!=small:
        temp=list1[i]
        list1[i]=list1[small]
        list1[small]=temp
print("sorted list : ",list1)
```

### Study at Home



www.teachics.org

# teachics.

The Computer Science Learning Platform.

# Thank You