DOCVERIFY

AI-Based Document Verification and Forgery Detection System

MASTER RESEARCH & ENGINEERING HANDOVER REPORT (PHASES 1 — 5)

Project Title:	DocVerify: AI-Based Document Verification System
Author / Role:	Senior Machine Learning, Computer Vision & Full-Stack AI Engineer
Current Project Status:	Phase 1 ■ | Phase 2 ■ | Phase 3 ■ | Phase 4 ■ | Phase 5 ■ (COMPLETE)
Next Milestone:	Phase 6 (Production Containerization & REST API Finalization)
Execution Date:	2026-10-17
Target Audience:	Research Advisors, Evaluators, Examiners, ChatGPT & External AI Handover Agents
Dataset:	SIDTD (Synthetic Identity Document Tampering Dataset) — Template Subset

Lifecycle Phase Summary & Key Results

Component / Phase	Methodology / Innovation	Key Benchmark Result
Phase 1: Dataset Audit	Physical file inspection, VIA schema decoding	2,222 images, 10 templates, 0% corruption
Phase 2: Group Split	927 Connected Identity Clusters (Union-Find)	0.0% Identity Leakage across splits
Phase 2: Baseline AI	EfficientNet-B0 fine-tuned on Train identities	Test Acc: 79.69%, ROC-AUC: 0.9112
Phase 3: Explainability	Grad-CAM & HiRes-CAM on features[8]	Pointing Acc: 0.59%, Mean IoU: 0.0085
Phase 3: Multi-Scale Discovery	High-resolution local crop ablation	Proves downsampling bottleneck (60.5% rec)
Phase 4: OCR Extraction	EasyOCR v1.7.2 with document enhancement	Real Test CER: 5.01%, Exact Match: 71.52%
Phase 4: Patch Verification	Contextual patch inspection with frozen CNN	Recovers 60.53% (23/38) of missed forgeries
Phase 4: Evidence Fusion	Multi-modal calibrated logistic fusion	Test Acc: 86.88%, ROC-AUC: 0.9553 (FNs -58%)
Phase 5: System Integration	Unified Multi-Modal Engine + Streamlit Web App	Interactive Dashboard, CAMs & PDF Reports

Notice: This handover PDF is the official project continuity record covering Phases 1 through 5. It establishes the complete scientific progression, frozen architectural decisions, code implementations, metric tables, and operational instructions for Phase 6.

1. Project Overview & Scientific Progression

DocVerify is an AI-based document verification and tampering detection system designed to inspect national identity documents (ID cards, passports) and determine whether a document is genuine or tampered with, providing actionable, explainable evidence. The project follows a strict scientific research progression where each architectural component is empirically justified before adoption.

Completed Phase Milestones:

- **Phase 1 (Audit & Understanding):** Verified 2,222 physical JPEGs, identified 500 CMYK images, decoded VIA annotations, and proved 93% identity leakage in random splits.
- **Phase 2 (Identity-Disjoint Baseline):** Eliminated leakage via 927 connected identity clusters; trained EfficientNet-B0 baseline (79.69% Test Acc, 0.9112 ROC-AUC).
- **Phase 3 (Explainability & Localization):** Evaluated Grad-CAM against 169 ground-truth bounding boxes, uncovered spatial misalignment, and demonstrated that downsampling hurts micro-forgeries.
- **Phase 4 (OCR, Patch & Evidence Fusion):** Combined Global CNN + Patch Verification + OCR Consistency. Achieved 86.88% Accuracy, 90.53% Recall, and 0.9553 ROC-AUC, reducing False Negatives from 38 to 16.
- **Phase 5 (System Integration & Web UI):** CURRENT COMPLETED MILESTONE. Engineered unified inference engine, interactive Streamlit application with visual explainability, and automated ReportLab PDF certificates.

2. Chronological Project History & Key Discoveries

Phase 1: Dataset Audit Findings

Audited all files under `E:\DocverifyAi\Dataset`. Proved that 2,222 physical images exist on disk (1,000 Real, 1,222 Fake), while the predefined CSV split referenced 3,139 rows from an alternate run. Exactly 500 real images are encoded in CMYK color space. Discovered that 93% of base identities in validation/test overlap with train, requiring an identity-disjoint split.

Phase 2: Identity-Disjoint Baseline Formulation

Constructed an identity graph linking donor and recipient documents in Crop_and_Replace splicing, forming 927 isolated identity clusters. Trained ImageNet-pretrained EfficientNet-B0 on 1,565 train images and tested on 320 unseen test identities. Baseline results: Accuracy = 79.69%, Precision = 82.91%, Recall = 77.51%, F1 = 80.12%, ROC-AUC = 0.9112 (TN=124, FP=27, FN=38, TP=131). Error analysis revealed that 38 false negatives occurred primarily on micro-manipulated text fields.

Phase 3: Explainability & Ground-Truth Localization

Implemented Grad-CAM and HiRes-CAM on `model.features[8]`. Benchmarked against 169 test fake ground-truth bounding boxes: Pointing Game Accuracy was 0.59% and Mean IoU was 0.0085. This demonstrated that while the CNN accurately classifies documents globally, its post-hoc activation heatmaps do not tightly isolate micro-manipulations. A multi-scale crop study proved that inspecting high-resolution patches recovers 60.53% of missed forgeries.

Phase 4: Multi-Modal Evidence Fusion & Breakthrough

Phase 4 addressed the micro-forgery downsampling bottleneck by integrating high-resolution patch verification and OCR field consistency. EasyOCR achieved 5.01% CER on real test documents. Multi-modal fusion on the untouched test split achieved **86.88% Accuracy and 0.9553 ROC-AUC**, slashing missed forgeries by 57.9% (FNs cut from 38 to 16) while keeping False Positives steady (FP=26 vs FP=27).

Phase 5: System Integration & Web Deployment

Phase 5 integrated all validated components into a production-grade Streamlit web application (`app.py`) powered by `src/inference_engine.py`, `src/template_layouts.py`, and `src/report_generator.py`. Operates independently of ground-truth bounding boxes by using canonical layout projections. Generates downloadable audit-ready PDF certificates with embedded Grad-CAM overlays.

3. Formal Project Change Log

Complete record of all created, modified, and deleted files across the project lifecycle:

Lifecycle	File Path	Purpose / Change Description
Phase 1	`scripts/dataset_audit.py`	Non-destructive dataset audit and integrity verifier.
Phase 2	`scripts/build_manifest.py`	Manifest compiler and 927 connected-cluster group splitter.
Phase 2	`scripts/verify_split.py`	Mathematical zero-leakage split verifier.
Phase 2	`scripts/train_phase2.py`	EfficientNet-B0 training and evaluation pipeline.
Phase 2	`models/phase2/best_model.pth`	FROZEN BASELINE CHECKPOINT (Val F1: 0.8356)
Phase 3	`scripts/gradcam_phase3.py`	Grad-CAM & HiRes-CAM engine on features[8].
Phase 3	`scripts/evaluate_localization.py`	Pointing Game and Bounding-Box IoU evaluator.
Phase 4	`scripts/ocr_phase4.py`	EasyOCR text extractor, CER/WER evaluator, and format checks.
Phase 4	`scripts/patch_verification_phase4.py`	High-resolution patch verification engine with frozen CNN.
Phase 4	`scripts/evidence_fusion_phase4.py`	Multi-modal evidence fusion engine and ablation benchmark.
Phase 5	`src/template_layouts.py`	Canonical bounding box coordinates for 10 document types.
Phase 5	`src/report_generator.py`	ReportLab automated PDF certificate generator.
Phase 5	`src/inference_engine.py`	Unified multi-modal inference class (CNN, Patch, OCR, Fusion).
Phase 5	`app.py`	Streamlit interactive web dashboard and explainability viewer.
Phase 5	`scripts/test_phase5.py`	End-to-end regression and verification test suite.
Phase 5	`requirements.txt & README.md`	Standardized dependencies and quick-start documentation.
Phase 5	`outputs/phase5/DocVerify_Phase5_Handover_Report.pdf`	This Master Research Handover Document.
Status	`Deleted Files`	NONE. No project files were deleted.
Status	`Dataset Status`	ORIGINAL SIDTD DATASET MODIFIED: NO (Strictly Untouched)

4. Technical Implementation & Mathematical Formulations

Unified Inference Pipeline Architecture:

DocVerify processes an input document I through four complementary verification pathways: (1) Global CNN feature extraction yielding P_{global}, (2) Local high-resolution contextual cropping yielding P_{patch}, (3) Optical Character Recognition yielding text legibility confidence C_{ocr} and syntax anomaly flags F_{format}, and (4) Calibrated regularized logistic fusion.

Mathematical Formulations:

- **High-Res Patch Extraction:** To avoid downsampling small text fields (4×10 px) to sub-pixel noise, the patch engine extracts crops scaled by $2.5\times$: $\text{Patch} = \text{Crop}(I, x_c, y_c, 2.5 \cdot \max(w, h))$, resized to 256×256 and cropped to 224×224.
- **Grad-CAM on Features[8]:** $L_{\text{Grad-CAM}}^c = \text{ReLU}\left(\sum_k \alpha_k^c A^k\right)$ where $\alpha_k^c = \frac{1}{Z} \sum_i \sum_j \frac{\partial y^c}{\partial A_{i,j}^k}$.
- **Calibrated Logistic Evidence Fusion:** $z = \beta_0 + \beta_1 P_{\text{global}} + \beta_2 P_{\text{patch}} + \beta_3 C_{\text{ocr}} + \beta_4 F_{\text{mismatch}} + \beta_5 F_{\text{format}}$, with final risk $P_{\text{fusion}}(\text{FAKE}) = \frac{1}{1 + e^{-z}}$.

5. Quantitative Results & Ablation Benchmarks

All four configurations were benchmarked on the untouched test split (320 samples: 151 Real, 169 Fake):

Ablation System / Configuration	Accuracy	Precision	Recall	F1-Score	ROC-AUC	Missed FNs
Config A: Global EfficientNet-B0 Baseline	79.69%	82.91%	77.51%	80.12%	0.9112	38 / 169
Config B: Global + High-Res Patch	80.94%	79.35%	86.39%	82.72%	0.9208	23 / 169
Config C: Global + OCR Evidence	85.62%	83.98%	89.94%	86.86%	0.9551	17 / 169
Config D: Full Multi-Modal Fusion	**86.88%**	**85.47%**	**90.53%**	**87.93%**	**0.9553**	**16 / 169**

Granular Forgery Type Breakdown

Forgery Mechanism	Samples	Global Recall	Patch Recall	Full Fusion Recall	Net Improvement
Crop_and_Replace (Splicing)	24	70.83%	70.83%	91.67%	+20.84%
Inpaint_and_Rewrite	145	78.62%	79.31%	90.34%	+11.72%

6. Visual Evidence & Evaluation Plots

Visual artifacts generated during Phase 4 and Phase 5 benchmarking:




Figure 1: ROC Curves across Ablation Configurations




Figure 2: Confusion Matrix of Full Fusion (Acc: 86.88%)

End-to-End System Latency Breakdown (Measured on CPU)

Pipeline Component	Measured Latency (s)	Share (%)	Role / Notes
Global CNN Forward Pass	0.074s	2.5%	EfficientNet-B0 inference on 224x224 tensor
Dual CAM Heatmaps	0.305s	10.4%	Grad-CAM + HiRes-CAM on features[8]
Patch Verification (7 fields)	0.477s	16.3%	High-resolution contextual field crops
EasyOCR Field Extraction	2.064s	70.7%	Contrast normalization + character reading
Evidence Fusion	0.001s	<0.1%	Calibrated logistic decision regression
Total Warm Pipeline	**2.600s**	**100.0%**	**Complete document verification cycle**

7. Continuity & Next Phase Handoff (Phase 6 Roadmap)

Completed Project Deliverables (Phases 1 through 5):

- ✔ Phase 1 dataset audit and 100% verified paired annotation mapping.
- ✔ Phase 2 identity-disjoint split (927 clusters, 0.0% leakage).
- ✔ Phase 2 EfficientNet-B0 baseline (79.69% Test Acc, 0.9112 ROC-AUC).
- ✔ Phase 3 Grad-CAM & HiRes-CAM explainability and quantitative localization evaluation.
- ✔ Phase 4 OCR extraction (5.01% CER on real documents) and field consistency checks.
- ✔ Phase 4 High-Resolution patch verification recovering 60.53% of missed forgeries.
- ✔ Phase 4 Multi-Modal Evidence Fusion achieving 86.88% Accuracy, 90.53% Recall, and 0.9553 ROC-AUC.
- ✔ Phase 5 System Integration: Streamlit Web Dashboard (`app.py`), Modular Inference Engine (`src/`), and Automated ReportLab PDF Certificate Generator.

System Limitations & Operational Boundaries:

1. **Downsampled CAM Bottleneck:** Grad-CAM computes on 7×7 activations. When projected back to 2167×1360 documents, CAM blobs highlight macroscopic regions rather than individual character strokes, which is solved by patch verification.
2. **Template Boundary:** Candidate field generation currently supports 10 canonical templates. Unseen national documents fallback to aspect-ratio heuristic matching.
3. **CPU Compute Footprint:** EasyOCR accounts for ~70% of CPU inference time (~2.06s). GPU acceleration is recommended for high-volume enterprise deployment.

Frozen Decisions — DO NOT ALTER IN FUTURE PHASES:

1. **Original SIDTD Dataset:** Must remain completely untouched under `Dataset/`.
2. **Identity-Disjoint Split:** The 927-cluster split in `dataset_manifest.csv` is permanent.
3. **Phase 2 Classifier Checkpoint:** `models/phase2/best_model.pth` is frozen.
4. **Evaluation Protocol:** No tuning on test data; validation features only.
5. **Safe CMYK Ingestion:** Image loading must always invoke `.convert('RGB')` using Pillow.

Exact Run Instructions:

- **Launch Web Application:** `streamlit run app.py` (accessible at http://localhost:8501)
- **Execute Test Suite:** `python scripts/test_phase5.py` (validates all 7 regression tests)

Roadmap Status: Phase 1: COMPLETE | Phase 2: COMPLETE | Phase 3: COMPLETE | Phase 4: COMPLETE | Phase 5: COMPLETE | Phase 6: READY TO COMMENCE.