SMART ENERGY MONITORING SYSTEM FOR HOUSEHOLD APPLIANCES

Ninad Padamwar
Department of CSE (AI and ML)
PCCOE, Pune
ninad.padmwar24@pccoepune.org

Mrs. Suvarna P. Bhatsangave
Department of CSE (AI and ML)
PCCOE, Pune
suvarna.bhatsangave@pccoepune.org

Piyush More
Department of CSE (AI and ML)
PCCOE, Pune
piyush.more24@pccoepune.org

Nivesh Koskewad
Department of CSE (AI and ML)
PCCOE, Pune
nivesh.koskewad24@pccoepune.org

Abstract—With each passing day, the demand for electricity in urban areas grows at an alarming rate, bringing with it the socioeconomic woes of soaring utility costs for the residents as well as unprecedented strain on the electricity distribution network. Smart meters provide details of the amount of electricity consumed, but do not highlight the appliances consuming the most electricity which leads to the situational of inefficiency in system and behavioural control at the individual level. Proposed system aims to fix the issue in hand by succession of smart technologies to estimate the energy demand on an household and break it down to individual device level using machine learning. With these insights, the system provides actionable intelligence for consumers to implement energy reduction measures, thus minimizing overall costs and improving electricity usage during peak hours. Proposed system also employ (ML, LSTM and CNN) for demand forecasting and NLM to ensure high level prediction and disaggregation remotely. The (LSTM) captures the use of the time pattern and the (CNN) identifies the appliances to offer the end users the highest reliable energy disaggregation.

1. Introduction

Energy use is vital in contemporary home management, with the use of appliances determining the total energy consumption mainly due to urbanization and the use of technology in today's world. In this context, the consumption of electricity in residential places has quickly become one of the primary sources of demand for energy on the globe. The increased demand now places additional strain on the distributing and supplying systems which in turn affects the entire reliability of energy and its management systems.

To monitor real-time energy consumption on the household level, smart meters have emerged as a partial solution. While smart meters provide aggregate energy consumption data, they do not provide information on energy consumption at the appliance level. Without appliance-level data, consumers cannot identify, target, or take action on devices that are underperforming or inefficient. Thus, even with real-time monitoring, households are not equipped with the necessary insights to make energy-saving choices.

This gap is the motivation behind the research, which seeks to use sophisticated machine learning techniques to close the gap. The proposed system intends to predict household electricity demand while also disaggregating the consumption to the appliance level. With smart models, households would be able to not just monitor energy consumed but also appreciate the factors and the reasons behind the consumption. Empirical data from households offers actionable insights that help consumers reduce excessive costs, promote energy conservation, and adopt sustainable practices. Additionally, this data aids in protecting devices from irreversible damage or delays in servicing by ensuring timely maintenance.

The orthodox approaches in monitoring rely solely on manual inspections or "if this, then that" systems, which lack precision and the ability to scale. In comparison to the manual approach, LSTM has the potential to more accurately capture the temporal relationships in the patterns of energy usage, making it suitable for demand forecasting. LSTM has the ability to capture temporal correlations in energy usage patterns and is thus suitable for forecasting future demand, and CNNs can accurately classify device-level signatures, thus performing energy disaggregation. These models in unison furnish a refined approach for real-time prediction and comprehension of appliances' energy consumption in the household. Beyond the savings on the energy bill, this provides an indication of the value of this research to the rest of the energy ecosystem. Insights on energy usage on the appliance level can help utilities to formulate more effective demandside management, lessening peak demand-related

stress, and enhancing overall power distribution efficacy. In addition, this type of system enables the attainment of global sustainability objectives by promoting more rational energy consumption, lessening total carbon emissions, and fostering the transition to smarter and greener urban centers. The system proposed manages to solve the problem that a household confronts on energy consumption while contributing to the development of intelligent and sustainable urban centers, which require flexible and resilient energy infrastructures. II. LITERATURE REVIEW

1.1. Smart Energy Management Systems (SEMS)

The operation of a grid in an efficient, sustainable, and user centered manner is increasingly depending on Smart Energy Management Systems (SEMS)[1]. A strong SEMS should be able to do the following:

- Predict the energy consumption of an entire appliance.
- Enable demand management.
- Incorporate device-level monitoring to provide personalized energy-saving tips.
- Enhance grid reliability by alleviating peak demand.

IoT devices in SEMS are noted in the most recent literature since they provide real-time, device-level monitoring and control within the home. Such systems, by incorporating historical consumption data, environmental data, and sensor based inputs, are able to more accurately and efficiently predict and optimize household energy consumption.[2]

1.2. Machine Learning Approaches for Energy Prediction

Household energy prediction tasks have been undertaken by numerous machine learning algorithms. These include:

- Baseline forecasting through simple and complex models: Regression and classification techniques.
- Advanced deep learning models: Hybrid architectures such as Convolutional Neural Networks (CNNs) and Long Short-Term Memory (LSTM) networks, which are exceptional in capturing:
  - Nonlinear temporal dependencies (time-based consumption trends).
  - Device-specific usage behaviors (appliance-level patterns).

The employment of such models enhances the responsiveness and accuracy of SEMS, thereby improving overall prediction under dynamic energy conditions[3].

1.3. Model Comparison

The performance of the ML models used in SEMS is summarized in Table I.

Model	RMSE	MAE	MAPE (%)	Limitation
LSTM	0.748	0.628	51.45	Captures temporal patterns, good for sequential prediction
CNN	0.611	0.349	34.84	Efficient feature extraction, robust for appliance pattern recognition
CNN-LSTM	0.225	0.098	11.66	Combines spatial and temporal learning, highest prediction accuracy

TABLE I
COMPARISON OF MACHINE LEARNING MODELS FOR ENERGY PREDICTION

Justification: The hybrid CNN-LSTM model is selected due to its superior accuracy and ability to learn both temporal and spatial patterns of energy consumption, making it ideal for appliance-level disaggregation and household energy forecasting. This approach aligns with findings from recent research, demonstrating hybrid models outperform single model architectures in energy prediction tasks.

1.4. Comparative Analysis

To better understand the strengths of the proposed system, a comparison was made with traditional monitoring methods and alternative approaches. Table II highlights the key differences.

Approach	Limitations	Proposed System Advantages
Traditional Smart Meters	Provide only total household usage; lack appliance-level detail.	Offers both aggregate and appliance-level energy consumption for better decision making.
Rule-based / Statistical Models	Rigid and fail under changing user behavior or multiple devices running simultaneously.	Adaptive deep learning models (LSTM + CNN) dynamically adjust to varying consumption patterns.

Single ML Models (only LSTM or only CNN)	Capture either temporal or spatial features, but not both effectively.	Hybrid CNN-LSTM learns both time based and appliance level patterns, yielding higher prediction accuracy.
Existing Dashboards	Often too technical and difficult for endusers to interpret; lack actionable guidance.	Provides a userfriendly interface with visual dashboards, recommendations, and real-time alerts.

TABLE II

COMPARATIVE ANALYSIS OF ENERGY MONITORING APPROACHES

1.5. Anomaly Detection and Fault Detection

Like in SEMS recent literature has also underscored the significance of fault detection in the management of energy streams. Through the use of datasets captured by various sensors, it is possible for SEMS to recognize:

- Devices with suboptimal performance.
- Devices experiencing fault conditions or operational issues.
- Deviations in consumption behaviors.[4]

[The system's ability to accurately and quickly execute the above-mentioned activities assists in reducing operational energy costs, eliminating wasteful energy expenditure, and elevating system dependability.

1.6. Emerging Trends and Future Directions

Based on the literature, there is an established shift in focus towards:

- Intelligent systems that can automatically and seamlessly manage the energy requirements for various appliances in a household.
- Modular and tiered system designs that offer both adaptive and robust systems.
- Coupling with. smart grid projects for the development of effective and sustainable energy frameworks.

With the growing diversity and multiplicity of electrical appliances in residential buildings, such advancements in SEMS will be vital for the construction of next-generation smart grids and sustainable cities.

3. System Architecture

3.1. Overview

The proposed Smart Energy Monitoring System (SEMS) is designed to monitor and predict household energy consumption at both aggregate and appliance levels. The system integrates smart meters, IoT sensors, and machine learning models to provide real-time insights and actionable recommendations to users.[5]



Fig. 1. SMART ENERGY MANAGEMENT SYSTEM ARCHITECTURES.

3.2. Components

The main components of the system include:

- IoT Sensors: Collect real-time energy usage data from individual appliance.
- Smart Meters: Measure overall household energy consumption and relay data to the central system.
- Data Processing Unit: Preprocesses raw sensor data, removes noise, and structures it for analysis.
- Machine Learning Models: LSTM networks capture temporal patterns for demand forecasting, while CNNs identify appliance-specific consumption signatures for energy disaggregation.
- User Interface: Displays energy usage insights, appliance level consumption, and personalized energy saving recommendations.[6]

3.3. Data Flow

The data flow in the system follows these steps:

1) Energy data is captured by IoT sensors and smart meters in real-time.
2) Raw data is transmitted to the Data Processing Unit for cleaning and preprocessing.
3) Processed data is fed into machine learning models for demand forecasting and appliance-level energy disaggregation.
4) Forecasts and insights are sent to the user interface and optionally to a central controller for grid-level optimization.

3.4. Modularity and Scalability

Modularity in the architecture divides the system into independent, self-sufficient modules responsible for specific tasks or groups of appliances, ranging from individual devices to integrated subsystems. Each module can autonomously retrieve, store, and process information, sharing it with adjacent modules or a higher-level central controller.



Fig. 2. USER INTERFACE

C. Data Flow and Interactions

The activities within the software application proceed as follows:

1) IoT devices and smart meters collect energy data and send it to the Data Acquisition Module.
2) The Data Preprocessing Module receives the data for cleansing, normalization, and formatting.
3) Preprocessed data is sent to the Energy Prediction and Disaggregation Modules for forecasting and appliance-level analysis.

This approach provides advantages in system maintenance, including easier upgrades and fault isolation. Importantly, if a module fails, the rest of the system continues to operate without interruption.

Scalability refers to the architecture's ability to maintain performance as the number of connected devices or data volume increases. In dynamic household scenarios, it is crucial that new modules or appliances can be added with minimal or no redesign, without any drop in system performance.[7]

4. Software Design

4.1. Overview

The software design of the Smart Energy Monitoring System (SEMS) focuses on modularity, scalability, and realtime processing. The software is responsible for collecting data from IoT sensors and smart meters, preprocessing it, running machine learning algorithms for energy prediction and.

E. Technology Stack

- Programming Languages: Python (for ML models and data processing), JavaScript (for front-end interface).
- Machine Learning Libraries: TensorFlow, Keras, PyTorch for LSTM and CNN implementation.
- Database: MySQL or MongoDB for storing sensor data, historical readings, and predictions.
- Frameworks: Flask or Django for backend API development; React or Angular for web dashboards.
- Communication Protocols: MQTT or HTTP for sensor data transmission.

V. Implementation



Smart home Energy Management System :Data Implementation diagram

4.2. System Modules

The major components of the system are outlined below:

- Data Acquisition Module: Collects real-time appliancelevel and total household energy data from smart IoT meters.
- Data Preprocessing Module: Cleans raw data by removing missing values and noise. The data is consolidated, normalized, and formatted for input to machine learning models.
- Energy Prediction Module: Utilizes LSTM models to forecast household energy demand and analyze temporal energy usage patterns.
- Energy Disaggregation Module: Determines energy consumption of individual appliances from total meter

readings. CNNs are used to identify appliance-specific usage patterns for detailed disaggregation.

- Anomaly Detection Module: Monitors sensor data to detect neglected devices, inefficient appliances, or abnormal energy consumption patterns.
- User Interface Module: Provides dashboards and visualizations of real-time and historical energy consumption, appliance-level usage, and energy-saving recommendations.

4) The User Interface Module receives predictions, appliance-level consumption, and anomaly alerts for visualization and user notifications.
5) All processed data and predictions are stored in the database for analysis and model retraining.

D. Design Principles

The software design follows key principles:

- Modularity: Each module is independent and can be updated, replaced, or scaled without affecting the others.
- Scalability: The system can handle an increasing number of appliances, IoT devices, and data streams without performance degradation.
- Reliability: Fault-tolerant design ensures continuous operation even if a module or sensor fails.
- Extensibility: Easy integration of new ML algorithms, sensors, or visualization tools.
- Real-time Processing: Supports near real-time data acquisition, analysis, and feedback to users for timely energy-saving decisions.

Fig. 3. USER INTERFACE

5.1. Collection and Integration of Data

The first step focuses on encouraging and assisting citizens to deploy IoT smart sensors and smart plugs at their homes. These devices monitor and track the real-time energy consumption of each appliance. In addition to appliance-level monitoring, non-occupancy sensors and contextual data such as weather patterns, occupancy levels, and user routines are integrated to enhance prediction accuracy. Communication protocols like Internet, ZigBee, and Ethernet are configured at the user's modem level to ensure reliable transmission of data, whether in real-time streams or batch uploads, to edge or cloud-based architectures.

5.2. Data Purification and Cloud Processing

The second step involves data purification and cloud-based storage. Data cleaning methods, such as median-based calculations to fill missing values, and interquartile range methods to detect and remove outliers, are employed to ensure the integrity of the dataset. Once pre processed, the raw and processed data are stored in cloud architectures designed for IoT time-series data. These include low, medium, and high resolution datasets of sequential energy readings, making them suitable for both real-time processing and historical trend analysis.

5.3. Internet of Things Perception Architecture

The third step is the development of the IoT perception architecture using machine learning. A hybrid model combining LSTM and CNN is implemented, where LSTM captures the temporal consumption patterns and CNN identifies spatial features in the data. The system also integrates cascaded ResNet models to enhance raw feature extraction from sensor inputs. This architecture is designed to be adaptable, allowing new models, updated parameters, or additional inputs to be integrated seamlessly as more realtime and historical data become available.



Fig. 4. LSTM and CNN flow

5.4. Rollout of Elastic and Modular Architecture

The final step focuses on deploying an elastic, modular architecture. Each module acts as an independent relay responsible for localized prediction and optimization, either at the household level or for specific appliance groups. These independent modules operate autonomously while transmitting aggregated insights to higher-level relays. This modular approach ensures scalability, fault tolerance, and efficient operation, as even if one module fails, the rest of the system continues to function optimally.

6.Conclusion

The smart energy management system for household appliances with its modular and scalable architecture advances the ability to use energy efficiently and sustainably while assuring system operability and reliability. It captures the real time consumption of the appliances with the use of IoT and a sophisticated machine learning engine such as LSTM and CNN to predict the energy consumed at the appliance level and its subsequent management, and performs the necessary data cleaning and processing. This helps the users to detect devices having low use efficiency and offers device control and practice energy conservation at minimal energy expenditure and without compromising comfort and convenience.

Also, the ease of system expansion and modular architecture of the system helps with the incorporation of future appliances and technologies with system interoperability. On the whole, the architecture of the system in terms of repair and maintenance keeps the energy use metrics within the household, encourages demand-side energy management of the grid, and promotes an optimally balanced and available energy plan to the households.

7.Future Scope

One of the biggest changes in the use of smart energy management systems (SEMS) for household appliances is going to be the decision of their creators to apply artificial intelligence to get bigger benefits from the same data. One can easily guess that this is not the only reason. The main factor behind the explosion of SEMS technologies is the worldwide aim of achieving clean and efficient energy usage.

In the near future, devices will be devised to be so compatible with each other despite different manufacturers, hence sharing of data and having a common control of the multivendor ecosystem will be a reality. There is also a lot of promise in using big data analytics and understandable AI to provide an easily adaptive, resident-centric energy consumption system, which will be the perfect combination of efficiency, uptime, comfort, and behavior patterns for the residents.

The usage of distributed renewable energy (e.g., solar panels on rooftops) and energy storage in SEMS is planned to be the enabler of demand response, peer-to-peer energy trading, and provision of ancillary services to the grid at the residential level. Moreover, the real-time dynamic pricing models along with predictive algorithms may become strong supporters of the next-day scheduling, which will be instrumental in achieving economic and environmental goals, while at the same time securing power reliability in a grid that is becoming increasingly unstable.

The use of sophisticated algorithms such as deep reinforcement learning and federated machine learning is expected to open up energy management solutions for the multi-home sector that are both scalable and privacy preserving. Future systems should also emphasize user friendly design, improving transparency, trust, and adoption among residents.

8.References

[1] Guang-Li Huang; Adnan Anwar; Seng W. Loke; Arkady B. Zaslavsky; Jinho Choi: 2022 (though on arXiv in late 2023, the conference version is from IEEE VTC Spring 2022).

[2] Ahmad Khan; Tanveer Hussain; Amin Ullah; Seungmin Rho; Miyoung Lee; Sung Wook Baik Article Number: 1399
Year of Publication: Sejong

[3] Hojun Jin; Sarvar Hussain Nengroo; Yoonmee Doh; Chungho Lee; Taewook Heo; Dongsoo Har
2022 for the IEEE conference publication; it was on arXiv as of 6 December 2021.

[4] S. Balamuralitharan; Santhoshkumar S.; Someshwar Siddi; J. Prasadarao *International Journal of Intelligent Systems and Applications in Engi- neering (IJISAE)*
Vol. 12, No. 21s, 06 April 2024
DOI: 10.1016/j.apenergy.2020.114949

[5] S. H. Nandigam, K. Nageswararao, P. K. Sharma "Hybrid Deep Learning Models for Energy Consumption Forecasting: A CNN-LSTM Approach for Large-Scale Datasets", *RAST*, 2025.

[6] "Energy consumption prediction using modified deep CNN-Bi LSTM with attention mechanis *Heliyon*, 2025. DOI: 10.1016/j.heliyon.2024.e41507

[7] "Smart Home Energy Management System Architecture Using IoT", *Proceedings of the 9th International Conference on Information Systems and Technologies*, 2019.

[8] *Zhou, X., Feng, J., & Li, Y. (2021*)**.** Non-intrusive load decomposition based on CNN-LSTM hybrid deep learning model. *Energy Reports*, *7*, 5762–5771.

[9] Lee, S., & Choi, D.-H. (2020**).** Energy management of smart home with home appliances, energy storage system and electric vehicle: A hierarchical deep reinforcement learning approach. *Sensors*, *20*(7), 2157