

**Name: Swarnabh Paul**

**Section: Y**

**Roll no: 19CS8122**

**Assignment no: 4**

**Questions attempted:**

**a,b**

# Question (a)

## Contents of Linked List header file:

```
using namespace std;
class node
{
public:
    int data;
    node *link;
    node(int, node*);
};
node::node(int x=0, node *l=NULL)
{
    data=x;
    link=l;
}
class sll
{
    node head;
    node* createNewNode(int, node*);
    bool isempty();
public:
    sll(node *l);
    sll(const sll&);
    ~sll();
    void deletesll();
    void insertBeg(int);
    void Delete(int);
    bool search(int);
    void display();
    int size();
};
sll::sll(node *l=NULL)
{
    head.data=0;
    head.link=l;
    if(l!=NULL)
    {
        int cnt=1;
        node *t=l;
        while(t->link!=NULL)
        {
            t=t->link;
            cnt++;
        }
        head.data=cnt;
    }
    cout<<"List constructed"<<endl;
}
sll::sll(const sll &s)
{
    head.data=s.head.data;
    head.link=NULL;
    node *t=s.head.link;
    if(t!=NULL)
```

```

        {
            insertBeg(t->data);
            head.data--;
            t=t->link;
            node *p=head.link;
            for(int i=1;i<s.head.data;i++,t=t->link,p=p->link)
                p->link=createNewNode(t->data,NULL);
        }
    }

void sll::deletesll()
{
    node *t;
    for(int i=0;i<head.data;i++)
    {
        t=head.link;
        head.link=head.link->link;
        delete t;
    }
    head.data=0;
}

bool sll::isempty()
{
    return (head.data==0);
}

void sll::insertBeg(int x)
{
    head.link=createNewNode(x,head.link);
    head.data++;
}

node* sll::createNewNode(int x,node *l)
{
    node *t=new node(x,l);
    return t;
}

sll::~~sll()
{
    deletesll();
    cout<<"List destroyed"<<endl;
}

void sll::Delete(int x)
{
    if(isempty())
    {
        cout<<"List is empty\n";
        return;
    }
    node *p=head.link;
    node *q;
    if(p->data==x)
    {
        head.link=p->link;
        delete p;
        head.data--;
    }
    else
    {

```

```

        while (p!=NULL&& p->data!=x)
        {
            q=p;
            p=p->link;
        }
        if (p==NULL)
            cout<<"No match :: deletion failed\n";
        else
        {
            q->link=p->link;
            delete p;
            head.data--;
        }
    }
}

bool sll::search(int x)
{
    node *t=head.link;
    int i;
    for (i=0; i<head.data; i++, t=t->link)
        if (t->data==x)
            return true;
    return false;
}

void sll::display()
{
    node *t=head.link;
    for (int i=0; i<head.data; i++, t=t->link)
    {
        cout<<t->data<<" --> ";
    }
    cout<<"||"<<endl;
}

int sll::size()
{
    return head.data;
}

```

### **Code:**

```

#include<iostream>
#include<stdbool.h>
#include<math.h>
#include<time.h>
#include"MyLinkedList.h"
using namespace std;
class hashing
{
    sll *ht;
    int htsize, mode;
    int hashfn(int);
    int hashfn2(int);
public:
    hashing(int, int);
    ~hashing();
    bool Search(int);

```

```

    void Insert(int);
    void Delete(int);
    void Display();
    double TableLoadDistr();
};

int hashing::hashfn(int x)
{
    return (x%htsize);
}

int hashing::hashfn2(int x)
{
    x=abs(x);
    int s=0;
    while(x)
    {
        s+=(x%10);
        x/=10;
    }
    return (s%htsize);
}

hashing::hashing(int n=10,int m=0)
{
    ht=new sll[n];
    htsize=n;
    mode=m%2;
}

hashing::~~hashing()
{
    for(int i=0;i<htsize;i++)
        ht[i].deletesll();
    delete []ht;
}

bool hashing::Search(int x)
{
    int index;
    switch(mode)
    {
        case 0: index=hashfn(x);    break;
        case 1: index=hashfn2(x);   break;
    }
    return (ht[index].search(x));
}

void hashing::Insert(int x)
{
    int index;
    switch(mode)
    {
        case 0: index=hashfn(x);    break;
        case 1: index=hashfn2(x);   break;
    }
    ht[index].insertBeg(x);
}

void hashing::Delete(int x)
{
    int index;
    switch(mode)
    {

```

```

        case 0: index=hashfn(x);    break;
        case 1: index=hashfn2(x);   break;
    }
    if(Search(x))
    {
        ht[index].Delete(x);
    }
    else
        cout<<"Element not found. Deletion not possible."<<endl;
}

void hashing::Display()
{
    for(int i=0;i<htsize;i++)
        ht[i].display();
}

double hashing::TableLoadDistr()
{
    int totalElements=0;
    double deviation=0.0, expectedLoad=100.0/htsize, bucketLoad;
    for(int i=0;i<htsize;i++)
        totalElements+=ht[i].size();

    cout<<"Expected load in each bucket = "<<expectedLoad<<"%"<<endl;
    for(int i=0;i<htsize;i++)
    {
        bucketLoad=ht[i].size()*100.0/totalElements;
        cout<<"Load in bucket "<<i+1<<" = "<<bucketLoad<<"%"<<endl;
        deviation+=fabs(expectedLoad-bucketLoad);
    }
    return deviation;
}

unsigned long int myrand(unsigned long int x)
{
    unsigned long long int m=2147483647, a=65539;
    unsigned long int r=(x*a)%m;
    return r;
}

int main()
{
    hashing h1, h2(10,1);
    double deviation1, deviation2;
    unsigned long int seed;
    int e;
    time_t seconds=time(NULL);
    seed=seconds;
    for(int i=0;i<100;i++)
    {
        seed=myrand(seed);
        h1.Insert(seed%100+1);
        h2.Insert(seed%100+1);
    }
    cout<<"Displaying hash table:"<<endl;
    h1.Display();
    deviation1=h1.TableLoadDistr();
    cout<<"Total percentage deviation is: "<<deviation1<<endl;
    h2.Display();
    deviation2=h2.TableLoadDistr();
}

```



62 --> 92 --> 12 --> 12 --> 92 --> 42 --> 42 --> 12 --> 62 --> 12 --> ||  
 83 --> 63 --> 3 --> 53 --> 53 --> 73 --> 43 --> 13 --> 53 --> 23 --> 83 --> ||  
 34 --> 84 --> 4 --> 34 --> 54 --> 34 --> 94 --> 4 --> 44 --> 84 --> 54 --> 54 --> 74 -->  
 54 --> 4 --> 94 --> 34 --> ||  
 35 --> 5 --> 45 --> 35 --> 55 --> 65 --> 15 --> 85 --> 45 --> 95 --> ||  
 56 --> 76 --> 66 --> 36 --> 96 --> 86 --> 36 --> 66 --> 66 --> 56 --> 56 --> 36 --> ||  
 47 --> 67 --> 47 --> 7 --> 57 --> 87 --> 17 --> 87 --> ||  
 78 --> 78 --> 58 --> 78 --> 88 --> 68 --> 28 --> ||  
 79 --> 59 --> 39 --> 39 --> 39 --> 49 --> 89 --> 59 --> 39 --> 19 --> 59 --> ||

Expected load in each bucket = 10%

Load in bucket 1 = 9%

Load in bucket 2 = 5%

Load in bucket 3 = 10%

Load in bucket 4 = 11%

Load in bucket 5 = 17%

Load in bucket 6 = 10%

Load in bucket 7 = 12%

Load in bucket 8 = 8%

Load in bucket 9 = 7%

Load in bucket 10 = 11%

Total percentage deviation is: 22

73 --> 55 --> 91 --> 19 --> 28 --> ||  
 56 --> 47 --> 83 --> 47 --> 92 --> 92 --> 65 --> 100 --> 10 --> 56 --> 10 --> 100 --> 56  
 --> 74 --> 83 --> ||  
 84 --> 66 --> 39 --> 39 --> 39 --> 57 --> 39 --> 66 --> 84 --> 66 --> ||  
 67 --> 30 --> 76 --> 58 --> 49 --> 3 --> 12 --> 12 --> 94 --> 12 --> 12 --> 85 --> 94 -->  
 ||  
 59 --> 4 --> 59 --> 86 --> 4 --> 40 --> 13 --> 59 --> 68 --> 4 --> 95 --> ||  
 78 --> 78 --> 5 --> 78 --> 87 --> 96 --> 41 --> 50 --> 23 --> 87 --> ||  
 79 --> 60 --> 60 --> 42 --> 51 --> 42 --> 15 --> 88 --> ||  
 34 --> 61 --> 34 --> 7 --> 89 --> 34 --> 43 --> 61 --> 34 --> ||  
 35 --> 62 --> 53 --> 53 --> 35 --> 44 --> 17 --> 62 --> 53 --> ||  
 36 --> 63 --> 45 --> 54 --> 36 --> 54 --> 54 --> 45 --> 54 --> 36 --> ||

Expected load in each bucket = 10%

Load in bucket 1 = 5%

Load in bucket 2 = 15%

Load in bucket 3 = 10%

Load in bucket 4 = 13%

Load in bucket 5 = 11%

Load in bucket 6 = 10%

Load in bucket 7 = 8%

Load in bucket 8 = 9%



Load in bucket 9 = 9%

Load in bucket 10 = 10%

Total percentage deviation is: 18

hashfn2() is better hash function.

Enter value to search for: 40

Search successful. Element found.

Enter element to delete: 40

Displaying hash table:

30 --> 60 --> 60 --> 50 --> 100 --> 10 --> 10 --> 100 --> ||

61 --> 41 --> 91 --> 51 --> 61 --> ||

62 --> 92 --> 12 --> 12 --> 92 --> 42 --> 42 --> 12 --> 62 --> 12 --> ||

83 --> 63 --> 3 --> 53 --> 53 --> 73 --> 43 --> 13 --> 53 --> 23 --> 83 --> ||

34 --> 84 --> 4 --> 34 --> 54 --> 34 --> 94 --> 4 --> 44 --> 84 --> 54 --> 54 --> 74 -->  
54 --> 4 --> 94 --> 34 --> ||

35 --> 5 --> 45 --> 35 --> 55 --> 65 --> 15 --> 85 --> 45 --> 95 --> ||

56 --> 76 --> 66 --> 36 --> 96 --> 86 --> 36 --> 66 --> 66 --> 56 --> 56 --> 36 --> ||

47 --> 67 --> 47 --> 7 --> 57 --> 87 --> 17 --> 87 --> ||

78 --> 78 --> 58 --> 78 --> 88 --> 68 --> 28 --> ||

79 --> 59 --> 39 --> 39 --> 39 --> 49 --> 89 --> 59 --> 39 --> 19 --> 59 --> ||

List destroyed

List destroyed

List destroyed

List destroyed

List destroyed

List destroyed

List destroyed

List destroyed

List destroyed

List destroyed

List destroyed

List destroyed

List destroyed

List destroyed

List destroyed

List destroyed

List destroyed

List destroyed

List destroyed

List destroyed

## Question (b)

### Code:

```
#include<iostream>
#include<stdbool.h>
#include<math.h>
using namespace std;
class node
{
public:
    int exp, coeff;
    node *link;
    node(int, int, node*);
};
node::node(int c=0, int e=0, node *l=NULL)
{
    coeff=c;
    exp=e;
    link=l;
}
class polynomial
{
    node head;
    bool isempty();
    node *createNewNode(int, int, node*);
public:
    polynomial(node*);
    polynomial(const polynomial&);
    ~polynomial();
    void DeletePoly();
    void InsertTerm(int, int);
    void DeleteTerm(int, int);
    void DisplayPoly();
    double EvalPoly(double);
    polynomial* AddPoly(const polynomial &p);
};
bool polynomial::isempty()
{
    return (head.coeff==0);
}
node* polynomial::createNewNode(int c, int e, node *l)
{
    node *t=new node(c, e, l);
    return t;
}
polynomial::polynomial(node *l=NULL)
{
    head.coeff=0;
    head.exp=0;
    head.link=l;
    if(l!=NULL)
    {
        int cnt=0, Max=l->exp;
        node *t=l;
        while(t=NULL)
```

```

        {
            t=t->link;
            cnt++;
            if (t->exp>Max)
                Max=t->exp;
        }
        head.coeff=cnt;
        head.exp=Max;
    }
    cout<<"Polynomial constructed"<<endl;
}
polynomial::polynomial(const polynomial &p)
{
    head.coeff=p.head.coeff;
    head.exp=p.head.exp;
    head.link=NULL;
    node *t=p.head.link;
    if (t!=NULL)
    {
        head.link=createNewNode(t->coeff,t->exp,head.link);
        t=t->link;
        node *q=head.link;
        for(int i=1;i<p.head.coeff;i++,q=q->link,t=t->link)
            q->link=createNewNode(t->coeff,t->exp,NULL);
    }
}
polynomial::~~polynomial()
{
    DeletePoly();
    cout<<"Polynomial destroyed"<<endl;
}
void polynomial::DeletePoly()
{
    node *t;
    for(int i=0;i<head.coeff;i++)
    {
        t=head.link;
        head.link=head.link->link;
        delete t;
    }
    head.coeff=0;
}
void polynomial::InsertTerm(int c,int e)
{
    if(isempty())
    {
        head.link=createNewNode(c,e,head.link);
    }
    else if(head.link->exp>e)
    {
        head.link=createNewNode(c,e,head.link);
    }
    else
    {
        node *p=head.link;
        while(p->link!=NULL&& p->link->exp<e)
            p=p->link;
    }
}

```

```

        p->link=createNewNode(c,e,p->link);
    }
    head.coeff++;
}
void polynomial::DeleteTerm(int c,int e)
{
    if(isempty())
    {
        cout<<"Polynomial is empty\n";
        return;
    }
    node *p=head.link;
    node *q;
    if(p->coeff==c&&p->exp==e)
    {
        head.link=p->link;
        delete p;
        head.coeff--;
    }
    else
    {
        while(p!=NULL&&(p->coeff!=c||p->exp!=e))
        {
            q=p;
            p=p->link;
        }
        if(p==NULL)
            cout<<"No match :: deletion failed\n";
        else
        {
            q->link=p->link;
            delete p;
            head.coeff--;
        }
    }
}
void polynomial::DisplayPoly()
{
    if(head.coeff==0)
    {
        cout<<0<<endl;
        return;
    }
    node *t=head.link;
    cout<<t->coeff<<"x^"<<t->exp;
    t=t->link;
    for(int i=1;i<head.coeff;i++,t=t->link)
    {
        if(t->coeff>=0)
            cout<<"+";
        cout<<t->coeff<<"x^"<<t->exp;
    }
    cout<<endl;
}
double polynomial::EvalPoly(double x)
{
    double result=0.0;

```

```

    node *t=head.link;
    for(int i=0;i<head.coeff;i++,t=t->link)
        result+=(t->coeff)*pow(x,t->exp);
    return result;
}
polynomial* polynomial::AddPoly(const polynomial &p)
{
    int i=0;
    polynomial *t=new polynomial;
    node *a=head.link;
    node *b=p.head.link;
    node *c;
    t->head.coeff=0;
    t->head.exp=0;
    t->head.link=NULL;
    while(a!=NULL&&b!=NULL)
    {
        if(a->exp<b->exp)
        {
            if(t->head.coeff==0)
            {
                t->head.link=createNewNode(a->coeff,a->exp,t->head.link);
                c=t->head.link;
            }
            else
            {
                c->link=createNewNode(a->coeff,a->exp,c->link);
                c=c->link;
            }
            (t->head.coeff)++;
            a=a->link;
        }
        else if(a->exp>b->exp)
        {
            if(t->head.coeff==0)
            {
                t->head.link=createNewNode(b->coeff,b->exp,t->head.link);
                c=t->head.link;
            }
            else
            {
                c->link=createNewNode(b->coeff,b->exp,c->link);
                c=c->link;
            }
            (t->head.coeff)++;
            b=b->link;
        }
        else
        {
            if(t->head.coeff==0)
            {
                t->head.link=createNewNode(a->coeff+b->coeff,a->exp,t-
>head.link);
                c=t->head.link;
            }
            else
            {

```

```

        c->link=createNewNode(a->coeff+b->coeff,a->exp,c->link);
        c=c->link;
    }
    (t->head.coeff)++;
    a=a->link;
    b=b->link;
}
}
while(a!=NULL)
{
    if(t->head.coeff==0)
    {
        t->head.link=createNewNode(a->coeff,a->exp,t->head.link);
        c=t->head.link;
    }
    else
    {
        c->link=createNewNode(a->coeff,a->exp,c->link);
        c=c->link;
    }
    (t->head.coeff)++;
    a=a->link;
}
while(b!=NULL)
{
    if(t->head.coeff==0)
    {
        t->head.link=createNewNode(b->coeff,b->exp,t->head.link);
        c=t->head.link;
    }
    else
    {
        c->link=createNewNode(b->coeff,b->exp,c->link);
        c=c->link;
    }
    (t->head.coeff)++;
    b=b->link;
}
return t;
}
int main()
{
    polynomial p;
    p.InsertTerm(-4,3);
    p.InsertTerm(2,2);
    p.InsertTerm(6,0);
    p.InsertTerm(-7,1);
    p.DisplayPoly();
    polynomial q=p;
    p.DeleteTerm(6,0);
    p.DisplayPoly();
    q.DisplayPoly();
    cout<<q.EvalPoly(-2.5)<<endl;
    polynomial a,b;
    a.InsertTerm(5,0);
    a.InsertTerm(-1,1);
    a.InsertTerm(1,2);

```

```

    a.InsertTerm(4,3);
    cout<<"a = ";
    a.DisplayPoly();
    b.InsertTerm(2,1);
    b.InsertTerm(6,2);
    b.InsertTerm(-10,0);
    cout<<"b = ";
    b.DisplayPoly();
    polynomial *t=b.AddPoly(a);
    cout<<"a+b = ";
    t->DisplayPoly();
    delete t;
    return 0;
}

```

### **Output:**

Polynomial constructed

$6x^0-7x^1+2x^2-4x^3$

$-7x^1+2x^2-4x^3$

$6x^0-7x^1+2x^2-4x^3$

98.5

Polynomial constructed

Polynomial constructed

$a = 5x^0-1x^1+1x^2+4x^3$

$b = -10x^0+2x^1+6x^2$

Polynomial constructed

$a+b = -5x^0+1x^1+7x^2+4x^3$

Polynomial destroyed

Polynomial destroyed

Polynomial destroyed

Polynomial destroyed

Polynomial destroyed