



# localhost

---

Report generated by Tenable Nessus™

Sat, 02 Aug 2025 13:34:09 IST

---

---

## TABLE OF CONTENTS

---

### Vulnerabilities by Host

• 192.168.43.170.....	4
-----------------------	---

Nessus Essentials

---

## Vulnerabilities by Host

---

---

**192.168.43.170**



#### Scan Information

---

Start time: Sat Aug 2 13:25:29 2025  
End time: Sat Aug 2 13:34:02 2025

#### Host Information

---

Netbios Name: DESKTOP-3RRTG48  
IP: 192.168.43.170  
MAC Address: 00:0C:29:06:E0:C5  
OS: Microsoft Windows 10 Education

#### Vulnerabilities

**57608 - SMB Signing not required**

#### Synopsis

---

Signing is not required on the remote SMB server.

#### Description

---

Signing is not required on the remote SMB server. An unauthenticated, remote attacker can exploit this to conduct man-in-the-middle attacks against the SMB server.

#### See Also

---

<http://www.nessus.org/u?df39b8b3>  
<http://technet.microsoft.com/en-us/library/cc731957.aspx>  
<http://www.nessus.org/u?74b80723>  
<https://www.samba.org/samba/docs/current/man-html/smb.conf.5.html>  
<http://www.nessus.org/u?a3cac4ea>

#### Solution

---

Enforce message signing in the host's configuration. On Windows, this is found in the policy setting 'Microsoft network server: Digitally sign communications (always)'. On Samba, the setting is called 'server signing'. See the 'see also' links for further details.

#### Risk Factor

---

Medium

#### CVSS v3.0 Base Score

---

5.3 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:N/I:L/A:N)

#### CVSS v3.0 Temporal Score

---

4.6 (CVSS:3.0/E:U/RL:O/RC:C)

#### CVSS v2.0 Base Score

---

5.0 (CVSS2#AV:N/AC:L/Au:N/C:N/I:P/A:N)

#### CVSS v2.0 Temporal Score

---

3.7 (CVSS2#E:U/RL:OF/RC:C)

#### Plugin Information

---

Published: 2012/01/19, Modified: 2022/10/05

#### Plugin Output

---

tcp/445/cifs

## 10114 - ICMP Timestamp Request Remote Date Disclosure

### Synopsis

It is possible to determine the exact time set on the remote host.

### Description

The remote host answers to an ICMP timestamp request. This allows an attacker to know the date that is set on the targeted machine, which may assist an unauthenticated, remote attacker in defeating time-based authentication protocols.

Timestamps returned from machines running Windows Vista / 7 / 2008 / 2008 R2 are deliberately incorrect, but usually within 1000 seconds of the actual system time.

### Solution

Filter out the ICMP timestamp requests (13), and the outgoing ICMP timestamp replies (14).

### Risk Factor

Low

### CVSS v2.0 Base Score

2.1 (CVSS2#AV:L/AC:L/Au:N/C:P/I:N/A:N)

### References

CVE	CVE-1999-0524
XREF	CWE:200

### Plugin Information

Published: 1999/08/01, Modified: 2024/10/07

### Plugin Output

icmp/0

```
The ICMP timestamps seem to be in little endian format (not in network format)
The remote clock is synchronized with the local clock.
```

## 45590 - Common Platform Enumeration (CPE)

### Synopsis

It was possible to enumerate CPE names that matched on the remote system.

### Description

By using information obtained from a Nessus scan, this plugin reports CPE (Common Platform Enumeration) matches for various hardware and software products found on a host.

Note that if an official CPE is not available for the product, this plugin computes the best possible CPE based on the information available from the scan.

### See Also

<http://cpe.mitre.org/>

<https://nvd.nist.gov/products/cpe>

### Solution

n/a

### Risk Factor

None

### Plugin Information

Published: 2010/04/21, Modified: 2025/07/14

### Plugin Output

tcp/0

```
The remote operating system matched the following CPE :
```

```
cpe:/o:microsoft:windows_10 -> Microsoft Windows 10
```

## 10736 - DCE Services Enumeration

### Synopsis

A DCE/RPC service is running on the remote host.

### Description

By sending a Lookup request to the portmapper (TCP 135 or epmapper PIPE) it was possible to enumerate the Distributed Computing Environment (DCE) services running on the remote port. Using this information it is possible to connect and bind to each service by sending an RPC request to the remote port/pipe.

### Solution

n/a

### Risk Factor

None

### Plugin Information

Published: 2001/08/26, Modified: 2021/10/04

### Plugin Output

tcp/135/epmap

The following DCERPC services are available locally :

Object UUID : 00000000-0000-0000-0000-000000000000  
UUID : 51a227ae-825b-41f2-b4a9-1ac9557a1018, version 1.0  
Description : Unknown RPC service  
Annotation : Ngc Pop Key Service  
Type : Local RPC service  
Named pipe : samss lpc

Object UUID : 00000000-0000-0000-0000-000000000000  
UUID : 51a227ae-825b-41f2-b4a9-1ac9557a1018, version 1.0  
Description : Unknown RPC service  
Annotation : Ngc Pop Key Service  
Type : Local RPC service  
Named pipe : SidKey Local End Point

Object UUID : 00000000-0000-0000-0000-000000000000  
UUID : 51a227ae-825b-41f2-b4a9-1ac9557a1018, version 1.0  
Description : Unknown RPC service  
Annotation : Ngc Pop Key Service  
Type : Local RPC service  
Named pipe : protected\_storage

Object UUID : 00000000-0000-0000-0000-000000000000  
UUID : 51a227ae-825b-41f2-b4a9-1ac9557a1018, version 1.0  
Description : Unknown RPC service  
Annotation : Ngc Pop Key Service  
Type : Local RPC service



```
Named pipe : lsasspirpc

Object UUID : 00000000-0000-0000-0000-000000000000
UUID : 51a227ae-825b-41f2-b4a9-1ac9557a1018, version 1.0
Description : Unknown RPC service
Annotation : Ngc Pop Key Service
Type : Local RPC service
Named pipe : lsapolicylookup

Object UUID : 00000000-0000-0000-0000-000000000000
UUID : 51a227ae-825b-41f2-b4a9-1ac9557a1018, version 1.0
Description : Unknown RPC service
Annotation : Ngc Pop Key Service
Type : Local RPC service
Named pipe : LSA_EAS_ENDPOINT

Object UUID : 00000000-0000-0000-0000-000000000000
UUID : 51a227ae-825b-41f2-b4a9-1ac9557a1018, version 1.0
Description : Unknown RPC service
Annotation : Ngc Pop Key Service
Type : Local RPC service
Named pipe : LSA_IDPEXT_ENDPOINT

Object UUID : 00000000-0000-0000-0000-000000000000
UUID : 51a227ae-825b-41f2-b4a9-1ac9557a1018, version 1.0
Description : Unknown RPC service
Annotation : Ngc Pop Key Service
Type : Local RPC service
Named pipe : lsacap

Object UUID : 00000000-0000-0000-0000-000000000000
UUID : 51a227ae-825b-41f2-b4a9-1ac9557a1018, version 1.0
Description : Unknown RPC service
Annotation : Ngc [...]
```

## 10736 - DCE Services Enumeration

### Synopsis

A DCE/RPC service is running on the remote host.

### Description

By sending a Lookup request to the portmapper (TCP 135 or epmapper PIPE) it was possible to enumerate the Distributed Computing Environment (DCE) services running on the remote port. Using this information it is possible to connect and bind to each service by sending an RPC request to the remote port/pipe.

### Solution

n/a

### Risk Factor

None

### Plugin Information

Published: 2001/08/26, Modified: 2021/10/04

### Plugin Output

tcp/445/cifs

```
The following DCERPC services are available remotely :

Object UUID : 00000000-0000-0000-0000-000000000000
UUID : 650a7e26-eab8-5533-ce43-9c1dfce11511, version 1.0
Description : Unknown RPC service
Annotation : Vpn APIs
Type : Remote RPC service
Named pipe : \PIPE\ROUTER
Netbios name : \\DESKTOP-3RRTG48

Object UUID : 00000000-0000-0000-0000-000000000000
UUID : 7f1343fe-50a9-4927-a778-0c5859517bac, version 1.0
Description : Unknown RPC service
Annotation : DfsDs service
Type : Remote RPC service
Named pipe : \PIPE\wkssvc
Netbios name : \\DESKTOP-3RRTG48

Object UUID : 00000000-0000-0000-0000-000000000000
UUID : f6beaff7-1e19-4fbb-9f8f-b89e2018337c, version 1.0
Description : Unknown RPC service
Annotation : Event log TCPIP
Type : Remote RPC service
Named pipe : \pipe\eventlog
Netbios name : \\DESKTOP-3RRTG48

Object UUID : 00000000-0000-0000-0000-000000000000
UUID : 3c4728c5-f0ab-448b-bda1-6ce01eb0a6d6, version 1.0
```

Description : Unknown RPC service  
Annotation : DHCPv6 Client LRPC Endpoint  
Type : Remote RPC service  
Named pipe : \pipe\eventlog  
Netbios name : \\DESKTOP-3RRTG48

Object UUID : 00000000-0000-0000-0000-000000000000  
UUID : 3c4728c5-f0ab-448b-bda1-6ce01eb0a6d5, version 1.0  
Description : DHCP Client Service  
Windows process : svchost.exe  
Annotation : DHCP Client LRPC Endpoint  
Type : Remote RPC service  
Named pipe : \pipe\eventlog  
Netbios name : \\DESKTOP-3RRTG48

Object UUID : 00000000-0000-0000-0000-000000000000  
UUID : 3473dd4d-2e88-4006-9cba-22570909dd10, version 5.0  
Description : Unknown RPC service  
Annotation : WinHttp Auto-Proxy Service  
Type : Remote RPC service  
Named pipe : \pipe\eventlog  
Netbios name : \\DESKTOP-3RRTG48

Object UUID : 00000000-0000-0000-0000-000000000000  
UUID : b58aa02e-2884-4e97-8176-4ee06d794184, version 1.0  
Description : Unknown RPC service  
Type : Remote RPC service  
Named pipe : \pipe\trkwks  
Netbios name : \\DESKTOP-3RRTG48

Object UUID : 00000000-0000-0000-0000-000000000000  
UUID : 0767a036-0d22-48aa-ba69-b619480f38cb, version 1.0  
Description : Unknown RPC service  
Annotation : PcaSv [...]

## 10736 - DCE Services Enumeration

### Synopsis

A DCE/RPC service is running on the remote host.

### Description

By sending a Lookup request to the portmapper (TCP 135 or epmapper PIPE) it was possible to enumerate the Distributed Computing Environment (DCE) services running on the remote port. Using this information it is possible to connect and bind to each service by sending an RPC request to the remote port/pipe.

### Solution

n/a

### Risk Factor

None

### Plugin Information

Published: 2001/08/26, Modified: 2021/10/04

### Plugin Output

tcp/49664/dce-rpc

The following DCERPC services are available on TCP port 49664 :

Object UUID : 00000000-0000-0000-0000-000000000000  
UUID : 51a227ae-825b-41f2-b4a9-1ac9557a1018, version 1.0  
Description : Unknown RPC service  
Annotation : Ngc Pop Key Service  
Type : Remote RPC service  
TCP Port : 49664  
IP : 192.168.43.170

Object UUID : 00000000-0000-0000-0000-000000000000  
UUID : 12345778-1234-abcd-ef00-0123456789ac, version 1.0  
Description : Security Account Manager  
Windows process : lsass.exe  
Type : Remote RPC service  
TCP Port : 49664  
IP : 192.168.43.170

Object UUID : 00000000-0000-0000-0000-000000000000  
UUID : b25a52bf-e5dd-4f4a-aea6-8ca7272a0e86, version 2.0  
Description : Unknown RPC service  
Annotation : KeyIso  
Type : Remote RPC service  
TCP Port : 49664  
IP : 192.168.43.170

Object UUID : 00000000-0000-0000-0000-000000000000  
UUID : 8fb74744-b2ff-4c00-be0d-9ef9a191felb, version 1.0

Description : Unknown RPC service  
Annotation : Ngc Pop Key Service  
Type : Remote RPC service  
TCP Port : 49664  
IP : 192.168.43.170

## 10736 - DCE Services Enumeration

### Synopsis

A DCE/RPC service is running on the remote host.

### Description

By sending a Lookup request to the portmapper (TCP 135 or epmapper PIPE) it was possible to enumerate the Distributed Computing Environment (DCE) services running on the remote port. Using this information it is possible to connect and bind to each service by sending an RPC request to the remote port/pipe.

### Solution

n/a

### Risk Factor

None

### Plugin Information

Published: 2001/08/26, Modified: 2021/10/04

### Plugin Output

tcp/49665/dce-rpc

The following DCERPC services are available on TCP port 49665 :

Object UUID : 765294ba-60bc-48b8-92e9-89fd77769d91  
UUID : d95afe70-a6d5-4259-822e-2c84da1ddb0d, version 1.0  
Description : Unknown RPC service  
Type : Remote RPC service  
TCP Port : 49665  
IP : 192.168.43.170

## 10736 - DCE Services Enumeration

### Synopsis

A DCE/RPC service is running on the remote host.

### Description

By sending a Lookup request to the portmapper (TCP 135 or epmapper PIPE) it was possible to enumerate the Distributed Computing Environment (DCE) services running on the remote port. Using this information it is possible to connect and bind to each service by sending an RPC request to the remote port/pipe.

### Solution

n/a

### Risk Factor

None

### Plugin Information

Published: 2001/08/26, Modified: 2021/10/04

### Plugin Output

tcp/49666/dce-rpc

The following DCERPC services are available on TCP port 49666 :

Object UUID : 00000000-0000-0000-0000-000000000000  
UUID : f6beaff7-1e19-4fbb-9f8f-b89e2018337c, version 1.0  
Description : Unknown RPC service  
Annotation : Event log TCPIP  
Type : Remote RPC service  
TCP Port : 49666  
IP : 192.168.43.170

Object UUID : 00000000-0000-0000-0000-000000000000  
UUID : 3c4728c5-f0ab-448b-bda1-6ce01eb0a6d6, version 1.0  
Description : Unknown RPC service  
Annotation : DHCPv6 Client LRPC Endpoint  
Type : Remote RPC service  
TCP Port : 49666  
IP : 192.168.43.170

Object UUID : 00000000-0000-0000-0000-000000000000  
UUID : 3c4728c5-f0ab-448b-bda1-6ce01eb0a6d5, version 1.0  
Description : DHCP Client Service  
Windows process : svchost.exe  
Annotation : DHCP Client LRPC Endpoint  
Type : Remote RPC service  
TCP Port : 49666  
IP : 192.168.43.170

Object UUID : 00000000-0000-0000-0000-000000000000

UUID : 3473dd4d-2e88-4006-9cba-22570909dd10, version 5.0  
Description : Unknown RPC service  
Annotation : WinHttp Auto-Proxy Service  
Type : Remote RPC service  
TCP Port : 49666  
IP : 192.168.43.170



## 10736 - DCE Services Enumeration

### Synopsis

A DCE/RPC service is running on the remote host.

### Description

By sending a Lookup request to the portmapper (TCP 135 or epmapper PIPE) it was possible to enumerate the Distributed Computing Environment (DCE) services running on the remote port. Using this information it is possible to connect and bind to each service by sending an RPC request to the remote port/pipe.

### Solution

n/a

### Risk Factor

None

### Plugin Information

Published: 2001/08/26, Modified: 2021/10/04

### Plugin Output

tcp/49667/dce-rpc

The following DCERPC services are available on TCP port 49667 :

Object UUID : 00000000-0000-0000-0000-000000000000  
UUID : 86d35949-83c9-4044-b424-db363231fd0c, version 1.0  
Description : Unknown RPC service  
Type : Remote RPC service  
TCP Port : 49667  
IP : 192.168.43.170

Object UUID : 00000000-0000-0000-0000-000000000000  
UUID : 3a9ef155-691d-4449-8d05-09ad57031823, version 1.0  
Description : Unknown RPC service  
Type : Remote RPC service  
TCP Port : 49667  
IP : 192.168.43.170

Object UUID : 736e6573-0000-0000-0000-000000000000  
UUID : c9ac6db5-82b7-4e55-ae8a-e464ed7b4277, version 1.0  
Description : Unknown RPC service  
Annotation : Impl friendly name  
Type : Remote RPC service  
TCP Port : 49667  
IP : 192.168.43.170

Object UUID : 00000000-0000-0000-0000-000000000000  
UUID : 98716d03-89ac-44c7-bb8c-285824e51c4a, version 1.0  
Description : Unknown RPC service  
Annotation : XactSrv service

Type : Remote RPC service  
TCP Port : 49667  
IP : 192.168.43.170

Object UUID : 00000000-0000-0000-0000-000000000000  
UUID : 1a0d010f-1c33-432c-b0f5-8cf4e8053099, version 1.0  
Description : Unknown RPC service  
Annotation : IdSegSrv service  
Type : Remote RPC service  
TCP Port : 49667  
IP : 192.168.43.170

Object UUID : 00000000-0000-0000-0000-000000000000  
UUID : 552d076a-cb29-4e44-8b6a-d15e59e2c0af, version 1.0  
Description : Unknown RPC service  
Annotation : IP Transition Configuration endpoint  
Type : Remote RPC service  
TCP Port : 49667  
IP : 192.168.43.170

Object UUID : 00000000-0000-0000-0000-000000000000  
UUID : 2e6035b2-e8f1-41a7-a044-656b439c4c34, version 1.0  
Description : Unknown RPC service  
Annotation : Proxy Manager provider server endpoint  
Type : Remote RPC service  
TCP Port : 49667  
IP : 192.168.43.170

Object UUID : 00000000-0000-0000-0000-000000000000  
UUID : c36be077-e14b-4fe9-8abc-e856ef4f048b, version 1.0  
Description : Unknown RPC service  
Annotation : Proxy Manager client server endpoint  
Type : Remote RPC service  
TCP Port : 49667  
IP : 192.168.43.170

Object UUID : 00000000-0000-0000-0000-000000000000  
UUID : a398e520-d59a-4bdd-aa7a-3c1e0303a5 [...]

## 10736 - DCE Services Enumeration

### Synopsis

A DCE/RPC service is running on the remote host.

### Description

By sending a Lookup request to the portmapper (TCP 135 or epmapper PIPE) it was possible to enumerate the Distributed Computing Environment (DCE) services running on the remote port. Using this information it is possible to connect and bind to each service by sending an RPC request to the remote port/pipe.

### Solution

n/a

### Risk Factor

None

### Plugin Information

Published: 2001/08/26, Modified: 2021/10/04

### Plugin Output

tcp/49668/dce-rpc

The following DCERPC services are available on TCP port 49668 :

Object UUID : 00000000-0000-0000-0000-000000000000  
UUID : 12345678-1234-abcd-ef00-0123456789ab, version 1.0  
Description : IPsec Services (Windows XP & 2003)  
Windows process : lsass.exe  
Type : Remote RPC service  
TCP Port : 49668  
IP : 192.168.43.170

Object UUID : 00000000-0000-0000-0000-000000000000  
UUID : 0b6edbfa-4a24-4fc6-8a23-942b1eca65d1, version 1.0  
Description : Unknown RPC service  
Type : Remote RPC service  
TCP Port : 49668  
IP : 192.168.43.170

Object UUID : 00000000-0000-0000-0000-000000000000  
UUID : ae33069b-a2a8-46ee-a235-ddfd339be281, version 1.0  
Description : Unknown RPC service  
Type : Remote RPC service  
TCP Port : 49668  
IP : 192.168.43.170

Object UUID : 00000000-0000-0000-0000-000000000000  
UUID : 4a452661-8290-4b36-8fbe-7f4093a94978, version 1.0  
Description : Unknown RPC service  
Type : Remote RPC service

TCP Port : 49668  
IP : 192.168.43.170

Object UUID : 00000000-0000-0000-0000-000000000000  
UUID : 76f03f96-cdfd-44fc-a22c-64950a001209, version 1.0  
Description : Unknown RPC service  
Type : Remote RPC service  
TCP Port : 49668  
IP : 192.168.43.170

## 10736 - DCE Services Enumeration

### Synopsis

A DCE/RPC service is running on the remote host.

### Description

By sending a Lookup request to the portmapper (TCP 135 or epmapper PIPE) it was possible to enumerate the Distributed Computing Environment (DCE) services running on the remote port. Using this information it is possible to connect and bind to each service by sending an RPC request to the remote port/pipe.

### Solution

n/a

### Risk Factor

None

### Plugin Information

Published: 2001/08/26, Modified: 2021/10/04

### Plugin Output

tcp/49670/dce-rpc

The following DCERPC services are available on TCP port 49670 :

Object UUID : 00000000-0000-0000-0000-000000000000  
UUID : 367abb81-9844-35f1-ad32-98f038001003, version 2.0  
Description : Service Control Manager  
Windows process : svchost.exe  
Type : Remote RPC service  
TCP Port : 49670  
IP : 192.168.43.170

## 10736 - DCE Services Enumeration

### Synopsis

A DCE/RPC service is running on the remote host.

### Description

By sending a Lookup request to the portmapper (TCP 135 or epmapper PIPE) it was possible to enumerate the Distributed Computing Environment (DCE) services running on the remote port. Using this information it is possible to connect and bind to each service by sending an RPC request to the remote port/pipe.

### Solution

n/a

### Risk Factor

None

### Plugin Information

Published: 2001/08/26, Modified: 2021/10/04

### Plugin Output

tcp/49671/dce-rpc

The following DCERPC services are available on TCP port 49671 :

```
Object UUID : 00000000-0000-0000-0000-000000000000
UUID : 6b5bdd1e-528c-422c-af8c-a4079be4fe48, version 1.0
Description : Unknown RPC service
Annotation : Remote Fw APIs
Type : Remote RPC service
TCP Port : 49671
IP : 192.168.43.170
```

## 54615 - Device Type

### Synopsis

It is possible to guess the remote device type.

### Description

Based on the remote operating system, it is possible to determine what the remote system type is (eg: a printer, router, general-purpose computer, etc).

### Solution

n/a

### Risk Factor

None

### Plugin Information

Published: 2011/05/23, Modified: 2025/03/12

### Plugin Output

tcp/0

```
Remote device type : general-purpose  
Confidence level : 99
```

## 35716 - Ethernet Card Manufacturer Detection

### Synopsis

The manufacturer can be identified from the Ethernet OUI.

### Description

Each ethernet MAC address starts with a 24-bit Organizationally Unique Identifier (OUI). These OUIs are registered by IEEE.

### See Also

<https://standards.ieee.org/faqs/regauth.html>

<http://www.nessus.org/u?794673b4>

### Solution

n/a

### Risk Factor

None

### Plugin Information

Published: 2009/02/19, Modified: 2020/05/13

### Plugin Output

tcp/0

```
The following card manufacturers were identified :
```

```
00:0C:29:06:E0:C5 : VMware, Inc.
```



## 86420 - Ethernet MAC Addresses

### Synopsis

This plugin gathers MAC addresses from various sources and consolidates them into a list.

### Description

This plugin gathers MAC addresses discovered from both remote probing of the host (e.g. SNMP and Netbios) and from running local checks (e.g. ifconfig). It then consolidates the MAC addresses into a single, unique, and uniform list.

### Solution

n/a

### Risk Factor

None

### Plugin Information

Published: 2015/10/16, Modified: 2025/06/10

### Plugin Output

tcp/0

```
The following is a consolidated list of detected MAC addresses:  
- 00:0C:29:06:E0:C5
```

## 12053 - Host Fully Qualified Domain Name (FQDN) Resolution

### Synopsis

It was possible to resolve the name of the remote host.

### Description

Nessus was able to resolve the fully qualified domain name (FQDN) of the remote host.

### Solution

n/a

### Risk Factor

None

### Plugin Information

Published: 2004/02/11, Modified: 2025/03/13

### Plugin Output

tcp/0

```
192.168.43.170 resolves as DESKTOP-3RRTG48.
```

## 53513 - Link-Local Multicast Name Resolution (LLMNR) Detection

### Synopsis

The remote device supports LLMNR.

### Description

The remote device answered to a Link-local Multicast Name Resolution (LLMNR) request. This protocol provides a name lookup service similar to NetBIOS or DNS. It is enabled by default on modern Windows versions.

### See Also

<http://www.nessus.org/u?51eae65d>

<http://technet.microsoft.com/en-us/library/bb878128.aspx>

### Solution

Make sure that use of this software conforms to your organization's acceptable use and security policies.

### Risk Factor

None

### Plugin Information

Published: 2011/04/21, Modified: 2023/10/17

### Plugin Output

udp/5355/llmnr

```
According to LLMNR, the name of the remote host is 'DESKTOP-3RRTG48'.
```

### Synopsis

---

It was possible to obtain information about the remote operating system.

### Description

---

Nessus was able to obtain the remote operating system name and version (Windows and/or Samba) by sending an authentication request to port 139 or 445. Note that this plugin requires SMB to be enabled on the host.

### Solution

---

n/a

### Risk Factor

---

None

### Plugin Information

---

Published: 2001/10/17, Modified: 2021/09/20

### Plugin Output

---

tcp/445/cifs

```
The remote Operating System is : Windows 10 Education 19045
The remote native LAN manager is : Windows 10 Education 6.3
The remote SMB Domain Name is : DESKTOP-3RRTG48
```

## 26917 - Microsoft Windows SMB Registry : Nessus Cannot Access the Windows Registry

### Synopsis

Nessus is not able to access the remote Windows Registry.

### Description

It was not possible to connect to PIPE\winreg on the remote host.

If you intend to use Nessus to perform registry-based checks, the registry checks will not work because the 'Remote Registry Access'

service (winreg) has been disabled on the remote host or can not be connected to with the supplied credentials.

### Solution

n/a

### Risk Factor

None

### References

XREF IAVB:0001-B-0506

### Plugin Information

Published: 2007/10/04, Modified: 2020/09/22

### Plugin Output

tcp/445/cifs

```
Could not connect to the registry because:  
Could not connect to IPC$
```

## 11011 - Microsoft Windows SMB Service Detection

### Synopsis

A file / print sharing service is listening on the remote host.

### Description

The remote service understands the CIFS (Common Internet File System) or Server Message Block (SMB) protocol, used to provide shared access to files, printers, etc between nodes on a network.

### Solution

n/a

### Risk Factor

None

### Plugin Information

Published: 2002/06/05, Modified: 2021/02/11

### Plugin Output

tcp/139/smb

```
An SMB server is running on this port.
```

## 11011 - Microsoft Windows SMB Service Detection

### Synopsis

A file / print sharing service is listening on the remote host.

### Description

The remote service understands the CIFS (Common Internet File System) or Server Message Block (SMB) protocol, used to provide shared access to files, printers, etc between nodes on a network.

### Solution

n/a

### Risk Factor

None

### Plugin Information

Published: 2002/06/05, Modified: 2021/02/11

### Plugin Output

tcp/445/cifs

```
A CIFS server is running on this port.
```

## 100871 - Microsoft Windows SMB Versions Supported (remote check)

### Synopsis

It was possible to obtain information about the version of SMB running on the remote host.

### Description

Nessus was able to obtain the version of SMB running on the remote host by sending an authentication request to port 139 or 445.

Note that this plugin is a remote check and does not work on agents.

### Solution

n/a

### Risk Factor

None

### Plugin Information

Published: 2017/06/19, Modified: 2019/11/22

### Plugin Output

tcp/445/cifs

```
The remote host supports the following versions of SMB :  
  SMBv1  
  SMBv2
```



## 106716 - Microsoft Windows SMB2 and SMB3 Dialects Supported (remote check)

### Synopsis

It was possible to obtain information about the dialects of SMB2 and SMB3 available on the remote host.

### Description

Nessus was able to obtain the set of SMB2 and SMB3 dialects running on the remote host by sending an authentication request to port 139 or 445.

### Solution

n/a

### Risk Factor

None

### Plugin Information

Published: 2018/02/09, Modified: 2020/03/11

### Plugin Output

tcp/445/cifs

```
The remote host supports the following SMB dialects :
_version_  _introduced in windows version_
2.0.2      Windows 2008
2.1        Windows 7
3.0        Windows 8
3.0.2      Windows 8.1
3.1.1      Windows 10

The remote host does NOT support the following SMB dialects :
_version_  _introduced in windows version_
2.2.2      Windows 8 Beta
2.2.4      Windows 8 Beta
3.1        Windows 10
```

### Synopsis

---

It is possible to determine which TCP ports are open.

### Description

---

This plugin is a SYN 'half-open' port scanner. It shall be reasonably quick even against a firewalled target.

Note that SYN scans are less intrusive than TCP (full connect) scans against broken services, but they might cause problems for less robust firewalls and also leave unclosed connections on the remote target, if the network is loaded.

### Solution

---

Protect your target with an IP filter.

### Risk Factor

---

None

### Plugin Information

---

Published: 2009/02/04, Modified: 2025/07/14

### Plugin Output

---

tcp/135/epmap

```
Port 135/tcp was found to be open
```

### Synopsis

---

It is possible to determine which TCP ports are open.

### Description

---

This plugin is a SYN 'half-open' port scanner. It shall be reasonably quick even against a firewalled target.

Note that SYN scans are less intrusive than TCP (full connect) scans against broken services, but they might cause problems for less robust firewalls and also leave unclosed connections on the remote target, if the network is loaded.

### Solution

---

Protect your target with an IP filter.

### Risk Factor

---

None

### Plugin Information

---

Published: 2009/02/04, Modified: 2025/07/14

### Plugin Output

---

tcp/139/smb

```
Port 139/tcp was found to be open
```

### Synopsis

---

It is possible to determine which TCP ports are open.

### Description

---

This plugin is a SYN 'half-open' port scanner. It shall be reasonably quick even against a firewalled target.

Note that SYN scans are less intrusive than TCP (full connect) scans against broken services, but they might cause problems for less robust firewalls and also leave unclosed connections on the remote target, if the network is loaded.

### Solution

---

Protect your target with an IP filter.

### Risk Factor

---

None

### Plugin Information

---

Published: 2009/02/04, Modified: 2025/07/14

### Plugin Output

---

tcp/445/cifs

```
Port 445/tcp was found to be open
```

## 19506 - Nessus Scan Information

### Synopsis

This plugin displays information about the Nessus scan.

### Description

This plugin displays, for each tested host, information about the scan itself :

- The version of the plugin set.
- The type of scanner (Nessus or Nessus Home).
- The version of the Nessus Engine.
- The port scanner(s) used.
- The port range scanned.
- The ping round trip time
- Whether credentialed or third-party patch management checks are possible.
- Whether the display of superseded patches is enabled
- The date of the scan.
- The duration of the scan.
- The number of hosts scanned in parallel.
- The number of checks done in parallel.

### Solution

n/a

### Risk Factor

None

### Plugin Information

Published: 2005/08/26, Modified: 2025/06/25

### Plugin Output

tcp/0

Information about this scan :

```
Nessus version : 10.9.1
Nessus build : 20006
Plugin feed version : 202508020137
Scanner edition used : Nessus Home
Scanner OS : LINUX
Scanner distribution : ubuntu1604-x86-64
Scan type : Normal
Scan name : localhost
```

```
Scan policy used : Advanced Scan
Scanner IP : 192.168.43.138
Port scanner(s) : nessus_syn_scanner
Port range : default
Ping RTT : 161.919 ms
Thorough tests : no
Experimental tests : no
Scan for Unpatched Vulnerabilities : no
Plugin debugging enabled : no
Paranoia level : 1
Report verbosity : 1
Safe checks : yes
Optimize the test : yes
Credentialed checks : no
Patch management checks : None
Display superseded patches : yes (supersedence plugin did not launch)
CGI scanning : disabled
Web application tests : disabled
Max hosts : 100
Max checks : 5
Recv timeout : 5
Backports : None
Allow post-scan editing : Yes
Nessus Plugin Signature Checking : Enabled
Audit File Signature Checking : Disabled
Scan Start Date : 2025/8/2 13:25 IST (UTC +05:30)
Scan duration : 508 sec
Scan for malware : no
```

## 209654 - OS Fingerprints Detected

### Synopsis

Multiple OS fingerprints were detected.

### Description

Using a combination of remote probes (TCP/IP, SMB, HTTP, NTP, SNMP, etc), it was possible to gather one or more fingerprints from the remote system. While the highest-confidence result was reported in plugin 11936, "OS Identification", the complete set of fingerprints detected are reported here.

### Solution

n/a

### Risk Factor

None

### Plugin Information

Published: 2025/02/26, Modified: 2025/03/03

### Plugin Output

tcp/0

Following OS Fingerprints were found

Remote operating system : Microsoft Windows 10 Pro  
Confidence level : 56  
Method : MLSinFP  
Type : unknown  
Fingerprint : unknown

Remote operating system : Windows 10 Home  
Windows 10 Pro  
Windows 10 Pro Education  
Windows 10 Enterprise  
Windows 10 Enterprise LTSC  
Windows 10 Education  
Windows 10 IoT Core  
Windows 10 IoT Enterprise  
Windows 10 S  
Confidence level : 70  
Method : Misc  
Type : general-purpose  
Fingerprint : unknown

Remote operating system : Microsoft Windows Server 2019  
Confidence level : 70  
Method : SinFP  
Type : general-purpose  
Fingerprint : SinFP:  
P1:B11113:F0x12:W8192:00204ffff:M1460:

P2:B11113:F0x12:W8192:O0204ffff0103030801010402:M1460:  
P3:B00000:F0x00:W0:O0:M0  
P4:191301\_7\_p=139

Remote operating system : Windows 10.0  
Confidence level : 70  
Method : smb  
Type : general-purpose  
Fingerprint : unknown

Remote operating system : Microsoft Windows 10 Education  
Confidence level : 99  
Method : MSRPC  
Type : general-purpose  
Fingerprint : unknown



## 11936 - OS Identification

### Synopsis

It is possible to guess the remote operating system.

### Description

Using a combination of remote probes (e.g., TCP/IP, SMB, HTTP, NTP, SNMP, etc.), it is possible to guess the name of the remote operating system in use. It is also possible sometimes to guess the version of the operating system.

### Solution

n/a

### Risk Factor

None

### Plugin Information

Published: 2003/12/09, Modified: 2025/06/03

### Plugin Output

tcp/0

```
Remote operating system : Microsoft Windows 10 Education
Confidence level : 99
Method : MSRPC
```

```
The remote host is running Microsoft Windows 10 Education
```

## 117886 - OS Security Patch Assessment Not Available

### Synopsis

OS Security Patch Assessment is not available.

### Description

OS Security Patch Assessment is not available on the remote host.

This does not necessarily indicate a problem with the scan.

Credentials may not have been provided, OS security patch assessment may not be supported for the target, the target may not have been identified, or another issue may have occurred that prevented OS security patch assessment from being available. See plugin output for details.

This plugin reports non-failure information impacting the availability of OS Security Patch Assessment. Failure information is reported by plugin 21745 : 'OS Security Patch Assessment failed'. If a target host is not supported for OS Security Patch Assessment, plugin 110695 : 'OS Security Patch Assessment Checks Not Supported' will report concurrently with this plugin.

### Solution

n/a

### Risk Factor

None

### References

XREF IAVB:0001-B-0515

### Plugin Information

Published: 2018/10/02, Modified: 2021/07/12

### Plugin Output

tcp/0

The following issues were reported :

```
- Plugin      : no_local_checks_credentials.nasl
  Message     :
Credentials were not provided for detected SMB service.
```

## 96982 - Server Message Block (SMB) Protocol Version 1 Enabled (uncredentialed check)

### Synopsis

The remote Windows host supports the SMBv1 protocol.

### Description

The remote Windows host supports Server Message Block Protocol version 1 (SMBv1). Microsoft recommends that users discontinue the use of SMBv1 due to the lack of security features that were included in later SMB versions. Additionally, the Shadow Brokers group reportedly has an exploit that affects SMB; however, it is unknown if the exploit affects SMBv1 or another version. In response to this, US-CERT recommends that users disable SMBv1 per SMB best practices to mitigate these potential issues.

### See Also

<https://blogs.technet.microsoft.com/filecab/2016/09/16/stop-using-smb1/>

<https://support.microsoft.com/en-us/help/2696547/how-to-detect-enable-and-disable-smbv1-smbv2-and-smbv3-in-windows-and>

<http://www.nessus.org/u?8dcab5e4>

<http://www.nessus.org/u?234f8ef8>

<http://www.nessus.org/u?4c7e0cf3>

### Solution

Disable SMBv1 according to the vendor instructions in Microsoft KB2696547. Additionally, block SMB directly by blocking TCP port 445 on all network boundary devices. For SMB over the NetBIOS API, block TCP ports 137 / 139 and UDP ports 137 / 138 on all network boundary devices.

### Risk Factor

None

### References

XREF IAVT:0001-T-0710

### Plugin Information

Published: 2017/02/03, Modified: 2020/09/22

### Plugin Output

tcp/445/cifs

```
The remote host supports SMBv1.
```



## 110723 - Target Credential Status by Authentication Protocol - No Credentials Provided

### Synopsis

Nessus was able to find common ports used for local checks, however, no credentials were provided in the scan policy.

### Description

Nessus was not able to successfully authenticate directly to the remote target on an available authentication protocol. Nessus was able to connect to the remote port and identify that the service running on the port supports an authentication protocol, but Nessus failed to authenticate to the remote service using the provided credentials. There may have been a protocol failure that prevented authentication from being attempted or all of the provided credentials for the authentication protocol may be invalid. See plugin output for error details.

Please note the following :

- This plugin reports per protocol, so it is possible for valid credentials to be provided for one protocol and not another. For example, authentication may succeed via SSH but fail via SMB, while no credentials were provided for an available SNMP service.
- Providing valid credentials for all available authentication protocols may improve scan coverage, but the value of successful authentication for a given protocol may vary from target to target depending upon what data (if any) is gathered from the target via that protocol. For example, successful authentication via SSH is more valuable for Linux targets than for Windows targets, and likewise successful authentication via SMB is more valuable for Windows targets than for Linux targets.

### Solution

n/a

### Risk Factor

None

### References

XREF IAVB:0001-B-0504

### Plugin Information

Published: 2018/06/27, Modified: 2024/04/19

### Plugin Output

tcp/0

```
SMB was detected on port 445 but no credentials were provided.  
SMB local checks were not enabled.
```



## 10287 - Traceroute Information

### Synopsis

It was possible to obtain traceroute information.

### Description

Makes a traceroute to the remote host.

### Solution

n/a

### Risk Factor

None

### Plugin Information

Published: 1999/11/27, Modified: 2023/12/04

### Plugin Output

udp/0

```
For your information, here is the traceroute from 192.168.43.138 to 192.168.43.170 :  
192.168.43.138  
192.168.43.170
```

```
Hop Count: 1
```

## 20094 - VMware Virtual Machine Detection

### Synopsis

The remote host is a VMware virtual machine.

### Description

According to the MAC address of its network adapter, the remote host is a VMware virtual machine.

### Solution

Since it is physically accessible through the network, ensure that its configuration matches your organization's security policy.

### Risk Factor

None

### Plugin Information

Published: 2005/10/27, Modified: 2019/12/11

### Plugin Output

tcp/0

```
The remote host is a VMware virtual machine.
```



## 135860 - WMI Not Available

### Synopsis

WMI queries could not be made against the remote host.

### Description

WMI (Windows Management Instrumentation) is not available on the remote host over DCOM. WMI queries are used to gather information about the remote host, such as its current state, network interface configuration, etc.

Without this information Nessus may not be able to identify installed software or security vulnerabilities that exist on the remote host.

### See Also

<https://docs.microsoft.com/en-us/windows/win32/wmisdk/wmi-start-page>

### Solution

n/a

### Risk Factor

None

### Plugin Information

Published: 2020/04/21, Modified: 2025/07/21

### Plugin Output

tcp/445/cifs

```
Can't connect to the 'root\CIMV2' WMI namespace.
```

### Synopsis

It was possible to obtain the network name of the remote host.

### Description

The remote host is listening on UDP port 137 or TCP port 445, and replies to NetBIOS nbtscan or SMB requests.

Note that this plugin gathers information to be used in other plugins, but does not itself generate a report.

### Solution

n/a

### Risk Factor

None

### Plugin Information

Published: 1999/10/12, Modified: 2021/02/10

### Plugin Output

udp/137/netbios-ns

```
The following 6 NetBIOS names have been gathered :
```

```
DESKTOP-3RRTG48  = File Server Service
DESKTOP-3RRTG48  = Computer name
WORKGROUP        = Workgroup / Domain name
WORKGROUP        = Browser Service Elections
WORKGROUP        = Master Browser
__MSBROWSE__     = Master Browser
```

```
The remote host has the following MAC address on its adapter :
```

```
00:0c:29:06:e0:c5
```