Arista Access Switch Mumbai-MH-48 Alarm Handling SOP

Node: Arista-Access-Mumbai-MH-48 | **Vendor:** Arista | **Severity:** Critical | **Alarm Code:** ALARM_2064

Description

This SOP outlines the procedures to handle the critical alarm ALARM_2064 on the Arista Access Switch Mumbai-MH-48. The alarm is triggered due to a high CPU utilization.

Potential Root Causes

Cause	Probability
High CPU utilization due to high traffic volume	High
Misconfigured QoS policy	Medium
Software bug	Low

Diagnostic Commands

```
show system resources
show system processes
show qos policy map
show interface stats
```

Resolution Steps

Step 1: {'Step': 'Check CPU utilization and identify the process causing high utilization', 'Action': 'Run "show system resources" command to view CPU utilization and identify the top processes using system resources.'}

Step 2: {'Step': 'Adjust QoS policy to prioritize critical traffic', 'Action': 'Run "Configure Terminal editing mode" and adjust the QoS policy to prioritize critical traffic using the "class-map" and "policy-map" commands.'}

Step 3: {'Step': 'Restart the switch or specific processes', 'Action': 'Run "reload in " or "process restart " command to restart the switch or specific processes causing high CPU utilization.'}

Post-Check Verification

```
show system resources
show system processes
show qos policy map
```

```
show interface stats
```