

Standard Operating Procedure for Resolving Critical Alarm ALARM_5263 on Cisco-Access-Bangalore-KA-72

Node: Cisco-Access-Bangalore-KA-72 | **Vendor:** Cisco | **Severity:** Critical | **Alarm Code:** ALARM_5263

Description

This SOP outlines the steps to diagnose and resolve the Critical Alarm ALARM_5263 on the Cisco Access Switch, Bangalore KA-72.

Potential Root Causes

Cause	Probability
Power Supply Failure	High
CPU Overload	Medium
Memory Leak	Low

Diagnostic Commands

```
show environment power
show system resources
show memory
show cpu usage
```

Resolution Steps

- Step 1: {'Step': '1. Check Power Supply Status', 'Action': "Verify the power supply status using the 'show environment power' command. If the power supply is faulty, replace it with a new one."}
- Step 2: {'Step': '2. Check CPU Overload', 'Action': "Verify the CPU usage using the 'show cpu usage' command. If the CPU usage is high, restart the switch or consider upgrading the CPU."}
- Step 3: {'Step': '3. Check Memory Leak', 'Action': "Verify the memory usage using the 'show memory' command. If the memory usage is high, restart the switch or consider upgrading the memory."}
- Step 4: {'Step': '4. Clear Alarm', 'Action': "Clear the alarm using the 'clear alarm' command."}

Post-Check Verification

```
show alarm history
show environment power
```

```
show system resources
```

```
show memory
```

```
show cpu usage
```