

Standard Operating Procedure (SOP) for Cisco Access Switch - Alarm Code ALARM_8561

Node: Cisco-Access-Chennai-TN-100 | **Vendor:** Cisco | **Severity:** Major | **Alarm Code:** ALARM_8561

Description

This SOP outlines the steps to diagnose, resolve and verify the fix for the ALARM_8561 on the Cisco Access Switch, Node ID: Cisco-Access-Chennai-TN-100.

Potential Root Causes

Cause	Probability
High CPU utilization due to software bugs or misconfiguration	High
Physical interface issues (e.g., fiber optic cable damage)	Medium
Configuration errors or inconsistencies	Low

Diagnostic Commands

```
show processes cpu | include Sys
show interfaces | exclude up
show run | include spanning-tree
show ip interface brief | exclude up
```

Resolution Steps

Step 1: {'Step': '1. Check CPU utilization and identify the process causing high CPU usage', 'Action': "Use the command 'show processes cpu | include Sys' to identify the process causing high CPU utilization. Refer to Cisco documentation for possible software bugs or misconfiguration.", 'CLI_Commands': 'show processes cpu | include Sys'}

Step 2: {'Step': '2. Check physical interface status and troubleshoot any issues', 'Action': "Use the command 'show interfaces | exclude up' to identify any physical interface issues. Troubleshoot the issue by checking the fiber optic cable, SFP transceivers, and switch configurations.", 'CLI_Commands': 'show interfaces | exclude up'}

Step 3: {'Step': '3. Verify configuration and correct any errors or inconsistencies', 'Action': "Use the command 'show run | include spanning-tree' to verify the spanning tree configuration. Correct any errors or inconsistencies in the configuration.", 'CLI_Commands': 'show run | include spanning-tree'}

Step 4: {'Step': '4. Verify IP interface status and troubleshoot any issues', 'Action': "Use the command 'show ip interface brief | exclude up' to verify the IP interface status. Troubleshoot any issues by checking the IP address, subnet mask, and default gateway.", 'CLI_Commands': 'show ip interface brief | exclude up'}

Post-Check Verification

```
show processes cpu | include Sys
show interfaces | exclude up
show ip interface brief | exclude up
show spanning-tree summary
```