

SOP: Resolving Alarm ALARM_2101 on Cisco-Access-Delhi-NCR-18 Access Switch

Node: Cisco-Access-Delhi-NCR-18 | **Vendor:** Cisco | **Severity:** Major | **Alarm Code:** ALARM_2101

Description

ALARM_2101: Major Alarm on Cisco-Access-Delhi-NCR-18 Due to Link Down (GigabitEthernet0/0/1)

Potential Root Causes

Cause	Probability
Physical Link Down	High
Cable or Connector Fault	Medium
Network Congestion or Loop Detected	Low

Diagnostic Commands

```
show interface GigabitEthernet0/0/1 | include up | down
show controllers GigabitEthernet0/0/1
show spanning-tree vlan 1 detail
show ip traffic
```

Resolution Steps

- Step 1: {'Step': '1. Verify Physical Connection', 'Action': 'Check the physical connection between the access switch and the adjacent device', 'CLI_Command': 'show interface GigabitEthernet0/0/1 | include up | down'}
- Step 2: {'Step': '2. Replace Faulty Cable or Connector', 'Action': 'Replace the faulty cable or connector if detected', 'CLI_Command': 'no shutdown'}
- Step 3: {'Step': '3. Check for Network Congestion or Loop', 'Action': 'Verify the network topology and check for any congestion or loop issues', 'CLI_Command': 'show spanning-tree vlan 1 detail'}
- Step 4: {'Step': '4. Reset the Interface', 'Action': 'Reset the interface using the CLI command 'interface GigabitEthernet0/0/1' followed by 'no shutdown'', 'CLI_Command': 'interface GigabitEthernet0/0/1\nno shutdown'}

Post-Check Verification

```
show interface GigabitEthernet0/0/1 | include up | down
show ip traffic
```

```
show controllers GigabitEthernet0/0/1
```