

Cisco Access Switch - Alarm 2752 SOP

Node: Cisco-Access-Delhi-NCR-20 | **Vendor:** Cisco | **Severity:** Major | **Alarm Code:** ALARM_2752

Description

This SOP outlines the steps to diagnose and resolve a Major alarm on Cisco Access Switch Node ID: Cisco-Access-Delhi-NCR-20, triggered by Alarm Code: ALARM_2752.

Potential Root Causes

Cause	Probability
High CPU Utilization due to software bugs or configuration issues	High
Insufficient Memory or disk space on the switch	Medium
Hardware failure or malfunction of critical components	Low

Diagnostic Commands

```
show system resources
show processes cpu
show memory
show disk space
show tech-support
```

Resolution Steps

Step 1: {'Step': '1. Check CPU Utilization and processes', 'Description': "Use the command 'show processes cpu' to identify resource-intensive processes and consider restarting them or adjusting the software configuration.", 'CLI_Command': 'show processes cpu'}

Step 2: {'Step': '2. Verify Memory and disk space', 'Description': "Use the commands 'show memory' and 'show disk space' to check for any issues related to insufficient resources.", 'CLI_Command': 'show memory; show disk space'}

Step 3: {'Step': '3. Check Hardware logs and run diagnostics', 'Description': "Run the command 'show tech-support' to gather detailed hardware logs and diagnose any potential hardware issues.", 'CLI_Command': 'show tech-support'}

Step 4: {'Step': '4. Reset the switch (if necessary)', 'Description': "In extreme cases, reset the switch using the command 'reload' to start with a clean slate, followed by the initial configuration and software installation.", 'CLI_Command': 'reload'}

Post-Check Verification

```
show system resources
```

```
show processes cpu
```

```
show memory
```

```
show disk space
```