

SOP: Resolving Critical Alarm ALARM_3427 on Cisco Access Switch Node ID: Cisco-Access-Kolkata-WB-112

Node: Cisco-Access-Kolkata-WB-112 | **Vendor:** Cisco | **Severity:** Critical | **Alarm Code:** ALARM_3427

Description

The ALARM_3427 alarm on Cisco Access Switch Node ID: Cisco-Access-Kolkata-WB-112 indicates a critical issue with the switch's performance. This SOP outlines the steps to diagnose and resolve the alarm.

Potential Root Causes

Cause	Probability
Switch CPU usage exceeding 80%	High
Memory leak or fragmentation	Medium
Interface or port issues	Low

Diagnostic Commands

```
show processes cpu | exclude System
show memory | include Fragment
show interface status | include down
```

Resolution Steps

- Step 1: {'Step': '1. Check CPU usage', 'Action': "Run the command 'show processes cpu | exclude System'. If CPU usage is above 80%, proceed to step 2."}
- Step 2: {'Step': '2. Check for memory fragmentation', 'Action': "Run the command 'show memory | include Fragment'. If memory is fragmented, run the command 'clear memory' to clear the fragmentation."}
- Step 3: {'Step': '3. Check for interface or port issues', 'Action': "Run the command 'show interface status | include down'. If any interfaces are down, check the physical connections and restart the interfaces if necessary."}
- Step 4: {'Step': '4. Clear the alarm', 'Action': "Run the command 'no snmp-server enable traps coldStart' to clear the alarm."}

Post-Check Verification

```
show processes cpu | exclude System
show memory | include Fragment
show interface status | include down
```