

SOP for Resolving ALARM_4232 on Cisco-Access-Mumbai-MH-52

Node: Cisco-Access-Mumbai-MH-52 | **Vendor:** Cisco | **Severity:** Major | **Alarm Code:** ALARM_4232

Description

ALARM_4232 is a Major alarm indicating a critical issue on the Cisco-Access-Mumbai-MH-52 Access Switch. This SOP outlines the steps to diagnose and resolve the issue.

Potential Root Causes

Cause	Probability
Excessive CPU utilization due to high traffic volume	High
Misconfigured Quality of Service (QoS) policy	Medium
Faulty switch hardware or software	Low

Diagnostic Commands

```
show system resources | include CPU
show interface | include errors
show mac address-table | include learn
show qos policy-map
show logging | include errors
```

Resolution Steps

Step 1: {'Step': '1. Check CPU utilization and traffic volume', 'Action': "Run the command 'show system resources | include CPU' to monitor CPU utilization and identify potential causes of high traffic volume. Take corrective action to manage traffic volume, such as implementing Quality of Service (QoS) policies or upgrading switch hardware."}

Step 2: {'Step': '2. Verify QoS policy configuration', 'Action': "Run the command 'show qos policy-map ' to verify the QoS policy configuration. Adjust the policy settings as needed to ensure proper traffic prioritization and policing."}

Step 3: {'Step': '3. Check for hardware or software issues', 'Action': "Run the command 'show logging | include errors' to identify any hardware or software errors. Replace faulty hardware or update software to the latest version to resolve the issue."}

Step 4: {'Step': '4. Clear the alarm', 'Action': "Run the command 'clear alarm ' to clear the ALARM_4232 alarm."}

Post-Check Verification

```
show system resources | include CPU
show interface | include errors
show mac address-table | include learn
show qos policy-map
show logging | include errors
```