

# SOP for Resolving Major Alarm ALARM\_2200 on Cisco-PE-Delhi-NCR-16

**Node:** Cisco-PE-Delhi-NCR-16 | **Vendor:** Cisco | **Severity:** Major | **Alarm Code:** ALARM\_2200

## Description

This SOP outlines the steps to diagnose and resolve Major Alarm ALARM\_2200 on Cisco-PE-Delhi-NCR-16, a Provider Edge Router running Cisco IOS.

## Potential Root Causes

| Cause                   | Probability |
|-------------------------|-------------|
| Interface Flapping      | High        |
| Routing Protocol Issues | Medium      |
| Hardware Failure        | Low         |

## Diagnostic Commands

```
show int status
show ip bgp summary
show ip ospf neighbor
show tech-support
```

## Resolution Steps

- Step 1: {'Step': 'Verify interface status', 'Action': "Run 'show int status' command to check for any interface flapping."}
- Step 2: {'Step': 'Verify routing protocol configuration', 'Action': "Run 'show ip bgp summary' command to check for any routing protocol issues."}
- Step 3: {'Step': 'Verify hardware health', 'Action': "Run 'show tech-support' command to check for any hardware failure."}
- Step 4: {'Step': 'Clear BGP sessions', 'Action': "Run 'clear ip bgp \*' command to clear BGP sessions."}
- Step 5: {'Step': 'Re-establish routing protocols', 'Action': "Run 'no shut' command on interfaces and 'clear ip ospf process' command to re-establish routing protocols."}

## Post-Check Verification

```
show bgp summary
show ip ospf neighbor
```

```
show int status
```