

# Cisco PE Router Delhi NCR-33 Alarm Handling Procedure for ALARM\_3215

**Node:** Cisco-PE-Delhi-NCR-33 | **Vendor:** Cisco | **Severity:** Critical | **Alarm Code:** ALARM\_3215

## Description

This SOP outlines the steps to diagnose and resolve a critical alarm on Cisco PE Router Delhi NCR-33, identified by ALARM\_3215.

## Potential Root Causes

| Cause                | Probability |
|----------------------|-------------|
| High CPU Utilization | High        |
| Memory Leak          | Medium      |
| Interface Flapping   | Low         |

## Diagnostic Commands

```
show processes cpu sort | exclude kld
show memory | include free
show interfaces | include flaps
```

## Resolution Steps

Step 1: {'Step': '1. Check CPU Utilization', 'Action': 'Run the command `show processes cpu sort | exclude kld` to identify the process consuming high CPU resources. If the issue persists, consider rebooting the router. If not resolved, proceed to step 2.', 'Commands': ['reload']}

Step 2: {'Step': '2. Check Memory Leak', 'Action': 'Run the command `show memory | include free` to verify the free memory. If memory leak is identified, run the command `process cpu-list` to identify the memory-intensive process. Terminate the process if necessary. If not resolved, proceed to step 3.', 'Commands': ['kill process ', 'clear process cpu-list']}

Step 3: {'Step': '3. Check Interface Flapping', 'Action': 'Run the command `show interfaces | include flaps` to identify the flapping interface. Run the command `show interfaces` to verify the interface configuration. If the interface is not configured correctly, make the necessary changes. If not resolved, escalate to a senior engineer.', 'Commands': ['shutdown ', 'no shutdown']}

## Post-Check Verification

```
show processes cpu sort | exclude kld
show memory | include free
```

```
show interfaces | include flaps
```